

## Widget Styling

In this lecture we will learn about the various ways to **style widgets**!

```
In [18]: %%html
<style>
.example-container { background: #999999; padding: 2px; min-height: 100px; }
.example-container.sm { min-height: 50px; }
.example-box { background: #9999FF; width: 50px; height: 50px; text-align: center }
.example-box.med { width: 65px; height: 65px; }
.example-box.lrg { width: 80px; height: 80px; }
</style>
```

```
In [19]: import ipywidgets as widgets
from IPython.display import display
```

## Basic styling

The widgets distributed with IPython can be styled by setting the following traits:

- width
- height
- background\_color
- border\_color
- border\_width
- border\_style
- font\_style
- font\_weight
- font\_size
- font\_family

The example below shows how a Button widget can be styled:

```
In [21]: button = widgets.Button(
    description='Hello World!',
    width=100, # Integers are interpreted as pixel measurements.
    height='2em', # em is valid HTML unit of measurement.
    color='lime', # Colors can be set by name,
    background_color='#0022FF', # and also by color code.
    border_color='cyan')
display(button)
```

## Parent/child relationships

To display widget A inside widget B, widget A must be a child of widget B. Widgets that can contain other widgets have a `children` attribute. This attribute can be set via a keyword argument in the widget's constructor or after construction. Calling `display` on an object with children automatically displays the children.

```
In [23]: from IPython.display import display

float_range = widgets.FloatSlider()
string = widgets.Text(value='hi')
container = widgets.Box(children=[float_range, string])

container.border_color = 'red'
container.border_style = 'dotted'
container.border_width = 3
display(container) # Displays the `container` and all of it's children.
```

## After the parent is displayed

Children can be added to parents after the parent has been displayed. The parent is responsible for rendering its children.

```
In [24]: container = widgets.Box()
container.border_color = 'red'
container.border_style = 'dotted'
container.border_width = 3
display(container)

int_range = widgets.IntSlider()
container.children=[int_range]
```

## Fancy boxes

If you need to display a more complicated set of widgets, there are specialized containers that you can use. To display multiple sets of widgets, you can use an `Accordion` or a `Tab` in combination with one `Box` per set of widgets (as seen below). The "pages" of these widgets are their children. To set the titles of the pages, use `set_title`.

## Accordion

```
In [25]: name1 = widgets.Text(description='Location:')
zip1 = widgets.BoundedIntText(description='Zip:', min=0, max=99999)
page1 = widgets.Box(children=[name1, zip1])

name2 = widgets.Text(description='Location:')
zip2 = widgets.BoundedIntText(description='Zip:', min=0, max=99999)
page2 = widgets.Box(children=[name2, zip2])

accord = widgets.Accordion(children=[page1, page2], width=400)
display(accord)

accord.set_title(0, 'From')
accord.set_title(1, 'To')
```

## TabWidget

```
In [7]: name = widgets.Text(description='Name:', padding=4)
color = widgets.Dropdown(description='Color:', padding=4, options=['red', 'orange'])
page1 = widgets.Box(children=[name, color], padding=4)

age = widgets.IntSlider(description='Age:', padding=4, min=0, max=120, value=50)
gender = widgets.RadioButtons(description='Gender:', padding=4, options=['male', 'female'])
page2 = widgets.Box(children=[age, gender], padding=4)

tabs = widgets.Tab(children=[page1, page2])
display(tabs)

tabs.set_title(0, 'Name')
tabs.set_title(1, 'Details')
```

## Alignment

Most widgets have a description attribute, which allows a label for the widget to be defined. The label of the widget has a fixed minimum width. The text of the label is always right aligned and the widget is left aligned:

```
In [8]: display(widgets.Text(description="a:"))
display(widgets.Text(description="aa:"))
display(widgets.Text(description="aaa:"))
```

If a label is longer than the minimum width, the widget is shifted to the right:

```
In [9]: display(widgets.Text(description="a:"))
display(widgets.Text(description="aa:"))
display(widgets.Text(description="aaa:"))
display(widgets.Text(description="aaaaaaaaaaaaaaaaaaaaa:"))
```

If a description is not set for the widget, the label is not displayed:

```
In [10]: display(widgets.Text(description="a:"))
display(widgets.Text(description="aa:"))
display(widgets.Text(description="aaa:"))
display(widgets.Text())
```

## Flex boxes

Widgets can be aligned using the FlexBox, HBox, and VBox widgets.

## Application to widgets

Widgets display vertically by default:

```
In [11]: buttons = [widgets.Button(description=str(i)) for i in range(3)]
display(*buttons)
```

## Using hbox

To make widgets display horizontally, they can be children of an HBox widget.

```
In [12]: container = widgets.HBox(children=buttons)
display(container)
```

## Visibility

The visible property of widgets can be used to hide or show widgets that have already been displayed (as seen below). The visible property can be:

- True - the widget is displayed
- False - the widget is hidden, and the empty space where the widget would be is collapsed
- None - the widget is hidden, and the empty space where the widget would be is shown

```
In [13]: w1 = widgets.Latex(value="First line")
w2 = widgets.Latex(value="Second line")
w3 = widgets.Latex(value="Third line")
display(w1, w2, w3)
```

```
In [14]: w2.visible=None
```

```
In [15]: w2.visible=False
```

```
In [16]: w2.visible=True
```

## Another example

In the example below, a form is rendered, which conditionally displays widgets depending on the state of other widgets. Try toggling the student check-box.

```
In [17]: form = widgets.VBox()
first = widgets.Text(description="First:")
last = widgets.Text(description="Last:")

student = widgets.Checkbox(description="Student:", value=False)
school_info = widgets.VBox(visible=False, children=[
    widgets.Text(description="School:"),
    widgets.IntText(description="Grade:", min=0, max=12)
])

pet = widgets.Text(description="Pet:")
form.children = [first, last, student, school_info, pet]
display(form)

def on_student_toggle(name, value):
    if value:
        school_info.visible = True
    else:
        school_info.visible = False
student.on_trait_change(on_student_toggle, 'value')
```

## Conclusion

You should now have an understanding of how to style widgets!