

Remote Data Access

Functions from `pandas_datareader.data` and `pandas_datareader.wb` extract data from various Internet sources into a pandas DataFrame. Currently the following sources are supported:

- [Yahoo! Finance](#)
- [Google Finance](#)
- [Enigma](#)
- [St.Louis FED \(FRED\)](#)
- [Kenneth French's data library](#)
- [World Bank](#)
- [OECD](#)
- [Eurostat](#)
- [Thrift Savings Plan](#)
- Oanda currency historical rate
- Nasdaq Trader symbol definitions<code>remote_data.nasdaq_symbols

It should be noted, that various sources support different kinds of data, so not all sources implement the same methods and the data elements returned might also differ.

Yahoo! Finance

Historical stock prices from Yahoo! Finance.

```

In [1]: import pandas_datareader.data as web

In [2]: import datetime

In [3]: start = datetime.datetime(2010, 1, 1)

In [4]: end = datetime.datetime(2013, 1, 27)

In [5]: f = web.DataReader("F", 'yahoo', start, end)

RemoteDataErrorTraceback (most recent call last)
<ipython-input-5-679b50ab962b> in <module>()
----> 1 f = web.DataReader("F", 'yahoo', start, end)

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/data.pyc in DataReader(name, data_source, start, end, retry_count,
pause, session, access_key)
    115             adjust_price=False, chunksize=25,
    116             retry_count=retry_count, pause=pause,
--> 117             session=session).read()
    118
    119     elif data_source == "yahoo-actions":

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/yahoo/daily.pyc in read(self)
    75     def read(self):
    76         """ read one data from specified URL """
--> 77         df = super(YahooDailyReader, self).read()
    78         if self.ret_index:
    79             df['Ret_Index'] = _calc_return_index(df['Adj Close'])

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in read(self)
    155         if isinstance(self.symbols, (compat.string_types, int)):
    156             df = self._read_one_data(self.url,
--> 157                                     params=self._get_params(self.symbols))
    158         # Or multiple symbols, (e.g., ['GOOG', 'AAPL', 'MSFT'])
    159         elif isinstance(self.symbols, DataFrame):

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _read_one_data(self, url, params)
    72         """ read one data from specified URL """
    73         if self._format == 'string':
--> 74             out = self._read_url_as_StringIO(url, params=params)
    75         elif self._format == 'json':
    76             out = self._get_response(url, params=params).json()

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _read_url_as_StringIO(self, url, params)
    83         Open url (and retry)
    84         """
--> 85         response = self._get_response(url, params=params)
    86         text = self._sanitize_response(response)
    87         out = StringIO()

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _get_response(self, url, params)
    118         if params is not None and len(params) > 0:
    119             url = url + "?" + urlencode(params)
--> 120         raise RemoteDataError('Unable to read URL: {0}'.format(url))
    121
    122     def _read_lines(self, out):

RemoteDataError: Unable to read URL: http://ichart.finance.yahoo.com/table.csv?
a=0&ignore=.csv&s=F&b=1&e=27&d=0&g=d&f=2013&c=2010

```

```
In [6]: f.ix['2010-01-04']
```

```
NameErrorTraceback (most recent call last)  
<ipython-input-6-a881e6f45410> in <module>()  
----> 1 f.ix['2010-01-04']
```

```
NameError: name 'f' is not defined
```

Historical corporate actions (Dividends and Stock Splits) with ex-dates from Yahoo! Finance.

```

In [7]: import pandas_datareader.data as web

In [8]: import datetime

In [9]: start = datetime.datetime(2010, 1, 1)

In [10]: end = datetime.datetime(2015, 5, 9)

In [11]: web.DataReader('AAPL', 'yahoo-actions', start, end)

RemoteDataErrorTraceback (most recent call last)
<ipython-input-11-d102632855e1> in <module>()
----> 1 web.DataReader('AAPL', 'yahoo-actions', start, end)

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/data.pyc in DataReader(name, data_source, start, end, retry_count,
pause, session, access_key)
    120         return YahooActionReader(symbols=name, start=start, end=end,
    121                                     retry_count=retry_count, pause=pause,
--> 122                                     session=session).read()
    123     elif data_source == "yahoo-dividends":
    124         return YahooDailyReader(symbols=name, start=start, end=end,

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in read(self)
    155         if isinstance(self.symbols, (compat.string_types, int)):
    156             df = self._read_one_data(self.url,
--> 157                                     params=self._get_params(self.symbols))
    158         # Or multiple symbols, (e.g., ['GOOG', 'AAPL', 'MSFT'])
    159         elif isinstance(self.symbols, DataFrame):

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _read_one_data(self, url, params)
    72         """ read one data from specified URL """
    73         if self._format == 'string':
--> 74             out = self._read_url_as_StringIO(url, params=params)
    75         elif self._format == 'json':
    76             out = self._get_response(url, params=params).json()

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _read_url_as_StringIO(self, url, params)
    83         Open url (and retry)
    84         """
--> 85         response = self._get_response(url, params=params)
    86         text = self._sanitize_response(response)
    87         out = StringIO()

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _get_response(self, url, params)
    118         if params is not None and len(params) > 0:
    119             url = url + "?" + urlencode(params)
--> 120         raise RemoteDataError('Unable to read URL: {0}'.format(url))
    121
    122     def _read_lines(self, out):

RemoteDataError: Unable to read URL: http://ichart.finance.yahoo.com/x?
a=0&s=AAPL&b=1&e=9&d=4&g=v&f=2015&c=2010

```

Historical dividends from Yahoo! Finance.

```

In [12]: import pandas_datareader.data as web

In [13]: import datetime

In [14]: start = datetime.datetime(2010, 1, 1)

In [15]: end = datetime.datetime(2013, 1, 27)

In [16]: f = web.DataReader("F", 'yahoo-dividends', start, end)

RemoteDataErrorTraceback (most recent call last)
<ipython-input-16-42b2f1e0124d> in <module>()
----> 1 f = web.DataReader("F", 'yahoo-dividends', start, end)

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/data.pyc in DataReader(name, data_source, start, end, retry_count,
pause, session, access_key)
    125         adjust_price=False, chunksize=25,
    126         retry_count=retry_count, pause=pause,
--> 127         session=session, interval='v').read()
    128
    129     elif data_source == "google":

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/yahoo/daily.pyc in read(self)
    75     def read(self):
    76         """ read one data from specified URL """
--> 77         df = super(YahooDailyReader, self).read()
    78         if self.ret_index:
    79             df['Ret_Index'] = _calc_return_index(df['Adj Close'])

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in read(self)
    155         if isinstance(self.symbols, (compat.string_types, int)):
    156             df = self._read_one_data(self.url,
--> 157                                     params=self._get_params(self.symbols))
    158         # Or multiple symbols, (e.g., ['GOOG', 'AAPL', 'MSFT'])
    159         elif isinstance(self.symbols, DataFrame):

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _read_one_data(self, url, params)
    72         """ read one data from specified URL """
    73         if self._format == 'string':
--> 74             out = self._read_url_as_StringIO(url, params=params)
    75         elif self._format == 'json':
    76             out = self._get_response(url, params=params).json()

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _read_url_as_StringIO(self, url, params)
    83         Open url (and retry)
    84         """
--> 85         response = self._get_response(url, params=params)
    86         text = self._sanitize_response(response)
    87         out = StringIO()

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/base.pyc in _get_response(self, url, params)
    118         if params is not None and len(params) > 0:
    119             url = url + "?" + urlencode(params)
--> 120         raise RemoteDataError('Unable to read URL: {0}'.format(url))
    121
    122     def _read_lines(self, out):

RemoteDataError: Unable to read URL: http://ichart.finance.yahoo.com/table.csv?
a=0&ignore=.csv&s=F&b=1&e=27&d=0&g=v&f=2013&c=2010

```

```
In [17]: f

NameErrorTraceback (most recent call last)
<ipython-input-17-9a8ad92c50ca> in <module>()
----> 1 f

NameError: name 'f' is not defined
```

Yahoo! Finance Quotes

Experimental

The YahooQuotesReader class allows to get quotes data from Yahoo! Finance.

```
In [18]: import pandas_datareader.data as web

In [19]: amzn = web.get_quote_yahoo('AMZN')

In [20]: amzn
Out[20]:
```

	PE	change_pct	last	short_ratio	time
AMZN	181.93	+0.85%	966.07	2.09	4:00pm

Yahoo! Finance Options

Experimental

The Options class allows the download of options data from Yahoo! Finance.

The `get_all_data` method downloads and caches option data for all expiry months and provides a formatted `DataFrame` with a hierarchical index, so its easy to get to the specific option you want.

```

In [21]: from pandas_datareader.data import Options

In [22]: aapl = Options('aapl', 'yahoo')

In [23]: data = aapl.get_all_data()

In [24]: data.iloc[0:5, 0:5]
Out[24]:

```

Strike	Expiry	Type	Symbol	Last	Bid	Ask	Chg \
2.5	2017-05-19	call	AAPL170519C00002500	153.15	151.95	154.40	8.449997
		put	AAPL170519P00002500	0.02	0.00	0.02	0.000000
	2017-06-16	put	AAPL170616P00002500	0.01	0.00	0.01	-0.010000
	2017-08-18	call	AAPL170818C00002500	153.30	153.15	154.10	0.000000
	2018-01-19	call	AAPL180119C00002500	153.13	151.60	154.55	0.000000

Strike	Expiry	Type	Symbol	PctChg
2.5	2017-05-19	call	AAPL170519C00002500	5.839666
		put	AAPL170519P00002500	0.000000
	2017-06-16	put	AAPL170616P00002500	-50.000000
	2017-08-18	call	AAPL170818C00002500	0.000000
	2018-01-19	call	AAPL180119C00002500	0.000000


```

#Show the $100 strike puts at all expiry dates:
In [25]: data.loc[(100, slice(None), 'put'),:].iloc[0:5, 0:5]
Out[25]:

```

Strike	Expiry	Type	Symbol	Last	Bid	Ask	Chg	PctChg
100	2017-05-19	put	AAPL170519P00100000	0.01	0.00	0.02	-0.01	-50
	2017-05-26	put	AAPL170526P00100000	0.04	0.01	0.05	0.00	0
	2017-06-16	put	AAPL170616P00100000	0.01	0.00	0.01	0.00	0
	2017-06-30	put	AAPL170630P00100000	0.01	0.00	0.03	0.00	0
	2017-07-21	put	AAPL170721P00100000	0.01	0.00	0.01	-0.01	-50


```

#Show the volume traded of $100 strike puts at all expiry dates:
In [26]: data.loc[(100, slice(None), 'put'), 'Vol'].head()
Out[26]:

```

Strike	Expiry	Type	Symbol	Vol
100	2017-05-19	put	AAPL170519P00100000	25
	2017-05-26	put	AAPL170526P00100000	2
	2017-06-16	put	AAPL170616P00100000	52
	2017-06-30	put	AAPL170630P00100000	10
	2017-07-21	put	AAPL170721P00100000	15

```

Name: Vol, dtype: float64

```

If you don't want to download all the data, more specific requests can be made.

```

In [27]: import datetime

In [28]: expiry = datetime.date(2016, 1, 1)

In [29]: data = aapl.get_call_data(expiry=expiry)

In [30]: data.iloc[0:5:, 0:5]
Out[30]:

```

Strike	Expiry	Type	Symbol	Last	Bid	Ask	Chg \
2.5	2017-05-19	call	AAPL170519C00002500	153.15	151.95	154.40	8.449997
5.0	2017-05-19	call	AAPL170519C00005000	150.65	149.45	151.65	0.000000
7.5	2017-05-19	call	AAPL170519C00007500	148.05	146.95	149.30	0.000000
10.0	2017-05-19	call	AAPL170519C00010000	143.53	145.65	146.60	0.000000
20.0	2017-05-19	call	AAPL170519C00020000	133.52	135.65	136.60	0.000000

Strike	Expiry	Type	Symbol	PctChg
2.5	2017-05-19	call	AAPL170519C00002500	5.839666
5.0	2017-05-19	call	AAPL170519C00005000	0.000000
7.5	2017-05-19	call	AAPL170519C00007500	0.000000
10.0	2017-05-19	call	AAPL170519C00010000	0.000000
20.0	2017-05-19	call	AAPL170519C00020000	0.000000

Note that if you call `get_all_data` first, this second call will happen much faster, as the data is cached.

If a given expiry date is not available, data for the next available expiry will be returned (January 15, 2015 in the above example).

Available expiry dates can be accessed from the `expiry_dates` property.


```
In [31]: aapl.expiry_dates
Out[31]:
[datetime.date(2017, 5, 19),
 datetime.date(2017, 5, 26),
 datetime.date(2017, 6, 2),
 datetime.date(2017, 6, 9),
 datetime.date(2017, 6, 16),
 datetime.date(2017, 6, 23),
 datetime.date(2017, 6, 30),
 datetime.date(2017, 7, 21),
 datetime.date(2017, 8, 18),
 datetime.date(2017, 9, 15),
 datetime.date(2017, 10, 20),
 datetime.date(2017, 11, 17),
 datetime.date(2017, 12, 15),
 datetime.date(2018, 1, 19),
 datetime.date(2018, 2, 16),
 datetime.date(2018, 6, 15),
 datetime.date(2019, 1, 18)]

In [32]: data = aapl.get_call_data(expiry=aapl.expiry_dates[0])

In [33]: data.iloc[0:5:, 0:5]
Out[33]:
```

Strike	Expiry	Type	Symbol	Last	Bid	Ask	Chg \
2.5	2017-05-19	call	AAPL170519C00002500	153.15	151.95	154.40	8.449997
5.0	2017-05-19	call	AAPL170519C00005000	150.65	149.45	151.65	0.000000
7.5	2017-05-19	call	AAPL170519C00007500	148.05	146.95	149.30	0.000000
10.0	2017-05-19	call	AAPL170519C00010000	143.53	145.65	146.60	0.000000
20.0	2017-05-19	call	AAPL170519C00020000	133.52	135.65	136.60	0.000000

Strike	Expiry	Type	Symbol	PctChg
2.5	2017-05-19	call	AAPL170519C00002500	5.839666
5.0	2017-05-19	call	AAPL170519C00005000	0.000000
7.5	2017-05-19	call	AAPL170519C00007500	0.000000
10.0	2017-05-19	call	AAPL170519C00010000	0.000000
20.0	2017-05-19	call	AAPL170519C00020000	0.000000

A list-like object containing dates can also be passed to the expiry parameter, returning options data for all expiry dates in the list.

```
In [34]: data = aapl.get_near_stock_price(expiry=aapl.expiry_dates[0:3])

In [35]: data.iloc[0:5:, 0:5]
Out[35]:
```

Strike	Expiry	Type	Symbol	Last	Bid	Ask	Chg	PctChg
152.5	2017-05-26	call	AAPL170526C00152500	4.05	4.00	4.10	-0.45	-9.999995
	2017-06-02	call	AAPL170602C00152500	4.09	4.10	4.15	-0.16	-3.764702
155.0	2017-05-19	call	AAPL170519C00155000	1.11	1.11	1.12	-0.48	-30.188679
	2017-05-26	call	AAPL170526C00155000	2.00	2.00	2.02	-0.35	-14.893614
	2017-06-02	call	AAPL170602C00155000	2.50	2.52	2.55	-0.35	-12.280699

The `month` and `year` parameters can be used to get all options data for a given month.

Google Finance

```

In [36]: import pandas_datareader.data as web

In [37]: import datetime

In [38]: start = datetime.datetime(2010, 1, 1)

In [39]: end = datetime.datetime(2013, 1, 27)

In [40]: f = web.DataReader("F", 'google', start, end)

In [41]: f.ix['2010-01-04']
Out[41]:
Open           10.17
High           10.28
Low            10.05
Close          10.28
Volume      60855796.00
Name: 2010-01-04 00:00:00, dtype: float64

```

Google Finance Quotes

Experimental

The GoogleQuotesReader class allows to get quotes data from Google Finance.

```

In [42]: import pandas_datareader.data as web

In [43]: q = web.get_quote_google(['AMZN', 'GOOG'])

In [44]: q
Out[44]:
   change_pct  last      time
AMZN      0.85  966.07  2017-05-16 16:00:00
GOOG      0.63  943.00  2017-05-16 16:00:00

```

Google Finance Options

Experimental

The Options class allows the download of options data from Google Finance.

The `get_options_data` method downloads options data for specified expiry date and provides a formatted `DataFrame` with a hierarchical index, so its easy to get to the specific option you want.

Available expiry dates can be accessed from the `expiry_dates` property.

```
In [45]: from pandas_datareader.data import Options

In [46]: goog = Options('goog', 'google')

In [47]: data = goog.get_options_data(expiry=goog.expiry_dates[0])

In [48]: data.iloc[0:5, 0:5]
Out[48]:
```

				Last	Bid	Ask	Chg	PctChg
Strike	Expiry	Type	Symbol					
350	2017-06-16	call	G00G170616C00350000	580.50	590.5	593.80	0	0
		put	G00G170616P00350000	0.03	NaN	0.45	0	0
360	2017-06-16	call	G00G170616C00360000	482.80	580.5	585.00	0	0
		put	G00G170616P00360000	0.05	NaN	0.15	0	0
370	2017-06-16	call	G00G170616C00370000	474.20	570.5	575.00	0	0

Enigma

Access datasets from [Enigma](#), the world's largest repository of structured public data.

```
In [49]: import os

In [50]: import pandas_datareader as pdr

In [51]: df = pdr.get_data_enigma('enigma.trade.ams.toxic.2015', os.getenv('ENIGMA_API_KEY'))

ValueErrorTraceback (most recent call last)
<ipython-input-51-8b19d4dc1932> in <module>()
----> 1 df = pdr.get_data_enigma('enigma.trade.ams.toxic.2015', os.getenv('ENIGMA_API_KEY'))

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/data.pyc in get_data_enigma(*args, **kwargs)
    42
    43 def get_data_enigma(*args, **kwargs):
--> 44     return EnigmaReader(*args, **kwargs).read()
    45
    46

/home/docs/checkouts/readthedocs.org/user_builds/pandas-
datareader/envs/latest/local/lib/python2.7/site-packages/pandas_datareader-0.4.0-
py2.7.egg/pandas_datareader/enigma.pyc in __init__(self, datapath, api_key, retry_count, pause,
session)
    47         self._api_key = os.getenv('ENIGMA_API_KEY')
    48         if self._api_key is None:
--> 49             raise ValueError("Please provide an Enigma API key or set "
    50                             "the ENIGMA_API_KEY environment variable\n"
    51                             "If you do not have an API key, you can get ")

ValueError: Please provide an Enigma API key or set the ENIGMA_API_KEY environment variable
If you do not have an API key, you can get one here: https://app.enigma.io/signup

In [52]: df.columns

NameErrorTraceback (most recent call last)
<ipython-input-52-6a4642092433> in <module>()
----> 1 df.columns

NameError: name 'df' is not defined
```

FRED

```
In [53]: import pandas_datareader.data as web

In [54]: import datetime

In [55]: start = datetime.datetime(2010, 1, 1)

In [56]: end = datetime.datetime(2013, 1, 27)

In [57]: gdp = web.DataReader("GDP", "fred", start, end)

In [58]: gdp.ix['2013-01-01']
Out[58]:
GDP      16475.4
Name: 2013-01-01 00:00:00, dtype: float64

# Multiple series:
In [59]: inflation = web.DataReader(["CPIAUCSL", "CPILFESL"], "fred", start, end)

In [60]: inflation.head()
Out[60]:
```

	CPIAUCSL	CPILFESL
DATE		
2010-01-01	217.488	220.633
2010-02-01	217.281	220.731
2010-03-01	217.353	220.783
2010-04-01	217.403	220.822
2010-05-01	217.290	220.962

Fama/French

Access datasets from the [Fama/French Data Library](#). The `get_available_datasets` function returns a list of all available datasets.

```
In [61]: from pandas_datareader.famafrench import get_available_datasets
```

```
In [62]: import pandas_datareader.data as web
```

```
In [63]: len(get_available_datasets())
```

```
Out[63]: 262
```

```
In [64]: ds = web.DataReader("5_Industry_Portfolios", "famafrench")
```

```
In [65]: print(ds['DESCR'])
```

```
5 Industry Portfolios
```

```
-----
```

This file was created by CMPT_IND_RETS using the 201703 CRSP database. It contains value- and equal-weighted returns for 5 industry portfolios. The portfolios are constructed at the end of June. The annual returns are from January to December. Missing data are indicated by -99.99 or -999. Copyright 2017 Kenneth R. French

```
0 : Average Value Weighted Returns -- Monthly (87 rows x 5 cols)
1 : Average Equal Weighted Returns -- Monthly (87 rows x 5 cols)
2 : Average Value Weighted Returns -- Annual (7 rows x 5 cols)
3 : Average Equal Weighted Returns -- Annual (7 rows x 5 cols)
4 : Number of Firms in Portfolios (87 rows x 5 cols)
5 : Average Firm Size (87 rows x 5 cols)
6 : Sum of BE / Sum of ME (7 rows x 5 cols)
7 : Value-Weighted Average of BE/ME (7 rows x 5 cols)
```

```
In [66]: ds[4].ix['1926-07']
```

```
KeyErrorTraceback (most recent call last)
```

```
<ipython-input-66-79093f940e41> in <module>()
```

```
----> 1 ds[4].ix['1926-07']
```

```
/usr/lib/python2.7/dist-packages/pandas/core/indexing.pyc in __getitem__(self, key)
```

```
68         return self._getitem_tuple(key)
```

```
69     else:
```

```
---> 70         return self._getitem_axis(key, axis=0)
```

```
71
```

```
72     def _get_label(self, label, axis=0):
```

```
/usr/lib/python2.7/dist-packages/pandas/core/indexing.pyc in _getitem_axis(self, key, axis)
```

```
965         return self._get_loc(key, axis=axis)
```

```
966
```

```
--> 967         return self._get_label(key, axis=axis)
```

```
968
```

```
969     def _getitem_iterable(self, key, axis=0):
```

```
/usr/lib/python2.7/dist-packages/pandas/core/indexing.pyc in _get_label(self, label, axis)
```

```
84         raise IndexError('no slices here, handle elsewhere')
```

```
85
```

```
---> 86         return self.obj._xs(label, axis=axis)
```

```
87
```

```
88     def _get_loc(self, key, axis=0):
```

```
/usr/lib/python2.7/dist-packages/pandas/core/generic.pyc in xs(self, key, axis, level, copy, drop_level)
```

```
1484                                     drop_level=drop_level)
```

```
1485     else:
```

```
-> 1486         loc = self.index.get_loc(key)
```

```
1487
```

```
1488         if isinstance(loc, np.ndarray):
```

```
/usr/lib/python2.7/dist-packages/pandas/tseries/period.pyc in get_loc(self, key, method, tolerance)
```

```
667         return Index.get_loc(self, key.ordinal, method, tolerance)
```

```
668     except KeyError:
```

```
--> 669         raise KeyError(key)
```

```
670
```

```
671     def _maybe_cast_slice_bound(self, label, side, kind):
```

```
KeyError: Period('1926-07', 'M')
```

World Bank

`pandas` users can easily access thousands of panel data series from the [World Bank's World Development Indicators](#) by using the `wb` I/O functions.

Indicators

Either from exploring the World Bank site, or using the search function included, every world bank indicator is accessible.

For example, if you wanted to compare the Gross Domestic Products per capita in constant dollars in North America, you would use the `search` function:

```
In [1]: from pandas_datareader import wb

In [2]: wb.search('gdp.*capita.*const').iloc[:,2]
Out[2]:
```

	id	name
3242	GDPPCKD	GDP per Capita, constant US\$, millions
5143	NY.GDP.PCAP.KD	GDP per capita (constant 2005 US\$)
5145	NY.GDP.PCAP.KN	GDP per capita (constant LCU)
5147	NY.GDP.PCAP.PP.KD	GDP per capita, PPP (constant 2005 internation...

Then you would use the `download` function to acquire the data from the World Bank's servers:

```
In [3]: dat = wb.download(indicator='NY.GDP.PCAP.KD', country=['US', 'CA', 'MX'], start=2005,
end=2008)

In [4]: print(dat)
```

		NY.GDP.PCAP.KD
country	year	
Canada	2008	36005.5004978584
	2007	36182.9138439757
	2006	35785.9698172849
	2005	35087.8925933298
Mexico	2008	8113.10219480083
	2007	8119.21298908649
	2006	7961.96818458178
	2005	7666.69796097264
United States	2008	43069.5819857208
	2007	43635.5852068142
	2006	43228.111147107
	2005	42516.3934699993

The resulting dataset is a properly formatted `DataFrame` with a hierarchical index, so it is easy to apply `.groupby` transformations to it:

```
In [6]: dat['NY.GDP.PCAP.KD'].groupby(level=0).mean()
Out[6]:
country
Canada      35765.569188
Mexico       7965.245332
United States 43112.417952
dtype: float64
```

Now imagine you want to compare GDP to the share of people with cellphone contracts around the world.

```
In [7]: wb.search('cell.*%').iloc[:, :2]
Out[7]:
```

	id	name
3990	IT.CEL.SETS.FE.ZS	Mobile cellular telephone users, female (% of ...
3991	IT.CEL.SETS.MA.ZS	Mobile cellular telephone users, male (% of po...
4027	IT.MOB.COV.ZS	Population coverage of mobile cellular telepho...

Notice that this second search was much faster than the first one because `pandas` now has a cached list of available data series.

```
In [13]: ind = ['NY.GDP.PCAP.KD', 'IT.MOB.COV.ZS']
In [14]: dat = wb.download(indicator=ind, country='all', start=2011, end=2011).dropna()
In [15]: dat.columns = ['gdp', 'cellphone']
In [16]: print(dat.tail())
```

country	year	gdp	cellphone
Swaziland	2011	2413.952853	94.9
Tunisia	2011	3687.340170	100.0
Uganda	2011	405.332501	100.0
Zambia	2011	767.911290	62.0
Zimbabwe	2011	419.236086	72.4

Finally, we use the `statsmodels` package to assess the relationship between our two variables using ordinary least squares regression. Unsurprisingly, populations in rich countries tend to use cellphones at a higher rate:

```

In [17]: import numpy as np
In [18]: import statsmodels.formula.api as smf
In [19]: mod = smf.ols("cellphone ~ np.log(gdp)", dat).fit()
In [20]: print(mod.summary())

```

OLS Regression Results

```

=====
Dep. Variable:          cellphone    R-squared:                0.297
Model:                  OLS         Adj. R-squared:           0.274
Method:                 Least Squares    F-statistic:             13.08
Date:                   Thu, 25 Jul 2013    Prob (F-statistic):      0.00105
Time:                   15:24:42          Log-Likelihood:          -139.16
No. Observations:       33              AIC:                    282.3
Df Residuals:           31              BIC:                    285.3
Df Model:                1
=====

```

	coef	std err	t	P> t	[95.0% Conf. Int.]	
Intercept	16.5110	19.071	0.866	0.393	-22.384	55.406
np.log(gdp)	9.9333	2.747	3.616	0.001	4.331	15.535

```

=====
Omnibus:                 36.054    Durbin-Watson:           2.071
Prob(Omnibus):            0.000    Jarque-Bera (JB):        119.133
Skew:                     -2.314    Prob(JB):                1.35e-26
Kurtosis:                 11.077    Cond. No.:               45.8
=====

```

Country Codes

The `country` argument accepts a string or list of mixed [two](#) or [three](#) character ISO country codes, as well as dynamic [World Bank exceptions](#) to the ISO standards.

For a list of the the hard-coded country codes (used solely for error handling logic) see

```
pandas_datareader.wb.country_codes.
```

Problematic Country Codes & Indicators

! Note

The World Bank's country list and indicators are dynamic. As of 0.15.1, `wb.download()` is more flexible. To achieve this, the warning and exception logic changed.

The world bank converts some country codes, in their response, which makes error checking by pandas difficult. Retired indicators still persist in the search.

Given the new flexibility of 0.15.1, improved error handling by the user may be necessary for fringe cases.

To help identify issues:

There are at least 4 kinds of country codes:

1. Standard (2/3 digit ISO) - returns data, will warn and error properly.
2. Non-standard (WB Exceptions) - returns data, but will falsely warn.
3. Blank - silently missing from the response.
4. Bad - causes the entire response from WB to fail, always exception inducing.

There are at least 3 kinds of indicators:

1. Current - Returns data.
2. Retired - Appears in search results, yet won't return data.
3. Bad - Will not return data.

Use the `errors` argument to control warnings and exceptions. Setting errors to ignore or warn, won't stop failed responses. (ie, 100% bad indicators, or a single "bad" (#4 above) country code).

See docstrings for more info.

OECD

[OECD Statistics](#) are available via `DataReader`. You have to specify OECD's data set code.

To confirm data set code, access to `each data -> Export -> SDMX Query`. Following example is to download "Trade Union Density" data which set code is "UN_DEN".

```
In [67]: import pandas_datareader.data as web

In [68]: import datetime

In [69]: df = web.DataReader('UN_DEN', 'oecd', end=datetime.datetime(2012, 1, 1))

In [70]: df.columns
Out[70]:
Index([u'Australia', u'Austria', u'Belgium', u'Canada', u'Czech Republic',
       u'Denmark', u'Finland', u'France', u'Germany', u'Greece', u'Hungary',
       u'Iceland', u'Ireland', u'Italy', u'Japan', u'Korea', u'Luxembourg',
       u'Mexico', u'Netherlands', u'New Zealand', u'Norway', u'Poland',
       u'Portugal', u'Slovak Republic', u'Spain', u'Sweden', u'Switzerland',
       u'Turkey', u'United Kingdom', u'United States', u'OECD countries',
       u'Chile', u'Slovenia', u'Estonia', u'Israel'],
      dtype='object', name=u'Country')

In [71]: df[['Japan', 'United States']]
Out[71]:
Country      Japan  United States
Time
2010-01-01  18.403807      11.383460
2011-01-01  18.995042      11.329488
2012-01-01  17.972384      10.815352
```

Eurostat are available via `DataReader`.

Get ` Rail accidents by type of accident (ERA data)

<http://appsso.eurostat.ec.europa.eu/nui/show.do?dataset=tran_sf_railac&lang=en>`_ data. The result will be a `DataFrame` which has `DatetimeIndex` as index and `MultiIndex` of attributes or countries as column. The target URL is:

- http://appsso.eurostat.ec.europa.eu/nui/show.do?dataset=tran_sf_railac&lang=en

You can specify dataset ID “tran_sf_railac” to get corresponding data via `DataReader`.

```
In [72]: import pandas_datareader.data as web
```

```
In [73]: df = web.DataReader("tran_sf_railac", 'eurostat')
```

```
In [74]: df
```

```
Out[74]:
```

```
ACCIDENT    Collisions of trains, including collisions with obstacles within the clearance gauge  
\
```

```
UNIT
```

```
Number
```

```
GEO
```

```
Austria
```

```
FREQ
```

```
Annual
```

```
TIME_PERIOD
```

2010-01-01	3
2011-01-01	2
2012-01-01	1
2013-01-01	4
2014-01-01	1
2015-01-01	7

```
ACCIDENT
```

```
UNIT
```

```
GEO    Belgium Bulgaria Switzerland Channel Tunnel Czech Republic
```

```
FREQ    Annual    Annual    Annual    Annual    Annual    Annual
```

```
TIME_PERIOD
```

2010-01-01	5	2	5	0	3
2011-01-01	0	0	4	0	6
2012-01-01	3	3	4	0	6
2013-01-01	1	2	6	0	5
2014-01-01	3	4	0	0	13
2015-01-01	0	3	3	0	14

```
ACCIDENT
```

```
UNIT
```

```
GEO    Germany (until 1990 former territory of the FRG) Denmark Estonia
```

```
FREQ    Annual    Annual    Annual
```

```
TIME_PERIOD
```

2010-01-01	13	0	1
2011-01-01	18	1	0
2012-01-01	23	1	3
2013-01-01	29	0	0
2014-01-01	32	0	0
2015-01-01	40	3	0

```
ACCIDENT
```

```
UNIT
```

```
GEO    Greece ... Total  
Latvia Netherlands Norway Poland Portugal
```

```
FREQ    Annual ... Annual    Annual    Annual    Annual    Annual
```

```
TIME_PERIOD
```

2010-01-01	4	...	41	24	20	449	42
2011-01-01	1	...	35	29	36	488	27
2012-01-01	2	...	25	30	19	379	36
2013-01-01	2	...	26	36	30	328	48
2014-01-01	1	...	22	20	28	313	50
2015-01-01	1	...	25	31	19	307	23

```
ACCIDENT
```

```
UNIT
```

```
GEO    Romania Sweden Slovenia Slovakia United Kingdom
```

```
FREQ    Annual    Annual    Annual    Annual    Annual
```

```
TIME_PERIOD
```

2010-01-01	271	69	21	85	62
2011-01-01	217	54	11	84	78
2012-01-01	215	47	14	96	75
2013-01-01	180	43	13	94	84
2014-01-01	185	53	15	113	54
2015-01-01	141	40	14	87	40

```
[6 rows x 210 columns]
```

EDGAR Index

** As of December 31st, the SEC disabled access via FTP. EDGAR support currently broken until re-write to use HTTPS. **

Company filing index from EDGAR (SEC).

The daily indices get large quickly (i.e. the set of daily indices from 1994 to 2015 is 1.5GB), and the FTP server will close the connection past some downloading threshold . In testing, pulling one year at a time works well. If the FTP server starts refusing your connections, you should be able to reconnect after waiting a few minutes.

TSP Fund Data

Download mutual fund index prices for the TSP.

```

In [75]: import pandas_datareader.tsp as tsp

In [76]: tspreader = tsp.TSPReader(start='2015-10-1', end='2015-12-31')

In [77]: tspreader.read()
Out[77]:

```

	L Income	L 2020	L 2030	L 2040	L 2050	G Fund	F Fund	\
date								
2015-10-01	17.5164	22.5789	24.2159	25.5690	14.4009	14.8380	17.0467	
2015-10-02	17.5707	22.7413	24.4472	25.8518	14.5805	14.8388	17.0924	
2015-10-05	17.6395	22.9582	24.7571	26.2306	14.8233	14.8413	17.0531	
2015-10-06	17.6338	22.9390	24.7268	26.1898	14.7979	14.8421	17.0790	
2015-10-07	17.6639	23.0324	24.8629	26.3598	14.9063	14.8429	17.0725	
2015-10-08	17.6957	23.1364	25.0122	26.5422	15.0240	14.8437	17.0363	
2015-10-09	17.7048	23.1646	25.0521	26.5903	15.0554	14.8445	17.0511	
...	
2015-12-22	17.7493	23.1452	24.9775	26.4695	14.9611	14.9076	16.9607	
2015-12-23	17.8015	23.3149	25.2208	26.7663	15.1527	14.9084	16.9421	
2015-12-24	17.7991	23.3039	25.2052	26.7481	15.1407	14.9093	16.9596	
2015-12-28	17.7950	23.2811	25.1691	26.7015	15.1101	14.9128	16.9799	
2015-12-29	17.8270	23.3871	25.3226	26.8905	15.2319	14.9137	16.9150	
2015-12-30	17.8066	23.3216	25.2267	26.7707	15.1556	14.9146	16.9249	
2015-12-31	17.7733	23.2085	25.0635	26.5715	15.0263	14.9154	16.9549	

	C Fund	S Fund	I Fund	
date				
2015-10-01	25.7953	34.0993	23.3202	NaN
2015-10-02	26.1669	34.6504	23.6367	
2015-10-05	26.6467	35.3565	24.1475	
2015-10-06	26.5513	35.1320	24.2294	
2015-10-07	26.7751	35.6035	24.3671	
2015-10-08	27.0115	35.9016	24.6406	
2015-10-09	27.0320	35.9772	24.7723	
...
2015-12-22	27.4848	35.0903	23.8679	
2015-12-23	27.8272	35.5749	24.3623	
2015-12-24	27.7831	35.6084	24.3272	
2015-12-28	27.7230	35.4625	24.2816	
2015-12-29	28.0236	35.8047	24.4757	
2015-12-30	27.8239	35.5126	24.4184	
2015-12-31	27.5622	35.2356	24.0952	

[62 rows x 11 columns]

Oanda currency historical rate

Download currency historical rate from [Oanda](#).

```

In [1]: from pandas_datareader.oanda import get_oanda_currency_historical_rates
In [2]: start, end = "2016-01-01", "2016-06-01"
In [3]: quote_currency = "USD"
In [4]: base_currency = ["EUR", "GBP", "JPY"]
In [5]: df_rates = get_oanda_currency_historical_rates(
    start, end,
    quote_currency=quote_currency,
    base_currency=base_currency
)
In [6]: print(df_rates)

```

	EUR/USD	GBP/USD	JPY/USD
Date			
2016-01-01	1.087090	1.473989	0.008320
2016-01-02	1.087090	1.473989	0.008320
2016-01-03	1.087090	1.473989	0.008320
2016-01-04	1.086730	1.473481	0.008370
2016-01-05	1.078760	1.469430	0.008388
...
2016-05-28	1.111669	1.462630	0.009072
2016-05-29	1.111669	1.462630	0.009072
2016-05-30	1.112479	1.461999	0.009006
2016-05-31	1.114269	1.461021	0.009010
2016-06-01	1.115170	1.445410	0.009095

[153 rows x 3 columns]

Nasdaq Trader Symbol Definitions

Download the latest symbols from

``Nasdaq<ftp://ftp.nasdaqtrader.com/SymbolDirectory/nasdaqtraded.txt/>`__.`

Note that Nasdaq updates this file daily, and historical versions are not available. More information on the *field*<<http://www.nasdaqtrader.com/trader.aspx?id=symboldirdefs/>> definitions.

```

In [12]: from pandas_datareader.nasdaq_trader import get_nasdaq_symbols
In [13]: symbols = get_nasdaq_symbols()
In [14]: print(symbols.ix['IBM'])

```

Nasdaq Traded	True
Security Name	International Business Machines Corporation Co...
Listing Exchange	N
Market Category	
ETF	False
Round Lot Size	100
Test Issue	False
Financial Status	NaN
CQS Symbol	IBM
NASDAQ Symbol	IBM
NextShares	False

Name: IBM, dtype: object