

Лабораторная работа

Номер 14

Андрюшин Н. С.

01 января 1970

Российский университет дружбы народов, Москва, Россия

Информация

- Андрюшин Никита Сергеевич
- Студент
- Российский университет дружбы народов

Приобретение навыков настройки доступа групп пользователей к общим ресурсам по протоколу SMB.

Установка пакетов Samba на сервере

```
[nsandryushin@server.nsandryushin.net ~]$ sudo dnf -y install samba samba-client cifs-utils
[sudo] password for nsandryushin:
Last metadata expiration check: 0:08:01 ago on Sat 06 Dec 2025 10:54:04 AM UTC.
Dependencies resolved.
=====
Package                                Architecture      Version            Repository          Size
=====
Installing:
  cifs-utils                            x86_64            7.2-1.el10         baseos              117 k
  samba                                 x86_64            4.22.4-106.el10    baseos              959 k
  samba-client                          x86_64            4.22.4-106.el10    appstream           770 k
Installing dependencies:
  libnetapi                             x86_64            4.22.4-106.el10    baseos              144 k
  samba-common-tools                    x86_64            4.22.4-106.el10    baseos              481 k
  samba-dcerpc                          x86_64            4.22.4-106.el10    baseos              716 k
  samba-ldb-ldap-modules                x86_64            4.22.4-106.el10    baseos               35 k
  samba-libs                            x86_64            4.22.4-106.el10    baseos              124 k

Transaction Summary
=====
Install 8 Packages
```

Рис. 1: Установка пакетов Samba на сервере

Создание пользователей, групп и каталога

```
[nsandryushin@server.nsandryushin.net ~]$ sudo groupadd -g 1010 sambagroup  
[nsandryushin@server.nsandryushin.net ~]$ sudo usermod -aG sambagroup nsandryushin  
[nsandryushin@server.nsandryushin.net ~]$ sudo mkdir -p /srv/smbashare  
[nsandryushin@server.nsandryushin.net ~]$ sudo nano /etc/samba/smb.conf
```

Рис. 2: Создание пользователей, групп и каталога

Настройка smb.conf

```
GNU nano 2.1 /etc/samba/smb.conf
# you modified it.
#
# Note:
# SMB1 is disabled by default. This means clients without support for SMB2 or
# SMB3 are no longer able to connect to smbd (by default).

[global]
workgroup = MSANDRYUSHIN-NET
security = user
passdb backend = tdbsam

printing = cups
printcap name = cups
load printers = yes
cups options = raw

# Install samba-usershares package for support
include = /etc/samba/usershares.conf

[homes]
comment = Home Directories
valid users = %S, %S%5
browseable = No
read only = No
inherit acls = Yes

[printers]
comment = All Printers
path = /var/tmp
printable = Yes
create mask = 0600
browseable = No

[printers]
comment = Printer Drivers
path = /var/lib/samba/drivers
# printadmin is a local group
write list = printadmins root
force group = printadmin
create mask = 0664
directory mask = 0775

[sambashare]
comment = My Samba Share
path = /srv/sambashare
write list = sambagroup

Wrote 18 lines.
```

Рис. 3: Настройка smb.conf

Проверка конфигурации

```
[nsandryushin@server nsandryushin.net ~]$ sudo testparm
Load smb config files from /etc/samba/smb.conf
Loaded services file OK.
Weak crypto is allowed by 0x0000 (e.g. NTLM as a compatibility fallback)

Server role: ROLE_STANDALONE

Press enter to see a dump of your service definitions

# Global parameters
[global]
    printcap name = cups
    security = USER
    workgroup = NSANDRYUSHIN-NET
    idmap config * : backend = tdb
    cup.s options = raw
    include = /etc/samba/usershares.conf

[homes]
    browseable = No
    comment = Home Directories
    inherit acls = Yes
    read only = No
    valid users = %S %Dn%5S

[printers]
    browseable = No
    comment = All Printers
    create mask = 0600
    path = /var/tmp
    printable = Yes

[print$]
    comment = Printer Drivers
    create mask = 0604
    directory mask = 0775
    force group = printadmin
    path = /var/lib/samba/drivers
    write list = printadmin root

[smbashare]
    comment = My Samba Share
    path = /srv/smbashare
    write list = smbashgroup
[nsandryushin@server nsandryushin.net ~]$
```

Рис. 4: Проверка конфигурации

Запуск службы SMB

```
[nsandryushin@server.nsandryushin.net ~]$ systemctl start smb
[nsandryushin@server.nsandryushin.net ~]$ systemctl enable smb
Created symlink '/etc/systemd/system/multi-user.target.wants/smb.service' → '/usr/lib/systemd/system/smb.service'.
[nsandryushin@server.nsandryushin.net ~]$ systemctl status smb
● smb.service - Samba SMB Daemon
   Loaded: loaded (/usr/lib/systemd/system/smb.service; enabled; preset: disabled)
   Active: active (running) since Sat 2025-12-06 11:09:05 UTC; 16s ago
 Invocation: 041c727ca1ba4b9fa5732a89e084ff04
    Docs: man:smbd(8)
          man:samba(7)
          man:smb.conf(5)
 Main PID: 9968 (smbd)
   Status: "smbd: ready to serve connections..."
    Tasks: 3 (limit: 10407)
  Memory: 13.6M (peak: 13.8M)
     CPU: 204ms
    CGroup: /system.slice/smb.service
            └─9968 /usr/sbin/smbd --foreground --no-process-group
              └─9975 /usr/sbin/smbd --foreground --no-process-group
                └─9976 /usr/sbin/smbd --foreground --no-process-group

Dec 06 11:09:05 server.nsandryushin.net systemd[1]: Starting smb.service - Samba SMB Daemon...
Dec 06 11:09:05 server.nsandryushin.net systemd[1]: Started smb.service - Samba SMB Daemon.
[nsandryushin@server.nsandryushin.net ~]$
```

Рис. 5: Запуск службы SMB

Проверка доступа через smbclient

```
[nsandryushin@server.nsandryushin.net ~]$ smbclient -L //server
Password for [NSANDRYUSHIN-NET\nsandryushin]:
Anonymous login successful
```

Sharename	Type	Comment
-----	----	-----
print\$	Disk	Printer Drivers
smbashare	Disk	My Samba Share
IPC\$	IPC	IPC Service (Samba 4.22.4)

```
SMB1 disabled -- no workgroup available
[nsandryushin@server.nsandryushin.net ~]$ less /usr/lib/firewalld/services/samba.xml
```

Рис. 6: Проверка доступа через smbclient

Файл конфигурации службы samba.xml

```
<?xml version="1.0" encoding="utf-8"?>
<service>
  <short>Samba</short>
  <description>This option allows you to access and participate in Windows file and printer sharing networks. You need the samba package installed for this option to be useful.</description>
  <include service="samba-client"/>
  <port protocol="tcp" port="139"/>
  <port protocol="tcp" port="445"/>
</service>
/usr/lib/firewalld/services/samba.xml (END)
```

Рис. 7: Файл конфигурации службы samba.xml

Настройка Firewall и прав доступа

```
[nsandryushin@server.nsandryushin.net ~]$ firewall-cmd --add-service=samba
success
[nsandryushin@server.nsandryushin.net ~]$ firewall-cmd --add-service=samba --permanent
success
[nsandryushin@server.nsandryushin.net ~]$ firewall-cmd --reload
success
[nsandryushin@server.nsandryushin.net ~]$ sudo chgrp sambagroup /srv/smbashare
[nsandryushin@server.nsandryushin.net ~]$ sudo chmod g=rwx /srv/smbashare
[nsandryushin@server.nsandryushin.net ~]$ cd /srv
[nsandryushin@server.nsandryushin.net srv]$ ls -Z
unconfined_u:object_r:nfs_t:s0 nfs unconfined_u:object_r:var_t:s0 smbashare
```

Рис. 8: Настройка Firewall и прав доступа

Настройка контекста SELinux

```
[nsandryushin@server.nsandryushin.net srv]$ sudo semanage fcontext -a -t samba_share_t "/srv/sambashare(/.*)?"
[nsandryushin@server.nsandryushin.net srv]$ restorecon -vR /srv/sambashare
restorecon: Could not set context for /srv/sambashare: Operation not permitted
[nsandryushin@server.nsandryushin.net srv]$ sudo restorecon -vR /srv/sambashare
Relabeled /srv/sambashare from unconfined_u:object_r:var_t:s0 to unconfined_u:object_r:samba_share_t:s0
[nsandryushin@server.nsandryushin.net srv]$ ls -Z
      unconfined_u:object_r:nfs_t:s0 nfs      unconfined_u:object_r:samba_share_t:s0 sambashare
[nsandryushin@server.nsandryushin.net srv]$
```

Рис. 9: Настройка контекста SELinux

Настройка boolean SELinux

```
[nsandryushin@server.nsandryushin.net srv]$ sudo setsebool samba_export_all_rw 1
[nsandryushin@server.nsandryushin.net srv]$ sudo setsebool samba_export_all_rw 1 -P
[nsandryushin@server.nsandryushin.net srv]$ id
uid=1001(nsandryushin) gid=1001(nsandryushin) groups=1001(nsandryushin),10(wheel) context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
```

Рис. 10: Настройка boolean SELinux

Создание тестового файла и SMB-пользователя

```
[nsandryushin@server.nsandryushin.net srv]$ cd /srv/smbashare
[nsandryushin@server.nsandryushin.net sambashare]$ touch user@server.txt
touch: cannot touch 'user@server.txt': Permission denied
[nsandryushin@server.nsandryushin.net sambashare]$ sudo touch nsandryushin@server.txt
[nsandryushin@server.nsandryushin.net sambashare]$ sudo smbpasswd -L -a nsandryushin
New SMB password:
Retype new SMB password:
Added user nsandryushin.
[nsandryushin@server.nsandryushin.net sambashare]$ █
```

Рис. 11: Создание тестового файла и SMB-пользователя

Установка пакетов на клиенте

```
[nsandryushin@client.nsandryushin.net ~]$ sudo dnf -y install samba-client cifs-utils
[sudo] password for nsandryushin:
Extra Packages for Enterprise Linux 10 - x86_64                7.2 kB/s | 38 kB    00:05
Extra Packages for Enterprise Linux 10 - x86_64                1.2 MB/s | 5.5 MB    00:04
Rocky Linux 10 - BaseOS                                         230 B/s | 4.3 kB    00:05
Rocky Linux 10 - BaseOS                                         689 kB/s | 4.1 MB    00:05
Rocky Linux 10 - AppStream                                       1.5 kB/s | 4.3 kB    00:02
Rocky Linux 10 - AppStream                                       1.5 MB/s | 1.9 MB    00:01
Rocky Linux 10 - CRB                                             14 kB/s | 4.3 kB    00:00
Rocky Linux 10 - CRB                                             756 kB/s | 483 kB    00:00
Rocky Linux 10 - Extras                                           8.9 kB/s | 3.1 kB    00:00
Rocky Linux 10 - Extras                                          12 kB/s | 4.8 kB    00:00
Dependencies resolved.
=====
Package      Architecture      Version      Repository      Size
=====
Installing:
cifs-utils   x86_64            7.2-1.el10   baseos          117 k
samba-client x86_64            4.22.4-106.el10 appstream       770 k
=====
Transaction Summary
=====
Install 2 Packages

Total download size: 887 k
Installed size: 3.8 M
Downloading Packages:
(1/2): cifs-utils-7.2-1.el10.x86_64.rpm                       969 kB/s | 117 kB    00:00
(2/2): samba-client-4.22.4-106.el10.x86_64.rpm                 2.0 MB/s | 770 kB    00:00
-----
Total                                     889 kB/s | 887 kB    00:00
Running transaction check
Transaction check succeeded.
Running transaction test
Transaction test succeeded.
Running transaction
  Preparing      :                                1/1
  Installing     : samba-client-4.22.4-106.el10.x86_64      1/2
  Running scriptlet: samba-client-4.22.4-106.el10.x86_64      1/2
  Installing     : cifs-utils-7.2-1.el10.x86_64             2/2
  Running scriptlet: cifs-utils-7.2-1.el10.x86_64             2/2

Installed:
cifs-utils-7.2-1.el10.x86_64                samba-client-4.22.4-106.el10.x86_64

Complete!
[nsandryushin@client.nsandryushin.net ~]$ sudo less /usr/lib/ Firewall/services/samba-client.xml
```

Рис. 12: Установка пакетов на клиенте


```
<?xml version="1.0" encoding="utf-8"?>
<service>
  <short>Samba Client</short>
  <description>This option allows you to access Windows file and printer sharing networks. You need the s
amba-client package installed for this option to be useful.</description>
  <include service="netbios-ns"/>
  <port protocol="udp" port="138"/>
</service>
(END)
```

Рис. 13: Просмотр samba-client.xml

Настройка окружения на клиенте

```
[nsandryushin@client.nsandryushin.net ~]$ sudo firewall-cmd --add-service=samba-client
success
[nsandryushin@client.nsandryushin.net ~]$ sudo firewall-cmd --add-service=samba-client --permanent
success
[nsandryushin@client.nsandryushin.net ~]$ sudo firewall-cmd --reload
success
[nsandryushin@client.nsandryushin.net ~]$ sudo groupadd -g 1010 sambagroup
[nsandryushin@client.nsandryushin.net ~]$ sudo usermod -aG sambagroup nsandryushin
[nsandryushin@client.nsandryushin.net ~]$ sudo nano /etc/samba/smb.conf
```

Рис. 14: Настройка окружения на клиенте

Настройка рабочей группы на клиенте

```
GNU nano 8.1 /etc/samba/smb.conf
# See smb.conf.example for a more detailed config file or
# read the smb.conf manpage.
# Run 'testparm' to verify the config is correct after
# you modified it.
#
# Note:
# SMB1 is disabled by default. This means clients without support for SMB2 or
# SMB3 are no longer able to connect to smbd (by default).

[global]
    workgroup = NSANDRYUSHIN-NET
    security = user

    passdb backend = tdbsam

    printing = cups
    printcap name = cups
    load printers = yes
    cups options = raw

    # Install samba-usershares package for support
    include = /etc/samba/usershares.conf

[homes]
    comment = Home Directories
    valid users = %S, %D%%S
    browseable = No
    read only = No
    inherit acls = Yes
```

Рис. 15: Настройка рабочей группы на клиенте

Проверка списка ресурсов сервера с клиента

```
[nsandryushin@client.nsandryushin.net ~]$ smbclient -L //server  
Password for [NSANDRYUSHIN-NET\nsandryushin]:
```

Sharename	Type	Comment
-----	----	-----
print\$	Disk	Printer Drivers
smbashare	Disk	My Samba Share
IPC\$	IPC	IPC Service (Samba 4.22.4)
nsandryushin	Disk	Home Directories

```
SMB1 disabled -- no workgroup available
```

```
[nsandryushin@client.nsandryushin.net ~]$
```

Рис. 16: Проверка списка ресурсов сервера с клиента

Ручное монтирование и проверка записи

```
[nsandryushin@client.nsandryushin.net ~]$ sudo mkdir /mnt/samba
[nsandryushin@client.nsandryushin.net ~]$ sudo mount -o username=nsandryushin,user,rw,uid=user_name,gid=sambagroup //server/smbashare /mnt/samba
mount: /mnt/samba: failed to parse mount options 'rw,username=nsandryushin,user,noexec,nosuid,nodev,uid=user_name,gid=sambagroup': Invalid argument.
mount: (hint) your fstab has been modified, but systemd still uses
        the old version; use 'systemctl daemon-reload' to reload.
[nsandryushin@client.nsandryushin.net ~]$ sudo mount -o username=nsandryushin,user,rw,uid=nsandryushin,gid=sambagroup //server/smbashare /mnt/samba
Password for nsandryushin@//server/smbashare:
mount: (hint) your fstab has been modified, but systemd still uses
        the old version; use 'systemctl daemon-reload' to reload.
[nsandryushin@client.nsandryushin.net ~]$ cd /mnt/samba
[nsandryushin@client.nsandryushin.net samba]$ touch nsandryushin@client.txt
[nsandryushin@client.nsandryushin.net samba]$ ls
nsandryushin@client.txt  nsandryushin@server.txt
[nsandryushin@client.nsandryushin.net samba]$ sudo umount /mnt/samba
umount: /mnt/samba: target is busy.
[nsandryushin@client.nsandryushin.net samba]$ cd ..
[nsandryushin@client.nsandryushin.net mnt]$ sudo umount /mnt/samba
[nsandryushin@client.nsandryushin.net mnt]$ █
```

Рис. 17: Ручное монтирование и проверка записи

Создание файла учетных данных

```
[nsandryushin@client.nsandryushin.net mnt]$ sudo touch /etc/samba/smbusers  
[nsandryushin@client.nsandryushin.net mnt]$ sudo chmod 600 /etc/samba/smbusers  
[nsandryushin@client.nsandryushin.net mnt]$ sudo nano /etc/samba/smbusers
```

Рис. 18: Создание файла учетных данных

Содержимое файла smbusers



```
GNU nano 8.1 /etc/samba/smbusers
username=nsandryushin
password=123456
```

Рис. 19: Содержимое файла smbusers

Редактирование fstab

```
GNU nano 8.1 /etc/fstab
#
# /etc/fstab
# Created by anaconda on Sat Sep  6 16:45:04 2025
#
# Accessible filesystems, by reference, are maintained under '/dev/disk/'.
# See man pages fstab(5), findfs(8), mount(8) and/or blkid(8) for more info.
#
# After editing this file, run 'systemctl daemon-reload' to update systemd
# units generated from this file.
#
UUID=bf9aaaae8-a4dd-4b5a-be57-7faf0fd4a158 / xfs defaults 0 0
UUID=c92e69ed-3ed5-4d9c-ba1a-47af2e3b4400 /boot xfs defaults 0 0
UUID=5072-7B38 /boot/efi vfat umask=0077,shortname=winnt 0 2
UUID=d95619c0-6bd0-463c-8065-1bcb2fcf63ed /home xfs defaults 0 0
UUID=44d16fce-ebea-40da-8e90-ef32b3bf6061 none swap defaults 0 0
server.nsandryushin.net:/srv/nfs /mnt/nfs nfs _netdev 0 0
#VAGRANT-BEGIN
# The contents below are automatically generated by Vagrant. Do not modify.
vagrant /vagrant vboxsf uid=1000,gid=1000,_netdev 0 0
#VAGRANT-END
//server/sambashare /mnt/samba cifs user,rw,uid=nsandryushin,gid=sambagroup,credentials=/etc/samba/smbus>
```

Рис. 20: Редактирование fstab

Проверка автоматического монтирования

```
[nsandryushin@client.nsandryushin.net mnt]$ sudo mount -a
mount: (hint) your fstab has been modified, but systemd still uses
        the old version; use 'systemctl daemon-reload' to reload.
[nsandryushin@client.nsandryushin.net mnt]$ ls samba/
nsandryushin@client.txt  nsandryushin@server.txt
[nsandryushin@client.nsandryushin.net mnt]$
```

Рис. 21: Проверка автоматического монтирования

Список файлов в общем ресурсе

```
[nsandryushin@client.nsandryushin.net ~]$ ls /mnt/samba/  
nsandryushin@client.txt nsandryushin@server.txt  
[nsandryushin@client.nsandryushin.net ~]$
```

Рис. 22: Список файлов в общем ресурсе

Подготовка каталогов provision на сервере

```
[nsandryushin@server.nsandryushin.net sambashare]$ cd /vagrant/provision/server
[nsandryushin@server.nsandryushin.net server]$ sudo mkdir -p /vagrant/provision/server/smb/etc/samba
[sudo] password for nsandryushin:
[nsandryushin@server.nsandryushin.net server]$ sudo cp -R /etc/samba/smb.conf /vagrant/provision/server/s
mb/etc/samba/
[nsandryushin@server.nsandryushin.net server]$ cd /vagrant/provision/server
[nsandryushin@server.nsandryushin.net server]$ sudo touch smb.sh
[nsandryushin@server.nsandryushin.net server]$ sudo chmod +x smb.sh
[nsandryushin@server.nsandryushin.net server]$ sudo nano smb.sh █
```

Рис. 23: Подготовка каталогов provision на сервере

Скрипт smb.sh для сервера

```
GNU nano 8.1      smb.sh
#!/bin/bash
LOGIN=nsandryushin
PASS=123456

echo "Provisioning script $0"
echo "Install needed packages"
dnf -y install samba samba-client cifs-utils
echo "Copy configuration files"
cp -R /vagrant/provision/serve/smb/etc/* /etc
chown -R root:root /etc/samba/*
restorecon -vR /etc
echo "Configure firewall"
firewall-cmd --add-service samba --permanent
firewall-cmd --reload
echo "Users and groups"
groupadd -g 1010 sambagroup
usermod -aG sambagroup $LOGIN
echo -ne "$PASS\n$PASS\n" | smbpasswd -L -a -s $LOGIN
echo "Make share dir"
mkdir -p /srv/sambashare
chgrp sambagroup /srv/sambashare
chmod g+rxw /srv/sambashare
echo "Tuning SELinux"
semanage fcontext -a -t samba_share_t "/srv/sambashare(/.*)?"
setsebool samba_export_all_rw 1
setsebool samba_export_all_rw 1 -P
restorecon -vR /srv/sambashare
echo "Start smb service"
systemctl enable smb
systemctl start smb
systemctl restart firewalld
```

Рис. 24: Скрипт smb.sh для сервера

Подготовка каталогов provision на клиенте

```
[nsandryushin@client.nsandryushin.net ~]$ cd /vagrant/provision/client
[nsandryushin@client.nsandryushin.net client]$ sudo mkdir -p /vagrant/provision/client/smb/etc/samba
[sudo] password for nsandryushin:
[nsandryushin@client.nsandryushin.net client]$ sudo cp -R /etc/samba/smb.conf /vagrant/provision/client/s
mb/etc/samba/
[nsandryushin@client.nsandryushin.net client]$ sudo cp -R /etc/samba/smbusers /vagrant/provision/client/s
mb/etc/samba/
[nsandryushin@client.nsandryushin.net client]$ cd /vagrant/provision/client
[nsandryushin@client.nsandryushin.net client]$ sudo touch smb.sh
[nsandryushin@client.nsandryushin.net client]$ sudo chmod +x smb.sh
[nsandryushin@client.nsandryushin.net client]$ sudo nano smb.sh █
```

Рис. 25: Подготовка каталогов provision на клиенте

Скрипт smb.sh для клиента

```
GNU nano 8.1                                smb.sh
#!/bin/bash
LOGIN=nsandryushin
echo "Provisioning script $0"

mkdir -p /mnt/samba
echo "Install needed packages"
dnf -y install samba-client cifs-utils
echo "Copy configuration files"
cp -R /vagrant/provision/client/smb/etc/* /etc
chown -R root:root /etc/samba/*
restorecon -vR /etc
echo "Configure firewall"
firewall-cmd --add-service samba-client --permanent
firewall-cmd --reload
echo "Users and groups"
groupadd -g 1010 sambagroup
usermod -aG sambagroup $LOGIN
echo "Mounting dirs"
mkdir -p /srv/sambashare
echo "///server/sambashare /mnt/samba cifs [user,rw,credentials=/etc/samba/smbusers,uid=user,gid=sambagrou"
restorecon -vR /etc
umount /mnt/samba
mount /mnt/samba
```

Рис. 26: Скрипт smb.sh для клиента

Обновленный Vagrantfile

```

117     preswrv_order: true,
118     path: "provision/server/sfs.sh",
119     type: "shell",
120     preswrv_order: true,
121     path: "provision/server/smb.sh",
122 end
123
124 ## Client configuration
125 config.vm.define "client", autostart: false do |client|
126   client.vm.box = "hyperviso1"
127   client.vm.hostname = "client"
128   client.vm.boot_timeout = 1400
129
130   client.ssh.insert_key = false
131   client.ssh.username = "vagrant"
132   client.ssh.password = "vagrant"
133
134   client.vm.network :private_network,
135     type: "dhcp",
136     virtualbox____l2tpot true
137
138   client.vm.provider :virtualbox do |virtualbox|
139     virtualbox.customize ["modifyvm", :id, "--vcpus", "4"]
140     virtualbox.customize ["modifyvm", :id, "--vramsize", "3330"]
141   end
142
143   client.vm.provision "client_dummy",
144     type: "shell",
145     preswrv_order: true,
146     path: "provision/client/01-dummy.sh"
147
148   client.vm.provision "client_routing",
149     type: "shell",
150     preswrv_order: true,
151     path: "provision/client/01-routing.sh"
152
153   client.vm.provision "client_mail",
154     type: "shell",
155     preswrv_order: true,
156     path: "provision/client/mail.sh"
157
158   client.vm.provision "client_ssh",
159     type: "shell",
160     preswrv_order: true,
161     path: "provision/client/ssh.sh"
162
163   client.vm.provision "client_sftp",
164     type: "shell",
165     preswrv_order: true,
166     path: "provision/client/sfs.sh"
167
168   client.vm.provision "ssh client",
169     type: "shell",
170     preswrv_order: true,
171     path: "provision/client/smb.sh"
172 end

```

Рис. 27: Обновленный Vagrantfile

В результате выполнения лабораторной работы были получены навыки настройки и использования Samba