

# Alabama Roads Project

## Background

This is a ‘proof of concept’ exercise that will attempt to predict road safety using the Google streetview api and a retrained (transfer learning based) version of Tensorflow to enable mass prediction of road safety on large datasets. The ultimate output would be a heat map/scoring of predicted road safety across Alabama.

## Take streetview photos

### Import roads

To do this we will use the road shapefile in the raw project data folder

~/Dropbox/pkg.data/alabama\_roads/raw/us82erik/us82\_dissolve. If you do not currently have access to the folder, you can download the folder by going to this Dropbox web link. Ideally, you should be able to dynamically link locally by using Dropbox desktop...r

To build the streetview folders, the first step is to discretize the road shapefile and then use the google streetview metadata api to get locations of nearest google streetview picture (henceforth called pano\_id). In this case the picture will be manually tuned to have the car driving in the ‘correct’ direction. In the future, this can easily be done with tensorflow as well, by simply ensuring that the photo taken is on the right (not the left) side of the road. Again, this can be easily automated in tensorflow in the future for bigger data applications.

```
if (!(file.exists(roads.clean.location))) {
  roads <- rgdal::readOGR(dsn = path.expand(roads.raw.location),
    layer = "us82d", verbose = FALSE)
  roads <- sp::spTransform(roads, CRSobj = CRS(proj.env))
  saveRDS(roads, file = roads.clean.location)
} else {
  roads <- readRDS(roads.clean.location)
}
# Plot
map.center <- as.numeric(geosphere::centroid(rgeos::gBuffer(roads,
  width = 0.1)))
```

```
## Warning in rgeos::gBuffer(roads, width = 0.1): Spatial object is not
## projected; GEOS expects planar coordinates
```

```
map <- ggmap::get_googlemap(center = c(lon = map.center[1],
  lat = map.center[2]), zoom = 7)
```

```
## Map from URL : http://maps.googleapis.com/maps/api/staticmap?center=32.890998,-87.106853&zoom=7&size=
```

```
roads_fortify <- ggplot2::fortify(roads)
p <- ggmap(map) + geom_line(data = roads_fortify,
  aes(x = long, y = lat, group = group))
print(p)
```



## Roads Discretize to points

This discretizes the roads into points creates the points to find the panoids. The goal of the road discretization is solely to build a set of points with which to find the nearest pano\_id.

```
if (!(file.exists(road.points.location))) {
  road.points <- suppressWarnings(sample.line(roads,
    sdist = 0.0075))
  road.points$long <- road.points@coords[, 1]
  road.points$lat <- road.points@coords[, 2]
  saveRDS(road.points, file = road.points.location)
} else {
  road.points <- readRDS(road.points.location)
}
knitr::kable(head(road.points@data))
```

ID	long	lat
1	-87.84014	33.28436
2	-87.84006	33.28435
3	-87.83999	33.28434
4	-87.83991	33.28434
5	-87.83984	33.28433
6	-87.83976	33.28433

## Pano\_ids and meta data

### Points to panoids

This can be automated in the future to adjust the sdist parameter in the road.points chunk to optimally collect all panoids while minimizing the number of repeats samples. This will speed up the meta\_data api calls. For now we will just fill in the data data with the 24529 road points that we have sampled. Two camera bearings are assigned for each panoid. This is based on aiming the camera at the previous and next pano\_id. Order is based on the roads.points file and retained in the field dt\_pano\_ids\$pano\_id\_order.

```
if (!(file.exists(panoids.location))) {
  points.ids.full <- road.points$ID
  points.files <- list.files(road.points.panoid.location)
  points.ids.done <- sapply(points.files, function(x) stringr::str_extract(x,
    stringr::regex("(?<=id\\:).+(?=\\;)",
      perl = TRUE)))
  points.ids.not.done <- points.ids.full[!(points.ids.full %in%
    points.ids.done)]

  while (length(points.ids.not.done) > 0) {
    if (length(points.ids.not.done) > 1) {
      points.ids <- sample(points.ids.not.done,
        10)
    } else {
      points.ids <- points.ids.not.done
    }
    cat("Assigning", length(points.ids), "points to panoids.",
      length(points.ids.not.done), "remain \n")
    l.panoids <- lapply(points.ids, function(x) streetview.metadata(data.table::as.data.table(road.
      x), ), api_key = api.key, save.location = road.points.panoid.location))
    points.files <- list.files(road.points.panoid.location)
    points.ids.done <- sapply(points.files,
      function(x) stringr::str_extract(x,
        stringr::regex("(?<=id\\:).+(?=\\;)",
          perl = TRUE)))
    points.ids.not.done <- points.ids.full[!(points.ids.full %in%
      points.ids.done)]
  }

  # Combine all ponoids into a data.table
  files.to.load <- points.files <- list.files(road.points.panoid.location,
    full.names = TRUE)
  dt.file <- readRDS(files.to.load[1])
  for (iLoad in 2:length(files.to.load)) {
    f.to.load <- files.to.load[iLoad]
    f <- readRDS(f.to.load)
    l.file <- list(dt.file, f)
    dt.file <- rbindlFist(l.file, use.names = TRUE,
      fill = TRUE)
  }
  dt_pano_ids <- dt.file
  # Unique record for each pano Id and retain
  # order from roads.point
  dt_pano_ids$roads.point.id <- as.integer(dt_pano_ids$roads.point.id)
```

```

setkey(dt_pano_ids, roads.point.id)
# Find unique panoids
dt_pano_ids[, `:=`(pano_id_order, .GRP), by = pano_id]
dt_pano_ids <- unique(dt_pano_ids[, .(date,
  location.lat, location.lng, pano_id, pano_id_order,
  status)])
dt_pano_ids$location.lng <- as.numeric(dt_pano_ids$location.lng)
dt_pano_ids$location.lat <- as.numeric(dt_pano_ids$location.lat)
setkey(dt_pano_ids, pano_id_order)
# Get bearings for pictures (ahead and behind)
# (Simply aim at panoids in front and behind.)
dt_pano_ids$lat.lead <- data.table::shift(dt_pano_ids$location.lat,
  1, type = "lead")
dt_pano_ids$lng.lead <- data.table::shift(dt_pano_ids$location.lng,
  1, type = "lead")
dt_pano_ids$lat.lag <- data.table::shift(dt_pano_ids$location.lat,
  1, type = "lag")
dt_pano_ids$lng.lag <- data.table::shift(dt_pano_ids$location.lng,
  1, type = "lag")
dt_pano_ids <- na.omit(dt_pano_ids)
dt_pano_ids$bearings.lead <- sapply(1:nrow(dt_pano_ids),
  function(x) geosphere::bearing(c(dt_pano_ids[x,
    location.lng], dt_pano_ids[x, location.lat]),
    c(dt_pano_ids[x, lng.lead], dt_pano_ids[x,
    lat.lead])))
dt_pano_ids$bearings.lag <- sapply(1:nrow(dt_pano_ids),
  function(x) geosphere::bearing(c(dt_pano_ids[x,
    location.lng], dt_pano_ids[x, location.lat]),
    c(dt_pano_ids[x, lng.lag], dt_pano_ids[x,
    lat.lag])))
saveRDS(dt_pano_ids, file = panoids.location)
} else {
  dt_pano_ids <- readRDS(panoids.location)
}
knitr::kable(head(dt_pano_ids[, .(date, pano_id,
  pano_order = pano_id_order, lat = location.lat,
  lng = location.lng, bear.lead = bearings.lead,
  bear.lag = bearings.lag)]))

```

date	pano_id	pano_order	lat	lng	bear.lead	bear.lag
2016-05	lk4vKW941erchBtIeRqenA	2	33.28436	-87.84009	92.64210	-87.35684
2016-05	8sR6h5ILqzn3NSvXhYhP_g	3	33.28435	-87.84000	100.73244	-87.35785
2016-05	5YeX5au5BuKvr-VE8mnHYg	4	33.28434	-87.83991	98.83936	-79.26751
2016-05	7ixd4IHZEO1aUZSMVo_OcQ	5	33.28433	-87.83982	97.23829	-81.16059
2016-05	LMB6s5_qe2463PujYfHafw	6	33.28432	-87.83973	97.02418	-82.76167
2016-05	6TTjtyYJ1NmTOpE0T-_Yzg	7	33.28431	-87.83964	96.80426	-82.97577
There are	20104 in this data set.					

Pano\_ids and camera direction

Snap street view picture

Tensorflow