




GENERAL NOTES UNLESS OTHERWISE NOTED:

- REFERENCE 3UFRAME.SLDPRT FOR MODEL BASE DEF
- BREAK ALL EDGES
- 3. MATERIAL: ALUMINUM 6061-T6
- ANODIZATION: TYPE II, BLACK
- TOLERANCE UNDIMENSIONED RADII TO ± 0.5
- OVERALL PROFILE TOLERANCE 0.1 A B C TO A MINIMUM GRID OF 5MM UNLESS OTHERWISE SPECIFIED
- 7. INTERNAL CORNERS RADIUS IS 0.2MM MAXIMUM
- ENGRAVE ALL TEXT WITH 90 DEG V BIT WITH DEPTH OF 0.2MM BEFORE ANODIZATION



| REVISIONS | | | | | | | | | | |
|-----------|------|--|-----------|------------|--|--|--|--|--|--|
| ZONE | REV. | DESCRIPTION | DATE | DRAWN BY | | | | | | |
| | Α | INITIAL COMMIT | 7/07/2021 | MARVIN LIN | | | | | | |
| | В | REVISED FOR CLARITY AND TO MEET ASME Y14.5 | 7/27/2021 | MARVIN LIN | | | | | | |
| | С | FURTHER CLARITY REVISIONS | 8/15/2021 | MARVIN LIN | | | | | | |
| | D | added anodization notes | 9/18/2021 | MARVIN LIN | | | | | | |
| | E | FIXED DRAWING ERRORS | 9/26/2021 | MARVIN LIN | | | | | | |





| | UNLESS OTHERWISE SPECIFIED | DRAWN BY | N | MARVIN LIN | 9/26/ | 2021 | 21 | |
|----------------------|---|--|------------|------------|--------|----------|------|--|
| | DECIMAL ANGULAR | CHECKED | | | 9/26/ | 2021 | | |
| | .X ± 0.1 .X ± 0.1 .XX ± 0.01 .XX ± 0.01 .XXX ± 0.005 SURFACE ROUGHNESS: INTERPRET PER ASME Y14.5-2009 | ENG APPR. | | | | JF | 5A5 | |
| MATERIAL (SEE NOTES) | | MFG APPR. | | | | | | |
| FINISH (SEE NOTES) | | Y | Y 3U Frame | | | DWG. NO. | | |
| WEIGHT (REF) | | ф П | UNITS | REVISION | FORMAT | SCALE | PAGE | |
| WEIGHT (RELY | DO NOT SCALE DRAWING | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | MM | E | В | 1:2 | 1/5 | |

