Receipt Assisted Feedback and Authenticated Policy Transfer for Wireless Sensor Routing

Shivam Bhardwaj[1]*, Dr. Abhishek Kumar Pandey[2] and Dr. Abhinandan Tripathi[3]

[1] Assistant Professor, Department of Computer Applications (MCA), United Institute of Management, Prayagraj, Uttar Pradesh, India

[2] Department of Computer Science and Engineering, Bennett University, Greater Noida, India

[3] Department of Computer Science and Engineering, Buddha Institute of Technology, Gorakhpur, India

*Corresponding author: shibambhardwaj@gmail.com; ORCID: 0009-0005-4554-7397
Abhishek Kumar Pandey: abhishek.pandey2@bennett.edu.in; ORCID: 0000-0003-3799-9754
Abhinandan Tripathi: abhinandan282@bit.ac.in

Abstract

Routing feedback consumes radio capacity and may confuse missing evidence with forwarding failure. We evaluate receipt assisted feedback and a separate authenticated transport for frozen sensor-routing policies. The first experiment fixes the feedback ledger before 750 IEEE 802.15.4 simulation runs on 30 new fixtures, with active proof, naive passive, frozen prior and capacity matched policy controls. Under blackholes, delivery increases from 71.28% to 75.94% relative to active proofs, a paired gain of 4.67 percentage points (95% interval 2.36–6.97; Holm adjusted p=0.0161). Energy per delivered byte improves while total modeled radio energy increases slightly. A second protocol evaluates attention, multilayer perceptron and greedy routing in 180 runs using byte-serialized neighbor state, hop authentication, replay protection and signed sink receipts. Attention delivery is 81.61% in benign conditions and 61.11% with selective dropping; paired comparisons establish no superiority over the controls. Four virtual serial devices also exercise the host radio adapter and reveal a receive-time freshness bug, which is corrected. The corrected integration delivers all ten offered packets in that functional fixture. A separate four-board Cortex-M3 emulator executes compiled radio-interface firmware; all three host-policy controls deliver ten of ten packets. These results provide traceable feedback and implementation evidence while exposing transfer and attribution limits. Virtual serial interfaces and modeled radio energy do not establish physical board operation, measured energy consumption or absolute deadline compliance.

Keywords: Wireless sensor networks; Routing feedback; Authentication; Policy transfer; Reproducibility; Virtual validation

1. Introduction

Multihop sensor routing relies on link estimates, path progress and control messages, as illustrated by RPL, expected transmission count and the Collection Tree Protocol [1, 2, 3]. Adding security evidence creates another dependency: an extra acknowledgment may increase confidence in one hop while occupying airtime needed by another packet. A mechanism should therefore be judged jointly by what it observes and what it sends.

Passive watchdog monitoring and explicit acknowledgment schemes have addressed forwarding misbehavior for decades [4, 5]. Overhearing establishes that a relay attempted transmission; it does not establish reception by the intended next hop. Conversely, silence can result from an unsuccessful first link, contention or missed reception. Treating every silence as a malicious action can change routing

even in an attack free network. The present study examines that observation ambiguity without introducing an intrusion classifier.

Recent work links trust to edge assisted routing [6], optimizer based next hop selection [7], learned trust estimation [8], failure aware deep Q learning [9] and opportunistic forwarder selection [10]. Trust gated reinforcement learning [11] and secure deep reinforcement learning [12] further demonstrate current interest in the interaction between security and routing. Table 1 maps their stated mechanisms to this study. Their reported performance values are not used as directly comparable baselines because the channels, workloads and attack models differ.

Our initial architecture studies did not establish joint superiority over a capacity matched multilayer perceptron. A subsequent 600-run radio telemetry study also found no corrected architecture advantage and exposed a cost of the active proof mechanism. These negative stages motivated one feedback redesign; they remain available with their raw outputs. The new experiment asks a narrower question: can a receipt assisted passive mechanism replace active proofs without materially degrading a frozen prior control on a new fixture set?

1.1 Contribution and research questions

The contribution is an auditable feedback-mechanism comparison: first-hop acknowledgment gates evidence, a record retains the strongest observation rather than every duplicate, and missing observations remain censored. The implementation connects these rules to actual packet reception callbacks. It does not claim to invent watchdog monitoring, censoring, attention or reinforcement learning. Figure 1 separates radio events from simulator-held state, and Fig. 2 shows the event logic.

Three questions organize the evaluation. RQ1 asks whether the replacement improves blackhole delivery relative to active proofs under the frozen multiple-testing rule. RQ2 asks whether it remains within prespecified delivery, critical-service and energy-efficiency margins against frozen-prior attention. RQ3 asks whether the naive passive and capacity matched controls support attribution to censoring or architecture. These questions distinguish a useful replacement from a unique algorithmic advantage.

A separate implementation stage asks whether the same frozen policies can operate on authenticated wire state and node-local transit service. It evaluates 180 new radio runs and a virtual serial-interface fixture without transferring the earlier performance claim to the new transport. Sections 2–4 describe the frozen feedback benchmark; Section 5 defines and evaluates the authenticated branch.

2. System model and methods

2.1 Radio traffic and threat model

The network contains 100 stationary sensors and one sink at (75, 75) m in a 150 × 150 m field. The ns-3.44 low-rate wireless personal area network model supplies unslotted medium access, acknowledgments and packet-level reception [13]. Log-distance loss uses exponent 3 and reference loss 40 dB; the weak-link condition uses 54 dB. A separate 50 m range limit is retained. This is a radio simulation, not a measurement of an operational sensor deployment.

Each run lasts 4 s and offers 60 source packets after a 0.4 s warm-up. Source intervals are 20 ms, or 2 ms for the congested burst. Traffic classes occur with probabilities 0.35, 0.45 and 0.20 and deadlines of 90, 350 and 1,500 ms. A 64-byte application frame contains 12 identifier bytes and 52 payload bytes; lower-layer overhead is additional. Periodic application-level telemetry broadcasts are termed beacons here; they are not IEEE superframe beacons. They occur every 0.5 s with a 3 ms node offset. Table 2 records the common settings.

In blackhole settings, 25% of sensor identities are selected independently for each fixture. A faulty relay accepts a packet but does not invoke its forwarding decision. It continues to produce the modeled beacon and receipt behavior; forged control values, collusion and compromised sink behavior are outside the threat model. Fault labels control the simulator and evaluation only. The policy receives forwarding observations rather than node attack labels.

2.2 State construction and frozen routing policy

A received beacon admits an observer-specific cache entry with energy fraction, pending-request pressure, timestamp and link-quality indication. An entry expires after 0.75 s. Candidate construction excludes the current node, previously visited nodes, exhausted nodes and nodes beyond 50 m. At most eight candidates are retained using the fixed preselection score

$$S_{uv} = 1.25\, g_{uv} + 0.75\, q_{uv} + 0.25\, e_v - 0.55\, R_{uv} - 0.20\, Q_v \tag{1}$$

• g is sinkward progress divided by 50 m; q is estimated MAC success probability; both are dimensionless.

• e is remaining modeled energy divided by 0.5 J, Q is pending-request pressure normalized by 32, and R is the evidence-risk upper proxy; all are dimensionless.

The complete observation has 13 context values and eight ten-value candidate rows. Context includes local energy and queue state, normalized sink distance, remaining deadline, class indicators and six source-service debts. Each candidate row contains a sink indicator, energy fraction, estimated MAC success, received link quality, queue pressure, sinkward progress, evidence risk and uncertainty, expected retries, and normalized link delay. The training RSSI proxy is replaced by received link-quality indication during radio transfer; this feature shift is retained rather than learned away.

Separate shared encoders transform context x and candidate h into 96-dimensional vectors. Query-to-candidate scoring and a shared bias produce the logit

$$\ell_{uv} = \frac{q_\theta(x_u)^T k_\theta(h_{uv})}{\sqrt{96}} + b_\theta(huv) \tag{2}$$

• ℓ is a dimensionless action logit; x and h are the context and candidate feature vectors.

• qθ and kθ are learned query/key transforms and bθ is a learned candidate bias; θ is fixed throughout transfer.

Masked argmax selects the relay. Candidate encoding is shared and the critic uses masked mean pooling, following the set-function motivation in [14]. Attention has 63,368 parameters. The capacity matched perceptron has 63,554 parameters and a 203-unit hidden width. Candidate order is score ranked, and equal scores use the configured identity tie break. Consequently, the implementation supports shared candidate scoring but does not prove invariance of the entire routing pipeline to every node relabeling.

Both checkpoint families were trained on seeds 41001–41030 for 400 episodes per seed using eight updates of 50 episodes and three full-batch PPO epochs per update. Learning rate is 0.0003, clipping 0.2, discount 0.99, generalized-advantage factor 0.95 and entropy coefficient 0.01 [15, 16]. Six cost channels penalize class-specific deadline violation and loss. Lagrange multipliers update at rate 0.03 with clipping to [0, 50]. This finite-budget Lagrangian training is not the algorithmic guarantee of constrained policy optimization [17]. No checkpoint or threshold is retuned on the new radio fixtures.

2.3 Receipt assisted censored evidence

Each observer u stores a record for selected relay v and packet p. The record contains its expected first-link success, acknowledgment status, expiry, strongest seen evidence and credited strength. A

successfully received overheard data frame supplies strength 0.5. A reverse receipt originating from sink delivery supplies strength 1. The maximum rule prevents repeated receptions from accumulating arbitrary strength:

$$s_{uvp} \leftarrow \max\{s_{uvp},\ 0.5\, I_{overheard}, I_{receipt}\} \tag{3}$$

• s is the strongest evidence strength, dimensionless and bounded by 1.

• I_overheard and I_receipt indicate matched received forwarding frames and reverse receipts, respectively; they are dimensionless binary observations.

Credit is eligible only after the observer obtains a successful MAC acknowledgment for its own data request and the new strength exceeds the amount previously credited. An early observation waits for that acknowledgment. The implemented positive update is

$$\alpha_{uv} \leftarrow \alpha_{uv} + \ clip\left(q_{uv} \max\{0, s_{uvp} - c_{uvp}\},\ 0.05,\ 1\right), c_{uvp} \leftarrow s_{uvp} \tag{4}$$

• α is a dimensionless effective success count, initialized to 1; c is the credited record strength, initialized to 0.

• q is the dimensionless link-success estimate at registration. The clipping floor applies to each positive increment, not to their sum.

The effective failure count β stays at its prior of 1 in the censored arm. A failed first hop closes the record without positive credit. An acknowledged record with no observed forwarding evidence expires after 150 ms without a failure increment. A late receipt may still upgrade an acknowledged censored record. Near q<0.1, separate half credits interact with the clipping floor and can exceed one full q-weighted increment. The audited decision histories have minimum q=0.6923, so that edge case is outside the observed runs; a calibrated posterior interpretation is nevertheless inappropriate.

The existing risk coordinates are retained as evidence preferences. With the rate-anomaly term inactive, the mean and upper proxy are

$$\rho_{uv} = 0.75\left(1 - \frac{\alpha_{uv}}{\alpha_{uv} + \beta_{uv}}\right), R_{uv} = clip\left(\rho_{uv} + 1.645 \times 0.75\sigma_{uv},\ 0,\ 1\right) \tag{5}$$

• ρ and R are dimensionless risk coordinates.

• σ is the beta-form standard deviation sqrt[αβ / ((α+β)²(α+β+1))], used as a dimensionless uncertainty proxy rather than a calibrated maliciousness interval.

The naive passive control receives identical observations and deduplicates them, but penalizes missing acknowledged forwarding at expiry. The active control uses separate proof packets and its earlier timeout convention; it can credit a proof without applying the passive first-hop ACK gate. Frozen prior preserves the same initial risk coordinates but disables updates. Capacity matched MLP uses the censored ledger. Table 3 makes these differences explicit. Active versus censored therefore compares complete feedback mechanisms, including semantics and traffic, rather than isolating airtime alone.

2.4 Source service state and simulator boundaries

Per-class service debt follows the virtual-queue form motivated by long-run constraint tracking [18]:

$$Z_c \leftarrow \max\{0, Z_c + I_{violation} - b_c\} \tag{6}$$

• Zc is a dimensionless source-service debt and bc is the allowed violation fraction for class c.

• I_violation is 1 for a missing or late delivered packet and 0 otherwise; loss has a separate analogous channel.

In this radio transfer, only the source updates those debts after receipt or a 1.5 s expiry. Intermediate nodes do not update a complete service debt for their transit packets. A shared per-packet visited set

prevents loops, and a simulator reverse-path map routes receipts. Their state dissemination is not serialized. Beacon energy and queue values likewise use a simulator metadata sidecar keyed to the transmitted identifier; an actual radio receive callback gates availability, but the values are not decoded from wire fields. Figure 1 marks this boundary explicitly. It is a controlled transfer of routing decisions, not an embedded distributed protocol implementation.

Algorithm 1 specifies the tested observer logic. Its event sequence appears in Fig. 2. Simulated radio callback controls check an actual two-hop forwarding observation, silence at an out-of-range observer and zero proof frames in the passive configuration. These checks establish callback behavior; they do not establish authentication or intrusion-detection accuracy.

3. Experimental design

3.1 Development separation and untouched fixtures

Figure 3 accounts for the evidence stages using a PRISMA-inspired staged layout; it is experimental accounting, not a systematic-review selection diagram. The earlier 76001–76030 telemetry fixtures informed the redesign. Protocol, source and the decision rule were published at commit 4027f071322cb5682f39329f656d76df3b68ff62 before evaluation of fixtures 77001–77030. Technical pilot 76901 is excluded from inference. Each new fixture pairs the unchanged attention/MLP checkpoints from 41001 plus its fixture offset.

Five feedback/policy arms cross five settings and 30 fixtures: 750 runs and 45,000 source packets. All runs are retained. Each fixture shares topology, offered packets, traffic classes and blackhole identities across arms. Protocol-induced event schedules can diverge, so identical seeds do not imply identical per-event radio draws. The unit of inference is the complete paired fixture and checkpoint, not individual packets or repeated training of the same network trace. Geometry remains drawn from one stationary placement family with a central sink.

3.2 Endpoints and radio accounting

The primary routing summaries count sink reception against all offered source packets. Delivery fraction is

$$D = \frac{N_{delivered}}{60} \tag{7}$$

• D is dimensionless; Ndelivered counts distinct packet identifiers received by the sink during the 4 s horizon.

For critical class 0, non-delivery counts as a violation, as does delivery beyond 90 ms:

$$V = \frac{\sum_{p \in C_0} I[\, p \ \ missing \ \vee delay_p > \ 0.09 \ \ s\,]}{|C_0|} \tag{8}$$

• V is a dimensionless violation fraction and C0 is the set of offered critical-class packets.

• delayp is sink reception time minus source generation time, in seconds.

Custom PHY-state integration charges every sensor’s transmit, receive/listen and off intervals, including control traffic and retries. The sink is recorded separately and excluded from the sensor numerator. The assumed 3 V current model gives

$$E = 3 \sum_{u \in sensors} \left(0.0174\, T_{u,TX} + 0.0188\, T_{u,RX/listen} + 0.000020\, T_{u,off}\right) \quad (9)$$

• E is modeled sensor radio energy in joules; residence times T are in seconds and coefficients are amperes.

• The supply is 3 V. Currents are explicit assumptions, not calibrated measurements; CPU, sensing and cryptography are excluded.

Energy efficiency divides this common-horizon expenditure by delivered application payload bytes:

$$\eta = \frac{E}{52\, N_{delivered}} \quad (10)$$

• η is radio joules per delivered payload byte; 52 is payload bytes per packet.

• A lower η can result from a larger delivered-byte denominator even if total E does not decrease.

3.3 Statistical analysis and frozen gate

For each endpoint and comparator, the paired difference is computed once per fixture and summarized across 30 fixtures. Two-sided 95% Student t intervals are unadjusted descriptive intervals. The prespecified 60-test Holm family combines five settings, four comparators and three endpoints [19]. Mean delivery and violation differences are reported in percentage points; energy-efficiency differences use J/byte. The family is not reduced after inspection of results.

All four frozen gate checks are required: a positive blackhole delivery difference versus active proofs with Holm $p<0.05$; a one-sided 95% delivery lower bound above −1 point versus frozen prior; a critical-violation upper bound below +1 point; and an energy-efficiency geometric-ratio upper bound below 1.02. Table 5 reports each check. These margins define an incremental replacement criterion. They do not replace the original absolute class-0 deadline-violation budget of 1.5%.

4. Results

4.1 Delivery and matched controls

Under blackholes, censored passive attention delivered 75.94% of offered packets, compared with 71.28% for active proofs. The paired difference was +4.67 percentage points, with 95% CI [2.36, 6.97] and Holm p=0.0161. Figure 4 shows setting-level intervals, while Fig. 5 retains every paired fixture and all blackhole comparator contrasts. No other setting's delivery contrast against active proofs survived the 60-test correction. The effect therefore belongs to the specified blackhole condition rather than to all tested traffic regimes.

Table 4 reports the full blackhole endpoint contrasts. Censored minus naive passive delivery was −0.17 points, and censored minus frozen prior was +0.06 points; neither contrast was significant after correction. The capacity matched MLP contrast was +0.44 points and also inconclusive. These controls rule out a claim that the observed replacement gain establishes a unique benefit from censoring, evidence updating or attention. They do not prove equivalence outside the declared margins.

4.2 Energy efficiency and control traffic

Blackhole energy per delivered payload byte decreased by 0.0006443 J/byte relative to active proofs, with 95% CI [−0.0009740, −0.0003145] and Holm p=0.0239. Total sensor radio energy instead rose from 22.546943 to 22.547473 J. This small descriptive increase, 0.000531 J, must not be reported as energy saving. The receive/listen state accounts for a mean 99.36% of modeled sensor radio energy across all 750 runs.

Figure 6 separates the absolute energy numerator, delivered-byte efficiency and PHY transmission count. In blackhole settings, censored passive generated 60.57 fewer PHY transmissions per run on average than active proofs. Every passive/frozen arm requested zero forwarding proofs, while the active arm requested 3,369 across 150 runs. Beacons and existing reverse receipts remain in every arm. Because assumed receive/listen current exceeds transmit current, fewer transmitted frames need not reduce common-horizon joules in this always-listening model. Higher delivery explains the favorable energy-per-byte ratio.

4.3 Gate outcome and service limits

The three blackhole frozen-prior margins passed: the one-sided delivery lower bound was −0.405 percentage points, the critical-violation upper bound +0.925 points, and the geometric energy-efficiency ratio upper bound 1.00505. Together with the corrected active-proof delivery contrast, all four gate checks passed (Table 5). The upper critical bound is close to its +1-point margin, so the result should be read at its declared threshold rather than as a large safety reserve.

The critical-violation decrease against active proofs did not survive multiple-testing correction. Absolute critical violations for censored passive remain approximately 26.2% under blackholes, far above the original 1.5% budget. Passing the replacement gate therefore establishes neither absolute deadline compliance nor a guaranteed quality-of-service controller.

4.4 Implementation and trace audit

The action/ledger verifier passed 67,522 decisions, 24,747 passive observations, 28,353 evidence updates and 75,750 node-energy identities. An additional endpoint audit reconstructed all 750 final delivery and critical-violation values from source decision times and sink reception events, checked beacon and decision counts, and reconciled PHY-state energy. All 30 gzip streams read successfully to end of stream. The frozen-stage 51-test suite and radio callback control passed; the expanded implementation suite now contains 83 passing tests.

The trace of fixture 77004 was truncated during release-integrity checking and regenerated under the unchanged frozen implementation. All 750 canonical summary rows matched the pre-recovery summary exactly; no parameter, checkpoint or analysis rule changed. Audit code, provenance and the recovery record are distributed with the raw traces. This internal consistency check is not an independent radio implementation, external capture or a replay of every beacon-receive callback and service-state transition.

5. Authenticated transport and virtual validation

5.1 Local state and authenticated evidence

The transport in Fig. 7 is a separate implementation branch. It serializes coordinates, modeled remaining radio energy, queue state and transmit time into 58-byte application telemetry frames. Each node uses only its configured own and sink coordinates, its received authenticated cache, local MAC outcomes and packet-carried history. Pairwise HMAC-SHA256 with a 128-bit tag protects each hop [20]. Provisioned 64-bit boot sessions and a 64-entry replay window reject stale sessions and duplicates. Data binds immutable source fields with a source authenticator. The sink signs the source, session and packet identity using Ed25519 [21]; a signed receipt returns along node-local reverse records. Maximum application frame size is 114 bytes.

Passive third-party overhearing receives no authenticated forwarding credit in this branch because pairwise keys cannot verify another pair’s onward message. Local successful MAC acknowledgment and a verified sink receipt jointly enable positive forwarding credit. Missing receipts are censored. Node records are bounded at 128 entries with 2 s expiry. Keys and sessions are provisioned out of

band; protected key storage, online key exchange and truthful telemetry from a compromised key holder are not provided.

5.2 Frozen policy transfer protocol

The protocol and source were committed before observing the new outcomes (commit 5f06b9213e73206aad11ec8f3a96079a17011a20). Thirty independent topology seeds, 83001–83030, each pair one frozen attention checkpoint with its capacity matched multilayer perceptron checkpoint and a greedy progress control. A six-node diamond uses two first-hop alternatives and two downstream relays. Nominal coordinates are (0,0), (25,−15), (25,15), (50,−15), (50,15) and (75,0) m, with independent ±2 m jitter. Range is 38 m. Benign and selective-dropping conditions produce 180 runs. In the latter, relay 1 discards received data with an even packet identifier after MAC reception; this label is unavailable to the router.

Each 7.5 s run offers 60 packets with 16-byte payloads, beginning at 0.5 s at 75 ms intervals, with traffic class cycling through the three deadline classes. Authenticated unicast telemetry is attempted to every provisioned peer every 0.5 s with 2 ms staggering. Out-of-range requests and all modeled radio costs remain in the record. The three arms share strict distance-progress filtering and the eight-candidate limit. Greedy selects the shortest remaining sink distance; learned arms retain their original weights. Fixed ns-3 seeds and streams pair fixtures, although different actions consume different random sequences.

The 93-element observation comprises 13 context coordinates and eight ten-coordinate candidates. Neighbor geometry and energy come from decoded telemetry. MAC success uses a Beta(9,1) prior; acknowledgment delay uses an exponentially weighted estimate with coefficient 0.2 and a 5 ms initial value. Received LQI replaces the training RSSI proxy. Queue coordinates use raw MAC pending-request counts rather than the normalized pressure used during training. Forwarding risk is a positive-only transform of signed-receipt success counts and current link reliability. Each node tracks separate class delay and loss debts. These declared substitutions constitute distribution shift; the transfer does not reproduce the training observation model or establish calibrated intrusion probabilities.

5.3 Transfer results and audit

Table 6 and Fig. 8 report all 180 runs. Attention delivers 81.61% in benign conditions, compared with 82.72% for greedy and 83.72% for the multilayer perceptron. Its paired delivery differences are −1.11 points versus greedy (95% interval −3.39 to 0.83) and −2.11 points versus the perceptron (−4.50 to 0.28). Under selective dropping, attention delivers 61.11%, greedy 62.89% and the perceptron 60.50%; the attention differences are −1.78 points (−6.50 to 2.67) and +0.61 points (−2.56 to 3.78), respectively. Intervals use 10,000 paired percentile bootstrap samples across fixtures with seed 94001. These exploratory intervals are not multiplicity-adjusted superiority tests.

The transfer establishes execution with byte-serialized simulated radio frames and multiple candidate choices, but supplies no evidence of an attention advantage. Critical deadline failure remains 31.17% in benign attention runs and 47.83% under selective dropping, counting undelivered packets as failures. Total modeled radio energy is approximately 2.519 and 2.520 J per six-node run. Always-on listening and repeated authenticated control traffic limit energy differentiation; no embedded CPU or cryptographic energy is included.

The audit reconstructed 27,240 decisions, including 14,001 with multiple candidates, checked 88,538 received byte frames against prior transmissions, verified 46,204 public sink-signature occurrences and reconciled 1,080 radio-energy identities. It also matched candidate cache values to received beacon bytes and recomputed fixed-policy probabilities. Secret hop tags are checked by runtime nodes

rather than exported for public re-verification. The original 750-run traces, checkpoints and gate remain unchanged.

5.4 Virtual serial devices and firmware boundary

Four pseudo-terminal serial devices implement the board-facing TX, RX, MAC-confirm and telemetry contract while ns-3 transports the exact application bytes. Four independent host-adapter processes exercise the same serial interface intended for later board integration. The first diagnostic delivered five of ten packets and exposed false freshness rejections: the host sampled its clock before a blocking serial read. Sampling again after receipt corrected the defect. The corrected functional fixture delivers ten of ten packets, settles service at both intermediate relays and records no freshness rejection. Both captures are retained; this single fixture is not a reliability estimate.

The pseudo-terminal devices model the firmware API without MCU execution. Rechecks with greedy, multilayer perceptron and attention host policies each deliver ten of ten packets. A separate Renode 1.17.0 backend executes compiled C firmware on four emulated CC2538 ARM Cortex-M3 boards (Fig. 7). Firmware parses UART JSON, enforces frame bounds, drives the IEEE 802.15.4 radio FIFO and correlates MAC acknowledgments. Host processes retain routing inference and cryptography. All three controls deliver ten of ten packets and return ten verified source receipts each. Each run passes five probes: labeled uncalibrated telemetry, exact 114-byte delivery and acknowledgment, rejection of 115-byte frames, malformed-hex rejection and failed out-of-range transmission. The independent capture audit verifies received bytes against MCU UART output, public sink signatures and packet identities. Development captures are retained for startup synchronization and metadata corrections. A stricter later audit rejects an older greedy capture because its relay-1 final log is missing, despite its retained summary. New runs require all ten offered packet identities at the sink, ten runtime-accepted signed source receipts, complete source/relay final records, five successful probes and a public capture audit before receiving a pass status; all three new controls meet this gate.

Renode uses a deterministic range medium, not the ns-3 physical-layer model of the statistical study. Its energy fraction is a fixed placeholder explicitly labeled emulated_no_power_model; queue telemetry counts pending MCU acknowledgment records. No battery result follows from this fixture. The four-node chain provides one feasible next hop per relay, so successful execution does not compare policy quality or estimate reliability. Deadline debts remain nonzero. Compiled firmware execution is demonstrated only in emulation; physical clock and pin initialization, embedded policy/crypto execution, physical RF behavior and calibrated current measurements remain unvalidated.

6. Discussion

6.1 Critical vulnerabilities and limitations

The strongest supported result is a replacement of the tested active proof mechanism. Its comparator changes feedback eligibility and expiry conventions as well as radio traffic, so causation cannot be assigned solely to proof airtime. The naive and frozen-prior controls provide no corrected evidence for a unique censoring effect. The earlier unsuccessful architecture comparisons remain part of the evidence record.

State locality is incomplete in the frozen benchmark. Geometry, packet history and reverse receipt paths are simulator inputs; beacon values use receive-gated metadata. Source-only service debt does not establish transit-aware distributed queue control. In that frozen benchmark, forged receipts, deceptive telemetry, compromised sources, collusion and mobility are untested. Successful passive transmission is evidence of an attempt, not intended-receiver delivery, and the effective-count score is not a live intrusion detector.

The four-second horizon, common central sink and 60-packet burst do not establish steady-state scalability or network lifetime. Candidate scoring is linear in the bounded candidate count after cache sorting, but each expiration poll scans every retained watch. With W records, memory is O(W) and expiration is O(W) per millisecond poll. There is no long-horizon reclamation policy or measured embedded inference cost. Always-listening radio assumptions also exclude the cost of waking specifically to obtain evidence.

The passive strength 0.5, 150 ms expiry, 0.75 s cache life, current model and fixed inference checkpoints were not varied in the new holdout. Their sensitivity remains unknown. Deployment changes to state serialization, acknowledgment authentication, source-service tracking or ledger retirement must be assessed in a separate frozen experiment rather than inserted into this one after observing its outcome.

6.2 High novelty opportunities

A stronger next contribution would measure when evidence is worth acquiring. An adaptive observation policy could choose between silence, passive listening and authenticated probes using the expected reduction in delivery loss minus measured radio and processing cost. The discriminating experiment would match feedback semantics and data airtime, introduce duty cycling and adversarial receipts, and reserve new topology and hardware settings. This direction is not implemented in the present study; it follows from the attribution limits exposed here.

7. Conclusions

Receipt assisted passive feedback passed a prespecified incremental gate on 30 new simulation fixtures, improving blackhole delivery by 4.67 percentage points over active proofs. Matched controls did not establish a unique censoring or attention advantage. A separate authenticated transport executes frozen attention and capacity matched policies using received wire state and local service records. Its 180-run transfer study also establishes no attention superiority. Virtual serial devices expose and help correct a host receive-time defect. Together, these stages support a reproducible feedback comparison and an auditable implementation boundary. Compiled radio-interface firmware also executes on four emulated Cortex-M3 boards. Absolute service compliance, physical-board firmware operation, embedded policy/crypto execution and physical energy validation remain open.

Acknowledgments

No funding was received for this research. The authors declare no competing interests. This simulation and emulation study involved no human participants, clinical data or animal experiments.

Data and code availability: code, frozen protocol, checkpoints, historical negative outcomes, raw traces and figure sources are available at https://github.com/DrShivamBhardwaj/JICCE_LA_CPPO_Reproducibility. The pre-outcome source freeze is 4027f071322cb5682f39329f656d76df3b68ff62. The complete earlier evidence manuscript is retained in publication/censored_feedback/.

Declaration of generative AI use

ChatGPT assisted manuscript drafting, code preparation, analysis scripts and programmatic figure plotting. All numerical results reported here come from the retained executable experiments and traces. Responsibility for scientific verification, interpretation and final approval rests with the authors.

References

[1] T. Winter et al., “RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks,” IETF, RFC 6550, 2012. DOI: 10.17487/RFC6550.

[2] D. S. J. De Couto, D. Aguayo, J. Bicket, and R. Morris, “A high-throughput path metric for multi-hop wireless routing,” in Proceedings of MobiCom, pp. 134–146, 2003. DOI: 10.1145/938985.939000.

[3] O. Gnawali, R. Fonseca, K. Jamieson, D. Moss, and P. Levis, “Collection tree protocol,” in Proceedings of SenSys, pp. 1–14, 2009. DOI: 10.1145/1644038.1644040.

[4] S. Marti, T. J. Giuli, K. Lai, and M. Baker, “Mitigating routing misbehavior in mobile ad hoc networks,” in Proceedings of MobiCom, pp. 255–265, 2000. DOI: 10.1145/345910.345955.

[5] K. Liu, J. Deng, P. K. Varshney, and K. Balakrishnan, “An acknowledgment-based approach for the detection of routing misbehavior in MANETs,” IEEE Transactions on Mobile Computing, vol. 6, no. 5, pp. 536–550, 2007. DOI: 10.1109/TMC.2007.1036.

[6] A. Saleh, P. Joshi, R. S. Rathore, and S. S. Sengar, “Trust-aware routing mechanism through an edge node for IoT-enabled sensor networks,” Sensors, vol. 22, no. 20, Art. no. 7820, 2022. DOI: 10.3390/s22207820.

[7] N. Kumar and S. Sharma, “PathGuard: Trustworthy routing for sustainable and secure IoT-WSN networks,” Wireless Personal Communications, vol. 136, pp. 469–487, 2024. DOI: 10.1007/s11277-024-11289-8.

[8] P. Goswami, T. Khan, V. Pathak, and A. Alabdultif, “Machine learning based dynamic trust estimation framework for securing wireless sensor networks,” Scientific Reports, vol. 15, Art. no. 35821, 2025. DOI: 10.1038/s41598-025-19768-z.

[9] S. Tao, H. Tang, J. Wang, and B. Li, “A failure risk-aware multi-hop routing protocol in LPWANs using deep Q-network,” Sensors, vol. 25, no. 14, Art. no. 4416, 2025. DOI: 10.3390/s25144416.

[10] A. A. Lata and M. Kang, “RLFS-OR: Reinforcement learning-based forwarder selection for opportunistic routing in wireless sensor networks,” Electronics, vol. 15, no. 5, Art. no. 910, 2026. DOI: 10.3390/electronics15050910.

[11] R. Zheng, D. Yamkhin, J. Wei, H. Liu, and Z. Khurelbaatar, “Trust-gated reinforcement learning-based secure routing for wireless sensor networks,” Journal of Computational and Cognitive Engineering, online first, 2026. DOI: 10.47852/bonviewJCCE62029141.

[12] R. Gupta, S. K. Gupta, S. B. Singh, R. Kumar, and R. Muthukkumar, “Adaptive deep reinforcement learning–based secure routing for wireless sensor networks,” Scientific Reports, 2026. DOI: 10.1038/s41598-026-62519-x.

[13] ns-3 Project, “IEEE 802.15.4 low-rate wireless personal area network model,” ns-3 Model Library, release 3.44. Available: https://www.nsnam.org/docs/release/3.44/models/ns-3-model-library.pdf. Accessed October 16, 2026.

[14] M. Zaheer et al., “Deep sets,” in Advances in Neural Information Processing Systems, vol. 30, pp. 3391–3401, 2017. Available: https://papers.nips.cc/paper/6931-deep-sets.

[15] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, “Proximal policy optimization algorithms,” arXiv:1707.06347, 2017. DOI: 10.48550/arXiv.1707.06347.

[16] J. Schulman, P. Moritz, S. Levine, M. I. Jordan, and P. Abbeel, “High-dimensional continuous control using generalized advantage estimation,” in Proceedings of ICLR, 2016. Available: https://arxiv.org/abs/1506.02438.

[17] J. Achiam, D. Held, A. Tamar, and P. Abbeel, “Constrained policy optimization,” in Proceedings of ICML, vol. 70, pp. 22–31, 2017. Available: https://proceedings.mlr.press/v70/achiam17a.html.

[18] M. J. Neely, Stochastic Network Optimization with Application to Communication and Queueing Systems. Morgan and Claypool, 2010. DOI: 10.2200/S00271ED1V01Y201006CNT007.

[19] S. Holm, “A simple sequentially rejective multiple test procedure,” Scandinavian Journal of Statistics, vol. 6, no. 2, pp. 65–70, 1979. Available: https://www.jstor.org/stable/4615733.

[20] H. Krawczyk, M. Bellare, and R. Canetti, “HMAC: Keyed-hashing for message authentication,” IETF, RFC 2104, 1997. DOI: 10.17487/RFC2104.

[21] S. Josefsson and I. Liusvaara, “Edwards-curve digital signature algorithm (EdDSA),” IETF, RFC 8032, 2017. DOI: 10.17487/RFC8032.

Algorithm 1 Observer feedback and routing

Input: received MAC events, cached telemetry, fixed policy θ, ledger mode and 150 ms timeout.

Output: next-hop requests and updated observer evidence coordinates.

Steps:

1. At a routing event, reject a visited or exhausted node and enforce the 22-hop cap.
2. Construct receive-gated candidates, retain at most eight and evaluate the masked fixed policy.
3. Register the observer–relay–packet record with expected link success; send the data frame.
4. On own first-hop ACK success, mark the record eligible; credit any stored uncredited observation.
5. On ACK failure, close the passive record without success or failure credit.
6. On a matched received forward attempt, retain maximum strength 0.5.
7. On a matched received reverse delivery receipt, retain maximum strength 1.0.
8. Apply a positive update only if eligible and strength exceeds credited strength; deduplicate repeats.
9. At each 1 ms poll, close expired records; censor missing evidence in the proposed arm.
10. Allow a later receipt to upgrade an acknowledged censored record; keep failure count at its prior.
11. Update source service debt on receipt or service expiry; retain the frozen policy for later decisions.

Table 1. Literature and experimental focus

Study	Verified mechanism	Relation to this experiment
Watchdog [4]	Overheard forwarding attempts	Established passive observation; reception ambiguity remains
2ACK [5]	Reverse acknowledgment scheme	Explicit feedback adds traffic; no numerical cross-study ranking
TARM [6]	Edge assisted trust routing	Trust-aware routing context; different state and deployment
PathGuard [7]	Trust and optimizer next-hop selection	Publisher abstract verified; not independently replicated
SMART [8]	Learned multi-feature trust estimation	Detection task differs from forwarding evidence preference
FRDR [9] and RLFS-OR [10]	Failure-aware and opportunistic learning	Different radio and duty-cycle assumptions
TG-RL-SR [11] and secure DRL [12]	Trust gated and secure routing	Recent context; claims not treated as matched experimental effects
This study	ACK gated passive evidence; four controls	Frozen 30-fixture evaluation with retained negative stages

Table 2. Frozen network settings

Parameter	Value
Sensors and sink	100 sensors; one central sink
Field and range	150 × 150 m; 50 m hard range
Radio engine	ns-3.44; unslotted IEEE 802.15.4
Propagation	Log distance exponent 3; reference loss 40 or 54 dB
Run and offered load	4 s; 60 packets; 0.4 s warm-up
Source intervals	20 ms normal; 2 ms congested
Payload and identifiers	52 and 12 bytes; 64-byte application frame
Telemetry broadcast and cache	0.5 s period; 3 ms/node staggering; 0.75 s expiry
Feedback expiry and poll	150 ms; 1 ms
Traffic classes	Probabilities 0.35, 0.45, 0.20; deadlines 90, 350, 1,500 ms
Blackhole ratio	0 or 25%; non-forging forwarding faults
Assumed voltage and currents	3 V; TX 17.4 mA; RX/listen 18.8 mA; off 20 µA
Policy parameters	Attention 63,368; MLP 63,554; fixed weights
Holdout	30 fixtures × 5 settings × 5 arms = 750 runs

Table 3. Feedback controls

Arm	Evidence and expiry	Policy and interpretation
Active proofs	Separate proofs; legacy timeout and ACK eligibility	Attention; joint feedback and traffic comparator
Naive passive	Overhear/receipt positives; missing ACKed forwarding penalized	Attention; missing-observation control
Frozen prior	Same initial risk coordinates; no evidence updates	Attention; score-update control
Capacity MLP	Censored ledger with same radio observations	63554 parameters; representation control
Censored passive	Own ACK required; max-strength credit; missing evidence censored	63368-parameter attention; proposed replacement

Table 4. Blackhole paired effects

Comparator	Delivery points	Critical violation points	Energy mJ per byte
Active proofs	+4.667 [+2.365, +6.969] p=0.01612	-4.518 [-8.253, -0.783] p=1	-0.644 [-0.974, -0.315] p=0.02385
Naive passive	-0.167 [-1.557, +1.223] p=1	-0.017 [-2.381, +2.348] p=1	-0.066 [-0.416, +0.284] p=1
Frozen prior	+0.056 [-0.498, +0.609] p=1	-0.124 [-1.388, +1.139] p=1	-0.011 [-0.078, +0.057] p=1
Capacity MLP	+0.444 [-1.461, +2.350] p=1	-2.384 [-6.065, +1.298] p=1	-0.076 [-0.364, +0.212] p=1

Values are censored passive minus comparator; intervals are unadjusted paired 95% intervals. p values are Holm adjusted over the original 60 tests. Negative critical-violation and energy-per-byte differences favor censored passive. These are differences, not absolute arm means.

Table 5. Prespecified incremental gate

Check	Frozen criterion	Observed result
Delivery versus active proofs	Positive gain and Holm $p<0.05$	+4.667 points; p=0.0161; pass
Delivery versus frozen prior	One-sided lower bound >-1 point	−0.405 points; pass
Critical violations versus frozen prior	One-sided upper bound $<+1$ point	+0.925 points; pass
Energy efficiency versus frozen prior	One-sided geometric upper ratio <1.02	1.00505; pass
Joint incremental decision	All four checks required	Pass; absolute QoS compliance not established




Fig. 1. Frozen benchmark architecture.




Fig. 2. ACK-gated evidence lifecycle.




Fig. 3. Frozen evaluation stages.




Fig. 4. Delivery effects across settings.




Fig. 5. Blackhole observations and effects.




Fig. 6. Modeled radio-energy attribution.

Table 6. Authenticated policy transfer.

Condition / policy	Delivery (%)	Receipts (%)	Critical failure (%)	Radio energy (J)
Benign / greedy	82.72	79.22	31.17	2.5188
Benign / mlp	83.72	79.72	30.83	2.5189
Benign / attention	81.61	77.61	31.17	2.5189
Dropping / greedy	62.89	60.56	46.67	2.5204
Dropping / mlp	60.50	58.22	48.50	2.5206
Dropping / attention	61.11	58.17	47.83	2.5205

Means over 30 fixtures per condition and policy. Receipt rates count source-verified sink receipts. Critical failure includes undelivered critical packets. Energy covers modeled radio residence, not board or host CPU energy.




Fig. 7. Authenticated state and virtual interfaces.




Fig. 8. Frozen policy transfer and paired effects.