

# Removing Insiders' Trust from The Estonian Internet Voting System (IVXV)

Shymaa M. Arafat

Associate Professor (Independent, <https://github.com/DrShymaa2022>)

[shar.academic@gmail.com](mailto:shar.academic@gmail.com), [shymaa.arafat@gmail.com](mailto:shymaa.arafat@gmail.com)

OSCE/ODIHR in Feb 2025: “Political parties historically opposing e-voting currently have 4 main areas of concern”, the first 2 are

**E2EV & Protection against internal threats (insider attacks)** which was explained in their 2023 report as

**“An insider with sufficient resources to alter the system, if able to do so undetected, could manage to control which votes are removed and therefore partially impact the results”**

Consistency Checks:

=> We propose 2 alternative solutions

Verkle Trees:

Since both use the same timing service, PKIX, generalize what voters using eID can currently do as a double check for individual verifiability using the existing *myID* service:

Verify:

*Count (original votes file) =*

*Count\_Transactions (source=all, destination=IVXV, time=election\_interval)*

-The same could be repeated for checking the integrity of all votes. The verification process could be a simple **hash cascade**, a sophisticated **ZKP**, or even a comparison between sorted versions of the common fields between the two lists:

Verify:

*(original votes file) =*

*Transactions (source=all, destination=IVXV, time=election\_interval)*

-The first check could be instead accompanied by some kind of **Risk Limiting Audits (RLA)**s, where only a sample of random votes could be selected to check manually. Here, TXs stored in the Estonian information system will play the role of paper ballots to compare with IVXV data.

*for all  $i \in \text{sample}$*

*{  $n = \text{Count (original votes file, vote\_ID=i)}$ ;*

*Verify:*

*$n = \text{Count\_Transactions (source=i, destination=IVXV, time=election\_interval)}$ ;*

*for all  $j=1$  to  $n$  //in time order*

*Verify:*

*Original votes file(vote\_ID=i, order=j) =*

*Transaction((source=i, destination=IVXV);*

*}*

Cite as:

Shymaa M. Arafat, “Removing Insiders’ Trust from The Estonian Internet Voting System (IVXV)”, E-Vote-ID 2025, Track-4 Posters and Demos, 10<sup>th</sup> International Conference on Electronic Voting, 1-3 Oct 2025, Nancy France.


Although [3] has introduced integrity checks to remove trust in the Ballot Process, technically **IVXV trust assumption** admitted in [4] remains; *the Vote Collector (VC) and the Registration Service (RS) are not to collude together*. A recent paper [5/table1] that applied automated formal verification tools on IVXV has reached a similar result; the system fails to provide its goals (integrity and privacy) if 2 out of 3 colluded (VC, RS, and the timestamping service TMS). In this poster, we propose **two alternative solutions** for the Estonian System to eliminate insider attacks.

-**The first** is to use different queries and/or statistical techniques (like RLAs [6]) to *check the consistency of multiple sources of information that already exist in the Estonian government*; digital IDs activity logs where myID service [7] is an example.

-**The second** is to *aggregate votes online in an Authenticated Data Structure that cryptographically proves the number of values* stored in it (the number of votes in our case); we suggest the use of **Verkle Trees** [8] for their fast proof generation time as benchmarked (independently by someone else) in [9] to have **time ~ 1 second for  $n < 2^{22} \sim 4$  million**. (on Windows Intel i5-4690K, 22GB)

- OSCE/ODHIR, “Estonia Parliamentary Elections”, 5 Mar 2023, [https://osce.org/files/f/documents/f/f/551179\\_0.pdf](https://osce.org/files/f/documents/f/f/551179_0.pdf) (p.10/ft.22)
- OSCE/ODHIR, “Opinion on the Regulations of Internet Voting in Estonia”, 17 June 2025, <https://osce.org/files/f/documents/e/a/593435.pdf> (quoted part from sec.3/28)
- T. Treier and K. Duuna, “Identifying and Solving a Vulnerability in the Estonian Internet Voting Process: Subverting Ballot Integrity Without Detection”, IEEE Access, Vol.12, <https://ieeexplore.ieee.org/document/10811882>
- K. Snetkov, N. Vakarjuk, J. Willemson, “Trust Assumptions in Voting Systems”. In Computer Security. ESORICS 2023 International Workshops. Lecture Notes in Computer Science, vol 14399. Springer, Cham, [https://doi.org/10.1007/978-3-031-54129-2\\_18](https://doi.org/10.1007/978-3-031-54129-2_18); full paper at <https://arxiv.org/pdf/2309.10391>
- S. Baloglu, S. Bursuc, S. Mauw, and J. Pang, “Formal Verification and Solutions for Estonian E-Voting”, In ACM Asia Conference on Computer and Communications Security (ASIA CCS ’24), July 2024, Singapore, Singapore. ACM, New York, NY, USA, <https://doi.org/10.1145/3634737.3657009>
- Risk Limiting Audits (RLAs), “What is RLAs”, <https://verifiedvoting.org/audits/whatisrla/>; “RLAs Frequently Asked Questions” <https://www.sos.state.co.us/pubs/elections/RLA/faqs.html>
- <https://myid.skidsolutions.eu/en>
- Zero Knowledge Berkely MOOC 2023, lecture 5, “KZG polynomial commitment scheme”; <https://youtu.be/tAdLHQVWIUY>
- Jan Oberst, “Towards Stateless Clients in Ethereum: Benchmarking Verkle /trees and Binary Merkle Trees with SNARKs”, 18 April 2025, <https://arxiv.org/html/2504.14069v1>
- [https://github.com/DrShymaa2022/SoK\\_Estonia\\_IVXV\\_EVoteID/blob/main/Estonia\\_EVoteID\\_long.pdf](https://github.com/DrShymaa2022/SoK_Estonia_IVXV_EVoteID/blob/main/Estonia_EVoteID_long.pdf)
- M. Harrison and T. Haines, "On the Applicability of STARKs to Counted-as-Collected Verification in Existing Homomorphically E-Voting Systems", Mar 2024; [https://fc24.ifca.ai/voting/papers/Voting24\\_HH\\_On\\_the\\_Applicability\\_of\\_STARKs\\_to\\_Counted-as-Collected\\_Verification\\_in\\_Exisitng\\_Homomorphically\\_E-Voting\\_Systems.pdf](https://fc24.ifca.ai/voting/papers/Voting24_HH_On_the_Applicability_of_STARKs_to_Counted-as-Collected_Verification_in_Exisitng_Homomorphically_E-Voting_Systems.pdf)
- J. Müller, “Breaking and Fixing Vote Privacy of the Estonian E-Voting Protocol IVXV”, In: Matsuo, S., et al. Financial Cryptography and Data Security. FC 2022 International Workshops. FC 2022. LNCS(13412), [https://doi.org/10.1007/978-3-031-32415-4\\_22](https://doi.org/10.1007/978-3-031-32415-4_22)

-Verkle Tree, [8], is a vector data structure that authenticates its elements based on **KZG polynomial commitments** (as the polynomial coefficients, and their number reflects the polynomial degree) because they provide **cryptographic proof of the number of elements stored in them** (the number of votes in our case). Hence, we propose to aggregate all votes in a Verkle Tree (VT); every used Verkle Tree will add a line or 2 to the code **{VT=VT+H[i] \* committed\_vote; i++;}**, the vector **H** is calculated in the setup phase and **T** secrecy is critical  **$H_0 = G, H_1 = T \cdot G, H_2 = T^2 \cdot G, \dots, H_{p-1} = T^{(p-1)} \cdot G$**  (Time comparisons with Merkle + Plonk in [9], discussion on [10] for Verkle Trees vs. STARKs [11] or Merkle Trees. Finally, [12] suggested a ZKP to every vote in 2022 to defend vote privacy attacks by insiders.)



-The flowchart shows the steps, resulting into:

➤ Combined with [3,9/5.2], we may use **only one VT** to prove the number of recorded votes

▪ **Verify:  $n(VT\_1) = \text{count(votes list)}$**

**OR:**

▪ **Verify:  $n(VT\_1) = n(VT\_2) + n(VT\_3)$**

▪ **Verify:  $n(VT\_end) = n(VT\_2) - n(VT\_4 + VT\_5)$**

➤ **VT\_3 [i]** can prove the number and values of every deleted (multiple) vote for the sampled voters

➤ In the 2-levels VT\_3 case, QR codes can include the number of multiple votes for each voter.