

## Me:

This paper presents an opposing point of view to mine (<https://arxiv.org/html/2502.06385v2>)

Can I ask you a scientific question: How do you compare his words about voters downloading a malicious voting application:

*"All the following assumptions need to hold:*

- 1-the voter is successfully directed to an unofficial distribution channel,*
- 2-the voter does not verify authenticity of the voting application, and*
- 3-the voter does not report suspicious crash of the application.*

*For assumption 2, we need to take into account that under Windows and macOS the voting application is signed with a developer key and the OS verifies the signature before running it. It is possible for an attacker to register as a developer, but this will leave more traces. Linux users are supposed to verify the checksum of the application themselves, but on the other hand, Linux users are more likely to do it. For assumption 3, we note that in order to have a significant effect, the attacker needs to manipulate many votes. However, the probability that no crashes will be reported decreases exponentially fast in the number of crashes (see below for the computations)"*

-How do you compare this with my suggestion

([https://github.com/DrShymaa2022/E\\_Vote\\_ID\\_2025\\_posters/blob/main/EncryptedcopyattackPoster\\_7\\_9\\_25.pdf](https://github.com/DrShymaa2022/E_Vote_ID_2025_posters/blob/main/EncryptedcopyattackPoster_7_9_25.pdf), <https://eprint.iacr.org/2025/506>) of either allowing only pre-registered voting applications using signature keys, or adding a simple button for users to check the finger print or file digest of the voting application? I pointed out to the Electrum Bitcoin wallet as an example and how the many steps could be batched in 1 click?

Where the authenticity way they currently offer their users(voters {:

<https://www.valimised.ee/en/internet-voting/guidelines/voter-applications-and-checking-authenticity>

## Grok:

To compare the arguments presented in the paper with your suggestions

([https://github.com/DrShymaa2022/E\\_Vote\\_ID\\_2025\\_posters/blob/main/EncryptedcopyattackPoster\\_7\\_9\\_25.pdf](https://github.com/DrShymaa2022/E_Vote_ID_2025_posters/blob/main/EncryptedcopyattackPoster_7_9_25.pdf), <https://eprint.iacr.org/2025/506>) regarding the security of voter applications in the context of Estonia's IVXV i-voting system, let's break down the key points and evaluate them systematically.

### Paper's Perspective on Malicious Voting Applications

The paper outlines a scenario where a voter might download a malicious voting application, emphasizing three necessary conditions for such an attack to succeed: The voter is directed to an unofficial distribution channel.

The voter does not verify the authenticity of the voting application. The voter does not report suspicious crashes of the application.

\*The author argues that these conditions are difficult to meet simultaneously due to existing safeguards: On Windows and macOS, the voting application is signed with a developer key, and the operating system verifies this signature before execution. An attacker would need to register as a developer to sign a malicious application, which leaves a traceable footprint, deterring such attempts.

On Linux, users are expected to verify the application's checksum manually. The paper suggests Linux users are more likely to perform this verification due to their technical proficiency.

\*Crash reporting: For an attack to have a significant impact (e.g., manipulating many votes), it would likely cause multiple application crashes. The probability that no crashes are reported decreases exponentially as the number of crashes increases, making large-scale attacks less feasible without detection.

The paper concludes that these factors make it challenging for an attacker to distribute and execute a malicious voting application without being noticed.

## **Your Suggestions**

In your work, you propose two enhancements to improve the security and usability of verifying voter applications:

Pre-registered Voting Applications Using Signature Keys: You suggest restricting voting to applications pre-registered with signature keys, which would ensure only authorized applications can be used.

Simplified Authenticity Check with a Single-Click Button: You propose adding a button that allows users to verify the fingerprint or file digest of the voting application with a single click, streamlining the process. You cite the Electrum Bitcoin wallet as an example, where multiple verification steps are batched into a single action to enhance user experience while maintaining security.

You argue that these measures would reduce the risk of voters using malicious applications by making verification more accessible and less error-prone, particularly for non-technical users.

## **Comparison of the Two Approaches**

Let's compare the paper's perspective with your suggestions across key dimensions: security, usability, and practicality.

### **1. Security**

Paper's Approach: Relies on existing OS-level signature verification for Windows and macOS, which is robust but assumes users will notice warnings if an application lacks a valid signature. For Linux, it depends on users manually verifying checksums, which is secure but only effective if users consistently perform this step. The crash-reporting assumption adds a layer of detection, as widespread crashes would likely trigger user reports, exposing the attack.

Weakness: The system's security partially depends on user vigilance (e.g., noticing OS warnings or verifying checksums on Linux). Non-technical users may overlook these safeguards, increasing the risk of downloading malicious applications from unofficial sources.

Your Suggestions: Pre-registered applications: Requiring applications to be pre-registered with signature keys adds a strong layer of control, ensuring only trusted applications can interact with the voting system. This reduces the attack surface by eliminating the possibility of unofficial applications being used, even if signed by a rogue developer. Single-click verification: A button to check the fingerprint or file digest simplifies the process of confirming an application's authenticity. By automating and batching verification steps (as in the Electrum Bitcoin wallet example), you reduce the likelihood of users skipping verification due to complexity or lack of technical knowledge.

Strength: Your approach proactively mitigates the risk of users being misled by unofficial channels or failing to verify authenticity, addressing the paper's assumptions 1 and 2 directly. It also reduces reliance on user reporting (assumption 3) by preventing malicious applications from being installed in the first place.

## **2. Usability**

Paper's Approach: Windows and macOS users benefit from automatic signature verification, which requires no additional user action unless a warning is triggered. However, users must recognize and respond appropriately to OS warnings, which may not be intuitive for all. Linux users face a higher usability barrier, as manually verifying checksums requires technical knowledge and effort, which the paper acknowledges but assumes Linux users are more likely to handle.

Weakness: The current process places a burden on users, particularly on Linux, where verification is not automated. Non-technical users may find the process daunting or may skip it entirely, increasing vulnerability to malicious applications.

Your Suggestions: Pre-registered applications: This approach is highly user-friendly, as it eliminates the need for users to verify applications manually. By restricting voting to pre-registered applications, the system ensures authenticity without requiring user intervention. Single-click verification: A one-click button to verify the application's fingerprint or digest significantly lowers the usability barrier. By drawing on the Electrum Bitcoin wallet's model, you propose a solution that is accessible to both technical and non-technical users, reducing errors and increasing adoption of secure practices.

Strength: Your suggestions prioritize usability, making it easier for all voters to use a secure application without needing to understand cryptographic concepts like checksums or signatures.

## **3. Practicality**

Paper's Approach: Leverages existing OS security features (e.g., code signing on Windows/macOS) and user behavior (e.g., crash reporting), requiring minimal changes to the current IVXV system. For Linux, it relies on users following existing guidelines to verify checksums, which is practical for technically savvy users but less so for others.

Weakness: The approach assumes a baseline level of user competence and vigilance, which may not hold for all voters. It also does not address the possibility of sophisticated social engineering attacks that could direct users to unofficial channels.

Your Suggestions: Pre-registered applications: Implementing this would require changes to the IVXV system to enforce registration and validation of applications, potentially increasing development and maintenance costs. However, it aligns with modern security practices (e.g., app stores with vetted applications) and could be integrated into the existing infrastructure with clear protocols for key management. Single-click verification: Adding a verification button is a relatively straightforward enhancement that could be implemented within the voter application interface. By automating the verification process, it reduces the need for external instructions (e.g., the current guidelines at <https://www.valimised.ee/en/internet-voting/guidelines/voter-applications-and-checking-authenticity>), making it more practical for widespread adoption.

Strength: Your suggestions are feasible and align with user-friendly security practices in other domains (e.g., cryptocurrency wallets). They address the paper's assumptions by reducing reliance on user actions and enhancing system-level controls.

## **Current Authenticity Verification Process**

The Estonian i-voting system's guidelines instruct users to: Download the voter application from the official website.

Verify the application's authenticity by checking its digital signature or checksum, with step-by-step instructions provided for Windows, macOS, and Linux. Report any suspicious behavior to [abi@valimised.ee](mailto:abi@valimised.ee).

This process is robust but complex, particularly for Linux users who must manually compare checksums. The guidelines emphasize the importance of using the correct website and application, but they rely on users following detailed instructions, which may not be practical for non-technical voters. Your suggestions address these shortcomings by automating and simplifying the verification process.

### **Critical Analysis:**

-The paper's argument is grounded in the current system's safeguards but overestimates user diligence, especially for non-technical voters. The assumption that Linux users are more likely to verify checksums may not hold universally, and the reliance on crash reporting as a detection mechanism is reactive rather than preventive.

-Your suggestions, by contrast, are proactive: Pre-registered applications eliminate the possibility of unofficial applications being used, directly countering the paper's first assumption (unofficial distribution channels). Single-click verification addresses the second assumption (failure to verify authenticity) by making verification accessible and automatic, reducing the likelihood of human error. The Electrum Bitcoin wallet example is particularly compelling, as it demonstrates a real-world implementation of batched verification that balances security and usability. By applying this model to i-voting, your approach could significantly enhance the IVXV system's resilience to malicious applications while maintaining accessibility.

## **Conclusion**

*Your suggestions offer a more robust and user-friendly approach to securing voter applications compared to the paper's reliance on existing OS features and user vigilance. By enforcing pre-registered applications and simplifying verification with a single-click button, you address the paper's key assumptions more effectively, reducing the risk of malicious applications being used. The current Estonian guidelines, while thorough, place a significant burden on users, which your proposals mitigate. Implementing these changes would enhance both the security and usability of the IVXV system, making it a more trustworthy platform for internet voting.*

(used 25 web pages)

---

## **Me:**

He says that "it is possible for an attacker to register as a developer, but this will leave more traces", what traces does he mean?. Also, when talking about reporting a system crash, how the authorities be sure and get access to the malicious voting application? It is not clear what is the authorities action in this case and how would it prevent the attack spread?

## **Grok:** (Browsed arxiv.org)

Traces from Attacker Registering as a Developer The paper refers to the traces left by an attacker registering as a developer in the context of code-signing requirements for Windows and macOS applications. Specifically, this occurs under the discussion of Assumption 2 (the voter not verifying the application's authenticity). The voting application must be digitally signed with a developer certificate for the OS to allow execution without warnings. While an attacker could theoretically obtain such a certificate by enrolling in Apple's Developer Program (for macOS) or Microsoft's developer ecosystem (for Windows), this process creates auditable records that could expose the attacker's identity or actions

during a post-incident investigation. The implied traces include: Registration logs and account records: Developer programs require creating an account, often with personal or organizational details (e.g., email, payment information, or company affiliation). These are logged by the certificate authorities (e.g., Apple or Microsoft) and can be subpoenaed or audited if suspicious activity is detected.

Certificate issuance and usage footprints: Issuing a code-signing certificate generates metadata, such as timestamps, IP addresses, or device information tied to the registration. If the malicious application is distributed and later analyzed, the certificate's chain can be traced back to the attacker's developer account, revealing who signed it.

Audit trails in distribution channels: If the app is uploaded to official stores (e.g., Microsoft Store or Mac App Store), additional review logs or rejection histories could exist, but even sideloading leaves traces in the attacker's development environment or build tools.

These traces make the attack less anonymous and more attributable compared to unsigned malware, as they provide forensic leads for law enforcement or election officials to identify and prosecute the perpetrator. *The paper uses this to argue that the effort and risk of traceability deter casual attackers, though a state-sponsored actor might still mitigate it with proxies.*

**Reporting System Crashes:** Detection, Authority Access, and Prevention of Spread The paper addresses Assumption 3 (the voter not reporting a suspicious crash) by modeling the probability of the attack going undetected. It assumes that for the attack to meaningfully alter election results, the malicious application must be downloaded and run by a large number ( $n$ ) of voters (e.g., hundreds or thousands to swing a close race). The app would collect the voter's real ballot, crash before verification (to avoid detection via the system's additively homomorphic encryption checks), and secretly submit a manipulated vote to the server. However, crashes are inevitable in such tampered software, especially at scale, and the paper argues that user reports make large-scale success improbable. How Authorities Get Notified and Ensure Detection Voter Reporting Mechanism: Voters experiencing crashes (e.g., the app freezing or closing unexpectedly during voting) are encouraged to report via Estonia's official channels, such as emailing [abi@valimised.ee](mailto:abi@valimised.ee) (as outlined in the current guidelines you linked). Reports would describe the issue, including details like the download source, app version, and crash symptoms. With ( $n$ ) affected voters and each having a small independent probability  $p > 0$  of reporting (e.g.,  $p = 0.01$ ), the probability that no one reports is  $(1-p)^n$ .

or 1% for cautious users), the probability that no one reports is  $(1-p)^n$ . This decays exponentially to near-zero as ( $n$ ) grows—for instance, even with  $p = 0.001$ , the chance of zero reports drops below 1% for  $n > 700$ . The paper formalizes this as a negligible function in cryptographic terms: For any  $q \in [0, 1]$ ,  $q^n$  is negligible, meaning it becomes smaller than any polynomial inverse (e.g.,  $1/n^k$ ) for large ( $n$ ). This implies that authorities can be "sure" of detection with overwhelming probability (e.g., >99.999%) for attacks targeting enough votes to matter, based on statistical confidence from the binomial reporting model.

**Aggregation and Verification:** The National Electoral Committee (or OSCE/ODIHR observers) monitors incoming reports in real-time during the voting period. A spike in similar crash reports (e.g., clustered by app version or download timing) would trigger alerts, as it deviates from baseline error rates. To "ensure" validity, authorities cross-reference reports with server logs (e.g., anomalous vote submissions without verifications) and may request screenshots, crash dumps, or device logs from reporters.

### **How Authorities Access the Malicious Application**

Access isn't guaranteed from every report but becomes feasible at scale: From User-Submitted Evidence: Vigilant voters might attach the app file (or its installer) to their email report, especially if instructed in guidelines to preserve suspicious software. Technical users could provide file hashes or full binaries.

Forensic Analysis via Traces: Once crashes are confirmed as attack-related, authorities trace back using the developer traces (from above) or distribution logs (e.g., phishing site analytics if unofficial channels are identified). They could issue takedown requests to hosting providers or analyze seized devices.

Server-Side Clues: The IVXV system's backend logs partial interactions (e.g., incomplete verifications), allowing reconstruction of the malicious payload's behavior without needing the full app immediately.

Post-Election Forensics: If undetected during voting, audits could involve sampling voter devices or network traffic, but the paper emphasizes proactive reporting to enable real-time access.

In practice, Estonia's system has demonstrated rapid response to anomalies (e.g., fixing misconfigurations in hours during past elections), so even partial access from a few reports suffices to confirm malice. Authority Actions and Preventing Attack Spread The paper doesn't detail a rigid protocol but draws on Estonia's legal framework (e.g., the 2017 Election Act amendment) to outline responsive actions that halt spread and mitigate damage: Immediate Triage: Upon receiving clustered reports, the Electoral Committee declares a "material violation" if crashes suggest tampering. They issue public alerts via the official site (valimised.ee) and media, warning voters to stop using suspect apps and download from verified sources.

Quarantine and Invalidation: Affected votes can be annulled in part or whole—e.g., voiding all votes from a specific IP range, app version, or time window. Voters are notified to revote (Estonia's system allows multiple attempts until the deadline, overwriting priors).

Containment Measures: Block server acceptance of votes from tampered clients (e.g., via mismatched signatures or verification failures).

-Collaborate with ISPs or domain registrars to shut down unofficial distribution channels.

-Enhance monitoring: Ramp up anomaly detection algorithms to flag further suspicious submissions.

-Longer-Term Prevention: If the malicious app is recovered, it's reverse-engineered to understand the exploit, leading to patches (e.g., stricter client validation). This prevents spread by reducing (n) (fewer successful downloads) and increasing (p) (more reporting via awareness campaigns).

Overall, the prevention relies on the exponential improbability of zero reports disrupting the attack's scale: Even if 99% of users don't report, a few do, enabling swift isolation before widespread impact. This reactive model complements your proactive suggestions (e.g., pre-registered apps) by assuming human oversight as a backstop, though it risks some votes being lost if detection lags. In Estonia's context, the short voting window (typically 4-7 days) and high digital literacy amplify its effectiveness.

(1 web page)