

[Home](#)
[Spot Websocket API v2](#)
[Market Data](#)
[Instruments](#)

Instruments

CHANNEL `wss://ws.kraken.com/v2` `instrument`

The `instrument` channel provides a stream of reference data of all active assets and tradeable pairs.

It provides the symbol identifiers, precisions, trading parameters and rules.

Subscribe Request

[Subscribe Schema](#)
[Example: Subscribe](#)
[Subscribe Ack Schema](#)
[Example: Subscribe Ack](#)

MESSAGE BODY

method string	REQUIRED
Value: <code>subscribe</code>	
params object	
channel string	REQUIRED
Value: <code>instrument</code>	
snapshot boolean	
Possible values: <code>[true, false]</code>	
Default value: <code>true</code>	
Request a snapshot after subscribing.	
req_id integer	
Optional client originated request identifier sent as acknowledgment in the response.	

Snapshot / Update Responses

The snapshot and update responses share the same schema.

[Snapshot / Update Schema](#)
[Example: Snapshot](#)
[Example: Update](#)

MESSAGE BODY



Asset identifier of the base currency.

— **quote** string

Asset identifier of the quote currency.

— **cost_min** string

Minimum cost (price * qty) for new orders.

— **cost_precision** integer

Maximum precision used for cost prices.

— **has_index** boolean

Whether the pair has an index available for example stop-loss triggers.

— **margin_initial** float

Initial margin requirement (in percent, if marginable).

— **marginable** boolean

Possible values: [`true`, `false`]

Whether the pair can be traded on margin.

— **position_limit_long** integer

Limit for long positions (marginable pairs).

— **position_limit_short** integer

Limit for short positions (marginable pairs).

— **price_increment** float

Minimum price increment for new orders.

— **price_precision** integer

Maximum precision used for order prices.

— **qty_increment** float

Minimum quantity increment for new orders.

— **qty_min** float

Minimum quantity (in base currency) for new orders.

— **qty_precision** integer

Maximum precision used for order quantities.

— **status** string

Possible values: [`cancel_only`, `delisted`, `limit_only`, `maintenance`, `online`, `post_only`, `reduce_only`, `work_in_progress`]

Status of pair.

]

Example: Unsubscribe Ack

Optional client originated request identifier sent as acknowledgment in the response.