Spot Websocket API v2 ■ Market Data ■ Ticker (Level 1

Ticker (Level 1)

CHANNEL wss://ws.kraken.com/v2 ticker

The ticker channel streams level 1 market data, i.e. top of the book (best bid/offer) and recent trade data.

The feed accepts a list symbols for subscription and the updates are generated on trade events.

Subscribe Request

	Subscribe Schema Subscribe Ack Schema Example: Subscribe Example: Subscribe Ack	:k
MESSAGE BODY		
	method string	REQUIRED
	Value: subscribe	
_	params object	
	channel string	REQUIRED
	Value: ticker	
	— symbol array of strings	REQUIRED
	Example: ["BTC/USD", "MATIC/GBP"]	REGOIRED
	A list of currency pairs.	
	— event_trigger string	
	Possible values: [bbo], [trades]	
	Default value: trades	
	The book event that causes a new ticker update to be published on the channel.	
	bbo : on a change in the best-bid-offer price levels.	
	• trades: on every trade.	
	— snapshot boolean	
1	Possible values: [true , false]	

Default value: [true]

Request a snapshot after subscribing.

req_id integer

Optional client originated request identifier sent as acknowledgment in the response.

Snapshot / Update Response

The snapshot and update responses share the same schema. An update message is streamed on a trade event.

Snapshot / Update Schema Example: Snapshot Example: Update **MESSAGE BODY** channel string Value: ticker type string Possible values: [snapshot update] - data array [-[0] ticker object The ticker element is always the first and only item in the data payload. ask float Best ask price. -ask_qty float Best ask quantity. bid float Best bid price. bid_qty float Best bid quantity. - change float 24-hour price change (in quote currency).

```
change_pct float
24-hour price change (in percentage points).

- high float
24-hour highest trade price.

- last float
Last traded price (only guaranteed if traded within the past 24 hours).

- low float
24-hour lowest trade price.

- symbol string
Example: "BTC/USD"
The symbol of the currency pair.

- volume float
24-hour traded volume (in base currency terms).

- vwap float
24-hour volume weighted average price.
```

Unsubscribe Request

Unsubscribe Schema Example: Unsubscribe Example: Unsubscribe Ack Unsubscribe Ack Schema **MESSAGE BODY** - method string -**REQUIRED** Value: unsubscribe - params object - channel string -Value: ticker - symbol array of strings **REQUIRED** Example: ["BTC/USD", "MATIC/GBP"] A list of currency pairs. event_trigger string Possible values: [bbo , trades]

Default value: trades

The book event that causes a new ticker update to be published on the channel.

- bbo: on a change in the best-bid-offer price levels.
- trades: on every trade.

req_id integer

Optional client originated request identifier sent as acknowledgment in the response.