Transportation Research Part C 191 (2026) 105896

Contents lists available at ScienceDirect

Transportation Research Part C

journal homepage: www.elsevier.com/locate/trc

Corrigendum

Corrigendum to "Integrated order assignment and routing for on-demand food delivery with courier-drone coordination" [Trans. Res. Part C: Emerg. Technol. 192 (2026) 105864]

Xuting Sun, Kai Xue, Jiage Huo *, Huan Zhang

SILC Business School, Shanghai University, Shanghai 201899, PR China

The authors regret that

1. Equation (51): the term "$)y_{i+n,jd}$" was omitted during the page proof stage, and the set-up cost should be c_d. The corrected version of Equation (51) is shown as follows:

$$\begin{aligned}\text{Min}\boldsymbol{Z} = &\sum_{i\in R}\sum_{j\in V^+}\sum_{k\in K} c_i x_{n+i,jk} + \sum_{i\in R}\sum_{k\in K}\sum_{d\in D} c_{is_d} w^i_{s_d kd} + \sum_{d\in D} c_d z_d + \sum_{i\in V_d^-}\sum_{j\in V_d^+}\sum_{d\in D} c_{elec} e^d_{ij} y_{ijd} + \omega\Big[\sum_{i\in R}\sum_{k\in K}\sum_{j\in V^+}(a_{i+n,k} \\ &- e_i)x_{i+n,jk} + \sum_{i\in R}\sum_{d\in D}\sum_{j\in V_d^+}(a_{i+n,d} - e_i)y_{i+n,jd}\Big] \end{aligned} \tag{51}$$

It should be noted that this correction does not affect the theoretical derivations, computational implementation, numerical results, or conclusions of the paper.

2. Table 5: the optimality gap values reported for the 20-order and 30-order instances were inadvertently calculated using an incorrect denominator (i.e., LB). The definition of the optimality gap given in the table note is correct and remains unchanged. The corrected values of the Opt_Gap column are provided below.

n	Instance	Opt_Gap
20	0o50t75s1p125_201	7.30%
	0o50t75s1p125_202	24.05%
	0o50t75s1p125_203	21.98%
	0o50t75s1p125_204	31.67%
	0o50t75s1p125_205	27.32%
	0o50t75s1p100_206	25.20%
	0o50t75s1p100_207	31.84%
	0o50t75s1p100_208	22.87%
	0o50t75s1p100_209	13.45%
	0o50t75s1p100_210	15.50%
30	0o50t75s1p125_301	13.26%
	0o50t75s1p125_302	18.14%

(*continued on next page*)

DOI of original article: https://doi.org/10.1016/j.trc.2026.105864.

* Corresponding author.
E-mail addresses: sunxuting@shu.edu.cn (X. Sun), xuekai@shu.edu.cn (K. Xue), huojiage@163.com (J. Huo), hzhang07@shu.edu.cn (H. Zhang).

https://doi.org/10.1016/j.trc.2026.105896

Available online 1 August 2026
0968-090X/© 2026 Published by Elsevier Ltd.

(*continued*)

n	Instance	Opt_Gap
	0o50t75s1p125_303	22.20%
	0o50t75s1p125_304	27.17%
	0o50t75s1p125_305	29.04%
	0o50t75s1p100_306	24.33%
	0o50t75s1p100_307	27.01%
	0o50t75s1p100_308	24.18%
	0o50t75s1p100_309	25.20%
	0o50t75s1p100_310	30.35%

3. Table 2: the column heading "#drones per stations" should be corrected to "#drones per station".

4. Table 8: the column heading "Ave. CPU time" should be corrected to "Ave. CPU time(s)".
5. In Fig. 1(b), the pickup nodes listed as "p2, p2, and p4" should read "p2, p3, and p4."
6. In Section 5.4.1, "MWTR" should be corrected to "MWTD."
7. In Section 6.7, the reference to "the x-axis in Fig. 10" should be corrected to "the x-axis in Fig. 12."
8. In the introduction to the coordination constraints, "Constraints (11) to (13)" should be corrected to "Constraints (11) to (14)".
9. Equation (46): "arcmax" should be corrected to "argmax".

The authors would like to apologise for any inconvenience caused.