EP EQUIPMENT CO., LTD.

EPL205Z (2.0T Pallet Truck) & EFL252 (2.5T Li-Ion Forklift)

LITHIUM-ION WAREHOUSE & COUNTERBALANCE LINEUP | Document No: DOC-EP-LI-SERIES-2026

TECHNICAL SPECIFICATION SHEET (VDI 2198 / ISO 5053 STANDARD)

Specification Parameter	Official Standard Value / Configuration
1. Manufacturer	EP Equipment Co., Ltd. (Hangzhou, China)
2. Model 1: EPL205Z	2,000 kg Ride-On Electric Lithium Pallet Truck (48V/24V Li-Ion)
3. EPL205Z Fork Dimensions	55 x 170 x 1,150 mm (Width across forks: 550 / 685 mm)
4. EPL205Z Turning Radius (Wa)	1,720 mm (Folded Platform) / 2,140 mm (Platform Down)
5. EPL205Z Service Weight	680 kg (with Plug-in LiFePO4 Battery & Integrated BMS)
6. EPL205Z Travel Speed	9.0 / 10.0 km/h (EPS Electric Power Steering Standard)
7. Model 2: EFL252	2,500 kg IC-Chassis Electric Lithium Counterbalance Forklift
8. EFL252 Load Center (c)	500 mm
9. EFL252 Battery Spec	80V / 205Ah LiFePO4 (Integrated Charger 380V / Opportunity Charge)
10. EFL252 Overall Dimensions	L2: 2,535 mm x B1: 1,154 mm x H6: 2,160 mm
11. EFL252 Turning Radius (Wa)	2,290 mm
12. EFL252 Big Tire Design	Front 7.00-12 / Rear 6.00-9 High Ground Clearance (120 mm)
13. Waterproof Rating	IPX4 Outdoor All-Weather Operation
14. Warranty Coverage	LiFePO4 Battery: 3-5 Years / Structural & Drive Components: 1-2 Years

OPERATOR PRE-SHIFT INSPECTION & PREVENTIVE MAINTENANCE MANUAL SUMMARY

- Daily Check 1: Inspect polyurethane load wheels on EPL205Z for flat spots or debris entanglement.
- Daily Check 2: Test tiller arm belly-button emergency reverse switch and horn before operation.
- Periodic Service: Check drive wheel gearbox oil every 1,000 hrs; keep charger vents clean.

Archived in ebro_FL Official Forklift Technical Document Repository (fl-demo.ebro.run)