HANGCHA GROUP CO., LTD.

CPCD35-XRG2 (3.5 Ton Diesel Stage-V)

X SERIES INTERNAL COMBUSTION COUNTERBALANCE FORKLIFT | Document No: DOC-HC-X-CPCD35-2026

TECHNICAL SPECIFICATION SHEET (VDI 2198 / ISO 5053 STANDARD)

Specification Parameter	Official Standard Value / Configuration
1. Manufacturer	Hangcha Group Co., Ltd. (HANGCHA)
2. Model Designation	CPCD35-XRG2 (X Series 3.5T IC Diesel)
3. Drive / Power Type	Diesel Engine (Stage V / Tier 4 Final DPF + DOC)
4. Rated Load Capacity (Q)	3,500 kg
5. Load Center Distance (c)	500 mm
6. Standard Lift Height (h3)	3,000 mm (Opt: 4,500 mm 3-Stage Full Free Mast)
7. Fork Dimensions (s/e/l)	50 x 125 x 1,070 mm (1,220 mm Optional)
8. Overall Length to Fork Face (l2)	2,810 mm
9. Overall Width (b1)	1,225 mm
10. Overhead Guard Height (h6)	2,110 mm
11. Minimum Turning Radius (Wa)	2,460 mm
12. Travel Speed (Laden / Unladen)	19.0 / 19.5 km/h
13. Lifting Speed (Laden / Unladen)	440 / 480 mm/s
14. Max Gradeability (Laden)	20%
15. Service Weight	4,720 kg
16. Engine Model & Rated Output	Xinchai 4D27G51 / Kubota V2403-CR-TE5B (42.6 kW @ 2,400 rpm)
17. Displacement / Fuel Tank	2,670 cc / 70 Liters
18. Transmission Type	Powershift Hydrodynamic 1-Forward / 1-Reverse
19. Tires (Front / Rear)	28x9-15-14PR / 6.50-10-10PR Pneumatic or Solid
20. Safety Equipment	OPS Operator Presence Sensing, Soft Landing System, LED Work Lamps
21. Warranty Coverage	1 Year or 2,000 Operating Hours (Powertrain 2 Years)

OPERATOR PRE-SHIFT INSPECTION & PREVENTIVE MAINTENANCE MANUAL SUMMARY

- Daily Check 1: Check engine oil dipstick, coolant expansion tank, and fuel water separator before start.
- Daily Check 2: Monitor DPF soot load level; perform stationary regeneration when indicator illuminates.
- Daily Check 3: Check tire tread/pressure, wheel nut torque, and mast carriage rollers.
- Periodic Service: Engine oil & filter every 250-500 hrs; transmission fluid every 1,000 hrs.

Archived in ebro_FL Official Forklift Technical Document Repository (fl-demo.ebro.run)