HANGCHA GROUP CO., LTD.

CPD25-XEY2-SI (2.5 Ton 80V PMSM Lithium)

XE SERIES LITHIUM-ION PERMANENT MAGNET FORKLIFT | Document No: DOC-HC-XE-CPD25-2026

TECHNICAL SPECIFICATION SHEET (VDI 2198 / ISO 5053 STANDARD)

Specification Parameter	Official Standard Value / Configuration
1. Manufacturer	Hangcha Group Co., Ltd. (HANGCHA)
2. Model Designation	CPD25-XEY2-SI (XE Series Lithium)
3. Drive / Power Type	80V LiFePO4 Lithium-Ion (CATL Cell Module)
4. Rated Load Capacity (Q)	2,500 kg
5. Load Center Distance (c)	500 mm
6. Standard Lift Height (h3)	3,000 mm (Opt: 4,500 mm Triplex Mast)
7. Fork Dimensions (s/e/l)	40 x 122 x 1,070 mm
8. Overall Length to Fork Face (l2)	2,490 mm
9. Overall Width (b1)	1,150 mm
10. Overhead Guard Height (h6)	2,135 mm
11. Minimum Turning Radius (Wa)	2,150 mm
12. Travel Speed (Laden / Unladen)	16.0 / 17.0 km/h
13. Lifting Speed (Laden / Unladen)	430 / 550 mm/s
14. Max Gradeability (Laden)	18%
15. Service Weight	3,820 kg
16. Battery Voltage / Capacity	80V / 230Ah Standard (Opt: 80V / 280Ah, 410Ah)
17. Synchronous Motor System	Permanent Magnet Synchronous Motor (PMSM) - 15% Energy Saving
18. Water Resistance Rating	IPX4 Full Vehicle Protection
19. Warranty Coverage	Battery: 5 Years or 10,000 Hours / Truck: 2 Years or 4,000 Hours

OPERATOR PRE-SHIFT INSPECTION & PREVENTIVE MAINTENANCE MANUAL SUMMARY

- Daily Check 1: Verify CATL BMS status on color TFT cluster and check emergency disconnect switch.
- Daily Check 2: Inspect fork stopper pins, mast tilt pins, and overhead guard bolts.
- Periodic Service: Zero battery water maintenance; inspect hydraulic oil cleanliness every 1,000 hrs.

Archived in ebro_FL Official Forklift Technical Document Repository (fl-demo.ebro.run)