ANHUI HELI CO., LTD.

CPD25-GB2Li (2.5 Ton 80V LiFePO4)

G2 SERIES LITHIUM-ION COUNTERBALANCE FORKLIFT | Document No: DOC-HELI-G2-CPD25-2026

TECHNICAL SPECIFICATION SHEET (VDI 2198 / ISO 5053 STANDARD)

Specification Parameter	Official Standard Value / Configuration
1. Manufacturer	Anhui Heli Co., Ltd. (HELI)
2. Model Designation	CPD25-GB2Li (G2 Series Lithium)
3. Drive / Power Type	Electric 80V LiFePO4 Lithium-Ion Battery
4. Rated Load Capacity (Q)	2,500 kg
5. Load Center Distance (c)	500 mm
6. Standard Lift Height (h3)	3,000 mm (Opt: 4,500 / 4,700 mm Triplex Mast)
7. Free Lift Height (h2)	155 mm (Triplex Full Free: 1,480 mm)
8. Fork Dimensions (s/e/l)	40 x 122 x 1,070 mm (Cascade Side Shifter Optional)
9. Overall Length to Fork Face (l2)	2,485 mm
10. Overall Width (b1)	1,180 mm
11. Overhead Guard Height (h6)	2,140 mm
12. Minimum Turning Radius (Wa)	2,120 mm
13. Travel Speed (Laden / Unladen)	18.0 / 19.0 km/h
14. Lifting Speed (Laden / Unladen)	460 / 540 mm/s
15. Max Gradeability (Laden / Unladen)	20% / 25%
16. Service Weight (with Battery)	3,980 kg
17. Battery Voltage / Rated Capacity	80V / 271Ah (Opt: 80V / 404Ah LiFePO4)
18. Drive Motor / Pump Motor Rating	AC 16.6 kW / AC 24.0 kW Maintenance-Free
19. Charger Spec & Charging Time	80V 130A Fast Opportunity Charger (1.5 - 2.0 Hours)
20. Waterproof & Protection Rating	IPX4 Whole-Truck Outdoor Rain Protection
21. Warranty Coverage	Battery & BMS: 5 Years or 10,000 Hours / Chassis: 2 Years

OPERATOR PRE-SHIFT INSPECTION & PREVENTIVE MAINTENANCE MANUAL SUMMARY

- Daily Check 1: Verify LiFePO4 BMS SOC indicator, insulation status, and charging gun pins before shift.
- Daily Check 2: Inspect hydraulic mast chains, tilt cylinders, and Cascade side-shift hoses for oil leaks.
- Daily Check 3: Test service wet disc brake, regenerative braking response, and ratchet parking brake.
- Periodic Service: Replace hydraulic return filter every 1,000 hrs; gear oil every 2,000 hrs.

Archived in ebro_FL Official Forklift Technical Document Repository (fl-demo.ebro.run)