HD HYUNDAI SITE SOLUTION

25B-9U (2.5 Ton Dual AC Electric)

9U SERIES 4-WHEEL ELECTRIC COUNTERBALANCE FORKLIFT | Document No: DOC-HCE-25B9U-2026

TECHNICAL SPECIFICATION SHEET (VDI 2198 / ISO 5053 STANDARD)

Specification Parameter	Official Standard Value / Configuration
1. Manufacturer	HD Hyundai Site Solution (HYUNDAI Material Handling)
2. Model Designation	25B-9U (4-Wheel Sit-Down Counterbalance)
3. Drive / Power Type	48V Electric (Lead-Acid 725Ah or Li-Ion Option)
4. Rated Load Capacity (Q)	2,500 kg
5. Load Center Distance (c)	500 mm
6. Standard Lift Height (h3)	3,000 mm (TF470 4,700 mm 3-Stage Full Free Optional)
7. Fork Dimensions (s/e/l)	45 x 100 x 1,050 mm
8. Overall Length to Fork Face (l2)	2,352 mm
9. Overall Width (b1)	1,160 mm
10. Overhead Guard Height (h6)	2,160 mm
11. Minimum Turning Radius (Wa)	2,019 mm
12. Travel Speed (Laden / Unladen)	16.1 / 18.2 km/h
13. Lifting Speed (Laden / Unladen)	390 / 590 mm/s
14. Max Gradeability (Laden)	22.0%
15. Service Weight (with Battery)	4,296 kg
16. Drive / Hydraulic Pump Motor	Dual ZAPI AC Controller - Drive 12.0 kW / Pump 18.0 kW
17. Brake Type	Wet Disc Brake (Oil-Cooled Enclosed Maintenance-Free)
18. Safety Features	OPSS (Operator Presence Sensing), HAC (Hill-Start Assist), Curve Speed Control
19. Warranty Coverage	2 Years or 3,000 Hours Domestic Official Warranty

OPERATOR PRE-SHIFT INSPECTION & PREVENTIVE MAINTENANCE MANUAL SUMMARY

- Daily Check 1: For Lead-Acid battery models, verify electrolyte level and specific gravity weekly.
- Daily Check 2: Test OPSS seat switch interlock and auto-parking/anti-roll back function on slope.
- Periodic Service: Wet disc brake oil replacement every 2,000 hrs; hydraulic oil every 2,000 hrs.

Archived in ebro_FL Official Forklift Technical Document Repository (fl-demo.ebro.run)