HD HYUNDAI SITE SOLUTION

30D-9S (3.0 Ton Stage-V Diesel)

9S SERIES HEAVY-DUTY DIESEL FORKLIFT | Document No: DOC-HCE-30D9S-2026

TECHNICAL SPECIFICATION SHEET (VDI 2198 / ISO 5053 STANDARD)

Specification Parameter	Official Standard Value / Configuration
1. Manufacturer	HD Hyundai Site Solution (HYUNDAI Material Handling)
2. Model Designation	30D-9S (9S Series Diesel Counterbalance)
3. Drive / Power Type	Diesel Engine (Hyundai HMC D4HB / Kubota V3307 Stage-V)
4. Rated Load Capacity (Q)	3,000 kg
5. Load Center Distance (c)	500 mm
6. Standard Lift Height (h3)	3,000 mm (Opt: TF450 / TF470 / TF600)
7. Fork Dimensions (s/e/l)	45 x 122 x 1,050 mm
8. Overall Length to Fork Face (l2)	2,692 mm
9. Overall Width (b1)	1,230 mm
10. Overhead Guard Height (h6)	2,175 mm
11. Minimum Turning Radius (Wa)	2,426 mm
12. Travel Speed (Laden / Unladen)	18.5 / 19.6 km/h
13. Lifting Speed (Laden / Unladen)	480 / 520 mm/s
14. Max Gradeability (Laden)	23.9%
15. Service Weight	4,381 kg
16. Engine Rated Output	50 kW (68 PS) @ 2,300 rpm
17. Brake Type	Enclosed Wet Disc Brake System
18. Safety Features	OPSS, Load Weight Indicator, Rear View Camera & Blue Spot Light
19. Warranty Coverage	2 Years or 3,000 Hours Official Domestic Service

OPERATOR PRE-SHIFT INSPECTION & PREVENTIVE MAINTENANCE MANUAL SUMMARY

- Daily Check 1: Drain water from fuel pre-filter and inspect radiator core for dust blockage.
- Daily Check 2: Allow 3-minute turbocharger cool-down idle before engine shut-off.
- Periodic Service: Engine oil & filter every 500 hrs; DPF ash cleaning every 3,000-4,500 hrs.

Archived in ebro_FL Official Forklift Technical Document Repository (fl-demo.ebro.run)