

1 Logical and Relational Operators

Logical operators are useful when writing code. Logical operators, when combined with flow control, allow for complex choices to be compactly expressed.

1.1 Relational Operators

The core logical operators are

Symbol	Function	Definition
>	greater	Greater than
>=	greater_equal	Greater than or equal to
<	less	Less than
<=	less_equal	Less than or equal to
==	equal	Equal to
!=	not_equal	Not equal to

2 Logical Operators

Logical expressions can be combined using four logical devices,

Keyword (Scalar)	Function	Bitwise	True if . . .
and	logical_and	Both	True
or	logical_or	Either or Both True	
not	logical_not		Not True
	logical_xor	\wedge	One True and One False

There are three versions of all operators except XOR. The keyword version (e.g. and) can only be used with scalars and so it not useful when working with NumPy. Both the function and bitwise operators can be used with NumPy arrays, although care is requires when using the bitwise operators.

2.1 Bitwise operators

Bitwise operators have high priority – higher than logical comparisons – and so parentheses are requires around comparisons. For example, $(x > 1) \& (x < 5)$ is a valid statement, while $x > 1 \& x < 5$, which is evaluated as $(x > (1 \& x)) < 5$, produces an error.

```
>>> x = arange(2.0,4)
>>> y = x >= 0
>>> z = x < 2
>>> logical_and(y, z)
array([False, False, True, True, False, False], dtype=bool)
>>> y & z
```

```
array([False, False, True, True, False, False], dtype=bool)
>>> (x > 0) & (x < 2)
array([False, False, True, True, False, False], dtype=bool)
```

2.2 Multiple tests: all and any

The commands `all` and `any` take logical input and are self-descriptive. `all` returns `True` if all logical elements in an array are 1.

- If `all` is called without any additional arguments on an array, it returns `True` if all elements of the array are logical true and 0 otherwise.
- `any` returns logical(`True`) if any element of an array is `True`.

Both `all` and `any` can also be used along a specific dimension using a second argument or the keyword argument `axis` to indicate the axis of operation (0 is column-wise and 1 is row-wise).

When used column- or row-wise, the output is an array with one less dimension than the input, where each element of the output contains the truth value of the operation on a column or row.

```
>>> x = array([[1,2],[3,4]])
>>> y = x <= 2
>>> y
array([[ True,  True],
       [False,  False]], dtype=bool)
>>> any(y)
True
>>> any(y,0)
array([[ True,  True]], dtype=bool)
>>> any(y,1)
array([[ True],
       [False]], dtype=bool)
```

2.2.1 allclose

`allclose` can be used to compare two arrays for near equality. This type of function is important when comparing floating point values which may be effectively the same although not identical.

```
>>> eps = np.finfo(np.float64).eps
>>> eps
2.2204460492503131e16
>>> x = randn(2)
>>> y = x + eps
115
>>> x == y
array([False, False], dtype=bool)
>>> allclose(x,y)
True
```

The tolerance for being close can be set using keyword arguments either relatively (rtol) or absolutely (atol).

2.2.2 array_equal

array_equal tests if two arrays have the same shape and elements. It is safer than comparing arrays directly since comparing arrays which are not broadcastable produces an error.

2.2.3 array_array_equiv

array_equiv tests if two arrays are equivalent, even if they do not have the exact same shape. Equivalence is defined as one array being broadcastable to produce the other.

```
>>> x = randn(10,1)
>>> y = tile(x,2)
>>> array_equal(x,y)
False
>>> array_equiv(x,y)
True
```

2.3 is*

A number of special purpose logical tests are provided to determine if an array has special characteristics. Some operate element-by-element and produce an array of the same dimension as the input while other produce only scalars. These functions all begin with is.

```

\begin{tabular}{|c|c|c|}
Operator & True if . . . & Method of operation \\ \hline
isnan & 1 if nan & element-by-element \\ \hline
isinf & 1 if inf & element-by-element \\ \hline
isfinite & 1 if not inf and not nan & element-by-element \\ \hline
isposfin, isnegfin & 1 for positive or negative inf & element-by-element \\ \hline
isreal & 1 if not complex valued & element-by-element \\ \hline
iscomplex & 1 if complex valued & element-by-element \\ \hline
isreal & 1 if real valued & element-by-element \\ \hline
is_string_like & 1 if argument is a string & scalar \\ \hline
is_numlike & 1 if is a numeric type & scalar \\ \hline
isscalar & 1 if scalar & scalar \\ \hline
isvector & 1 if input is a vector & scalar \\ \hline
\end{tabular}

```