

# FoSAP Lecture Notes

Emma van Emelen

June 2, 2020

# Contents

<b>1</b>	<b>Structure and Tasks</b>	<b>3</b>
1.1	The structure of computer systems . . . . .	3
1.2	The Structure and Tasks of an OS . . . . .	3
1.3	Multitasking & Interrupts . . . . .	3
<b>2</b>	<b>C Programming</b>	<b>3</b>
<b>3</b>	<b>Shell Programming</b>	<b>3</b>
<b>4</b>	<b>Process Management</b>	<b>3</b>
4.1	The Definition of a Process . . . . .	3
4.2	Memory Allocation . . . . .	3
4.3	Process Types . . . . .	4
4.3.1	Process Coordination . . . . .	4
4.3.2	Pipes . . . . .	4
4.3.3	Message Passing . . . . .	4
4.3.4	Shared Memory . . . . .	4
4.4	Threads . . . . .	4

# 1 Structure and Tasks

## 1.1 The structure of computer systems

## 1.2 The Structure and Tasks of an OS

## 1.3 Multitasking & Interrupts

# 2 C Programming

# 3 Shell Programming

# 4 Process Management

## 4.1 The Definition of a Process

A process is simply a running program. This program consists of sequentially executed code, which defines state changes. Part of a process is a full description of the CPU's current state, like the program counter, registers, the stack, the heap and any variables or files that are being worked on. A process is created like this:

1. Create the Process environment in RAM.
  - create the heap
  - create the stack
  - load program code
  - load libraries
2. wait for CPU assignment
3. Load operation into CPU register and execute
4. If a process is interrupted, its state is saved and another process will get CPU time.

## 4.2 Memory Allocation

A process gets 3GiB of memory by default. Memory allocation is broken up into 5 parts.

- The stack, which holds function parameters and local variables. This is automatically managed memory.
- The heap, which is dynamically allocated memory `malloc`. This gives the programmer full control over the Memory management but can cause a lot of problems, if not used carefully. Heap-Buffer-Overflows are very common when manually controlling the memory allocation. This happens when a program writes more data into memory than the variable has been assigned. This then overwrites any memory that comes after the variable's memory space.
- Statically allocated memory and global data. this is broken up into bss, for **NULL**-initialized variables and data, for other variables.
- The code, which holds the executable program code

## 4.3 Process Types

1. **The User Process**, for System Programs and Applications. These all run in **User-Mode**
2. **The System Process**, for parts of the Kernel. This includes but is not limited to memory management, file system management and device management. These Processes have a higher priority and operate in **Kernel-Mode**.

There are multiple active processes at any given time, which have to be coordinated efficiently, because they can all use the same resources. These resources may include memory space, CPU time and IO-devices, such as storage, sensors, screens and peripherals.

### 4.3.1 Process Coordination

### 4.3.2 Pipes

### 4.3.3 Message Passing

### 4.3.4 Shared Memory

## 4.4 Threads