# MICRO BIRD® G5 GM - MFSAB

Versatile transportation for up to 30 passengers



Multi-Function School Activity Bus
Built to FMVSS/CMVSS School bus construction for your peace of mind.



Integrated child seats and 3-point lap and shoulder seat belts are available for enhanced safety and versatility.



Maximum visibility of loading zone is provided by fully-glassed entrance door and unobstructed "More-View" window.

Standard 32" electric double-opening door.



LED clearance lights, direction lights and stop lights are standard equipment offering enhanced safety, while reducing operating and maintenance costs.



### Also Available:

Special needs Micro Bird with double-leaf wheelchair doors offer protection on both sides of the lift, thus adding to passenger safety, while offering superior weather seal and door strength.



## MICRO BIRD® G5 GM - SPECIFICATIONS



BODY DIMENSIONS	MODEL	100	200	200C
	Maximum passenger capacity	24	30	24
	Number of rows	5	5	5
	Exterior length overall	262"	289"	289"
	Exterior width overall	96"	96"	96"
	Exterior height overall	110″	112"	118″
	Interior floor length	151.25"	177.25"	177.25"
<b>≥</b>	Interior width at hip	93″	93″	93"
B0I	Interior height at center line	76″	76″	76"
	Entrance door	32" x 80"	32" x 80"	32" x 80"
	Side windows	35" x 30"	35" x 30"	35" x 30"
	Rear bumper	3/16" x 9.5" with 12" wrap around		
GMC / CHEVY CHASSIS	MODEL	100	200	200C
	Wheelbase	139″	159″	159″
	Engine	4.8 L gas* / 6.0 L gas / 6.6 L diesel		
	Transmission	6-speed automatic heavy duty overdrive		
	GVWR	10,000 lbs* / 12,300 lbs / 14,200 lbs		
	Fuel tank	33 gallons		
	Brakes	4-wheel anti-lock, 4-wheel disc		
	Tires	LT225/75R16E all-season, blackwall		
	Alternator	145 amp		
	Battery	600 CCA (gas) / 770 CCA (diesel)		

\*4.8 L gas engine only available with 10,000 lbs GVWR

Bumper steel Emergency triangular warning device* Entrance door electric Entrance door grab handle left Floor steel Floor plywood 1/2" (4 ply) Flooring grey rib in aisle Flooring grey smooth under seat Flooring steps grey with white nosing FMVSS seat belt anchorage Heater 20,500 BTU Interior below window embossed aluminum Interior mirror 6" x 16" Joint strength Lights clearance LED Lights back-up incandescent Lights stop and tail LED		4.8 L gas engine only available with 10,
VV I LIGHTS STON AND TALL LELL	STANDARD BODY EQUIPMENT	Emergency triangular warning device* Entrance door electric Entrance door grab handle left Floor steel Floor plywood 1/2" (4 ply) Flooring grey rib in aisle Flooring grey smooth under seat Flooring steps grey with white nosing FMVSS seat belt anchorage Heater 20,500 BTU Interior below window embossed aluminum Interior mirror 6" x 16" Joint strength Lights clearance LED Lights dome (4) Lights marker LED Lights back-up incandescent

Lights turn LED

Mirrors crossview

Padding all doors Paint exterior white Paint interior white Paint rub rail white Rear door 2 windows Rear door 3 point slide bar latch Rear door retainer? Reflective tape rear emergency exit\* Roof bow one piece, hat section type Rub rail floor level Rub rail seat level with wrap around Shut-off valve under body Speakers (2) Stepwell light LED Undercoating Windows back (2) tinted 62% Windows rear door tinted 62% Windows side tinted 62%

Mirrors rearview

Air conditioning
Audio / P.A. systems
Back-up sensors
Barriers
Bumper aluminum
Driver side auxiliary step
Electronic sleeping child monitoring system
Emergency equipment
Entrance door grab handle right
Floor plywood 5/8" (5 ply) marine grade
Heater 42,000 BTU
Integrated toddler seats
Lap and shoulder belt seating
Lift door (Standard on model 200C)
Lift door with tinted windows
Lift wheelchair

Lift wheelchair tie-down
Lights back-up LED
Light monitoring system
Luggage containment systems
Reflective exterior signs
Remote / heated mirrors
Rub rail skirt level
Rub rail window level
Seats
Vandal lock system
Video monitoring / tracking system
Wheelchair and occupant restraint system
Wheelchair lift with interlock device

\*Standard in the US, optional in Canada




### **Galvanized Steel Structure and Side Impact Barriers**

- Completely gasketed steel body frame ensures that all exterior elements, including dust, moisture and noise, remain outside the passenger compartment.
- Superior side impact protection is offered by the use of heavy-gauge steel side impact barriers that incorporate the seat rail into the design for extra strength.



### Double Action Energy Absorbing Body Mounting Blocks

- Absorb road vibration
- Reduce noise transfer to the cabin interior
- Offer extended body durability
- Smoother passenger ride
- Prevent frame collapse
- Eliminate the need for periodic tightening of body bolts



### **Superior Insulation**

- 1.5" fiberglass throughout
- Insulated roof bows
- Reduction in noise transfer into passenger compartment
- Prevents condensation



#### Extra Wide Body Design

- Aerodynamic styling
- Wider seating for increased comfort
- Wider aisle for increased safety
- Better compartmentalization

### Floor Plans

A wide range of configurations to better accomodate your needs.







More options available: Specifications shown in this brochure were in effect at time of printing. In keeping with its policy of continual improvement, Micro Bird, Inc. reserves the right to change specifications without notice and without incurring obligations.



