Supporting Information for: "The Impossibility of Faithful Explanation Under Underdetermination"

Drake Caraker, Bryan Arnold, David Rhoads

Contents

1 Proofs of All Propositions **3**
1.1 Proof of Proposition 2 (Tightness) . . . 3
1.2 Proof of Proposition 3 (Necessity) . . . 3
1.3 Proof of Proposition 4 (G-Invariance Implies Stability) . . . 3

2 All Nine Instance Details **4**
2.1 Instance 1: Feature Attribution Under Collinearity . . . 4
2.2 Instance 2: Attention Maps . . . 4
2.3 Instance 3: Counterfactual Explanations . . . 4
2.4 Instance 4: Concept Probes (TCAV) . . . 5
2.5 Instance 5: Causal Discovery . . . 5
2.6 Instance 6: Model Selection . . . 5
2.7 Instance 7: Saliency Maps (GradCAM) . . . 5
2.8 Instance 8: Language Model Self-Explanations . . . 6
2.9 Instance 9: Mechanistic Interpretability . . . 6

3 Experiment Methodology **6**
3.1 General Protocol . . . 6
3.2 Datasets . . . 6
3.3 Model Architectures . . . 7
3.4 Perturbation Protocol for Attention and Saliency . . . 7

4 Lean Verification Details **7**
4.1 Summary Statistics . . . 7
4.2 Axiom Inventory . . . 7
4.3 Axiom Stratification . . . 8
4.4 Axiom Substitution Analysis . . . 8
4.5 Key Theorem List . . . 8

5 Regulatory Analysis **9**
5.1 EU AI Act Article 13 (Transparency) . . . 9
5.2 NIST AI RMF (MAP 1.5, MEASURE 2.6) . . . 9
5.3 OCC SR 11-7 (Model Risk Management) . . . 9

6 Cross-Domain Connections **10**
6.1 Quine–Duhem Underdetermination 10
6.2 Economics: Partial Identification 10
6.3 Database Theory: View Update Problem 10
6.4 Legal Interpretation: Statutory Ambiguity 10
6.5 Medical Diagnosis: Differential Diagnosis 10

1 Proofs of All Propositions

1.1 Proof of Proposition 2 (Tightness)

Proof. We construct three witnesses, one for each achievable pair.

(i) Faithful + Decisive (drop Stable). Set $E = \mathsf{explain}$. Faithfulness: for every θ, $\perp(E(\theta), \mathsf{explain}(\theta)) = \perp(\mathsf{explain}(\theta), \mathsf{explain}(\theta))$, which is false by irreflexivity of $\perp$. Decisiveness: for every θ and h, $\perp(\mathsf{explain}(\theta), h) \Rightarrow \perp(E(\theta), h)$ holds by identity. Stability fails: the Rashomon property provides θ_1, θ_2 with $\mathsf{observe}(\theta_1) = \mathsf{observe}(\theta_2)$ and $\perp(\mathsf{explain}(\theta_1), \mathsf{explain}(\theta_2))$, so $\mathsf{explain}(\theta_1) \neq \mathsf{explain}(\theta_2)$, hence $E(\theta_1) \neq E(\theta_2)$.

(ii) Faithful + Stable (drop Decisive). Let $c \in \mathcal{H}$ satisfy $\neg \perp(c, \mathsf{explain}(\theta))$ for all θ (a "neutral" or "agnostic" explanation). Set $E(\theta) = c$ for all θ. Faithfulness holds by construction. Stability holds because E is constant. Decisiveness fails because E abstains on every distinction: $\perp(\mathsf{explain}(\theta), h)$ does not imply $\perp(c, h)$ in general.

(iii) Stable + Decisive (drop Faithful). Let $c \in \mathcal{H}$ be "maximally committal": for every θ and h, $\perp(\mathsf{explain}(\theta), h) \Rightarrow \perp(c, h)$. Set $E(\theta) = c$. Stability holds (constant map). Decisiveness holds by construction. Faithfulness fails because c may satisfy $\perp(c, \mathsf{explain}(\theta))$ for some θ—indeed, it must, since it inherits incompatibilities from both sides of the Rashomon witness. □

1.2 Proof of Proposition 3 (Necessity)

Proof. ($\Rightarrow$) If the Rashomon property holds, Theorem 1 shows no faithful, stable, and decisive E exists.

($\Leftarrow$) If the Rashomon property fails, then for all θ_1, θ_2 with $\mathsf{observe}(\theta_1) = \mathsf{observe}(\theta_2)$, $\neg \perp(\mathsf{explain}(\theta_1), \mathsf{explain}(\theta_2))$. Set $E = \mathsf{explain}$.

- **Faithfulness**: $\neg \perp(\mathsf{explain}(\theta), \mathsf{explain}(\theta))$ by irreflexivity.
- **Decisiveness**: $\perp(\mathsf{explain}(\theta), h) \Rightarrow \perp(E(\theta), h)$ by identity.
- **Stability**: Suppose $\mathsf{observe}(\theta_1) = \mathsf{observe}(\theta_2)$. We need $\mathsf{explain}(\theta_1) = \mathsf{explain}(\theta_2)$. By the negated Rashomon property, their explanations are compatible: $\neg \perp(\mathsf{explain}(\theta_1), \mathsf{explain}(\theta_2))$. Under the additional hypothesis that the native explanation is *injective on incompatibility classes* (i.e., compatible explanations on the same observe-fiber are equal), stability follows. In the Lean formalization, this is captured by the `no_rashomon_implies_all_three` theorem, which assumes the negation of the Rashomon property directly implies equality of native explanations on each fiber.

□

1.3 Proof of Proposition 4 (G-Invariance Implies Stability)

Proof. Let θ_1, θ_2 with $\mathsf{observe}(\theta_1) = \mathsf{observe}(\theta_2)$. By transitivity of the G-action on observe-fibers, there exists $g \in G$ with $g \cdot \theta_1 = \theta_2$. By G-invariance, $E(\theta_2) = E(g \cdot \theta_1) = E(\theta_1)$. □

2 All Nine Instance Details

2.1 Instance 1: Feature Attribution Under Collinearity

Explanation system. Configuration space $\mathbf{\Theta}$: trained models from a fixed class (GBDT, Lasso, neural networks), indexed by random seed. Observable space Y: input–output functions. Explanation space $\mathcal{H}$: attribution vectors $(\varphi_1, \ldots, \varphi_P) \in \mathbb{R}^P$. Incompatibility: $\varphi \perp \varphi'$ if there exist collinear features j, k with $\varphi_j > \varphi_k$ and $\varphi'_k > \varphi'_j$.

Rashomon property. Collinear features induce a Rashomon set: models that differ only in which feature within a correlated group acts as primary predictor D'Amour et al. [2022], Fisher et al. [2019].

Quantitative bounds. GBDT: ratio $1/(1-\rho^2)$ diverges as $\rho \to 1$. Lasso: infinite ratio (one feature zeroed). Random forest: $O(1/\sqrt{T})$ convergence (the mechanism behind Dash).

Resolution. Dash: average SHAP values over ensemble of retrained models.

Experiments. 20 XGBoost models on UCI datasets, differing only in random seed. SHAP flip rate: 33%. Prediction equivalence: >99%.

2.2 Instance 2: Attention Maps

Explanation system. $\mathbf{\Theta}$: neural network weight configurations. Y: input–output functions. $\mathcal{H} = \Delta^T$: attention distributions over T tokens. $\perp$: different argmax tokens.

Rashomon property. D'Amour et al. [2022] and Jain and Wallace [2019] demonstrate that functionally equivalent networks attend maximally to different tokens.

Experiments. 10 DistilBERT models with weight perturbations ($\sigma \in \{0.01, 0.02\}$) on 200 SST-2 sentences. Prediction agreement: 100%. Argmax flip rate: 60.0% [95% CI: 59–61%]. Mean Kendall τ: 0.30.

Resolution. Averaged attention rollout over the Rashomon set of equivalent models.

2.3 Instance 3: Counterfactual Explanations

Explanation system. $\mathbf{\Theta}$: model parameters defining decision boundaries. Y: prediction vectors on test set. $\mathcal{H} = \mathcal{X}$: counterfactual points. $\perp$: opposite directions from query point $((x'_1 - x_0)^\top (x'_2 - x_0) < 0)$.

Rashomon property. Within a small loss tolerance, models can place decision boundaries on opposite sides of the query point Semenova et al. [2022].

Experiments. 20 XGBoost models on German Credit. Direction flip rate: 23.5% [CI: 20.6–26.6%]. Cross-model recourse validity: 61.3%. Most unstable feature: `checking_status` at 43% flip rate.

Resolution. Rashomon-robust recourse: the set of counterfactuals valid across all models in the Rashomon set Karimi et al. [2020].

2.4 Instance 4: Concept Probes (TCAV)

Explanation system. $\mathbf{\Theta}$: weight configurations. Y: input–output functions. $\mathcal{H} = \mathbb{R}^c$: concept activation vectors (unit directions). $\perp$: structurally distinct directions not related by concept-subspace rotation.

Rashomon property. Bolukbasi et al. [2016] and Ravfogel et al. [2020] show that concept directions vary substantially across architectures and seeds.

Experiments. 15 MLP classifiers (128–64, ReLU) on `load_digits`. Prediction agreement: 97.2%. Mean $|\cos|$: 0.10 (nearly orthogonal). Concept direction instability $(1 - |\cos|)$: 0.90. TCAV score SD: 0.16.

Resolution. Averaged concept activation vector or subspace over the Rashomon set.

2.5 Instance 5: Causal Discovery

See main text, Section 3.2. The Rashomon property is derived from Markov equivalence (Proposition 4). Resolution: CPDAG reporting Chickering [2002].

2.6 Instance 6: Model Selection

Explanation system. $\mathbf{\Theta}$: model classes (e.g., depth-3 tree, depth-5 tree, linear model). Y: prediction accuracy on test set. $\mathcal{H}$: model identities. $\perp$: different model choices.

Rashomon property. The Rashomon set generically contains multiple models with near-identical accuracy Rudin et al. [2024], Semenova et al. [2022].

Experiments. 20 XGBoost configurations on UCI datasets. Best-model flip rate: 80.0%. ΔAUC < 0.02.

Resolution. Report the Rashomon set or ensemble rather than a single "best" model.

2.7 Instance 7: Saliency Maps (GradCAM)

Explanation system. $\mathbf{\Theta}$: CNN weight configurations. Y: image classification function. $\mathcal{H}$: saliency heatmaps (spatial attribution maps). $\perp$: different peak-activation locations.

Rashomon property. Adebayo et al. [2018] show that saliency maps can be insensitive to model weights, and Hooker et al. [2019] demonstrate that saliency rankings shift under model perturbation.

Experiments. 10 ResNet-18 models with weight perturbations on CIFAR-10. Peak flip rate: 9.6%. Prediction agreement: 78.8%.

Resolution. Averaged GradCAM heatmap over equivalent models.

2.8 Instance 8: Language Model Self-Explanations

Explanation system. $\mathbf{\Theta}$: language model weight configurations. Y: next-token prediction function. $\mathcal{H}$: self-generated explanations (chain-of-thought, cited tokens). $\perp$: different cited evidence for the same prediction.

Rashomon property. Turpin et al. [2024] show that chain-of-thought explanations are unfaithful: models produce different reasoning chains for the same answer. Lanham et al. [2023] and Ye and Durrett [2022] confirm instability across model variants.

Experiments. 10 DistilBERT models on SST-2. Citation flip rate: 34.5%. Prediction agreement: 100%.

Resolution. Averaged attention rollout or ensemble explanation aggregation.

2.9 Instance 9: Mechanistic Interpretability

See main text, Section 3.3. Rashomon property: 85 valid circuits for a single task Meloux et al. [2025]. Resolution: circuit equivalence classes.

3 Experiment Methodology

3.1 General Protocol

For each instance, we follow a common experimental design:

1. **Train K models** from independent random seeds on the same dataset with the same architecture and hyperparameters.
2. **Verify functional equivalence**: confirm that all K models achieve statistically indistinguishable performance (prediction agreement $> 95\%$ or $\Delta\text{AUC} < 0.03$).
3. **Extract explanations**: apply the domain-specific explanation method to each model.
4. **Measure instability**: compute pairwise instability metrics across all $\binom{K}{2}$ model pairs.
5. **Negative control**: verify that instances without the Rashomon property (e.g., unique-solution linear regression) show 0% instability.
6. **Bootstrap confidence intervals**: 1000 bootstrap resamples for all reported metrics.

3.2 Datasets

- **Attribution, counterfactual, model selection**: UCI German Credit, UCI Adult, and synthetic collinear datasets.
- **Attention, LLM explanation**: Stanford Sentiment Treebank (SST-2), 200 sentences.
- **Concept probe**: `sklearn load_digits`, 8×8 digit images.
- **Saliency map**: CIFAR-10, 100 test images.

3.3 Model Architectures

- **Attribution**: XGBoost (100 trees, max depth 6).
- **Attention / LLM**: DistilBERT (6 layers, 12 heads, 66M parameters) with Gaussian weight perturbation.
- **Counterfactual**: XGBoost on German Credit.
- **Concept probe**: MLP (128–64, ReLU), trained with SGD.
- **Model selection**: XGBoost with 20 hyperparameter configurations.
- **Saliency**: ResNet-18 with Gaussian weight perturbation.

3.4 Perturbation Protocol for Attention and Saliency

For transformer and CNN models, we use weight perturbation within the zero-loss manifold rather than full retraining. Gaussian noise with standard deviation σ is added to all model weights. The perturbation magnitude σ is chosen to preserve prediction accuracy within 1% of the original model. This faithfully models the Rashomon set: the perturbed models are functionally equivalent but differ in internal representations.

Limitation: The distribution over perturbations may differ from the distribution induced by stochastic gradient descent. Full retraining experiments for transformers are computationally expensive and are left to future work.

4 Lean Verification Details

4.1 Summary Statistics

Table 1: Lean 4 formalization summary.

Component	Count	Notes
Files	73	All in `UniversalImpossibility/`
Theorems + lemmas	346	Verified by `grep -c`
Axioms	72	Domain-specific; core uses 0
`sorry`	0	Zero admitted goals
Core impossibility	1 theorem	Zero axiom dependencies
GBDT instance	4 axioms	Surjectivity, first-mover, split structure
DASH resolution	6 axioms	+ cross-group symmetry
Causal instance	3 axioms	CPDAG Markov equivalence
Neural net instance	2 axioms	Overparameterization + symmetry
Fairness instance	2 axioms	Unequal base rates + equal accuracy

4.2 Axiom Inventory

The 72 axioms fall into four categories:

Type declarations (6 axioms). `Model`, `numTrees`, `numTrees_pos`, `attribution`, `splitCount`, `firstMover`. These declare the types and basic constants of the GBDT framework.

Core behavioral properties (6 axioms). `firstMover_surjective`, `splitCount_firstMover`, `splitCount_nonFirstMover`, `proportionality_global`, `splitCount_crossGroup_symmetric`, `splitCount_cross` These encode the structure of gradient-boosted decision trees.

Measure infrastructure (2 axioms). `modelMeasurableSpace`, `modelMeasure`. These connect the model space to Mathlib's measure theory library.

Universal instance axioms (58 axioms). Per-instance type and Rashomon witness axioms for the nine instances (attention, counterfactual, concept, causal, model selection, saliency, LLM, mechanistic interpretability, fairness).

4.3 Axiom Stratification

The axiom dependencies are strictly stratified:

- **Core impossibility** (`explanation_impossibility`): **0 axioms**. The Rashomon property enters as a hypothesis, not an axiom.
- **Attribution impossibility** (`attribution_impossibility`): **0 behavioral axioms** (only type declarations).
- **GBDT impossibility** (`gbdt_impossibility_local`): 4 axioms (surjectivity, first-mover, non-first-mover, split-count).
- **Quantitative bounds** (`impossibility`): 5 axioms (+ proportionality).
- **DASH resolution** (`consensus_equity`): 6 axioms (+ cross-group symmetry).

4.4 Axiom Substitution Analysis

We have verified that:

1. Removing any single core behavioral axiom blocks the corresponding impossibility proof (each axiom is necessary).
2. The Rashomon property can be substituted with any domain-specific witness (Markov equivalence, collinearity, weight-space symmetry) without changing the core proof.
3. The causal instance achieves *zero* axioms for the Rashomon property itself (it is derived from Markov equivalence as a theorem).

4.5 Key Theorem List

Theorem name	File	Axioms
`explanation_impossibility`	ExplanationSystem.lean	0
`attribution_impossibility`	Trilemma.lean	0

`attribution_impossibility_weak`	Trilemma.lean	0
`attribution_impossibility_abstract`	AttributionInstance.lean	0
`attention_impossibility`	AttentionInstance.lean	3
`counterfactual_impossibility`	CounterfactualInstance.lean	3
`concept_impossibility`	ConceptInstance.lean	3
`causal_instance_impossibility`	CausalInstance.lean	3
`mech_interp_impossibility`	MechInterpInstance.lean	3
`gInvariant_stable`	UniversalResolution.lean	0
`universal_design_space_dichotomy`	UniversalDesignSpace.lean	0
`no_rashomon_all_three`	Necessity.lean	0
`generic_underspecification`	Ubiquity.lean	0
`consensus_equity`	Corollary.lean	6
`gbdt_impossibility_local`	General.lean	4
`ratio_tendsto_atTop`	Ratio.lean	5
`lasso_impossibility`	Lasso.lean	2
`causal_rashomon_from_markov`	MarkovEquivalence.lean	0

5 Regulatory Analysis

5.1 EU AI Act Article 13 (Transparency)

The EU AI Act EU Parliament [2024] requires "appropriate transparency" and "meaningful information about the logic involved" for high-risk systems. "Meaningful" implies faithfulness and decisiveness; "appropriate" across model versions implies stability. Theorem 1 shows all three simultaneously is impossible under the Rashomon property.

Resolution. Report G-invariant explanations with explicit uncertainty. Disclose which property is sacrificed (typically decisiveness).

5.2 NIST AI RMF (MAP 1.5, MEASURE 2.6)

The NIST framework National Institute of Standards and Technology [2023] requires interpretability to be "defined, appropriate to the AI risk, and documented." This implicitly assumes all three desiderata are simultaneously achievable.

Resolution. Explicitly specify which leg of the trilemma is prioritized for each use case and document the tradeoff in the system card.

5.3 OCC SR 11-7 (Model Risk Management)

SR 11-7 Office of the Comptroller of the Currency [2011] requires conceptual soundness (faithfulness), outcomes analysis across versions (stability), and effective challenge (decisiveness). These three pillars map directly onto the trilemma.

Resolution. Use ensemble explanations (Dash) for stability and partial faithfulness. Document decisiveness limitations. Direct effective challenge at modeling choices rather than explanation artifacts.

6 Cross-Domain Connections

6.1 Quine–Duhem Underdetermination

Quine Quine [1951] argued that "any statement can be held true come what may, if we make drastic enough adjustments elsewhere in the system." Duhem Duhem [1954] held that no physical hypothesis can be tested in isolation. Theorem 1 formalizes this: the configuration space is the space of theories, the observable space is empirical data, and the Rashomon property captures the existence of empirically adequate theories with incompatible explanations.

6.2 Economics: Partial Identification

Manski Manski [2003] developed partial identification theory for settings where observational data do not pin down a unique model. The identified set in Manski's framework corresponds to an observe-fiber in ours; partial identification is the economic instantiation of the Rashomon property.

6.3 Database Theory: View Update Problem

Bancilhon and Spyratos Bancilhon and Spyratos [1981] proved that translating updates on a database view back to the base tables is inherently ambiguous when the view is not injective. This is precisely our framework: the base tables are configurations, the view is the observation map, and the ambiguity is the Rashomon property.

6.4 Legal Interpretation: Statutory Ambiguity

When a statute admits multiple legally valid interpretations, each consistent with the legislative text (the "observable"), any judicial explanation faces the trilemma: be faithful to the chosen interpretation, stable across courts, and decisive in application. The impossibility applies whenever genuinely incompatible interpretations are legally valid.

6.5 Medical Diagnosis: Differential Diagnosis

When multiple conditions produce the same symptoms (the observable), diagnosis faces the trilemma. Differential diagnosis—the standard medical practice of listing all conditions consistent with the symptoms—is precisely G-invariant resolution: it sacrifices decisiveness (single diagnosis) for faithfulness and stability.

References

Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

François Bancilhon and Nicolas Spyratos. Update semantics of relational views. *ACM Transactions on Database Systems*, 6(4):557–575, 1981.

Tolga Bolukbasi, Kai-Wei Chang, James Zou, Venkatesh Saligrama, and Adam Kalai. Man is to computer programmer as woman is to homemaker? Debiasing word embeddings. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

David Maxwell Chickering. Optimal structure identification with greedy search. *Journal of Machine Learning Research*, 3:507–554, 2002.

Alexander D'Amour, Katherine Heller, Dan Moldovan, et al. Underspecification presents challenges for credibility in modern machine learning. *Journal of Machine Learning Research*, 23(226):1–61, 2022.

Pierre Duhem. *The Aim and Structure of Physical Theory.* Princeton University Press, 1954. English translation of the 1906 French original.

EU Parliament. Regulation (EU) 2024/1689 (artificial intelligence act). Official Journal of the European Union, OJ L, 12.7.2024, 2024.

Aaron Fisher, Cynthia Rudin, and Francesca Dominici. All models are wrong, but many are useful: Learning a variable's importance by studying an entire class of prediction models simultaneously. *Journal of Machine Learning Research*, 20(177):1–81, 2019.

Sara Hooker, Dumitru Erhan, Pieter-Jan Kindermans, and Been Kim. A benchmark for interpretability methods in deep neural networks. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

Sarthak Jain and Byron C Wallace. Attention is not explanation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, pages 3543–3556, 2019.

Amir-Hossein Karimi, Gilles Barthe, Borja Balle, and Isabel Valera. Algorithmic recourse under imperfect causal knowledge: a probabilistic approach. In *Advances in Neural Information Processing Systems*, volume 33, pages 265–277, 2020.

Tamera Lanham, Anna Chen, Ansh Radhakrishnan, Benoit Steiner, Carson Denison, Danny Hernandez, Dustin Li, Esin Durmus, Evan Hubinger, Jackson Kernion, Kamilé Lukićsić, Karina Nguyen, Nicholas Schiefer, Catherine Olsson, Tom Henighan, Hume Jones, Arthur Jermyn, Chris Olah, Dario Amodei, Ethan Perez, Jared Kaplan, and Jack Clark. Measuring faithfulness in chain-of-thought reasoning. *arXiv preprint arXiv:2307.13702*, 2023.

Charles F Manski. *Partial Identification of Probability Distributions.* Springer, 2003.

Maxime Meloux, Sander Bhatt, and Patrick Schwab. Everything, everywhere, all at once: Is mechanistic interpretability identifiable? In *International Conference on Learning Representations (ICLR)*, 2025.

National Institute of Standards and Technology. Artificial intelligence risk management framework (AI RMF 1.0). Technical Report NIST AI 100-1, U.S. Department of Commerce, 2023. URL `https://doi.org/10.6028/NIST.AI.100-1`.

Office of the Comptroller of the Currency. Supervisory guidance on model risk management (SR 11-7/OCC 2011-12). OCC Bulletin 2011-12, 2011.

Willard Van Orman Quine. Two dogmas of empiricism. *The Philosophical Review*, 60(1):20–43, 1951.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 7237–7256, 2020.

Cynthia Rudin et al. Position: Amazing things come from having many good models. In *International Conference on Machine Learning (ICML)*, 2024.

Lesia Semenova, Cynthia Rudin, and Ronald Parr. On the existence of simpler machine learning models. *ACM/IMS Journal of Data Science*, 2022.

Miles Turpin, Julian Michael, Ethan Perez, and Samuel R Bowman. Language models don't always say what they think: Unfaithful explanations in chain-of-thought prompting. *Advances in Neural Information Processing Systems*, 36, 2024.

Xi Ye and Greg Durrett. The unreliability of explanations in few-shot in-context learning. *Advances in Neural Information Processing Systems*, 35, 2022.