

Essential Mathematics: *Propositional Calculus & Predicate Calculus*

© Copyright of this lecture resides with C.E. Dickerson and S. Ji.
Reproduction is prohibited except with prior written consent.

Lecture 14

Loughborough University accepts no third party liability for the contents of this lecture
and gives no endorsement to any products, processes and services mentioned within.



1

A Fundamental Principle

- **Principle of Definition**
 - *One needs both a formal definition of a design for precision, and a prose definition for comprehensibility.**
- **Levels of Precision**
 - Formalisms (e.g. the Predicate Calculus) are the most precise.
 - Graphical languages can be more intuitive but may not be formal.
- **Models**
 - In software and systems engineering practices, a model is generally considered to be an abstraction that represents a system.
 - But the term *model* can also be given formal definitions.

*Brooks, *Mythical Man-Month*, p.234, 6.3. This is taken as the Third Principle of Architecture and Systems Engineering in EA&PSE. Refer to p.xxi.



2

2

The Significance for MBSE

- INCOSE regards the aim of MBSE to be a *formalised* application of modelling to support
 - System Requirements
 - Analysis and Design
 - Verification & Validation
- The extent of the formalisation in the application is limited by how formal the supporting models are!
- Any approach to MBSE in which the models are not founded on formal models will fall short of the aim.
- Models using logic and set theory are formal.

MBSE: Model Based Systems Engineering

Formal: having a recognized form, structure, or set of rules (see OED)



3

3

Overview

Key Concepts

*The need for both precision
and comprehension*

Logic as a formal language

*Logic as the basis for the
concept of Model*

Key Topics

- What is a Good Model?
- Propositional Calculus
- Circuit Example
 - Series
 - Parallel
- Predicate Calculus



4

4

Models in Science and Logic

- Stephen Hawking attributes a good model to be
 - Simple
 - Mathematically correct
 - Experimentally verifiable
- By analogy, a logical model of a natural language sentence¹ should be
 - Simple
 - Logically well-formed and consistent
 - Verifiable through logical interpretation²

¹The concept of logical modelling presented here is motivated by the meaning of models using the predicate calculus [see, e.g. J. L. Bell, *Models and Ultraproducts*]. Refer to the logical model of *system* in Lecture 24-02. See also ISO/IEC 24707:2018 – Common Logic.

² In mathematics, this is called the first order model theory of Tarski.



Languages and Methods of Mathematics, Science, and Engineering

- Mathematics uses
 - Formal logic (the predicate calculus) for description
 - Logical methods and mathematical induction for reasoning
- Science uses
 - Mathematics for description (but not as a formal language)
 - Models and experimental methods for reasoning
- Engineering uses
 - Science, mathematics for description and reasoning
 - Tools, prototypes, tests as methods for design and decision

A mathematical formalisation of systems engineering was consistently sought in the late 20th century.¹

¹ Refer to EA&PSE 1.1.1 for a brief history.



Overview

Key Concepts

*The need for both precision
and comprehension*

Logic as a formal language

*Logic as the basis for the
concept of Model*

Key Topics

- What is a Good Model?
- **Propositional Calculus**
- Circuit Example
 - Series
 - Parallel
- Predicate Calculus

First Order Formal Languages of Logic

- The logical languages of mathematical logic are the
 - Propositional Calculus¹
 - Predicate Calculus
- The term *calculus* derives from the Latin for calculation.
 - In logic, *Calculus* refers to the calculation of truth.
 - In the *Calculus* of Newton and Leibnitz, it refers to the calculation of limits.
- *Propositions* are declarative statements and are represented by [abstract] propositional variables.
- *Predicates* are statements of relationships between variables and are represented by [abstract] predicate letters and [abstract] individual variables.

¹ The Propositional Calculus is also called the Sentence Calculus.
It is the syntax of first order logic.

What is the Propositional Calculus?

- A formal language built from
 - Propositional variables
 - Logical connectives
 - Punctuation symbols
- Formalises that part of logic in which validity (truth)
 - Depends only on the truth values of the variables *and*
 - How propositions are assembled using connectives
 - Not on the internal meaning of the propositions

Propositional Formulae

- Propositional variables are denoted by p, q, \dots
- The logical connectives are
 - Not: \neg
 - And: \wedge
 - Or¹: \vee
- Punctuation symbols: $()$
- Examples of propositional formulae:

p q $\neg p$ $p \wedge q$ $p \vee q$

¹ This is the 'inclusive' Or (and is not exclusive).

Interpretation: Truth Values

Boolean rules are the basis of control logic

- Propositional formula are completely interpreted by
 - The truth values of the propositions involved
 - Boolean rules of logic
- The truth table to the right is sufficient to determine the truth value of any propositional formula.

p	q	$\neg p$	$p \wedge q$	$p \vee q$
T	T	F	T	T
T	F	F	F	T
F	T	T	F	T
F	F	T	F	F

Overview

Key Concepts

The need for both precision and comprehension


Logic as a formal language

Logic as the basis for the concept of Model

Key Topics

- What is a Good Model?
- Propositional Calculus
- Circuit Example
 - **Series**
 - **Parallel**
- Predicate Calculus


Series Circuits: Light Bulbs in Series



Class Exercise on Series Circuit

- Write a sentence in the propositional calculus that expresses the state of the circuit in terms of the state of the light bulbs.
- Use the sentence to reason about the circuit reliability in terms of the light bulb reliability.

Parallel Circuits: Light Bulbs in Parallel



Class Exercise on Parallel Circuit

- Write a sentence in the propositional calculus that expresses the state of the circuit in terms of the state of the light bulbs.
- Use the sentence to reason about the circuit reliability in terms of the light bulb reliability.

Overview

Key Concepts

The need for both precision and comprehension

Logic as a formal language

Logic as the basis for the concept of Model

Key Topics


- What is a Good Model?
- Propositional Calculus
- Circuit Example
 - Series
 - Parallel
- **Predicate Calculus**



What is a Predicate? Example of use cases for a system

Note that the System and <verb - noun> phrase always form a sentence.


Aircraft <request permission> from ATC.



Actor 1

(e.g. subject of verb)

System



ATC <provide service> to Airport.



Actor 2

(e.g. object for service)

A predicate is that part of a sentence containing a verb and stating something about the subject.



What is the Predicate Calculus?

- A formal language built from
 - Individual variables (denoted by lower case letters)
 - Symbols for constants (e.g., c)
 - Predicate letters (denoted by capital letters)
 - Logical connectives (to include equality, =)
 - Punctuation symbols
- Predicate letters are interpreted as relations
- It formalises that part of logic in which validity
 - Depends on how predicates are assembled
 - As well as on the internal meaning of the predicates (i.e. their interpretations)



19

19

Predicate Formulae

- Predicate variables are denoted by $u_1, u_2 \dots, v, \dots$
- Constants are denoted as $c_1, c_2 \dots, c$, etc.
- Predicate letters are denoted by P, Q, etc.
- The logical connectives are
 - Not: \neg
 - And: \wedge Or: \vee
- Quantifiers: Universal, Existential (see 'sentences')
- Examples of predicate formulae:

$P(u_1, u_2) \quad Q(v, c) \quad P(u_1, u_2) \wedge Q(v, c) \quad \neg P(u_1, u_2) \vee Q(v, c)$




20

20

Predicates, Relations and Relational Structures

- The predicates $P_1(u_1, c)$ and $P_2(u_1, u_2)$ represent relations; for example, the relations R_1 and R_2 where $u_1 \rightarrow x$, and $u_2 \rightarrow y$.
- The set of relations $\{R_1, R_2\}$ is a relational structure in the xy - plane
 - $x > 0$ is a relation in the xy - plane and $x < y$ is another
 - The intersection is the region below $y = x$ in Quadrants I, IV*
- The intersection is an *interpretation* of: $P_1(u_1, 0) \wedge P_2(u_1, u_2)$



*Note: this is how a feasible region is constructed in system design.



21

21

Sentences, Structures, and Models

- A *model* is typically considered to be an abstraction that represents something; *but in logic...*
 - There is a distinction between models and representations e.g., in UML, diagrams are *representations* of models; in the same way that the symbol 2 represents the concept of two
- In Tarski Model Theory* the concept of *Model* is precise:

A *model* is a relational structure for which the interpretation of a sentence becomes valid.

The *relational structure* is referred to as a *model of the sentence*.
- In the previous slide, the feasible region in the graph is a *model of the sentence*: for each $u_1, u_2 : P_1(u_1, 0) \wedge P_2(u_1, u_2)$

* This is also called First Order Model Theory because the predicates represent first order relations. It is adopted in ISO/IEC:24707.



22

22

Interpretation and Scope of Predicates

- If x were selected from the counting numbers (i.e. the values of x could be 1, 2, ...) then $R_1(x, 0)$ would be true.
- If x were selected from the positive real numbers and y from the negative ones then $R_2(x, y)$ would be true.
- But if x and y were both selected from the positive real numbers; the truth of $R_2(x, y)$ could only be decided based on specific values (instances) of x, y
- The truth of $R_1(x, 0)$ and $R_2(x, y)$ also depends on whether
 - *Every* value (instance) of x, y is considered or
 - Only *some* values (instances) of x, y are considered
 - This is why sentences in the Predicate Calculus use the universal and existential scope operators, i.e. for decidability

Questions?