



# B/S体系软件设计

胡晓军



- **B/S**开发基础
- **HTML/CSS/JavaScript**
- **PHP/Node.js/Python**
- **Java EE**
- **ASP.NET**
- **Client**技术的发展
- **Web**应用优化

- **HTML5与CSS3基础教程（第8版）**
  - **Elizabeth Castro / Bruce Hyslop**，望以文译
  - 人民邮电出版社
- **深入浅出Spring Boot 2.x**
  - 杨开振
  - 人民邮电出版社
- **Front-end Development with ASP.NET Core, Angular, Bootstrap**
  - **Simone Chiazza**
  - **Wrox**



- 完成一个大程



- **Internet**, 因特网, 互联网
- **Internet历史**
  - 20世纪60年代, **ARPA Net**
  - 20世纪80年代, **TCP/IP**
  - **1986, NSFNet**
  - 20世纪90年代, **Internet**开始迅速发展
- **Internet基础服务**
  - **WWW**
  - **Email**
  - **FTP**
  - **Telnet**




- 主机模式：
  - **all computation take place in the main computer, using dummy terminal**
- **C/S架构 (Client/Server)**
  - **most computation take place in the server, client is a computer carrying part computation**
- **B/S架构 (Browser/Server)**
  - **thin client, limited ability of client, using Web browser**



# B/S结构的优点

- 维护方便，能够降低总体拥有成本。
  - B/S比C/S的维护工作量大大减少了
  - B/S相对C/S能够降低总体拥有成本
- 选择更多
- 移动办公
- 系统整合





- **TCP/IP(Transmission Control Protocol/Internet Protocol)**

- 网络层: **IP, IPv4, IPv6**
- 传输层: **TCP(Transmission Control Protocol), UDP(User Datagram Protocol)**
- 应用层:

- ◆ **HTTP**

- ◆ **FTP**

- ◆ **SMTP**

- ◆ **Telnet**

- ◆ **DNS**

- ◆ **...**

- **IP地址和域名**





# World Wide Web (WWW)

- **Core Components**

- **Servers**

- ◆ **Store files and execute remote commands**

- **Browsers (i.e., clients)**

- ◆ **Retrieve and display “pages” of content linked by hypertext**

- **Networks**

- ◆ **Send information back and forth upon request**

- **Problems**

- **How to identify an object**

- **How to retrieve an object**

- **How to interpret an object**



- **URI (Uniform Resource Identifier)**

- **protocol://hostname:port/directory/object**
  - ◆ **http://www.cs.iastate.edu/index.html**
  - ◆ **ftp://popeye.cs.iastate.edu/welcome.txt**
  - ◆ **https://finance.yahoo.com/q/cq?s=ibm&d=v1**
- **Implementation: extend hierarchical namespace to include**
  - ◆ **anything in a file system**
  - ◆ **server side processing**

- **HTTP (Hyper Text Transfer Protocol)**

- **An application protocol for information sending/receiving**

- **HTML (Hypertext Markup Language)**

- **An language specification used to interpret the information receiving from server**



- **Request-response exchange**

- **Server runs over TCP, Port 80**
- **Client sends HTTP requests and gets responses from server**
- **Synchronous request/reply protocol**

- **Stateless**

- **No state is maintained by clients or servers across requests and responses**
- **Each pair of request and response is treated as an independent message exchange**

- **Resource metadata**

- **Information about resources are often included in web transfers and can be used in several ways**



- **GET**

- Transfer resource from given URL

- **HEAD**

- Get resource metadata (headers) only

- **PUT**

- Store/modify resource under a given URL

- **DELETE**

- Remove resource

- **POST**

- Provide input for a process identified by the given URL (usually used to post CGI parameters)




# HTTP Request Processing

- **The client**
  - 1. Contact its local DNS to find out the IP address of `www.cs.iastate.edu`**
  - 2. Initiate a TCP connection on port 80**
  - 3. Send the get request via the established socket**  
**GET /index.html HTTP/1.0**
- **The server**
  - 4. Send its response containing the required file**
  - 5. Tell TCP to terminate connection**
- **The browser**
  - 6. Parse the file and display it accordingly**
  - 7. Repeat the same steps in the presence of any embedded objects**



# HTTP/1.0 Example





# Response Code of HTTP 1.0

- **2xx success**
- **3xx redirection**
- **4xx client error in request**
- **5xx server error; can't satisfy the request**



# Server Response

```
HTTP/1.0 200 OK
Content-Type: text/html
Content-Length: 1234
Last-Modified: Mon, 19 Nov 2001 15:31:20 GMT
<HTML>
<HEAD>
<TITLE>CS Home Page</TITLE>
</HEAD>
...
</BODY>
</HTML>
```





# HTTP/1.0 Caching

- **A modifier to the GET request:**
  - **If-modified-since** – return a “not modified” response if resource was not modified since specified time
- **A response header:**
  - **Expires** – specify to the client for how long it is safe to cache the resource
- **A request directive:**
  - **No-cache** – ignore all caches and get resource directly from server



# Issues with HTTP/1.0

- **Each resource requires a new connection**
  - Large number of embedded objects in a web page
  - Many short lived connections
- **Serial vs. parallel connections**
  - Serial connection downloads one object at a time (e.g., MOSAIC) causing long latency to display a whole page
  - Parallel connection (e.g., NETSCAPE) opens several connections (typically 4) contributing to network congestion
- **HTTP uses TCP as the transport protocol**
  - TCP is not optimized for the typical short-lived connections
  - Most Internet traffic fit in 10 packets (overhead: 7 out of 17)
    - ◆ Too slow for small object
    - ◆ May never exit slow-start phase



# Highlights of HTTP/1.1

- **Persistent connections**
- **Pipelined requests/responses**
- **Support for virtual hosting**
- **More explicit support on caching**
- **Internet Caching Protocol (ICP)**
- **Content negotiation/adaptation**
- **Range Request**



# Persistent Connections

- **The basic idea was**

- **reducing the number of TCP connections opened and closed**
- **reducing TCP connection costs**
- **reducing latency by avoiding multiple TCP slow-starts**
- **avoid bandwidth wastage and reducing overall congestion**
  - ◆ **A longer TCP connection knows better about networking condition**


- **New GET methods**

- **GETALL**
- **GETLIST**



# Pipelined Requests/Responses

- **Buffer requests and responses to reduce the number of packets**
- **Multiple requests can be contained in one TCP segment**
- **Note: order of responses has to be maintained**
- **Question: why not just send the embedded objects right away without being asked?**






# Support for Virtual Hosting

- **Problem – outsourcing web content to some company**
  - <http://www.hostmany.com/A> ⇔ <http://www.A.com>
  - <http://www.hostmany.com/B> ⇔ <http://www.B.com>
- **In HTTP/1.0, a request for <http://www.A.com/index.html> has in its header only:**
  - GET /index.html HTTP/1.0
- **It is not possible to run two web servers at the same IP address, because GET is ambiguous**
- **HTTP/1.1 addresses this by adding “Host” header**

GET /index.html HTTP/1.1  
Host: www.A.com




# HTTP 2演进





# HTTP 2.0

- **Binary instead of textual**
- **Fully multiplexed instead of ordered and blocking**
- **Use one connection for parallelism**
- **Uses header compression to reduce overhead**
- **Allows servers to “push” responses proactively into client caches**








# HTTP 2 Data Flow


## HTTP 2.0 connection



- **Streams are multiplexed by splitting communication into frames**
  - Frames are sent over single TCP connection
- **Frames are interleaved**
  - Frames are prioritized
  - Frames are flow controlled



# HTTP 2 Push



- HTTP 2 Server Push is cacheable
- Client may cancel by sending RST\_STREAM frame



# HTTP 2 Header Compression

*Request headers*

:method	GET
:scheme	https
:host	example.com
:path	/resource
user-agent	Mozilla/5.0 ...
custom-hdr	some-value



*Static table*

1	:authority	
2	:method	GET
...	...	...
51	referer	
...	...	...
62	user-agent	Mozilla/5.0 ...
63	:host	example.com
...	...	...

*Dynamic table*




*Encoded headers*

2	
7	
63	
19	Huffman("/resource")
62	
	Huffman("custom-hdr")
	Huffman("some-value")



# 基本Web服务器





- **Hyper-Text Markup Language**
  - **Hyper-Text Transport Protocol**
  - **Cascading Style Sheet**
- 
- **XML**




# Client side script/program

- **JavaScript**
- **VBScript**
- **Java Applet**
- **ActiveX**



# CGI(Common Gateway Interface)





# Better CGI

- **FastCGI**
- **Java Servlet**





# Server side module

- **NSAPI**
- **ISAPI**
- **Apache: mod\_perl**



# Server side script

- **Server Side Include**
- **PHP**
- **Active Server Pages**
- **Java Server Pages**



- **Client:**

- **HTML/CSS**

- **JavaScript**

- **Server**

- **PHP**

- **JSP**

- **Java Servlet**

- **ASP.NET**



- **IIS**

- 安装
- 配置
- 运行控制

- **Nginx**

- 安装
- 配置
- 运行控制

- **其他**

- **Java EE**应用服务器