

18 JavaBeans and Bean Events




What is JavaBean?

A JavaBeans component is a **serializable public class with a public no-arg constructor**.

Javabeans就是一个普通的java类，但符合某种特定规范。使用Javabeans的好处是解决代码重复编写，功能区分明确，提高了代码的可维护性。

遵循某种设计原则



What is JavaBean?

//设计学生类

public class Students

{

private String name;

private int age;

public Students()

{}

public void setName(String name) {this.name=name;}

public String getName() {return this.name;}


public void setAge(int age) {this.age = age;}

public int getAge() {return this.age;}

}

What is JavaBean?

Every GUI class is a JavaBeans component, because (1) it is a public class; (2) it has a public no-arg constructor; (3) It is an extension of `java.awt.Component`, which implements `java.io.Serializable`.



Why JavaBeans?

The JavaBeans technology was developed to **enable the programmers to rapidly build applications by assembling objects and test them during design time**, thus **making reuse of the software more productive**.

JavaBeans is a software component architecture that extends the power of the Java language by enabling well-formed objects to be manipulated visually at design time in a pure Java builder tool, such as JBuilder and NetBeans.



JavaBeans and Builder Tools

NOTE: This chapter does not require that you use any builder tools. If you are interested to use JavaBeans in rapid Java application development using JBuilder or Sun ONE Studio, please refer to Supplement I, “*Rapid Java Application Development Using JBuilder*” or Supplement J, “*Rapid Java Application Development Using Sun ONE Studio*,” on the companion Website.



JavaBeans Properties and Naming Patterns

- ➡ The get method is named

`get<PropertyName>()`,

which takes no parameters and returns an object of the type identical to the property type.

- ➡ For a property of boolean type, the get method should be named

`is<PropertyName>()`,

which returns a boolean value.

- ➡ The set method should be named

`set<PropertyName>(newValue)`,

which takes a single parameter identical to the property type and returns void.



Properties and Data Fields

Properties describe the state of the bean. Naturally, data fields are used to store properties. However, **a bean property is not necessarily a data field**. For example, in the MessagePanel class in Example 12.5 in Chapter 13, you may create a new property named `messageLength` that represents the number of the characters in message. The get method for the property may be defined as follows:

```
public int getMessageLength() {  
    return message.length();  
}
```

NOTE: A property may be read-only with a get method but no set method, or write-only with a set method but no get method.



Bean Events

A bean may communicate with other beans. The **Java event delegation model** provides the foundation for beans to send, receive, and handle events. When something happens to a bean, such as a mouse click on a `javax.swing.JButton` bean, **an event object is created to encapsulate information pertaining to the event.** The bean passes the event object to the interested beans for the event to be processed.

Events are typically **generated** by Java GUI components, such as `javax.swing.JButton`, but are not limited to GUI components. This section introduces the development of custom events and the beans that can generate events.

The Event Delegation Model

事件委托模型





Figure 15.3



Predefined Event Pairs

(Event Classes and Listener Interface)




Examples:


ActionEvent/ActionListener

AdjustmentEvent/AdjustmentListener

Examples of Event Pairs




Source Components



The source component detects events and processes the events by invoking the event listeners' handler.



Listener Components



The listener is registered with the source, and the source invokes the listener's handler to process the event.

Creating Custom Source Components

Unicast Registration Methods:

A source component must have the appropriate registration and deregistration methods for adding and removing listeners.

Events can be **unicasted** (only one object is notified of the event) or **multicasted** (each object in a list of listeners is notified of the event). The naming pattern for adding a unicast listener is

```
public void add<Event>Listener(<Event>Listener l)  
    throws TooManyListenersException;
```



Creating Custom Source Components

Multicast Registration Methods:

The naming pattern for adding a **multicast** listener is the same, **except that it does not throw the TooManyListenersException.**

```
public void add<Event>Listener(<Event>Listener l)
```

The naming pattern for removing a listener (either unicast or multicast) is:

```
public void remove<Event>Listener(<Event>Listener l)
```

A source component contains the code that creates an event object and passes it to the listening components by calling a method in the listener's event listener interface. You may use a standard Java event class like `ActionEvent` to create event objects or may define your own event classes if necessary.

Example: Creating a Source Component

CourseWithActionEvent

-courseName: String
-students: ArrayList<String>
-enrollmentCap: int

The name of the course.

The students who take the course.

The maximum enrollment (default: 10).

+CourseWithActionEvent()
+CourseWithActionEvent(courseName: String)
+getCourseName(): String
+addStudent(student: String): void
+getStudents(): String[]
+getNumberOfStudents(): int
+getEnrollmentCap(): int

Creates a default course.

Creates a course with the specified name.

Returns the course name.

Adds a new student to the course list.

Returns the students for the course as an array.

Returns the number of students for the course.

Returns the enrollment cap.

+setEnrollmentCap(enrollmentCap: int): void

Sets a new enrollment cap.

+addActionListener(e: ActionEvent): void

Adds a new ActionEvent listener.

+removeActionListener(e: ActionEvent): void

Deletes an ActionEvent listener.

-processEvent(e: ActionEvent): void

Processes an ActionEvent.

CourseWithActionEvent

TestCourseWithActionEvent

TestCourseWithActionEvent

```
public class CourseWithActionEvent {  
    private String courseName = "default name";  
    private ArrayList<String> students = new ArrayList<String>();  
    private int enrollmentCap = 10;  
    private ArrayList<ActionListener> actionListenerList;
```

```
    public CourseWithActionEvent() {  
    }
```

```
    public CourseWithActionEvent(String courseName) {  
        this.courseName = courseName;  
    }
```

```
    public String getCourseName() {  
        return courseName;  
    }
```

```
    public void addStudent(String student) {  
        if (students.size() >= enrollmentCap) // Fire ActionEvent  
            processEvent(new ActionEvent(this,  
                ActionEvent.ACTION_PERFORMED, null));
```

```
        else  
            students.add(student);  
    }
```

```
    public ArrayList<String> getStudents() {  
        return students;  
    }
```

```
    public int getNumberOfStudents() {  
        return students.size();  
    }
```

```
    public int getEnrollmentCap() {  
        return enrollmentCap;  
    }
```

```
    public void setEnrollmentCap(int enrollmentCap) {  
        this.enrollmentCap = enrollmentCap;  
    }
```



```

/** Register an action event listener */
public synchronized void addActionListener
(ActionListener listener) {
    if (actionListenerList == null) {
        actionListenerList = new ArrayList<ActionListener>(2);
    }

    if (!actionListenerList.contains(listener)) {
        actionListenerList.add(listener);
    }
}

/** Remove an action event listener */
public synchronized void removeActionListener
(ActionListener listener) {
    if (actionListenerList !=
        null && actionListenerList.contains(listener)) {
        actionListenerList.remove(listener);
    }
}

```

```

/** Fire ActionEvent */
private void processEvent(ActionEvent e) {
    ArrayList<ActionListener> list;

    synchronized (this) {
        if (actionListenerList == null) return;
        list = (ArrayList<ActionListener>)actionListenerList.clone();
    }


    for (int i = 0; i < list.size(); i++) {
        ActionListener listener = (ActionListener)list.get(i);
        listener.actionPerformed(e);
    }
}

```



```
public class TestCourseWithActionEvent {  
    CourseWithActionEvent course =  
        new CourseWithActionEvent("Java Programming");  
  
    public TestCourseWithActionEvent() {  
        course.setEnrollmentCap(2);  
        ActionListener listener = new Listener();  
        course.addActionListener(listener);  
        course.addStudent("John");  
        course.addStudent("Jim");  
        course.addStudent("Tim");  
    }  
  
    public static void main(String[] args) {  
        new TestCourseWithActionEvent();  
    }  
  
    private class Listener implements ActionListener {  
        @Override  
        public void actionPerformed(ActionEvent e) {  
            System.out.println("Enrollment cap exceeded");  
        }  
    }  
}
```


Interaction Between Source and Listener Components



The listener is registered with the source course, and the source invokes the listener's handler `actionPerformed` to process the event.

Example: Creating a Custom Event Set

Problem: This example creates a **custom** event named EnrollmentEvent for describing enrollment events, and its corresponding listener interface EnrollmentListener for defining an enrollmentExceeded handler.



```
public class EnrollmentEvent extends java.util.EventObject {
    private String studentToEnroll;
    private int enrollmentCap;

    /** Construct a EnrollmentEvent */
    public EnrollmentEvent(Object source, String studentToEnroll,
        int enrollmentCap) {
        super(source);
        this.studentToEnroll = studentToEnroll;
        this.enrollmentCap = enrollmentCap;
    }

    public String getStudentToEnroll() {
        return studentToEnroll;
    }

    public long getEnrollmentCap() {
        return enrollmentCap;
    }
}
```

```
1 public interface EnrollmentListener extends java.util.EventListener {
2     /** Handle an EnrollemntEvent, to be implemented by a listener */
3     public void enrollmentExceeded(EnrollmentEvent e);
4 }
5
```

```

public class CourseWithEnrollmentEvent {
    private String courseName = "default name";
    private ArrayList<String> students = new ArrayList<String>();
    private int enrollmentCap = 10;
    private ArrayList<EnrollmentListener> enrollmentListenerList;

    public CourseWithEnrollmentEvent() {
    }

    public CourseWithEnrollmentEvent(String courseName) {
        this.courseName = courseName;
    }

    public String getCourseName() {
        return courseName;
    }

    public void addStudent(String student) {
        if (students.size() == enrollmentCap) // Fire EnrollmentEvent
            processEvent(new EnrollmentEvent(this,
                student, enrollmentCap));
        else
            students.add(student);
    }

    public ArrayList<String> getStudents() {
        return students;
    }

    public int getNumberOfStudents() {
        return students.size();
    }

    public int getEnrollmentCap() {
        return enrollmentCap;
    }

    public void setEnrollmentCap(int enrollmentCap) {
        this.enrollmentCap = enrollmentCap;
    }
}

```




```

/** Register an action event listener */
public synchronized void addEnrollmentListener
    (EnrollmentListener listener) {
    if (enrollmentListenerList == null) {
        enrollmentListenerList = new ArrayList<EnrollmentListener>(2);
    }

    if (!enrollmentListenerList.contains(listener)) {
        enrollmentListenerList.add(listener);
    }
}

/** Remove an action event listener */
public synchronized void removeEnrollmentListener
    (EnrollmentListener listener) {
    if (enrollmentListenerList !=
        null && enrollmentListenerList.contains(listener)) {
        enrollmentListenerList.remove(listener);
    }
}

/** Fire EnrollmentEvent */
private void processEvent(EnrollmentEvent e) {
    ArrayList<EnrollmentListener> list;

    synchronized (this) {
        if (enrollmentListenerList == null) return;
        list = (ArrayList<EnrollmentListener>)
            enrollmentListenerList.clone();
    }

    for (int i = 0; i < list.size(); i++) {
        EnrollmentListener listener = (EnrollmentListener)list.get(i);
        listener.enrollmentExceeded(e);
    }
}

```



```
public class TestCourseWithEnrollmentEvent {  
    CourseWithEnrollmentEvent course =  
        new CourseWithEnrollmentEvent("Java Programming");  
  
    public TestCourseWithEnrollmentEvent() {  
        course.setEnrollmentCap(2);  
        EnrollmentListener listener = new NewListener();  
        course.addEnrollmentListener(listener);  
        course.addStudent("John Smith");  
        course.addStudent("Jim Peterson");  
        course.addStudent("Tim Johnson");  
    }  
  
    public static void main(String[] args) {  
        new TestCourseWithEnrollmentEvent();  
    }  
  
    private class NewListener implements EnrollmentListener {  
        public void enrollmentExceeded(EnrollmentEvent e) {  
            System.out.println(e.getStudentToEnroll() + " attempted to "  
                + "enroll. The enrollment cap is " + e.getEnrollmentCap());  
        }  
    }  
}
```




Creating Custom Event Pairs

You have already used [event sets](#) (e.g., `ActionEvent/ActionListener`) and [event source components](#) (`JButton`) in Java GUI programming. You can create your own event sets and source components.

A custom event class must extend [java.util.EventObject](#) or a subclass of [java.util.EventObject](#). Additionally, it may provide constructors to create events, data members and methods to describe the event.

A custom event listener interface must extend [java.util.EventListener](#) or a subinterface of [java.util.EventListener](#), and define the signature of the handlers for the event. By convention, the listener interface should be named `<Event>Listener` for the corresponding event class named `<Event>`.




Example: Source Component Using Custom Event Pairs

CourseWithEnrollmentEvent

TestCourseWithEnrollmentEvent



Interaction Between Source and Listener Components



The listener is registered with the source course, and the source invokes the listener's handler `enrollmentExceeded` to process the event.

```

@SuppressWarnings("serial")
public class JButton extends AbstractButton implements Accessible {

    /**|

public abstract class AbstractButton extends JComponent implements ItemSelectable, Sw

public abstract class JComponent extends Container implements Serializable,
                                TransferHandler.HasGetTransferHandler
{
    /**|

    /** A list of event listeners for this component. */
    protected EventListenerList listenerList = new EventListenerList();|

```



AbstractButton

```
/**
 * Adds a ChangeListener to the button.
 * @param l the listener to be added
 */
```

```
public void addChangeListener(ChangeListener l) {
    listenerList.add(ChangeListener.class, l);
}
```

```
/**
 * Removes a ChangeListener from the button.
 * @param l the listener to be removed
 */
```

```
public void removeChangeListener(ChangeListener l) {
    listenerList.remove(ChangeListener.class, l);
}
```

```
protected void fireStateChanged() {
    // Guaranteed to return a non-null array
    Object[] listeners = listenerList.getListenerList();
    // Process the listeners last to first, notifying
    // those that are interested in this event
    for (int i = listeners.length-2; i>=0; i-=2) {
        if (listeners[i]==ChangeListener.class) {
            // Lazily create the event:
            if (changeEvent == null)
                changeEvent = new ChangeEvent(this);
            ((ChangeListener)listeners[i+1]).stateChanged(changeEvent);
        }
    }
}
```

```

public void addActionListener(ActionListener l) {
    listenerList.add(ActionListener.class, l);
}

/**
 * Removes an <code>ActionListener</code> from the button.
 * If the listener is the currently set <code>Action</code>
 * for the button, then the <code>Action</code>
 * is set to <code>null</code>.
 *
 * @param l the listener to be removed
 */
public void removeActionListener(ActionListener l) {
    if ((l != null) && (getAction() == l)) {
        setAction(null);
    } else {
        listenerList.remove(ActionListener.class, l);
    }
}

protected void fireActionPerformed(ActionEvent event) {
    // Guaranteed to return a non-null array
    Object[] listeners = listenerList.getListenerList();
    ActionEvent e = null;
    // Process the listeners last to first, notifying
    // those that are interested in this event
    for (int i = listeners.length-2; i>=0; i-=2) {
        if (listeners[i]==ActionListener.class) {
            // Lazily create the event:
            if (e == null) {
                String actionCommand = event.getActionCommand();
                if (actionCommand == null) {
                    actionCommand = getActionCommand();
                }
                e = new ActionEvent(AbstractButton.this,
                                   ActionEvent.ACTION_PERFORMED,
                                   actionCommand,
                                   event.getWhen(),
                                   event.getModifiers());
            }
            ((ActionListener)listeners[i+1]).actionPerformed(e);
        }
    }
}

```

