

# 04. More Shell Commands, Keyboard Shortcuts, Live Code

CPSC 120: Introduction to Programming  
Kevin A. Wortman ~ CSU Fullerton

# Agenda

0. Sign-in sheet
1. Q&A
2. More Shell Commands
3. Keyboard Shortcuts
4. Live Code

# 1. Q&A

# Q&A

Let's hear your questions about...

- This week's Lab
- Linux
- Any other issues

Reminder: write these questions in your notebook during lab

## 2. More Shell Commands

# code

\$ code [FILE...]

- [VS Code](#): text editor
- Starts VS Code
- Each FILE... is opened in a tab

# rm

```
$ rm [OPTION...] FILE...
```

- rm: **ReMove** regular file
- by default, only deletes regular files (not directories)
- to delete directories, add the -Rf option:

```
$ rm -Rf lab-5-directory
```

- -R: **recursive**; enter a directory, and its directories, and its directories...
- -f: **force**; delete hidden files, esp. git metadata

# echo \$?

```
$ echo $?
```

- Prints the **exit code** of the previous command
- 0 means success
- Positive or negative number means failure



# clang++

```
$ clang++ [OPTION...] SOURCE
```

- clang++: open source C++ compiler
- SOURCE must be a path to a C++ source file
  - usually ends in .cc
- Tries to compile SOURCE
  - On failure, clang++ prints **messages** describing **syntax errors** or **warnings** (problems)
  - On success, creates an executable object code program named **a.out**
- (There are many OPTIONS to clang++ that we'll cover later.)

# Running your program; ./a.out

\$ ./PROG

- tldr; the command is **./a.out**
- To run a program
  - The command name is the path of the executable object code program file
  - For technical reasons, this must begin with a directory name
  - To run program **PROG** in the current directory, run **./PROG**
- The clang++ command on the previous slide creates program **a.out**
- To run it, use command

\$ **./a.out**

# 3. Keyboard Shortcuts

# Review: Shell and Terminal

- **Shell:** a special Unix program that allows a user (you) to run and interact with other programs
- **Terminal:** a thing that lets you see shell input/output
  - Physical terminal: monitor, keyboard, connection to real computer
  - Terminal emulator: program that simulates a physical terminal
- **Prompt:** when the shell is waiting for a command, It prints a “prompt” ending in \$ (dollar sign)
- You type a **command**, then the Enter key to run the command
- Unix programs are **concise**: if everything worked, there is no stdout output



# Review: Keyboard-First Principle

- Humans can type faster than they can click
- Excessive mouse moving causes Repetitive Stress Injury
  - RSI, Carpal Tunnel Syndrome
- **Keyboard-First Principle:** using keyboard is better than mouse

# Cannot Move Cursor by Clicking

- Terminal does not have a mouse!
- Cannot click to move cursor
- Instead, use keyboard shortcuts

# Keyboard Shortcuts

- **Tab:** if possible, **autocomplete**
  - tap twice to show possible completions
- **Left/Right** arrow: move cursor one character
- **CTRL+A:** move cursor to **beginning** of command
- **CTRL+E:** move cursor to **end** of command
- **Up/Down** arrow: scroll through command **history**
- **CTRL+Shift+C:** copy
- **CTRL+SHIFT+V:** paste


## 4. Live Code




# Live Code

- Interactive
- Instructor: **driver**
- Students: **navigators**
- Today:
  - Practice categorizing errors
  - [Pingo](#) survey


# The Development Cycle




# Review: Choose Tool Flowchart




# Preview: Debug Flowchart




# Preview: Debug command error flowchart



# Preview: Debug compile error flowchart



# Preview: Steps for Solving a Programming Problem



# Prompt: Fancy Tip Calculator

- INPUT: subtotal of a restaurant bill
- OUTPUT: print out tax, tip, and total
- Sales tax = 7.75%
- Tip = 20%
- Total = subtotal + sales tax + tip