Q-FUSION: Adaptive Classical-Quantum Representation Allocation under Severe Resource Constraints for Multimodal Brain Tumour Segmentation

Jonath Jimmi[1*] and Co-Author Placeholder[1]

[1*]Department of Information Technology, Manipal Institute of Technology Bengaluru, Manipal Academy of Higher Education, Bengaluru, 560064, Karnataka, India.

*Corresponding author(s). E-mail(s): jonath.jimmi@learner.manipal.edu;
Contributing authors: coauthor@placeholder.edu;

Abstract

Hybrid classical-quantum machine learning (QML) models for medical image analysis frequently confront three fundamental bottlenecks: classical gradient collapse where gating routers degenerate into purely classical pathways, the spatial reconstruction paradox where severe quantum latent constraints destroy high-resolution anatomical boundaries, and the absence of parameter-matched classical controls. In this work, we present Q-FUSION, an adaptive classical-quantum architecture designed to operate under strict latent-dimension and variational circuit constraints. To resolve classical collapse, we introduce an annealed regularized routing objective that balances early quantum-classical pathway exploration before converging to sample-dependent allocation. To resolve the spatial reconstruction paradox, we formulate quantum-conditioned spatial modulation via Feature-wise Linear Modulation (FiLM), allowing compact 8-dimensional quantum state measurements to modulate high-resolution 3D convolutional feature maps without high-dimensional unflattening layers. To eliminate parameter count confounders, all quantum variational circuits are paired with capacity-matched classical surrogate transformations achieving strict 0.0000% capacity variance. We evaluate Q-FUSION across two cohorts: 150 patients from the multi-sequence BraTS2021 benchmark across one to four physical imaging sequences (T1, T1ce, T2, FLAIR) and 181 patients from the SynthRAD2023 cross-modality benchmark (MRI and CT). On BraTS2021, when input complexity expands to full quad-modal imaging ($\boldsymbol{M = 4}$), classical baseline pooling degrades by 4.41% in Dice

Similarity Coefficient (DSC) due to cross-modal feature dilution, whereas adaptive routing maintains 0.7015 DSC (+4.79% over the classical baseline) through dynamic representation reallocation ($\bar{\boldsymbol{\alpha}} = \mathbf{0.4883}$). Under multi-seed evaluation on SynthRAD2023, adaptive routing achieves a +2.47% mean DSC advantage over rigid quantum fusion ($\mathbf{0.8039 \pm 0.0945}$ vs. $\mathbf{0.7792 \pm 0.1011}$). Furthermore, under simulated physical gate depolarizing noise ($\boldsymbol{p} \in [\mathbf{0.000, 0.050}]$), adaptive routing limits zero-shot degradation to 0.01% DSC compared to a monotonic 0.32% loss in rigid quantum architectures. Our findings demonstrate that adaptive classical-quantum routing provides architectural resilience against cross-modal interference and NISQ hardware noise under identical resource constraints.

Keywords: Quantum Machine Learning, Multimodal Medical Imaging, Brain Tumour Segmentation, Adaptive Routing, FiLM Modulation, NISQ Fault-Resilience

1 Introduction

Variational quantum algorithms and hybrid quantum-classical neural networks have emerged as candidate frameworks for extracting complex representations from high-dimensional data [1, 2]. In medical imaging, multimodal volumetric acquisitions—such as multi-parametric magnetic resonance imaging (MRI) and computed tomography (CT)—provide complementary tissue properties indispensable for accurate diagnosis and tumour delineation [3, 4]. However, deploying parameterised quantum circuits (PQCs) within 3D medical vision pipelines exposes severe structural limitations. Contemporary noisy intermediate-scale quantum (NISQ) devices restrict processing to modest qubit counts ($N \leq 12$) and shallow circuit depths ($L \leq 5$) to avoid unmitigated decoherence and barren plateaus [5–7].

When a high-dimensional 3D medical volume is compressed to fit the narrow input bandwidth of a quantum circuit, two competing failures typically manifest. First, if the network attempts to reconstruct voxel-level segmentations directly from low-dimensional quantum state measurements, fine boundary information is irreversibly destroyed—a phenomenon we define as the *spatial reconstruction paradox*. Prior works frequently circumvented this issue by inserting high-capacity classical projection layers (often exceeding 200,000 parameters) after the quantum circuit. Such designs obscure whether reported performance gains originate from quantum representation utility or simply unconstrained classical capacity.

Second, when classical and quantum branches are fused through fixed, static combination ratios (e.g., 50/50 concatenation), optimization dynamics frequently degrade. Classical neural network layers propagate smooth, high-magnitude gradients, whereas quantum expectation measurements exhibit higher variance and susceptibility to hardware noise. In unregularized gating schemes, the routing mechanism rapidly degenerates to 100% classical processing and 0% quantum processing—a failure mode termed *classical collapse*. Conversely, rigid 100% quantum processing forces all representations through noisy, restricted quantum bottlenecks, degrading performance when input dimensionality or modality complexity increases.

In this work, we propose **Q-FUSION**, an adaptive classical-quantum fusion framework designed to operate under strict parameter and quantum-resource constraints. Rather than claiming unconditional quantum computational advantage, we investigate a concrete scientific hypothesis: *Can a dynamic, trainable gating router learn to allocate computational representations between classical and quantum pathways to preserve complementary multimodal information, while spatial modulation shields volumetric reconstruction from severe quantum bottleneck constraints?*

The contributions of this study are structured as follows:

1. **Resolution of Classical Collapse via Annealed Routing:** We introduce a piecewise linear annealed routing penalty that explicitly enforces pathway exploration during early training epochs before allowing the gating scalar $\alpha(x) \in [0, 1]$ to settle on an equilibrium allocation.
2. **Quantum-Conditioned Spatial Modulation:** To bypass the spatial reconstruction paradox without high-capacity unflattening layers, we implement Feature-wise Linear Modulation (FiLM) [8]. Compact 8-dimensional quantum state measurements modulate classical 3D feature maps through affine scaling and shifting parameters, preserving spatial geometry in the classical CNN while incorporating global quantum conditioning.
3. **Strict Capacity-Matched Classical Controls:** We design parameter- and capacity-matched classical surrogate transformations possessing identical weight counts (24 parameters) and identical value bounds ($[-1, 1]$), ensuring exact 0.0000% capacity variance between classical-quantum and classical-classical architectures.
4. **Empirical Multi-Modality Scaling on BraTS2021:** On a standardized 150-patient cohort from BraTS2021 [9], we evaluate scaling across $M \in \{1, 2, 3, 4\}$ physical MRI sequences (T1, T1ce, T2, FLAIR). We demonstrate that at $M = 4$, classical pooling suffers a 4.41% DSC degradation due to feature dilution, whereas adaptive routing maintains representation stability (+4.79% DSC over classical baselines) through automated routing rebalancing.
5. **NISQ Hardware Noise Characterization:** We benchmark open-system gate depolarizing noise ($p \in [0.000, 0.050]$) on density-matrix simulators, demonstrating that adaptive routing provides structural buffering against physical hardware decoherence.

2 Related Work

2.1 Quantum Machine Learning and Variational Circuits

Parameterized quantum circuits (PQCs) represent the predominant approach for implementing machine learning models on near-term NISQ hardware [1, 5]. In variational quantum classifiers, classical data vectors are mapped into quantum Hilbert spaces using non-linear feature maps, such as angle embedding or amplitude embedding [2]. The quantum state is subsequently transformed via parameterized single-qubit rotations and multi-qubit entangling operations (e.g., CNOT or CZ gates) before terminal measurement of Pauli observables yields classical expectation values. Pérez-Salinas et al. [10] introduced the data re-uploading paradigm, demonstrating

that interleaving data encoding layers with parameterized unitary operations dramatically expands circuit expressivity without requiring exponential qubit scaling. However, training deep variational circuits remains constrained by barren plateaus—regions in the parameter space where cost function gradients vanish exponentially with system size [6]—and noise-induced barren plateaus arising from environmental decoherence [7].

2.2 Hybrid Classical-Quantum Architectures in Medical Imaging

Recent efforts have explored hybrid models combining classical convolutional neural networks (CNNs) with quantum bottlenecks for 2D and 3D medical image segmentation and classification [11]. In typical hybrid pipelines, classical encoders compress volumetric inputs down to low-dimensional latent vectors, which are then processed by a quantum circuit before entering a task-specific head. A recurring vulnerability across existing literature is the lack of parameter-matched classical controls. When a quantum circuit is evaluated without comparison against an equally parameterized classical nonlinear transformation, reported performance gains cannot be rigorously isolated to quantum representation properties rather than arbitrary hyperparameter tuning. Furthermore, static fusion mechanisms (such as fixed concatenation or static averaging) fail to account for heteroskedastic noise and varying information density across different patient scans.

2.3 Multimodal Representation and Feature Modulation

In neuro-oncology, standard clinical imaging protocols acquire multiple complementary modalities [3, 9]. For instance, T1-weighted MRI provides high structural contrast, T2-weighted and FLAIR sequences delineate edema and peritumoural infiltration, and T1-weighted contrast-enhanced (T1ce) scans highlight hypervascular active tumour regions. Combining multiple volumetric modalities introduces the challenge of modality interference: as supplementary input channels are incorporated into a fixed-capacity network, redundant or conflicting feature distributions can dilute salient anatomical signals. To integrate conditioning signals without unflattening low-dimensional vectors into spatial volumes, Feature-wise Linear Modulation (FiLM) [8] applies affine transformations directly to intermediate convolutional feature maps:

$$F' = \gamma(z) \odot F + \beta(z) \tag{1}$$

where γ and β generate channel-wise scaling and shifting vectors based on a conditioning representation z. FiLM has been successfully applied to visual reasoning and conditional generation; in this work, we demonstrate its utility as a mathematical bridge connecting compact quantum representations with high-resolution 3D convolutional feature maps.

3 Methodology

The overall architecture of Q-FUSION is illustrated in Figure 1.




Fig. 1 The Q-FUSION architecture. Volumetric multimodal inputs $X \in \mathbb{R}^{B\times M\times 64\times 64\times 64}$ are processed through a weight-shared 3D CNN encoder to extract modality-invariant spatial representations F_m, aggregated via mean pooling. A trainable gating router $\mathcal{R}$ regularized by an annealed exploration penalty computes a dynamic allocation scalar $\alpha(x) \in [0, 1]$ balancing the 24-parameter variational quantum circuit against a 24-parameter capacity-matched classical surrogate (0.0000% parameter variance). The blended bottleneck representation z' modulates the unflattened 3D spatial feature map via FiLM, preserving anatomical spatial geometry for 3D segmentation without high-capacity unflattening layers.

The network consists of four coordinated components: (1) an M-channel parameter-invariant 3D CNN encoder, (2) parallel classical surrogate and variational quantum bottlenecks, (3) a dynamic classical-quantum gating router regularized by an annealed exploration penalty, and (4) a quantum-conditioned 3D spatial modulation decoder.

3.1 Multimodal 3D Encoding and Channel Aggregation

Let $X \in \mathbb{R}^{B\times M\times D\times H\times W}$ denote a batch of B patient scans comprising M co-registered volumetric modalities (where $M \in \{1, 2, 3, 4\}$). To enforce exact parameter invariance across arbitrary modality combinations, all M channels are processed through a single, weight-shared 3D convolutional encoder $\mathcal{E}_{\text{cnn}}$:

$$F_m = \mathcal{E}_{\text{cnn}}(X[:, m : m + 1]), \quad m \in \{1, \ldots, M\} \tag{2}$$

where $F_m \in \mathbb{R}^{B\times C\times D'\times H'\times W'}$ represents the spatial feature map for modality m, with channel dimension $C = 32$ and downsampled spatial resolution $8 \times 8 \times 8$.

The M spatial representations are aggregated via channel-wise mean pooling:

$$F = \frac{1}{M} \sum_{m=1}^{M} F_m \in \mathbb{R}^{B \times 32 \times 8 \times 8 \times 8} \tag{3}$$

Global average spatial pooling is subsequently applied to extract a compact multimodal summary vector:

$$z_{\text{pool}} = \text{AdaptiveAvgPool3D}(F) \in \mathbb{R}^{B \times 32} \tag{4}$$

A linear compression projection maps z_{pool} to the input vector $z_{\text{comp}} \in \mathbb{R}^{B \times 24}$ required by the parallel bottlenecks.

3.2 Quantum Bottleneck: Sequential Data Re-uploading

The quantum pathway comprises an N-qubit parameterized circuit with L sequential data re-uploading layers [10]. In our canonical configuration ($N = 8$ qubits, $L = 3$ layers), the input vector $z_{\text{comp}} \in \mathbb{R}^{24}$ is partitioned into three 8-dimensional chunks $z_{\text{comp}}^{(l)} \in \mathbb{R}^8$ for $l \in \{1, 2, 3\}$. At each layer l, the features are embedded via parameterized Pauli-Y rotations:

$$U_{\text{enc}}(z_{\text{comp}}^{(l)}) = \bigotimes_{j=0}^{N-1} R_y \left(z_{\text{comp},j}^{(l)} \right) \tag{5}$$

Following data encoding, a parameterized entangling block transforms the register:

$$U_{\text{ent}}(\theta^{(l)}) = \left(\prod_{j=0}^{N-1} \text{CNOT}_{(j,(j+1) \bmod N)} \right) \left(\bigotimes_{j=0}^{N-1} R_y \left(\theta_j^{(l)} \right) \right) \tag{6}$$

where $\theta \in \mathbb{R}^{3 \times 8}$ denotes the trainable quantum weight tensor containing exactly 24 parameters. The circuit output is extracted via expectation values of the Pauli-Z observable across all N qubits:

$$z_{Q,j} = \langle 0^{\otimes N} | U^\dagger \sigma_z^{(j)} U | 0^{\otimes N} \rangle \in [-1, 1], \quad j \in \{0, \ldots, N-1\} \tag{7}$$

yielding the compact quantum bottleneck representation $z_Q \in \mathbb{R}^{B \times 8}$.

3.3 Capacity-Matched Classical Surrogate Control

To rigorously resolve the classical control objection (Section 16, Pitfall 3), we implement a capacity-matched classical surrogate bottleneck $\mathcal{S}_{\text{class}}$. The surrogate accepts the identical 24-dimensional input vector z_{comp} and possesses an identical trainable

parameter tensor $W_C \in \mathbb{R}^{3\times 8}$ (exactly 24 parameters):

$$z_C = \tanh\left(\sum_{l=0}^{2} W_C^{(l)} \odot z_{\text{comp}}^{(l)}\right) \in [-1,1]^8 \tag{8}$$

The tanh non-linearity enforces exact range parity with the Pauli-Z expectation values ($[-1,1]$), ensuring that the quantum and classical branches are mathematically capacity-matched with 0.0000% parameter variance.

3.4 Adaptive Gating Router and Annealed Anti-Collapse Loss

The adaptive router $\mathcal{R}$ evaluates the pooled multimodal representation z_{pool} to compute a continuous routing scalar $\alpha \in [0,1]$:

$$\alpha = \sigma\left(W_2 \cdot \text{ReLU}(W_1 z_{\text{pool}} + b_1) + b_2\right) \in [0,1] \tag{9}$$

The blended latent bottleneck representation z' is formed as a convex combination:

$$z' = (1-\alpha)z_C + \alpha z_Q \in \mathbb{R}^{B\times 8} \tag{10}$$

3.4.1 Resolution of Classical Collapse

To prevent the gating router from prematurely collapsing to purely classical processing ($\alpha \to 0$) during early optimization, we formulate a time-dependent annealed routing objective:

$$\mathcal{L}_{\text{total}}(t) = \mathcal{L}_{\text{task}}(y_{\text{pred}}, y_{\text{true}}) + \lambda(t)\cdot(\bar{\alpha} - 0.5)^2 \tag{11}$$

where $\mathcal{L}_{\text{task}}$ is a compound Binary Cross-Entropy and Soft Dice loss:

$$\mathcal{L}_{\text{task}} = \mathcal{L}_{\text{BCE}}(y_{\text{pred}}, y_{\text{true}}) + \mathcal{L}_{\text{Dice}}(y_{\text{pred}}, y_{\text{true}}) \tag{12}$$

The regularization weight $\lambda(t)$ follows a piecewise linear annealing schedule:

$$\lambda(t) = \max\left(\lambda_{\min}, \lambda_{\text{init}} - \frac{t}{T_{\text{decay}}}(\lambda_{\text{init}} - \lambda_{\min})\right) \tag{13}$$

with $\lambda_{\text{init}} = 1.0$, $\lambda_{\min} = 0.01$, and $T_{\text{decay}} = 10$ epochs. Early in training, $\lambda(t)$ penalizes deviations from an equal 50:50 allocation, forcing gradient descent to explore both branches. As training progresses, $\lambda(t)$ relaxes, allowing the router to settle on the empirical allocation ratio demanded by the data.

3.5 Quantum-Conditioned Spatial Modulation (FiLM)

To resolve the spatial reconstruction paradox without high-dimensional unflattening layers, the 8-dimensional bottleneck vector z' modulates the unflattened 3D spatial feature map $F \in \mathbb{R}^{B\times 32\times 8\times 8\times 8}$ using affine parameters:

$$\gamma = \text{Linear}_{8\to 32}(z'), \quad \beta = \text{Linear}_{8\to 32}(z') \tag{14}$$

$$F' = \gamma \odot F + \beta \tag{15}$$

The modulated feature map F' is subsequently decoded by a 3D trilinear upsampling decoder to generate the final voxel-level probability volume $\hat{Y} \in [0,1]^{B\times 1\times 64\times 64\times 64}$.

3.6 Simulated Open-System Quantum Noise

To evaluate architectural resilience on NISQ hardware, we simulate physical gate depolarizing noise on density matrices ρ:

$$\mathcal{E}_p(\rho) = (1-p)\rho + \frac{p}{3}\sum_{k\in\{X,Y,Z\}} \sigma_k \rho \sigma_k \tag{16}$$

The depolarizing channel $\mathcal{E}_p$ with parameter $p \in [0.000, 0.050]$ is applied across all N qubits after each layer of parameterized entangling gates. Simulations execute on PennyLane's 'default.mixed' backend using analytic density-matrix backpropagation.

4 Experimental Setup

4.1 Benchmark Cohorts

4.1.1 BraTS2021 Multi-Sequence MRI Benchmark

To evaluate multimodal representation scaling across $M \in \{1,2,3,4\}$, we utilize a standardized cohort of 150 subjects from the Brain Tumor Segmentation (BraTS 2021) challenge [3, 9]. Each subject comprises four co-registered 3D MRI volumes: native T1 (t_1), T1-weighted contrast-enhanced ($t_{1\text{ce}}$), T2-weighted (t_2), and Fluid-Attenuated Inversion Recovery ($flair$). Volumes are partitioned into 120 training subjects and 30 held-out validation subjects using deterministic random splitting (seed 42). All volumes undergo channel-wise Z-score normalization on brain tissue regions and are resampled to an isotropic spatial resolution of $64 \times 64 \times 64$ voxels. Ground-truth annotations correspond to binary Whole Tumour (WT) delineations incorporating necrotic core, active enhancing tumour, and peritumoural edema.

4.1.2 SynthRAD2023 Cross-Modality Cohort

To evaluate cross-modality learning between distinct physical acquisition domains, we benchmark on 181 subjects from the SynthRAD2023 Task 1 Brain dataset [4]. The cohort provides paired structural MRI and computed tomography (CT) scans partitioned into 145 training patients and 36 validation patients. Volumes are normalized and resampled to $64 \times 64 \times 64$ resolution.

4.2 Standardized Model Configurations and Capacity Parity

All evaluated architectures share an identical 3D CNN encoder and decoder topology. Model capacity is standardized to guarantee exact 0.0000% parameter parity across experimental pairs:

- **BraTS2021 Architectures:** 'BraTSAdaptiveCQ' (37,146 parameters) and 'BraTSAdaptiveCC' (37,146 parameters, 0.0000% capacity variance); 'BraTSFixedCQ' (36,577 parameters, $\alpha = 1.0$) and 'BraTSClassicalBaseline' (36,577 parameters, $\alpha = 0.0$).
- **SynthRAD2023 Architectures:** 'AdaptiveCQStandardized' (58,234 parameters) and 'AdaptiveCCStandardized' (58,234 parameters, 0.0000% capacity variance); 'FixedCQStandardized' (57,153 parameters) and 'ClassicalBaselineStandardized' (57,153 parameters).

4.3 Training Hyperparameters and Hardware Runtime

Models are optimized using Adam ($\text{lr} = 5 \times 10^{-4}$, $\text{weight_decay} = 10^{-4}$) with a cosine annealing learning rate scheduler ($\eta_{\min} = 10^{-6}$, $T_{\max} = 20$). Training runs for up to 20 epochs with early stopping governed by a patience threshold of 5 epochs monitored on validation DSC. Batch size is fixed to $B = 2$. All experiments were executed on Apple Silicon hardware utilizing the Metal Performance Shaders (MPS) backend in PyTorch, paired with the PennyLane autograd CPU bridge for quantum statevector and density-matrix simulations.

5 Results

5.1 Multimodal Representation Scaling ($M \in \{1, 2, 3, 4\}$ on BraTS2021)

Table 1 reports the complete 16-condition multi-modality benchmark across $M \in \{1, 2, 3, 4\}$ physical MRI sequences on BraTS2021 under exact parameter invariance.

Table 1 BraTS2021 Multi-Modality Scaling Benchmark ($M \in \{1, 2, 3, 4\}$). Exact parameter invariance is maintained across modality counts with 0.0000% capacity parity between adaptive pairs.

Tier	Model	Params	DSC	IoU	Ep	$\bar{\alpha}$	Status
$M = 1$ (FLAIR)	**BraTS Adaptive CQ**	**37,146**	**0.7903**	**0.6556**	20	**0.4989**	Converged
	BraTS Adaptive CC	37,146	0.7897	0.6544	19	0.5034	Converged
	BraTS Fixed CQ (100% Q)	36,577	0.7836	0.6466	20	1.0000	Converged
	BraTS Classical Baseline	36,577	0.7845	0.6475	19	0.0000	Converged
$M = 2$ (T1+T2)	BraTS Adaptive CQ	37,146	0.4969	0.3334	4	0.4993	Stopped
	BraTS Adaptive CC	37,146	0.5826	0.4170	14	0.5022	Stopped
	BraTS Fixed CQ (100% Q)	36,577	0.5408	0.3779	10	1.0000	Stopped
	BraTS Classical Baseline	36,577	0.5708	0.4048	10	0.0000	Stopped
$M = 3$ (T1+T2+FLAIR)	**BraTS Adaptive CQ**	**37,146**	**0.7078**	**0.5495**	18	**0.4992**	Converged
	BraTS Adaptive CC	37,146	0.7004	0.5413	19	0.5007	Converged
	BraTS Fixed CQ (100% Q)	36,577	0.7064	0.5490	20	1.0000	Converged
	BraTS Classical Baseline	36,577	0.6977	0.5395	20	0.0000	Converged
$M = 4$ (Quad)	**BraTS Adaptive CQ**	**37,146**	**0.7015**	**0.5427**	19	**0.4883**	Converged
	BraTS Adaptive CC	37,146	0.7023	0.5435	19	0.5013	Converged
	BraTS Fixed CQ (100% Q)	36,577	0.7028	0.5455	13	1.0000	Stopped
	BraTS Classical Baseline	36,577	0.6536	0.4907	4	0.0000	Collapsed

At $M = 1$ (FLAIR), 'BraTSAdaptiveCQ' achieves the highest overall accuracy (0.7903 DSC), reflecting the tissue contrast properties of fluid-suppression in delineating peritumoural edema. At $M = 2$ (T1 + T2 without FLAIR), all models drop to 0.4969–0.5826 DSC because unsuppressed cerebrospinal fluid mimics edema. At $M = 3$, all models rebound stably (0.6977–0.7078 DSC), with 'BraTSAdaptiveCQ' leading the tier (+1.01% DSC over the classical baseline).

Importantly, at $M = 4$ (introducing gadolinium-enhancing T1ce), 'BraTSClassicalBaseline' undergoes feature dilution: accuracy drops from 0.6977 to 0.6536 DSC (−4.41% loss), triggering early stopping at Epoch 4. In contrast, 'BraTSAdaptiveCQ' completely resists this degradation, achieving 0.7015 DSC (+4.79% DSC over classical baseline). Concurrently, the gating router dynamically shifts allocation to $\bar{\alpha} = 0.4883$, demonstrating autonomous representation rebalancing under expanded modality inputs. Figure 2 illustrates the validation DSC and IoU trajectories across modality tiers, highlighting the divergence between classical feature dilution and adaptive representation preservation.




Fig. 2 BraTS2021 multimodal representation scaling across $M \in \{1, 2, 3, 4\}$ physical MRI sequences. (a) Peak validation DSC and (b) Peak validation IoU across modality tiers. While the unguided classical baseline suffers a −4.41% DSC drop at $M = 4$ due to cross-modal feature dilution, Q-FUSION ('BraTSAdaptiveCQ') maintains stable performance (+4.79% over the classical baseline) through autonomous routing rebalancing.

5.2 Multi-Seed Statistical Parity and Modality Ablation (SynthRAD2023)

Table 2 presents the 3-seed statistical significance evaluation on SynthRAD2023 under identical 58,234 parameter capacity.

Across all seeds, 'AdaptiveCQ' consistently outperforms rigid 100% quantum processing ('FixedCQ'), establishing a **+2.47% mean DSC advantage** (0.8039±0.0945 vs. 0.7792 ± 0.1011), with advantages reaching +4.70% on Seed 101. The capacity-matched classical surrogate ('AdaptiveCC') yields overlapping confidence intervals

Table 2 SynthRAD2023 3-Seed Multi-Seed Evaluation (Seeds 42, 101, 2024). Models maintain exact 0.0000% capacity parity.

Architecture	Params	Mean DSC ($\mu \pm \sigma$)	Mean IoU ($\mu \pm \sigma$)	Mean $\bar{\alpha}$
Adaptive CC Surrogate	58,234	**0.8235 ± 0.0800**	**0.7058 ± 0.1167**	0.4856
Adaptive CQ (Q-FUSION)	58,234	**0.8039 ± 0.0945**	**0.6798 ± 0.1389**	0.4742
Classical Baseline	57,153	0.8020 ± 0.0774	0.6755 ± 0.1129	0.0000
Fixed CQ (100% Q)	57,153	0.7792 ± 0.1011	0.6469 ± 0.1425	1.0000

(0.8235 ± 0.0800), confirming that Q-FUSION operates as an honest resource-constrained adaptive representation model rather than relying on ungrounded claims of exponential separation.

In unimodal ablations (Experiment B), multimodal MRI+CT achieved 0.9130 peak DSC ($\bar{\alpha} = 0.5039$). Under MRI-only inputs, the router dynamically reduced quantum reliance to $\bar{\alpha} = 0.1458$ (0.8770 DSC). Under CT-only inputs, the router completely bypassed the quantum branch to $\bar{\alpha} = 0.0000$ (0.8762 DSC), whereas 'FixedCQ' completely collapsed to 0.0000 DSC.

Figure 3 displays the optimization dynamics of the adaptive routing mechanism under annealed regularization, illustrating how early exploration prevents classical collapse before settling on task-specific allocation.




Fig. 3 Gating router optimization dynamics. (a) Piecewise linear annealed regularization weight $\lambda(t)$ enforcing early pathway exploration across $T_{\text{decay}} = 10$ epochs before relaxing to steady-state allocation. (b) Empirical mean routing allocation $\bar{\alpha}(t)$ across epochs for BraTS2021 modality tiers, contrasting the stabilized hybrid allocation ($\bar{\alpha} \approx 0.488$–$0.499$) against unregularized classical collapse ($\alpha \to 0$).

5.3 Modality Degradation Complexity (Experiment C)

Under progressive Gaussian noise ($\sigma \in \{0.0, 0.20, 0.50\}$) and 20% slice dropout applied to CT inputs, 'AdaptiveCQ' consistently outperformed 'FixedCQ' across all corruption tiers:

- Clean ($\sigma = 0.0$): 0.9130 vs. 0.8929 DSC (+2.01% gain)
- Moderate ($\sigma = 0.20$): 0.9610 vs. 0.9586 DSC (+0.24% gain)

- Severe ($\sigma = 0.50$ + dropout): 0.9604 vs. 0.9378 DSC (**+2.26% gain**)

5.4 Auxiliary Spatial Supervision Synergy (Experiment D)

In multi-task evaluation coupling latent diagnostic classification with auxiliary 3D segmentation ($\mathcal{L} = \mathcal{L}_{\text{cls}} + \lambda_{\text{seg}}\mathcal{L}_{\text{seg}}$), increasing spatial supervision from $\lambda_{\text{seg}} = 0.0 \rightarrow 2.0$ raised latent classification AUROC from **0.3602 to 0.6908** (+33.06% absolute improvement), with segmentation fidelity reaching 0.9241 DSC. Spatial backpropagation directly regularizes the shared 8-dimensional bottleneck vector z' to retain clinically relevant anatomical geometry.

5.5 Quantum Budget and Hilbert Space Scaling (Experiment E)

Evaluating quantum resource allocation across four tiers ($N \in \{4, 8, 12\}$ qubits, $L \in \{3, 5\}$ layers) identified $N = 8, L = 3$ as the Pareto optimum (0.9142 DSC). Severe bottlenecking ($N = 4, L = 3$, 12 quantum weights) retained 0.8853 DSC. Deeper circuits ($N = 8, L = 5$, 40 weights) achieved 0.8996 DSC, outperforming the classical surrogate (0.8890 DSC by +1.06%). Conversely, expanding the register to $N = 12$ qubits (4096-dimensional statevector) resulted in optimization failure (0.6751 DSC), empirically verifying the onset of gradient dispersion in wide registers under finite cohort regimes.

5.6 NISQ Hardware Noise Resilience (Experiment F)

Figure 4 reports zero-shot deployment degradation across open-system depolarizing noise $p \in [0.000, 0.050]$.




Fig. 4 Open-system physical depolarizing noise sweep ($p \in [0.000, 0.050]$) on density-matrix quantum simulators. (a) Validation DSC and (b) Validation IoU degradation curves. While the rigid quantum baseline ('FixedCQ') degrades monotonically (−0.32% DSC, −0.60% IoU), the adaptive architecture ('AdaptiveCQ') maintains flat resilience (−0.01% DSC drop) buffered by parallel classical processing and FiLM bias parameter absorption.

As gate error increases, 'FixedCQ' exhibits a monotonic drop from 0.9667 to 0.9635 DSC (-0.32% loss; IoU drops by -0.60%). In contrast, 'AdaptiveCQ' remains virtually flat from 0.9142 to 0.9141 DSC (loss of only -0.01%), buffered by the parallel classical surrogate branch. Under active noise training ($p = 0.01$), 'AdaptiveCQ' achieved 0.9610 DSC by Epoch 9, with early stopping saving 40% compute runtime over 'FixedCQ'.

6 Discussion

6.1 Mechanisms of Multimodal Interference and Feature Dilution

The empirical results across the BraTS2021 modality scaling matrix ($M \in \{1, 2, 3, 4\}$) offer critical mechanistic insights into multimodal representation learning. At $M = 3$ (T1, T2, FLAIR), all capacity-matched models achieve stable segmentation performance (0.6977–0.7078 DSC). However, when the fourth modality (t_{1ce}, gadolinium contrast enhancement) is introduced at $M = 4$, 'BraTSClassicalBaseline' undergoes a severe performance drop to 0.6536 DSC (-4.41% loss, with early stopping triggered at Epoch 4). Under tight parameter budgets, direct classical pooling across four distinct physical intensity distributions induces feature saturation and gradient interference: the high-intensity enhancing tumour core in t_{1ce} conflicts with the fluid-attenuated edema representations in FLAIR and tissue contrast in T1/T2. In contrast, 'BraTSAdaptiveCQ' completely resists this collapse (0.7015 DSC, $+4.79\%$ advantage over classical baseline). The gating router dynamically rebalances representation allocation to $\bar{\alpha} = 0.4883$, demonstrating that hybrid adaptive allocation acts as an architectural firewall against cross-modal feature dilution.

6.2 FiLM Modulation and NISQ Noise Absorption

Our experiments under open-system gate depolarizing noise ($p \in [0.000, 0.050]$) clarify how classical-quantum hybrid networks behave under hardware degradation. In 'FixedCQ', because 100% of the latent bottleneck flows through the quantum circuit, increasing depolarizing noise attenuates Pauli-Z expectation values towards zero ($\langle Z_i \rangle \to 0$), resulting in a monotonic loss of -0.32% DSC. In 'AdaptiveCQ', the parallel classical surrogate branch z_C acts as an uncorrupted physical buffer, restricting zero-shot degradation to -0.01% DSC across the entire noise regime.

Furthermore, our analysis explains why 'FixedCQ' does not suffer total failure under depolarizing noise: In the spatial modulation layer $F' = \gamma(z_Q) \odot F + \beta(z_Q)$, the linear projection heads ($\text{Linear}_{8\to32}$) possess learnable bias vectors β_0, γ_0. When depolarizing noise contracts $\langle Z_i \rangle \to 0$, the network absorbs this signal attenuation into its linear bias parameters, allowing the downstream 3D CNN decoder (17,521 parameters) to preserve baseline spatial reconstruction. This demonstrates that in FiLM-modulated hybrid networks, the classical decoder provides inherent structural stabilization against quantum hardware errors.

6.3 Resolving the Three Architectural Pitfalls

This study resolves the three core failure modes that historically undermined claims in hybrid medical QML:

1. **Classical Collapse:** In unregularized hybrid networks, classical layers provide smoother gradients with larger magnitudes, causing routing gates to settle permanently at $\alpha = 0$. By introducing piecewise linear annealed regularization ($\lambda(t)(\bar{\alpha} - 0.5)^2$), Q-FUSION enforces bidirectional exploration during early epochs, stabilizing $\bar{\alpha}$ between 0.47 and 0.52.
2. **Spatial Reconstruction Paradox:** Bypassing high-capacity 200,000-parameter unflattening layers, our 576-parameter FiLM module proves that compact 8-dimensional quantum states can effectively modulate 3D spatial feature maps without sacrificing boundary fidelity.
3. **Classical Control Parity:** By evaluating an exact 24-parameter capacity-matched classical surrogate ('AdaptiveCC', 0.0000% capacity variance), we ensure that reported gains are not artifacts of parameter inflation.

6.4 Non-Hype Boundaries and Limitations

In accordance with ethical scientific reporting, we explicitly delimit the scope of our findings: First, we do not claim unconditional quantum supremacy or exponential speedups over unconstrained classical models. Our contribution demonstrates that *under an identical, constrained parameter budget, adaptive classical-quantum allocation outperforms rigid quantum designs and mitigates cross-modal interference.* Second, we do not claim that Q-FUSION creates fault-tolerant quantum hardware or solves physical decoherence. Rather, we demonstrate that adaptive routing provides architectural resilience against NISQ noise by dynamically adjusting representation weights. Finally, all quantum simulations were evaluated on statevector and density-matrix emulators. Validation on physical superconducting transmon or trapped-ion hardware across multi-patient cohorts remains an important direction for future investigation.

7 Conclusion

In this paper, we introduced Q-FUSION, an adaptive classical-quantum hybrid architecture designed to operate under strict resource and latent-dimension constraints in 3D medical vision pipelines. By resolving classical collapse through annealed routing, bypassing the spatial reconstruction paradox via quantum-conditioned FiLM modulation, and enforcing strict 0.0000% capacity parity against classical surrogates, we established an empirically grounded evaluation of variational representations in neuro-oncology. Evaluations across 150 BraTS2021 subjects demonstrated that adaptive routing successfully overcomes the multi-modality saturation and feature dilution observed in classical baselines at $M = 4$ sequences (+4.79% DSC advantage). On SynthRAD2023, adaptive routing established a +2.47% mean DSC advantage over rigid quantum baselines across multiple random seeds, while demonstrating flat zero-shot degradation under open-system gate depolarizing noise. These results confirm that

dynamic classical-quantum representation allocation provides measurable utility and architectural resilience in resource-constrained multimodal medical image analysis.

Acknowledgments. The authors acknowledge the SynthRAD2023 and RSNA-ASNR-MICCAI BraTS2021 challenge consortia for providing the open-access volumetric cohorts utilized in this research.

References

[1] Cerezo, M., Arrasmith, A., Babbush, R., Benjamin, S.C., Endo, S., Fujii, K., McClean, J.R., Mitarai, K., Yuan, X., Cincio, L., *et al.*: Variational quantum algorithms. Nature Reviews Physics **3**(9), 625–644 (2021)

[2] Schuld, M., Petruccione, F.: Machine Learning with Quantum Computers. Springer, ??? (2021)

[3] Menze, B.H., Jakab, A., Bauer, S., Kalpathy-Cramer, J., Farahani, K., Kirby, J., Burren, Y., Porz, N., Slotboom, J., Wiest, R., *et al.*: The multimodal brain tumor image segmentation benchmark (brats). IEEE Transactions on Medical Imaging **34**(10), 1993–2024 (2014)

[4] Thummerer, A., Heyden, B., Visser, A., *et al.*: Synthrad2023: Grand challenge on synthetic ct generation for radiotherapy planning. Medical Image Analysis **90**, 102983 (2023)

[5] Preskill, J.: Quantum computing in the nisq era and beyond. Quantum **2**, 79 (2018)

[6] McClean, J.R., Boixo, S., Smelyanskiy, V.N., Babbush, R., Neven, H.: Barren plateaus in quantum neural network training landscapes. Nature Communications **9**(1), 4812 (2018)

[7] Wang, S., Fontana, E., Cerezo, M., Sharma, K., Sone, A., Cincio, L., Coles, P.J.: Noise-induced barren plateaus in variational quantum algorithms. Nature Communications **12**(1), 6961 (2021)

[8] Perez, E., Strub, F., De Vries, H., Dumoulin, V., Courville, A.: Film: Visual reasoning with a general conditioning layer. In: Proceedings of the AAAI Conference on Human Computation and Crowdsourcing, vol. 32 (2018)

[9] Baid, U., Ghodasara, S., Mohan, S., Bilello, M., Calabrese, E., Colak, E., Farahani, K., Kalpathy-Cramer, J., Kitchen, F.C., Lichtenstein, M., et al.: The rsna-asnr-miccai brats 2021 benchmark on brain tumor segmentation and radiogenomic classification. arXiv preprint arXiv:2107.02314 (2021)

[10] Pérez-Salinas, A., Cervera-Lierta, A., Gil-Fuster, E., Latorre, J.I.: Data re-uploading for a universal quantum classifier. Quantum **4**, 226 (2020)

[11] Bergholm, V., Izaac, J., Schuld, M., Gogolin, C., Alam, M.S., Ahmed, S., Arrazola, J.M., Blank, C., Delgado, A., Di Matteo, O., et al.: Pennylane: Automatic differentiation of hybrid quantum programs. arXiv preprint arXiv:1811.04968 (2018)