

TASK RISK ASSESSMENT (TRA)

[illegible]

Task Risk Assessment Form

No.	Task /Activity	Hazard and Consequence		Initial Risk			Mitigating Controls	Residual Risk		
	Sequential Steps	Hazard	Consequence	Probability	Consequence Severity	Risk Rating	Measures to Reduce Risk to ALARP	Probability	Consequence Severity	Risk Rating
1	Review TRA and TBT	Miscommunication	Personnel Injury / Environmental Pollution	1	2	2	Situational awareness and proper use of PPE. Hard hats, impact gloves, cotton gloves, latex gloves, steel toed boots, safety glasses and or side shields	1	1	1
2	Prior to any task being undertaken ensure that all personnel are aware of the hazards involved.	Electrical shock, possible slips trips and falls. Pinch points poor body position. Hydraulic discharge and spills.	Personnel Injury / Environmental Pollution	2	3	6	All personnel must be aware of their surrounds and weather conditions. Use proper Manual Handling techniques, i.e., Always use proper body positioning, lift with legs, and obtain second personnel when loads are over 40lbs. Read all SDS on chemicals used, use PPE that is specified in SDS and be aware of where all spill kits are located.	2	2	4
3	Remove seagnet and 8 pin burton	Electrical shock	Personnel Injury / Damage to equipment	3	4	12	Turn off TMS power and turn grounding wheel on until new motor has been installed.	2	2	4
4	Disconnect hydraulic lines from QD and drain motor.	Hydraulic discharge and spills	Environmental pollution	2	3	6	Spill kit on hand for accidental discharge on deck or overboard. Place all oil in bucket for proper disposal	1	2	2
5	Remove drum drive train guard, loosen drum drive chain tensioner, and remove sprocket adapter	Pinch points, strains and slips trips and falls	Personnel Injury / Damage to equipment	3	4	12	Personnel are to wear impact gloves and or cotton gloves when removing items.	2	2	4
6	Install ratchet strap to support old motor for removal	Pinch points, line of fire, dropped objects	Personnel Injury / Damage to equipment	2	3	6	Check Ratchet straps for wear and tears. Use proper ratchet strap for weight limit. Attach ratchet straps to proper load points	1	2	2
7	Remove Drum motor mounting brackets and drum motor	Pinch points, line of fire, dropped objects	Personnel Injury / Damage to equipment	2	3	6	Personnel are to wear impact gloves and or cotton gloves when removing items. Two persons lifting over 40 lbs.	1	2	2

8	Reinstall Drum motor mounting brackets and drum motor	Pinch points, line of fire, dropped objects	Personnel Injury / Damage to equipment	2	3	6	Personnel are to wear impact gloves and or cotton gloves when removing items. Two persons lifting over 40 lbs.	1	2	2
9	Install ratchet strap to support new motor for removal	Pinch points, line of fire, dropped objects	Personnel Injury / Damage to equipment	2	3	6	Check Ratchet straps for wear and tears. Use proper ratchet strap for weight limit. Attach ratchet straps to proper load points	1	2	2
10	Install drum drive train guard, loosen drum drive chain tensioner, install sprocket adapter and chain	Pinch points, strains and slips trips and falls	Personnel Injury / Damage to equipment	3	4	12	Personnel are to wear impact gloves and or cotton gloves when removing items.	2	2	4
11	Reinstall all hydraulic lines from QD and fill and air bleed new motor.	Hydraulic discharge and spills	Environmental pollution	2	3	6	Spill kit on hand for accidental discharge on deck or overboard. Place all oil in bucket for proper disposal	1	2	2
12	Reinstall seaneet and 8 pin burton	Electrical shock	Personnel Injury / Damage to equipment	3	4	12	Turn off TMS power and turn grounding wheel on until new motor has been installed.	2	2	4
13	Begin testing new motor	Electrical shock, damage to equipment.	Personnel Injury / Damage to equipment	3	4	12	Good communication with deck crew always when testing motor functions	2	2	4

TRA Approval	Name	Position	Signature	Date
By signing, the Approver confirms that the TRA has been reviewed and considers the task acceptable to proceed with residual risk meeting the acceptance criteria of DO Risk Matrix.				

*Reference DO-HSE-FRM-140 for DeepOcean Risk Assessment Matrix (RAM) and Guidewords