Augmented Reality with Location Tracking

Authors:
Drew Barclay
Maricar Aliasut
Llandro Ojeda

Advisors:
Dr. Robert McLeod
Dr. Ekram Hossain

Final report submitted in partial satisfaction of the requirements for the degree of
Bachelor of Science

in

Electrical & Computer Engineering

in the

Faculty of Engineering

of the

University of Manitoba

Spring 2017

University of Manitoba

Abstract

Faculty of Engineering
Electrical & Computer Engineering

Bachelor of Science

Augmented Reality with Location Tracking

by Drew Barclay
Maricar Aliasut
Llandro Ojeda

- Statement of the problem
  - Procedures and methods used
  - Results and Conclusions

Acknowledgements

The acknowledgments and the people to thank go here, don't forget to include your project advisor. . .

Include a list here of everyone who's open source stuff we used, and eg. the guy who did the ranging proof on those forums?

Contributions

The contribution page gives a concise statement of what novelty the thesis makes. In a multi-author thesis, it also gives the attribution for each component of the work, including the report.

Contents

List of Figures

List of Tables

List of Abbreviations

PCB Printed circuit board.
UWB Ultra-wideband. A type of radio technology.

Physical Constants

Speed of Light $\quad c_0 = 2.997\,924\,58 \times 10^8\,\mathrm{m\,s^{-1}}$ (exact)

List of Symbols

a	distance	m
P	power	$W (J s^{-1})$
ω	angular frequency	rad

Chapter 1

Introduction

1.1 Stuff

The Introduction can be made into its own chapter but no more than about 10% of the space of the total report should be allocated to introductory remarks. The Introduction is a good place to give a literature review (i.e., if a literature review is not the main purpose of the report), put the subject matter into context, and give the relevant motivation for the work which was performed. The remaining body of the report should be broken up into chapters in a logical manner.

1.1.1 Motivation

Talk about FPS games where positions are shown and allow easy finding of team members?

1.1.2 Overview of the Design

Go over tags/anchors (define each), how each tag is hooked up to a cellphone by USB, where cellphone calculates positions and shows them. Talk specifically about Arduino/DWM1000?

Chapter 2

Rangefinding

2.1 Overview

Rangefinding is the act of determining the distance between two things.

2.1.1 The System

The rangefinding subsystem is comprised of **nodes** in a network, each of which is capable of sending and receiving wireless signals.
(PUT IN A DIAGRAM OF A NETWORK AND RANGES HERE)

Each node is either an **anchor** or a **tag**. Both tags and anchors use essentially the same hardware and code, but anchors are assumed to be stationary while tags are mobile. Stationary nodes are required so as to provide a consistent frame of reference for other nodes when calculating positions later on. More information on this can be found in !!!TO-DO INSERT LABEL!!!.

The rangefinding subsystem's purpose is to determine the distances between every pair of nodes in the network. With this data, the position calculation subsystem can then determine the positions of every anchor and tag in 3D space.

2.1.2 Rangefinding

Rangefinding is done wirelessly. The underlying concept is that if we can calculate the times at which we send and receive a signal, then - since light travels at a fixed speed - we can determine the distance the signal traveled, which is the distance between the nodes.

The basic method is this:

1. Each node broadcasts a message to every other node, and every node responds.

2. The time it took for the message to travel from one node to another and then back (minus the time spent processing the received messages) is calculated.

3. With some simple math involving the speed of light the distance between the nodes is calculated.

This method of calculating range is known as **time-of-flight** (TOF).

Each node is comprised of a DWM1000, can send wireless signals, and an Arduino microcontroller.

2.1.3 Requirements

There are a number of useful characteristics a rangefinding system should have:

- Ranges should be accurate and not very noisy.

- Ranges should be calculated at a high frequency. If they are not, then we cannot calculate positions quickly and moving objects will have their positions displayed inaccurately.

- The system should be able to cover a large area.

- The system should be robust to nodes entering/leaving the network.

It will be demonstrated how we sought to satisfy these criteria.
(TODO TALK ABOUT WHAT IS COMING UP IN THE REST OF THE CHAPTER)

2.2 Time-of-Flight

This section briefly covers the math behind time-of-flight range calculations. For something more in-depth, the DWM1000 User Guide (INSERT CITATION HERE) has a comprehensive write-up of the different ways wireless ranging can be performed.

2.2.1 Basic Two-Way Ranging

In the case where there are two nodes communicating with each other, one can calculate the time it takes a signal to propagate between them, t_p, as:

$$t_p = \frac{t_{round} - t_{process}}{2}$$

A diagram displaying this can be found in !!INSERT HERE!!.

2.2.2 Asymmetric Two-Way Ranging

Because the clocks of two nodes may not pass time at the same rate, the above equation will not be as accurate as possible. The DWM1000 User Guide presents, without proof, the following equation for more accurate rangefinding:

$$t_p = \frac{round_1 round_2 - reply_1 * reply_2}{round1 + round2 + reply1 + reply2}$$

$round_1$, $round_2$, $reply_1$, $reply_2$ are respectively the total times taken (EXPLAIN BETTER HERE). See (INSERT FIGURE HERE).

A possible proof of this equation can be found in (INSERT APPENDIX THING HERE).

2.3 Wireless Communications

At the start of the project, it was determined that a technology would need to be chosen to handle wireless communications for ranging purposes. A number of options were considered. The ideal technology would:

- Be inexpensive.

- Have good range for in-door use.

- Allow for extremely precise measurements of time. Due to the speed of light, a nanosecond of error in timing calculations would lead to approximately 30cm of error in the calculated distance.

- Be small. As tags are attached to cellphones, they must be small.

2.3.1 Bluetooth in Phones: A Failed Approach

Originally, the goal was to use Bluetooth for ranging. The reason for this was that Android cellphones, which usually have Bluetooth transceivers, could be used for tags and anchors. This would save a large amount of time, as cellphones include batteries, are easy to program, and almost everyone has one (which would make letting people use our project as easy as downloading an app). We would just need to put a few phones running our app around a room, and we'd get ranging.

Unfortunately, it became clear early on that Bluetooth - specifically, Bluetooth used on Android cellphones - was not suitable. The time it took to send a Bluetooth message itself through the Android OS suffered massive variance of milliseconds (ADD IN APPENDIX CITATION WITH OUR CODE?), which would lead to 300 km of error in calculated distances! Android does not have any guarantees on timing, and does not allow low-level programming access to its internals (even when rooted). As such, we abandoned the idea of using phones as nodes.

2.3.2 Ultra-wideband and the DWM1000

After doing some research, we discovered the Decawave DWM1000 ultra-wideband transceiver. This chip is advertised as specifically being suited for ranging applications. It uses ultra-wideband technology rather than Bluetooth, Wi-Fi, or similar technologies.

Ultra-wideband, in contrast to Wi-Fi and other radio technologies, occupies a large bandwidth and transmits information via high-bandwidth pulses. Ultra-wideband is suited to tracking applications due to its resistance to multipath propagation, a phenomenon where signals reflect off of surfaces and thus reach the antennae via multiple paths (causing interference). An in-depth look at ultra-wideband is beyond the scope of this report, but interested readers might look more at (INCLUDE SOURCES HERE!!!).

The DWM1000 is advertised as:

- Allowing one to locate objects with up to 10cm accuracy.

- Having a range of up to 290m.

- Having a data rate of up to 6.8Mb/s.

- Having a small physical size.

Because these qualities satisfied our requirements, the DWM1000 was chosen for the foundational technology of the ranging part of the project.

2.4 Design of the Hardware

The hardware design for tags is an Arduino Pro Mini 3.3V connected to a DWM1000 over a PCB.

2.4.1   The Microcontroller

To interface with the DWM1000, a microcontroller was needed. The Arduino Pro Mini 3.3V was chosen because:

- Group members had previous experience with programming Arduinos.

- It was inexpensive.

- It worked off of 3.3V power, which was what the DWM1000 required. This obviated the need for voltage stepping.

- It is capable of floating point math, which is useful for asynchronous two-way ranging. As well, barely any processing power or RAM was needed. Each microcontroller only needed to hold a small number of timestamps, so the small amount of memory and slow processor was not important.

- Small physical size. As tags are attached to cellphones, they must be small.

- Batteries would not be needed to power tags, since power could be delivered via USB from the cellphone. This further simplified the design and kept costs low.

The only real downside of the Pro Mini was that it required a lot of soldering.

2.4.2   The PCB

Several designs were considered for the PCB connecting the Arduino and DWM1000. The most important factor was size. A PCB was constructed only for the tags, and anchors - which did not need to be reduced in size - were left in breadboard form in order to save costs and time. Making alterations to the PCB design to allow for a barrel jack power adapter (the only distinguishing feature between tags and anchors) would, however, have been extremely simple.

The first design idea we tried was to place the Arduino and DWM on top of each other, resulting in the smallest possible size. See (INSERT FIGURE HERE). However, the physical dimensions of the two components made this impossible. The other possibility was to place each component on opposite sides of the PCB (INSERT FIGURE HERE), but the Arduino's design demanded breakout headers to solder it into the board, which meant the PCB had to have holes drilled. This essentially ran into the same problem as with the original.

The second idea was to make two PCBs. The Arduino would connect to a PCB above it, and that PCB would connect to a board above it with the DWM1000 it. Because it was layered, the pins connecting the layers could be arranged such that the Arduino and DWM1000 were essentially above each other (but without interfering with their pins, as before). See (INSERT FIGURE). In the end, this design was abandoned because the breakout pins would add to much vertical length, it was expensive, and because it was much more complex to design.

As such, the end design required the Arduino and DWM1000 to be spread out over the board, resulting in the PCB being quite long and narrow. The PCB design was done in Eagle and ordered from PCBWay. The result can be seen in (INSERT FIGURE).

2.5   Arduino Software

Go into our open source library to help with the use of the DWM by thotro. Talk about the protocol we made.

2.6   DWM1000 Bugs

Go into specific issues with calibrating antennae delay, with sending delayed transmissions, etc.

2.7   Results

Go into how accurate rangefinding is, operating frequency, etc. Have tables!

2.8   Conclusion

Talk about how we now have a subsystem which can fully handle calculating ranges between things.

Chapter 3

Position Calculation

3.1 Overview

Talk about the goal of this section: to calculate positions of objects given the ranges between them. Talk about how Arduinos and Androids are connected by FTDI.

3.2 High-Level Example in 2D

Maybe this?

3.3 Extending This to 3D

Do the math on how we actually calculate things here.

3.4 Arbitrariness (pick a better title later)

The positions calculated from ranges do not correspond to the real world! We must use the cellphones' accelerometer (for gravity) and magnetic sensor (for compass direction/inclination) to map these positions to reality.

Go over how this is done.

3.5 Getting the Ranges

Talk about FTDI and our protocol to communicate from Arduino to Android. Go over how they are parsed (put in appendix of parsing code)

3.6 Conclusion

This subsystem calculates positions; we figured out how ranges are obtained, how they are calculated. Go over this in more detail.

Chapter 4

Augmented Reality

4.1 Overview

Talk about the goal of this section: to take positions from the position calculation subsystem, then render them on the screen to show where things are (even behind walls, etc.)

Make sure to note that we'll have youtube videos up and give links.

Don't forget an appendix with major code.

4.2 Tech Used

Go over OpenGL, the 3D text rendering library we're using, Android's rotation calculations.

4.3 3D Math Overview

Touch on matrices, projection/view/model matrices. Talk about how we use OpenGL's implementation to place things in 3D space.

4.4 Camera Field of View and OpenGL Field of View

Talk about how we make positions accurate here. Go over how we just overlay the camera and OpenGL surface on each other. Discuss Android camera limitations/FPS results.

4.5 Cellphone Rotation

Discuss in detail more about how Android implements getting the rotation, the limits of it when moving + in strong magnetic fields.

4.6 Billboard Effect

Talk about how doing the inverted view matrix multiplication causes things to always face the screen. Give pictures! Motivation here is to make 2D images that we can place in 3D space and have them face the screen.

4.7 HUD

Go over how the HUD is made. (Still need to finish that too so we can get pictures.)

4.8 Calibration

Talk about how we can take the cellphone's rotation matrix and calibrate the positions we calculate from anchors/tags.

4.9 Results

Show off how accurate we are. Have Youtube videos displaying such.

4.10 Conclusion

Conclusion of this section: we can render positions on the screen and have 3D math to do so etc.

Chapter 5

Conclusion

5.1 Stuff

The final chapter is the Conclusions chapter; there should be no surprises in the Conclusion: it is just a summary–about a page long–of what has been achieved. A short description of possible future work can be included in this chapter.

Appendix A

Arduino Code

```cpp
//Created by Drew Barclay
//Code uses thotro's dwm1000-arduino project
//Protocol: one byte for ID, then five bytes for the timestamp of the sending
//For each device, append one byte for the ID of the device, one byte for the

#include <SPI.h>
#include <DW1000.h>

class Device {
public:
  byte id;
  byte transmissionCount;
  DW1000Time timeDevicePrevSent;
  DW1000Time timePrevReceived;
  DW1000Time timeSent;
  DW1000Time timeDeviceReceived;
  DW1000Time timeDeviceSent;
  DW1000Time timeReceived;
  float lastComputedRange;
  bool hasReplied;

  Device() : lastComputedRange(0.0f), id(0), hasReplied(false) {}

  void computeRange();

  float getLastComputedRange() {
    return this->lastComputedRange;
  }
};

// CONSTANTS AND DATA START
//number of devices that can form a network at once
#define NUM_DEVICES 6
Device devices[NUM_DEVICES];
int curNumDevices;

// connection pins
const uint8_t PIN_RST = 9; // reset pin
const uint8_t PIN_IRQ = 2; // irq pin
const uint8_t PIN_SS = SS; // spi select pin
```

```
// data buffer
#define LEN_DATA 256
byte data[LEN_DATA];

//id for this device
const byte OUR_ID = 5;

long lastTransmission; //from millis()

// delay time before sending a message, should be at least 3ms (3000us)
const unsigned int DELAY_TIME_US = 2048 + 1000 + NUM_DEVICES*83 + 200; //shoul

volatile bool received; //Set when we are interrupted because we have received
// CONSTANTS AND DATA END

void Device::computeRange() {
  // only call this when timestamps are correct, otherwise strangeness may res
  // asymmetric two-way ranging (more computationly intense, less error prone)
  DW1000Time round1 = (timeDeviceReceived - timeDevicePrevSent).wrap();
  DW1000Time reply1 = (timeSent - timePrevReceived).wrap();
  DW1000Time round2 = (timeReceived - timeSent).wrap();
  DW1000Time reply2 = (timeDeviceSent - timeDeviceReceived).wrap();

  DW1000Time tof = (round1 * round2 - reply1 * reply2) / (round1 + round2 + re
  this->lastComputedRange = tof.getAsMeters();
}

void setup() {
    received = false;
    curNumDevices = 0;
    lastTransmission = millis();

    Serial.begin(115200);
    delay(1000);
    // initialize the driver
    DW1000.begin(PIN_IRQ, PIN_RST);
    DW1000.select(PIN_SS);
    Serial.println(F("DW1000_initialized_..."));
    // general configuration
    DW1000.newConfiguration();
    DW1000.setDefaults();
    DW1000.setDeviceAddress(OUR_ID);
    DW1000.setNetworkId(10);
    DW1000.enableMode(DW1000.MODE_LONGDATA_RANGE_ACCURACY);
    DW1000.commitConfiguration();
    Serial.println(F("Committed_configuration_..."));

    // attach callback for (successfully) sent and received messages
    DW1000.attachSentHandler(handleSent);
    DW1000.attachReceivedHandler(handleReceived);
```

```
        DW1000.attachErrorHandler(handleError);
        DW1000.attachReceiveFailedHandler(handleReceiveFailed);

        receiver(); //start receiving
}

void handleError() {
    Serial.println("Error!");
}

void handleReceiveFailed() {
    Serial.println("Receive failed!");
}

void handleSent() {

}

void handleReceived() {
    received = true;
}

void receiver() {
        DW1000.newReceive();
        DW1000.setDefaults();
        // so we don't need to restart the receiver manually
        DW1000.receivePermanently(true);
        DW1000.startReceive();
}

void parseReceived() {
    unsigned int len = DW1000.getDataLength();
    DW1000Time timeReceived;
    DW1000.getData(data, len);
    DW1000.getReceiveTimestamp(timeReceived);

    if (len < 6) {
        Serial.println("Received message with length <6, error.");
        return;
    }

    //Parse data
    //First byte, ID
    byte fromID = data[0];
    //Second byte, 5 byte timestamp when the transmission was sent (their clock)
    DW1000Time timeDeviceSent(data + 1);

    // If this device is not in our list, add it now.
    int idx = -1;
    for (int i = 0; i < curNumDevices; i++) {
     if (devices[i].id == fromID) {
```

```
      idx = i;
    }
  }
  if (idx == −1) { //If we haven't seen this device before...
    Serial.print("New device found. ID: "); Serial.println(fromID);
    if (curNumDevices == NUM_DEVICES) {
      Serial.println("Max # of devices exceeded. Returning early from receive.
      return;
    }
    devices[curNumDevices].id = fromID;
    devices[curNumDevices].timeDeviceSent = timeDeviceSent;
    devices[curNumDevices].transmissionCount = 1;
    idx = curNumDevices;
    curNumDevices++;
  }

  devices[idx].hasReplied = true;

  //Now, a list of device−specific stuff
  for (int i = 6; i < len;) {
    //First byte, device ID
    byte deviceID = data[i];
    i++;

    //Second byte, transmission counter
    byte transmissionCount = data[i];
    i++;

    //Next five bytes are the timestamp of when the device received our last t
    DW1000Time timeDeviceReceived(data + i);
    i += 5;

    //Next four bytes are a float representing the last calculated range
    float range;
    memcpy(&range, data + i, 4);
    i+= 4;

    //Is this our device? If so, we have an update to do and a range to report
    if (deviceID == OUR_ID) {
      //Mark down the two timestamps it included, as well as the time we recei
      devices[idx].timeDeviceReceived = timeDeviceReceived;
      devices[idx].timeDeviceSent = timeDeviceSent;
      devices[idx].timeReceived = timeReceived;

      Serial.print("Transmission received from tag "); Serial.print(devices[id

      //If everything looks good, we can compute the range!
      if (transmissionCount == 0) {
        //Error sending, reset everything.
        devices[idx].transmissionCount = 1;
      } else if (devices[idx].transmissionCount == transmissionCount) {
```

```
        if (devices[idx].transmissionCount > 1) {
          devices[idx].computeRange();
          Serial.print("!range_"); Serial.print(OUR_ID); Serial.print("_"); Se
        }
        devices[idx].transmissionCount++;
      } else {
        //Error in transmission!
        devices[idx].transmissionCount = 0;
        Serial.println("Transmission_count_does_not_match.");
      }

      devices[idx].timeDevicePrevSent = timeDeviceSent;
      devices[idx].timePrevReceived = timeReceived;
    }

    Serial.print("!range_"); Serial.print(fromID); Serial.print("_"); Serial.p
  }
  //TODO if our device was not in the list and we think it should have been, r
}

void doTransmit() {
  data[0] = OUR_ID;

  //Normally we would set the timestamp for when we send here (starting at the

  int curByte = 6;
  for (int i = 0; i < curNumDevices; i++) {
    data[curByte] = devices[i].id;
    curByte++;
    data[curByte] = devices[i].transmissionCount;
    curByte++;
    devices[i].timeReceived.getTimestamp(data + curByte); //last timestamp wil
    curByte += 5;
    float range = devices[i].getLastComputedRange();
    memcpy(data + curByte, &range, 4); //floats are 4 bytes
    curByte += 4;

    if (devices[i].hasReplied) {
      devices[i].transmissionCount++; //Increment for every transmission, the
      devices[i].hasReplied = false; //Set to not for this round
    }
  }

  //Do the actual transmission
  DW1000.newTransmit();
  DW1000.setDefaults();

  //Now we figure out the time to send this message!
  DW1000Time deltaTime = DW1000Time(DELAY_TIME_US, DW1000Time::MICROSECONDS);
  DW1000Time timeSent = DW1000.setDelay(deltaTime);
  timeSent.getTimestamp(data + 1); //set second byte (5 bytes will be written)
```

```
  DW1000.setData(data, curByte);
  DW1000.startTransmit();

  for (int i = 0; i < NUM_DEVICES; i++) {
    devices[i].timeSent = timeSent;
  }
}

void loop() {
  unsigned long curMillis = millis();

  if (received) {
    received = false;
    parseReceived();
  }

  if (curMillis − lastTransmission > 300) {
    doTransmit();
    lastTransmission = curMillis;
  }
}
```