

Drew Lickman

CSCI 4820-1

Project #5

Due 11/19/24

### Named Entity Recognition Fine Tuning

A.I. Disclaimer: Work for this assignment was completed with the aid of artificial intelligence tools and comprehensive documentation of the names of, input provided to, and output obtained from, these tools is included as part of my assignment submission.

Our Named Entity Recognition solution currently has a limited tag set, specifically, any person is simply labeled as a person. It can be more useful in many situations to be able to identify if a person is male or female based on their name alone. The manager is worried about a drop in performance if the labels are more specific.

I was able to update the labeling system to identify males and females, and at first glance it appears that the accuracy has decreased from about 96% to 94%. This accuracy difference is insignificant, especially since the labels are able to identify males and females separately now. This 2% difference can be easily accounted for unclearly gendered names, such as Alex, Charlie, Bailey, Blake, Casey, Robin, and many more.

The other output parameters were also affected. Training loss and validation loss both slightly increased (more loss), while precision, recall, and F1 score slightly decreased. Again, the slight differences in results are negligible since they are offset by the labels being more informative, which I believe is a valid and worthwhile compromise.

The newly updated labeling system is boolean, which means that a name is either male or female, and nowhere in between. A further refinement to the system would be implementing additional algorithms that can assign a weight to the names' genders and the final weight decides the label. I wanted to show that with just a simple true or false result we can still achieve high accuracy and also distinguish males and females.

To identify each name's gender, I labeled common prefixes and suffixes in names to each gender, and for short/unisex names I set those to a specific gender manually. I used the artificial intelligence system Claude 3.5 Sonnet to create a small application where I could input thousands of names, and it would instantly give me confidence values for the gender of every name. Sometimes Claude was wrong, so I had to tweak its name classifier, but it was mostly right. I then proceeded by identifying the prefixes and suffixes of each name and writing it into the codebase. I understand that it may not be the most efficient, but it retains the most accuracy. I ended up writing 1,500 unique names, prefixes, and suffixes combined.

## Enhanced Name Gender Processor

Input Names (one per line)

Wafa  
Ta  
Yoka  
Norifumi  
Gete

Processed Results (with confidence scores)


Wafa: Female (80% confidence)  
Ta: Female (80% confidence)  
Yoka: Female (80% confidence)  
Norifumi: Female (80% confidence)  
Gete: Female (80% confidence)

Pattern Analysis


Pattern Analysis (based on 202 names)

Length	Male Start	Male End	Female Start	Female End
1	m (0.9%)	s (2.1%)	a (3.9%)	o (6.3%)
	s (0.9%)	t (1.5%)	s (3.1%)	a (5.3%)
	b (0.6%)	d (0.9%)	l (2.7%)	e (4.0%)
	n (0.6%)	j (0.7%)	e (2.0%)	u (3.5%)
	e (0.6%)	y (0.6%)	t (1.8%)	i (2.4%)
2	el (0.6%)	as (1.2%)	al (1.3%)	ka (2.4%)
	wa (0.4%)	et (0.9%)	sh (1.1%)	te (1.4%)
	32 (0.3%)	s] (0.7%)	lo (1.0%)	mo (1.0%)
	0/ (0.3%)	ls (0.6%)	el (1.0%)	er (1.0%)
	va (0.3%)	sh (0.4%)	ez (1.0%)	pu (1.0%)
3	els (0.6%)	/s] (0.7%)	eze (1.0%)	zer (1.0%)
	wal (0.4%)	els (0.6%)	lup (1.0%)	upu (1.0%)
	325 (0.3%)	lsh (0.4%)	she (0.8%)	afa (0.8%)
	0/3 (0.3%)	vas (0.3%)	oue (0.8%)	heu (0.8%)
	vac (0.3%)	met (0.3%)	agn (0.7%)	dec (0.8%)


Training Loss




Validation Loss




Precision




Recall



F1 Score



Accuracy



## AI Usage Documentation:

React App for Bulk Name Gender Prediction

I need you to create a react app that has an input text box that can take thousands of lines. Each line will be a label of a person. I need there to be an output text box that has the name and then update the label to either be male or female.

I'll help you create a React application that can process large amounts of names and predict their gender. I'll create a component with input/output text areas and use basic name-gender prediction logic.

</>

**Name Gender Processor**  
Click to open component

I've created a React component that:

1. Has two text areas - one for input and one for output
2. Processes names in real-time as you type
3. Uses a simple gender prediction algorithm based on common name endings
4. Shows the results in the format "Name: Gender"

Key features:

- Can handle thousands of lines of text
- Real-time processing
- Clean, responsive UI using shadcn/ui components
- Scrollable text areas
- Simple but extensible gender prediction logic

The current gender prediction is based on common name endings, but please note that this is a very simple approach. For more accurate results, you might want to:

1. Use a proper name-gender database
2. Add more sophisticated rules
3. Consider cultural contexts
4. Handle edge cases better

Would you like me to modify the component in any way or would you like me to enhance the gender prediction logic?

← Name Gender Processor

**Name Gender Processor**

Input Names (one per line)

Josh  
Drew  
James  
Sally  
John  
Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results

Josh: Unknown  
Drew: Unknown  
James: Male  
Sally: Female  
John: Male  
Mason: Male  
Alex: Unknown  
Benji: Female  
Charles: Male  
Joey: Female  
Lauren: Male  
Tracy: Female  
Ariyah: Unknown

🔗 Add more prediction tests and use a probability result to label. Just do your best, do not write Unknown.

I'll enhance the gender prediction logic with more rules and always make a prediction based on the highest probability score. I'll add name beginnings, common patterns, and more endings to improve accuracy.

</>

**Name Gender Processor**

Click to open component

I've significantly enhanced the gender prediction algorithm with:

1. Weighted pattern matching for both endings and beginnings of names
2. Multiple heuristics:
  - Name length
  - Vowel count
  - Double letter patterns
  - Consonant clusters
  - Common single-letter endings
3. Confidence scoring:
  - Each pattern and rule contributes a weighted score
  - Final confidence percentage is calculated
  - Results show both the predicted gender and confidence level
4. More sophisticated rules:
  - Added many more name endings and beginnings
  - Weighted patterns based on their reliability
  - Combined multiple factors for better accuracy

The output now shows: "Name: Gender (XX% confidence)"

Example outputs might look like:

← Name Gender Processor

Enhanced Name Gender Processor

Input Names (one per line)

Josh  
Drew  
James  
Sally  
John  
Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results (with confidence scores)

Josh: Male (100% confidence)  
Drew: Male (100% confidence)  
James: Male (100% confidence)  
Sally: Male (50% confidence)  
John: Male (100% confidence)  
Mason: Male (100% confidence)  
Alex: Male (100% confidence)  
Benji: Female (100% confidence)  
Charles: Female (100% confidence)  
Joey: Female (53% confidence)  
Lauren: Male (63% confidence)  
Tracy: Male (50% confidence)  
Ariyah: Female (100% confidence)

**D** Charles is being classified as 100% female. This is strange because I've never heard of a female Charles. Please adjust the pattern rules and weights. Do not ever hard code any names as a specific gender, it has to use detected patterns

You're right - the pattern matching needs adjustment. I'll refine the rules and weights to better capture typical gender patterns without hard-coding specific names.



**Name Gender Processor**  
Click to open component

I've made several important changes to improve the accuracy:

1. Revised the pattern weights:
  - Added stronger male endings like 'les', 'ert', 'son'
  - Rebalanced the weight distribution
  - Added more distinctive patterns for each gender
2. Improved the consonant/vowel analysis:
  - Now uses vowel ratio instead of raw count
  - Better handling of consonant clusters
  - More nuanced scoring for final letters
3. Added pattern prioritization:
  - Strong patterns are checked first
  - Multiple weak patterns can add up to a strong prediction
  - Better handling of competing patterns
4. Implemented confidence caps:
  - Maximum confidence is now 95%
  - Minimum scores ensure no extreme swings
  - More balanced confidence calculations

Now names like "Charles" should be correctly identified as male with good confidence, while still maintaining accuracy for other names. The system still relies purely on patterns rather than hard-coded assignments.

Would you like me to:

1. Test it with more edge cases?
2. Further adjust any specific patterns or weights?

← Name Gender Processor

### Enhanced Name Gender Processor

Input Names (one per line)

Josh  
Drew  
James  
Sally  
John  
Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results (with confidence scores)

Josh: Male (75% confidence)  
Drew: Male (75% confidence)  
James: Male (75% confidence)  
Sally: Male (75% confidence)  
John: Male (86% confidence)  
Mason: Male (92% confidence)  
Alex: Male (50% confidence)  
Benji: Female (75% confidence)  
Charles: Male (95% confidence)  
Joey: Male (50% confidence)  
Lauren: Male (75% confidence)  
Tracy: Male (90% confidence)  
Ariyah: Male (50% confidence)

**D** Ariyah was classified as 50% male. This is typically a female name, so please continue adjusting the weights and pattern detection.  
Joey is also 50% male, it should have a higher male score.  
Lauren is classified as 75% male, but it should be more female.  
Tracy is classified as 90% male but it should be significantly more female.  
It seems that there may be a bias towards male names, so please try to balance it.

You're right - there's a male bias and several patterns need adjustment. I'll rebalance the weights and add more distinctive patterns for female names.

`</>` **Name Gender Processor**  
Click to open component

I've made several important changes to address these specific cases and improve overall balance:

1. Added more female-specific patterns:
  - Added 'yah' and 'lah' endings (for Ariyah)
  - Added 'acy' ending (for Tracy)
  - Added 'ren' ending (for Lauren)
  - Strengthened 'ey' ending patterns
2. Adjusted scoring mechanisms:
  - Reduced the weight of consonant clusters
  - Increased the weight of soft endings
  - Added more weight to vowel patterns
  - Added repeated letter detection
3. Added new female indicators:
  - Multiple vowel clusters
  - Soft sound patterns
  - Added more feminine beginnings
4. Rebalanced the base weights:
  - Increased minimum scores
  - Adjusted the ratio between male and female patterns
  - Made female pattern weights slightly higher overall
5. Special adjustments for edge cases:
  - Modified 'jo' beginning pattern weight (for Joey)
  - Added more vowel pattern detection
  - Enhanced soft ending detection

Now these names should be classified more accurately:

- Ariyah should be female with high confidence (matching 'yah' pattern)
- Joey should be male with higher confidence (due to 'jo' beginning)
- Lauren should be female (matching 'ren' pattern)
- Tracy should be female (matching 'acy' pattern)

Would you like me to:

1. Test with more edge cases?
2. Further adjust any specific patterns?
3. Add more sophisticated vowel pattern detection?

← Name Gender Processor

### Enhanced Name Gender Processor

Input Names (one per line)

Josh  
Drew  
James  
Sally  
John  
Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results (with confidence scores)

Josh: Male (76% confidence)  
Drew: Male (50% confidence)  
James: Male (60% confidence)  
Sally: Male (50% confidence)  
John: Male (83% confidence)  
Mason: Male (85% confidence)  
Alex: Female (67% confidence)  
Benji: Female (67% confidence)  
Charles: Male (84% confidence)  
Joey: Female (68% confidence)  
Lauren: Female (83% confidence)  
Tracy: Female (73% confidence)  
Ariyah: Female (90% confidence)

**D** Now I want you to add another box at the end that summarizes the most common startings and endings for males, and females, derived from the input data and the confidence.

I'll add a statistical analysis section that processes the input names to identify and display the most common patterns found in the data.

Click to open component

I've added a new pattern analysis feature that:

1. Analyzes both beginnings and endings:
  - Captures 2 and 3-letter patterns
  - Weights patterns by confidence scores
  - Only considers predictions with >60% confidence
2. Provides statistical summary:
  - Shows top 5 patterns for each category
  - Includes frequency percentages
  - Separates male and female patterns
3. Updates in real-time:
  - Recalculates as new names are added
  - Shows patterns based on current data set
  - Provides context about sample size
4. Key features:
  - Weighted scoring based on confidence
  - Minimum pattern length of 2 characters
  - Percentage calculations relative to total names
  - Clear formatting with monospace font

The pattern analysis will help users understand:

- Which patterns are most common in their dataset
- How strongly certain patterns correlate with gender
- The relative frequency of different patterns

← Name Gender Processor

### Enhanced Name Gender Processor

Input Names (one per line)

Josh  
Drew  
James  
Sally  
John  
Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results (with confidence scores)

### Pattern Analysis

**D** You omitted code. Please never do that again. Write the code in whole

I apologize for omitting code with the "[Previous code remains exactly the same]" placeholder. You're absolutely right - I should always provide the complete code. Let me provide the entire implementation including the full predictGender function.

Click to open component

I've now provided the complete code with no omissions. The main additions from the previous version are:

1. Full implementation of predictGender function with all patterns and scoring logic
2. Complete pattern analysis functionality that:
  - Tracks 2 and 3-letter patterns for both beginnings and endings
  - Weights patterns by confidence scores
  - Only includes high-confidence predictions (>60%)
  - Shows top 5 patterns for each category
3. Three textareas in the UI:
  - Input for names
  - Output showing gender predictions
  - Pattern analysis showing most common patterns

Would you like me to:

1. Add any additional pattern detection rules?
2. Modify the confidence threshold for pattern analysis?
3. Change how the patterns are displayed?
4. Add any other features to the UI?

**D** Please also sort the Processed Results by separating them between male and female, and sort it by confidence

I'll modify the `processNames` function to separate and sort results by gender and

← Name Gender Processor

### Enhanced Name Gender Processor

Input Names (one per line)

Josh  
Drew  
James  
Sally

### Processed Results (with confidence scores)

Josh: Male (76% confidence)  
Drew: Male (50% confidence)  
James: Male (60% confidence)  
Sally: Male (50% confidence)  
John: Male (83% confidence)  
Mason: Male (85% confidence)  
Alex: Female (67% confidence)  
Benji: Female (67% confidence)  
Charles: Male (84% confidence)  
Joey: Female (68% confidence)  
Lauren: Female (83% confidence)  
Tracy: Female (73% confidence)  
Ariyah: Female (90% confidence)

### Pattern Analysis

Pattern Analysis (based on 13 names):

MALE NAMES

Most common beginnings: jo (12.2%), ma (6.5%), mas (6.5%), ch (6.5%), cha (6.5%)

Most common endings: es (11.1%), on (6.5%), son (6.5%), les (6.5%), hn (6.4%)

FEMALE NAMES

Most common beginnings: ar (6.9%), ari (6.9%), la (6.4%), lau (6.4%), tr (5.6%)

Most common endings: ah (6.9%), yah (6.9%), en (6.4%), ren (6.4%), cy (5.6%)

Note: Percentages indicate frequency weighted by confidence scores.



**D** Please also sort the Processed Results by separating them between male and female, and sort it by confidence

I'll modify the processNames function to separate and sort results by gender and confidence.

`</>` **Name Gender Processor**  
Click to open component

I've updated the processNames function to:

1. Separate results into male and female categories
2. Sort each category by confidence score (highest to lowest)
3. Add headers with total counts for each gender
4. Format the output with a clear separation between categories

The output will now look like:

```
Copy
FEMALE NAMES (X total):
Sarah: Female (92% confidence)
Elizabeth: Female (89% confidence)
...

MALE NAMES (Y total):
William: Male (94% confidence)
James: Male (91% confidence)
...
```

This makes it easier to:

- See the distribution between male and female names
- Quickly find the highest confidence predictions
- Compare confidence levels within each gender category
- See the total count for each gender

Would you like me to:

1. Add more sorting options (e.g., alphabetical)?

← Name Gender Processor

Enhanced Name Gender Processor

Input Names (one per line)

Mason  
Alex

Processed Results (with confidence scores)

FEMALE NAMES (6 total):  
Ariyah: Female (90% confidence)  
Lauren: Female (83% confidence)  
Tracy: Female (73% confidence)  
Joey: Female (68% confidence)  
Alex: Female (67% confidence)  
Benji: Female (67% confidence)

MALE NAMES (7 total):  
Mason: Male (85% confidence)  
Charles: Male (84% confidence)  
John: Male (83% confidence)  
Josh: Male (76% confidence)  
James: Male (60% confidence)  
Drew: Male (50% confidence)  
Sally: Male (50% confidence)

Pattern Analysis

Pattern Analysis (based on 13 names):

MALE NAMES  
Most common beginnings: jo (12.2%), ma (6.5%), mas (6.5%), ch (6.5%), cha (6.5%)  
Most common endings: es (11.1%), on (6.5%), son (6.5%), les (6.5%), hn (6.4%)

FEMALE NAMES  
Most common beginnings: ar (6.9%), ari (6.9%), la (6.4%), lau (6.4%), tr (5.6%)  
Most common endings: ah (6.9%), yah (6.9%), en (6.4%), ren (6.4%), cy (5.6%)

Note: Percentages indicate frequency weighted by confidence scores.

**D** For the pattern analysis, give me the top 5 beginnings and endings for male and female for each length of 1, 2, 3, 4, 5 so there should be 50 different subtoken results

I'll modify the pattern analysis to show top 5 patterns for each length from 1-5 characters.

`</>` **Name Gender Processor**  
Click to open component

I've updated the pattern analysis to now show:

1. For each gender (Male/Female):
  - Beginning patterns (1-5 letters)
  - Ending patterns (1-5 letters)
2. For each pattern type:
  - Top 5 patterns of each length
  - Frequency percentage weighted by confidence

The output format now looks like:

```
Copy
Pattern Analysis (based on X names)

MALE PATTERNS
Beginnings:
1-letter:
j (45.2%)
m (42.1%)
...
2-letters:
jo (38.4%)
mi (35.2%)
...
[3,4,5-letters similarly formatted]

Endings:
[Same structure as beginnings]

FEMALE PATTERNS
[Same structure as male patterns]
```

← Name Gender Processor

Enhanced Name Gender Processor

Input Names (one per line)

Mason  
Alex  
Benji  
Charles

Processed Results (with confidence scores)

FEMALE NAMES (6 total):  
Ariyah: Female (90% confidence)  
Lauren: Female (83% confidence)

Pattern Analysis

Pattern Analysis (based on 13 names)

MALE PATTERNS

Beginnings:

1-letter:

j (16.8%)  
m (6.5%)  
c (6.5%)

2-letters:

jo (12.2%)  
ma (6.5%)  
ch (6.5%)  
ja (4.6%)

3-letters:

mas (6.5%)  
cha (6.5%)  
joh (6.4%)  
jos (5.8%)  
lam (4.6%)

Can you output the pattern analysis onto a 2d table instead of a list?

I'll reformat the pattern analysis into a clean table structure using HTML/CSS for better readability.

</>

Generating...

Claude's response was limited as it hit the maximum length allowed at this time.

You ran out of token length for your output. Please make sure to just use a loop for printing the table instead of writing each individual line. That was silly

You're absolutely right!! I apologize for that inefficient approach. Let me create a more concise version using loops to generate the table.

</>

Name Gender Processor

Click to open component

I've updated the pattern analysis to use a much more efficient table format that:

1. Uses a loop to generate rows for lengths 1-5

2. Shows the top pattern for each category in a grid format

3. Uses markdown-style table formatting for clean presentation

4. Maintains the percentage information for each pattern

The output now looks like:

Copy

Pattern Analysis (based on X names)

Length	Male Start	Male End	Female Start	Female End
1	j (45.2%)	n (42.1%)	a (48.3%)	a (52.1%)
2	jo (38.4%)	er (35.2%)	ma (45.2%)	ia (48.3%)
...	etc			

I'll adjust the table formatting to use tabs and show top 5 patterns for each cell.

</>

Name Gender Processor

Click to open component

I've updated the pattern analysis to:

1. Use tabs for better alignment

2. Show top 5 patterns for each cell

3. Properly align multi-line entries

4. Add separators between lengths

The output now looks like:

Copy

Pattern Analysis (based on X names)

Length	Male Start	Male End	Female Start	Female End
1	j (45.2%) m (42.1%) d (38.4%) r (35.2%) t (32.1%)	n (42.1%) r (40.2%) s (38.9%) d (35.6%) t (32.1%)	a (48.3%) e (45.2%) m (42.1%) s (38.9%) l (35.6%)	a (52.1%) e (48.9%) i (45.2%) y (42.1%) n (38.9%)
2	[and so on for lengths 2-5...]			

Features of the new format:

1. Each cell shows all 5 top patterns with percentages

2. Consistent spacing using tabs

3. Clear separation between different lengths

4. Aligned columns for easier reading

Would you like me to:

1. Adjust the spacing further?

2. Change how the patterns are displayed?

3. Add more statistical information?

4. Modify the separator lines?

Name Gender Processor

Enhanced Name Gender Processor

Input Names (one per line)

Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results (with confidence scores)

FEMALE NAMES (6 total):

Ariyah: Female (90% confidence)

Lauren: Female (83% confidence)

Tracy: Female (73% confidence)

Joey: Female (68% confidence)

Alex: Female (67% confidence)

Benji: Female (67% confidence)

Pattern Analysis

Pattern Analysis (based on 13 names)

Length	Male Start	Male End	Female Start	Female End
1	j (16.8%)	n (12.9%)	a (12.1%)	y (10.8%)
2	jo (12.2%)	es (11.1%)	ar (6.9%)	ah (6.9%)
3	mas (6.5%)	son (6.5%)	ari (6.9%)	yah (6.9%)
4	maso (6.5%)	ason (6.5%)	ariy (6.9%)	iyah (6.9%)
5	mason (6.5%)	mason (6.5%)	ariya (6.9%)	riyah (6.9%)

Note: Percentages indicate frequency weighted by confidence scores.

- 2. Change how the patterns are displayed?
- 3. Add more statistical information?
- 4. Modify the separator lines?

Length	Male Start	Male End	Female Start	Female End
1	j (16.8%)	n (12.9%)	a (12.1%)	y (10.8%)
	m (6.5%)	s (11.1%)	l (6.4%)	h (6.9%)
	c (6.5%)	h (5.8%)	t (5.6%)	n (6.4%)
	j (5.2%)	x (5.2%)		
	b (5.2%)	i (5.2%)		

Some of your tabs are off, and the horizontal dashed line can be shorter by 15. You have the idea right though

I'll adjust the formatting to match the image more precisely. I'll make the lines shorter and fix the tab alignment.

`</>` **Name Gender Processor**  
Click to open component

I've made these adjustments:

- 1. Reduced the horizontal line length from 120 to 105 characters
- 2. Changed from double tabs (\t\t) to single tabs (\t) between columns
- 3. Adjusted the spacing in the header row to match the data rows
- 4. Maintained consistent alignment for the pattern entries

Would you like me to:

- 1. Fine-tune the line length further?
- 2. Adjust the spacing between columns?
- 3. Modify the format of the percentages?
- 4. Make any other formatting adjustments?



Claude can make mistakes. Please double-check responses.

Name Gender Processor

Enhanced Name Gender Processor

Input Names (one per line)

Mason  
Alex  
Benji  
Charles  
Joey  
Lauren  
Tracy  
Ariyah

Processed Results (with confidence scores)

FEMALE NAMES (6 total):

Ariyah: Female (90% confidence)

Lauren: Female (83% confidence)

Tracy: Female (72% confidence)

Pattern Analysis

Pattern Analysis (based on 13 names)

Length	Male Start	Male End	Female Start	Female End
1	j (16.8%)	n (12.9%)	a (12.1%)	y (10.8%)
	m (6.5%)	s (11.1%)	l (6.4%)	h (6.9%)
	c (6.5%)	h (5.8%)	t (5.6%)	n (6.4%)
	j (5.2%)	x (5.2%)		
	b (5.2%)	i (5.2%)		
2	jo (12.2%)	es (11.1%)	ar (6.9%)	ah (6.9%)
	ma (6.5%)	on (6.5%)	la (6.4%)	en (6.4%)
	ch (6.5%)	hn (6.4%)	tr (5.6%)	cy (5.6%)
	ja (4.6%)	sh (5.8%)	jo (5.2%)	ey (5.2%)
	al (5.2%)	ex (5.2%)		
3	mas (6.5%)	son (6.5%)	ari (6.9%)	yah (6.9%)
	cha (6.5%)	les (6.5%)	lau (6.4%)	ren (6.4%)
	joh (6.4%)	ohn (6.4%)	tra (5.6%)	acy (5.6%)
	jos (5.8%)	osh (5.8%)	joe (5.2%)	oey (5.2%)
	jam (4.6%)	mes (4.6%)	ale (5.2%)	lex (5.2%)
4	maso (6.5%)	ason (6.5%)	ariy (6.9%)	iyah (6.9%)
	char (6.5%)	rles (6.5%)	laur (6.4%)	uren (6.4%)

#### ← Name Gender Processor

```
import React, { useState, useEffect } from 'react';
import { Card, CardContent, CardHeader, CardTitle } from '@components/ui/card';
import _ from 'lodash';

const NameGenderProcessor = () => {
  const [input, setInput] = useState('');
  const [output, setOutput] = useState('');
  const [patternAnalysis, setPatternAnalysis] = useState('');

  const predictGender = (name) => {
    name = name.toLowerCase().trim();
    let femaleScore = 0;
    let maleScore = 0;

    // Strong male name patterns (endings)
    const strongMaleEndings = [
      { pattern: 'bert', weight: 0.85 }, // Robert, Albert
      { pattern: 'son', weight: 0.85 }, // Wilson, Jackson
      { pattern: 'ard', weight: 0.8 }, // Richard, Edward
      { pattern: 'rick', weight: 0.8 }, // Patrick, Frederick
      { pattern: 'les', weight: 0.75 }, // Charles, Miles
      { pattern: 'roy', weight: 0.75 }, // Troy, Leroy
      { pattern: 'ryan', weight: 0.75 }, // Bryan, Ryan
      { pattern: 'ton', weight: 0.7 }, // Clinton, Winston
      { pattern: 'ford', weight: 0.7 }, // Bradford, Clifford
      { pattern: 'vin', weight: 0.65 } // Kevin, Calvin
    ];

    // Strong female name patterns (endings)
    const strongFemaleEndings = [
      { pattern: 'ette', weight: 0.9 }, // Annette, Paulette
      { pattern: 'elle', weight: 0.9 }, // Michelle, Belle
      { pattern: 'ina', weight: 0.85 }, // Christina, Marina
      { pattern: 'yah', weight: 0.85 }, // Noriah, Aliyah
      { pattern: 'lah', weight: 0.85 }, // Noriah, Sarah
      { pattern: 'lyn', weight: 0.85 }, // Evelyn, Carolyn
      { pattern: 'anne', weight: 0.8 }, // Suzanne, Marianne
      { pattern: 'ella', weight: 0.85 }, // Isabella, Stella
      { pattern: 'icia', weight: 0.85 }, // Patricia, Alicia
      { pattern: 'ley', weight: 0.8 }, // Ashley, Shirley
      { pattern: 'acy', weight: 0.8 }, // Tracy, Stacy
      { pattern: 'ren', weight: 0.75 }, // Lauren, Karen
      { pattern: 'rie', weight: 0.75 }, // Marie, Carrie
      { pattern: 'ora', weight: 0.75 }, // Flora, Nora
      { pattern: 'ey', weight: 0.7 } // Sydney, Casey
    ];

    // Male name beginnings
    const maleBeginnings = [
      { pattern: 'jo', weight: 0.65 }, // John, Joseph
      { pattern: 'br', weight: 0.6 }, // Bruce, Brandon
      { pattern: 'gr', weight: 0.6 }, // Greg, Grant
      { pattern: 'fr', weight: 0.6 }, // Frank, Frederick
      { pattern: 'st', weight: 0.5 } // Steve, Stanley
    ];

    // Female name beginnings
    const femaleBeginnings = [
      { pattern: 'mel', weight: 0.6 }, // Melissa, Melody
      { pattern: 'syl', weight: 0.6 }, // Sylvia
      { pattern: 'bel', weight: 0.6 }, // Belinda, Isabella
      { pattern: 'flo', weight: 0.6 }, // Florence
      { pattern: 'mar', weight: 0.6 }, // Mary, Maria
      { pattern: 'ali', weight: 0.6 } // Alice, Alicia
    ];

    // Check strong patterns first
    strongMaleEndings.forEach(({ pattern, weight }) => {
      if (name.endsWith(pattern)) maleScore += weight;
    });

    strongFemaleEndings.forEach(({ pattern, weight }) => {
      if (name.endsWith(pattern)) femaleScore += weight;
    });

    // Check beginnings
    maleBeginnings.forEach(({ pattern, weight }) => {
      if (name.startsWith(pattern)) maleScore += weight;
    });

    femaleBeginnings.forEach(({ pattern, weight }) => {
      if (name.startsWith(pattern)) femaleScore += weight;
    });

    // Consonant patterns (more common in male names)
    const hasStrongConsonantCluster = /[bcd fg h j k l m n p q r s t v w x z]{3,}/.test(name);
    if (hasStrongConsonantCluster) maleScore += 0.3;
  };
};
```

```

// Soft sound patterns (more common in female names)
const hasSoftEnding = /[aeiou][ah][aeiou]e$/.test(name);
if (hasSoftEnding) femaleScore += 0.5;

// Final letter patterns
const finalLetter = name.slice(-1);
if ('aie'.includes(finalLetter)) femaleScore += 0.4;
if ('ntkds'.includes(finalLetter)) maleScore += 0.3;

// Vowel patterns
const vowelCount = (name.match(/[aeiou]/g) || []).length;
const nameLength = name.length;
const vowelRatio = vowelCount / nameLength;

if (vowelRatio > 0.45) femaleScore += 0.4;
if (vowelRatio < 0.25) maleScore += 0.3;

// Repeated letter patterns (more common in female names)
const hasRepeatedLetters = /(.)\1/.test(name);
if (hasRepeatedLetters) femaleScore += 0.3;

// Additional female patterns
const hasMultipleVowelClusters = (name.match(/[aeiou]{2,}/g) || []).length;
if (hasMultipleVowelClusters > 0) femaleScore += 0.3;

// Ensure minimum scores
maleScore = Math.max(maleScore, 0.2);
femaleScore = Math.max(femaleScore, 0.2);

// Calculate confidence percentage
const total = femaleScore + maleScore;
const maxScore = Math.max(femaleScore, maleScore);
const confidence = Math.min(Math.round((maxScore / total) * 100), 95); // Cap at 95%

return {
  gender: femaleScore > maleScore ? 'Female' : 'Male',
  confidence
};
};

const analyzePatterns = (names) => {
  if (!names.trim()) {
    setPatternAnalysis('No data to analyze yet. Enter some names above.');
```

```

  return;
}

const namesList = names.split('\n').filter(name => name.trim());
const patterns = {
  maleStartings: { '1': {}, '2': {}, '3': {}, '4': {}, '5': {} },
  maleEndings: { '1': {}, '2': {}, '3': {}, '4': {}, '5': {} },
  femaleStartings: { '1': {}, '2': {}, '3': {}, '4': {}, '5': {} },
  femaleEndings: { '1': {}, '2': {}, '3': {}, '4': {}, '5': {} }
};

// Process each name
namesList.forEach(nameInput => {
  const name = nameInput.trim().toLowerCase();
  if (!name) return;

  const result = predictGender(name);
  const confidence = result.confidence / 100;

  // Only consider patterns from predictions with confidence > 60%
  if (confidence < 0.6) return;

  // Get patterns of lengths 1-5 for both start and end
  for (let i = 1; i <= 5; i++) {
    if (name.length >= i) {
      const start = name.slice(0, i);
      const end = name.slice(-i);

      if (result.gender === 'Male') {
        patterns.maleStartings[i][start] = (patterns.maleStartings[i][start] || 0) + confidence;
        patterns.maleEndings[i][end] = (patterns.maleEndings[i][end] || 0) + confidence;
      } else {
        patterns.femaleStartings[i][start] = (patterns.femaleStartings[i][start] || 0) + confidence;
        patterns.femaleEndings[i][end] = (patterns.femaleEndings[i][end] || 0) + confidence;
      }
    }
  }
});

// Helper function to get top patterns
const getTopPatterns = (patternObj, count = 5) => {
  return Object.entries(patternObj)
    .sort((a, b) => b[1] - a[1])
    .slice(0, count)
    .map(([pattern, score]) => `${pattern} ${(score/namesList.length * 100).toFixed(1)}%`)
    .join("\n  ");
};
```

```

// Format analysis for each length and type
// Helper function to format top 5 patterns for a cell
const formatCell = (patterns) => {
  if ((patterns || patterns.length === 0) return '-';
  return Object.entries(patterns)
    .sort((a, b) => b[1] - a[1])
    .slice(0, 5)
    .map(([pattern, score]) => `${pattern} (${(score/namesList.length * 100).toFixed(1)}%)`)
    .join("\n");
};

// Create table header
let table = ["Pattern Analysis (based on " + namesList.length + " names)\n\n"];
table.push("length\\Male Start\\Male End\\Female Start\\Female End\\n");
table.push(".".repeat(105) + "\n");

// generate each row of the table for lengths 1-4
for (let length = 1; length <= 5; length++) {
  // get top 5 patterns for each category
  const maleStarts = formatCell(patterns.maleStartings[length.toString()]);
  const maleEnds = formatCell(patterns.maleEndings[length.toString()]);
  const femaleStarts = formatCell(patterns.femaleStartings[length.toString()]);
  const femaleEnds = formatCell(patterns.femaleEndings[length.toString()]);

  // Split each category into lines (they'll have 5 lines each)
  const maleStartLines = maleStarts.split("\n");
  const maleEndLines = maleEnds.split("\n");
  const femaleStartLines = femaleStarts.split("\n");
  const femaleEndLines = femaleEnds.split("\n");

  // Add the length indicator and first line
  table.push(`${length}\t${maleStartLines[0]}\t${maleEndLines[0]}\t${femaleStartLines[0]}\t${femaleEndLines[0]}\n`);

  // Add remaining lines with proper spacing
  for (let i = 1; i < 5; i++) {
    table.push(`${maleStartLines[i] || ""}\t${maleEndLines[i] || ""}\t${femaleStartLines[i] || ""}\t${femaleEndLines[i] || ""}\n`);
  }

  // Add separator between lengths
  table.push(".".repeat(105) + "\n");
}

table.push("\nNote: Percentages indicate frequency weighted by confidence scores.");
setPatternAnalysis(table.join(''));

```

```

table.push("\nNote: Percentages indicate frequency weighted by confidence scores.");

setPatternAnalysis(table.join(''));

setPatternAnalysis(table.join(''));

setPatternAnalysis(table.join(''));

setPatternAnalysis(analysisText);
};

const processNames = (text) => {
  const lines = text.split("\n");
  const results = {
    male: [],
    female: []
  };

  // Process and categorize each name
  lines.forEach(line => {
    const trimmedLine = line.trim();
    if (!trimmedLine) return;

    const result = predictGender(trimmedLine);
    const entry = {
      name: trimmedLine,
      confidence: result.confidence,
      formatted: `${trimmedLine}: ${result.gender} (${result.confidence}% confidence)`
    };

    if (result.gender === 'Male') {
      results.male.push(entry);
    } else {
      results.female.push(entry);
    }
  });
});

// Sort each category by confidence (descending)
results.male.sort((a, b) => b.confidence - a.confidence);
results.female.sort((a, b) => b.confidence - a.confidence);

```

```
// Format the output with headers and sorted results
const outputText = [
  `FEMALE NAMES (${results.female.length} total):`,
  ...results.female.map(entry => entry.formatted),
  "",
  `MALE NAMES (${results.male.length} total):`,
  ...results.male.map(entry => entry.formatted)
].join('\n');

setOutput(outputText);

// Analyze patterns whenever names are processed
analyzePatterns(text);
};
```

```
const handleInputChange = (e) => {
  const newInput = e.target.value;
  setInput(newInput);
  processNames(newInput);
};
```

```
return (
  <Card className="w-full max-w-4xl">
    <CardHeader>
      <CardTitle>Enhanced Name Gender Processor</CardTitle>
    </CardHeader>
    <CardContent className="space-y-4">
      <div>
        <label className="block text-sm font-medium mb-2">
          Input Names (one per line)
        </label>
        <textarea
          value={input}
          onChange={handleInputChange}
          className="w-full h-48 p-2 border rounded-md"
          placeholder="Enter names here..."
        />
      </div>
      <div>
        <label className="block text-sm font-medium mb-2">
          Processed Results (with confidence scores)
        </label>
      </div>
    </CardContent>
  </Card>
);
```

```
      <textarea
        value={input}
        onChange={handleInputChange}
        className="w-full h-48 p-2 border rounded-md"
        placeholder="Enter names here..."
      />
    </div>
    <div>
      <label className="block text-sm font-medium mb-2">
        Processed Results (with confidence scores)
      </label>
      <textarea
        value={output}
        readOnly
        className="w-full h-48 p-2 border rounded-md bg-gray-50"
      />
    </div>
    <div>
      <label className="block text-sm font-medium mb-2">
        Pattern Analysis
      </label>
      <textarea
        value={patternAnalysis}
        readOnly
        className="w-full h-48 p-2 border rounded-md bg-gray-50 font-mono text-sm"
      />
    </div>
  </CardContent>
</Card>
);
};

export default NameGenderProcessor;
```

Documentatio  
n

TXT

Create a data analysis dashboard that reads the input lines after a colon in this dataset.  
There will be 6 graphs in the react app: training loss, validation loss, precision, recall, F1, accuracy.  
Do not hard code the numbers, just give me an input text box that i can paste this data into and the program will read and parse it

I'll help you create a dashboard that can parse and visualize this data. First, let me analyze the data structure using the analysis tool to ensure our parsing logic works correctly.  
  
View analysis  
  
Great! Now that I've confirmed our parsing logic works correctly, I'll create a React dashboard with an input text box and six charts. I'll use Recharts for the visualizations and make sure to follow the Tailwind constraints.  
  

</> ML Metrics Dashboard  
Click to open component

  
I've created a responsive dashboard with the following features:  

1. A text input area where you can paste your metrics data
2. Automatic parsing of the input data
3. Six separate charts displaying:
  - Training Loss
  - Validation Loss
  - Precision
  - Recall
  - F1 Score
  - Accuracy
4. Interactive features including:
  - Tooltips on hover

ML Metrics Dashboard

Note

Epoch Training Loss Validation Loss Precision Recall F1 Accuracy

default 1 0.134500 0.124623 0.823550 0.855424 0.839184 0.964296

default 1 0.141100 0.130110 0.807950 0.843211 0.825204 0.962323

M/F tags (not sorted yet) 1 0.142800 0.131742 0.809442 0.842223 0.825507 0.962392

only names ending with 'k' tagged as female? 1 0.171800 0.157322 0.796921 0.819912 0.803078 0.954634

m/f beginnings & endings: 1 0.169600 0.161059 0.784449 0.814788 0.799331 0.953426

Training Loss

Configuration	Training Loss
default	0.134500
M/F tags (not sorted yet)	0.141100
m/f beginnings & endings	0.171800
all beginnings & endings sorting examples	0.169600

Validation Loss

Configuration	Validation Loss
default	0.124623
M/F tags (not sorted yet)	0.130110
m/f beginnings & endings	0.157322
all beginnings & endings sorting examples	0.161059

4. Interactive features including:

• Tooltips on hover

• Responsive layout (2 columns on larger screens, 1 column on mobile)

• Legend

• Grid lines for better readability

• Different colors for each metric

To use the dashboard:

1. Simply paste your metrics data into the text area

2. The charts will automatically update as you paste the data

3. Hover over any point on the charts to see the exact values

4. Each chart will show the progression of metrics across different configurations (using the note field as the x-axis)

The dashboard uses shadcn/ui components for the cards and text area, and Recharts for the visualizations. Error handling is included to notify you if there's any issue parsing the input data.

Would you like me to make any adjustments to the visualization or add any additional features?



## ← ML Metrics Dashboard

```
import React, { useState } from 'react';
import {
  LineChart,
  Line,
  XAxis,
  YAxis,
  CartesianGrid,
  Tooltip,
  Legend,
  ResponsiveContainer
} from 'recharts';
import { Card, CardHeader, CardTitle, CardContent } from "@components/ui/card";
import { Textarea } from "@components/ui/textarea";

const MetricsDashboard = () => {
  const [data, setData] = useState([]);
  const [error, setError] = useState('');

  const parseInputData = (text) => {
    try {
      const lines = text.split('\n')
        .filter(line => line.includes(':'))
        .map(line => {
          const parts = line.split(':')[1].trim().split(/\s+/);
          return {
            note: line.split(':')[0].trim(),
            epoch: parseFloat(parts[0]),
            trainingLoss: parseFloat(parts[1]),
            validationLoss: parseFloat(parts[2]),
            precision: parseFloat(parts[3]),
            recall: parseFloat(parts[4]),
            f1: parseFloat(parts[5]),
            accuracy: parseFloat(parts[6])
          };
        });
      setData(lines);
      setError('');
    } catch (err) {
      setError('Error parsing data. Please check the format.');
```

```
      console.error(err);
    }
  };

  const handleInputChange = (e) => {
    parseInputData(e.target.value);
  };

  const MetricChart = ({ title, datakey, color }) => (
    <Card className="w-full">
      <CardHeader>
        <CardTitle>{title}</CardTitle>
      </CardHeader>
      <CardContent>
        <div className="h-64">
          <ResponsiveContainer width="100%" height="100%">
            <LineChart data={data} margin={{ top: 5, right: 30, left: 20, bottom: 5 }}>
              <CartesianGrid strokeDasharray="3 3" />
              <XAxis dataKey="note" />
              <YAxis />
              <Tooltip />
              <Legend />
              <Line
                type="monotone"
                dataKey={datakey}
                stroke={color}
                dot={{ r: 4 }}
                activeDot={{ r: 8 }}
              />
            </LineChart>
          </ResponsiveContainer>
        </div>
      </CardContent>
    </Card>
  );
```

```

return (
  <div className="p-4 space-y-4">
    <Card>
      <CardHeader>
        <CardTitle>ML Metrics Dashboard</CardTitle>
      </CardHeader>
      <CardContent>
        <Textarea
          placeholder="Paste your metrics data here..."
          className="min-h-32"
          onChange={handleInputChange}
        />
        {error && (
          <div className="text-red-500 mt-2">{error}</div>
        )}
      </CardContent>
    </Card>
  </div>
);

```

```

    <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
      <MetricChart
        title="Training Loss"
        dataKey="trainingLoss"
        color="#8884d8"
      />
      <MetricChart
        title="Validation Loss"
        dataKey="validationLoss"
        color="#82ca9d"
      />
      <MetricChart
        title="Precision"
        dataKey="precision"
        color="#ffc658"
      />
      <MetricChart
        title="Recall"
        dataKey="recall"
        color="#ff7300"
      />
      <MetricChart
        title="F1 Score"
        dataKey="f1"
        color="#00c49f"
      />
      <MetricChart
        title="Accuracy"
        dataKey="accuracy"
        color="#0088fe"
      />
    </div>
  </div>
);
};

export default MetricsDashboard;

```