



<u>NOTE:</u>	
1.	REFER TO FREE PACKAGE FOR FURNITURE, BUILT-IN MILL WORK AND FINISH SPECIFICATIONS
2.	SMOKE DETECTORS, SPRINKLERS, AND OTHER EMERGENCY DEVICES TO BE LOCATED PER LOCAL CODE - INDICATED FOR INTENT ONLY.
3.	PROVIDE EMERGENCY LIGHTING PER LOCAL CODE. WALL DEVICES TO BE MOUNTED AT 12" A.F.F. TYPICAL LUNG.
4.	REFER TO HOME 2 SUITES BY HILTON STANDARDS MANUAL FOR ADDITION GUESTROOM, GUESTROOM BATH, GUESTROOM KITCHEN AND INDOOR POOL REQUIREMENTS.

CEILING LEGEND:	
A.	PRIMED AND PAINTED GYPSUM BOARD
B.	PRIMED AND PAINTED GYPSUM BOARD - MOISTURE RESISTANT

GR-###	FURNISHINGS LEGEND:
GR-100	OTTOMAN @ SOFA
GR-101	SLEEPER SOFA
GR-102	DINING CHAIR @ ONE BEDROOM SUITE
GR-103	EAST AFRICAN CHAIR
GR-200	SIDE TABLE LAMP
GR-201	DESK LAMP
GR-202	NIGHTSTAND SCONCE
GR-203	VANITY SCONCE
GR-204	SCONCE @ WALL HOOKS
GR-205	FLOOR LAMP
GR-206	TABLE LAMP (ADA)
GR-207	NIGHTSTAND SCONCE (DQ)
GR-208	NOT USED
GR-300	QUEEN HEADBOARD
GR-301	KING HEADBOARD
GR-302	VANITY
GR-303	ACCESSIBLE VANITY
GR-304-316	WORKING WALL
GR-317	DINING TABLE
GR-318	SOFA SIDE TABLE
GR-319	NIGHTSTAND @ RIGHT
GR-320	RIGHT DECORATIVE SHELF ABOVE DESK
GR-321	WALL SHELF @ BATHROOM
GR-322	DOUBLE QUEEN NIGHTSTAND
GR-323	NIGHTSTAND @ LEFT
GR-324	WALL SHELF @ ADA BATHROOM
GR-325	LEFT DECORATIVE SHELF ABOVE DESK
GR-400	BLACKOUT SHEER ROLLER SHADE
GR-401	ADA ADA ROLLER SHADE
GR-402	DIVIDER DRAPERY
GR-402.1	DIVIDER DRAPERY HARDWARE
GR-403	CLOSET DRAPERY
GR-404	CLOSET DRAPERY (ADA)
GR-405	DIVIDER DRAPERY (ADA)
GR-500	ARTWORK @ SLEEPER SOFA
GR-501	VANITY MIRROR
GR-502	FULL LENGTH MIRROR
GR-503	ART ABOVE TABLE
GR-600	QUEEN MATTRESS 5ET
GR-600.1	QUEEN BEDPAD
GR-601	KING MATTRESS 5ET
GR-601.1	KING BEDPAD
GR-602	QUEEN BED BASE
GR-602.ADA	QUEEN ACCESSIBLE BED BASE
GR-603	QUEEN BED SKIRT (ADA)
GR-603	KING BED BASE
GR-603.ADA	KING ACCESSIBLE BED BASE
GR-603.1	ACCESSIBLE KING BED SKIRT (ADA)
900	REFRIGERATOR
902	DISH-WASHER
903	TELEVISION
904	CLOCK/ RADIO
908	TU FURNITURE

KEY NOTES:	
1	PTAC UNIT
3	IN BATHROOM LOCATIONS ONLY, LIGHT SWITCH EQUIPPED WITH NIGHTLIGHT, MOUNTED SO TOP OF SWITCH IS 48" MAX A.F.F
4	MANUAL BLACK OUT ROLLER SHADE TO EXTEND 6" BEYOND WINDOW OPENING; SHEER ROLLER SHADE TO BE MOUNTED INSIDE WINDOW OPENING
5	SHOWER ENCLOSURE WITH TEMPERED GLASS DOOR
6	FLOOR DRAIN
7	PREMANUFACTURED SHOWER PAN
8	CEILING MOUNTED DRAPERY ROD - PROVIDE BLOCKING AS REQUIRED
9	ALTERNATE LOCATION OF DOOR FOR CONNECTING ROOMS TO ACCESSIBLE ROOMS - REFER TO OVERALL PLANS FOR LOCATION OF ACCESSIBLE ROOMS
10	DEDICATED CIRCUIT FOR DISHWASHER
11	RANGE TOP STYLE MICROWAVE AFFIXED TO WALL
12	MIRROR
13	BEGIN CARPET TILE THIS SIDE WITH FULL TILE - FIRST TWO ROWS OF TILE TO BE INSTALLED AROUND BUILT-IN CASEGOODS
14	SWITCH CONTROLLING GARBAGE DISPOSAL GANGED WITH DUPLEX REFER TO HADG FOR ACCESSIBLE ROOM REQUIREMENTS.
15	DEDICATED CIRCUIT FOR GARBAGE DISPOSAL
16	FIRE HORN IN STANDARD ROOMS. FIRE HORN/STROBE IN COMMUNICATION FEATURES ROOMS
17	LAYOUT AND CONSTRUCTION IS TO START AT REFRIGERATOR HOLD DIM. & PROCEED UP THE WALL FROM THAT END-FINAL INSTALLATION IS ROD AT CLOSET. TO BE SCRIBED AT WALL AS REQUIRED; END OF KITCHEN MUST TERMINATE AT OUTSIDE FACE OF BATHROOM WALL.
18	RECESSED CEILING LIGHT FOR WET LOCATIONS WITH SHATTER PROOF LENS
19	TOILET EXHAUST GRILLE
20	MAKE-UP AIR DIFFUSER
21	EXTENT OF SLEEPER SOFA
22	APPROXIMATE LOCATIONS OF MILLWORK SUPPORTS ON FLOOR. PROVIDE SHIMS OR LEVELERS UNDER SUPPORTS TO PREVENT CARPET CRUSHING
23	ROOM SIGNAGE
24	HARD WIRED THERMOSTAT FOR PTAC, MOUNTED 48" MAX TO TOP OF DEVICE. COMMUNICATION BETWEEN THERMOSTAT AND PTAC MAY BE WIRELESS.
25	EXTEND J-BOX, DEVICE AND COVER PLATE FLUSH WITH MILLWORK BACK PANEL
26	DROPPED GYPSUM BOARD BULKHEAD @ ROUGH OPENING - WHERE PRE-MANUFACTURED SHOWER INSERT IS INDICATED MEASURE ROUGH OPENING FROM FACE OF GYPSUM BOARD
28	DOORBELL ON/OFF SWITCH (COMMUNICATION FEATURES ROOMS ONLY) SIGNAGE AS REQ'D.
30	EDGE OF PTAC ABOVE CARPET TILES
31	MIN. CEILING HEIGHT MUST BE MAINTAINED - REFER TO HOME 2 SUITES BY HILTON STANDARDS MANUAL
32	FRAMING SUBCONTRACTOR TO PROVIDE 3/4" F.R.T. PLYWOOD BLOCKING TO RECEIVE ITEM INDICATED - EXTEND FULL LENGTH OF OBJECT
33	GENERAL CONTRACTOR TO COORDINATE WITH FIXTURE FABRICATOR WHERE NECESSARY TO PROVIDE PROPER BLOCKING IN WALL FOR ITEM KEYNOTED
34	BI-PASS SLIDING GLASS DOOR, BRUSHED ALUMINUM FINISH, CLEAR GLASS, WITH 24" BAR PULL HARDWARE
35	SWITCHES CONTROLLING MECHANICAL SHAPES - REFER TO FFE MANUAL
36	OUTLET ABOVE FOR MICROWAVE - REFER TO ROOM ELEVATION MOUNT DEVICE HORIZONTALLY - FACE PLATE TO BE WHITE
37	REQUIRED ACCESSIBLE CLEAR FLOOR AREA DESIGNATION
39	CENTER ARTWORK OVER SOFA
40	COUNTERTOP MICROWAVE
41	GRAPHIC ART REFER TO ACCESSORIES LEGEND AND CONSTRUCTION PLAN
42	ACCESSIBLE VANITY; CLEAR AREA OF SINK/VANITY MUST BE ACCESSIBLE
43	ADDITIONAL HORN/STROBE LOCATED IN C.F. BATHROOMS ONLY
44	WAP IN 3-GANG BOX MOUNTED VERTICALLY UNDER DESK. MAINTAIN 6" LEAKAGE FROM ALL BOXES. TYP ALL GUEST ROOMS. COORDINATE WALL LOCATION WITH CASEGOODS TO AVOID CONFLICTS. VISIT CONNECTED ROOM:HILTON.COM FOR CURRENT WIRELESS INTERNET REQ'S AND LIST OF APPROVED INTEGRATORS.
45	EACH CABLE MUST HOTSPUR BETWEEN THE GUEST ROOM AND THE IDF ON EACH FLOOR. VISIT CONNECTED ROOM:HILTON.COM FOR CURRENT REQUIREMENTS AND OPTIONS
46	OPTION WIRED DATA CONNECTION FOR GUEST USE: A) ADD CAT6 RJ-45 CABLE JACK AND PATCH CORD THROUGH DESKTOP GROMMET - OR - B) PATCH CORD FROM WAP PORT THROUGH DESKTOP GROMMET. IF OUTLET IS LOCATED ABOVE THE DESK, REMOVE GROMMET AND PATCH CORD.
47	TV CONNECTIONS FOR FREE-TO-GUEST CONTENT: A) NO SMART TV; COAX CABLE BEHIND TV. CAT6 RJ-45 JACK BEHIND TV. PATCH CORD TO WAP UNDER DESK. PATCH CORD TO EDGE CONTROLLER FOR CONNECTED ROOM. MIN. 6" CLEARANCE FROM WALL BOXES - OR - B) SMART TV-INTERNET PROTECTED TELEVISION COAX NOT REQ'D. CAT6 RJ-45 JACK BEHIND TV. PATCH CORD TO WAP UNDER DESK. PATCH CORD TO EDGE CONTROLLER FOR CONNECTED ROOM. CAT6 RJ-45 JACK BEHIND TV IN ONE-BEDROOM TV. MIN. 6" CLEARANCE FROM WALL BOXES. VISIT HILTONTV.COM FOR ADDITIONAL INFORMATION.
48	PROVIDE HINGE STOP AT DOOR
49	HARDWIRED BLACK OUT ROLLER SHADE WITH NO EXPOSED WIRES
50	PROVIDE OUTLET FOR UNDER CABINET LIGHTING BY OTHERS. COORDINATE WITH ELECTRICAL. AT ACC. GUESTROOMS, THE COOK LIGHT AT MOUNTED MICROWAVE FOR NON-ACC ROOMS WILL SUFFICE
51	ROLLER SHADE TO EXTEND PAST WINDOW FRAME TO REDUCE LIGHT LEAKAGE - REFER TO SPECIFICATION AND MANUFACTURER'S INSTALLATION REQUIREMENTS
52	DEDICATED CIRCUIT FOR INDUCTION BURNER

SHEET.

A501