



NOTE:	1. REFER TO FFSE PACKAGE FOR FURNITURE, BUILT-IN MILLWORK AND FINISH SPECIFICATIONS 2. SMOKE DETECTORS, SPRINKLERS, AND OTHER EMERGENCY DEVICES TO BE LOCATED PER LOCAL CODE - INDICATED FOR INTENT ONLY. 3. PROVIDE EMERGENCY LIGHTING PER LOCAL CODE. WALL DEVICES TO BE MOUNTED AT 12" A.F.F. TYPICAL U.N.O. 4. REFER TO HOME 2 SUITES BY HILTON STANDARDS MANUAL FOR ADDITION GUESTROOM, GUESTROOM BATH, GUESTROOM KITCHEN AND INDOOR POOL REQUIREMENTS.
-------	---

KEY NOTES:	
1	PTAC UNIT
3	IN BATHROOM LOCATIONS ONLY, LIGHT SWITCH EQUIPPED WITH NIGHTLIGHT, MOUNTED SO TOP OF SWITCH IS 48" MAX A.F.F
4	MANUAL BLACK OUT ROLLER SHADE TO EXTEND 6" BEYOND WINDOW OPENING; SHEER ROLLER SHADE TO BE MOUNTED INSIDE WINDOW OPENING
5	SHOWER ENCLOSURE WITH TEMPERED GLASS DOOR
6	FLOOR DRAIN
7	PREMANUFACTURED SHOWER PAN
8	CEILING MOUNTED DRAPERY ROD - PROVIDE BLOCKING AS REQUIRED
9	ALTERNATE LOCATION OF DOOR FOR CONNECTING ROOMS TO ACCESSIBLE ROOMS - REFER TO OVERALL PLANS FOR LOCATION OF ACCESSIBLE ROOMS
10	DEDICATED CIRCUIT FOR DISHWASHER
11	RANGE TOP STYLE MICROWAVE AFFIXED TO WALL
12	MIRROR
13	BEGIN CARPET TILE THIS SIDE WITH FULL TILE - FIRST TWO ROWS OF TILE TO BE INSTALLED AROUND BUILT-IN CASEGOODS
14	SWITCH CONTROLLING GARBAGE DISPOSAL GANGED WITH DUPLEX REFER TO HADG FOR ACCESSIBLE ROOM REQUIREMENTS.
15	DEDICATED CIRCUIT FOR GARBAGE DISPOSAL
16	FIRE HORN IN STANDARD ROOMS. FIRE HORN/STROBE IN COMMUNICATION FEATURES ROOMS
17	LAYOUT AND CONSTRUCTION IS TO START AT REFRIGERATOR HOLD DIM. & PROCEED UP THE WALL FROM THAT END-FINAL INSTALLATION IS ROD AT CLOSET. TO BE SCRIBED AT WALL AS REQUIRED. END OF KITCHEN MUST TERMINATE AT OUTSIDE FACE OF BATHROOM WALL.
18	RECESSED CEILING LIGHT FOR WET LOCATIONS WITH SHATTER PROOF LENS
19	TOILET EXHAUST GRILLE
20	MAKE-UP AIR DIFFUSER
21	EXTENT OF SLEEPER SOFA
22	APPROXIMATE LOCATIONS OF HILLWORK DESKTOP ON FLOOR. PROVIDE SHIMS OR LEVELERS UNDER SUPPORTS TO PREVENT CARPET CRUSHING
23	ROOM SIGNAGE
24	HARD WIRED THERMOSTAT FOR PTAC, MOUNTED 48" MAX TO TOP OF DECK. COMMUNICATION BETWEEN THERMOSTAT AND PTAC MAY BE WIRELESS.
25	EXTEND J-BOX, DEVICE AND COVER PLATE FLUSH WITH HILLWORK BACK PANEL
26	DROPPED GYPSUM BOARD BULKHEAD @ ROUGH OPENING - WHERE PRE-MANUFACTURED SHOWER INSERT IS INDICATED MEASURE ROUGH OPENING FROM FACE OF GYPSUM BOARD
28	DOORBELL ON/OFF SWITCH (COMMUNICATION FEATURES ROOMS ONLY) SIGNAGE AS REQ'D.
30	EDGE OF PTAC ABOVE CARPET TILES
31	MIN. CEILING HEIGHT MUST BE MAINTAINED - REFER TO HOFIE 2 SUITES BY HILTON STANDARDS MANUAL
32	FRAMING SUBCONTRACTOR TO PROVIDE 3/4" F.R.T. PLY-WOOD BLOCKING TO RECEIVE ITEM INDICATED - EXTEND FULL LENGTH OF OBJECT
33	GENERAL CONTRACTOR TO COORDINATE WITH FIXTURE FABRICATOR WHERE NECESSARY TO PROVIDE PROPER BLOCKING IN WALL FOR ITEM KEYNOTED
34	BI-PASS SLIDING GLASS DOOR, BRUSHED ALUMINUM FINISH, CLEAR GLASS, WITH 24" BAR PULL HARDWARE
35	SWITCHES CONTROLLING MECHANICAL SHADES - REFER TO FFE MANUAL
36	OUTLET ABOVE FOR MICROWAVE - REFER TO ROOM ELEVATION MOUNT DEVICE HORIZONTALLY - FACE PLATE TO BE WHITE
37	REQUIRED ACCESSIBLE CLEAR FLOOR AREA DESIGNATION
39	CENTER ARTWORK OVER SOFA
40	COURTOUT MICRO WAVE
41	GRAPHIC ART REFER TO ACCESSORIES LEGEND AND CONSTRUCTION PLAN
42	ACCESSIBLE VANITY; CLEAR AREA OF SINK/VANITY MUST BE ACCESSIBLE
43	ADDITIONAL HORN STROBE: LOCATED IN C.F. BATHROOMS ONLY
44	WAP IN 3-GANG BOX MOUNTED VERTICALLY UNDER DESK, MAINTAIN 6" BETWEEN ALL BOXES, TYP ALL GUESTROOMS. COORDINATE WALL LOCATION WITH CASEGOODS TO AVOID CONFLICTS. VISIT CONNECT ROOM/HILTON.COM FOR CURRENT WIRELESS INTERNET REQ'S AND LIST OF APPROVED INTEGRATORS.
45	EACH CABLE MUST HOMERUN BETWEEN THE GUESTROOM AND THE IDF ON EACH FLOOR; VISIT CONNECTROOM.HILTON.COM FOR CURRENT REQUIREMENTS AND OPTIONS.
46	OPTION WIRE D DATA CONNECTION FOR GUEST USE: A) ADD CAT6 RJ-45 CABLE JACK AND PATCH CORD THROUGH DESKTOP GROMMET - OR - B) PATCH CORD FROM WAP PORT THROUGH DESKTOP GROMMET. IF OUTLET IS LOCATED ABOVE THE DESK, REMOVE GROMMET AND PATCH CORD.
47	TV CONNECTIONS FOR FREE-TO-GUEST CONTENT: A) NO SMART TV; COAX CABLE BEHIND TV. CAT6 RJ-45 JACK BEHIND TV, RUN IN SHIRT TUBE IN WALL TO WAP UNDER DESK. PATCH CORD TO EDGE CONTROLLER FOR CONNECTED ROOM. MIN. 6" CLEARANCE FROM WALL BOXES - OR - B) SMART TV-INTERNET PROTOCOL TELEVISION CANNOT REQ'D. CAT6 RJ-45 JACK BEHIND TV. CAT6 RJ-45 JACK BEHIND TV IN WALL TO WAP UNDER DESK. PATCH CORD TO EDGE CONTROLLER FOR CONNECTED ROOM. CAT6 RJ-45 JACK BEHIND TV IN ONE-BEDROOM TV. MIN. 6" CLEARANCE FROM WALL BOXES. VISIT HILTONHDTV.COM FOR ADDITIONAL INFORMATION.
48	PROVIDE HINGE STOP AT DOOR
49	HARDWIRED BLACK OUT ROLLER SHADE WITH NO EXPOSED WIRES
50	PROVIDE OUTLET FOR UNDER CABINET LIGHTING BY OTHERS. COORDINATE WITH ELECTRICAL AT ACC. GUESTROOMS; THE COOK LIGHT AT MOUNTED MICROWAVE FOR NON-ACC ROOMS WILL SUFFICE
51	ROLLER SHADE TO EXTEND PAST WINDOW FRAME TO REDUCE LIGHT LEAKAGE - REFER TO SPECIFICATION AND MANUFACTURER'S INSTALLATION REQUIREMENTS
52	DEDICATED CIRCUIT FOR INDUCTION BURNER

GENERAL NOTES

M MAUST
ARCHITECTURAL
SERVICES
DIVISION OF
L.E.M., INC.
112 NORTH MAIN STREET
GOSHEN, INDIANA 46526

* Architects
* Planners
* Consultants
* Construction Mgmt.
* Rule 5 and M54 Filing
PHONE (574) 537-8500
FAX (574) 537-0808



SHEET SIZE 24x36

FT. WAYNE, INDIANA.

REVISIONS:

PRELIMINARY - NOT
FOR CONSTRUCTION

DATE: 05/01/26

JOB NO.: MAS-26-105

NAME: _____

GUEST BATHROOM

ELEVATIONS

SHEET:

A509