

Tonnage Emails:

Doc-No. 12940840 25/MAY/2026 (MON) 10:48 (+0300)

PRIME MARITIME INC. - PIRAEUS
71, Akti Miaouli Str – 7th floor
TEL:+30 210 4527001/2/3/4
E-mail:chartering@primemaritime.gr, www.primemaritime.gr

DEAR SIRs

GOOD DAY

OUR DIRECT OWS OPEN AS FOLLOWS

PLS PPSE SUIT

PACIFIC

=====

SARONIC CHAMPION (93K – SCRUBBER FITTED / 2011) – OPEN VUNG ANG,
VIETNAM 08-12 JUNE

SARONIC CHAMPION

LIBERIA FLAG

BUILT 2011

CLASS LR

ABT 93.116 DWT ON ABT 14.90 MTRS SSW (SCANTLING)

LOA 229.253 MTRS / BEAM 38.00 MTRS

GRAIN CAP ABT 110.330 CBM

7/7 HO/HA – SCRUBBER FITTED

SPEED / CONS (INCLUDING A/E)

BALLAST : ABT 12.75 KNOTS ON ABT 30.50 MTS IFO 380 CST + ABT 0,1 MTS LSGO

LADEN : ABT 11.75 KNOTS ON ABT 30.50 MTS IFO 380 CST + ABT 0,1 MTS LSGO

PORT/ANCHORAGE CONSUMPTION:

IDLE: ABT 3.5 MT IFO 380 CST + ABT 1.8 MTS LSGO

WORKING: ABT 4.0 MT IFO 380 CST + ABT 1.8 MTS LSGO

IN CASE OF COLD/HOT CLIMATES AN ADDITIONAL ABT 1.5 MT LSGO DAILY.

ADA

BEST REGARDS,

GEORGE RACHIOTIS

+30 699 223 8161

&

PAVLOS PANTELIS

+30 697 083 5423

Pls note our e-mail addresses:

chartering@primemaritime.gr	for all your orders
position@primemaritime.gr	for all your vessels positions
operation@primemaritime.gr	for post fixing/operation matters
snp@primemaritime.gr	for s&p department

TELIX MSG: 0C7E3-00 25/05/26 10:20 +03:00

/ VP

good day,

PLS PR,OSE FOR THE BELOW TONNAGE list:

PACIFIC OCEAN

=====

MV SHENG AN HAI DWT 56564 OPEN XIAMEN, china O/A 2ND JUNE 2026

MV FENG HUI HAI DWT 63260 OPEN GUANGZHOU, CHINA O/A 6TH JUNE 2026

MV YUANPING SEA DWT 55646 OPEN MANILA, PHI O/A 3RD JUNE 2026

MV SHENG DE HAI DWT 56721 OPEN SAMALAJU, MALAYSIA O/A 3RD JUNE 2026

INDIAN OCEAN

=====

MV YIN HUA 1 DWT 46613 OPEN CHITTAGONG, B.DESH O/A 5TH JUNE 2026

MV BI JIA SHAN DWT 56623 OPEN GWADAR, PAKISTAN O/A 2ND JUNE 2026

MV yuanning sea DWT 55580 OPEN SOHAR, OMAN O/A 30TH may 2026

MV COS ORCHID DWT 55550 OPEN DAR ES SALAAM, TANZANIA O/A 1ST JUNE 2026

VSL PARTICULAR:

=====

M/V: SHENG AN HAI

BUILT: 2012.12

FLAG: CHINA

CLASS: CCS

LOA 189.99M/ BEAM 32.26M / M.DEPTH 18M/ LBP 185M

DWT 56564.4MT ON 12.8M SSW DRAFT-TPC 58.8

INTL TONNAGE: 32976GT/ 19142NT

HO/HA: 5/5

GRAIN 71634.09CBM

BALE 68162.27CBM

ELECTRIC HYDRAULIC HATCH COVERS.

GEARS: 4*30T (HOOK USE) OR 24T(GRAB USE)

NUMBER OF GRABS: 4*6~12CBM

DETAILS AS ATTACHED VSL DESCRIPTION.

SPD/CONS:

BALLAST: ABT 12.5 KNOTS ON 23 MT LSFO 380

LADEN: ABT 12 KNOTS ON 24 MT LSFO 380

PORT IDLE: ABT 2.8 MT /LSFO 0.05MT/MGO PER DAY

PORT WORKING: ABT 5.6 MT/LSFO 0.05MT/MGO PER DAY

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS), NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE. IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

ALL DETAILS ABOUT

MV FENG HUI HAI

2017 BLT HONG KONG FLAG SDSTBC

63260.8 DWT ON 13.30 M SSW TPC=62.3T/CM

LOA/BEAM 199.9/32.26M

GT/NT 36378/21646

5 HO/5 HA

CARGO HOLDS CO2 FITTED.

78771.0 /73430CBM GRAIN/BALE CAPACITY

4 X 30 TON CRANES AND 4 X12 CMB GRAB

ABOUT 11.0/10.5 KNOTS ON ABOUT 20.5MT/21.0MT LSFO (380) + 0.05MT MGO

ON BALLAST/LADEN IN GOOD WEATHER CONDITION.

5.0/3.0MT/D LSFO + 0.1 MT MGO IN PORT WHEN WORK/IDLE VESSEL BURNS MGO IN M/E

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN

SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS), NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE. IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

ALL DETAILS ABOUT

MV SHENG DE HAI

IMO NO. : 9663178 CALL SIGN: BPNY

PORT OF REGISTRY: HAIKOU

FLAG: PRC CLASS: CCS

BUILDER : COSCO(DALIAN)SHIPYARD CO.,LTD.,CHINA

DATE OF DELIVERY: NOVEMBER 2013

TYPE : BULK CARRIER NUMBER OF HATCH : 5 NUMBER OF HOLD: 5

LOA : 189.99M LBP : 185M BREADTH: 32.26M DEPTH: 18.00M

SUMMER DWT:56704.2MT DRAFT:12.8M TPC : 58.8 (T/CM)

GRAIN CAPACITY: 71634.1CBM

GROSS TONNAGE / NET TONNAGE: 32973 / 19142 PANAMA TONNAGE:27337

MAIN ENGINE: DMD MAN B&W 6S50MC-C(MARK7) M/E POWER: 12890PS(9480KW)

AUXILIARY ENGINE: DAIHATSU 5DK-20, OUTPUT: 600KW * 900RPM

GEAR AND GRAB: 4X30MT ELECTRO-HYDRAULIC SINGLE DECK CRANE AND
4X12CBM GRABS

HATCH COVER TYPE: TRANS-FOLDING TYPE

SPEED/CONS (FOR GUIDANCE ONLY AND WOG):

ABT 13K ON LSFO ABT 24MT(B) / ABT 12K ON LSFO ABT 25MT(L) + ABT 0.05MDO AT
SEA

PORT IDLE : ABT LSFO 3.0 MT+ ABT 0.1 MDO (MT/24HOURS)

PORT WORKING : ABT LSFO 5.0 MT+ ABT 0.2MDO (MT/24HOURS)

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST
WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN
SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING
POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED
WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN
BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS),NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE. IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

ALL DETAILS ABOUT

MV YIN HUA 1

2013 BLT CHINA FLAG SDBC

CALL SIGN: BPOD

IMO NUMBER: 9673501

MMSI: 413297610

CLASS:CCS

DWT 46613 MT ON 10.90 M SSW TPC 57.7

LOA/BEAM 189.99/32.26

GRT/NRT 29232/15729

5 HO/5 HA

CARGO HOLDS CO2 FITTED.

60276.1 CBM GRAIN/56986.3 CBM BALE CAPACITY

H1/10833.3M3 H2/12841.7M3 H3/12182.8M3 H4/12815.5M3

H5/11602.8M3

4X36T CRANE/GRAB 4X12 CBM

SPEED/ CONS:

ABT 11.5KNOTS(BALLAST) ON ABT 19.00MTS LSFO 380 CST

ABT 10.5KNOTS(LADEN) ON ABT 20.00MTS LSFO 380 CST

IDLE/WORKING ABT 3MTS/5MTS LSFO

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST
WATER AT SEA,STARTING/STANDBY/STOPPING ENGINES,

WHILE MANEUVERING IN SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT
OF

PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS,

NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL
VLSFO

WHEN BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER
CONDITION

AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4
AND

DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO
1.25

METERS),NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL.

EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER"

PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN
0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL
ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST
EDITION

NOT AVAILABLE.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL
CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR
CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

ALL DETAILS ABOUT

MV BI JIA SHAN

HONG KONG/11, SDBC, GRABBER

56,625 MTDW ON 12.80M SSW

LOA/BM 189.99 / 32.26M, GT/NT 32,962 / 19,142

GRAIN CAPAC: 71,634.09CBM

5HO/5HA GRABS 4 X 12.0 CBM

CRANE 4 X 30T (HOOK USE) OR 24T (GRAB USE)

HATCH COVERS: WATER-TIGHT DOUBLE SKIN FOLDING TYPE WITH FLAT

TOP AND OUT PLACED, HYDRAULIC CYLINDERS

SPEED:

ABT 11.0KTS (BALLAST) ON ABT 18.5 MT LSFO 380CST

ABT 10.0KTS (LADEN) ON ABT 19.0MT LSFO 380CST

PORT CONS: ABT 3.50MT LSFO PER DAY (IDLE)

ABT 5.50MT LSFO PER DAY (WORKG)

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS), NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE. IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

ALL DETAILS ABOUT

MV YUANNING SEA

2004BLTPANAMA FLAG SDSTBC

55,580DWT ON 12.52M SSW TPC 56.4

LOA/BEAM 189.94/32.26M

GT/NT 30,881/18,188

5 HO/5 HA

69,451.6/65,978.9 CBM GRAIN/BALE CAPACITY

4 X 30TON CRANES, 4 X 6-10 CBM GRAB

ABOUT 11.0/10.5 KNOTS ON ABOUT 17.0/18.0 MT LSFO (380) ON BALLAST/LADEN IN GOOD WEATHER CONDITION.

4.6 MT LSFO + 0.2 MTMGO/3.5 MT LSFO + 0.2 MTMGO IN PORT WHEN WORK/IDLE

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS),NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE.IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

ALL DETAILS ABOUT

MV. COS ORCHID

DWT 55550 MT DRAFT OF 12.5 M SSW

BUILT 2006 FEB 23 EX NANTONG-KAWASHAKI SHIPYARD

SINGAPORE FLAG SDBC

LOA/BEAM 189.9/32.26M TPC 56.4

GRT/NRT 30953/18171

5 HO/HA 4X30T CRANE/GRAB 4X12CUM

GRAIN 69450 CBM

SPEED & CONSUMPTION BASIS SCANTLING DRAFT:

- LADEN ABOUT 12.35 KNOTS ON ABOUT 24.6 MT LSFO+ ABT 0.1MTS LSMGO
- BALLAST ABOUT 12.65 KNOTS ON ABOUT 23.5 MT LSFO+ABT 0.1MTS LSMGO
- PORT IDLE ABOUT 3.5MT LSFO+ ABT 0.1MTS LSMGO
- WORKING ABOUT 5.0MT LSFO + ABT 0.1MTS LSMGO

ECO SPEED FOR REFERENCE ONLY WITHOUT GUARANTEE:

- ABT 12.0 KTS (BALLAST) ON ABT 22.5 MT LSFO 380CST+ABT 0.1MTS LSMGO
- ABT 12.0 KTS (LADEN) ON ABT 23.5 MT LSFO 380CST+ABT 0.1MTS LSMGO

(ALL ABOUT MEANS AN ALLOWANCE OF 0.5 KNOT ON SPEED AND 5% ON CONSUMPTION)

BUNKER QUALITY - VLFO ISO 8217-2017(E), LSMGO ISO 8217-2017(E).

(LSFO SUPPLIED SHOULD BE IN COMPLIANCE WITH MARPOL 73/78 ANNEX VI)
LSMGO WITH SULPHUR CONTENT AT OR BELOW 0.1% LSMGO

CHARTERERS TO COMPLY WITH FUEL SULPHUR CONTENTS AS PER LATEST REQUIREMENTS OF MARPOL ANNEX VI.

VESSEL ONLY HAVE ONE MGO TANK AND CAN'T SEPARATE, OWNERS WILL AGREE MIXING LSMGO WITH WHICH ALREADY ON BOARD.

VESSEL HAS LIBERTY TO CONSUME DIESEL OIL BY BOTH M/E AND A/E WHENEVER VESSEL ENCOUNTER HEAVY SEA / SEVERE WEATHER CONDITIONS, MANEUVERING, IN/OUT OF PORTS, NAVIGATING IN SHALLOW / RESTRICTED / BUSY / CONGESTED WATER, CANALS AND RIVERS, STARTING/ STOPPING OF A/E, BURNING OF SLUDGE OIL BY INCINERATOR, DURING LOW LOAD OR UNSTEADY

LOADING OPERATION OF A/E.VSL WILL BURN ADDITIONAL 2MT LSFO PER DAY
WHEN HEAVY BALLASTING /DEBALLASTING.

GOOD WEATHER CONDITION IN THS C/P SHALL MEANS ALL WEATHER CONDITONS
NOT EXCEEDING WIND FORCE BEAUFORT FOUR, DOUGLAS SEA STATE THREE, NO
ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL.THE VESSEL'S
PERFORMANCE SHALL ONLY BE ASSESSED ON THE BASIS OF ITS PERFORMANCE
IN GOOD WEATHER AS DEFINED IN THIS DESCRIPTION. WHERE CHARTERERS
PROVE THAT AN UNDER-PERFORMANCE HAS OCCURRED DURING A GOOD
WEATHER PERIOD, ANY CLAIMS ARISING THEREFROM SHALL BE RESTRICTED TO
THAT GOOD WEATHER PERIOD ONLY, AND NO CLAIMS WHATSOEVER MAY BE
BROUGHT FOR UNDERPERFORMANCE, LOSS OF TIME, OR OVER-CONSUMPTION
DURING PERIODS OF TIME THAT ARE NOT GOOD WEATHER PERIODS.

ALL DETAILS ABOUT

END

Doc-No. 12939935 25/MAY/2026 (MON) 08:41 (+0300)

PRIME MARITIME INC. - PIRAEUS
71, Akti Miaouli Str – 7th floor
TEL:+30 210 4527001/2/3/4
E-mail:chartering@primemaritime.gr, www.primemaritime.gr

GOOD DAY

OUR CLOSE OWS OPEN ASF

PLS PPSE SUIT

MV TRUE FRIEND/51K/ 09 - BEJAIA , 1ST JUNE ONW - EX OUR CP

MV TRUE FRIEND
=====

OPEN HATC BOX

DWT: 51.241/

BUILT : 2009

FLAG: BARBADOS

BULK CARRIER

CLASSIFICATION: NK

GROSS TONNAGE (INTERNATIONAL: 30.655

NET TONNAGE (INTERNATIONAL): 15.707

LENGTH OVER ALL (LOA): 182.98 M

TPC : 54.97 M/T

(L.B.P): 178 M

MOULDED BREADTH: 32.26 M

MOULDED DEPTH: 17.45 M

5/5 HO/HA

GRAIN : ABT 59,676

CRANES: 4X30.5T (OUTREACH: ABT 9.87M/R MAX)

NIL GRABS

SPEED/CONSUMPTION:

ALL SPEED/CONSUMPTION ARE GIVEN BASIS ABT & GOOD WEATHER CONDITION FOR 12 CONSECUTIVE HOURS, WINDS UP AND INCLUDING BEAUFORT 4/TOTAL COMBINED (SEA AND SWELL) SIGNIFICANT WAVE HEIGHT CONFINED TO LIMITS OF MAXIMUM 1.5

METRES, CURRENTS CAN/WILL BE FACTORED IN UPON VOYAGE EVALUATION TO REFLECT THE TRUE PERFORMANCE OF THE VESSEL.

MAIN ENGINE: MITSUI MAN-BMW - 6S50 MC-C

MARK 7 MCO: 7.700KWx104 RPM

#ECO SP&CO

11.0K@21.5 MT/(BALLAST) &0.25MGO

11.0K@22.0 MT (LADEN)&0.25MGO.

#PORT:

IDLE 2.5 IFO + 0.5MGO.

WORKING: 5.0 IFO+0.5MGO

BEST REGARDS

KOSTAS SOTIROPOULOS

MOB : +30 698 03 97 728

Pls note our e-mail addresses:

chartering@primemaritime.gr	for all your orders
position@primemaritime.gr	for all your vessels positions
operation@primemaritime.gr	for post fixing/operation matters
snp@primemaritime.gr	for s&p department

TELIX MSG: 0C2ZL-00 22/05/26 10:55 +03:00

- / KP

GOOD DAY,

PLEASED TO HEAR.

MV BLUE STAR (38K DWT) - OPEN 25 MAY GABES, TUNISIA

GEARED SELF-TRIMMING SINGLE DECK BULK CARRIER

BUILT 2011 SAMHO SHIPBUILDING CO LTD, KOREA

LIBERIAN FLAG / CLASSED HIGHEST ABS / IMO NO 9579327

37,947 MTDWT ON 10,63 M SSW (TPC 49,16)

LOA 179,98 / BEAM 30,00M

GT/NT 23.204/11.900

5 H/H

CARGO HOLDS CUBIC 48.133,5/46.689,5 CBM (GRAIN/BALE)

NO1 8.117 / 7.874

NO2 10.240 / 9.933

NO3 10.269 / 9.960

NO4 10.269 / 9.960

NO5 9.237 / 8.959

FOLDING TYPE H/COVERS

NO1: (L)16,00 X (B) 12,3 M F / 17,00M A

NO2-5: (L)19,20 X (B) 20.20M

TANKTOP DIMENSIONS

NO1: (L) 25,60M /(B) 4,20M F - 19,80M A

NO2,3,4:(L) 24,00M /(B)22,10M F - 22,10M A

NO5: (L) 24,80M /(B)22,10M F - 13,80M A

TANK TOP STRENGTH (UNIFORM LOAD): 20,00 MT/M2

H/COVER STRENGTH (UNIFORM LOAD): 1,75 MT/M2

4 X 35MT CRANES

CO2 FITTED / ELECTRICAL VENTILATED

BWTS FITTED (ALPHA LAVAL)

MAIN ENGINE: MAN-B&W 6S42MC - 7.929 BHP

GENERATORS: 3 X 600 KW

BOW THRUSTER: N/A

CEMENT HOLE: ON THE TOP OF CARGO HATCH COVER

SPEED AND CONSUMPTION:

ABT 11,0 KN ON ABT 17,0 (L)/ ABT 11,5 ON ABT 16,0 (B) MT IFO + 0,2 MT MGO INCL D/G

PORT CONSUMPTION:

2,5 MT IDLE / 5 MT (WORKING CRANES) IFO + 0,2MT MGO

ABOVE SPEED & CONSUMPTION FIGURES ARE GIVEN BASIS GOOD WEATHER CONDITIONS FOR 24 CONSECUTIVE HOURS NOT EXCEEDING WIND FORCE 4 OF BEAUFORT SCALE AND DOUGLAS SEA STATE 3 (SIGNIFICANT WAVE HEIGHT OF MAX 1,25 METER), WITH NO ADVERSE CURRENTS, NO NEGATIVE INFLUENCE OF SWELL, IN DEEP WATER, ON EVEN KEEL, UNRESTRICTED PASSAGE, SEA TEMPERATURE OF MAXIMUM 28 CELSIUS AND BASIS CLEAN & SMOOTH HULL AND PROPELLER.

THE VESSEL MAY BURN ADDITIONAL FUELS IN CASE OF EMERGENCY AND NAVIGATION IN RESTRICTED AREAS LIKE APPROACHES, CHANNELS, SHALLOW WATERS ETC. AND STARTING AND STOPPING OF ENGINE AND FLUSHING THE SYSTEM AND BURNING SLUDGE AND HOLD CLEANING AND BALLASTING AND DE-BALLASTING AND BALLAST WATER EXCHANGE AND DURING MECHANICAL CARGO VENTILATION ETC.

FOR THE PURPOSE OF CALCULATING VESSEL'S PERFORMANCE UNDER THE CHARTER PARTY IT IS AGREED THAT ALL DAYS ON WHICH THE ABOVE CONDITIONS ARE NOT MET, ARE EXPRESSLY EXCLUDED FROM CALCULATIONS. IN CASE OF DISPUTE, THE RELEVANT DATA TO BE OBTAINED FROM THE VESSEL'S LOGS, WHICH SHALL BE BINDING ON BOTH PARTIES.

TELiX MSG: 0BYXM-00 21/05/26 10:30 +03:00

/ VP

good day,

PLS PROPOSE FOR THE BELOW TONNAGE list:

ECSA + W. AFRICA

MV DE SHENG HAI DWT 38,821.5 MT OPEN MUCURIPE, BRAZIL O/A 24-25 MAY 2026

CONTI+MED

M/V AN DING HAI DWT 38,800 MT - OPEN CASABLANCA O/A 28-30 MAY 2026

VSL PARTICULAR:

=====

MV JIAN GUO HAI

2016 BLT HONGKONG FLAG SDBC

IMO NO. 9751286

DWT 38766.6MT ON 10.5M SSW

TPC: 54MT ON SUMMER DRAFT

LOA/BEAM 179.95/32.00M

GT/NT25,622/13,063

5 HO/5 HA

GEAR: 4 X 30 TON CRANES, 4 X10 CMB GRAB

ABOUT 14.5/14KNOTS ON ABOUT 21MT/22 MT LSFO (380) ON

BALLAST/LADEN IN GOOD WEATHER CONDITION, EXCLUDING EXCHANGING
BALLAST AND HOLD CLEANING.

ADDITIONAL 2.6MT SHOULD BE USED BY BOLIER FOR HEATING THE LSFO AT SEA OR AT ANCHORAGE WHEN VESSEL SAILING/STAYING IN THE VERY COLD AREA.

IN PORT: ABT 4.5MT/2.5 MT LSFO IN PORT WHEN WORK/IDLE, EXCLUDING BALLASTING/DEBALLASTING AND EXCHANGING BALLAST.

OWNERS PROVIDE VSL'S ECONOMICAL SPEED/CONS AS BELOW WITHOUT GUARANTEE BSS, AND THE MASTER ALWAYS HAS AN OPTION TO RUN AT FULL SPEED FOR ABOUT 2 HOURS ON DAILY BASIS

ABT 12.5/12.0 KNOTS ON ABOUT 16.5/17.0 MT LSFO (380) ON BALLAST/LADEN IN GOOD WEATHER CONDITION WOG.

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN BALLASTING/DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS), NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE. IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

OPEN HATCH BOX-SHAPE HOLD ON NO. 2,3,4

ccdc45daff57c0687272d367acc782e

ALL DETAILS ABOUT WITHOUT GUARANTEE

++

MV AN DING HAI

2017 BLT HONGKONG FLAG SDBC

IMO NO. 9751303

38800.9 DWT ON 10.5M SSW

TPC:54MT ON SUMMER DRAFT

GRAIN/BALE CAPACITY 50873.7 /49572.6 M3

LOA/BEAM 179.95/32.00M

GT/NT25,622/13,063

5 HO/5 HA

GEAR: 4 X 30 TON CRANES, 4 X10 CBM RADIO REMOTE CONTROL GRAB

ABOUT 14.5/14.0 KNOTS ON ABOUT 20.5MT/21.5 MT LSFO (380) ON BALLAST/LADEN IN

GOOD WEATHER CONDITION, EXCLUDING EXCHANGING BALLAST AND HOLD CLEANING.

ADDITIONAL 2.6MT SHOULD BE USED BY BOLIER FOR HEATING THE LSFO AT SEA OR AT

ANCHORAGE WHEN VESSEL SAILING/STAYING IN THE VERY COLD AREA.

IN PORT: ABT 4.5MT/2.5 MT LSFO IN PORT WHEN WORK/IDLE, EXCLUDING

BALLASTING/DEBALLASTING AND EXCHANGING BALLAST.

OWNERS PROVIDE VSL'S ECONOMICAL SPEED/CONS AS BELOW WITHOUT GUARANTEE BSS, AND THE MASTER ALWAYS

HAS AN OPTION TO RUN AT FULL SPEED FOR ABOUT 2 HOURS ON DAILY BASIS

ECONOMICAL SPEED ABOUT 12.5/12 KNOTS ON ABOUT 16.5/17.0 TONS LSFO (380) ONBALLAST/LADEN IN GOOD WEATHER CONDITION WOG.

THE VESSEL TO HAVE THE LIBERTY OF USING LSMGO FOR EXCHANGING BALLAST WATER AT SEA, STARTING/STANDBY/STOPPING ENGINES, WHILE MANEUVERING IN SHALLOW/NARROW WATERS, CANALS, RIVERS, IN/OUT OF PORTS AND DURING POOR VISIBILITY AND ALSO DURING MAINTENANCE WORKS, NARROW/CONFINED WATERS ETC. THE VESSEL WILL CONSUME ADDITIONAL VLSFO WHEN BALLASTING /DEBALLASTING/BALLAST EXCHANGING/HOLD CLEANING ETC.

ALL ABOVE SPEED/CONSUMPTIONS ARE GIVEN UNDER GOOD WEATHER CONDITION AND CLEAN BOTTOM, SMOOTH SEA, WITH BEAUFORT SCALE MAX WIND FORCE 4 AND DOUGLAS SEA STATE 3 (THREE, I.E. THE SUM OF WAVE + SWELL HEIGHT UP TO 1.25 METERS), NO ADVERSE CURRENT AND NO NEGATIVE INFLUENCE OF SWELL. EXTRAPOLATION OF "GOOD WEATHER" PERFORMANCE FOR "BAD WEATHER" PERIODS IS NOT ALLOWED. POSITIVE CURRENT FACTOR ON SHIP'S FAVOR.

BUNKERS SPEC:

LSFO: IF380CST-RMG380-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.50%

MGO: MGO DMA ISO8217-2017

LSMGO: MGO-DMA-LS ISO8217-2017, SULPHUR CONTENT NOT MORE THAN 0.10%

CHARTERERS UNDER THIS CP WARRANT TO SUPPLY BUNKERS TO MEET MARPOL ANNEX VI LATEST REQUIREMENTS.

BUNKER ISO 8217-2010 TO BE ALLOWED IN CASE ISO 8217-2017 OR LATEST EDITION NOT AVAILABLE. IF ANY DISPUTE ABOUT BUNKER QUALITY, BUNKER SAMPLE TO BE INSPECTED AS PER ISO 8217-2017.

MIXING OF BUNKERS UNDER NO CIRCUMSTANCES ALLOWED.

BIMCO FUEL SULPHUR CONTENT CLAUSE AND BIMCO BUNKER QUALITY CONTROL CLAUSE FOR TIME CHARTER PARTIES AND BIMCO 2020 MARINE FUEL SULPHUR CONTENT CLAUSE FOR TIME CHARTER PARTIES TO APPLY.

OPEN HATCH BOX-SHAPE HOLD ON NO. 2,3,4

ALL DETAILS ABOUT WITHOUT GUARANTEE

VC CARGO

TELIX MSG: 09A76-00 22/05/26 13:32 +03:00

22 MAY 2026

ATTN CHARTERING DESK !

DEAR SIR

GOOD DAY

PLEASE OFFER FIRM FOR FOLL FULY FIRM CARGO

15,000 - 20,000 MTS 10PCT MOLOCHOPT
LOAD PORT : KOH SI CHANG , THAILAND
DISCHARGE PORT: KANDLA + CHENNAI
LOAD RATE: 1,000 MTS PWWD SSHEX
DISCHARGE RATE: 1500 MTS PWWD SSHEX
LAYCAN: MID JULY 2026
COM : 3.75 PCT TTL

-

MCD LIDOMAR
Att. Chartering Desk
/Catalin
Good day

Jeddah / Bilbao

20 000 mt HRC max 28,5 mt

FIOS

4000 mt fhinc / CQD disch

25 June - 5 July try later

3,75% here

--

Best regards/Cristescu
As brokers only ,
Phone: (+) 40-751-991111
EMAIL lidomar@lidomar.ro
re:7647terdhf

Skype cccatalin

Please add our email to your regular distribution list.

In case the content of our messages are not of your interest please
kindly advise in return in order to remove you from the distribution list.

+++++

PLS OFFER FIRM FOR FOLL OUR CLOSE AND DIR CHRTRS

20-30,000 mts iron slag in bulk
LP:Bushehr

DP: Doha
10000/12000
25-30 july
3.75% TTL

+++++

Cargo:30,000 mts of Urea in bulk
POL: Blk
POD: Iskenderun or Durban
5000/5000
LAYCAN: 16-20 July
COMM:1.25% TTL

TC CARGO

TELIX MSG: 0C2V5-00 22/05/26 10:45 +03:00

- / KP

GOOD DAY,

PLEASED TO HEAR.

CHINA / NOPAC
ACC DAI AN OCEAN SHIPPING COMPANY LIMITED
DELIVERY TM VANCOUVER
LC 10-17 JUNE
SMX-UMX, PREF UMX
1 TCT WITH GRAINS
REDELIVERY CHITTAGONG
3.75 ADDCOM PUS

SEASIA
ACC DAI AN OCEAN SHIPPING COMPANY LIMITED
SMX-UMX MAX 20 YRS.
DELY TO MAKE SANGATTA (NEAR TO TJ BARA), E KALI OF INDONESIA.

29-2ND JUN
1 TCT WITH CLINKER TO BDESH.
DURATION ABT 30 DAYS WOG.
3.75PCT ADDOM PUS
TRY PERIOD
PLS ADV THE OUTREACH

WORLDWIDE
ACC DAI AN OCEAN SHIPPING COMPANY LIMITED
SUPRA/ULTRA DELY WW
FULL MAY
1-3 YEARS TRY SHORT PERIOD
FLAT OR INDEX BOTH WORKABLE
3.75 ADDCOM PUS

Please provide suitable, rated vessels for our following firm requirements.

- * A/C SeaSchiffe
- * 1 TCT with Steels/Gens/lawfuls
- * 22k dwt upto HMAX
- * Delivery: ECI
- * Laycan: 15-18 July
- * Redel: Med via GOA transit
- * Duration: abt 35-40 days wog
- * 3.75% Adc

+++++

- * A/C SeaSchiffe
- * 1 TCT with Steels/Gens/lawfuls
- * 33k dwt upto HMAX
- * Delivery: ECI
- * Laycan: 21-23 July
- * Redel: ARAG via COGH transit
- * Duration: abt 50-55 days wog
- * 3.75% Adc

We look forward to hearing from you.

Best regards,

Steve

Sea Schiffe DMCC

Skype: switson87

M: +91-8459221078

+++++