

Chapter 11

Transaction Management

Concurrent and Consistent Data Access

Architecture and Implementation of Database Systems
Summer 2014

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Torsten Grust
Wilhelm-Schickard-Institut für Informatik
Universität Tübingen



The “Hello World” of Transaction Management

- My bank issued me a debit card to access my account.
- Every once in a while, I'd use it at an ATM to draw some money from my account, causing the ATM to perform a **transaction** in the bank's database.

Example (ATM transaction)

```
1 bal ← read_bal (acct_no) ;  
2 bal ← bal - 100 € ;  
3 write_bal (acct_no, bal) ;
```



- My account is **properly updated** to reflect the new balance.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Concurrent Access

The problem is: My wife has a card for the very same account, too.

⇒ We might end up using our cards at different ATMs at the **same time**, *i.e.*, **concurrently**.

Example (Concurrent ATM transactions)

me

```
bal ← read (acct) ;
```

```
bal ← bal − 100 ;
```

```
write (acct, bal) ;
```

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Concurrent Access

The problem is: My wife has a card for the very same account, too.

⇒ We might end up using our cards at different ATMs at the **same time**, *i.e.*, **concurrently**.

Example (Concurrent ATM transactions)

me

$bal \leftarrow \text{read}(acct);$

$bal \leftarrow bal - 100;$

$\text{write}(acct, bal);$

my wife

$bal \leftarrow \text{read}(acct);$

$bal \leftarrow bal - 200;$

$\text{write}(acct, bal);$

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Concurrent Access

The problem is: My wife has a card for the very same account, too.

⇒ We might end up using our cards at different ATMs at the **same time**, i.e., **concurrently**.

Example (Concurrent ATM transactions)

me	my wife	DB state
$bal \leftarrow \text{read}(acct);$		1200
$bal \leftarrow bal - 100;$	$bal \leftarrow \text{read}(acct);$	1200
	$bal \leftarrow bal - 200;$	1200
$\text{write}(acct, bal);$		1100
	$\text{write}(acct, bal);$	1000

- The first **update was lost** during this execution. Lucky me!



If the Plug is Pulled ...

- This time, I want to **transfer** money over to another account.

Example (Money transfer transaction)

```
// Subtract money from source (checking) account
1 chk_bal ← read_bal (chk_acct_no) ;
2 chk_bal ← chk_bal - 500 € ;
3 write_bal (chk_acct_no, chk_bal) ;

// Credit money to the target (savings) account
4 sav_bal ← read_bal (sav_acct_no) ;
5 sav_bal ← sav_bal + 500 € ;
6 ⚡
7 write_bal (sav_acct_no, sav_bal) ;
```

- Before the transaction gets to step 7, its execution is **interrupted/cancelled** (power outage, disk failure, software bug, ...). My money is **lost** 😊.



ACID Properties

To prevent these (and many other) effects from happening, a DBMS guarantees the following **transaction properties**:

- A** **Atomicity** Either **all** or **none** of the updates in a database transaction are applied.
- C** **Consistency** Every transaction brings the database from one **consistent** state to another. (While the transaction executes, the database state may be temporarily inconsistent.)
- I** **Isolation** A transaction must not see any effect from other transactions that run in parallel.
- D** **Durability** The effects of a **successful** transaction remain persistent and may not be undone for system reasons.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling


Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Concurrency Control



Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Anomalies: Lost Update

- We already saw an example of the **lost update** anomaly on slide 3:

The effects of one transaction are lost due to an uncontrolled overwrite performed by the second transaction.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Anomalies: Inconsistent Read

Reconsider the money transfer example (slide 4), expressed in SQL syntax:

Example

Transaction 1

```
1 UPDATE Accounts
2   SET balance = balance - 500
3   WHERE customer = 1904
4   AND account_type = 'C';

5 UPDATE Accounts
6   SET balance = balance + 500
7   WHERE customer = 1904
8   AND account_type = 'S';
```

Transaction 2

```
1 SELECT SUM(balance)
2   FROM Accounts
3  WHERE customer = 1904;
```

- Transaction 2 sees a temporary, **inconsistent** database state.



Anomalies: Dirty Read

At a different day, my wife and me again end up in front of an ATM at roughly the same time. This time, my transaction is cancelled (**aborted**):

Example

me	my wife	DB state
$bal \leftarrow \text{read}(acct);$		1200
$bal \leftarrow bal - 100;$		1200
$\text{write}(acct, bal);$		1100
	$bal \leftarrow \text{read}(acct);$	1100
	$bal \leftarrow bal - 200;$	1100



Anomalies: Dirty Read

At a different day, my wife and me again end up in front of an ATM at roughly the same time. This time, my transaction is cancelled (**aborted**):

Example

me	my wife	DB state
$bal \leftarrow \text{read}(acct);$		1200
$bal \leftarrow bal - 100;$		1200
$\text{write}(acct, bal);$		1100
	$bal \leftarrow \text{read}(acct);$	1100
	$bal \leftarrow bal - 200;$	1100
abort;		1200



Anomalies: Dirty Read

At a different day, my wife and me again end up in front of an ATM at roughly the same time. This time, my transaction is cancelled (**aborted**):

Example

me	my wife	DB state
$bal \leftarrow \text{read}(acct);$		1200
$bal \leftarrow bal - 100;$		1200
$\text{write}(acct, bal);$		1100
	$bal \leftarrow \text{read}(acct);$	1100
	$bal \leftarrow bal - 200;$	1100
		1200
abort;	$\text{write}(acct, bal);$	900


- My wife's transaction has already read the modified account balance before my transaction was **rolled back** (i.e., its effects are undone).



Concurrent Execution

- The **scheduler** decides the execution order of concurrent database accesses.

The transaction scheduler



Database Objects and Accesses

- We now assume a slightly simplified model of database access:
 - ① A database consists of a number of named **objects**. In a given database state, each object has a **value**.
 - ② Transactions access an object o using the two operations $\text{read } o$ and $\text{write } o$.
- In a **relational** DBMS we have that

$\text{object} \equiv \text{attribute} \quad .$

This defines the **granularity** of our discussion. Other possible granularities:

$\text{object} \equiv \text{row}, \text{object} \equiv \text{table} \quad .$

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Transactions

Database transaction

A **database transaction** T is a (strictly ordered) sequence of **steps**. Each **step** is a pair of an **access operation** applied to an **object**.

- Transaction $T = \langle s_1, \dots, s_n \rangle$
- Step $s_i = (a_i, e_i)$
- Access operation $a_i \in \{r(\text{ead}), w(\text{rite})\}$

The **length** of a transaction T is its number of steps $|T| = n$.

We could write the money transfer transaction as

$$T = \langle (r(\text{ead}), \textit{Checking}), (w(\text{rite}), \textit{Checking}), \\ (r(\text{ead}), \textit{Saving}), (w(\text{rite}), \textit{Saving}) \rangle$$

or, more concisely,

$$T = \langle r(C), w(C), r(S), w(S) \rangle .$$



Schedules

Schedule

A **schedule** S for a given set of transactions $\mathbf{T} = \{T_1, \dots, T_n\}$ is an arbitrary sequence of execution steps

$$S(k) = (T_j, a_i, e_i) \quad k = 1 \dots m,$$



such that

- 1 S contains all steps of all transactions and nothing else and
- 2 the order among steps in each transaction T_j is preserved:

$$(a_p, e_p) < (a_q, e_q) \text{ in } T_j \Rightarrow (T_j, a_p, e_p) < (T_j, a_q, e_q) \text{ in } S$$

(read "<" as: *occurs before*).

We sometimes write

$$S = \langle r_1(B), r_2(B), w_1(B), w_2(B) \rangle$$

to abbreviate

$$S(1) = (T_1, \text{read}, B) \quad S(3) = (T_1, \text{write}, B)$$

$$S(2) = (T_2, \text{read}, B) \quad S(4) = (T_2, \text{write}, B)$$



Serial Execution



Serial execution

One particular schedule is **serial execution**.


- A schedule S is **serial** iff, for each contained transaction T_j , all its steps are adjacent (no interleaving of transactions and thus **no concurrency**).

Briefly:

$$S = T_{\pi 1}, T_{\pi 2}, \dots, T_{\pi n} \quad (\text{for some permutation } \pi \text{ of } 1, \dots, n)$$


Consider again the ATM example from slide 3.

- $S = \langle r_1(B), r_2(B), w_1(B), w_2(B) \rangle$
- This is a schedule, but it is **not** serial.



If my wife had gone to the bank one hour later (initiating transaction T_2), the schedule probably would have been serial.

- $S = \langle r_1(B), w_1(B), r_2(B), w_2(B) \rangle$



Correctness of Serial Execution

- Anomalies such as the “lost update” problem on slide 3 can **only** occur in multi-user mode.
 - If all transactions were fully executed one after another (no concurrency), no anomalies would occur.
- ⇒ **Any serial execution is correct.**
- Disallowing concurrent access, however, is **not practical**.

Correctness criterion

Allow concurrent executions if their **overall effect is equivalent to an (arbitrary) serial execution**.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Conflicts

What does it mean for a schedule S to be **equivalent** to another schedule S' ?

- Sometimes, we may be able to **reorder** steps in a schedule.
 - We must not change the order among steps of any transaction T_j (↗ slide 13).
 - Rearranging operations must not lead to a different **result**.
- Two operations (T_i, a, e) and (T_j, a', e') are said to be **in conflict** $(T_i, a, e) \leftrightarrow (T_j, a', e')$ if their order of execution matters.
 - When reordering a schedule, we must not change the relative order of such operations.
- Any schedule S' that can be obtained this way from S is said to be **conflict equivalent** to S .



Conflicts

Based on our read/write model, we can come up with a more machine-friendly definition of a conflict.

Conflicting operations

Two operations (T_i, a, e) and (T_j, a', e') are **in conflict** (\leftrightarrow) in S if

- 1 they belong to two **different transactions** ($T_i \neq T_j$), and
- 2 they access the **same database object**, i.e., $e = e'$, and
- 3 at least one of them is a write operation.

- This inspires the following **conflict matrix**:

	read	write
read		×
write	×	×

- **Conflict relation** \prec_S :

$$(T_i, a, e) \prec_S (T_j, a', e') \\ :=$$

$$(T_i, a, e) \leftrightarrow (T_j, a', e') \wedge (T_i, a, e) \text{ occurs before } (T_j, a', e') \text{ in } S$$



Conflict Serializability

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Conflict serializability

A schedule S is **conflict serializable** iff it is **conflict equivalent to some serial schedule S'** .

- The execution of a conflict-serializable S schedule is **correct**.
- Note: S does **not** have to be a serial schedule.



Serializability: Example

Example (Three schedules S_i for two transactions $T_{1,2}$, with S_2 serial)

Schedule S_1

T_1	T_2
read A	
write A	
	read A
	write A
read B	
write B	
	read B
	write B

Schedule S_2

T_1	T_2
read A	
write A	
read B	
write B	
	read A
	write A
	read B
	write B

Schedule S_3

T_1	T_2
read A	
write A	
	read A
	write A
	read B
	write B
read B	
write B	

- Conflict relations:

$$\left. \begin{array}{l}
 (T_1, r, A) \prec_{S_1} (T_2, w, A), (T_1, r, B) \prec_{S_1} (T_2, w, B), \\
 (T_1, w, A) \prec_{S_1} (T_2, r, A), (T_1, w, B) \prec_{S_1} (T_2, r, B), \\
 (T_1, w, A) \prec_{S_1} (T_2, w, A), (T_1, w, B) \prec_{S_1} (T_2, w, B) \\
 \\
 (\text{Note: } \prec_{S_2} = \prec_{S_1}) \\
 \\
 (T_1, r, A) \prec_{S_3} (T_2, w, A), (T_2, r, B) \prec_{S_3} (T_1, w, B), \\
 (T_1, w, A) \prec_{S_3} (T_2, r, A), (T_2, w, B) \prec_{S_3} (T_1, r, B), \\
 (T_1, w, A) \prec_{S_3} (T_2, w, A), (T_2, w, B) \prec_{S_3} (T_1, w, B)
 \end{array} \right\} \Rightarrow S_1 \text{ serializable}$$



The Conflict Graph

- The serializability idea comes with an effective test for the correctness of a schedule S based on its **conflict graph** $G(S)$ (also: **serialization graph**):
 - The **nodes** of $G(S)$ are all transactions T_i in S .
 - There is an **edge** $T_i \rightarrow T_j$ iff S contains operations (T_i, a, e) and (T_j, a', e') such that $(T_i, a, e) \prec_S (T_j, a', e')$ (read: *in a conflict equivalent serial schedule, T_i must occur before T_j*).
- S is conflict serializable iff $G(S)$ is **acyclic**.
An equivalent serial schedule for S may be immediately obtained by sorting $G(S)$ **topologically**.



Serialization Graph

Example (ATM transactions (↗ slide 3))

- $S = \langle r_1(A), r_2(A), w_1(A), w_2(A) \rangle$
- Conflict relation:
 - $(T_1, r, A) \prec_S (T_2, w, A)$
 - $(T_2, r, A) \prec_S (T_1, w, A)$
 - $(T_1, w, A) \prec_S (T_2, w, A)$



Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking


Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Serialization Graph

Example (ATM transactions (↗ slide 3))

- $S = \langle r_1(A), r_2(A), w_1(A), w_2(A) \rangle$
- Conflict relation:
 $(T_1, r, A) \prec_S (T_2, w, A)$
 $(T_2, r, A) \prec_S (T_1, w, A)$
 $(T_1, w, A) \prec_S (T_2, w, A)$



⇒ **not** serializable

Example (Two money transfers (↗ slide 4))


- $S = \langle r_1(C), w_1(C), r_2(C), w_2(C), r_1(S), w_1(S), r_2(S), w_2(S) \rangle$
- Conflict relation:
 $(T_1, r, C) \prec_S (T_2, w, C)$
 $(T_1, w, C) \prec_S (T_2, r, C)$
 $(T_1, w, C) \prec_S (T_2, w, C)$
⋮



Serialization Graph

Example (ATM transactions (↗ slide 3))

- $S = \langle r_1(A), r_2(A), w_1(A), w_2(A) \rangle$
- Conflict relation:
 - $(T_1, r, A) \prec_S (T_2, w, A)$
 - $(T_2, r, A) \prec_S (T_1, w, A)$
 - $(T_1, w, A) \prec_S (T_2, w, A)$



⇒ **not** serializable

Example (Two money transfers (↗ slide 4))

- $S = \langle r_1(C), w_1(C), r_2(C), w_2(C), r_1(S), w_1(S), r_2(S), w_2(S) \rangle$
- Conflict relation:
 - $(T_1, r, C) \prec_S (T_2, w, C)$
 - $(T_1, w, C) \prec_S (T_2, r, C)$
 - $(T_1, w, C) \prec_S (T_2, w, C)$
 - \vdots



⇒ serializable



Query Scheduling

Can we build a scheduler that **always** emits a serializable schedule?


Idea:

- Require each transaction to obtain a **lock** before it accesses a data object o :

Locking and unlocking of o

```
1 lock o ;  
2 ...access o ...;  
3 unlock o ;
```

- This prevents **concurrent** access to o .



Locking

- If a lock cannot be granted (e.g., because another transaction T' already holds a **conflicting** lock) the requesting transaction T gets **blocked**.
 - The scheduler **suspends** execution of the blocked transaction T .
 - Once T' **releases** its lock, it may be granted to T , whose execution is then **resumed**.
- ⇒ Since other transactions can continue execution while T is blocked, locks can be used to **control the relative order of operations**.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Locking and Scheduling

Example (Locking and scheduling)

- Consider two transactions $T_{1,2}$:
- Two valid schedules (respecting lock and unlock calls) are:

T_1
lock A
write A
lock B
unlock A
write B
unlock B

T_2
lock A
write A
lock B
write B
write A
unlock A
write B
unlock B

Schedule S_1

T_1	T_2
lock A	
write A	
lock B	
unlock A	
	lock A
	write A
write B	
unlock B	
	lock B
	write B
	write A
	unlock A
	write B
	unlock B

Schedule S_2

T_1	T_2
	lock A
	write A
	lock B
	write B
	write A
	unlock A
lock A	
write A	
	write B
	unlock B
lock B	
write B	
unlock B	
unlock A	

- Note: Both schedules $S_{1,2}$ are serializable. **Are we done yet?**



Locking and Serializability

Example (Proper locking does *not* guarantee serializability yet)

Even if we adhere to a properly nested lock/unlock discipline, the scheduler might still yield **non-serializable schedules**:

Schedule S_1

T_1	T_2
lock A	
lock C	
write A	
write C	
unlock A	
	lock A
	write A
	lock B
	unlock A
	write B
	unlock B
unlock C	
lock B	
write B	
unlock B	
	lock C
	write C
	unlock C

 What is the conflict graph of this schedule?



ATM Transaction with Locking

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Example (Two concurrent ATM transactions with locking)

Transaction 1	Transaction 2	DB state
read (acct);		1200
	read (acct);	
write (acct);		1100
	write (acct);	1000

ATM Transaction with Locking

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Example (Two concurrent ATM transactions with locking)

Transaction 1

```
lock(acct);  
read(acct);  
unlock(acct);
```

```
lock(acct);  
write(acct);  
unlock(acct);
```

Transaction 2

```
lock(acct);  
read(acct);  
unlock(acct);
```

```
lock(acct);  
write(acct);  
unlock(acct);
```

DB state

1200

1100

1000


⇒ Again: on its own, proper locking does **not** guarantee serializability yet.

Two-Phase Locking (2PL)

The **two-phase locking protocol** poses an additional restriction on how transactions have to be written:

Definition (Two-Phase Locking)

- Once a transaction has **released** any lock (i.e., performed the first `unlock`), it must **not** acquire any new lock:



- Two-phase locking is **the** concurrency control protocol used in database systems today.



Again: ATM Transaction



Example (Two concurrent ATM transactions with locking, \rightarrow 2PL)

Transaction 1

```
lock (acct) ;  
read (acct) ;  
unlock (acct) ;
```

```
lock (acct) ;  
write (acct) ;  
unlock (acct) ;
```

Transaction 2

```
lock (acct) ;  
read (acct) ;  
unlock (acct) ;
```

```
lock (acct) ;  
write (acct) ;  
unlock (acct) ;
```

DB state

1200

1100

1000

Again: ATM Transaction



Example (Two concurrent ATM transactions with locking, \neg 2PL)

Transaction 1

```
lock (acct) ;  
read (acct) ;  
unlock (acct) ;
```

```
lock (acct) ; ⚡  
write (acct) ;  
unlock (acct) ;
```

Transaction 2

```
lock (acct) ;  
read (acct) ;  
unlock (acct) ;
```

```
lock (acct) ; ⚡  
write (acct) ;  
unlock (acct) ;
```

DB state

1200

1100

1000

⚡ These locks violate the 2PL principle.

A 2PL-Compliant ATM Transaction

- To comply with the two-phase locking protocol, the ATM transaction must not acquire any new locks after a first lock has been released:

A 2PL-compliant ATM withdrawal transaction

```
1 lock (acct) ;           } lock phase
2 bal ← read_bal (acct) ;
3 bal ← bal - 100 € ;
4 write_bal (acct, bal) ;
5 unlock (acct) ;         } unlock phase
```



Resulting Schedule

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Example

Transaction 1	Transaction 2	DB state
<code>lock(acct);</code> <code>read(acct);</code>	<code>lock(acct);</code>	1200
<code>write(acct);</code> <code>unlock(acct);</code>	Transaction blocked	1100
	<code>lock(acct);</code> <code>read(acct);</code> <code>write(acct);</code> <code>unlock(acct);</code>	900

Resulting Schedule



Example

Transaction 1	Transaction 2	DB state
lock (acct) ; read (acct) ;	lock (acct) ;	1200
write (acct) ; unlock (acct) ;	<div>Transaction blocked</div> <div>↓</div> lock (acct) ; read (acct) ; write (acct) ; unlock (acct) ;	1100 900

- **Theorem:** The use of 2PL-compliant locking **always** leads to a correct and **serializable** schedule or to a **deadlock**.

Lock Modes

- We saw earlier that two **read** operations do not conflict with each other.
- Systems typically use different types of locks (**lock modes**) to allow read operations to run concurrently.
 - **read locks** or **shared locks**: mode S
 - **write locks** or **exclusive locks**: mode X
- Locks are only in conflict if at least one of them is an X lock:

Shared vs. exclusive lock compatibility

	shared (S)	exclusive (X)
shared (S)		×
exclusive (X)	×	×

- It is a safe operation in two-phase locking to (try to) **convert a shared lock into an exclusive lock during the lock phase** (lock upgrade) \Rightarrow improved concurrency.



Deadlocks

- Like many lock-based protocols, two-phase locking has the risk of **deadlock** situations:

Example (Proper schedule with locking)

Transaction 1

lock (A) ;

⋮

do something

⋮

lock (B) ;

[wait for T_2 to release lock]

Transaction 2

lock (B) ;

⋮

do something

⋮

lock (A) ;

[wait for T_1 to release lock]

- Both transactions would wait for each other **indefinitely**.



Deadlock Handling

- **Deadlock detection:**

- ① The system maintains a **waits-for graph**, where an edge $T_1 \rightarrow T_2$ indicates that T_1 is blocked by a lock held by T_2 .
- ② Periodically, the system tests for **cycles** in the graph.
- ③ If a cycle is detected, the deadlock is **resolved** by **aborting** one or more transactions.
- ④ Selecting the **victim** is a challenge:
 - Aborting **young** transactions may lead to **starvation**: the same transaction may be cancelled again and again.
 - Aborting an **old** transaction may cause a lot of computational investment to be thrown away (but the **undo** costs may be high).



Deadlock Handling

- **Deadlock detection:**

- ① The system maintains a **waits-for graph**, where an edge $T_1 \rightarrow T_2$ indicates that T_1 is blocked by a lock held by T_2 .
- ② Periodically, the system tests for **cycles** in the graph.
- ③ If a cycle is detected, the deadlock is **resolved** by **aborting** one or more transactions.
- ④ Selecting the **victim** is a challenge:
 - Aborting **young** transactions may lead to **starvation**: the same transaction may be cancelled again and again.
 - Aborting an **old** transaction may cause a lot of computational investment to be thrown away (but the **undo** costs may be high).

- **Deadlock prevention:**

Define an **ordering** \ll **on all database objects**. If $A \ll B$, then order the **lock** operations in all transactions in the same way (**lock**(A) before **lock**(B)).



Deadlock Handling

Other common technique:

- **Deadlock detection via timeout:**

Let a transaction T block on a lock request only until a **timeout** occurs (counter expires). On expiration, *assume* that a deadlock has occurred and **abort** T .

DB2. Timeout-based deadlock detection

```
db2 => GET DATABASE CONFIGURATION;
      :
      :
Interval for checking deadlock (ms)      (DLCHKTIME) = 10000
Lock timeout (sec)                      (LOCKTIMEOUT) = 30
      :
      :
```

- Also: lock-less **optimistic concurrency control** (↗ slide 42).

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking


Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control


Variants of Two-Phase Locking

- The two-phase locking discipline does not prescribe exactly when locks have to be acquired and released.
- Two possible variants:

Preclaiming and strict 2PL



Preclaiming 2PL



Strict 2PL

What could motivate either variant?


- 1 Preclaiming 2PL:
- 2 Strict 2PL:



Cascading Rollbacks

Consider three transactions:

Transactions $T_{1,2,3}$, T_1 fails later on




- When transaction T_1 aborts, transactions T_2 and T_3 have already read data written by T_1 (↗ dirty read, slide 9)
 - T_2 and T_3 need to be **rolled back**, too (**cascading roll back**).
 - T_2 and T_3 **cannot** commit until the fate of T_1 is known.
- ⇒ Strict 2PL can avoid cascading roll backs altogether. (**How?**)



Granularity of Locking

The **granularity** of locking is a trade-off:



⇒ **Idea: multi-granularity** locking.

¹ An DB2 tablespace represents a collection of tables that share a physical storage location.



Multi-Granularity Locking

- Decide the granularity of locks held **for each transaction** (depending on the characteristics of the transaction):
 - For example, acquire a **row lock** for

Row-selecting query (C_CUSTKEY is key)

```
1  SELECT *
2  FROM   CUSTOMERS
3  WHERE  C_CUSTKEY = 42
```

Q₁

and a **table lock** for

Table scan query

```
1  SELECT *
2  FROM   CUSTOMERS
```

Q₂

- How do such transactions know about each others' locks?
 - Note that locking is **performance-critical**. Q₂ does not want to do an extensive search for row-level conflicts.



Intention Locks

Databases use an additional type of locks: **intention locks**.

- Lock mode **intention share**: IS
- Lock mode **intention exclusive**: IX

Extended conflict matrix

	S	X	IS	IX
S		×		×
X	×	×	×	×
IS		×		
IX	×	×		

- A lock I□ on a coarser level of granularity means that there is some □ lock on a lower level.



Intention Locks

Multi-granularity locking protocol

- 1 Before a granule g can be locked in $\square \in \{S, X\}$ mode, the transaction has to obtain an $I\square$ lock on **all** coarser granularities that contain g .
- 2 If all intention locks could be granted, the transaction can lock granule g in the announced \square mode.

Example (Multi-granularity locking)

Query Q_1 (\nearrow slide 38) would, e.g.,

- obtain an IS lock on **table** CUSTOMERS (also on the containing tablespace and database) and
- obtain an S lock on the **row(s)** with $C_CUSTKEY = 42$.

Query Q_2 would place an

- S lock on table CUSTOMERS (and an IS lock on tablespace and database).

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Detecting Conflicts

- Now suppose an updating query comes in:

Update request

```
1 UPDATE CUSTOMERS
2 SET NAME = 'Seven_Teen'
3 WHERE C_CUSTKEY = 17
```

Q₃

- Q₃ will want to place
 - an IX lock on **table** CUSTOMER (and all coarser granules) and
 - an X lock on the **row** holding customer 17.

As such it is

- compatible** with Q₁
(there is no conflict between IX and IS on the table level),
- but **incompatible** with Q₂
(the table-level S lock held by Q₂ is in **conflict** with Q₃'s IX lock request).

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Optimistic Concurrency Control

- Up to here, the approach to concurrency control has been **pessimistic**:
 - Assume that transactions **will conflict** and thus protect database objects by locks and lock protocols.
- The converse is a **optimistic concurrency control** approach:
 - Hope for the best and let transactions freely proceed with their read/write operations.
 - Only just before updates are to be committed to the database, perform a check to see whether conflicts indeed did not happen.
- Rationale: Non-serializable conflicts are not that frequent. **Save the locking overhead** in the majority of cases and only invest effort if really required.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Optimistic Concurrency Control

Under **optimistic concurrency control**, transactions proceed in **three phases**:

Optimistic concurrency control

- 1 **Read Phase.** Execute transaction, but do **not** write data back to disk immediately. Instead, collect updates in the transaction's **private workspace**.
 - 2 **Validation Phase.** When the transaction wants to **commit**, test whether its execution was correct (only acceptable conflicts happened). If it is not, **abort** the transaction.
 - 3 **Write Phase.** Transfer data from private workspace into database.
- Note: Phases 2 and 3 need to be performed in a non-interruptible *critical section* (thus also called the **val-write phase**).

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Validating Transactions

Validation is typically implemented by looking at transaction T_j 's

- **Read Set** $RS(T_j)$ (attributes read by T_j) and
- **Write Set** $WS(T_j)$ (attributes written by T_j).

Backward-oriented optimistic concurrency control (BOCC)

Compare T_j against all **committed** transactions T_i .

Check **succeeds** if

$$T_i \text{ committed before } T_j \text{ started} \quad \text{or} \quad RS(T_j) \cap WS(T_i) = \emptyset .$$

Forward-oriented optimistic concurrency control (FOCC)

Compare T_j against all **running** transactions T_i .

Check **succeeds** if

$$WS(T_j) \cap RS(T_i) = \emptyset .$$



Optimistic Concurrency Control in IBM DB2

- DB2 V9.5 provides SQL-level constructs that enable database applications to implement optimistic concurrency control:
 - $RID(r)$: return row identifier for row r ,
 - ROW CHANGE TOKEN FOR r : unique number reflecting the time row r has last been updated.



DB2. Optimistic concurrency control

```
1 db2 => SELECT * FROM EMPLOYEES
```

```
2  
3  
4  
5  
6  
7  
8  
9  
10
```

ID	NAME	DEPT	SALARY
1	Alex	DE	300
2	Bert	DE	100
3	Cora	DE	200
4	Drew	US	200
5	Erik	US	400

```
11 db2 => SELECT E.NAME, E.SALARY,  
12         RID(E) AS RID, ROW CHANGE TOKEN FOR E AS TOKEN  
13         FROM EMPLOYEES E  
14         WHERE E.NAME = 'Erik'
```

NAME	SALARY	RID	TOKEN
Erik	400	16777224	74904229642240

Optimistic Concurrency Control in IBM DB2

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

DB2® Optimistic concurrency control

- The 'Erik' row belongs to our read set. Save its RID and TOKEN values to perform validation later.
- (...Time passes ...) Now try to save our changes to the row. Perform BOCC-style validation:

```
1 db2 => UPDATE EMPLOYEES E
2         SET E.SALARY = 450
3         WHERE RID(E) = 16777224 -- identify row
4         AND ROW CHANGE TOKEN FOR E = 74904229642240 -- row changed?
```

```
6 SQL0100W No row was found for FETCH, UPDATE or DELETE; or the
7 result of a query is an empty table.  SQLSTATE=02000
```

```
8
9 db2 => SELECT E.ID, E.NAME
10        RID(E) AS RID, ROW CHANGE TOKEN FOR E AS TOKEN
11        FROM EMPLOYEES E
```

ID	NAME	RID	TOKEN
1	Alex	16777220	74904229642240
2	Bert	16777221	74904229642240
3	Cora	16777222	74904229642240
4	Drew	16777223	74904229642240
5	Erik	16777224	141378732653941710

Multi-Version Concurrency Control

Looking back at the concurrency control strategies discussed up to this point, we have seen

- 1 **Wait Mechanisms**, i.e., **locks** and the associated two-phase locking protocol,
- 2 **Rollback Mechanisms**, i.e., a conditional write phase that makes it trivial to **take back any changes** made by a transaction.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Multi-Version Concurrency Control

Looking back at the concurrency control strategies discussed up to this point, we have seen

- 1 **Wait Mechanisms**, i.e., **locks** and the associated two-phase locking protocol,
- 2 **Rollback Mechanisms**, i.e., a conditional write phase that makes it trivial to **take back any changes** made by a transaction.

We now add

- 3 **Timestamp Mechanisms** that use a **DBMS-wide clock** to order transactions and decide visibility of rows.

The resulting **Multi-Version Concurrency Control (MVCC)** protocol is lock-less but comes with a space overhead (that requires **garbage collection** of rows).

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

MVCC: Timestamps

- In MVCC, each transaction T_i is assigned a **timestamp** t_i that represents the point in time when T_i started.
- Can implement timestamps based on
 - **actual system clock** (resolution, uniqueness, portability across OSs?),
or
 - **a DBMS-internal counter** used to assign transaction IDs (xid).
- Timestamp requirements:
 - ① unique: $t_i \neq t_j$ if $i \neq j$,
 - ② ordered: $t_i < t_j$ if T_i has started before T_j .

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

MVCC: Timestamps

- In MVCC, each transaction T_i is assigned a **timestamp** t_i that represents the point in time when T_i started.
- Can implement timestamps based on
 - **actual system clock** (resolution, uniqueness, portability across OSs?),
or
 - **a DBMS-internal counter** used to assign transaction IDs (xid).
- Timestamp requirements:
 - ① unique: $t_i \neq t_j$ if $i \neq j$,
 - ② ordered: $t_i < t_j$ if T_i has started before T_j .

MVCC: Semantics

Under MVCC, a transaction T_i operates on **the consistent state of the database that was current at time t_i** .



MVCC: Versions and Snapshots

In a concurrent DBMS, operations can **conflict** if they write the **same database object** (recall relation \leftrightarrow). Thus:

MVCC: Versions

Under MVCC, **multiple versions of the same database object** may exist at one time. Different transactions may read/write different (not necessarily the most recent) object versions.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

MVCC: Versions and Snapshots

In a concurrent DBMS, operations can **conflict** if they write the **same database object** (recall relation \leftrightarrow). Thus:

MVCC: Versions

Under MVCC, **multiple versions of the same database object** may exist at one time. Different transactions may read/write different (not necessarily the most recent) object versions.

MVCC uses **snapshots** to identify exactly which version of each database object are visible to a transaction:

MVCC: Snapshot

To take a **snapshot**, gather the following information:

- the highest `xid` of all committed transactions,
- a list of `xids` of all transactions currently executing.

Typically, a snapshot is taken at the time the transaction starts.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Control

Multi-Version
Concurrency Control

MVCC: Row Timestamps



Database Object \equiv Row

PostgreSQL implements MVCC at a granularity of rows: **multiple versions of the same row** may exist. Adopt this model in what follows.

- To help decide whether a particular row version is included in (or excluded from) a snapshot, attach to each row version two virtual/hidden attributes:
 - ① xmin: the xid of the transaction that **created** this row,
 - ② xmax: the xid of the transaction that **deleted** this row.
- Row **updates** are modelled as the two-step operation row deletion, then creation.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

MVCC: Row Timestamps



Database Object \equiv Row

PostgreSQL implements MVCC at a granularity of rows: **multiple versions of the same row** may exist. Adopt this model in what follows.

- To help decide whether a particular row version is included in (or excluded from) a snapshot, attach to each row version two virtual/hidden attributes:
 - ① `xmin`: the `xid` of the transaction that **created** this row,
 - ② `xmax`: the `xid` of the transaction that **deleted** this row.
- Row **updates** are modelled as the two-step operation row deletion, then creation.

MVCC: No Physical Deletion!

Note: ② implies that rows are **not actually physically deleted**. Instead, their `xmax` attribute is modified to record the deleting/updating transaction (\Rightarrow eventual row garbage).



Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

MVCC: Row Visibility (1)

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control

Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (1)



Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...
	30	—	...

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (1)



Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...	✓
	30	—	...	

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (1)



Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$

- Row visible in snapshot?

1	xmin	xmax	... data ...	✓
	30	—	...	
2	xmin	xmax	... data ...	
	50	—	...	

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (1)



Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$

- Row visible in snapshot?

①	xmin	xmax	... data ...	✓
	30	—	...	
②	xmin	xmax	... data ...	⚡
	50	—	...	

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (1)



Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$

- Row visible in snapshot?

1	<table><tr><th>xmin</th><th>xmax</th><th>... data ...</th></tr><tr><td>30</td><td>—</td><td>...</td></tr></table>	xmin	xmax	... data ...	30	—	...	✓
xmin	xmax	... data ...						
30	—	...						
2	<table><tr><th>xmin</th><th>xmax</th><th>... data ...</th></tr><tr><td>50</td><td>—</td><td>...</td></tr></table>	xmin	xmax	... data ...	50	—	...	⚡
xmin	xmax	... data ...						
50	—	...						
3	<table><tr><th>xmin</th><th>xmax</th><th>... data ...</th></tr><tr><td>110</td><td>—</td><td>...</td></tr></table>	xmin	xmax	... data ...	110	—	...	
xmin	xmax	... data ...						
110	—	...						

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (1)



Example (Decide Row Visibility)

- Current snapshot:² $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$

- Row visible in snapshot?

1	<table><tr><th>xmin</th><th>xmax</th><th>... data ...</th></tr><tr><td>30</td><td>—</td><td>...</td></tr></table>	xmin	xmax	... data ...	30	—	...	✓
xmin	xmax	... data ...						
30	—	...						
2	<table><tr><th>xmin</th><th>xmax</th><th>... data ...</th></tr><tr><td>50</td><td>—</td><td>...</td></tr></table>	xmin	xmax	... data ...	50	—	...	⚡
xmin	xmax	... data ...						
50	—	...						
3	<table><tr><th>xmin</th><th>xmax</th><th>... data ...</th></tr><tr><td>110</td><td>—</td><td>...</td></tr></table>	xmin	xmax	... data ...	110	—	...	⚡
xmin	xmax	... data ...						
110	—	...						

²For simplicity: assume that all other xids have committed (and not rolled back their work).

MVCC: Row Visibility (2)

Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...
	30	80	...



MVCC: Row Visibility (2)

Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...	⚡
	30	80	...	



MVCC: Row Visibility (2)



Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...	⚡
	30	80	...	

②	xmin	xmax	... data ...
	30	75	...

MVCC: Row Visibility (2)



Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...	⚡
	30	80	...	
②	xmin	xmax	... data ...	✓
	30	75	...	

MVCC: Row Visibility (2)



Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}, \underbrace{[25, 50, 75]} \rangle$
highest committed xid currently active xids
- Row visible in snapshot?

①	xmin	xmax	... data ...	⚡
	30	80	...	

②	xmin	xmax	... data ...	✓
	30	75	...	

③	xmin	xmax	... data ...	
	30	110	...	

MVCC: Row Visibility (2)



Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...	⚡
	30	80	...	
②	xmin	xmax	... data ...	✓
	30	75	...	
③	xmin	xmax	... data ...	✓
	30	110	...	

MVCC: Row Visibility (2)



Example (Decide Row Visibility)

- Current snapshot: $\langle \underbrace{100}_{\text{highest committed xid}}, \underbrace{[25, 50, 75]}_{\text{currently active xids}} \rangle$
- Row visible in snapshot?

①	xmin	xmax	... data ...	⚡
	30	80	...	
②	xmin	xmax	... data ...	✓
	30	75	...	
③	xmin	xmax	... data ...	✓
	30	110	...	

- Given the current state of the system, may row ① be considered garbage that can be collected?

MVCC: Garbage Collection

- The creation of new row versions during UPDATE (rather than replacing the existing row) requires the **reclamation of storage space** used by old row versions.
- Delay such **row garbage collection** until the old versions are guaranteed to be invisible to all current and future transactions.

Delayed Row Garbage Collection

Exactly when is it safe to declare a row as garbage and mark it for collection?



Row Cleanup

- **On-demand cleanup of a single page** when page is accessed during SELECT, UPDATE, DELETE.
- **Bulk cleanup** by scheduled auto-vacuum process or via an explicit VACUUM command.

Transaction
Management

Torsten Grust



ACID Properties

Anomalies

The Scheduler

Serializability

Query Scheduling

Locking

Two-Phase Locking

Optimistic
Concurrency Protocol

Multi-Version
Concurrency Control