M3 Browser

m3-browser.csv · 2026-10-09T17:57:45.332584+00:00

1. Executive review summary

Pre-model evidence for the declared tabular task; no composite reliability score or model-quality verdict is defined.

6	1	2
parsed rows	input features	declared targets

6 parsed rows; 1 selected input feature; 2 targets. Annotation coverage separates observation, expectation, metadata resolution, and declared uncertain validity.

2. Prioritized actions

No supported review findings in the computed scope. Coverage limitations and unavailable evidence still require review.

Composite scoring: not defined. Priorities are internal review rules, not validated performance or readiness ratings.

3. Dataset, roles, parsing, declarations

Purpose undeclared.

Roles: 1 features, 2 targets, 0 metadata, 0 ignored. Resolved roles and full declarations are retained in JSON.

Parsing: utf-8; pandas_default. Source-token review covers 18 comparable prefix cells. NA-like tokens may become missing; numeric-looking codes may lose leading zeros. No source values were rewritten.

4. Annotation or input coverage

Observed vectors: 4 complete, 2 partial, 0 empty. 6 rows have any annotation. Expected-vector completion: 0 / 0 rows with resolved requirements. Expected coverage is unavailable: no resolved expected annotations.

> Unknown expectation is separate from uncertain label validity. Supplied values remain in descriptive evidence. Optional absence does not establish intentional absence. Expected coverage must be read alongside unknown-expectation populations.

Per-target annotation coverage

Target	Observed / rows	Supplied / expected	Unknown expectation	Invalid / conflicts	Uncertain observed
y	5 / 6 (83.3%)	0 / 0 (Unavailable)	6 / 6	0 / 0	0
z	5 / 6 (83.3%)	0 / 0 (Unavailable)	6 / 6	0 / 0	0

Annotation state counts

Target	Absent	Expected gaps	Intentional absence	Unresolved metadata
y	1	0	0	0
z	1	0	0	0

5. Task-specific evidence

Finite vectors: 4 complete, 2 partial, 0 empty. Declared-constraint violation row union: 0. Per-output units and observed populations remain separate. Relationships in observed data say nothing about unavailable outputs.

Finite outputs (units remain separate)

Output	Finite / rows	Distinct	Median	IQR	Constraint violations
y	5 / 6	2	1	1	0
z	5 / 6	2	1	1	0

Declared output expectations

Output	Meaning	Units	Minimum / maximum	Integer / nonnegative
y	unspecified	Undeclared	Unavailable / Unavailable	None / None
z	unspecified	Undeclared	Unavailable / Unavailable	None / None

Verified input-target witnesses

No computed records to display in this scope. This is not a universal clean verdict.

Output dependencies (separate from inputs)

Outputs	Finite overlap / rows	Pearson	Identities	Unavailable reason
y / z	4 / 6	Unavailable	None verified	insufficient_paired_support

6. Features, repetition, annotation populations

All-column parsed duplicates: 0 extra rows. Selected-feature identity and observed annotation variation have separate scopes. Repetition may be legitimate or intentional weighting.

Selected-input repetition: 0 groups; 0 rows participate in observed annotation disagreement; 0 groups have mixed expectation/status metadata. These scopes remain separate.

Selected feature structure

Feature	Meaning	Storage	Observed distinct	Missing / rows
x	quantitative	int64	6	0 / 6

Annotation population contrasts

Cohort	Feature	Cohort sizes	Missing counts	Supported shape evidence
y:observed_vs_unresolved	x	5 / 1	0 / 0	fewer_than_20_finite_per_cohort
z:observed_vs_unresolved	x	5 / 1	0 / 0	fewer_than_20_finite_per_cohort

7 feature/cohort records computed; 5 have an empty comparison population. Empty populations support no shape contrast; their counts and reasons remain in JSON.

Population contrasts are descriptive within this file. They do not establish a missingness mechanism, representativeness, or deployment shift.

7. Applicability, bounds, scoring, limitations

Observed annotations are supplied evidence, not verified ground truth. No model performance, representativeness, clustering quality, or anomaly correctness is established.

Execution: completed. Coverage describes these checks, not a percentage of universal reliability. Source/header preflight, bounded row read, post-load frame measurement, cooperative stage deadlines; no hard memory or execution guarantee.

annotation cohorts: completed. Completed within the declared diagnostic scope.

output dependencies: completed. Completed within the declared diagnostic scope.

input relationships across outputs: exhaustive_within_methods. 2 output searches; scope examples: y, z. No observed relationship means only none verified in the searched scope; full per-output coverage is in JSON.

Presentation truncation

These records were computed and remain in JSON; their omission here is separate from analytical bounds and execution failures.

- cohort details with an empty population: 0 displayed of 5 computed; 5 omitted from this presentation.

8. Technical appendix

Methodology: tabular_multioutput_regression_v1 · Schema 1.2. Source SHA-256: `8703b8dd0d6fa2b5e80f3a71b092558000fea11641570ad09def81f2ce7876dd`. 19 detail rows displayed; appendix budget 100. Full checks, evidence references, declarations, bounds, and computed data are in JSON.

Check applicability and execution (repeated checks aggregated)

Check	Count and scope examples	Applicability	Execution	Reason
schema	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
missingness	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
column variation	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
categorical cardinality	1 checks; 1 scopes: dataset	not_applicable	not_run	No nonnumeric input columns.
feature missingness	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
exact duplicates	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
numeric summary	1 checks; 1 scopes: x	applicable	completed	Completed within declared scope
numeric outliers	1 checks; 1 scopes: x	applicable	completed	Completed within declared scope
feature semantics	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
annotation coverage	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
target coverage	2 checks; 2 scopes: y, z	applicable	completed	Completed within declared scope
annotation cohorts	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
multioutput regression	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
output evidence	2 checks; 2 scopes: y, z	applicable	completed	Completed within declared scope
parsing fidelity	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope

Relationship search: y

Method	Inputs	Status	Reason	Verified rows
exact_copy	x	verified_no_relationship	Applicable	5
affine_identity	x	blocked	insufficient_support	0

Relationship search: z

Method	Inputs	Status	Reason	Verified rows
exact_copy	x	verified_no_relationship	Applicable	5
affine_identity	x	blocked	insufficient_support	0