Partial Classification

partial_classification.csv · 2026-10-09T18:05:09.904356+00:00

1. Executive review summary

Pre-model evidence for the declared tabular task; no composite reliability score or model-quality verdict is defined.

60	1	1
parsed rows	input features	declared targets

60 parsed rows; 1 selected input feature; 1 target. Annotation coverage separates observation, expectation, metadata resolution, and declared uncertain validity.

2. Prioritized actions

No supported review findings in the computed scope. Coverage limitations and unavailable evidence still require review.

Composite scoring: not defined. Priorities are internal review rules, not validated performance or readiness ratings.

3. Dataset, roles, parsing, declarations

Purpose undeclared.

Roles: 1 features, 1 targets, 1 metadata, 0 ignored. Resolved roles and full declarations are retained in JSON.

Parsing: utf-8; pandas_default. Source-token review covers 180 comparable prefix cells. NA-like tokens may become missing; numeric-looking codes may lose leading zeros. No source values were rewritten.

4. Annotation or input coverage

Observed vectors: 40 complete, 0 partial, 20 empty. 40 rows have any annotation. Expected-vector completion: 0 / 0 rows with resolved requirements. Expected coverage is unavailable: no resolved expected annotations.

> Unknown expectation is separate from uncertain label validity. Supplied values remain in descriptive evidence. Optional absence does not establish intentional absence. Expected coverage must be read alongside unknown-expectation populations.

Per-target annotation coverage

Target	Observed / rows	Supplied / expected	Unknown expectation	Invalid / conflicts	Uncertain observed
y	40 / 60 (66.7%)	0 / 0 (Unavailable)	40 / 60	0 / 0	0

Annotation state counts

Target	Absent	Expected gaps	Intentional absence	Unresolved metadata
y	20	0	20	0

5. Task-specific evidence

Observed class distribution

Class	Count	Share of observed
a	20	50.0%
b	20	50.0%

6. Features, repetition, annotation populations

All-column parsed duplicates: 0 extra rows. Selected-feature identity and observed annotation variation have separate scopes. Repetition may be legitimate or intentional weighting.

Selected-input repetition: 0 groups; 0 rows participate in observed annotation disagreement; 0 groups have mixed expectation/status metadata. These scopes remain separate.

Selected feature structure

Feature	Meaning	Storage	Observed distinct	Missing / rows
x	assumed quantitative	int64	60	0 / 60

Annotation population contrasts

Cohort	Feature	Cohort sizes	Missing counts	Supported shape evidence
any_observed_vs_none	x	40 / 20	0 / 0	median 30, IQR 29; median 28.5, IQR 28.5
y:observed_vs_intentional_absence	x	40 / 20	0 / 0	median 30, IQR 29; median 28.5, IQR 28.5

4 feature/cohort records computed; 2 have an empty comparison population. Empty populations support no shape contrast; their counts and reasons remain in JSON.

Population contrasts are descriptive within this file. They do not establish a missingness mechanism, representativeness, or deployment shift.

7. Applicability, bounds, scoring, limitations

Observed annotations are supplied evidence, not verified ground truth. No model performance, representativeness, clustering quality, or anomaly correctness is established.

Execution: completed. Coverage describes these checks, not a percentage of universal reliability. Source/header preflight, bounded row read, post-load frame measurement, cooperative stage deadlines; no hard memory or execution guarantee.

annotation cohorts: completed. Completed within the declared diagnostic scope.

Presentation truncation

These records were computed and remain in JSON; their omission here is separate from analytical bounds and execution failures.

- cohort details with an empty population: 0 displayed of 2 computed; 2 omitted from this presentation.

8. Technical appendix

Methodology: tabular_partial_classification_v1 · Schema 1.2. Source SHA-256: `85c090149bb36dc203e9979f6ebc0efcb7bce69db8d531d078e76219bc298e52`. 15 detail rows displayed; appendix budget 100. Full checks, evidence references, declarations, bounds, and computed data are in JSON.

Check applicability and execution (repeated checks aggregated)

Check	Count and scope examples	Applicability	Execution	Reason
schema	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
missingness	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
column variation	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
categorical cardinality	1 checks; 1 scopes: dataset	not_applicable	not_run	No nonnumeric input columns.
feature missingness	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
exact duplicates	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
numeric summary	1 checks; 1 scopes: x	applicable	completed	Completed within declared scope
numeric outliers	1 checks; 1 scopes: x	applicable	completed	Completed within declared scope
feature semantics	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
annotation coverage	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
target coverage	1 checks; 1 scopes: y	applicable	completed	Completed within declared scope
annotation cohorts	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
classification distribution	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
annotation repetition	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope
parsing fidelity	1 checks; 1 scopes: dataset	applicable	completed	Completed within declared scope