Comparative tabular reliability

Review qualified findings and the completed analytical scope. No qualifying issue means none within completed definitions and bounds.

Execution: partial · Backend: duckdb_local. A clean result means no qualifying issue within completed definitions and bounds.

1. Summary

1 qualified review findings across 1 source(s). Comparisons have no composite score or risk band.

2. Actions

Moderate · dataset

Strong dependence between selected inputs warrants review

Review source provenance and the declared use.

observation. Dependence does not establish redundancy, causality or leakage; unique-value memorization is excluded.

3. Sources and declarations

source	rows	columns	sha256	task
dataset	1000	5	102a6a870e0843508f2eba911afdac30c5193f92906b92939a495d33b552fb2a	dataset_profile

Alignment is case-sensitive and declaration-bound. Identifier/key strings preserve decoded lexical identity, including leading zeros and whitespace. Effective parsing, annotation, semantic, mapping and key declarations are retained in JSON.

4. Overlap and schema evidence

Overlap counts are participating rows and grouped multiset intersections. Shared observations do not prove leakage; absence applies only to completed definitions.

5. Feature populations and missingness

source	column	role	storage	missing	missing percent	nonfinite	distinct
dataset	id	metadata	VARCHAR	0	0.0	0	1000
dataset	x	feature	BIGINT	0	0.0	0	1000
dataset	z	feature	BIGINT	0	0.0	0	1000
dataset	channel	feature	VARCHAR	0	0.0	0	2
dataset	label	ignored	VARCHAR	0	0.0	0	2

Missingness changes are signed percentage points. Distributions use observed categorical or finite quantitative values. Wasserstein-1 retains original units. Counts, full-population effects and separately qualified optional tests appear in JSON.

6. Targets, constraints and segments

scope	affected union	retained details	unsearched	stopping reason
dataset.missingness_structure	0	3	0	complete
dataset.dependencies	Unavailable	3	0	complete

Annotation expectation is independent of observed validity. Complete and partial vectors, declared requirements, subgroup mix and conditional populations retain their own denominators. Correlation, IQR candidates and conditional differences do not establish causality, fairness or anomaly correctness.

7. Methodology and coverage

Accepted task-family support does not mean exhaustive analytical searches. Planned limits complete bounded scope; omitted detail and unsearched scope remain explicit.

Method m4_local_2026_10_10. Parsing scalable_csv_v1. DuckDB 1.5.6. Searches are deterministic and bounded; required structural and configured overlap populations use every eligible record.

Resource defaults and runtime safeguards are engineering controls, not capacity guarantees. Disk planning estimates are conservative estimates, not upper bounds. Runtime 0.36 seconds; sampled peak worker RSS 119488512 bytes; recorded peak workspace 102400 bytes.

Parsed equality does not establish byte-identical records or proven leakage.

Effects and support describe supplied populations; conditional evidence is descriptive.

Search bounds and detail omissions remain visible in coverage.

8. Appendix and retained scope

check	status	population	unsearched	excluded columns
dataset.structure	completed	all eligible records	0	
dataset.repeated_inputs	completed	all eligible records	0	
dataset.missingness_structure	completed	all eligible records	0	
dataset.dependencies	completed	all eligible records	0	
controlled_optional_failure	failed	controlled optional scope	Unavailable	Test-only fixture; no runtime fault-injection setting is shipped.

Human detail omissions, unsearched analytical scope, blocked methods and failed execution are distinct. JSON preserves all retained computed records. Generated 2026-10-10T17:38:43.427144+00:00.