Comparative tabular reliability

Review qualified findings and the completed analytical scope. No qualifying issue means none within completed definitions and bounds.

Execution: completed · Backend: duckdb_local. A clean result means no qualifying issue within completed definitions and bounds.

1. Summary

0 qualified review findings across 2 source(s). Comparisons have no composite score or risk band.

2. Actions

No qualifying findings were produced within completed scope. Review declarations and unsearched scope before relying on this result.

3. Sources and declarations

source	rows	columns	sha256	task
source1	1000	5	102a6a870e0843508f2eba911afdac30c5193f92906b92939a495d33b552fb2a	classification
source2	1000	5	8b59e22bdac5c3cab44f10e67effeeaaedf393cb45d7d07b06199e1bf09bff8e	classification

Alignment is case-sensitive and declaration-bound. Identifier/key strings preserve decoded lexical identity, including leading zeros and whitespace. Effective parsing, annotation, semantic, mapping and key declarations are retained in JSON.

4. Overlap and schema evidence

pair	added	removed	storage or role changes
source1:source2	None	None	0

Overlap counts are participating rows and grouped multiset intersections. Shared observations do not prove leakage; absence applies only to completed definitions.

5. Feature populations and missingness

source	column	role	storage	missing	missing percent	nonfinite	distinct
source1	id	metadata	VARCHAR	0	0.0	0	1000
source1	x	feature	BIGINT	0	0.0	0	1000
source1	z	feature	BIGINT	0	0.0	0	1000
source1	channel	feature	VARCHAR	0	0.0	0	2
source2	id	metadata	VARCHAR	0	0.0	0	1000
source2	x	feature	BIGINT	0	0.0	0	1000
source2	z	feature	BIGINT	0	0.0	0	1000
source2	channel	feature	VARCHAR	0	0.0	0	2

pair	column	left rows	right rows	missing change pp	TV	CDF	Wasserstein 1	block
source1:source2	x	1000	1000	0.0	Unavailable	0.050000000000000044	50.000000000000064	Unavailable
source1:source2	z	1000	1000	0.0	Unavailable	0.0	0.0	Unavailable
source1:source2	channel	1000	1000	0.0	0.0	Unavailable	Unavailable	Unavailable
source1:source2	label	1000	1000	0.0	0.0	Unavailable	Unavailable	Unavailable

pair	column	left rows	right rows	missing change pp	TV	CDF	Wasserstein 1	block
source1:source2:segment1:segment_value1	x	500	500	0.0	Unavailable	0.050000000000000044	50.000000000000017	Unavailable
source1:source2:segment1:segment_value1	z	500	500	0.0	Unavailable	0.0	0.0	Unavailable
source1:source2:segment1:segment_value1	channel	500	500	0.0	0.0	Unavailable	Unavailable	Unavailable
source1:source2:segment1:segment_value1	label	500	500	0.0	0.0	Unavailable	Unavailable	Unavailable
source1:source2:segment1:segment_value2	x	500	500	0.0	Unavailable	0.050000000000000044	49.999999999999969	Unavailable
source1:source2:segment1:segment_value2	z	500	500	0.0	Unavailable	0.0	0.0	Unavailable
source1:source2:segment1:segment_value2	channel	500	500	0.0	0.0	Unavailable	Unavailable	Unavailable
source1:source2:segment1:segment_value2	label	500	500	0.0	0.0	Unavailable	Unavailable	Unavailable

Missingness changes are signed percentage points. Distributions use observed categorical or finite quantitative values. Wasserstein-1 retains original units. Counts, full-population effects and separately qualified optional tests appear in JSON.

6. Targets, constraints and segments

source	column	role	storage	missing	missing percent	nonfinite	distinct
source1	label	target	VARCHAR	0	0.0	0	2
source2	label	target	VARCHAR	0	0.0	0	2

scope	affected union	retained details	unsearched	stopping reason
source1.segments	Unavailable	6	0	complete
source2.segments	Unavailable	6	0	complete
source1:source2.segment_mix	Unavailable	1	0	complete

Annotation expectation is independent of observed validity. Complete and partial vectors, declared requirements, subgroup mix and conditional populations retain their own denominators. Correlation, IQR candidates and conditional differences do not establish causality, fairness or anomaly correctness.

7. Methodology and coverage

Accepted task-family support does not mean exhaustive analytical searches. Planned limits complete bounded scope; omitted detail and unsearched scope remain explicit.

Method m4_local_2026_10_10. Parsing scalable_csv_v1. DuckDB 1.5.6. Searches are deterministic and bounded; required structural and configured overlap populations use every eligible record.

Resource defaults and runtime safeguards are engineering controls, not capacity guarantees. Disk planning estimates are conservative estimates, not upper bounds. Runtime 0.49 seconds; sampled peak worker RSS 128139264 bytes; recorded peak workspace 184320 bytes.

Parsed equality does not establish byte-identical records or proven leakage.

Effects and support describe supplied populations; conditional evidence is descriptive.

Search bounds and detail omissions remain visible in coverage.

8. Appendix and retained scope

check	status	population	unsearched	excluded columns
source1.structure	completed	all eligible records	0	
source1.annotations	completed	all eligible records	0	
source1.repeated_inputs	completed	all eligible records	0	
source1.annotation_cohorts	completed	all eligible records	0	
source1.segments	completed	all eligible records	0	
source2.structure	completed	all eligible records	0	
source2.annotations	completed	all eligible records	0	
source2.repeated_inputs	completed	all eligible records	0	
source2.annotation_cohorts	completed	all eligible records	0	
source2.segments	completed	all eligible records	0	
source1:source2.schema	completed	all eligible records	0	
source1:source2.populations	completed	observed categorical or finite quantitative values; missing/non-finite counts separately	0	
source1:source2:segment1:segment_value1.populations	completed	observed categorical or finite quantitative values; missing/non-finite counts separately	0	

check	status	population	unsearched	excluded columns
source1:source2:segment1:segment_value2.populations	completed	observed categorical or finite quantitative values; missing/non-finite counts separately	0	
source1:source2.segment_mix	completed	declared segment mix; within-segment populations remain separate	0	

Human detail omissions, unsearched analytical scope, blocked methods and failed execution are distinct. JSON preserves all retained computed records. Generated 2026-10-10T17:33:54.777783+00:00.