long_headers

Review qualified findings and the completed analytical scope. No qualifying issue means none within completed definitions and bounds.

Execution: completed · Backend: duckdb_local. A clean result means no qualifying issue within completed definitions and bounds.

1. Summary

2 qualified review findings across 1 source(s). Comparisons have no composite score or risk band.

2. Actions

Moderate · dataset

Strong dependence between selected inputs warrants review

Review source provenance and the declared use.

observation. Dependence does not establish redundancy, causality or leakage; unique-value memorization is excluded.

Low · dataset

Quantitative feature scales differ substantially

Review source provenance and the declared use.

observation. Evidence does not establish a defect, causality, or leakage.

3. Sources and declarations

source	rows	columns	sha256	task
dataset	240	12	a98aeabb13198a8a0ee61336c1f8ca162b9065fe8d8f645adda83406de0ecbf5	clustering

Alignment is case-sensitive and declaration-bound. Identifier/key strings preserve decoded lexical identity, including leading zeros and whitespace. Effective parsing, annotation, semantic, mapping and key declarations are retained in JSON.

4. Overlap and schema evidence

Overlap counts are participating rows and grouped multiset intersections. Shared observations do not prove leakage; absence applies only to completed definitions.

5. Feature populations and missingness

source	column	role	storage	missing	missing percent	nonfinite	distinct
dataset	measurement_0_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_1_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_2_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_3_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240

source	column	role	storage	missing	missing percent	nonfinite	distinct
dataset	measurement_4_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_5_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_6_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_7_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_8_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_9_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_a…	feature	DOUBLE	0	0.0	0	240
dataset	measurement_10_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_…	feature	DOUBLE	0	0.0	0	240

source	column	role	storage	missing	missing percent	nonfinite	distinct
dataset	measurement_11_with_explicit_source_unit_a_very_long_declared_name_a_very_long_declared_name_…	feature	DOUBLE	0	0.0	0	240

Missingness changes are signed percentage points. Distributions use observed categorical or finite quantitative values. Wasserstein-1 retains original units. Counts, full-population effects and separately qualified optional tests appear in JSON.

6. Targets, constraints and segments

scope	affected union	retained details	unsearched	stopping reason
dataset.unsupervised_readiness	Unavailable	0	0	complete
dataset.missingness_structure	0	16	50	planned_bounds
dataset.dependencies	Unavailable	16	50	planned_bounds

Annotation expectation is independent of observed validity. Complete and partial vectors, declared requirements, subgroup mix and conditional populations retain their own denominators. Correlation, IQR candidates and conditional differences do not establish causality, fairness or anomaly correctness.

7. Methodology and coverage

Accepted task-family support does not mean exhaustive analytical searches. Planned limits complete bounded scope; omitted detail and unsearched scope remain explicit.

Method m4_local_2026_10_10. Parsing scalable_csv_v1. DuckDB 1.5.6. Searches are deterministic and bounded; required structural and configured overlap populations use every eligible record.

Resource defaults and runtime safeguards are engineering controls, not capacity guarantees. Disk planning estimates are conservative estimates, not upper bounds. Runtime 0.34 seconds; sampled peak worker RSS 115245056 bytes; recorded peak workspace 155648 bytes.

Parsed equality does not establish byte-identical records or proven leakage.

Effects and support describe supplied populations; conditional evidence is descriptive.

Search bounds and detail omissions remain visible in coverage.

8. Appendix and retained scope

12 long field labels shortened for display. Exact names are retained in JSON.

check	status	population	unsearched	excluded columns
dataset.structure	completed	all eligible records	0	
dataset.repeated_inputs	completed	all eligible records	0	

check	status	population	unsearched	excluded columns
dataset.unsupervised_readiness	completed	all eligible records	0	
dataset.missingness_structure	completed	all eligible records	50	
dataset.dependencies	completed	all eligible records	50	

Excluded-column previews show at most three shortened names; complete sets are retained in JSON. Human detail omissions, unsearched analytical scope, blocked methods and failed execution are distinct. JSON preserves all retained computed records. Generated 2026-10-10T17:41:10.231243+00:00.