Constrained

Source: constraint_union.csv · Target: outcome

1. Regression Review Summary

Regression dataset evidence is available for review. Priorities describe investigation needs, not a score or readiness verdict.

100 of 100 targets are finite, with 100 distinct finite values.

Rows	Feature inputs	Review findings	Finite targets
100	1	1	100

No validated scoring policy is defined for regression reliability.

Review priorities are investigation needs, not risk bands or a readiness verdict.

> **Relationship coverage: exhaustive within methods**
> No observed relationship means only none verified in the searched scope; unsearched relationships are unknown.

2. Priority Review Actions

Declared target constraint violations · High review priority

11 finite targets violate at least one user-declared requirement.

above_declared_maximum: 9; declared_nonnegative: 2; declared_integer: 1

Consequence: Declared violations may make observations incompatible with the intended outcome definition.

Action: Confirm the declaration and investigate violating observations; no values were removed.

Population: Name: finite targets; Denominator: 100. Requirements are user-declared; violations do not independently verify the declaration.

Evidence type: declared constraint violation · regression_constraints.14

3. Dataset, Target, and Declared Expectations

Target selected explicitly: **outcome**. Target intent: count. Integer-valued observations do not independently establish count semantics.

User-declared expectation	Value
kind	count
minimum	Not set
maximum	90
nonnegative	Yes
integer required	Yes
units	Not set

Units are display context; no unit conversion or semantic validity is inferred.

Column	Role	Parsed dtype	Observed values
input	feature	float64	100 / 100
outcome	target	float64	100 / 100

Parsing: Pandas default missing tokens; utf-8. All evidence concerns the parsed interpretation.

4. Target Coverage and Distribution

All-row coverage: 100 finite, 0 missing, 0 positive infinity, 0 negative infinity.

Distribution population: finite targets, including declared constraint violations. Units: Not declared.

Measurement	Finite-target evidence
min	-1
max	99
mean	49.475
sample std	29.054579
distinct count	100
zero count	0
negative count	2
integer count	99
non integer count	1
iqr	49.5
central 90 span	89.1
bowley skewness	0
modal share	1

Quantile strip



P1 -0.505 · P5 4.95 · Q1 24.75 · Median 49.5 · Q3 74.25 · P95 94.05 · P99 98.01

Finite target distribution

freedman diaconis capped 40; counts total 100 finite observations. Bin counts and interval definitions appear in the appendix.

1.5-IQR candidates: 0 lower, 0 upper, of 100 finite values. These are review candidates, not established errors.

Declared constraints

11 finite targets violate at least one declared requirement; 89 satisfy the declared constraints. No observations were removed.

User-declared rule	Violations / finite population
above declared maximum: 90	9 / 100
declared nonnegative: 0	2 / 100
declared integer: True	1 / 100

Concentration and numerical representation

Most-common-value share: 1% of finite targets. Boundary concentration does not establish clipping or saturation.

Boundary	Value	Count / finite share
observed minimum	-1	1 / 1%
observed maximum	99	1 / 1%
declared maximum	90	1 / 1%

Numerical representation: completed. Coarsest observed aligned grid: 1. Ordinary integer or fixed-decimal representation is descriptive and generates no rounding action.

5. Target Relationships and Feature Availability

Small or sparse relationships remain qualified technical evidence. No relationship conclusion covers unsearched candidates.

Actions require at least 30 finite overlapping rows, five distinct targets, 80% finite-target coverage, and complete numerical verification. Availability is user-declared or unknown; observed algebra does not prove leakage or actual model use.

Feature	User-declared availability
input	unknown

Distinct relationship groups

No relationship groups were verified in the searched scope. Unsearched candidates remain unknown.

Qualified technical relationship evidence

Observed relationship	Support and finite-target coverage	Interpretation

6. Missingness, Repetition, and Feature Evidence

0 parsed cells missing (0.0%). Rows with missing features: 0 / 100. Target coverage is reported separately.

input · 0 missing (0.0%)

Exact repetition and target variation within repeated inputs require context; automatic deduplication or label-error conclusions are not warranted.

0 repeated rows beyond each first occurrence; 0 exact groups; 0 participating rows.

Repeated-input groups: 0; varying-target groups: 0; varying-target rows: 0.

Example group rows / distinct targets	Target extrema / span

7. Coverage, Methods, Scoring Availability, and Limitations

No validated scoring policy is defined for regression reliability.

Coverage describes these checks, not a percentage of universal reliability.

Numerical shape, rounding, extremes, and repetition can be legitimate. Constraints apply only to declarations. Name cues and algebraic identities do not establish feature availability, causal direction, leakage, or label error. No cleaning, model training, prediction evaluation, or monitoring occurs.

Relationship search: exhaustive within methods. 1 eligible numerical columns; 1 selected for pairs; 2 candidates; 2 fully verified; 0 planned work skips; 0 unfinished candidates after interruption/failure.

Configured relation limits: Max single comparisons: 20000000; Max pair comparisons: 20000000; Max pair features: 32; Max screen rows: 512. Consumed comparisons: Single: 200; Pair: 0.

Selected pair columns: input.

Support thresholds are internally tested interpretation rules, not externally validated reliability cutoffs.

8. Technical Appendix

Parsing, execution, and coverage disclosure

Parser: pandas.read_csv / pandas 3.0.3. Comma delimiter, inferred header, blank lines skipped. Encoding: utf-8. Missing policy: Pandas default missing tokens. Source values were not rewritten.

Custom missing tokens: None configured; explicit column types: None configured.

Source SHA-256: 390f160cde66629d6931a2133a9b4803095e6b07b7137cab8678a7b15db209cd. Method: tabular_regression_v1.

Token inspection: 1160 bytes, 100 data records, 200 comparable cells; stopping reason: End of source. Alignment confirmed: Yes.

Interpretation review warnings are separate from data findings and scoring. Counts describe only inspected source tokens and are never extrapolated to the dataset. No warnings observed does not establish losslessness.

No parsing warnings observed within the inspected scope.

Operational safeguards

Source/header preflight, bounded row read, post-load frame measurement, cooperative stage deadlines; no hard memory or execution guarantee.

Backend: Pandas in memory; frame: 1732 bytes; elapsed: 0.00762 seconds.

Configured safeguard	Limit
Maximum source size	104857600 bytes
Maximum rows	1000000
Maximum columns	1000
Maximum loaded frame size	536870912 bytes
Cooperative elapsed-time limit	Not set

Check applicability and execution

Check / scope	Applicable	Execution	Reason / exclusions
schema · dataset	applicable	completed	No exclusions

Check / scope	Applicable	Execution	Reason / exclusions
missingness · dataset	applicable	completed	No exclusions
column variation · dataset	applicable	completed	No exclusions
categorical cardinality · dataset	not applicable	not run	No nonnumeric input columns.
feature missingness · dataset	applicable	completed	No exclusions
exact duplicates · dataset	applicable	completed	No exclusions
numeric summary · input	applicable	completed	No exclusions
numeric outliers · input	applicable	completed	Exclusions: Missing values: 0; Non finite values: 0
regression target · outcome	applicable	completed	No exclusions
regression sample std · outcome	applicable	completed	No exclusions
regression extremes · outcome	applicable	completed	No exclusions
regression bowley skewness · outcome	applicable	completed	No exclusions
regression histogram · outcome	applicable	completed	No exclusions
regression rounding · outcome	applicable	completed	No exclusions
regression constraints · outcome	applicable	completed	No exclusions
regression relationships · dataset	applicable	completed	No exclusions
regression names · dataset	applicable	completed	No exclusions
regression repeated inputs · dataset	applicable	completed	No exclusions
regression availability · dataset	applicable	completed	No exclusions
classification target · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
label conflicts · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
target leakage · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
classification scoring · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
parsing fidelity · dataset	applicable	completed	No exclusions

Coverage describes these checks, not a percentage of universal reliability.

Unsupported: semantic typing; missingness patterns; split/reference comparisons; model performance; non-tabular modalities.

Deterministic fixtures and corpus regression checks provide internal methodology validation. They do not establish external method validity or customer usefulness. Prediction and model-performance analysis belong to ConfidenceGuard.

Resolved source headers

Source position	Original header	Resolved name
1	input	input
2	outcome	outcome

Relationship search ledger

Method / columns	Status / reason	Screened / verified rows
exact copy · input	verified no relationship	0 / 100
affine identity · input	verified no relationship	0 / 100

Histogram count table

Lower	Upper	Count
-1	19	20
19	39	20
39	59	20
59	79	20
79	99	20

left closed, right open; final bin includes maximum

Grid alignment evidence

Step	Status	Aligned / finite share
1.0	completed	99 / 99

Step	Status	Aligned / finite share
0.1	completed	100 / 100
0.01	completed	100 / 100
0.001	completed	100 / 100

Feature numerical evidence

Feature	Finite summary	IQR evidence
input · 100 distinct	Finite 100; min 0; median 2450.5; max 9801	0

Evidence references

Evidence ID	Population / denominator	Method / measurements
schema.0	parsed records / 100	deterministic; /parsing/header_mapping, /profile/row_count, /profile/column_count
missingness.1	all parsed cells / 200	deterministic; /profile/missing_cells, /profile/missing_rate, /profile/missing_feature_row_rate
column_variation.2	all parsed columns / 2	deterministic; /profile/columns
categorical_cardinality.3	nonnumeric parsed columns / 0	deterministic; /profile/columns
feature_missingness.4	parsed feature cells / 100	deterministic; /profile/missing_feature_cells, /profile/missing_feature_cell_rate, /profile/missing_feature_row_rate
exact_duplicates.5	all parsed rows / 100	deterministic; /profile/duplicate_rows, /profile/duplicate_group_count, /profile/rows_in_duplicate_groups
numeric_summary.6	finite values; zero/negative/non-finite rates use total rows / 100	Finite-value descriptive statistics; /profile/columns/0/numeric_summary, /profile/columns/0/finite_count
numeric_outliers.7	finite numeric observations / 100	Finite-value 1.5-IQR fences; /profile/columns/0/outlier_count, /profile/columns/0/outlier_rate
regression_target.8	finite targets; coverage uses all parsed rows / 100	finite regression distribution; /profile/regression/target_statistics
regression_sample_std.9	finite targets / 100	deterministic; /profile/regression/target_statistics/sample_std
regression_extremes.10	finite targets / 100	deterministic; /profile/regression/target_statistics/extremes

Evidence ID	Population / denominator	Method / measurements
regression_bowley_skewness.11	finite targets / 100	deterministic; /profile/regression/target_statistics/bowley_skewness
regression_histogram.12	finite targets / 100	deterministic; /profile/regression/target_statistics/histogram
regression_rounding.13	finite targets / 100	deterministic; /profile/regression/target_statistics/rounding
regression_constraints.14	finite targets / 100	deterministic; /profile/regression/constraints Bounded parsed-row references: 1, 2, 92, 93, 94
regression_relationships.15	eligible numerical features; explicitly bounded candidate search / not applicable	bounded arithmetic identities; /profile/regression/search
regression_names.16	feature names; contextual cues only / 1	deterministic; /profile/regression/name_candidates
regression_repeated_inputs.17	finite targets grouped by exact feature values / 100	deterministic; /profile/regression/repeated_inputs
regression_availability.18	user-declared feature context / 1	deterministic; /profile/regression/feature_availability
parsing_fidelity.19	bounded source prefix / 200	bounded source token comparison; /parsing/fidelity_inspection, /parsing_warnings