Partial

Source: partial.csv · Target: outcome

Analysis incomplete
Unexpected diagnostic failure or execution interruption left some checks unavailable. Completed evidence remains available.

1. Regression Review Summary

Regression dataset evidence is available for review. Priorities describe investigation needs, not a score or readiness verdict.

40 of 40 targets are finite, with 40 distinct finite values.

Rows	Feature inputs	Review findings	Finite targets
40	1	0	40

No validated scoring policy is defined for regression reliability.

Review priorities are investigation needs, not risk bands or a readiness verdict.

Relationship diagnostics unavailable; no conclusion is supported.

2. Priority Review Actions

> No regression findings were generated by completed checks. Review parsing warnings, unavailable checks, and bounded searches separately.

3. Dataset, Target, and Declared Expectations

Target selected explicitly: **outcome**. Target intent: unspecified. Integer-valued observations do not independently establish count semantics.

User-declared expectation	Value
kind	unspecified
minimum	Not set
maximum	Not set

User-declared expectation	Value
nonnegative	Not set
integer required	Not set
units	Not set

Units are display context; no unit conversion or semantic validity is inferred.

Column	Role	Parsed dtype	Observed values
qa_optional_failure	feature	int64	40 / 40
outcome	target	int64	40 / 40

Parsing: Pandas default missing tokens; utf-8. All evidence concerns the parsed interpretation.

4. Target Coverage and Distribution

All-row coverage: 40 finite, 0 missing, 0 positive infinity, 0 negative infinity.

Distribution population: finite targets, including declared constraint violations. Units: Not declared.

Measurement	Finite-target evidence
min	0
max	39
mean	19.5
sample std	11.690452
distinct count	40
zero count	1
negative count	0
integer count	40
non integer count	0
iqr	19.5
central 90 span	35.1
bowley skewness	0
modal share	2.5

Quantile strip



P1 0.39 · P5 1.95 · Q1 9.75 · Median 19.5 · Q3 29.25 · P95 37.05 · P99 38.61

Finite target distribution

freedman diaconis capped 40; counts total 40 finite observations. Bin counts and interval definitions appear in the appendix.

1.5-IQR candidates: 0 lower, 0 upper, of 40 finite values. These are review candidates, not established errors.

Declared constraints

0 finite targets violate at least one declared requirement; 40 satisfy the declared constraints. No observations were removed.

User-declared rule	Violations / finite population
No numerical constraints declared.	

Concentration and numerical representation

Most-common-value share: 2.5% of finite targets. Boundary concentration does not establish clipping or saturation.

Boundary	Value	Count / finite share
observed minimum	0	1 / 2.5%
observed maximum	39	1 / 2.5%

Numerical representation: completed. Coarsest observed aligned grid: 1. Ordinary integer or fixed-decimal representation is descriptive and generates no rounding action.

5. Target Relationships and Feature Availability

Small or sparse relationships remain qualified technical evidence. No relationship conclusion covers unsearched candidates.

Actions require at least 30 finite overlapping rows, five distinct targets, 80% finite-target coverage, and complete numerical verification. Availability is user-declared or unknown; observed algebra does not prove leakage or actual model use.

Feature	User-declared availability
qa_optional_failure	unknown

Distinct relationship groups

No relationship groups were verified in the searched scope. Unsearched candidates remain unknown.

Qualified technical relationship evidence

Observed relationship	Support and finite-target coverage	Interpretation

6. Missingness, Repetition, and Feature Evidence

0 parsed cells missing (0.0%). Rows with missing features: 0 / 40. Target coverage is reported separately.

qa_optional_failure · 0 missing (0.0%)

Exact repetition and target variation within repeated inputs require context; automatic deduplication or label-error conclusions are not warranted.

0 repeated rows beyond each first occurrence; 0 exact groups; 0 participating rows.

Repeated-input groups: 0; varying-target groups: 0; varying-target rows: 0.

Example group rows / distinct targets	Target extrema / span

7. Coverage, Methods, Scoring Availability, and Limitations

No validated scoring policy is defined for regression reliability.

Coverage describes these checks, not a percentage of universal reliability.

Numerical shape, rounding, extremes, and repetition can be legitimate. Constraints apply only to declarations. Name cues and algebraic identities do not establish feature availability, causal direction, leakage, or label error. No cleaning, model training, prediction evaluation, or monitoring occurs.

Support thresholds are internally tested interpretation rules, not externally validated reliability cutoffs.

8. Technical Appendix

Parsing, execution, and coverage disclosure

Analysis incomplete — review unavailable checks below.

Parser: pandas.read_csv / pandas 3.0.3. Comma delimiter, inferred header, blank lines skipped. Encoding: utf-8. Missing policy: Pandas default missing tokens. Source values were not rewritten.

Custom missing tokens: None configured; explicit column types: None configured.

Source SHA-256: 456d2bd5c4cc998aaf7c9e7b9f402a0295e4c7988264ac81103093965544b457. Method: tabular_regression_v1.

Token inspection: 292 bytes, 40 data records, 80 comparable cells; stopping reason: End of source. Alignment confirmed: Yes.

Interpretation review warnings are separate from data findings and scoring. Counts describe only inspected source tokens and are never extrapolated to the dataset. No warnings observed does not establish losslessness.

No parsing warnings observed within the inspected scope.

Operational safeguards

Source/header preflight, bounded row read, post-load frame measurement, cooperative stage deadlines; no hard memory or execution guarantee.

Backend: Pandas in memory; frame: 772 bytes; elapsed: 0.005782 seconds.

Configured safeguard	Limit
Maximum source size	104857600 bytes
Maximum rows	1000000
Maximum columns	1000
Maximum loaded frame size	536870912 bytes
Cooperative elapsed-time limit	Not set

Check applicability and execution

Check / scope	Applicable	Execution	Reason / exclusions
schema · dataset	applicable	completed	No exclusions
missingness · dataset	applicable	completed	No exclusions
column variation · dataset	applicable	completed	No exclusions
categorical cardinality · dataset	not applicable	not run	No nonnumeric input columns.
feature missingness · dataset	applicable	completed	No exclusions
exact duplicates · dataset	applicable	completed	No exclusions
numeric summary · qa_optional_failure	applicable	completed	No exclusions
numeric outliers · qa_optional_failure	applicable	completed	Exclusions: Missing values: 0; Non finite values: 0
regression target · outcome	applicable	completed	No exclusions
regression sample std · outcome	applicable	completed	No exclusions
regression extremes · outcome	applicable	completed	No exclusions
regression bowley skewness · outcome	applicable	completed	No exclusions
regression histogram · outcome	applicable	completed	No exclusions
regression rounding · outcome	applicable	completed	No exclusions
regression constraints · dataset	not applicable	not run	No numerical constraints declared.
regression relationships · dataset	applicable	failed	RuntimeError: check failed; no conclusion was generated.
regression repeated inputs · dataset	applicable	completed	No exclusions
regression availability · dataset	applicable	completed	No exclusions
classification target · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
label conflicts · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
target leakage · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.
classification scoring · dataset	not applicable	not run	Regression uses numerical target evidence and no classification scores.

Check / scope	Applicable	Execution	Reason / exclusions
parsing fidelity · dataset	applicable	completed	No exclusions

Coverage describes these checks, not a percentage of universal reliability.

Unsupported: semantic typing; missingness patterns; split/reference comparisons; model performance; non-tabular modalities.

Deterministic fixtures and corpus regression checks provide internal methodology validation. They do not establish external method validity or customer usefulness. Prediction and model-performance analysis belong to ConfidenceGuard.

Resolved source headers

Source position	Original header	Resolved name
1	qa_optional_failure	qa_optional_failure
2	outcome	outcome

Relationship search ledger

Histogram count table

Lower	Upper	Count
0	9.75	10
9.75	19.5	10
19.5	29.25	10
29.25	39	10

left closed, right open; final bin includes maximum

Grid alignment evidence

Step	Status	Aligned / finite share
1.0	completed	40 / 100
0.1	completed	40 / 100
0.01	completed	40 / 100

Step	Status	Aligned / finite share
0.001	completed	40 / 100

Feature numerical evidence

Feature	Finite summary	IQR evidence
qa_optional_failure · 40 distinct	Finite 40; min 0; median 380.5; max 1521	0

Evidence references

Evidence ID	Population / denominator	Method / measurements
schema.0	parsed records / 40	deterministic; /parsing/header_mapping, /profile/row_count, /profile/column_count
missingness.1	all parsed cells / 80	deterministic; /profile/missing_cells, /profile/missing_rate, /profile/missing_feature_row_rate
column_variation.2	all parsed columns / 2	deterministic; /profile/columns
categorical_cardinality.3	nonnumeric parsed columns / 0	deterministic; /profile/columns
feature_missingness.4	parsed feature cells / 40	deterministic; /profile/missing_feature_cells, /profile/missing_feature_cell_rate, /profile/missing_feature_row_rate
exact_duplicates.5	all parsed rows / 40	deterministic; /profile/duplicate_rows, /profile/duplicate_group_count, /profile/rows_in_duplicate_groups
numeric_summary.6	finite values; zero/negative/non-finite rates use total rows / 40	Finite-value descriptive statistics; /profile/columns/0/numeric_summary, /profile/columns/0/finite_count
numeric_outliers.7	finite numeric observations / 40	Finite-value 1.5-IQR fences; /profile/columns/0/outlier_count, /profile/columns/0/outlier_rate
regression_target.8	finite targets; coverage uses all parsed rows / 40	finite regression distribution; /profile/regression/target_statistics
regression_sample_std.9	finite targets / 40	deterministic; /profile/regression/target_statistics/sample_std
regression_extremes.10	finite targets / 40	deterministic; /profile/regression/target_statistics/extremes
regression_bowley_skewness.11	finite targets / 40	deterministic; /profile/regression/target_statistics/bowley_skewness

Evidence ID	Population / denominator	Method / measurements
regression_histogram.12	finite targets / 40	deterministic; /profile/regression/target_statistics/histogram
regression_rounding.13	finite targets / 40	deterministic; /profile/regression/target_statistics/rounding
regression_repeated_inputs.14	finite targets grouped by exact feature values / 40	deterministic; /profile/regression/repeated_inputs
regression_availability.15	user-declared feature context / 1	deterministic; /profile/regression/feature_availability
parsing_fidelity.16	bounded source prefix / 80	bounded source token comparison; /parsing/fidelity_inspection, /parsing_warnings