

Writing tests that stand the test of time



Segun Famisa
Android GDE



segunfamisa

segunfamisa.com



Outline

Introduction to TDD

Challenges with TDD

Testing tools in practice

Writing maintainable tests

Recap



Introduction

An abstract background featuring a network of thin, light purple lines connecting small dots, creating a complex, web-like structure. The dots and lines are more prominent in the upper half of the image, fading into a solid dark purple background towards the bottom. The overall aesthetic is modern and technological.

So, what's **Test Driven Development**?

“

TDD is a software development process that relies on the repetition of a very short development cycle: requirements are turned into very specific test cases, then the software is improved to pass the new tests, only

Wikipedia

TDD is a software development process that relies on the repetition of a very short development cycle: requirements are turned into very specific test cases, then the software is improved to pass the new tests, only


TDD is a software development process that relies on the repetition of a very short development cycle: requirements are turned into very specific test cases, then the software is improved to pass the new tests, only



How to do TDD?


Red - Green - Refactor

Red - Green - Refactor




Write
failing test


Red - Green - Refactor



Red - Green - Refactor



Red - Green - Refactor





Why do we need tests?

Why do we need tests?

- Quick feedback about bugs/errors

Why do we need tests?

- Quick feedback about bugs/errors
- Good code design

Why do we need tests?

- Quick feedback about bugs/errors
- Good code design
- Documentation for code behavior

Why do we need tests?

- Quick feedback about bugs/errors
- Good code design
- Documentation for code behavior
- Confident refactoring



Challenges in practicing TDD

Challenges in practicing TDD

- Lack of time
- Lack of motivation
- Lack of knowledge
- Lack of resources
- Lack of support
- Lack of feedback
- Lack of consistency
- Lack of patience
- Lack of discipline
- Lack of focus
- Lack of organization
- Lack of communication
- Lack of collaboration
- Lack of documentation
- Lack of testing
- Lack of debugging
- Lack of refactoring
- Lack of optimization
- Lack of performance
- Lack of security
- Lack of scalability
- Lack of maintainability
- Lack of flexibility
- Lack of adaptability
- Lack of innovation
- Lack of creativity
- Lack of problem-solving
- Lack of decision-making
- Lack of leadership
- Lack of management
- Lack of teamwork
- Lack of communication
- Lack of collaboration
- Lack of documentation
- Lack of testing
- Lack of debugging
- Lack of refactoring
- Lack of optimization
- Lack of performance
- Lack of security
- Lack of scalability
- Lack of maintainability
- Lack of flexibility
- Lack of adaptability
- Lack of innovation
- Lack of creativity
- Lack of problem-solving
- Lack of decision-making
- Lack of leadership
- Lack of management
- Lack of teamwork

Challenges in practicing TDD

Legacy code

- Legacy code is difficult to test.

Challenges in practicing TDD

Time

- Tests are code too, so they take time to write

Challenges in practicing TDD


Bad tests

- Fragile and obscure tests defeat the purpose of TDD

Challenges in practicing TDD

Bad tests

- Fragile and obscure tests defeat the purpose of TDD
- “Bad tests” is worse than no tests - time and effort wasted without results



Tools & concepts for writing maintainable tests

Test doubles

Test doubles

Just like stunt doubles



<https://people.com/movies/actors-and-their-stunt-doubles-photos>

Test doubles - dummies

Test doubles - dummies

- Dummies are like placeholders. Just to fill in parameters.

Test doubles - stubs

Test doubles - stubs

- Objects that return predefined data
- They usually don't hold state/respond to other actions besides the one they are created for

Test doubles - stubs

```
interface IUserRepository {...}
```

Test doubles - stubs

```
interface IUserRepository {...}  
  
...  
class UserRepository(private val userDao: UserDao) : IUserRepository {  
  
    override fun getUser(userId: Long): User {  
        return userDao.findById(userId = userId)  
    }  
  
}
```

Test doubles - stubs

```
interface IUserRepository {...}
```

```
...
```

```
class UserRepository(private val userDao: UserDao) : IUserRepository {
```

```
    override fun getUser(userId: Long): User {
```

```
        return userDao.findById(userId = userId)
```

```
    }
```

```
}
```

Test doubles - stubs

```
interface IUserRepository {...}  
  
...  
class UserRepositoryStub() : IUserRepository {  
  
    override fun getUser(userId: Long): User {  
        return User(userId = 1, email = "sf@sf.com")  
    }  
}
```

Stub returns a preconfigured user

Test doubles - fakes

Test doubles - fakes

- Similar to stubs, slightly more realistic
- Contain working implementation, but different from real version
- Typically models the behavior of the real class

Test doubles - fakes

```
interface UserDao {...}
```

Test doubles - fakes

```
interface UserDao {...}
...
class FakeUserDao() : UserDao {

    val users = mutableListOf<User>()

    override fun insert(user: User) {
        users.add(user)
    }

    override fun findById(userId: Long): User {
        return users.find { it.userId == userId }
            ?: throw Exception("user not found")
    }
}
```


Test doubles - fakes

```
interface UserDao {...}
```

```
...
```

```
class FakeUserDao() : UserDao {
```

```
    val users = mutableListOf<User>()
```

```
    override fun insert(user: User) {  
        users.add(user)  
    }
```

```
    override fun findById(userId: Long): User {  
        return users.find { it.userId == userId }  
            ?: throw Exception("user not found")  
    }
```

```
}
```

Fake dao uses a list instead
of a db

Test doubles - fakes

```
interface UserDao {...}
...
class FakeUserDao() : UserDao {

    val users = mutableListOf<User>()

    override fun insert(user: User) {
        users.add(user)
    }

    override fun findById(userId: Long): User {
        return users.find { it.userId == userId }
            ?: throw Exception("user not found")
    }
}
```

Fake dao supports the same operations

Test doubles - mocks

Test doubles - mocks

- Objects pre-programmed with expected outputs for given inputs
- Ability to record method calls and verify them
- Throw exceptions if wanted method is not called

Test doubles - mocks

@Test

```
fun userShouldBeReturnedFromDao() {  
  
    val dao: UserDao = mock()  
    whenever(dao.getUser(userId = 5)).thenReturn(User(5, "sf@sf.com"))  
    ...  
  
}
```

Test doubles - mocks

@Test

```
fun userShouldBeReturnedFromDao() {
```

```
    val dao: UserDao = mock()
```

```
    whenever(dao.getUser(userId = 5)).thenReturn(User(5, "sf@sf.com"))
```

```
    ...
```

```
}
```

Mock pre-programmed with
input/output

Test doubles - mocks

```
// SettingsPresenterTest.kt
```

```
@Test
```

```
fun clickingIconShouldOpenProfileScreen() {
```

```
    ...
```

```
    val view: SettingsContract.View = mock()
```

```
    val presenter = SettingsPresenter(view, userRepo)  
    presenter.profileIconClicked()
```

```
    verify(view).openProfileScreen()
```

```
}
```

Test doubles - mocks

```
// SettingsPresenterTest.kt
```

```
@Test
```

```
fun clickingIconShouldOpenProfileScreen() {  
    ...
```

```
    val view: SettingsContract.View = mock()
```

```
    val presenter = SettingsPresenter(view, userRepo)  
    presenter.profileIconClicked()
```

```
    verify(view).openProfileScreen()
```

```
}
```

Ability to verify interactions

Test doubles - spies

Test doubles - spies

- Hybrid between stubs, fakes and mocks

Test doubles - spies

- Hybrid between stubs, fakes and mocks
- They are as real as stubs, but also have the ability to record interactions like mocks.



What are maintainable tests?



What are maintainable tests?

Tests are maintainable when:

- Old tests do not break often

What are maintainable tests?

Tests are maintainable when:

- Old tests do not break often
- Old tests are easy to update

What are maintainable tests?


Tests are maintainable when:

- Old tests do not break often
- Old tests are easy to update
- Easy to add new tests


An abstract background featuring a network of thin, light purple lines connecting small dots, creating a complex, web-like structure. The dots and lines are more prominent in the upper half of the image, fading into a solid dark purple background towards the bottom. The overall aesthetic is modern and technological.

Writing maintainable tests

1. Use a good test specification system



1. Use a good test specification system



Also known as

Arrange - Act - Assert

Or

Given - When - Then

1. Use a good test specification system

@Test

```
fun scenarioX() {
```

```
    // Given the dependencies/behavior
```

```
    // When we act on the scenario
```

```
    // Then assert that expected behavior happens
```

```
}
```

2. Test behavior, not implementation details

2. Test behavior, not implementation details

- For methods that return value, you should care only about the output, not how it was calculated.

2. Test behavior, not implementation details

@Test

```
fun `get user details from cache if available`() {  
    ...  
    val userRepo = UserRepository(cacheSource, networkSource)  
  
    // given that a user exists in cache  
    whenever(cacheSource.getUser(5)).thenReturn(User(5, "sf@sf.com"))  
  
    // when we get user from repository  
    val user = userRepo.getUser(userId = 5)  
  
    // then verify that the cache source was called  
    verify(cacheSource).getUser(5)  
}
```

2. Test behavior, not implementation details

@Test

```
fun `get user details from cache if available`() {  
    ...  
    val userRepo = UserRepository(cacheSource, networkSource)  
  
    // given that a user exists in cache  
    whenever(cacheSource.getUser(5)).thenReturn(User(5, "sf@sf.com"))  
  
    // when we get user from repository  
    val user = userRepo.getUser(userId = 5)  
  
    // then verify that the cache source was called  
    verify(cacheSource).getUser(5)  
}
```

**This tests implementation
details**

2. Test behavior, not implementation details

@Test

```
fun `get user details from cache if available`() {  
    ...  
    // given that a user exists in cache  
    val cachedUser = User(5, "sf@sf.com")  
    whenever(cacheSource.getUser(5)).thenReturn(cachedUser)  
  
    // when we get user from repository  
    val returnedUser = userRepo.getUser(userId = 5)  
  
    // then verify that the returned user is the one from cache  
    assertEquals(cachedUser, returnedUser)  
}
```

2. Test behavior, not implementation details

@Test

```
fun `get user details from cache if available`() {  
    ...  
    // given that a user exists in cache  
    val cachedUser = User(5, "sf@sf.com")  
    whenever(cacheSource.getUser(5)).thenReturn(cachedUser)  
  
    // when we get user from repository  
    val returnedUser = userRepo.getUser(user)  
  
    // then verify that the returned user is the one from cache  
    assertEquals(cachedUser, returnedUser)  
}
```

This tests general behavior of this repository in this scenario.

2. Test behavior, not implementation details

- For methods that return value, one should care only about the output, not how it was calculated.
- For methods that do not return any value, verify interactions with dependencies

2. Test behavior, not implementation details

- For methods that return value, one should care only about the output, not how it was calculated.
- For methods that do not return any value, verify interactions with dependencies
- Be careful about overusing mocks.

3. Assert/verify only one thing per test

3. Assert/verify only one thing per test

In most cases, only one assert / verify should be done in each test.

3. Assert/verify only one thing per test

In most cases, only one assert / verify should be done in each test.

A test should fail for only 1 reason

3. Assert/verify only one thing per test

```
@Test
fun `enabling setting updates preference and sends tracking`() {
    ...
    // when user enables the setting
    viewModel.enableSetting()

    // then verify that we set preference
    verify(userPreference).enableSetting()

    // then verify that we send tracking
    verify(trackingUtils).trackUserEnabledSetting()
}
```


3. Assert/verify only one thing per test

```
@Test
fun `enabling setting updates preference and sends tracking`() {
    ...
    // when user enables the setting
    viewModel.enableSetting()

    // then verify that we set preference
    verify(userPreference).enableSetting()

    // then verify that we send tracking
    verify(trackingUtils).trackUserEnabledSetting()
}
```

3. Assert/verify only one thing per test

```
@Test
fun `enabling setting updates preference and sends tracking`() {
    ...
    // when user enables the setting
    viewModel.enableSetting()

    // then verify that we set preference
    verify(userPreference).enableSetting()

    // then verify that we send tracking
    verify(trackingUtils).trackUserEnabledSetting()
}
```

The use of “and” suggests that the test is testing more than one thing

3. Assert/verify only one thing per test

@Test

```
fun `enabling setting updates preference`() {  
    ...  
    // then verify that we set preference  
    verify(userPreference).enableSetting()  
}
```

@Test

```
fun `enabling setting posts tracking`() {  
    ...  
    // then verify that we post tracking  
    verify(trackingUtils).trackUserEnabledSetting()  
}
```



4. Use descriptive test names

4. Use descriptive test names

From the test name, we should be able to tell why the test failed.

4. Use descriptive test names

From the test name, we should be able to tell why the test failed.

```
@Test
fun `search field is updated correctly when user has search history`() {
    ...
}
```

4. Use descriptive test names

From the test name, we should be able to tell why the test failed.

```
@Test
fun `search field is updated correctly when user has search history`() {
    ...
}
```



4. Use descriptive test names

From the test name, we should be able to tell why the test failed.

```
@Test
fun `search field is updated correctly when user has search history`() {
    ...
}
```

```
@Test
fun `search field is updated with last search when user has search history`() {
    ...
}
```


4. Use descriptive test names

From the test name, we should be able to tell why the test failed.

```
@Test
fun `search field is updated correctly when user has search history`() {
    ...
}
```

```
@Test
fun `search field is updated with last search when user has search history`() {
    ...
}
```



4. Use descriptive test names

Kotlin allows us to use to write test function names with spaces

```
@Test
fun `welcome dialog should be shown on first log in`() {
    // test goes here
}
```

4. Use descriptive test names

JUnit 5 allows to specify a custom display name for the test

```
@Test
@DisplayName("welcome dialog should be shown on first log in")
void showWelcomeDialogOnFirstLogin() {
    // test goes here
}
```

5. More tips

- Avoid logic in your tests -> if/else, loops, etc.

5. More tips

- Avoid logic in your tests -> if/else, loops, etc.
- Avoid abstractions in tests

5. More tips

- Avoid logic in your tests -> if/else, loops, etc.
- Avoid abstractions in tests
- Be generous with comments

5. More tips

- Avoid logic in your tests -> if/else, loops, etc.
- Avoid abstractions in tests
- Be generous with comments
- Use parameterized tests

Resources

- <https://martinfowler.com/articles/mocksArentStubs.html>
- <http://xunitpatterns.com/>
- <https://testing.googleblog.com/search/label/TotT>
- <https://mtlynch.io/good-developers-bad-tests/>
- <https://jeroenmols.com/blog/2018/12/06/fixthetest/>

Thank you!



@segunfamisa