
Smart Logistics API Flows

The React application uses the Node REST API for accounts, operations, telemetry, and reports. The .NET Supply Chain API exposes a separate protected purchase-order path. Paths below are relative to the configured API origin; use the Vercel same-origin proxy in the hosted UI.

Session lifecycle



Session lifecycle · Open the diagram for a full-size view.

The production cookie is HttpOnly, Secure, and SameSite=None; development uses SameSite=Lax. Cookie-authenticated unsafe requests must carry an exact allowed Origin unless a bearer authorization header is used. The API also supports bearer authentication for appropriate callers. Password-reset tokens cannot authenticate ordinary requests. The frontend mock-auth adapter is a separate demonstration mode.

Authentication endpoints

Method	Path	Access / purpose
POST	`/api/auth/login`	Public, rate-limited credential check
POST	`/api/auth/register`	Public, rate-limited registration subject to server policy
GET	`/api/auth/me`	Signed-in account
POST	`/api/auth/logout`	Session termination
POST	`/api/auth/request-reset`	Rate-limited reset request
POST	`/api/auth/reset-password`	Expiring reset token and new password
PATCH	`/api/auth/profile/{id}`	Same-account profile update
POST	`/api/auth/change-password/{id}`	Same account; current password required


Real-account passwords must satisfy the API's 12–128 character validation. Reset links expire after 15 minutes. Completing a reset increments `password_reset_version`, invalidating earlier reset links. Reset versioning is not a claim that every previously issued access token is immediately revoked.

Operations, telemetry, and reports

Method	Endpoint	Permitted roles
GET	`/api/operations/shipments`	admin, engineer, analyst, user
GET	`/api/operations/orders`	admin, engineer, analyst
GET	`/api/operations/shipments/export/report`	admin, analyst
GET	`/api/operations/orders/export/report`	admin, analyst
GET	`/api/telemetry`	admin, engineer, analyst
POST	`/api/telemetry`	admin, engineer
POST	`/supply-chain/api/v1/orders`	admin, engineer, analyst; .NET purchase-order API through the gateway
GET	`/supply-chain/api/v1/orders/{id}`	admin, engineer, analyst; .NET purchase-order API through the gateway

The gateway removes the `/supply-chain` prefix before forwarding to Supply Chain. Direct private-service requests use `/api/v1/orders`; that unprefixed path on the public gateway routes to Node instead.

Telemetry ingestion




Telemetry ingestion · Open the diagram for a full-size view.

```
{"deviceId":"sensor-42","metricName":"temperature","metricValue":22.5}
```

Device and metric names must be non-empty and at most 100 characters. The metric value must be finite. The API supplies the stored timestamp. Unlike signed logistics events, this endpoint has no documented provider/event deduplication key; callers should account for retry duplicates.

Signed logistics provider flow



Signed logistics provider flow · Open the diagram for a full-size view.

Endpoint: `POST /api/integrations/logistics/{provider}/events`.

Headers: `X-IMSOP-Timestamp` (Unix seconds) and `X-IMSOP-Signature` (`sha256=` followed by the hexadecimal HMAC). Sign `timestamp + "." + rawBody` with the provider's private signing secret. Sign the exact transmitted bytes; reformatting JSON changes the signature. The signature window is five minutes. Use UTC event timestamps and stable provider event IDs.

```
{
  "eventId": "evt-example-001",
  "eventType": "shipment.location",
  "trackingNumber": "SHP-EXAMPLE-001",
  "status": "in_transit",
  "occurredAt": "2026-10-21T10:00:00.000Z",
  "origin": "Hamburg",
  "destination": "Berlin",
  "carrier": "Example Carrier",
  "transportMode": "road",
  "location": {"latitude": 52.52, "longitude": 13.405, "label": "Berlin"}
}
```


Errors and operational checks

Treat `401` as a missing or invalid session, `403` as an authorization denial, and validation errors as requests to correct rather than retry unchanged. A duplicate provider event is an accepted `202` response. On transient delivery failures, preserve the event ID when retrying. Report upstream failures clearly rather than substituting fabricated records.

`GET /health` reports liveness; `GET /ready` tests database readiness. Neither alone verifies provider delivery, email, mapping, all permissions, or the end-to-end frontend proxy. Release checks should cover both permitted and denied roles, operations reads, exports, and logout.

Source references

Backend API reference Route source Architecture and database model

Source review: 21 October 2026. Examples use synthetic records.