

Application Database Schema

The dashboard uses PostgreSQL with Drizzle ORM. The source of truth is drizzle/schema.ts; checked-in SQL migrations live in drizzle/.



Incident response and downtime records



Threshold-generated incidents use stable `SF-*` platform classifications. A vendor diagnostic code is stored as supplied when available. The engineer role provides technician assignment and resolution permissions; downtime is explicitly confirmed by the assigned engineer or administrator. A lost device connection does not automatically prove a factory outage. Existing records inferred by migration 0010 need operational review before use in downtime KPIs. Mean downtime-to-resolution uses only records with both downtime and resolution timestamps.

Table	Purpose
users	Local identity, bcrypt password hash in `password`, role, and sign-in timestamps. Never expose the hash in API responses.
account_requests	Pending registration or password-help requests, safe applicant details, review status, reviewer and time. Registration hashes are erased after approval or dismissal.
system_settings	Durable application-wide settings changed by administrators. `demo_data_enabled` controls whether demo rows are included; replicas refresh it without requiring a deployment.
devices	Connectivity devices. Registrations support gateways, edge devices, sensors, actuators and controllers. Includes status, location, firmware, and simulator marker. Migration `0015_melted_dragon_lord` adds `edge_device`.
assets	Equipment identity, manufacturer name/designation, separate required postal fields, article and order codes, optional serial/rated values, lifecycle, current AAS JSON, monotonic AAS revision, and simulator marker.
asset_devices	Asset-to-gateway protocol, endpoint, and tag/register mappings. Store credentials on the edge gateway, not in mappings.
asset_lifecycle_events	Actor, transition, timestamp, and engineering note audit history.
asset_versions	Append-only AAS snapshots keyed by asset and revision, with change note, actor, and SHA-256 integrity digest. Migration baseline rows have no digest because prior revisions were not recorded.
login_rate_limits	Hashed IP/email identifiers, fixed-window counters, and expiration timestamps shared across application replicas.
sensor_readings	Nullable measurements, AAS asset attribution, named signals, Unix epoch millisecond timestamps, and a unique ingestion digest for retry deduplication. Indexes cover asset/date and device/date queries.
alerts	Stable platform/vendor error code, severity/status, metric observation, acknowledging actor/time, assigned engineer/time, confirmed downtime start, resolving actor/time, and lifecycle timestamps. Per-source transaction locks deduplicate threshold incidents by device/asset/metric; query indexes cover status/date and assignee/status.
alert_thresholds	Enabled per-device warning and critical bands used to classify telemetry into incidents.
firmware_versions, ota_deployments	Firmware catalog metadata and legacy rollout rows. OTA is disabled; a rollout row is not proof that a device downloaded, verified, installed, or booted a release.

Connection and lifecycle ids are application-level relationships, not database-enforced foreign keys in the current schema. Oracle-hosted BaSyx owns separate storage in the Aiven `basyx` PostgreSQL database; it is not part of the Drizzle application schema. Demo rows are marked `isDemo`; startup and viewing never seed. An explicit local CLI creates isolated showcase fixtures. Administrators control visibility separately; shared identities see only approved demo records.

Review migration SQL before applying changes. Set DATABASE_URL to the intended database before running pnpm db:migrate. pnpm e2e uses its own disposable PostgreSQL container.

Durable incident notifications

Migration `0013_incident_notifications` adds `notification_inbox` and an alert trigger. In the alert transaction, new warning/critical incidents and critical escalations notify current engineers/admins; assignment changes notify new/previous assignees and admins; resolution notifies the assigned technician/admins. Migration `0016_vengeful_victor_mancha` makes the alert link nullable so the same durable queue can carry account-created welcome mail without inventing an incident. The trigger does not backfill historical incidents or emit duplicate messages on unrelated incident updates.

Each row belongs to one account, optionally links to an alert, and retains title/body, read time, email status, attempts, next attempt time, safe error summary and provider acceptance time. Foreign-key cascades remove rows when their account or associated alert is deleted. The delivery worker atomically claims due rows using a two-minute lease and retries after a crash. `accepted` means the provider accepted the request, not that the email reached a mailbox. Eight failed attempts become `failed`; an authorized owner may retry an incident message after correcting configuration. `unconfigured` and `no_recipient` remain visible for incident messages; account welcome rows are email-only and do not appear in the incident inbox.

The inbox is queryable only by its owner. Reads do not acknowledge/resolve the factory incident. Email-provider credentials, sender identity and recipient policy are runtime secrets/configuration, not editable browser notification settings. Plan retention/archive policies for both telemetry and inbox history before long-term production operation.

Migration `0014_account_email_identity` adds a case-insensitive unique email index. Null emails remain allowed for legacy identity records. Existing duplicate case-folded email addresses must be reconciled by an administrator before migration. Migration `0033_account_requests` adds a pending review queue; registration creates no user or session until an individual administrator verifies the applicant and approves a selected role. The review and assigned role are recorded in the audit trail. Migration `0034_password_reset_tokens` adds single-use recovery records tied to the account access version and email address. Only a SHA-256 token hash is stored in clear; a separate AES-GCM payload lets the existing mail worker deliver the link without exposing it through notification inbox APIs. Delivery clears that payload, while expiry, consumption and account changes prevent later redemption. Passwords and raw reset tokens are never included in account API responses. Administrator-assisted recovery remains available after identity verification.

Trusted observation and access additions

Migrations 0024–0028 add disabled/recovery/session-generation state, hashed session revocations, immutable selected-field passport publications, engineering conversion metadata, reviewed threshold units, bounded ingestion quarantine with continuing counters, incident snapshots and append-only review history,

acquired/received gateway observations, and a singleton authenticated worker-status receipt. Acquisition time, receipt time, current eligibility and evidence mode are separate fields.

Scopes precede sample selection and aggregation. Source values, units, conversion version and quality remain inspectable. Unitless thresholds require review. Passport publication is explicit and revocable. Runtime checks compare migration hashes with the applied ledger.

Factory layouts and FX/TSN diagnostics


Migration `0031_factory_layouts` adds `factory_layouts`: UUID identity, owning user (with delete cascade), `live`/`configured` scope, name, JSON document, positive version, archive time and creation/update timestamps. The owner/scope/update index supports bounded layout listing. Saves check the expected version to reject stale updates. Geometry is visualization state, separate from asset identity, physical commissioning and telemetry history. Shared demo layout drafts and editable sandbox changes stay browser-local; they are not rows in this table. See factory layouts and editable demo.

FX/TSN reports use the existing `system_settings` JSON storage under a hashed `network-diagnostics:` gateway key; there is no separate diagnostics migration or high-rate packet-history table. The stored envelope contains the validated report, import time and actor. Each registered operational gateway retains one newest report, and an older replacement is rejected. Responses are bounded to 128 gateways and report coverage and staleness explicitly. Demo scenarios are synthetic examples, separate from operational reports. See the diagnostics store and FX/TSN report contract.

Named factories and retained activity

Migration `0032_named_factories` adds shared `factories`, canonical membership/placements in `factory_items`, and `factory_activity`. Each member references exactly one existing asset or device; native equipment uses its backing asset. Membership has unique record identity and a per-factory, case-insensitive tag. Physical dimensions, position and rotation are validated before saving. Optimistic factory versions protect concurrent team edits.

Factory, membership and canonical inventory triggers record safe before/after values with a transaction-local authenticated actor. Connection changes omit endpoint/mapping values; related thresholds, incident state, model revisions/scenarios, OTA metadata and passport publication events use explicit safe projections. Ordinary UPDATE/DELETE against retained activity is rejected; no application edit/delete endpoint or automatic purge exists. Canonical inventory deletion cascades its placement while retaining factory history. Operational rows are not backfilled or renamed. Existing personal layout tables remain separate. Roles and workflow.


DEVICES
ASSETS
FACTORIES
uuid id PK
string name
float width
float depth
json zones
int version
placed_as
placed_as
contains
retains
FACTORY_ITEMS
string ref PK
uuid factory_id FK
int asset_id FK
int device_id FK
string inventory_tag
float x
float z
float rotation
float width
float depth
float height
FACTORY_ACTIVITY
bigint id PK
uuid factory_id FK
string change_set
int actor_id
string actor_name
string actor_role
string action
string target_ref
json before_value
json after_value
timestamp created_at