
Data Scientist Path - Python

Dataquest

By

DANIEL RUIZ

DECEMBER 2019

Prelude

This set of notes tracks my journey through DataQuests' *Data Scientist Path* module with Python. These notes are one of many that I have decided to polish and make available for anyone interested. One of the benefits of this series are having a compendium of definitions, examples and personal thoughts that I can always refer back to if I need a reminder on a particular topic. In addition, I find that this medium reduces the search time for specific definitions, theorems, examples etc and thus aids in reinforcing my own knowledge when frequented. The act of writing also works as a ritual in helping to encode information within my brain.

In these notes, I have provided many definitions and examples that I have encountered through the *Data Scientist* module on Dataquest. We will now outline their brief summaries:

- §1: **Data Analysis and Visualization** goes over the fundamentals of the Python Pandas and NumPy modules. I also provide details on Data Exploration and Visualization and how to do this in Python.

Contents

1	Data Analysis and Visualization	3
1.1	Pandas and NumPy Fundamentals	3
1.1.1	Introduction to NumPy	3
1.1.2	Boolean Indexing with NumPy	4
1.1.3	Introduction to Pandas	5
1.1.4	Exploring Data with Pandas: Fundamentals	9
1.1.5	Exploring Data with Pandas: Intermediate	10
1.1.6	Data Cleaning Basics	10
1.2	Exploratory Data Visualization	14
1.2.1	Line Charts	14
1.2.2	Multiple Plots	16
1.2.3	Bar and Scatter Plots	20
1.2.4	Histograms and Box Plots	23
1.2.5	Guided Project: Visualizing Majors Based on College Majors	25
1.3	Storytelling Through Data Visualization	27
1.3.1	Improving Plot Aesthetics	27
1.3.2	Conditional Plots	28
1.3.3	Visualizing Geographic Data	30
2	The Command Line	33
2.1	Elements of the Command Line	33
2.1.1	Introduction to the Command Line	33
3	Working with Data Sources	34
3.1	SQL Fundamentals	34
3.1.1	Introduction to SQL	34
3.1.2	Summary Statistics	36
3.1.3	Group Summary Statistics	38
3.1.4	Subqueries	41
3.1.5	Guided Project: Analyzing CIA Factbook Data Using SQL	42
3.2	SQL Intermediate: Table Relations and Joins	42
3.2.1	Joining Data in SQL	42
3.2.2	Intermediate Joins in SQL	44
3.2.3	Building and Organizing Complex Queries	49
3.2.4	Querying SQLite from Python	54
3.2.5	Guided Project: Answering Business Questions Using SQL	55
3.2.6	Table Relations and Normalization	62

1 Data Analysis and Visualization

1.1 Pandas and NumPy Fundamentals

1.1.1 Introduction to NumPy

- CSV: Open, Read etc
- `NdArray.shape`
- Selecting rows/columns from an array
- `NdArray` Arithmetic: Addition, Subtraction, Multiplication, Division
- `NdArray` Methods: Mean, min, max, sum
- Overlap with Numpy Functions and Methods

Definition 1.1: NumPy Library

NumPy is the fundamental package for scientific computing with Python. It contains among other things:

- A powerful N -dimensional array object.
- Sophisticated (broadcasting) functions.
- Tools for integrating C/C++ and Fortran code.
- Useful linear algebra, Fourier transform, and random number capabilities

Besides its obvious scientific uses, NumPy can also be used as an efficient multi-dimensional container of generic data. Arbitrary data-types can be defined. This allows NumPy to seamlessly and speedily integrate with a wide variety of databases.

Definition 1.2: NdArray

```
class numpy.ndarray(shape, dtype=float, buffer=None, offset=0, strides=None,
order=None)
```

An array object represents a multidimensional, homogeneous array of fixed-size items. An associated data-type object describes the format of each element in the array (its byte-order, how many bytes it occupies in memory, whether it is an integer, a floating point number, or something else, etc.)

Arrays should be constructed using `array`, `zeros` or `empty` (refer to the See Also section below). The parameters given here refer to a low-level method (`ndarray(...)`) for instantiating an array.

PARAMETERS

shape : tuple of ints
Shape of created array.

dtype : data-type, optional
Any object that can be interpreted as a numpy data type.

buffer: object exposing buffer interface, optional
Used to fill the array with data.

offset: int, optional
Offset of array data in buffer.

strides : tuple of ints, optional
Strides of data in memory.

order: {'C', 'F'}, optional
 Row-major (C-style) or column-major (Fortran-style) order.

Definition 1.3: SIMD

Single instruction, multiple data (SIMD) is a class of parallel computers in Flynn's taxonomy. It describes computers with multiple processing elements that perform the same operation on multiple data points simultaneously. Such machines exploit data level parallelism, but not concurrency: there are simultaneous (parallel) computations, but only a single process (instruction) at a given moment.

Definition 1.4: Slice Object

class slice(start, stop, step)

Return a slice object representing the set of indices specified by range(start, stop, step). The start and step arguments default to None. Slice objects have read-only data attributes start, stop and step which merely return the argument values (or their default).

Ndarray Indexing

Ndarrays can be indexed using the standard Python `x[obj]` syntax, where `x` is the array and `obj` the selection. There are three kinds of indexing available: field access, basic slicing, advanced indexing. Which one occurs depends on `obj`.

Basic slicing extends Python's basic concept of slicing to `N` dimensions. Basic slicing occurs when `obj` is a slice object (constructed by `start:stop:step` notation inside of brackets), an integer, or a tuple of slice objects and integers. Ellipsis and `newaxis` objects can be interspersed with these as well.

1.1.2 Boolean Indexing with NumPy

- `genfromtxt` function
- NaN (Not a number)
- Boolean Arrays
- Boolean Indexing
- Assigning values to NdArrays with Indexing

Definition 1.5: Numpy `genfromtxt()`

`numpy.genfromtxt(fname, dtype=<class 'float'>, comments='#', delimiter=None, skip_header=0)`

Load data from a text file, with missing values handled as specified.

Each line past the first `skip_header` lines is split at the delimiter character, and characters following the comments character are discarded. For further parameters and documentation, see [1].

PARAMETERS

fname: file, str, `pathlib.Path`, list of str, generator.

File, filename, list, or generator to read. If the filename extension is `gz` or `bz2`, the file is first decompressed. Note that generators must return byte strings in Python 3k. The strings in a list or produced by a generator

are treated as lines.

dtype: dtype, optional.

Data type of the resulting array. If None, the dtypes will be determined by the contents of each column, individually.

comments: str, optional.

The character used to indicate the start of a comment. All the characters occurring on a line after a comment are discarded.

delimiter: str, int, or sequence, optional.

The string used to separate values. By default, any consecutive whitespaces act as delimiter. An integer or sequence of integers can also be provided as width(s) of each field.

skip_header: int, optional.

The number of lines to skip at the beginning of the file.

Definition 1.6: Numpy nan

numpy.nan

Python constant. IEEE 754 floating point representation of Not a Number (NaN).

NaN and NAN are equivalent definitions of nan. Please use nan instead of NAN.

1.1.3 Introduction to Pandas

- Dataframe Methods: Head, Tail, Info, Loc
- Series object
- Selecting Columns/Rows in a Dataframe

Definition 1.7: Pandas Library

Pandas is an open source, BSD-licensed library providing high-performance, easy-to-use data structures and data analysis tools for the Python programming language. Some key features of the library include:

- A fast and efficient *DataFrame* object for data manipulation with integrated indexing.
- Tools for reading and writing data between in-memory data structures and different formats: CSV and text files, Microsoft Excel, SQL databases, and the fast *HDF5* format.
- Intelligent data alignment and integrated handling of missing data: gain automatic label-based alignment in computations and easily manipulate messy data into an orderly form.

Definition 1.8: Dataframe

class `pandas.DataFrame(data=None, index=None, columns=None, dtype=None, copy=False)`

Two-dimensional size-mutable, potentially heterogeneous tabular data structure with labeled axes (rows and columns). Arithmetic operations align on both row and column labels. Can be thought of as a dict-like container for Series objects. The primary pandas data structure. For a list of methods and further documentation, see [2].

PARAMETERS

data: ndarray (structured or homogeneous), Iterable, dict, or DataFrame.

Dict can contain Series, arrays, constants, or list-like objects.

Changed in version 0.23.0: If data is a dict, column order follows insertion-order for Python 3.6 and later.

Changed in version 0.25.0: If data is a list of dicts, column order follows insertion-order for Python 3.6 and later.

index: Index or array-like.

Index to use for resulting frame. Will default to RangeIndex if no indexing information part of input data and no index provided.

columns: Index or array-like.

Column labels to use for resulting frame. Will default to RangeIndex (0, 1, 2,..., n) if no column labels are provided.

dtype: dtype, default None.

Data type to force. Only a single dtype is allowed. If None, infer.

copy: boolean, default False.

Copy data from inputs. Only affects DataFrame / 2d ndarray input

Example 1.1: Pandas Dataframe

In vanilla numpy, our arrays must house elements of the same data type. Pandas extends this by allowing for multiple data types.




Figure 1.1: Pandas Dataframe

Definition 1.9: File-like Object (Pandas)

By file-like object, we refer to objects with a `read()` method, such as a file handler (e.g. via builtin `open` function) or `StringIO`.

Definition 1.10: Pandas read_csv()

```
pandas.read_csv(filepath_or_buffer, sep=',', delimiter=None, header='infer',
names=None, index_col=None)
```

Read a comma-separated values (csv) file into DataFrame. Also supports optionally iterating or breaking of the file into chunks. There are much more parameters available for this function, see documentation [3].

PARAMETERS

filepath_or_buffer : str, path object or file-like object.

Any valid string path is acceptable. The string could be a URL. Valid URL schemes include http, ftp, s3, and file. For file URLs, a host is expected. A local file could be: file://localhost/path/to/table.csv. If you want to pass in a path object, pandas accepts any os.PathLike.

sep: str, default ','.

Delimiter to use. If sep is None, the C engine cannot automatically detect the separator, but the Python parsing engine can, meaning the latter will be used and automatically detect the separator by Python's builtin sniffer tool, csv.Sniffer.

delimiter: str, default None. Alias for sep.

header: int, list of int, default 'infer'.

Row number(s) to use as the column names, and the start of the data. Default behavior is to infer the column names: if no names are passed the behavior is identical to header=0 and column names are inferred from the first line of the file, if column names are passed explicitly then the behavior is identical to header=None. Explicitly pass header=0 to be able to replace existing names. The header can be a list of integers that specify row locations for a multi-index on the columns e.g. [0,1,3]. Intervening rows that are not specified will be skipped (e.g. 2 in this example is skipped). Note that this parameter ignores commented lines and empty lines if skip_blank_lines=True, so header=0 denotes the first line of data rather than the first line of the file.

names: array-like, optional.

List of column names to use. If file contains no header row, then you should explicitly pass header=None. Duplicates in this list are not allowed.

index_col: int, str, sequence of int / str, or False, default None.

Column(s) to use as the row labels of the DataFrame, either given as string name or column index. If a sequence of int / str is given, a MultiIndex is used.

Definition 1.11: Series

```
class pandas.Series(data=None, index=None, dtype=None, name=None, copy=False,
fastpath=False)
```

One-dimensional ndarray with axis labels (including time series).

Labels need not be unique but must be a hashable type. The object supports both integer- and label-based indexing and provides a host of methods for performing operations involving the index. Statistical methods from ndarray have been overridden to automatically exclude missing data (currently represented as NaN). For further methods and documentation, see [4].

Operations between Series (+, -, /, *) align values based on their associated index values— they need not be the same length. The result index will be the sorted union of the two indexes.

PARAMETERS

data: array-like, Iterable, dict, or scalar value.

Contains data stored in Series.

Changed in version 0.23.0: If data is a dict, argument order is maintained for Python 3.6 and later.

index: array-like or Index (1d).

Values must be hashable and have the same length as data. Non-unique index values are allowed. Will default to RangeIndex (0, 1, 2, .., n) if not provided. If both a dict and index sequence are used, the index will override the keys found in the dict.

dtype: str, numpy.dtype, or ExtensionDtype, optional.

Data type for the output Series. If not specified, this will be inferred from data. See the user guide for more usages.

copy: bool, default False.

Copy input data.

Example 1.2: Dataframe Indexing

Let *df* denote a Dataframe. Then, we can select some subset of the dataframe's columns via the following syntax:

Select by Label	Explicit Syntax	Common Shorthand
Single column	<code>df.loc[:, "col1"]</code>	<code>df["col1"]</code>
List of columns	<code>df.loc[:, ["col1", "col7"]]</code>	<code>df[["col1", "col7"]]</code>
Slice of columns	<code>df.loc[:, "col1": "col4"]</code>	

Figure 1.2: Indexing a Dataframe's Columns

Example 1.3: Series Indexing

Let *s* denote a Series. Then, we can select some subset of the series rows via the following syntax:

Select by Label	Explicit Syntax	Shorthand Convention
Single item from series	<code>s.loc["item8"]</code>	<code>s["item8"]</code>
List of items from series	<code>s.loc[["item1", "item7"]]</code>	<code>s[["item1", "item7"]]</code>
Slice of items from series	<code>s.loc["item2": "item4"]</code>	<code>s["item2": "item4"]</code>

Figure 1.3: Series Item(s) Selection

Select by Label	Explicit Syntax	Shorthand Convention
Single column from dataframe	<code>df.loc[:, "col1"]</code>	<code>df["col1"]</code>
List of columns from dataframe	<code>df.loc[:, ["col1", "col7"]]</code>	<code>df[["col1", "col7"]]</code>
Slice of columns from dataframe	<code>df.loc[:, "col1": "col4"]</code>	
Single row from dataframe	<code>df.loc["row4"]</code>	
List of rows from dataframe	<code>df.loc[["row1", "row8"]]</code>	
Slice of rows from dataframe	<code>df.loc["row3": "row5"]</code>	<code>df["row3": "row5"]</code>
Single item from series	<code>s.loc["item8"]</code>	<code>s["item8"]</code>
List of items from series	<code>s.loc[["item1", "item7"]]</code>	<code>s[["item1", "item7"]]</code>
Slice of items from series	<code>s.loc["item2": "item4"]</code>	<code>s["item2": "item4"]</code>

Figure 1.4: Summary of Dataframe / Series Item Selection

1.1.4 Exploring Data with Pandas: Fundamentals

- Dataframe Assignment
- Boolean Indexing with Dataframes
- New Columns in Dataframes

Pandas Arithmetic with Series

Because pandas is designed to operate like NumPy, a lot of concepts and methods from Numpy are supported. Recall that one of the ways NumPy makes working with data easier is with vectorized operations, or operations applied to multiple data points at once.

Just like with NumPy, we can use any of the standard Python numeric operators with series, including:

- `series_a + series_b`: Addition
- `series_a - series_b`: Subtraction
- `series_a * series_b`: Multiplication (Element-wise)
- `series_a / series_b`: Division (Element-wise)

Definition 1.12: Method Chaining

Method chaining, also known as named parameter idiom, is a common syntax for invoking multiple method calls in object-oriented programming languages. Each method returns an object, allowing the calls to be chained together in a single statement without requiring variables to store the intermediate results.

Useful Dataframe Methods

- `df.describe()`: Generate descriptive statistics that summarize the central tendency, dispersion and shape of a dataset's distribution, excluding NaN values.
- `df.mean()`: Return the mean of the values for the requested axis.
- `df.rename()`: Alter axes labels. Function / dict values must be unique (1-to-1). Labels not contained in a dict / Series will be left as-is. Extra labels listed don't throw an error.

1.1.5 Exploring Data with Pandas: Intermediate

- Dataframe iloc indexing
- Boolean Operators; Combining Boolean Arrays
- Dataframe sort_values method

Select by integer position	Explicit Syntax	Shorthand Convention
Single column from dataframe	<code>df.iloc[:,3]</code>	
List of columns from dataframe	<code>df.iloc[:,[3,5,6]]</code>	
Slice of columns from dataframe	<code>df.iloc[:,3:7]</code>	
Single row from dataframe	<code>df.iloc[20]</code>	
List of rows from dataframe	<code>df.iloc[[0,3,8]]</code>	
Slice of rows from dataframe	<code>df.iloc[3:5]</code>	<code>df[3:5]</code>
Single items from series	<code>s.iloc[8]</code>	<code>s[8]</code>
List of item from series	<code>s.iloc[[2,8,1]]</code>	<code>s[[2,8,1]]</code>
Slice of items from series	<code>s.iloc[5:10]</code>	<code>s[5:10]</code>

Figure 1.5: Dataframe Integer Indexing

pandas	Python equivalent	Meaning
<code>a & b</code>	<code>a and b</code>	<code>True</code> if both <code>a</code> and <code>b</code> are <code>True</code> , else <code>False</code>
<code>a b</code>	<code>a or b</code>	<code>True</code> if either <code>a</code> or <code>b</code> is <code>True</code>
<code>~a</code>	<code>not a</code>	<code>True</code> if <code>a</code> is <code>False</code> , else <code>False</code>

Figure 1.6: Boolean Operators in Pandas

1.1.6 Data Cleaning Basics

- Data Encoding
- Dataframe Column Cleaning
- Dataframe Text to Numeric Cleaning
- Series.astype() method

Example 1.4: Cleaning Column Names

The column labels have a variety of upper and lowercase letters, as well as parentheses, which will make them harder to work with and read. We aim to clean our column labels by using several python string methods that will:

- Replace spaces with underscores.
- Remove special characters.
- Make all labels lowercase.
- Shorten any long column names. (Specifically changing ‘Operating System’ to ‘os’)

CB 1.1.1

```

import pandas as pd
laptops = pd.read_csv('laptops.csv', encoding='Latin-1')

def mr_clean(s):
    s = s.strip()
    s = s.replace("Operating_System", "os")
    s = s.replace("_", "-")
    s = s.replace('"', "")
    s = s.replace("(", "")
    sfinal = s.lower()

    return sfinal

new_columns = []
for col in laptops.columns:
    new_columns.append(mr_clean(col))

laptops.columns = new_columns

```




Figure 1.7: Text to Numeric Data Workflow

Example 1.5: Cleaning Text into Numerical Data

We now consider the column for *ram* data. Exploring this column, we find a clear pattern that all stored values are strings of integers with the character 'GB' at the end of the string:

```
['8GB', '16GB', '4GB', '8GB', '32GB', '4GB', '8GB', '2GB']
```

Naturally, we want to modify the data type stored in this column so that we can easily manipulate it numerically (such as computing statistics). To do this, we'll remove the GB from the string and then recast the remaining integer-string to an integer.

CB 1.1.2

```

laptops["ram"] = laptops["ram"].str.replace('GB', '').astype(int)
laptops.rename({"ram": "ram_gb"}, axis=1, inplace = True)

```

```
ram_gb_desc = laptops['ram_gb'].describe()
```

Example 1.6: Extracting Data from Text

```
print(laptops["cpu"].head())
```

0	Intel Core i5 2.3GHz
1	Intel Core i5 1.8GHz
2	Intel Core i5 7200U 2.5GHz
3	Intel Core i7 2.7GHz
4	Intel Core i5 3.1GHz

```
Name: cpu, dtype: object
```

Figure 1.8: First 5 entries of the Laptops['cpu'] column

We can observe that the CPU column in Figure 1.8 contains several pieces of information. They all appear to express the manufacturer and then model. Naturally, we want to break this apart so that we can organize it according to manufacturer and model. We use the fact spaces separate key pieces of information, allowing us to use the `split()` method to construct a list of strings. Selecting the first element out of this list would give us the manufacturer. Constructing a new `cpu_manufacturer` column is therefore achieved with the following code:

```
# CS 1.1.3 #

laptops["cpu_manufacturer"] = (laptops["cpu"]
                               .str.split()
                               .str[0]
                               )
```

The parenthesis are included so that one line of code can be expressed on multiple lines. This is done for readability purposes.

Definition 1.13: Pandas Series.map()

Series.map(self, arg, na_action=None)

Map values of Series according to input correspondence. Used for substituting each value in a Series with another value, that may be derived from a function, a dict or a Series. When `arg` is a dictionary, values in Series that are not in the dictionary (as keys) are converted to NaN. However, if the dictionary is a dict subclass that defines `__missing__` (i.e. provides a method for default values), then this default is used rather than NaN. For further documentation, see [5].

PARAMETERS

arg: function, dict, or Series.

Mapping correspondence.

na_action: None, 'ignore', default None.

If 'ignore', propagate NaN values, without passing them to the mapping correspondence.

Example 1.7: Who Needs A Map?

Let s be a series containing fruit names. We note that s currently contains incorrectly spelt fruit names. Printing the series gives us a display of that incorrect spelling.

```
# CS 1.1.4 #
```

```
print(s)
```

Output:

```
0      pair
1     oranje
2   bannana
3     oranje
4     oranje
5     oranje
dtype: object
```

Hence, to fix the problem seen in CS 1.1.4, we define a dictionary called *corrections* that will be fed into the argument of the `map()` method. For each string that appears in the dictionary argument, it will be mapped to the corresponding value of that dictionary argument. For instance, $pair \mapsto pear$.

```
# CS 1.1.5 #
```

```
corrections = {
    "pair": "pear",
    "oranje": "orange",
    "bananna": "banana"
}
s = s.map(corrections)
print(s)
```

Output:

```
0      pear
1     orange
2     banana
3     orange
4     orange
5     orange
dtype: object
```

Handling Null Values

In pandas, null values will be indicated by either **NaN** or **None**. There are a few main options for handling missing values:

- Remove any rows that have missing values.
- Remove any columns that have missing values.
- Fill the missing values with some other values.
- Leave the missing values as is.

The first two options are often used to prepare data for machine learning algorithms, which are unable to

be used with data that includes null values. We can use the `DataFrame.dropna()` method to remove or drop rows and columns with null values.

Example 1.8: Cleaning the Weight Column

In this example, the weights column is filled with strings of numeric values followed by a *kg* or *kgs* string that needs to be removed. After both these strings are removed, we recast the entries as floats.

CS 1.1.6

```
laptops["weight"] = laptops["weight"].str.replace("kg", "")
laptops["weight"] = laptops["weight"].str.replace("s", "").astype(float)

laptops.rename({"weight": "weight_kg"}, axis=1, inplace = True)

laptops.to_csv('laptops_cleaned.csv', index=False)
```

A subtlety in the above approach is that once *kg* is removed, all entries that contained 'Xkgs' now contain 'Xs' (X denotes a numeric value), hence why I use the `replace("s", "")` argument. In addition, I have to recast as float with the `astype()` method on the second line due to the weight column still containing 'Xs' entries after the first `replace()` call.

1.2 Exploratory Data Visualization

1.2.1 Line Charts

Definition 1.14: Data Visualization

Data visualization is the graphical representation of information and data. By using visual elements like charts, graphs, and maps, data visualization tools provide an accessible way to see and understand trends, outliers, and patterns in data.

Definition 1.15: Matplotlib Library

Matplotlib is a Python 2D plotting library which produces publication quality figures in a variety of hardcopy formats and interactive environments across platforms. Matplotlib can be used in Python scripts, the Python and IPython shells, the Jupyter notebook, web application servers, and four graphical user interface toolkits. The library allows us to:

- Quickly create common plots using high-level functions.
- Extensively tweak plots.
- Create new kinds of plots from the ground up.

Matplotlib tries to make easy things easy and hard things possible. You can generate plots, histograms, power spectra, bar charts, error charts, scatter plots, etc., with just a few lines of code.

When working with commonly used plots in matplotlib, the general workflow is:

- Create a plot using data.
- Customize the appearance of the plot.
- Display the plot.
- Edit and repeat until satisfied.

Definition 1.16: Pyplot Module*matplotlib.pyplot**Provides a MATLAB-like plotting framework.***Definition 1.17: Plot() Function***matplotlib.pyplot.plot(*args, scalex=True, scaley=True, data=None, **kwargs)**Plot y versus x as lines and/or markers.***PARAMETERS:****x, y:** array-like or scalar.*The horizontal / vertical coordinates of the data points. x values are optional and default to range(len(y)).**Commonly, these parameters are 1D arrays.**They can also be scalars, or two-dimensional (in that case, the columns represent separate data sets).***fmt:** str, optional.*A format string, e.g. 'ro' for red circles. See the Notes section for a full description of the format strings. Format strings are just an abbreviation for quickly setting basic line properties. All of these and more can also be controlled by keyword arguments.***data:** indexable object, optional.*An object with labelled data. If given, provide the label names to plot in x and y.***Returns:***lines - A list of Line2D objects representing the plotted data.***Example 1.9: Plotting Monthly Unemployment Trends in 1948**

CB 1.2.1

```
import matplotlib.pyplot as plt
import pandas as pd
```

```
unrate = pd.read_csv('unrate.csv')
```

```
plt.plot(unrate['DATE'].head(12), unrate['VALUE'].head(12))
plt.xticks(rotation = 90)
plt.xlabel("Month")
plt.ylabel("Unemployment_Rate")
plt.title("Monthly_Unemployment_Trends,_1948")
plt.show()
```

Output:




Figure 1.9: Monthly Unemployment Trends, 1948

One can notice that we didn't assign the plot in Example 1.9 to a variable and then call a method on the variable to display it. We instead called the functions `plot()`, `show()` on the pyplot module directly.

This is because every time we call a pyplot function, the module maintains and updates the plot internally (also known as state). When we call `show()`, the plot is displayed and the internal state is destroyed. While this workflow isn't ideal when we're writing functions that create plots on a repeated basis as part of a larger application, it's useful when exploring data.

1.2.2 Multiple Plots

When we want to work with multiple plots, however, we need to be more explicit about which plot we're making changes to. This means we need to understand the matplotlib classes that pyplot uses internally to maintain state so we can interact with them directly. Let's first start by understanding what pyplot was automatically storing under the hood when we create a single plot:

- A container for all plots was created (returned as a Figure object)
- A container for the plot was positioned on a grid (the plot returned as an Axes object)
- Visual symbols were added to the plot (using the Axes methods)

Definition 1.18: Pyplot Figure Function

`matplotlib.pyplot.figure(num=None, figsize=None, dpi=None, facecolor=None, frameon=True, clear=False, **kwargs)`

Create a new figure. For further documentation, see [6].

PARAMETERS:

num: integer or string, optional, default: None.

If not provided, a new figure will be created, and the figure number will be incremented. The figure object holds this number in a number attribute. If num is provided, and a figure with this id already exists, make it active, and returns a reference to it. If this figure does not exist, create it and returns it. If num is a string, the window title will be set to this figure's num.

figsize: (float, float), optional, default: None.

Width, height in inches. If not provided, defaults to `rcParams["figure.figsize"] = [6.4, 4.8]`.

dpi: integer, optional, default: None.

Resolution of the figure. If not provided, defaults to `rcParams["figure.dpi"] = 100.0 = 100`.

facecolor: color spec.

The background color. If not provided, defaults to `rcParams["figure.facecolor"] = 'white' = 'w'`.

frameon: bool, optional, default: True.

If False, suppress drawing the figure frame.

clear: bool, optional, default: False

If True and the figure already exists, then it is cleared.

Definition 1.19: Matplotlib Axes Class

```
class matplotlib.axes.Axes(fig, rect, facecolor=None, frameon=True, sharex=None, sharey=None, label="",
xscale=None, yscale=None, **kwargs)
```

The Axes contains most of the figure elements: Axis, Tick, Line2D, Text, Polygon, etc., and sets the coordinate system.

Build an axes in a figure. For further documentation, see [7].

PARAMETERS:

fig: Figure.

The axes is build in the Figure fig.

rect: [left, bottom, width, height]

The axes is build in the rectangle rect. rect is in Figure coordinates.

sharex, sharey: Axes, optional.

The x or y axis is shared with the x or y axis in the input Axes.

frameon: bool, optional.

True means that the axes frame is visible.

Useful Matplotlib Methods

- `fig = plt.figure(figsize=(width, height))`
- `axes_obj = fig.add_subplot(nrows, ncols, plot_number)`

Example 1.10: Plotting Monthly Unemployment Trends from 1948-1952 on Subplots

```
# CB 1.2.2 #
```

```
import matplotlib.pyplot as plt
import pandas as pd
```

```

unrate = pd.read_csv('unrate.csv')

fig = plt.figure(figsize=(12,12))

axes = []
height = 5

for axnum in range(height):
    axes.append(fig.add_subplot(height,1,axnum+1))
    axes[axnum].plot(unrate['DATE'][axnum*12:(axnum+1)*12],
                     unrate['VALUE'][axnum*12:(axnum+1)*12])

plt.show()

```

Output:




Figure 1.10: Monthly Unemployment Trends, 1948-1952 Subplots

Example 1.11: Plotting Monthly Unemployment Trends from 1948-1952 on Base Plot

```
# CB 1.2.3 #
```

```
import matplotlib.pyplot as plt
```

```
import pandas as pd
```

```
unrate = pd.read_csv('unrate.csv')
```

```
fig = plt.figure(figsize=(10,6))
```

```
colors = ['red', 'blue', 'green', 'orange', 'black']
```

```
for i in range(5):
```

```
    start_index = i*12
```

```
    end_index = (i+1)*12
```

```
    subset = unrate[start_index:end_index]
```

```
    label = str(1948 + i)
```

```
    plt.plot(subset['MONIH'], subset['VALUE'], c=colors[i], label=label)
```

```
plt.title("Monthly Unemployment Trends, 1948-1952")
```

```
plt.xlabel("Month, Integer")
```

```
plt.ylabel("Unemployment Rate, Percent")
```

```
plt.legend(loc='upper left')
```

```
plt.show()
```

Output:




Figure 1.11: Monthly Unemployment Trends, 1948-1952

1.2.3 Bar and Scatter Plots

Example 1.12: Vertical Bar Plot for Age of Ultron Ratings

CB 1.2.4

```
import matplotlib.pyplot as plt
```

```
num_cols = ['RT_user_norm', 'Metacritic_user_norm', 'IMDB_norm',
            'Fandango_Ratingvalue', 'Fandango_Stars']
```

```
bar_heights = norm_reviews[num_cols].iloc[0].values
```

```
bar_positions = arange(5) + 0.75
```

```
tick_positions = range(1,6)
```

```
fig, ax = plt.subplots()
```

```
ax.bar(bar_positions, bar_heights, 0.5)
```

```
ax.set_xticks(tick_positions)
```

```
ax.set_xticklabels(num_cols, rotation=90)
```

```
ax.set_xlabel("Rating_Source")
```

```
ax.set_ylabel("Average_Rating")
```

```
ax.set_title("Average_User_Rating_For_Avengers:_Age_of_Ultron_(2015)")
```

```
plt.show()
```

Output:




Figure 1.12: Vertical Bar Plot for Age of Ultron Ratings

Example 1.13: Horizontal Bar Plot for Age of Ultron Ratings

```
# CB 1.2.5 #
```

```
import matplotlib.pyplot as plt
```

```
from numpy import arange
```

```
num_cols = ['RT_user_norm', 'Metacritic_user_nom', 'IMDB_norm',  
'Fandango_Ratingvalue', 'Fandango_Stars']
```

```
bar_widths = norm_reviews[num_cols].iloc[0].values
```

```
bar_positions = arange(5) + 0.75
```

```
tick_positions = range(1,6)
```

```
fig, ax = plt.subplots()
```

```
ax.barh(bar_positions, bar_widths, 0.5)
```

```
ax.set_yticks(tick_positions)
```

```
ax.set_yticklabels(num_cols)
```

```
ax.set_ylabel("Rating_Source")
```

```
ax.set_xlabel("Average_Rating")
```

```
ax.set_title("Average_User_Rating_For_Avengers:_Age_of_Ultron_(2015)")
```

```
plt.show()
```

Output:




Figure 1.13: Horizontal Bar Plot for Age of Ultron Ratings

Example 1.14: Scatter Plots for Movie Rating Sites vs Fandango

```
# CB 1.2.6 #
```

```
import matplotlib.pyplot as plt
```

```
fig = plt.figure(figsize=(5,10))
```

```
ax1 = fig.add_subplot(3,1,1)
```

```

ax2 = fig.add_subplot(3,1,2)
ax3 = fig.add_subplot(3,1,3)

axes = [ax1,ax2,ax3]

review_cols = ["RT_user_norm", "Metacritic_user_norm", "IMDB_norm"]
labels = ["Rotten_Tomatoes", "Metacritic", "IMDB"]

for i in range(3):
    axes[i].scatter(norm_reviews["Fandango_Ratingvalue"],
                    norm_reviews[review_cols[i]])
    axes[i].set_xlabel("Fandango")
    axes[i].set_ylabel(labels[i])
    axes[i].set_xlim(0,5)
    axes[i].set_ylim(0,5)

plt.show()

```

Output:




Figure 1.14: Scatter Plots among Movie Rating Sites

1.2.4 Histograms and Box Plots

Example 1.15: Movie Rating Distribution Histograms

CB 1.2.7

```
import matplotlib.pyplot as plt

fig = plt.figure(figsize=(5,20))
ax1 = fig.add_subplot(4,1,1)
ax2 = fig.add_subplot(4,1,2)
ax3 = fig.add_subplot(4,1,3)
ax4 = fig.add_subplot(4,1,4)
axes = [ax1, ax2, ax3, ax4]

col_titles = ["Fandango", "Rotten_Tomatoes", "Metacritic", "IMDB"]
col_names = ['Fandango_Ratingvalue', 'RT_user_norm', 'Metacritic_user_nom',
'IMDB_norm']

for i in range(4):
    axes[i].hist(norm_reviews[col_names[i]], bins=20, range=(0,5))
    axes[i].set_title("Distribution_of_" + col_titles[i] + "_Ratings")
    axes[i].set_ylim(0,50)

plt.show()
```

Output:




Figure 1.15: Movie Distribution Histogram Ratings

! For the sake of visual aesthetic, I've placed the plots horizontally. They are normally outputted vertically^a in the same order presented above (Fandango on top and IMDB on bottom).

^aIn the same way as Figure 1.14.

Box Plot Quartiles

In descriptive statistics, a box plot or boxplot is a method for graphically depicting groups of numerical data through their quartiles. Box plots may also have lines extending vertically from the boxes (whiskers) indicating variability outside the upper and lower quartiles, hence the terms box-and-whisker plot and box-and-whisker diagram.




Figure 1.16: Box Plot Quartiles

We have graphically depicted an example of such a box plot in Figure 1.16 for the movie rating website Rotten Tomatoes.

Example 1.16: Movie Rating Box Plots

```
# CB 1.2.8 #

num_cols = ['RT_user_norm', 'Metacritic_user_nom', 'IMDB_norm',
            'Fandango_Ratingvalue']

fig, ax = plt.subplots()

ax.boxplot(norm_reviews[num_cols].values)
ax.set_xticklabels(num_cols, rotation = 90)
ax.set_ylim(0,5)

plt.show()
```




Figure 1.17: Movie Distribution Ratings Box Plot

1.2.5 Guided Project: Visualizing Majors Based on College Majors

Pandas has many methods for quickly generating common plots from data in DataFrames. Like pyplot, the plotting functionality in pandas is a wrapper for matplotlib. This means we can customize the plots when necessary by accessing the underlying Figure, Axes, and other matplotlib objects. For further documentation on visualization in Pandas, see [8].

Example 1.17: Pandas Plot on Male Dominated Undergrad Majors

CB 1.2.9

```
import pandas as pd
import matplotlib.pyplot as plt

recent_grads = pd.read_csv('recent_grads.csv')
male_dominant = recent_grads[recent_grads['ShareWomen'] < 0.25]
male_dominant.plot(x = 'Major', y = 'ShareWomen',
title = 'Male-Dominated Majors', kind = 'bar', legend = None)
```

Output:




Figure 1.18: Male Dominated Majors

Example 1.18: Scatter Matrix Plots

CB 1.2.10

```
import pandas as pd
import matplotlib.pyplot as plt
```

```
recent_grads = pd.read_csv('recent_grads.csv')
scatter_matrix(recent_grads[['Sample_size', 'Median']], figsize=(10,10))
```

Output:




Figure 1.19: Scatter Matrix with 'Sample Size', 'Median' Columns

1.3 Storytelling Through Data Visualization

1.3.1 Improving Plot Aesthetics

Definition 1.20: Chartjunk

Chartjunk refers to all visual elements in charts and graphs that are not necessary to comprehend the information represented on the graph, or that distract the viewer from this information.

Markings and visual elements can be called chartjunk if they are not part of the minimum set of visuals necessary to communicate the information understandably. Examples of unnecessary elements that might be called chartjunk include heavy or dark grid lines, unnecessary text, inappropriately complex or gimmicky font faces, ornamented chart axes, and display frames, pictures, backgrounds or icons within data graphs, ornamental shading and unnecessary dimensions.

Example 1.19: Spine and Tick Removal

With the axis tick marks gone, the data-ink ratio is improved and the chart looks much cleaner. In addition, the spines in the chart now are no longer necessary. When we're exploring data, the spines and the ticks complement each other to help us refer back to specific data points or ranges. When a viewer is viewing our chart and trying to understand the insight we're presenting, the ticks and spines can get in the way.

```
# CB 1.3.1 #

import pandas as pd
import matplotlib.pyplot as plt

fig, ax = plt.subplots()
ax.plot(women_degrees['Year'], women_degrees['Biology'], label='Women')
ax.plot(women_degrees['Year'], 100-women_degrees['Biology'], label='Men')
ax.tick_params(bottom="off", top="off", left="off", right="off")
ax.spines["right"].set_visible(False)
ax.spines["left"].set_visible(False)
ax.spines["top"].set_visible(False)
ax.spines["bottom"].set_visible(False)

ax.legend(loc='upper_right')
ax.set_title('Percentage of Biology Degrees Awarded By Gender')
plt.show()
```




Figure 1.20: Percentage of Women Biology Degree Holders over Time

1.3.2 Conditional Plots

Definition 1.21: Seaborn Module

Seaborn is a Python data visualization library based on matplotlib. It provides a high-level interface for drawing attractive and informative statistical graphics. Seaborn works similarly to the pyplot module from matplotlib. We primarily use seaborn interactively, by calling functions in its top level namespace. Like the pyplot module from matplotlib, seaborn creates a matplotlib figure or adds to the current, existing figure each time we generate a plot.

Example 1.20: Seaborn

Under the hood, seaborn creates a histogram using matplotlib, scales the axes values, and styles it. In addition, seaborn uses a technique called kernel density estimation [9], or KDE for short, to create a smoothed line chart over the histogram.

```
# CB 1.3.2 #
```

```
import seaborn as sns
import matplotlib.pyplot as plt
sns.distplot(titanic["Age"])
plt.show()
```




Figure 1.21: Seaborn Plot

Example 1.21: Seaborn KDE

If we wish to only view the KDE plot in seaborn, one can use the `kdeplot()` function. In addition, shading the area underneath the KDE function can be accomplished by setting the `shade` parameter to `True`.

```
sns.kdeplot(titanic['Age'], shade = True)
plt.xlabel("Age")
```




Figure 1.22: KDEplot with Shade

Example 1.22: Seaborn Despinning and FacetGrid

The Seaborn `despine` function allows us to remove the spines from the graph. By default it will remove the top and right spines, but to remove left and bottom, we have to set these parameters to `True`.

The `FacetGrid` function allows us to display multiple graphs at the same time through conditional relationships. Along the row and column axes of the graph position in this grid, we can specify how to subset the titanic dataframe. In this example, we subset unique values for 'Pclass' along the column axis and unique values for 'Survived' along the row axis. In addition, we can also plot multiple figures on the same subplot with the `hue` parameter, further allowing us to subset unique values of 'Sex'.

CS 1.3.3

```
g = sns.FacetGrid(titanic, col="Pclass", row="Survived", hue="Sex", size=3)
g.map(sns.kdeplot, "Age", shade=True).add_legend()
sns.despine(left=True, bottom=True)
plt.show()
```




Figure 1.23: Seaborn FacetGrid with Despinning

1.3.3 Visualizing Geographic Data**Definition 1.22: Basemap**

`class mpl_toolkits.basemap.Basemap`

Sets up a `basemap[10]` with specified map projection. and creates the coastline data structures in map projection coordinates.

Calling a `Basemap` class instance with the arguments `lon`, `lat` will convert `lon/lat` (in degrees) to `x/y` map projection coordinates (in meters). The inverse transformation is done if the optional keyword `inverse` is set to `True`.

Example 1.23: Basemap Visualization with Airline Routes Data

```
# CB 1.3.4 #

import matplotlib.pyplot as plt
from mpl_toolkits.basemap import Basemap

fig, ax = plt.subplots(figsize=(15, 20))
ax.set_title('Scaled Up Earth With Coastlines')
m = Basemap(projection='merc', llcrnrlat=-80, urcrnrlat=80, llcrnrlon=-180,
            urcrnrlon=180)
longitudes = airports["longitude"].tolist()
latitudes = airports["latitude"].tolist()
x, y = m(longitudes, latitudes)
m.scatter(x, y, s=1)
m.drawcoastlines()
plt.show()
```




Figure 1.24: Geographic Data With Basemap

Example 1.24: Great Circles for Airline Flights

```
# CB 1.3.5 #

fig, ax = plt.subplots(figsize=(15, 20))
m = Basemap(projection='merc', llcrnrlat=-80, urcrnrlat=80, llcrnrlon=-180,
```



```

urcrnrlon=180)
m.drawcoastlines()

# Start writing your solution below this line

def create_great_circles(dataframe):

    for index, row in dataframe.iterrows():
        if abs(row['end_lat'] - row['start_lat']) < 180 and
            abs(row['end_lon'] - row['start_lon']) < 180:
            m.drawgreatcircle(row['start_lon'], row['start_lat'],
                              row['end_lon'], row['end_lat'])
        else:
            continue

dfw = geo_routes[geo_routes['source']=='DFW']

create_great_circles(dfw)
plt.show()

```




Figure 1.25: Great Circles for Airline Flights

2 The Command Line

2.1 Elements of the Command Line

2.1.1 Introduction to the Command Line

Definition 2.1: Command Line Interface

A *Command Line Interface (CLI)* is a text only interface through which users interact with computers by typing text instructions in a console (or terminal), using specific syntax.

As technology evolved and computers became ubiquitous, terminals were emulated within GUIs, giving rise to terminal emulators (also terminal window or just terminal).

Definition 2.2: Commands

Instructions sent to the CLI are called *commands* which, once input, are interpreted by a type of program called a *shell* or *command language interpreter*, and then run by your machine. Some of the most popular shells are Bash, Z shell, KornShell, Command Prompt and Windows PowerShell.

Definition 2.3: Command Parameters

The general syntax for commands are:

```
utility_name parameter1 parameter2 ... parameterN
```

By definition, a parameter is either an *option* or an *argument*. An **option** is a string of symbols that modifies the behavior of the command and it always starts with a dash (-). Other possible names for this parameter are *flag* and *switch*, but depending on who you ask they might not always be interchangeable. An **argument** — or *operand* — is an object upon which the command acts. The **utility** (also *command* or *program*) is the first item in the instruction.

3 Working with Data Sources

3.1 SQL Fundamentals

3.1.1 Introduction to SQL

Definition 3.1: SQL

SQL (Structured Query Language) is a domain-specific language used in programming and designed for managing data held in a relational database management system (RDBMS), or for stream processing in a relational data stream management system (RDSMS). It is particularly useful in handling structured data, i.e. data incorporating relations among entities and variables.

Definition 3.2: RDBMS

Connolly and Begg define Database Management System (DBMS) as a “software system that enables users to define, create, maintain and control access to the database”. RDBMS is an extension of that acronym that is sometimes used when the underlying database is relational.

SQL Comparison Operators

We can use the following comparison operators in SQL:

- <: Less than
- <=: Less than or equal to
- >: Greater than
- >=: Greater than or equal to
- =: Equal to
- !=: Not equal to

SQL Logical Operators

We can use the following logical operators in SQL [11]:

Operator	Result
ALL	TRUE if all of the subquery values meet the condition.
AND	TRUE if all the conditions separated by AND is TRUE.
ANY	TRUE if any of the subquery values meet the condition.
BETWEEN	TRUE if any of the subquery values meet the condition.
EXISTS	TRUE if the subquery returns one or more records.
IN	TRUE if the operand is equal to one of a list of expressions.
LIKE	TRUE if the operand matches a pattern.
NOT	Displays a record if the condition(s) is NOT TRUE.
OR	TRUE if any of the conditions separated by OR is TRUE.
SOME	TRUE if any of the subquery values meet the condition.

Definition 3.3: SELECT Operation

The *SELECT* statement is used to select data from a database. The data returned is stored in a result table, called the result-set.

If you wish to select columns *column1*, *column2*,..., the syntax is given by:

```
SELECT column1, column2, ...
FROM table_name;
```

If you wish to select all columns from *table_name*, you can use *:

```
SELECT * FROM table_name
```

Definition 3.4: WHERE Operation

The *WHERE* clause is used to filter records. The *WHERE* clause is used to extract only those records that fulfill a specified condition.

```
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

Definition 3.5: ORDER BY Operation

The *ORDER BY* keyword is used to sort the result-set in ascending or descending order.

```
SELECT column1, column2, ...
FROM table_name
ORDER BY column1, column2, ... ASC|DESC;
```

Example 3.1: Select, Where and Order

In this example, we have a table named “recent_grads”, from which we want to display particular rows and columns matching our criteria. We only want to display the *Major*, *ShareWomen* and *Unemployment_rate* column so we use the *SELECT* operation to do so. We use *FROM* to indicate the table and *WHERE* to establish the two desired criterions. We want to display rows where women held at least 30% of student population and had an unemployment rate less than 10%. Finally, when we display our information, we want to order it according to the *ShareWomen* values, descending.

```
# CB 1.4.1 #
```

```
SELECT Major, ShareWomen, Unemployment_rate
FROM recent_grads
WHERE ShareWomen > 0.3 AND Unemployment_rate < 0.1
ORDER BY ShareWomen DESC
```

Output
[121 rows x 3 columns]

Major	ShareWomen	Unemployment_rate
EARLY CHILDHOOD EDUCATION	0.9679981190000001	0.040104981
MATHEMATICS AND COMPUTER SCIENCE	0.927807246	0
ELEMENTARY EDUCATION	0.923745479	0.046585715
ANIMAL SCIENCES	0.91093257	0.05086249900000005
PHYSIOLOGY	0.9066773370000001	0.06916280000000001
MISCELLANEOUS PSYCHOLOGY	0.90558993	0.05190783
HUMAN SERVICES AND COMMUNITY ORGANIZA...	0.9040745440000001	0.037819026
NURSING	0.896018988	0.04486272400000001
GEOSCIENCES	0.881293889	0.024373731000000003
MASS MEDIA	0.8772275279999999	0.089836827
COGNITIVE SCIENCE AND BIOPSYCHOLOGY	0.854523227	0.075236167
ART HISTORY AND CRITICISM	0.845934379	0.060298284
EDUCATIONAL PSYCHOLOGY	0.8170988090000001	0.065112187
GENERAL EDUCATION	0.8128766059999999	0.057359929000000004

Figure 3.1: Displaying the result of Query CB 1.4.1

3.1.2 Summary Statistics

Definition 3.6: Aggregate Function

Aggregate functions are applied over columns of values and return a single value. `MIN()` and `MAX()`, for example, calculate and return the minimum and maximum values in a column.

Aggregate Functions [12]

Aggregate Function	Description
AVG	The <code>AVG()</code> aggregate function calculates the average of non-NULL values in a set.
CHECKSUM_AGG	The <code>CHECKSUM_AGG()</code> function calculates a checksum value based on a group of rows.
COUNT	The <code>COUNT()</code> aggregate function returns the number of rows in a group, including rows with NULL values.
COUNT_BIG	The <code>COUNT_BIG()</code> aggregate function returns the number of rows (with <code>BIGINT</code> data type) in a group, including rows with NULL values.
MAX	The <code>MAX()</code> aggregate function returns the highest value (maximum) in a set of non-NULL values.
MIN	The <code>MIN()</code> aggregate function returns the lowest value (minimum) in a set of non-NULL values.
STDEV	The <code>STDEV()</code> function returns the statistical standard deviation of all values provided in the expression based on a sample of the data population.
STDEVP	The <code>STDEVP()</code> function also returns the standard deviation for all values in the provided expression, but does so based on the entire data population.
SUM	The <code>SUM()</code> aggregate function returns the summation of all non-NULL values a set.
VAR	The <code>VAR()</code> function returns the statistical variance of values in an expression based on a sample of the specified population.
VARP	The <code>VARP()</code> function returns the statistical variance of values in an expression but does so based on the entire data population.

Definition 3.7: DISTINCT Statement

The `SELECT DISTINCT` statement is used to return only distinct (different) values. Inside a table, a column often contains many duplicate values; and sometimes you only want to list the different (distinct) values.

```
SELECT DISTINCT column1, column2, ...
FROM table_name;
```

Definition 3.8: SQL Alias

SQL aliases are used to give a table, or a column in a table, a temporary name. Aliases are often used to make column names more readable. An alias only exists for the duration of the query.

```
SELECT column_name AS alias_name
FROM table_name;
```


You may also drop the `AS` keyword so that the syntax can be expressed by

```
SELECT column_name alias_name
FROM table_name;
```

Example 3.2: Counting Distinct Values among Columns

```
# CB 1.4.2 #
```

```
SELECT COUNT(DISTINCT(Major)) "unique_majors",
COUNT(DISTINCT(Major_category)) "unique_major_categories",
COUNT(DISTINCT(Major_code)) "unique_major_codes"
FROM recent_grads
```



unique_majors	unique_major_categories	unique_major_codes
173	16	173

Figure 3.2: The Number of Unique Values in Major, Major Category and Major Code Columns

Example 3.3: Displaying Ordered Quartile Spread among Columns

```
# CB 1.4.3 #
```

```
SELECT Major, Major_category, P75th - P25th quartile_spread FROM recent_grads
ORDER BY quartile_spread LIMIT 10
```

Output
[10 rows x 3 columns]

Major	Major_category	quartile_spread
MILITARY TECHNOLOGIES	Industrial Arts & Consumer Services	0
SCHOOL STUDENT COUNSELING	Education	2000
LIBRARY SCIENCE	Education	2000
COURT REPORTING	Law & Public Policy	4000
PHARMACOLOGY	Biology & Life Science	5000
EDUCATIONAL ADMINISTRATION AND SUPERV...	Education	6000
COUNSELING PSYCHOLOGY	Psychology & Social Work	6800
SPECIAL NEEDS EDUCATION	Education	10000
MATHEMATICS TEACHER EDUCATION	Education	10000
SOCIAL WORK	Psychology & Social Work	10000

Figure 3.3: Quartile Spread for Majors

3.1.3 Group Summary Statistics

Definition 3.9: PRAGMA TABLE INFO

The `table.info` pragma is used to query information about a specific table. The result set will contain one row for each column in the table. It will display information such as the type of objects stored in the columns, Null values and meanings.

Definition 3.10: GROUP BY Statement

The `GROUP BY` statement groups rows that have the same values into summary rows, like “find the number of customers in each country”. The `GROUP BY` statement is often used with aggregate functions (`COUNT`, `MAX`, `MIN`, `SUM`, `AVG`) to group the result-set by one or more columns.

```
SELECT column_name(s)
FROM table_name
WHERE condition
GROUP BY column_name(s)
ORDER BY column_name(s);
```

Example 3.4: GROUP BY in Action

The `GROUP BY` statement works by partitioning the relevant column into its unique entries, then performing the desired operation on each group.




Figure 3.4: Grouping Operation

In this example, we aim to compute the average of women population percentages among each major category. Once done, we display it below in Figure 3.5.

CB 1.4.4

```
SELECT Major_category , AVG(ShareWomen) FROM recent_grads
GROUP BY Major_category
```

Output

[16 rows x 2 columns]

Major_category	AVG(ShareWomen)
Agriculture & Natural Resources	0.6179384232
Arts	0.56185119575
Biology & Life Science	0.584518475857143
Business	0.4050631853076923
Communications & Journalism	0.64383484025
Computers & Mathematics	0.5127519954545455
Education	0.6749855163125
Engineering	0.2571578951034483
Health	0.6168565694166667
Humanities & Liberal Arts	0.6761934042
Industrial Arts & Consumer Services	0.4493512688571429
Interdisciplinary	0.495397153
Law & Public Policy	0.3359896912
Physical Sciences	0.5087494197

Figure 3.5: Group By ShareWomen Averages in Major Categories

Definition 3.11: HAVING Statement

The *HAVING* clause was added to SQL because the *WHERE* keyword could not be used with aggregate functions.


```

SELECT column_name(s)
FROM table_name
WHERE condition
GROUP BY column_name(s)
HAVING condition
ORDER BY column_name(s);

```

Definition 3.12: ROUND Function

The `ROUND()` function rounds a number to a specified number of decimal places.

```

SELECT ROUND(numeric_column_name, dec_places)

```

Definition 3.13: CAST Function

The `CAST()` function converts a value (of any type) into the specified datatype.

Example 3.5: Casting

In this example, we want to display the ratio of women to the total, grouping by each `Major_category`, summing and dividing by the total.

```
# CB 1.4.5 #
```

```

SELECT Major_category, CAST(Sum(Women) as float) / CAST(Sum(total) as float) SW
FROM recent_grads
GROUP BY Major_category
ORDER BY SW

```

Output
[16 rows x 2 columns]

Major_category	SW
Law & Public Policy	0.030585069260274586
Business	0.08474280852841269
Industrial Arts & Consumer Services	0.16024926890405236
Computers & Mathematics	0.20935560252568494
Engineering	0.2195958577559186
Communications & Journalism	0.25032539397505355
Arts	0.39332735978495226
Humanities & Liberal Arts	0.490051410855147
Health	0.6735876346523325
Interdisciplinary	0.8009108653220559
Social Science	0.8748032892676134
Psychology & Social Work	1.0491780784895022
Education	1.0962729531109994
Biology & Life Science	1.273805694241862

Figure 3.6: The Output of Query 1.4.5

3.1.4 Subqueries

Definition 3.14: Subquery

A Subquery or Inner query or a Nested query is a query within another SQL query and embedded within the WHERE clause. A subquery is used to return data that will be used in the main query as a condition to further restrict the data to be retrieved. Subqueries can be used with the SELECT, INSERT, UPDATE, and DELETE statements along with the operators like =, <, >, >=, <= IN, BETWEEN, etc.

Definition 3.15: IN Operator

The IN operator allows you to specify multiple values in a WHERE clause. The IN operator is a shorthand for multiple OR conditions.

```
SELECT column_name(s)
FROM table_name
WHERE column_name IN (value1, value2, ...);
```

Example 3.6: Subqueries with IN Keyword

In this example, we want to write a query that returns the Major, Major_category columns for the rows where Major_category is one of the 5 highest group level sums for the Total column.

CB 1.4.6

```
SELECT Major, Major_category FROM recent_grads
WHERE Major_category IN (SELECT Major_category FROM recent_grads
GROUP BY Major_category
ORDER BY SUM(Total) DESC
LIMIT 5)
```

Output
[82 rows x 2 columns]

Major	Major_category
PETROLEUM ENGINEERING	Engineering
MINING AND MINERAL ENGINEERING	Engineering
METALLURGICAL ENGINEERING	Engineering
NAVAL ARCHITECTURE AND MARINE ENGINEE...	Engineering
CHEMICAL ENGINEERING	Engineering
NUCLEAR ENGINEERING	Engineering
ACTUARIAL SCIENCE	Business
MECHANICAL ENGINEERING	Engineering
ELECTRICAL ENGINEERING	Engineering
COMPUTER ENGINEERING	Engineering
AEROSPACE ENGINEERING	Engineering
BIOMEDICAL ENGINEERING	Engineering
MATERIALS SCIENCE	Engineering
ENGINEERING MECHANICS PHYSICS AND SCI...	Engineering

Figure 3.7: The Output of Query CB 1.4.6

3.1.5 Guided Project: Analyzing CIA Factbook Data Using SQL

Definition 3.16: SQLite

SQLite is a relational database management system (RDBMS) contained in a C library. In contrast to many other database management systems, SQLite is not a client-server database engine. Rather, it is embedded into the end program.

Example 3.7: Analyzing CIA Factbook Data

To enable the ability to use SQL and load up the `factbook.db` [13], we enter the following code into the Jupyter Notebook:

```
%%capture
%load_ext sql
%sql sqlite:///factbook.db
```

```
In [36]: %%sql
SELECT name, birth_rate, death_rate, ROUND(death_rate - birth_rate, 5) AS "Population Decline"
FROM facts
ORDER BY death_rate DESC
```

Done.

Out[36]:

name	birth_rate	death_rate	Population Decline
Lesotho	25.47	14.89	-10.58
Ukraine	10.72	14.46	3.74
Bulgaria	8.92	14.44	5.52
Guinea-Bissau	33.38	14.33	-19.05
Latvia	10.0	14.31	4.31
Chad	36.6	14.28	-22.32
Lithuania	10.1	14.27	4.17

Figure 3.8: Birth / Death Rates ordered by Death Rate per Country

3.2 SQL Intermediate: Table Relations and Joins

3.2.1 Joining Data in SQL

Definition 3.17: JOIN Operation

A *JOIN* clause is used to combine rows from two or more tables, based on a related column between them. The syntax for a join clause is given below.

SELECT [column_names] **FROM** [table_name_one]
INNER JOIN [table_name_two] **ON** [join_constraint];

ON, which tells the SQL engine what columns to use to join the two tables. The syntax for specifying table column names is given by “table_name.column_name”.

Definition 3.18: Inner and Outer Join

(INNER) JOIN: Returns records that have matching values in both tables.

LEFT (OUTER) JOIN: Returns all records from the left table, and the matched records from the right table.

RIGHT (OUTER) JOIN: Returns all records from the right table, and the matched records from the left table.

FULL (OUTER) JOIN: Returns all records when there is a match in either left or right table.




Figure 3.9: Inner and Outer Joins

Example 3.8: Population among Capital Cities

We want to write a query that returns the 10 capital cities with the highest population ranked from biggest to smallest population. It will include columns in the following order:

- `capital_city`, the name of the city.
- `country`, the name of the country the city is from.
- `population`, the population of the city.

CB 1.4.7

```
SELECT c.name capital_city, f.name country, c.population population
FROM cities c
INNER JOIN facts f ON f.id = c.facts_id
WHERE c.capital = 1
ORDER BY population DESC
LIMIT 10
```

Output
[10 rows x 3 columns]

capital_city	country	population
Tokyo	Japan	37217000
New Delhi	India	22654000
Mexico City	Mexico	20446000
Beijing	China	15594000
Dhaka	Bangladesh	15391000
Buenos Aires	Argentina	13528000
Manila	Philippines	11862000
Moscow	Russia	11621000
Cairo	Egypt	11169000
Jakarta	Indonesia	9769000

Figure 3.10: The Output of Query CB 1.4.7

Example 3.9: Population Density in Cities Across a Country

We will write a query that generates columns in the following order:

- `country`, the name of the country.
- `urban_pop`, the sum of the population in major urban areas belonging to that country.
- `total_pop`, the total population of the country.
- `urban_pct`, the percentage of the population within urban areas, calculated by dividing `urban_pop` by `total_pop`.

Lastly, we subject these rows to the criteria that we only want countries that have an `urban_pct` greater than 0.5 and that the rows should be sorted by `urban_pct` in ascending order.

CB 1.4.8

```
SELECT f.name country, urb.urban_pop urban_pop, f.population total_pop,
CAST(urban_pop as float) / CAST(f.population as float) urban_pct
FROM facts f
INNER JOIN (SELECT SUM(c.population) urban_pop, facts_id FROM cities c
GROUP BY facts_id) urb ON urb.facts_id = f.id
WHERE urban_pct > 0.5
ORDER BY urban_pct
```

Output
[18 rows x 4 columns]

country	urban_pop	total_pop	urban_pct
Uruguay	1672000	3341893	0.5003152404939356
Congo, Republic of the	2445000	4755097	0.5141850944365594
Brunei	241000	429646	0.5609269026128487
New Caledonia	157000	271615	0.5780240413821034
Virgin Islands	60000	103574	0.5792959623071428
Falkland Islands (Islas Malvinas)	2000	3361	0.5950609937518596
Djibouti	496000	828324	0.5987995035758954
Australia	13789000	22751014	0.6060828761302683
Iceland	206000	331918	0.6206352171319423
Israel	5226000	8049314	0.6492478737939655
United Arab Emirates	3903000	5779760	0.6752875551926032
Puerto Rico	2475000	3598357	0.6878139106264332
Bahamas, The	254000	324597	0.7825087724162577
Kuwait	2406000	2788534	0.8628189579183901

Figure 3.11: The Output of Query CB 1.4.8

3.2.2 Intermediate Joins in SQL

Joining more than Two Tables

The syntax for joining more than two tables in SQL is given below:

```
SELECT [column_names] FROM [table_name_one]
[join_type] JOIN [table_name_two] ON [join_constraint]
[join_type] JOIN [table_name_three] ON [join_constraint];
```

Chinook Database

In this mission, we use a database named chinook. Its schema diagram is presented below:




Figure 3.12: Chinook Database Schema

Example 3.10: Popular Albums

We want to write a query that returns the top 5 albums, as calculated by the number of times a track from that album has been purchased. The query will be sorted from most tracks purchased to least tracks purchased and return the following columns, in order:

- `album`, the title of the album.
- `artist`, the artist who produced the album.
- `tracks_purchased` the total number of tracks purchased from that album.

CB 1.4.9

```

SELECT
    trkart.album album,
    trkart.artist_name artist,
    SUM(il.quantity) tracks_purchased
FROM invoice_line il
INNER JOIN
    (SELECT
        t.track_id,
        art.name artist_name,
  
```

```

        alb.title album
    FROM artist art
    INNER JOIN album alb ON alb.artist_id = art.artist_id
    INNER JOIN track t ON t.album_id = alb.album_id
    ) trkart ON trkart.track_id = il.track_id
GROUP BY album
ORDER BY tracks_purchased DESC
LIMIT 5

```

Output
[5 rows x 3 columns]

album	artist	tracks_purchased
Are You Experienced?	Jimi Hendrix	187
Faceless	Godsmack	96
Mezmerize	System Of A Down	93
Get Born	JET	90
The Doors	The Doors	83

Figure 3.13: The Output of Query CB 1.4.9

Definition 3.19: Self / Recursive Join

A self JOIN is a regular join, but the table is joined with itself.

```

SELECT column_name(s)
FROM table1 T1, table1 T2
WHERE condition;

```

T1 and T2 are different table aliases for the same table.

Definition 3.20: Concatenation Operator

|| or concatenation operator is use to link columns or character strings. We can also use a literal. A literal is a character, number or date that is included in the SELECT statement.

Definition 3.21: CONCAT Function

The CONCAT() function adds two or more strings together.

```
CONCAT(string1, string2, ..., string_n)
```

Example 3.11: Employees and Supervisors

We will write a query that returns information about each employee and their supervisor. The report will include employees even if they do not report to another employee. The report will be sorted alphabetically by the employee_name column. The query will return the following columns, in order:

- **employee_name** - containing the first_name and last_name columns separated by a space (eg Luke Skywalker).
- **employee_title** - the title of that employee.
- **supervisor_name** - the first and last name of the person the employee reports to, in the same format as

employee_name.

- **supervisor_title** - the title of the person the employee reports to.

CB 1.4.10

SELECT

```
e1.first_name || " " || e1.last_name employee_name ,
e1.title employee_title ,
e2.first_name || " " || e2.last_name supervisor_name ,
e2.title supervisor_title
```

FROM employee e1

LEFT JOIN employee e2 **ON** e1.reports_to = e2.employee_id

ORDER BY employee_name

Output
[8 rows x 4 columns]

employee_name	employee_title	supervisor_name	supervisor_title
Andrew Adams	General Manager		
Jane Peacock	Sales Support Agent	Nancy Edwards	Sales Manager
Laura Callahan	IT Staff	Michael Mitchell	IT Manager
Margaret Park	Sales Support Agent	Nancy Edwards	Sales Manager
Michael Mitchell	IT Manager	Andrew Adams	General Manager
Nancy Edwards	Sales Manager	Andrew Adams	General Manager
Robert King	IT Staff	Michael Mitchell	IT Manager
Steve Johnson	Sales Support Agent	Nancy Edwards	Sales Manager

Figure 3.14: The Output of Query CB 1.4.10

Definition 3.22: LIKE Operator

The *LIKE* operator is used in a *WHERE* clause to search for a specified pattern in a column.

There are two wildcards often used in conjunction with the *LIKE* operator:

% - The percent sign represents zero, one, or multiple characters.

_ - The underscore represents a single character.

SELECT column1, column2, ...

FROM table_name

WHERE columnN **LIKE** pattern;

Definition 3.23: CASE Statement

The *CASE* statement goes through conditions and returns a value when the first condition is met (like an *IF-THEN-ELSE* statement). So, once a condition is true, it will stop reading and return the result. If no conditions are true, it returns the value in the *ELSE* clause.

If there is no *ELSE* part and no conditions are true, it returns *NULL*.

CASE

WHEN condition1 **THEN** result1

WHEN condition2 **THEN** result2

WHEN conditionN **THEN** resultN

ELSE result

END

AS *[new_column_name]*

Example 3.12: Customer Spending Habits

We will write a query that summarizes the purchases of each customer. For the purposes of this exercise, we do not have any two customers with the same name. The query will include the following columns, in order:

- **customer_name** - containing the `first_name` and `last_name` columns separated by a space (eg Luke Skywalker).
- **number_of_purchases** - counts the number of purchases made by each customer.
- **total_spent** - the total sum of money spent by each customer.
- **customer_category** - a column that categorizes the customer based on their total purchases. The column should contain the following values:
 - small spender - If the customer's total purchases are less than \$40.
 - big spender - If the customer's total purchases are greater than \$100.
 - regular - If the customer's total purchases are between \$40 and \$100 (inclusive).

Results will be ordered by the `customer_name` column.

CB 1.4.11

```

SELECT
  c.first_name || " " || c.last_name customer_name,
  COUNT(i.invoice_id) number_of_purchases,
  SUM(i.total) total_spent,
  CASE
    WHEN sum(i.total) < 40 THEN "small_spender"
    WHEN sum(i.total) > 100 THEN "big_spender"
    ELSE "regular"
  END
  AS customer_category
FROM customer c
LEFT JOIN invoice i ON c.customer_id = i.customer_id
GROUP BY customer_name
ORDER BY customer_name

```

Output
[59 rows x 4 columns]

customer_name	number_of_purchases	total_spent	customer_category
Aaron Mitchell	8	70.28999999999999	regular
Alexandre Rocha	10	69.3	regular
Astrid Gruber	9	69.3	regular
Bjørn Hansen	9	72.27000000000001	regular
Camille Bernard	9	79.2	regular
Daan Peeters	7	60.38999999999999	regular
Dan Miller	12	95.03999999999999	regular
Diego Gutiérrez	5	39.6	small spender
Dominique Lefebvre	9	72.27	regular
Eduardo Martins	12	60.39	regular
Edward Francis	13	91.08	regular
Ellie Sullivan	12	75.24000000000001	regular
Emma Jones	8	68.31	regular
Enrique Muñoz	11	98.01	regular

Figure 3.15: The Output of Query CB 1.4.11

3.2.3 Building and Organizing Complex Queries

Query Readability

A little time put into whitespace and capitalization pays off. A few tips to help make your queries more readable:

- *If a select statement has more than one column, put each on a new line, indented from the select statement.*
- *Always capitalize SQL function names and keywords*
- *Put each clause of your query on a new line.*
- *Use indenting to make subqueries appear logically separate.*

Another important consideration when writing readable queries is the use of alias names and shortcuts. Name aliases should be clear— a common convention is using the first letter of the table name, however if you feel that a query is complex you should consider using more explicit aliases. Similarly, at times lines like GROUP BY 1 can be confusing, and explicitly naming the column will make your query more readable. For further information, you can also consult [14].

Definition 3.24: WITH Statement

WITH clauses allow you to define one or more named subqueries before the start of the main query. The main query then refers to the subquery by its alias name, just as if it's a table in the database.

Syntax:

WITH [alias_name] **AS** ([subquery])

SELECT [main_query]

To create multiple subqueries with the WITH statement can be done by

WITH
[alias_name] **AS** ([subquery]),

```
[alias_name_2] AS ([subquery_2]),
[alias_name_3] AS ([subquery_3])
```

```
SELECT [main-query]
```

While each subquery can be independent, we can actually use the result of the first subquery in subsequent subqueries, and so on. This can be a useful way of building readable complex queries.

Definition 3.25: CREATE VIEW

In SQL, a view is a virtual table based on the result-set of an SQL statement. A view contains rows and columns, just like a real table. The fields in a view are fields from one or more real tables in the database.

You can add SQL functions, WHERE, and JOIN statements to a view and present the data as if the data were coming from one single table.

Syntax:

```
CREATE VIEW view_name AS
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

If you wish to add the view to a database, one can use

```
CREATE VIEW database_name.view_name AS
SELECT * FROM database_name.table_name;
```

Definition 3.26: DROP VIEW Command

A view is deleted with the DROP VIEW command.

Syntax:

```
DROP VIEW view_name;
```

Example 3.13

We will create a view called `customer_gt_90.dollars`:

The view will only contain the columns from customers, in their original order.

The view will only contain customers who have purchased more than \$90 in tracks from the store.

After the SQL query that creates the view, we will write a second query to display the newly created view.

```
# CB 1.4.12 #
```

```
CREATE VIEW chinook.customer_gt_90_dollars AS
SELECT c.* FROM invoice i
LEFT JOIN customer c ON i.customer_id = c.customer_id
GROUP BY i.customer_id
HAVING SUM(i.total) > 90;

SELECT * FROM chinook.customer_gt_90_dollars;
```

Output
[18 rows x 13 columns]

customer_id	first_name	last_name	company	address
1	Luís	Gonçalves	Embraer - Empresa Brasileira de Aeron...	Av. Brigadeiro Faria
3	François	Tremblay		1498 rue Bélanger
5	František	Wichterlová	JetBrains s.r.o.	Klanova 9/506
6	Helena	Holý		Rilská 3174/6
13	Fernanda	Ramos		Qe 7 Bloco G
17	Jack	Smith	Microsoft Corporation	1 Microsoft Way
20	Dan	Miller		541 Del Medio Avenue
21	Kathy	Chase		801 W 4th Street
22	Heather	Leacock		120 S Orange Ave
30	Edward	Francis		230 Elgin Street
34	João	Fernandes		Rua da Assunção 53
37	Fynn	Zimmermann		Berger Straße 10
42	Wyatt	Girard		9, Place Louis Bartho

Figure 3.16: The Output of Query CB 1.4.12

Definition 3.27: UNION Operator

The *UNION* operator is used to combine the result-set of two or more *SELECT* statements.

- Each *SELECT* statement within *UNION* must have the same number of columns.
- The columns must also have similar data types.
- The columns in each *SELECT* statement must also be in the same order.

Syntax:

```
[select_statement_one]
```

UNION

```
[select_statement_two]
```

<pre>SELECT first_name, last_name, email FROM table_one UNION SELECT user_id, first_name, last_name, email, phone_number FROM table_two</pre> <p>Not Valid Tables have different number of columns</p>	<pre>SELECT first_name, last_name, total_sales FROM table_one UNION SELECT first_name, last_name, email FROM table_two</pre> <p>Not Valid Types are not compatible (<i>total_sales</i> numeric vs <i>email</i> text)</p>	<pre>SELECT first_name, last_name, email FROM table_one UNION SELECT first_name, last_name, email FROM table_two</pre> <p>Valid Tables have the same number of columns and compatible types</p>
---	---	--

Figure 3.17: Example of SQL Union Validity

Definition 3.28: INTERSECT Operator

The SQL **INTERSECT** operator is used to return the results of 2 or more **SELECT** statements. However, it only returns the rows selected by all queries or data sets. If a record exists in one query and not in the other, it will be omitted from the **INTERSECT** results.

Syntax:

```
[select_statement_one]
INTERSECT
[select_statement_two]
```

Definition 3.29: EXCEPT Operator

Selects rows that occur in the first statement, but don't occur in the second statement.

Syntax:

```
[select_statement_one]
EXCEPT
[select_statement_two]
```

Example 3.14

We will write a query that works out how many customers that are in the USA and have purchased more than \$90 are assigned to each sales support agent. For the purposes of this exercise, no two employees have the same name.

The result will have the following columns, in order:

- `employee_name` - The first_name and last_name of the employee separated by a space.
- `customers_usa_gt_90` - The number of customer assigned to that employee that are both from the USA and have have purchased more than \$90 worth of tracks.

The result will include all employees with the title "Sales Support Agent", but not employees with any other title. Lastly, the results will be ordered by the `employee_name` column.

CB 1.4.13

```
WITH customers_usa_gt_90 AS
(
    SELECT * FROM customer_usa

    INTERSECT

    SELECT * FROM customer_gt_90_dollars
)

SELECT
    e.first_name || "_" || e.last_name employee_name,
    COUNT(c.customer_id) customers_usa_gt_90
FROM employee e
LEFT JOIN customers_usa_gt_90 c ON c.support_rep_id = e.employee_id
```

```
WHERE e.title = 'Sales_Support_Agent'
```

Output
[3 rows x 2 columns]

employee_name	customers_usa_gt_90
Jane Peacock	0
Margaret Park	2
Steve Johnson	2

Figure 3.18: The Output of Query CB 1.4.13

Example 3.15

We will create a query to find the customer from each country that has spent the most money at the store, ordered alphabetically by country. The query will return the following columns, in order:

- `country` - The name of each country that we have a customer from.
- `customer_name` - The `first_name` and `last_name` of the customer from that country with the most total purchases, separated by a space (eg Luke Skywalker).
- `total_purchased` - The total dollar amount that customer has purchased.

```
# CB 1.4.14 #
```

```
WITH
    customer_totals AS
    (
        SELECT
            SUM(i.total) purchase_total,
            c.*
        FROM invoice i
        INNER JOIN customer c ON c.customer_id = i.customer_id
        GROUP BY c.customer_id
    ),
    customer_max AS
    (
        SELECT
            MAX(purchase_total) max_purchase,
            ct.country country,
            ct.first_name || " " || ct.last_name customer_name
        FROM customer_totals ct
        GROUP BY ct.country
    )

SELECT
    cm.country country,
    cm.customer_name customer_name,
    cm.max_purchase total_purchased
FROM customer_max cm
ORDER BY country
```

Output
[24 rows x 3 columns]

country	customer_name	total_purchased
Argentina	Diego Gutiérrez	39.6
Australia	Mark Taylor	81.18
Austria	Astrid Gruber	69.3
Belgium	Daan Peeters	60.38999999999999
Brazil	Luís Gonçalves	108.89999999999998
Canada	François Tremblay	99.99
Chile	Luis Rojas	97.02000000000001
Czech Republic	František Wichterlová	144.54000000000002
Denmark	Kara Nielsen	37.61999999999999
Finland	Terhi Hämäläinen	79.2
France	Wyatt Girard	99.99
Germany	Fynn Zimmermann	94.05000000000001
Hungary	Ladislav Kovács	78.21
India	Manoj Pareek	111.86999999999999

Figure 3.19: The Output of Query CB 1.4.14

3.2.4 Querying SQLite from Python

Definition 3.30: SQLite Connect Function

Once we import the module, we connect to the database we want to query using the `connect()` function. This function requires a single parameter, which is the database we want to connect to. The `connect()` function returns a `Connection` instance, which maintains the connection to the database we want to work with.

Definition 3.31: SQLite Cursor Class

The `Cursor` class is a `SQLite` class that allows us to interact with the database such as executing SQL statements and fetching the next row of a query result set [See [15] for further information]. We will use the `Cursor` class to

- Run a query against the database.
- Parse the results from the database.
- Convert the results to native Python objects.
- Store the results within the `Cursor` instance as a local variable.

Executing Queries w/o Cursor Instance

The `SQLite` library actually allows us to skip creating a `Cursor` altogether by using the `execute` method within the `Connection` object itself. `SQLite` will create a `Cursor` instance for us under the hood and run our query against the database, allowing us to skip a step. Suppose that `jobs.db` is a database with a `recent_grads` table, then the code could look like:

```
conn = sqlite3.connect("jobs.db")
query = "select * from recent_grads;"
conn.execute(query).fetchall()
```

Definition 3.32: Cursor Fetching Methods

Each `Cursor` instance contains an internal counter that updates every time we retrieve results. When we call the `fetchone()` method, the `Cursor` instance will return a single result, and then increment its internal counter by 1. This means that if we call `fetchone()` again, the `Cursor` instance will actually return the second tuple in the results set (and increment by 1 again).

The `fetchmany()` method takes in an integer (n) and returns the corresponding results, starting from the current position. It then increments the `Cursor` instance's counter by n .


Example 3.16

In this example, we want to write and run a query that returns the `Major` and `Major_category` columns from `recent_grads`. We then fetch the first five results and store them as `five_results`.

CB 1.4.15

```
import sqlite3
conn = sqlite3.connect("jobs.db")
cursor = conn.cursor()

query = "SELECT Major, Major_category FROM recent_grads"
five_results = cursor.execute(query).fetchmany(5)
```



```
Variables
▼ five_results list (<class 'list'>)
[('PETROLEUM ENGINEERING', 'Engineering'),
 ('MINING AND MINERAL ENGINEERING', 'Engineering'),
 ('METALLURGICAL ENGINEERING', 'Engineering'),
 ('NAVAL ARCHITECTURE AND MARINE ENGINEERING', 'Engineering'),
 ('CHEMICAL ENGINEERING', 'Engineering')]
```

Figure 3.20: The Output of CB 1.4.15

3.2.5 Guided Project: Answering Business Questions Using SQL**Definition 3.33: Context Manager**

A context manager is an object that defines the runtime context to be established when executing a `with` statement. The context manager handles the entry into, and the exit from, the desired runtime context for the execution of the block of code. Context managers are normally invoked using the `with` statement (described in section The `with` statement), but can also be used by directly invoking their methods.

Typical uses of context managers include saving and restoring various kinds of global state, locking and unlocking resources, closing opened files, etc. [See [16] for a good article on this].

Definition 3.34: Python with statement

The `with` statement is used to wrap the execution of a block with methods defined by a context manager (see section With Statement Context Managers). This allows common `try...except...finally` usage patterns

to be encapsulated for convenient reuse.

```
with something_that_returns_a_context_manager() as my_resource:
    do_something(my_resource)
```

The execution of the with statement with one “item” proceeds as follows:

1. The context expression (the expression given in the with_item) is evaluated to obtain a context manager.
2. The context manager’s `__enter__()` is loaded for later use.
3. The context manager’s `__exit__()` is loaded for later use.
4. The context manager’s `__enter__()` method is invoked.
5. If a target was included in the with statement, the return value from `__enter__()` is assigned to it.

(Note: The with statement guarantees that if the `__enter__()` method returns without an error, then `__exit__()` will always be called. Thus, if an error occurs during the assignment to the target list, it will be treated the same as an error occurring within the suite would be. See step 6 below.)

6. The suite is executed.
7. The context manager’s `__exit__()` method is invoked. If an exception caused the suite to be exited, its type, value, and traceback are passed as arguments to `__exit__()`. Otherwise, three None arguments are supplied.

The following code

```
with EXPRESSION as TARGET:
    SUITE
```

is semantically equivalent to:

```
manager = (EXPRESSION)
enter = type(manager).__enter__
exit = type(manager).__exit__
value = enter(manager)
hit_except = False

try:
    TARGET = value
    SUITE
except:
    hit_except = True
    if not exit(manager, *sys.exc_info()):
        raise
finally:
    if not hit_except:
        exit(manager, None, None, None)
```

Definition 3.35: Pandas `read_sql_query()`

```
pandas.read_sql_query(sql, con, index_col=None, coerce_float=True, params=None, parse_dates=None,
chunksize=None)
```

Read SQL query into a `DataFrame`.

Returns a `DataFrame` corresponding to the result set of the query string. Optionally provide an `index_col` parameter to use one of the columns as the index, otherwise default integer index will be used [See [17] for further information].

PARAMETERS: `sql`: str SQL query or SQLAlchemy Selectable (select or text object)
SQL query to be executed.

con: SQLAlchemy connectable(engine/connection), database str URI
or sqlite3 DBAPI2 connection. Using SQLAlchemy makes it possible to use any DB supported by that library. If a DBAPI2 object, only sqlite3 is supported.

Example 3.17: Setting up SQLite in Python

The first task is to import the `SQLite`, `pandas` and `matplotlib` modules, and use the magic command `%matplotlib inline` to make sure any plots render in the notebook.

1. Create a `run_query()` function, that takes a SQL query as an argument and returns a pandas dataframe of that query.
2. Create a `run_command()` function that takes a SQL command as an argument and executes it using the `sqlite` module.
3. Create a `show_tables()` function that calls the `run_query()` function to return a list of all tables and views in the database.
4. Run the `show_tables()` function.

```
# CB 1.4.16 #
```

```
%matplotlib inline
```

```
import sqlite3
import pandas as pd
import matplotlib.pyplot as plt

def run_query(query):
    with sqlite3.connect('chinook.db') as conn:
        return pd.read_sql_query(query, conn)

def run_command(c):
    with sqlite3.connect('chinook.db') as conn:
        conn.isolation_level = None
        conn.execute(c)

def show_tables():
    query = """SELECT name, type FROM sqlite_master
               WHERE type IN ('table', 'view') """
    tables = run_query(query)
    print(tables)

show_tables()
```

	name	type
0	album	table
1	artist	table
2	customer	table
3	employee	table
4	genre	table
5	invoice	table
6	invoice_line	table
7	media_type	table
8	playlist	table
9	playlist_track	table
10	track	table
11	country_cust	view

Figure 3.21: The Output of CB 1.4.16

Example 3.18: Finding Total Tracks Purchased in Each Genre from the Chinook Database

We want to write a query that returns each genre, with the number of tracks sold in the USA:

- in absolute numbers.
- in percentages.

We'll create a plot to show this data.

CB 1.4.17

```
query_genre = """
WITH usa_tracks AS
(
  SELECT
    i.invoice_id invoice_id,
    il.track_id track_id,
    il.quantity
  FROM invoice i
  INNER JOIN invoice_line il ON il.invoice_id = i.invoice_id
  WHERE i.billing_country = 'USA'
),
usa_genre_tracks AS
(
  SELECT
    g.name genre,
    SUM(ut.quantity) total_tracks_purchased
  FROM usa_tracks ut
  INNER JOIN track t ON t.track_id = ut.track_id
  INNER JOIN genre g ON g.genre_id = t.genre_id
  GROUP BY 1
)

SELECT
  ugt.*,
  (
    CAST(ugt.total_tracks_purchased AS float) /
    CAST
  (
    (
```

```

SELECT SUM(ugt.total_tracks_purchased)
FROM usa_genre_tracks ugt
)
AS float
)
)*100 total_tracks_percent
FROM usa_genre_tracks ugt
GROUP BY 1
ORDER BY total_tracks_purchased DESC
"""

```

```

invoice_line = run_query(query_genre)
print(invoice_line)

```

	genre	total_tracks_purchased	total_tracks_percent
0	Rock	561	53.377735
1	Alternative & Punk	130	12.369172
2	Metal	124	11.798287
3	R&B/Soul	53	5.042816
4	Blues	36	3.425309
5	Alternative	35	3.330162
6	Latin	22	2.093245
7	Pop	22	2.093245
8	Hip Hop/Rap	20	1.902950
9	Jazz	14	1.332065
10	Easy Listening	13	1.236917
11	Reggae	6	0.570885
12	Electronica/Dance	5	0.475737
13	Classical	4	0.380590
14	Heavy Metal	3	0.285442
15	Soundtrack	2	0.190295
16	TV Shows	1	0.095147

Figure 3.22: The Output of CB 1.4.17

We can use the built-in pandas plotting methods to produce a plot for this data. We do this below.

```
# CS 1.4.18 #
```

```

invoice_line.plot(x = 'genre', y = 'total_tracks_purchased',
                  title = "Total_Number_of_Tracks_Sold_vs_Genre_(USA)",
                  kind = 'bar', legend = None)

```




Figure 3.23: The Output of CS 1.4.18

Example 3.19: Finding Transaction Details for Each Country from the Chinook Database

We will write a query that collates data on purchases from different countries. When a country has only one customer, we will collect them into an "Other" group.

The results should be sorted by the total sales from highest to lowest, with the "Other" group at the very bottom.

For each country, we will include:

- total number of customers.
- total value of sales.
- average value of sales per customer.
- average order value.

CB 1.4.19

```
c = """
CREATE VIEW country_cust AS
SELECT
    c.first_name || " " || c.last_name customer_name,
    COUNT(i.customer_id) customer_count,
    c.country country,
    SUM(i.total) total_spent
FROM customer c
INNER JOIN invoice i ON i.customer_id = c.customer_id
GROUP BY 1, 1
ORDER BY customer_count DESC
"""
```

```
d = "DROP_VIEW_country_cust"
```

```
run_command(d)
```

```

run_command(c)

query = """
With country_info AS
(
    SELECT
        cc.country,
        SUM(cc.customer_count) orders,
        Count(cc.customer_name) unique_customers,
        Sum(total_spent) total_sales
    FROM country_cust cc
    GROUP BY cc.country
    ORDER BY total_sales
),
other_info AS
(
    SELECT
        CASE
            WHEN ci.unique_customers = 1 THEN "Other"
            ELSE 0
        END
        AS country,
        SUM(ci.orders) orders,
        Count(ci.unique_customers) unique_customers,
        SUM(ci.total_sales) total_sales
    FROM country_info ci
    WHERE ci.unique_customers = 1
),
country_other_info AS
(
    SELECT *
    FROM
        (
            SELECT
                coi.*,
                CASE
                    WHEN coi.country = "Other" THEN "1"
                    ELSE 0
                END
                AS count
            FROM
                (
                    SELECT * FROM other_info

                UNION

                SELECT * FROM country_info ci
                WHERE ci.unique_customers != 1
                ) coi
            ORDER BY count ASC
        ) coi_new
)

```

```

SELECT
    country,
    unique_customers,
    total_sales,
    total_sales / CAST(unique_customers as float) average_sale_per_customer,
    total_sales / CAST(orders as float) average_order_value
FROM country_other_info

"""
querydf = run_query(query)
print(querydf)

```

	country	unique_customers	total_sales	average_sale_per_customer	average_order_value
0	Brazil	5	427.68	85.536000	7.011148
1	Canada	8	535.59	66.948750	7.047237
2	Czech Republic	2	273.24	136.620000	9.108000
3	France	5	389.07	77.814000	7.781400
4	Germany	4	334.62	83.655000	8.161463
5	India	2	183.15	91.575000	8.721429
6	Portugal	2	185.13	92.565000	6.383793
7	USA	13	1040.49	80.037692	7.942672
8	United Kingdom	3	245.52	81.840000	8.768571
9	Other	15	1094.94	72.996000	7.448571

Figure 3.24: The Output of CB 1.4.19

The trick in placing the ‘Other’ column at the very end is to assign some ordered value to ‘Other’ with all other countries held at some other constant value. This can be seen in the *country-other-info* subquery in the *WITH* section of CB 1.4.19.

3.2.6 Table Relations and Normalization

Definition 3.36: SQLite prompt

When you launch the SQLite shell, you will be shown the SQLite prompt, seen below by *sqlite>*.

```

$ sqlite3 chinook.db
— Loading resources from /home/dq/.sqliterc
SQLite version 3.21.0 2017-10-24 18:55:49
Enter ".help" for usage hints.
sqlite>

```

Definition 3.37: SQLite Dot Commands

SQLite has a number of dot commands which you can use to help you work with databases. When you use a dot command, you don’t need to use a semicolon. Some common dot commands are

- *.help* - Displays help text showing all dot commands and their function.
- *.tables* - Displays a list of all tables and views in the current database.
- *.shell [command]* - Run a command like *ls* or *clear* in the system shell.

- `.mode` - Allows us to select from a few different display modes. We'll use `.mode column` to allow for easier to read outputs.
- `.quit` - Quits the SQLite shell.

Example 3.20: Querying on SQLite Shell

We can send query instructions to the SQLite shell so that we can interact with the database.

```
sqlite> SELECT * FROM album LIMIT 10;
album_id  title                                     artist_id
-----
1         For Those About To Rock We Salute You  1
2         Balls to the Wall                      2
3         Restless and Wild                     2
4         Let There Be Rock                     1
5         Big Ones                             3
6         Jagged Little Pill                   4
7         Facelift                             5
8         Warner 25 Anos                       6
9         Plays Metallica By Four Cellos    7
10        Audioslave                       8
sqlite> 
```

Figure 3.25: SQLite Shell Query

Definition 3.38: CREATE TABLE

The `CREATE TABLE` statement is used to create a new table in a database.

```
CREATE TABLE [table_name] (
    [column1_name] [column1_type],
    [column2_name] [column2_type],
    [column3_name] [column3_type],
    [...]
);
```

Each column in SQLite must have a type. While some database systems have as many as 50 distinct data types, SQLite uses only 5 behind the scenes:

- `TEXT`
- `INTEGER`
- `REAL`
- `NUMERIC`
- `BLOB`

Alphabetical Index

	C		
Context Manager	55	SQL CREATE VIEW	50
		SQL DISTINCT Statement	37
	P	SQL GROUP BY Statement	38
Python With Statement	55	SQL HAVING Statement	39
		SQL IN Operator	41
	R	SQL INTERSECT	52
RDBMS	34	SQL JOIN	42
		Inner Join	43
		Outer Join	43
		Self/Recursive Join	46
	S	SQL LIKE Operator	47
SQL	34	SQL Logical Operators	34
SQL Aggregate Functions	36	SQL ORDER BY Operation	35
SQL Alias	37	SQL ROUND Function	40
SQL CASE	47	SQL SELECT Operation	34
SQL CAST Function	40	SQL Subquery	41
SQL Comparison Operators	34	SQL UNION	51
SQL Concatenation	46	SQL WHERE Operation	35
CONCAT Function	46	SQL WITH Statement	49
Operator	46	SQLite	42
SQL CREATE TABLE	63		

References

- [1] URL: <https://docs.scipy.org/doc/numpy/reference/generated/numpy.genfromtxt.html>.
- [2] URL: <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.DataFrame.html>.
- [3] URL: https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read_csv.html.
- [4] URL: <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.Series.html>.
- [5] URL: <https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.Series.map.html>.
- [6] URL: https://matplotlib.org/3.1.1/api/_as_gen/matplotlib.pyplot.figure.html.
- [7] URL: https://matplotlib.org/api/axes_api.html#matplotlib-axes.
- [8] URL: https://pandas.pydata.org/pandas-docs/stable/user_guide/visualization.html.
- [9] URL: https://en.wikipedia.org/wiki/Kernel_density_estimation.
- [10] URL: https://matplotlib.org/basemap/api/basemap_api.html#mpl_toolkits.basemap.Basemap.
- [11] URL: https://www.w3schools.com/sql/sql_operators.asp.
- [12] URL: <https://www.sqlservertutorial.net/sql-server/aggregate-functions/>.
- [13] URL: <https://www.cia.gov/library/publications/the-world-factbook/>.
- [14] URL: <https://www.sqlstyle.guide/>.
- [15] URL: <https://docs.python.org/3/library/sqlite3.html#cursor-objects>.
- [16] URL: <https://jeffknupp.com/blog/2016/03/07/python-with-context-managers/>.
- [17] URL: https://pandas.pydata.org/pandas-docs/stable/reference/api/pandas.read_sql_query.html.