

Drupal 8 User Guide



Drupal™



用戶指南

Drupal 8 User Guide

目录

i. Preface	vi
i.1. Copyright	vi
i.2. Audience and Goal	vi
i.3. Organization	vii
i.4. Reporting Problems	viii
i.5. Conventions of the Guide	ix
i.6. Guiding Scenario	xi
1. Understanding Drupal	1
1.1. Concept: Drupal as a Content Management System	1
1.2. Concept: Modules	3
1.3. Concept: Themes	4
1.4. Concept: Distributions	5
1.5. Concept: Types of Data	6
1.6. Concept: The Drupal Project	7
1.7. Concept: Drupal Licensing	8
2. Planning Your Site	10
2.1. Concept: Regions in a Theme	10
2.2. Planning Your Site Layout	11
2.3. Concept: Content Entities and Fields	13
2.4. Concept: Modular Content	15
2.5. Planning your Content Structure	16
2.6. Concept: Editorial Workflow	19
3. Installation	21
3.1. Concept: Server Requirements	21
3.2. Concept: Additional Tools	22
3.3. Preparing to Install	24
3.4. Running the Installer	27
4. Basic Site Configuration	34
4.1. Concept: Administrative Overview	34
4.2. Editing Basic Site Information	37
4.3. Installing a Module	39
4.4. Uninstalling Unused Modules	41
4.5. Configuring User Account Settings	43
4.6. Configuring the Theme	45
5. Basic Page Management	49
5.1. Concept: Paths, Aliases, and URLs	49
5.2. Creating a Content Item	50
5.3. Editing a Content Item	52
5.4. Editing with the In-Place Editor	53
5.5. Designating a Front Page for your Site	55
5.6. Concept: Menu	56
5.7. Adding a Page to the Navigation	58
5.8. Changing the Order of Navigation	60
6. Setting Up Content Structure	63
6.1. Adding a Content Type	63
6.2. Deleting a Content Type	67

6.3.	Adding Basic Fields to a Content Type	69
6.4.	Concept: Reference Fields	73
6.5.	Concept: Taxonomy	74
6.6.	Setting Up a Taxonomy	75
6.7.	Adding a Reference Field	80
6.8.	Concept: Forms and Widgets	84
6.9.	Changing Content Entry Forms	84
6.10.	Concept: View Modes and Formatters	87
6.11.	Changing Content Display	88
6.12.	Concept: Image Styles	91
6.13.	Setting Up an Image Style	92
6.14.	Concept: Responsive Image Styles	95
6.15.	Concept: Text Formats and Editors	96
6.16.	Configuring Text Formats and Editors	97
7.	Managing User Accounts	100
7.1.	Concept: Users, Roles, and Permissions	100
7.2.	Concept: The User 1 Account	101
7.3.	Creating a Role	102
7.4.	Creating a User Account	104
7.5.	Assigning Permissions to a Role	107
7.6.	Changing a User's Roles	109
7.7.	Assigning Authors to Content	111
8.	Blocks	114
8.1.	Concept: Blocks	114
8.2.	Creating A Custom Block	114
8.3.	Placing a Block in a Region	116
9.	Creating Listings with Views	119
9.1.	Concept: Uses of Views	119
9.2.	Concept: The Parts of a View	120
9.3.	Creating a Content List View	121
9.4.	Duplicating a View	126
9.5.	Adding a Block Display to a View	129
10.	Making Your Site Multilingual	134
10.1.	Concept: User Interface, Configuration, and Content translation	134
10.2.	Adding a Language	135
10.3.	Configuring Content Translation	136
10.4.	Translating Content	141
10.5.	Translating Configuration	142
11.	Extending and Customizing Your Site	146
11.1.	Finding Modules	146
11.2.	Enabling and Disabling Maintenance Mode	150
11.3.	Downloading and Installing a Module from Drupal.org	152
11.4.	Finding Themes	155
11.5.	Downloading and Installing a Theme from Drupal.org	158
11.6.	Manually Downloading Module or Theme Files	161
11.7.	Concept: Development Sites	163
11.8.	Making a Development Site	164
11.9.	Using Composer and Git to Download Files	166
11.10.	Deploying New Site Features	169

11.11. Synchronizing Configuration Versions	172
12. Preventing and Fixing Problems	175
12.1. Concept: Cache	175
12.2. Clearing the Cache	176
12.3. Concept: Data Backups	178
12.4. Concept: Log	179
12.5. Concept: Status Report	180
13. Security and Maintenance	182
13.1. Concept: Cron	182
13.2. Configuring Cron Maintenance Tasks	182
13.3. Concept: Security and Regular Updates	185
13.4. Keeping Track of Updates	186
13.5. Updating the Core Software	187
13.6. Updating a Module	189
13.7. Updating a Theme	192
14. Final Thoughts	195
14.1. Connecting with the Community	195
14.2. Getting Support	197
14.3. Learning More	198
Glossary	200
Index	206
A. Appendix	216
A.1. Guide-Wide Attributions	216

Preface

i.1. Copyright

This guide was written by contributors to the Drupal open-source project. It is copyright 2015-2016 by the individual contributors, and can be used in accordance with the [Creative Commons License, Attribution-ShareAlike 2.0](#) (CC BY-SA 2.0). Each page in this document (including this one) has an Attributions statement at the bottom, listing the people who contributed to writing and editing that page. See also [第 A.1 节 “Guide-Wide Attributions”](#) for guide-wide editing, translating, and project management information.

The CC BY-SA license (very similar to the GPL) allows anyone to copy, modify, and redistribute modifications of all or part of this work, as long as the following is complied with:

- You provide appropriate credit (see the license for more information).
- You provide a link to the license.
- You indicate whether changes have been made.
- You distribute your work under the same license as this original.

Attributions

This page was adapted and edited by [Jennifer Hodgdon](#), and [Jojo Alphonso](#) at [Red Crackle](#), from ["Documentation copyright and licensing"](#), copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

Copyright notice: Copyright 2015-2016 by the individual contributors; see [第 i.1 节 “Copyright”](#) for details. Licensed under [CC BY-SA 2.0](#).

i.2. Audience and Goal

This guide was written mainly for people with minimal knowledge of the Drupal content management system. The topics will help them become skilled at installing, administering, site building, and/or maintaining the content of a Drupal-based website. The guide is also aimed at people who already have some experience with a current or past version of Drupal, and want to expand the range of their skills and knowledge or update them to the current version.

This guide assumes that you have already decided you want to learn and use Drupal. If you need to learn more before deciding, see [第 1.1 节 “Concept: Drupal as a Content Management System”](#).

Depending on which aspects of Drupal you would like to learn, you will need some background knowledge to understand this guide: general Internet skills and knowledge

are assumed, and the guide concentrates on how to use the software itself. For instance, the sections about installing Drupal on a web server assume you can obtain web hosting and figure out how to transfer files to your chosen web host. Similarly, the sections about content management assume you can log into a website and fill in a web-based form.

After reading this guide, you should be able to:

- Plan the content architecture for a Drupal-based site
- Build the site that you planned
- Manage and administer your site
- Understand documentation and blog posts on topics not covered here, to expand your knowledge and skills
- Connect with the worldwide Drupal community

Attributions

Written by [Jennifer Hodgdon](#).

i.3. Organization

This user guide contains a series of topics, each of which covers either a task (how to do something) or a concept (background knowledge, terminology, and the like). Concept topics have names starting with Concept:, while task topics have names containing verbs, like Editing Basic Site Information.

The topics are grouped into chapters in a logical order, with concepts and tasks interleaved so that concepts are presented before related tasks, and tasks build on each other. To take advantage of this, you are encouraged to read the entire guide in its presented order, possibly skipping topics that are not of interest or that present information you already know. Remember to try out the tasks on your own site as you read the guide; most people learn better by doing rather than reading.

If you prefer, you can also use the index or table of contents to jump straight to a topic that you'd like to learn about, rather than reading the entire guide. To facilitate this approach, each topic lists the prerequisite knowledge that you'd need in order to understand it, if any (with links to the topics that present that knowledge); task topics also list site prerequisites (things that you would need to have configured or created on your site in order to perform the task). Also, most topics have sections at the end where you can find related information and/or tasks for expanded understanding, to continue your learning.

You may also want to refer to the [Glossary](#) section as you read – it gives brief definitions of most of the terminology used in the guide, with links to topics having more detailed explanations.

Attributions

Written by [Jennifer Hodgdon](#).

i.4. Reporting Problems

Goal

Report a problem with this guide, such as:

- Information that is incorrect or does not follow best practices
- Steps that do not work
- Screen shots or text that doesn't match what you see on the screen
- Unclear writing
- Places where a table or screen shot would help clarify the text
- Failure to define terminology
- Missing knowledge prerequisites or site prerequisites for a topic
- Typographical, spelling, grammar, or formatting errors
- Broken links

Steps

1. Make a note of the topic or topics that contain the problem you have found.
2. Log in to [Drupal.org](#) (you will need to create a user account if you do not already have one).
3. Visit the [User Guide issues page on Drupal.org](#).
4. Verify that the problem you found has not already been reported in another issue:
 - If there are only a few open issues, scan the Summary column to see if any of their descriptions match the problem you found. You may also need to read some of the issues to make sure, which you can do by clicking the links in the Summary column.
 - If the open issue list is long, enter either a keyword related to the problem you found or the title of the topic where the problem occurs in the Search for box, and click Search to reduce the issue list. Then either scan the summaries or read the issues to see if they match your problem.
5. If you determine that your problem has not already been reported, click Create a new issue, and fill in the issue report as follows:

Field name	Explanation	Example value
Title	Short summary of the problem you found	Instructions in "Adding a Content Type" do not work
Category	Type of issue being reported	Bug report

Field name	Explanation	Example value
Version	Version of the guide you found the problem in	8.x-0.x-dev
Issue summary	Details of the problem you found	In the "Adding a Content Type" topic, in step 3, when I clicked Save, I got the following error message: ...

6. Reread the Title and Issue summary you entered, and verify that the following information is included in your report:
 - A complete description of the problem you found
 - The name of the topic or topics where you found the problem
 - The language you are reading the guide in (if not English)
 - If you read the guide on a website, a link to the page or pages with the problem
7. Click Save to create the issue.
8. Check back on the issue in a few days. If one of the project maintainers has asked for clarification, respond by adding a comment to the issue.

Attributions

Written by [Jennifer Hodgdon](#).

i.5. Conventions of the Guide

Assumptions and prerequisites

This guide has the following assumptions and prerequisites:

- This guide is organized into topics; see [第 i.3 节 “Organization”](#) for details. Many topics include a Prerequisite knowledge section, which lists other topics whose content knowledge is needed in order to understand the topic you are reading. Some background knowledge that is not covered in the guide is also assumed; see [第 i.2 节 “Audience and Goal”](#) for details.
- Many task topics list Site prerequisites, which are tasks that you'll need to have completed on your site before you'll be able to do the task in the topic you are reading.
- The specifics of the site prerequisites relate to the scenario used throughout this guide of building a site for a farmers market (see [第 i.6 节 “Guiding Scenario”](#) for details). You can adapt the tasks to your own scenario, but you will also need to remember the changes you made when deciding if your site satisfies the site prerequisites for a task.

- For all task topics after 第 3.4 节 “Running the Installer”, there is also an implicit prerequisite: you must have installed the content management software on your site, and be logged in to a user account with sufficient permissions to do the task (such as the user account created when you installed your site, which automatically has full permissions).
- If you read all the topics in order, and perform all of the steps in the task topics as you go (staying logged in), you should have the background knowledge and site prerequisites in place for each topic as you read it.

Text conventions

The following conventions are used in the text of this guide:

- The URL example.com means the base URL of your website. See the Navigation section below for more details on how URLs internal to your site are indicated.
- Text you should see in the user interface of your site is shown in italics, such as: Click Save configuration. This only applies to text in the user interface that comes from the software, not to text that was entered in a previous topic. For example, in a topic about editing, you might see this instruction: Click Edit in the row of the About page (Edit would be in italics, but About would not be, because the About page was created in a previous topic).
- URLs, file names, and newly-introduced terminology are also shown in italics.
- Text that you should type at a shell command line is shown in monospace type, such as:
`drush cr`
- Within this guide, the word directory is always used to refer to file directories (which some people prefer to call folders).

Navigation

To do most of the task topics in this guide, you will need to navigate to one or more pages in the administrative interface of your site. You might see something like this in the instructions (this will make more sense after you have the base software installed):

In the Manage administrative menu, navigate to Structure > Taxonomy (admin/structure/taxonomy).

Navigation instructions like this assume that you have the core Toolbar module installed, and this example means that in the menu bar at the top of your site, you would need to click Manage to expose the menu choices, then click Structure, then :_Taxonomy_, and that at the end, you would be on a page with URL <http://example.com/admin/structure/taxonomy> (if your site base URL is <http://example.com>).



Here's another example:

In the Manage administrative menu, navigate to Configuration > System > Site information (admin/config/system/site-information).

In this example, after clicking on Manage and Configuration, you would need to find the System section of the page, and within that, click Site information. After that, you'd end up on <http://example.com/admin/config/system/site-information>.



One other note: if you are using the standard administrative core Seven theme, many "Add" buttons in the administrative interface are displayed with + signs on them. For instance, on admin/content, the Add new content button appears as + Add new content. However, this is theme-dependent and is not really part of the text on the button (for instance, it would not necessarily be read by a screen reader), so in this guide, the convention is to not mention the + sign on the buttons.

Filling in forms

Many of the task topics in this guide include steps where you will fill out a web form. In most cases, a screen capture image of the form will be included, along with a table of the values you will need to enter into each form field. For example, you might see a table that starts out like this, explaining the site information form you would see if you navigated to Configuration > System > Site information (admin/config/system/site-information):

Field name	Explanation	Example value
Site name	Name of your site	Anytown Farmers Market

To use this table, find the field labeled Site name in the form, and enter the name of your site in this field. An example site name of "Anytown Farmers Market" is suggested in the table, which relates to the scenario of building a website for a farmers market that you'll find all through this guide (see [第 i.6 节 “Guiding Scenario”](#) for details).

Attributions

Written/edited by [Jennifer Hodgdon](#).

i.6. Guiding Scenario

When reading this guide, it is helpful to have a website building project in mind. The following project scenario provides context and links together the examples in this guide:

You are making a website for a farmers market. The site needs to display information about the location and hours of the market, and an About page with the history of the market. It also needs to list the vendors. Vendors should be able to edit their listings (including a logo or photo), and post recipes. Site visitors should be able to browse recipes, or locate recipes using ingredients that they purchased at the market. Some visitors to your site speak another language, so the main pages and vendor pages need to be translated.

Attributions

Written/edited by [Jennifer Hodgdon](#).

第 1 章 Understanding Drupal

1.1. Concept: Drupal as a Content Management System

What is a Content Management System?

A content management system (CMS) is a software tool that lets users add, publish, edit, or remove content from a website, using a web browser on a smartphone, tablet, or desktop computer. Typically, the CMS software is written in a scripting language, and its scripts run on a computer where a database and a web server are installed. The content and settings for the website are usually stored in a database, and for each page request that comes to the web server, the scripts combine information from the database and assets (JavaScript files, CSS files, image files, etc. that are part of the CMS or have been uploaded) to build the pages of the website.

The combination of the operating system that the CMS runs on, the scripting language it is written in, the database it stores its information in, and the web server that runs the scripts to retrieve information and return it to the site visitor's web browser is known as the stack that the CMS runs on; the commonly used combination of the Linux operating system, Apache web server, MySQL database, and PHP scripting language is known as the LAMP stack.

What is Drupal?

Drupal is a flexible CMS based on the LAMP stack, with a modular design allowing features to be added and removed by installing and uninstalling modules, and allowing the entire look and feel of the website to be changed by installing and uninstalling themes. The base Drupal download, known as Drupal Core, contains the PHP scripts needed to run the basic CMS functionality, several optional modules and themes, and many JavaScript, CSS, and image assets. Many additional modules and themes can be downloaded from the [Drupal.org](https://www.drupal.org) website.

Drupal can also run on other technology stacks:

- The operating system can be Windows or Mac OS instead of Linux.
- The web server can be Nginx or IIS instead of Apache.
- The database can be PostgreSQL or SQLite instead of MySQL, or a MySQL-compatible replacement such as MariaDB or Percona.

Other operating systems, web servers, and databases can also be made to work; however, the scripts that the software uses are written in PHP, so that cannot be changed.

What are the reasons for using Drupal?

When building a website, you have your choice of using one of the many existing CMS packages and hosted services, developing your own CMS, or building the site without using a CMS. Here are some of the reasons you might choose to use Drupal:

- Building a small, simple site with static HTML pages is not difficult, and you can get a simple site up very quickly. Setting up a site in a CMS generally requires more time initially, but brings you the benefits of on-line editing (easier for less experienced content maintainers), uniformity (harder to maintain using static HTML for larger sites), and the possibility of more complex features requiring a database.
- Some CMS software is special-purpose; for instance, there are packages and hosted services that you can use to build a blog or a club membership website. Drupal, in contrast, is a general-purpose CMS. If you are building a special-purpose site, you might choose to use a special-purpose CMS; however, if your site falls even slightly outside the intended purpose, you will probably be better off using a general-purpose CMS rather than trying to adapt a special-purpose CMS.
- Building your own CMS-type software can seem attractive. However, using a general-purpose CMS like Drupal as a starting point is usually a better idea, because the basic CMS functionality (such as user accounts and content management) has thousands of developer hours behind it, including many years of user testing, bug fixing, and security hardening.
- Some CMS software packages are expensive to purchase a license for. Some are free or have a free version, but have restrictive licenses that do not allow you to make modifications and extensions. You might prefer to use a package (like Drupal) that has a less restrictive software license, and is developed by a world-wide community. See [第 1.6 节 “Concept: The Drupal Project”](#) for more on this topic.

Related topics

- [第 1.2 节 “Concept: Modules”](#)
- [第 1.3 节 “Concept: Themes”](#)
- [第 1.4 节 “Concept: Distributions”](#)
- [第 1.6 节 “Concept: The Drupal Project”](#)

Additional resources

- [The Drupal overview](#)
- [Drupal.org page "FAQ" \(Frequently Asked Questions\)](#)
- [Drupal.org page "Case Studies"](#)
- [Wikipedia page "Content management systems"](#)
- [Wikipedia page "Modular design"](#)

Attributions

Written and edited by [Kristof van Tomme](#) at [Pronovix](#), [Jennifer Hodgdon](#), and [Michael Lenahan](#) at [erdfisch](#).

1.2. Concept: Modules

Prerequisite knowledge

[第 1.1 节 “Concept: Drupal as a Content Management System”](#)

What is a module?

A module is a set of PHP, JavaScript, and/or CSS files that extends site features and adds functionality. You can turn the features and functionality on by installing the module, and you can turn it off by uninstalling the module; before uninstalling, you may need to remove data and configuration related to the feature or functionality. Each module that is installed adds to the time needed to generate pages on your site, so it is a good idea to uninstall modules that are not needed.

The core download provides modules for functionality such as:

- Managing user accounts (the core User module)
- Managing basic content (the core Node module) and fields (the core Field and Field UI modules; there are also core modules providing field types)
- Managing navigation menus (the core Menu UI module)
- Making lists, grids, and blocks from existing content (the core Views and Views UI modules)

You can download additional contributed modules from the [Drupal.org Module Downloads](#), or create your own custom modules.

Related topics

- [第 1.3 节 “Concept: Themes”](#)
- [第 1.4 节 “Concept: Distributions”](#)
- [第 4.4 节 “Uninstalling Unused Modules”](#)
- [第 11.1 节 “Finding Modules”](#)
- [第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#)
- [第 13.3 节 “Concept: Security and Regular Updates”](#)
- [第 13.6 节 “Updating a Module”](#)

Additional resources

[Drupal.org community documentation page "Module developer's guide"](#)

Attributions

Written by [Jennifer Hodgdon](#).

1.3. Concept: Themes

Prerequisite knowledge

[第 1.1 节 “Concept: Drupal as a Content Management System”](#)

What is a Theme?

A theme is a set of files that define the visual look and feel of your site. The core software and modules that run on your site determine which content (including HTML text and other data stored in the database, uploaded images, and any other asset files) is displayed on the pages of your site. The theme determines the HTML markup and CSS styling that wraps the content.

The core software provides several basic themes with the core distribution. These themes have largely been designed and built by the community over the last several years and will all be good choices for building your first sites and becoming more familiar with how the core software works.

Drupal is a well-established CMS so the market for 3rd party themes - both free and paid - is very robust.

If none of the 3rd party options suit your needs, you'll need to create a custom theme. A custom theme can be as simple as a single CSS file that adds styling to the markup provided by the core software. Guidance for creating custom themes in Drupal 8 can be found in the [Drupal.org community documentation page "Theming Drupal"](#).

Related topics

- [第 11.4 节 “Finding Themes”](#)
- [第 11.5 节 “Downloading and Installing a Theme from Drupal.org”](#)
- [第 1.2 节 “Concept: Modules”](#)

Additional resources

[Drupal.org community documentation page "Theming Drupal"](#)

Attributions

Written and edited by [John Grubb](#) and [Jennifer Hodgdon](#).

1.4. Concept: Distributions

Prerequisite knowledge

- [第 1.1 节 “Concept: Drupal as a Content Management System”](#)
- [第 1.2 节 “Concept: Modules”](#)
- [第 1.3 节 “Concept: Themes”](#)

What are Distributions?

Distributions provide site features and functions for a specific type of site as a single download containing the core software, contributed modules, themes, and pre-defined configuration. A distribution makes it possible to set up a complex, use-specific site in fewer steps than installing and configuring elements individually.

There are two main types of distributions:

Full-featured Distributions

A full-featured distribution is a project that provides a complete solution to set up a site for a specialized purpose such as academic, business, government, nonprofit, publishing, social, etc. For example, you could use an existing distribution for farmers markets to build your own website, or you could share your set-up for the farmers market site as a distribution for others to use.

Other Distributions

Distributions can also be quick-start tools that developers and site builders can use as a starting point.

Related topics

[第 14.1 节 “Connecting with the Community”](#)

Additional resources

[Drupal.org Drupal Distribution Downloads](#)

Attributions

Adapted and edited by [Diána Lakatos](#) and [Antje Lorch](#), from "[Distributions](#)" and "[Download & Extend - Distributions](#)" copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

1.5. Concept: Types of Data

What are the types of data?

The data and information on your site is divided up into four types, which are edited, translated, and stored differently. These four types are:

Content

Information (text, images, etc.) meant to be displayed to site visitors. This type of information tends to be relatively permanent, but can normally be edited.

Configuration

Information about your site that is not content, but is also relatively permanent, and is used to define how your site behaves or is displayed. It is sometimes also displayed to site visitors, but tends to be smaller pieces of text (like field labels, the name of your site, etc.) rather than larger chunks that you'd normally think of as Content.

State

Information of a temporary nature about the current state of your site, such as the time when cron jobs were last run.

Session

Information about individual site visitors' interactions with the site, such as whether they are logged in and their cookies. This is technically a subtype of State information, since it is also temporary.

Related topics

- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 13.1 节 “Concept: Cron”](#)
- [第 7.1 节 “Concept: Users, Roles, and Permissions”](#)
- [第 10.1 节 “Concept: User Interface, Configuration, and Content translation”](#)

Attributions

Adapted by [Jennifer Hodgdon](#) from "[Overview of Configuration \(vs. other types of information\)](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#)

1.6. Concept: The Drupal Project

Prerequisite knowledge

[第 1.1 节 “Concept: Drupal as a Content Management System”](#)

What is Free and Open Source Software?

Free and Open Source Software (FOSS) is software that is developed by a community of people, released under a non-commercial license, and whose source code (the program files that make up the software) is freely available. For more information on the non-commercial license used by Drupal, see [第 1.7 节 “Concept: Drupal Licensing”](#).

What is the Drupal project?

The Drupal project is a FOSS project whose purpose is to develop the core content management system software, as well as add-on modules, additional themes, translations, documentation, and special-purpose distributions. The people who contribute their time and money to the Drupal project come from all over the world, and are a diverse community that comes together for this common purpose.

The community encompasses many smaller groups who perform many different tasks such as developing a particular piece of Drupal-related software, writing documentation, maintaining the security of Drupal software, translating Drupal software into a particular language, using Drupal for some specific purpose, and coming together to meet in person within a particular geographical area.

For more on how you can connect to and communicate with the world-wide community, see [第 14.1 节 “Connecting with the Community”](#) and [第 14.2 节 “Getting Support”](#).

What is the Drupal Association?

The [Drupal Association](#) is a non-profit organization dedicated to supporting the Drupal project and community. Its main functions are:

- Putting on large conventions around the world
- Maintaining the Drupal.org websites and the servers that they run on
- Promoting Drupal as a web platform
- Supporting Drupal education and training
- Providing grants to the Drupal community in support of its mission
- Raising funds for these purposes

Related topics

- [第 1.7 节 “Concept: Drupal Licensing”](#)

- [第 13.3 节 “Concept: Security and Regular Updates”](#)
- [第 14.1 节 “Connecting with the Community”](#)
- [第 14.2 节 “Getting Support”](#)

Additional resources

- [Drupal project governance](#)
- [Drupal Code of Conduct](#)

Attributions

Written by [Jennifer Hodgdon](#).

1.7. Concept: Drupal Licensing

Prerequisite knowledge

[第 1.1 节 “Concept: Drupal as a Content Management System”](#)

What is Drupal Licensing?

Drupal and all contributed files hosted on Drupal.org are licensed under the GNU General Public License (GPL), version 2 or later. That means you are free to download, reuse, modify, and distribute any files that are part of a project on Drupal.org under the terms of GPL version 2 or 3. You can also run the core software in combination with any code with any license that is compatible with version 2 or 3.

Drupal contributors should follow these guidelines:

- All files (PHP, JavaScript, images, Flash, etc.) that are part of a project on Drupal.org have to be under GPL version 2 or later.
- All Drupal contributors retain copyright on their code, but agree to release it under the same license as Drupal.
- Drupal modules and themes are a derivative work of Drupal. If you distribute them, you must do so under the terms of GPL version 2 or later.
- All content on Drupal.org itself is copyrighted by its original contributors, and is licensed under the Creative Commons Attribution-ShareAlike license 2.0.
- Sample code on Drupal.org is also available under GPL version 2 or later.

Related topics

[第 14.1 节 “Connecting with the Community”](#)

Additional resources

- [Drupal.org page on "Licensing"](#)
- ["Drupal 8 LICENSE.txt" page on api.drupal.org](#)
- [GNU General Public License, version 2](#)
- [GNU General Public License, version 3](#)
- [Creative Commons Attribution-ShareAlike license 2.0.](#)
- ["Legal Group" on groups.drupal.org](#)

Attributions

Adapted by [Diána Lakatos](#) at [Pronovix](#) from "[Licensing](#)" copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

第 2 章 Planning Your Site

2.1. Concept: Regions in a Theme


Prerequisite knowledge

[第 1.3 节 “Concept: Themes”](#)

What is a region?

Besides its primary content, a web page contains other content such as site branding (site name, slogan, and logo), navigation aids (menus, links, and icons), formatted text, and images. Each theme provides a set of named regions, such as Header, Content, and Sidebar, where site builders may choose to place their content.

The available regions depend on the theme design. Only the Content region, which contains the primary content, is required; others are optional. The core Bartik theme provides the eighteen regions highlighted in the following image.



Related topics

- [第 8.1 节 “Concept: Blocks”](#)
- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 8.3 节 “Placing a Block in a Region”](#)

Additional resources

- [Drupal.org community documentation page "Assigning content to regions"](#)

Attributions

Written and edited by [John MacDonald](#), and [Michael Lenahan](#) at [erdfisch](#).

2.2. Planning Your Site Layout

Goal

Plan the navigation and layout of the site, for both mobile and desktop browsers.

Prerequisite knowledge

- [第 1.3 节 “Concept: Themes”](#)
- [第 2.1 节 “Concept: Regions in a Theme”](#)
- [第 i.6 节 “Guiding Scenario”](#)

Steps

It is a good idea to plan the site layout before you start building the site and writing content; however, your plan may need to be revised either before you start implementing it or after you have some of the site built with draft content in place, based on budgetary concerns or stakeholder feedback.

1. Make a list of the information that your site should present to visitors. In the farmers market scenario, this might include:
 - Location of the market, with directions and a map
 - Hours and days the market is open
 - History of the market
 - List of vendors
 - Details about each vendor
 - Searchable list of recipes
 - Details about each recipe
 - List of the most recently added recipes
2. Decide which information should be on which pages or types of pages on the site:

Information that should be on all pages

Address, hours, and recently-added recipes list

Vendor details pages

Information about each vendor on its own page

Recipe details pages

Details of each recipe on its own page

Home page

Location, map, directions, and hours

About page

History of the market

Vendors list page

List of vendors, with links to vendor detail pages

Recipe list page

Searchable list of recipes, with links to recipe detail pages

3. Decide which information is the most important on each page. Site visitors using mobile phones or other small browsers will often only see the content that is presented first, and they may not scroll down to see all of the information.
4. Decide which of these pages should appear in the main site navigation. For instance, the main navigation might consist of the Home, About, Vendors, and Recipes pages.
5. Make a rough design sketch for each page, showing how it would look when viewed on a small screen such as a phone, as well as on a larger screen such as a desktop browser. Considering that most site visitors will be using smaller browsers, it is a good idea to start with the phone-size layout, to make sure that these visitors will be able to find the information they need without too much scrolling.

In making these page layout plans, you might find that you need to revise your plan for which information should be on which pages. For example, you might decide that the address, hours, and recently-added recipes list would all fit well in the right sidebar area of all pages, when the site is viewed on desktop-sized browsers. On the other hand, you might decide that for mobile browsers, you would instead put the address and hours in a short format at the top of each page, but only display the recent recipe list at the bottom of the home page.

Expand your understanding

[第 2.5 节 “Planning your Content Structure”](#)

Attributions

Written by [Jennifer Hodgdon](#).

2.3. Concept: Content Entities and Fields

Prerequisite knowledge

- [第 1.5 节 “Concept: Types of Data”](#)
- [第 1.2 节 “Concept: Modules”](#)

What is a content entity?

A content entity (or more commonly, entity) is an item of content data, which can consist of text, HTML markup, images, attached files, and other data that is intended to be displayed to site visitors. Content entities can be defined by the core software or by modules.

Content entities are grouped into entity types, which have different purposes and are displayed in very different ways on the site. Most entity types are also divided into entity sub-types, which are divisions within an entity type to allow for smaller variations in how the entities are used and displayed. Here is a table of some common content entity types:

Entity type	Entity sub-type	Defining Module	Main uses
Content item	Content type	Node module	Content intended to be the main page area for pages on the site
Example: In the farmers market site example, you might have content types for basic pages, vendor pages, and recipe pages.			
Comment	Comment type	Comment module	Commentary added to content entities (typically to Content item entities)
Example: On a blog site, blog posts might have comments. They are not needed in the farmers market site example.			
User profile	(none)	User module	Data related to a person with a user account (login access) on the site
Example: Every site has at least basic user profiles with user names and email addresses; social networking sites may have more complex user profiles with more information.			
Custom block	Block type	Custom Block module	Text and images in smaller chunks, often displayed in

Entity type	Entity sub-type	Defining Module	Main uses
			the site header, footer, or sidebar
Example: In the farmers market site example, you might put the hours and location in a sidebar block.			
Taxonomy term	Vocabulary	Taxonomy module	Used to classify other types of content
Example: In the farmers market site example, you might classify Recipe content with an Ingredients taxonomy vocabulary, with taxonomy terms like Carrots and Tomatoes. In a blogging site, blog posts might be classified using a Tags vocabulary, and perhaps also a Categories vocabulary.			
File	(none)	File module	An image or attachment file that is tracked and managed by the site, often attached to other types of content
Example: In the farmers market site example, both Recipe and Vendor pages might have image attachments, which would (behind the scenes) be managed as File entities by the site.			
Contact form	Form type	Contact module	A form that lets site visitors contact site owners
Example: A contact form is needed in the farmers market site example.			

What is a field?

Within entity items, the data is stored in individual fields, each of which holds one type of data, such as formatted or plain text, images or other files, or dates. Field types can be defined by the core software or by modules.

Fields can be added by an administrator on entity sub-types, so that all entity items of a given entity sub-type have the same collection of fields available. For example, the Vendor content type in the farmers market example might have fields for the vendor name, a logo image, website URL, and description, whereas the Basic page content type might only have fields for the title and page body. When you create or edit entity items, you are specifying the values for the fields on the entity item.

Related topics

- 第 2.5 节 “Planning your Content Structure”

- [第 5.2 节 “Creating a Content Item”](#)
- [第 6.1 节 “Adding a Content Type”](#)
- [第 6.5 节 “Concept: Taxonomy”](#)
- [第 7.1 节 “Concept: Users, Roles, and Permissions”](#)
- [第 8.1 节 “Concept: Blocks”](#)

Attributions

Written and edited by [Jennifer Hodgdon](#) and [Grant Dunham](#).

2.4. Concept: Modular Content

Prerequisite knowledge

- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 2.2 节 “Planning Your Site Layout”](#)

What is modular content?

Given that the content of your site is stored in a database, it is desirable to make the content modular, meaning that certain pages on your site, rather than being edited as a whole page, are instead generated automatically from other content items. For instance, in the farmers market site scenario, you might create individual content items for recipes. If the recipe content items have a field that keeps track of ingredients, then your site could include a composite page that would list recipes, and allow visitors to search for a recipe that contained some particular ingredient they had bought at the market.

Smaller sections of pages can also be generated as composites. For instance, recipe content items could have a field that keeps track of which vendor submitted the recipe (see [第 6.4 节 “Concept: Reference Fields”](#)), with the vendor details edited in separate vendor content items. This would allow you to do the following on your site:

- On each Recipe page, there could be an area that displays some information about the vendor that submitted the recipe, such as their name and market stall number.
- Each vendor page could have a section that lists the recipes they have submitted.

The key idea is that each piece of information is only edited in one place. When vendor information is updated, all recipe pages that display that vendor information are automatically updated; when a recipe is submitted by a vendor, it is automatically displayed on the vendor page. The core Views module is the usual way to use modular content to create composite pages and page sections; see [第 9.1 节 “Concept: Uses of Views”](#) for more information. Also, view modes are useful for defining different ways

to display each content item; see [第 6.10 节 “Concept: View Modes and Formatters”](#) for more information.

Related topics

- [第 2.5 节 “Planning your Content Structure”](#)
- [第 6.1 节 “Adding a Content Type”](#)
- [第 6.3 节 “Adding Basic Fields to a Content Type”](#)
- [第 6.4 节 “Concept: Reference Fields”](#)
- [第 6.10 节 “Concept: View Modes and Formatters”](#)
- [第 9.1 节 “Concept: Uses of Views”](#)

Attributions

Written by [Jennifer Hodgdon](#).

2.5. Planning your Content Structure

Goal

Make a plan for the content structure of the site (which type and subtype of entity to use for which content), and which pages will contain listings of content.

Prerequisite knowledge

- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 2.4 节 “Concept: Modular Content”](#)
- [第 i.6 节 “Guiding Scenario”](#)

Steps

1. Brainstorm about what content your site needs to contain, which could include content that visitors would be looking for, as well as content that you want to show to visitors. The result could be the description in [第 i.6 节 “Guiding Scenario”](#).
2. For each identified piece of content, decide which content entity type would be the best fit. In doing this, you'll need to consider where and how the content will be used and edited on the site. For example, in the farmers market site scenario, you might want to display the hours and location of the farmers market on the sidebar of every page. For that content, a single custom block makes sense. As another example, you might decide that pages displaying information about each

vendor should be content items managed by the core Node module, because you want vendors to be able to edit their own listings. The core Node module permission system lets you do this easily.

These decisions do not necessarily always have only one right answer; for instance, you could decide that vendor pages should be user profiles instead of content items, but if you did that the content would be tied to a specific user account, and it would not be as easy to later change the ownership of a vendor page to a different user account.

3. Within each content entity type you identified, decide what division into entity sub-types would make sense. For example, in the farmers market site example, you would probably decide that under the Content item entity type, there should be one content type for basic pages (Home and About), one for vendor pages, and one for recipe pages.
4. For each entity sub-type you decided on, decide what fields are needed. For instance, the Vendor content type might need fields for the vendor name, web page URL, image, and description.
5. Decide on what entity listings are needed, which could be entire pages or smaller areas on the page. For each listing, you'll need to determine what entity items should be listed. Then you'll need to decide in what order and with what filtering options they should be displayed; for example, you might want to give the site visitor the option to search by keyword, to filter the list down to a subset, or to sort the list. You'll also need to decide what information from the entity items should be shown, which might result in adding to the list of fields you determined in the previous step. The farmers market site, for example, needs to have a Recipes listing page that lists content items of type Recipe, with the ability to filter by ingredients, so that means that the Recipe content type needs an Ingredients field.
6. For each identified field on each entity subtype, identify what type of data it should contain (such as plain text, formatted text, a date, an image file, etc.), and how many values should be allowed. Most fields are single-valued, but for example, a Recipe should allow for multiple values in its Ingredients field.
7. Consider which fields would be best as references to taxonomy term entities: fields whose values should be chosen from a list of allowed values. Allowed values that are expected to change and grow over time, are good candidates. An example is the Ingredients field for the Recipe content type.
8. Consider which fields should reference other content entities. An example is that since vendors will be submitting recipes, a field will be needed on the Recipe content type that references the Vendor content item for the vendor who submitted the recipe.

Here's an example of the resulting content structure for the farmers market scenario example site:

Entity type	Entity sub-type	Examples	Fields
Content item	Basic page	Home page, about page	Title, page body

Entity type	Entity sub-type	Examples	Fields
Content item	Vendor	A page for each vendor at the market	Vendor name, page body, image, URL
Content item	Recipe	A page for each submitted recipe	Recipe name, page body, image, reference to Vendor who submitted it, Ingredients taxonomy
Custom block	(generic)	Copyright notice for footer, Hours and location for sidebar	No special fields
Taxonomy term	Ingredients	Carrots, tomatoes, and other recipe ingredients	No special fields
Contact form	(generic)	Generic contact form	Name, email, subject, message
User profile	(none)	Will not be displayed on site	No special fields

And here are the listings the site needs:

Page or page area	Entity type and sub-type	Filter/sort/pagination	Fields displayed
Vendors page	Vendor content items	All vendors, alphabetical, paged	Image, vendor name, trimmed body
Recipes page	Recipe content items	Filter by ingredients, alphabetical, paged	Image, recipe name
Recent recipes sidebar	Recipe content items	List 5 most recent	Image, recipe name

Expand your understanding

- [第 6.1 节 “Adding a Content Type”](#)
- [第 6.3 节 “Adding Basic Fields to a Content Type”](#)
- [第 6.6 节 “Setting Up a Taxonomy”](#)

Related concepts

[第 6.5 节 “Concept: Taxonomy”](#)

Attributions

Written and edited by [Jennifer Hodgdon](#) and [Grant Dunham](#).

2.6. Concept: Editorial Workflow

Prerequisite knowledge

[第 1.1 节 “Concept: Drupal as a Content Management System”](#)

What is an Editorial Workflow?

An Editorial Workflow is the process organizations follow to create, review, edit and publish content.

Depending on the size and processes of the organization, multiple people in different roles can be part of the process. For example, content creators collect information and write content, editors review, edit, ask for changes, and publish the content once it's considered ready to be shared with the audience.

In your site, content types can have either a Published or an Unpublished flag to track their workflow states, that you can set for each content item when saving:

- Published content items are visible to all visitors of the site.
- Unpublished content items are not visible to the visitors of the site, but can be seen by authenticated users who have the permissions to view unpublished versions of specific content items.

Most content entity types support revision tracking, if it is enabled by an administrator for the entity sub-type. If you have revision tracking enabled, the software will store old versions of the content each time it's revised, and add notes about what is changed. This allows you to look at the history and revert to older versions.

Using the Unpublished flag and Revisions, you can build an editorial workflow that lets content creators and editors work on the live site without displaying the content to visitors. When the content is ready to be published, all they need to do is save it as Published.

Related topics

- [第 5.2 节 “Creating a Content Item”](#)
- [第 5.3 节 “Editing a Content Item”](#)

Additional resources

Talking about online content, organizations would also want to consider post-publication phases of the editorial workflow: content teams might need to update already published content. Some organizations might need a more complex workflow with the options to configure which content type goes through the workflow process, set up user roles and permissions, set different workflow states (for example draft, needs review, published).

For more complex workflows, you can add install or more modules from the [contributed Workbench Suite module](#) to your site.

Attributions

Written and edited by [Diána Lakatos](#) at [Pronovix](#), and [Grant Dunham](#).

第 3 章 Installation

3.1. Concept: Server Requirements

What are the requirements for running the core software?

Disk space

A minimum installation requires 15 MB. 60 MB is needed for a website with many contributed modules and themes installed. Keep in mind you need much more for the database, files uploaded by the users, media, backups, and other files.

Web server

Apache (Recommended)

Apache is the most commonly used web server. The core software will work on Apache 2.x hosted on UNIX/Linux, OS X, or Windows that have the Apache mod_rewrite module installed and enabled. The Apache VirtualHost configuration must contain the directive AllowOverride All to allow the .htaccess file to be used.

Nginx

Nginx is a commonly used web server that focuses on high concurrency, performance and low memory usage. The core software will work on Nginx 1.1 or greater hosted on UNIX/Linux, OS X, or Windows. The ngx_http_rewrite_module must be installed and enabled.

Hiawatha

Hiawatha is a web server with a strong focus on security. It also aims at being easy to use and lightweight. Research performed by independent researchers proves that Hiawatha offers a performance comparable to other web servers under normal conditions, but much better while under attack. URL Toolkit must be installed and configured to rewrite URLs.

Microsoft IIS

Microsoft IIS is a web server and set of feature extension modules for use with Microsoft Windows. The core software will work with IIS 5, IIS 6, or IIS 7 if PHP is configured correctly. Because clean URLs are required, you may need to use a third party product. For IIS 7, you can use the Microsoft URL Rewrite module or a third party solution.

Database

Use one of the following databases:

- MySQL - 5.5.3 (MariaDB 5.5.20, Percona 5.5.8) or higher with an InnoDB-compatible primary storage engine
- PostgreSQL - 9.1.2 or higher
- SQLite - 3.4.2 or higher

PHP

PHP 5.5.9 or higher.

Additional resources

[Drupal.org community documentation page "System requirements"](#)

Attributions

Adapted by [Karl Kedrovsky](#) and [Brian Emery](#) from ["System requirements"](#), copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

3.2. Concept: Additional Tools

What tools are available for site builders?

There are several additional tools available that help you create sites faster, more accurately and with less effort.

Drush

See below for more about Drush.

Git

[Git](#) is a version control system you can use to track changes made to files within your entire site, or files relating only to the module or theme that you are using. Git makes it possible to try out changes, and if necessary, revert to a previous version. It can be used as well to track changes in the configuration files and synchronize the configuration of different sites. Git has become the standard for web development projects.

Composer

See below for more about Composer.

Devel

The [contributed Devel module](#) helps with development tasks such as debugging and inspecting code, analyzing database queries, and generating dummy content.

What is special about Drush?

[Drush](#) is a command-line tool for building and maintaining sites, providing an alternative to using the administrative interface for many operations. Many site builders and maintainers prefer to use Drush whenever possible, and consider the time spent installing and learning to use Drush to be a good investment. Reasons to consider using Drush:

- Drush provides a large number of commands for tasks such as installing the base software, modules, and themes; updating software; performing database operations, including copying and querying; resetting passwords; and clearing the cache. Some contributed modules and themes also define Drush commands.
- Doing administrative tasks using Drush is typically faster and less tedious than performing the same tasks through the administrative interface.
- Since Drush is a command-line interface, you can write scripts that combine Drush commands and other commands on the server, to automate more complicated tasks.
- Drush provides additional functionality not available via the administrative interface; for example, running database queries.

If you want to use Drush, you will need to have command-line terminal access to the server where your website will be hosted, and you will need to have a compatible version of the Drush tool installed on that server. Check the [Drush website](#) for installation instructions and version compatibility. There is also documentation on the available Drush commands on that site.

What is Composer used for?

[Composer](#) is a tool for managing PHP dependencies, where the developer specifies what version of each external library is needed, and Composer manages the process of downloading and installing the libraries.

The core software is a primary user of Composer, because it makes use of several externally-developed software libraries, which must be downloaded and installed in order for the core software to work. When you install the core software, you either need to download an archive that contains compatible versions of the external libraries, or you need to run Composer to download the external libraries after the initial download.

Some contributed modules also make use of externally-developed software libraries; for example, a Facebook integration module might require Facebook's integration library to be installed for the module to work, and a geographical module might make use of a standard library of geographical functions. To install a module with external dependencies, you will need to run Composer.

What tools are available for module and theme developers?

In addition to the site builder tools mentioned above, the following tools are useful for module and theme developers.

Drupal Console

[Drupal Console](#) is a command-line tool that generates boilerplate code and interacts with a Drupal site. It can generate, for example, block or form code, install modules and themes, and create dummy content. Drupal Console makes use of the Symfony Console.

Coder

[Coder](#) is a command-line tool that checks if your modules and themes comply with coding standards and other best practices. It can also fix coding standard violations.

Firebug

[Firebug](#) is a Firefox plugin that allows viewing, editing, debugging, and monitoring CSS, HTML, and JavaScript in a separate browser window. The [contributed Drupal for Firebug module](#) displays Drupal debugging and SQL query information in the Firebug window.

Related topics

[第 11.9 节 “Using Composer and Git to Download Files”](#)

Additional resources

- [Drupal.org community documentation page "Development tools"](#)
- [Drupal.org community documentation page "Using Composer with Drupal"](#)

Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

3.3. Preparing to Install

Goal

Choose an appropriate way to install the core software, and handle any required prerequisites.

Prerequisite knowledge

- [第 3.1 节 “Concept: Server Requirements”](#)
- [第 3.2 节 “Concept: Additional Tools”](#)

Site prerequisites

If you want to use Drush to install the core software, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

Steps

1. Choose a method for installing the core software.

Try a free online demo

Use an online provider to get a demo installation of the core software in 20 minutes or less. See the [Drupal.org page "Try Drupal"](#).

Use a one-click installer from your hosting provider

If you choose to install the core software at your hosting provider, your hosting provider may have specific documentation and/or a one-click install that you can use. See [Drupal.org's list of hosting providers that support Drupal](#).

Use Drush

You will need to have Drush installed and command-line access to the site. See [第 3.2 节 “Concept: Additional Tools”](#).

Use the web installer

You will need space on a local or hosted web server to install the core software manually.

Use a pre-configured environment

Use a pre-configured environment or virtual machine that contains Drupal and all the required supporting software to install Drupal locally. See the section for your operating system under [Drupal.org's Local server setup guide](#) for possible options.

2. If you are installing using Drush or the web installer, set up a URL and hosting for your site, either at an external hosting provider or on your own computer. Verify that the hosting is working by putting a simple HTML file in the web root directory of the hosting, and visiting the URL for your site.
3. If you are installing using Drush or the web installer, create a database, along with a database user account with full access.
4. If you are installing using Drush, type the following at the Drush command line, where example is the name of the directory that the core software will be downloaded to, and DB_NAME, DB_USER and DB_PASS are your database's credentials:

```
drush dl drupal --drupal-project-rename=example
```

```
cd example
```

```
drush site-install standard --db-url='mysql://DB_USER:DB_PASS@localhost/DB_NAME'
```

5. If you are installing using the web installer, upload the core software files manually. To do this using Git and/or Composer, see [第 11.9 节 “Using Composer and Git to Download Files”](#); to do this by downloading a zipped archive:

- a. Go to <https://www.drupal.org> and click Download & Extend on the top-level menu.

Download & Extend

Download

[Download Drupal 8.1.10](#)

[Try a hosted Drupal demo](#)

See [Drupal's project page](#) for more information, older versions, and project development. Explore hosting options for your site. Browse [documentation](#) for more help and information.

- b. Click the Download Drupal button (of the appropriate version) to be taken to the Downloads page.

Downloads

Recommended releases

These are stable, well-tested versions that are actively supported.

Drupal core 8.1.4

Released: Jul 06 2016

The next patch release of Drupal 8 is ready for new development and use on production sites.

Drupal core 7.44

Released: Jun 15 2016

If you need stability and features from the widest variety of contributed modules and themes, this is the version for you.

- c. Click the version you wish to download under Recommended releases.

Releases

drupal 8.1.3

[Download
drupal-8.1.3.tar.gz
tar.gz](#)

11.97 MB

[Download
drupal-8.1.3.zip
zip](#)

19.55 MB

- d. Download the tar.gz or zip file to your local machine.
- e. Upload the downloaded file to your hosting account. Log in to the control panel and navigate to the HTML directory. Save the file there.
- f. Uncompress the tar.gz or zip file, which will create a new directory. If you do not have terminal access, or your hosting server is not running Linux, your hosting control panel's file manager should provide a way to extract the files. If you have terminal access to your hosting server (running Linux), you can use a command like:

```
tar -xzf drupal-8.3.2.tar.gz
```

- g. Delete the compressed file from the server, unless your unpacking method already deleted it.
- h. Rename the directory or reconfigure your web hosting, so that the directory name matches the directory your web hosting is configured to use for your site.

Expand your understanding

Run the installer if you chose web installer to install the core software. See [第 3.4 节“Running the Installer”](#).

Additional resources

[Drush](#)

Attributions

Written and edited by [Drew Gorton](#), [Michael Lenahan](#) at [erdfisch](#), [Jennifer Hodgdon](#), and [Jojo Alphonso](#) at [Red Crackle](#).

3.4. Running the Installer

Goal

Install the core software and create the admin account by running the included installer.

Prerequisite knowledge


[第 3.1 节“Concept: Server Requirements”](#)

Site prerequisites

[第 3.3 节“Preparing to Install”](#)

Steps

1. If you are using a 1-click install from a hosting provider or demo site, you will most likely see some or all of the following screens as part of the installation process. If you uploaded the core files manually, to start the installer, open a browser and visit the URL that you set up for your hosting.
2. Select a language on the first page of the installer; for example, English. You could optionally choose from any of the other listed languages. The language files for the chosen language will be downloaded and installed so that the rest of the installation process can be finished in the chosen language. After choosing a language, click Save and continue.



3. Select an installation profile. Installation profiles provide site features and functions for a specific type of site as a single download containing the core software, contributed modules, themes, and pre-defined configuration. Core contains two installation profiles. Select the core Standard installation profile. Click Save and continue.




4. The next step in the installer will verify that your system meets the minimum requirements. If it does not, you'll be presented with an outline of what needs to be corrected in order to proceed. If it does, the installer will automatically advance to the next step.
5. Provide details of the database you created in the [第 3.3 节 “Preparing to Install”](#) chapter. Then click Save and continue.

Field name	Explanation	Value
Database name	The custom name given to the database	drupal18
Database username	Username created	databaseUsername
Database password	Password chosen	



6. The next step will display a progress bar under the heading *Installing Drupal*. After the installer has completed, it will automatically advance to the next step.



7. The final step is to configure some basic information about your new site. Note that the user account you create in this step is the site's admin account. See [第 7.2 节 “Concept: The User 1 Account”](#) for important information about this unique account. You can safely name this account "admin", and make sure to choose a secure and unique password.

Fill in the form with the following information:

Field name	Explanation	Value
Site name	The name chosen for the site	Anytown Farmers Market
Site email address	The email associated with the site	info@example.com
Username	The designated user's credentials	admin
Password	The password chosen	
Confirm password	Repeat the password	
Email address	The user's email	admin@example.com

The remaining fields can likely be left at their default values.

Drupal 8.0.0

选择语言

选择安装配置文件

检查安装需求

设置数据库

安装网站

安装翻译

设置网站

完成翻译

设置网站

✓ 导入了一个翻译文件。添加了 5701 条翻译，更新了 0 条翻译，删除了 0 条翻译。

站点信息

站点名称 *

站点的email地址 *

系统自动发出的电邮，如注册信息，将会被送到这个地址。使用您以网站网址为结尾的地址可避免该邮件被当作垃圾邮件处理。

站点维护帐号

用户名 *

可以使用下列特殊字符：空格、点(.)、连字符(-)、单引号(')，下划线(_)以及@符号。

密码 *

密码强度： 强

确认密码 *

密码匹配： 是

电子邮件地址 *

区域设置

默认国家

中国 ▾

为站点选择它的国家。

默认时区

Asia/Shanghai ▾

网站日期会以默认所选择的时区来呈现。

更新通知

更新通知

自动检查更新

接收电子邮件提醒

当已安装的组件有可用更新和重要安全发布时，系统将会通知您。系统会向 [Drupal.org](#) 发送关于您站点的匿名统计信息。

保存并继续

32

8. Click Save and continue.
9. You will be redirected to the front page of your new site and you should see the message Congratulations, you installed Drupal! displayed at the top of the page.



Expand your understanding

Check the Status Report to see if there are any problems with the installation. See [第 12.5 节 “Concept: Status Report”](#).

Related concepts

- [第 11.7 节 “Concept: Development Sites”](#)
- [第 3.2 节 “Concept: Additional Tools”](#)

Additional resources

[Drupal.org community documentation page "Create A Database"](#)

Attributions

Written and edited by [Joe Shindelar](#) at [Drupalize.Me](#), and [Jojo Alphonso](#) at [Red Crackle](#).

第 4 章 Basic Site Configuration

4.1. Concept: Administrative Overview

Prerequisite knowledge

- [第 1.3 节 “Concept: Themes”](#)
- [第 1.2 节 “Concept: Modules”](#)

What is the administrative menu?

The toolbar provided by the core Toolbar module displays the Manage administrative menu at the top or left side of the site, for users with permission to see it. This menu provides access to all of the administrative areas of the site. The menu entries will vary depending on which modules are active on your site and the permissions of the person viewing the menu; if you install using the core Standard installation profile and have full administrative permissions, the top-level entries are as follows:



Content

Lists and manages existing content, and allows creation of new content.

Structure

Contains a list of links for managing structural elements of the site, such as blocks, content types, menus, and taxonomy.

Appearance

Manages themes and appearance-related settings.

Extend

Manages the installation and uninstallation of modules.

Configuration

Contains links to settings pages for various site features.

People

Manages users, roles, and permissions.

Reports

Contains links to logs, update information, search information, and other information about the site's status.

Help

Lists help topics for installed modules that provide them.

The arrow button on the far right side of the second line of the toolbar (or far left side, if the site is being viewed using a right-to-left-reading language like Arabic) can be used to switch the menu from appearing horizontally at the top of the page, to a vertical format on the left side (or right side, in right-to-left languages). When viewed vertically, the menu becomes an interactive tree.



内容



结构



外观

扩展

配置



人员

报告



可用更新

最新日志信息

可用的翻译更新

字段列表

最常见“拒绝访问”错误

最常见的“没有找到页

This guide has a standard way to describe navigation to administrative pages using the administrative toolbar. See [第 i.5 节 “Conventions of the Guide”](#) for more information.

What are contextual links?

Some administrative and editing functionality on the site can be accessed through the contextual links displayed by the core Contextual Links module. Contextual links take

you to some of the same pages that you can access through the administrative menu, but instead of having to navigate through the menu hierarchy, these links are provided near where the related content is displayed on your site.

Contextual links have to be activated to be visible. If your site's theme uses the default styling for contextual links, a pencil icon is used to indicate that contextual links are present and activated, and if you click the icon, you will see the contextual links. There are two ways to activate the pencil icons that provide access to the contextual links:

- If you are using a mouse in a browser, the icon will temporarily appear when you hover over an area that has related contextual links.
- You can click the master pencil icon (or its Edit link) at the right end of the top bar in the toolbar, which will activate all of the contextual links on the current page. This icon is only visible on pages with contextual links.



Attributions

Written by [Scott Wilkinson](#) and [Jennifer Hodgdon](#).

4.2. Editing Basic Site Information

Goal

Change basic site information such as Site name, Slogan, Default time zone.

Prerequisite knowledge

[第 4.1 节 “Concept: Administrative Overview”](#)

Steps

Configuring the basic site information

1. In the Manage administrative menu, navigate to Configuration > System > Basic site settings (admin/config/system/site-information) to change the Site name, Slogan, administrative Email address, or the Default front page path.
2. Fill in the available fields as appropriate for your site.

Field name	Explanation	Example value
Site name	Used to identify the site and displayed in browsers	Anytown Farmers Market
Slogan	Usually displayed sitewide	Farm Fresh Food
Email address	Used as From address in automated email messages (registrations, password resets, etc)	info@example.com

▼ 站点详情

站点名称 *
爱林镇农贸市场

站点口号
农场新鲜食材

如何使用基于你的站点主题。

电子邮件地址 *
info@example.com

在注册、请求新密码或其他通知时自动发送的电子邮件，将会使用这一邮件地址作为 *From* 的地址。（使用以您网站域名结尾的地址有助于将类似的电子邮件排除在垃圾邮件之外。）

3. After editing the fields, click Save configuration to see the changes applied to the site.

Configuring default Regional settings

1. In the Manage administrative menu, navigate to Configuration > Regional and language > Regional settings (admin/config/regional/settings).
2. Select the appropriate country from the Default country select list in the Locale section, and set which day will be displayed as First day of week on your site.
3. In the Time zones section, select the sitewide Default time zone from the list and configure user-specific time zones.

本地化

默认国家
中国 |▼

一周的第一天
星期日 |▼

时区

默认时区
Asia/Shanghai |▼

用户可以设置他们自己的时区

在登录时提醒用户他们的时区尚未设置
仅用于那些没有设置时区的用户。

新用户的时区

默认时区

空时区

用户可以在注册时自行设置他们的时区
仅用于那些没有设置时区的用户。

保存配置

- After editing the fields, click Save configuration to see the changes applied to the site.

Additional resources

[Drupal.org community documentation page "Getting started with Drupal 8 administration"](#)

Attributions

Written and edited by [Sree Veturi](#), [Michael Lenahan](#) at [erdfisch](#), and [Antje Lorch](#).

4.3. Installing a Module

Goal

Install a core module, or a contributed module whose files have already been uploaded to the site, through the administrative interface or using Drush.

Prerequisite knowledge

[第 1.2 节 “Concept: Modules”](#)

Site prerequisites

If you want to use Drush to install modules, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

Steps

You can use the administrative interface or Drush to install modules.

Using the administrative interface

1. In the Manage administrative menu, navigate to Extend (admin/modules). The Extend page appears showing all the available modules in your site.
2. Check the boxes for the module or modules you want to install. For example, check the box for the core Activity Tracker module.

The screenshot shows a list of modules under the 'Extend' section. The 'Activity Tracker' module is checked, while others like 'Actions', 'Aggregator', 'Automated Cron', and 'Ban' are unchecked. Each module has a brief description next to it.

模块	描述
<input type="checkbox"/> Actions	系统中特定事件发生时执行任务。
<input checked="" type="checkbox"/> Activity Tracker	跟踪用户的最新文章。
<input type="checkbox"/> Aggregator	利用 RSS、RDF 以及 Atom 等形式聚合外部源。
<input checked="" type="checkbox"/> Automated Cron	提供一种自动运行 cron 任务的途径，在每个服务器响应结束时执行这些任务。
<input type="checkbox"/> Ban	允许屏蔽 IP 地址。

3. Click Install. The checked modules will be installed.

Using Drush

1. In the Manage administrative menu, navigate to Extend (admin/modules). The Extend page appears showing all the available modules in your site.
2. Find the machine name of the module you want to install, by expanding the information area for the module. For instance, the core Activity Tracker module's machine name is tracker.
3. Run the following Drush command to install the module:

```
drush en tracker
```

Expand your understanding

If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Additional resources

[Drush](#)

Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

4.4. Uninstalling Unused Modules

Goal

Uninstall the core Search and History modules, as well as the core Activity Tracker module if you installed it in [第 4.3 节 “Installing a Module”](#), to reduce overhead.

Prerequisite knowledge

[第 1.2 节 “Concept: Modules”](#)

Site prerequisites

- You must have at least one unused module on your site that you want to uninstall, such as the core Search module.
- If you want to use Drush to uninstall modules, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

Steps

You can use the administrative interface or Drush to uninstall modules.

Using the administrative interface

1. In the Manage administrative menu, navigate to Extend > Uninstall (admin/modules/uninstall) where you will find the list of modules that are ready to be uninstalled.
2. Check the boxes for the modules you are uninstalling (Search, History, and Activity Tracker). Click Uninstall at the bottom of the page.

卸载	名称	描述
<input checked="" type="checkbox"/>	Activity Tracker	跟踪用户的最新文章。
<input type="checkbox"/>	Automated Cron	提供一种自动运行 cron 任务的途径，在每个服务器响应结束时执行这些任务。
<input type="checkbox"/>	Block	控制构建页面区块的可见性，区块为盒状的内容容器，可以放在网页的某个地方或区域上 下列原因使得 Block 无法卸载： • 支持：Custom Block
<input type="checkbox"/>	Breakpoint	为响应式设计管理断点和断点组。 下列原因使得 Breakpoint 无法卸载： • 支持：Toolbar

注意

You cannot uninstall a module if it is required by some other module(s) and/or functionality. For example, the core File module is required by the core Text Editor, CKEditor, and Image modules. It can't be uninstalled unless

you uninstall its dependent module(s) and functionality first. A module that cannot be uninstalled yet will have a disabled checkbox, restricting you from uninstalling it.

3. Step 2 will prompt you to confirm the module uninstall request. Click Uninstall.

确认卸载 ☆

首页 » 管理 » 扩展 » 卸载

下面的模块将彻底从您的站点卸载，所有关于这些模块的数据都将丢失！

- Activity Tracker
- History
- Search

▼ 配置缺失

已列出的配置将被删除

区块

- 搜索

搜索页面

- 内容
- 用户

您希望继续并卸载以上模块吗？

卸载 **取消**

Using Drush

1. In the Manage administrative menu, navigate to Extend (admin/modules). The Extend page appears showing all the available modules in your site.
2. Find the machine name of the module you want to uninstall, by expanding the information area for the module. For instance, the core Activity Tracker module's machine name is `tracker`.
3. Run the following Drush command to uninstall the module:

```
drush pm-uninstall tracker
```

Expand your understanding

- 第 3.2 节 “Concept: Additional Tools”
- 第 12.2 节 “Clearing the Cache”

- You can also uninstall the core Comment module by following these steps, but only after comment fields have been removed, which is a side effect of [第 6.2 节 “Deleting a Content Type”](#).

Attributions

Written and edited by [Surendra Mohan](#), and [Jojo Alphonso](#) at [Red Crackle](#).

4.5. Configuring User Account Settings

Goal

Turn off the ability for people to register user accounts on the site. Also, review and/or edit the email messages generated by the site for events related to user accounts.

Prerequisite knowledge

[第 4.1 节 “Concept: Administrative Overview”](#)

Steps

1. In the Manage administrative menu, navigate to Configuration > People > Account settings (admin/config/people/accounts).
2. Under Registration and cancellation, select Administrators only as the people with permissions to register user accounts. You can check Require email verification when a visitor creates an account in case you want to change the settings for account registration later on.

▼ **注册和取消注册**

谁可以注册账户？

仅限管理员
 访客
 访客，但须要管理员批准

访客创建帐号需要电子邮件确认
新用户在第一次登录时将会被请求验证他们的电邮地址，并会被系统指派一个密码。禁用此项，用户会在注册后马上登入网站，并在注册过程中选择他们自己的密码。

启用密码强度指示器

When cancelling a user account

禁用帐户，并保留其所有内容。
 禁用此帐户并撤下其所有内容。
 删除这个帐号，把此帐号所有的内容转到 *Anonymous* 用户下。
有选择取消账户的方法或管理用户权限的用户可以覆盖默认方式。

3. Optionally, change the default email address from which user account notifications from the farmers market website will be sent. This will help you maintain a separate email address from the one used for the website in general. For example, this email address for user account notifications will be useful for a staff member(s) communicating with vendors.

通知所用电子邮件地址

用于发送下面的邮件“发送者”电邮地址。如果访客，但须要管理员批准，系统也会往这个地址发送一封提醒邮件。

留空以使用系统默认邮件地址(info@example.com)。

4. Optionally, edit the email templates in the Emails section to customize automated emails. There are seven email templates available with the core. They are meant for different user-specific occasions. All of them can be personalized and three can be disabled via checkboxes: activation, blocking, and cancellation.

You can send out your own text (for example, welcoming the new vendors for whom accounts were just created) by editing the the Welcome (new user created by administrator) template.



5. Click Save configuration to save the changes.

Expand your understanding

- [第 12.2 节 “Clearing the Cache”](#)
- [第 7.4 节 “Creating a User Account”](#)

Related concepts

See [第 7 章 Managing User Accounts](#) for more information about user accounts and permissions.

Additional resources

[Security Guide](#) can help you with a more safety-focused approach to configuration.

Attributions

Written and edited by [Laura Vass](#) at [Pronovix](#), and [Jojo Alphonso](#) at [Red Crackle](#).

4.6. Configuring the Theme

Goal

Edit the settings of the default core Bartik theme to change the color scheme and to add a logo.


Prerequisite knowledge

[第 1.3 节 “Concept: Themes”](#)

Steps

1. In the Manage administrative menu, navigate to Appearance (admin/appearance).
2. Under Installed themes, you will find Bartik listed as your default theme. Under Bartik (default theme), click Settings.

已安装的主题



Bartik 8.2.3 (默认主题)

一个灵活的，可以重新修改颜色的主题，自带多个区域以及一个响应式的，移动优先的布局。

设置

3. Under Color scheme, click inside each color build box and type the proper color codes you would like to add. For example, use the following colors:

Area	Color
Header background top	#7db84a (green)
Header background bottom	#2a3524 (dark green)
Main background	#ffffff (white)
Sidebar background	#f8bc65 (light orange)
Sidebar borders	#e96b3c (orange)
Footer background	#2a3524 (dark green)
Title and slogan	#ffffff (white)
Text color	#000000 (black)
Link color	#2a3524 (dark green)

Note: You can also use the color wheel on the right to select colors of your choice. The web color codes will be added for you.

配色方案

颜色集 ▾

页头背景顶部	#7db84a	
页头背景底部	#2a3524	
主背景	#ffffff	
边栏背景	#f8bc65	
边栏边框	#e96b3c	
页脚背景	#2a3524	
标题和口号	#ffffff	
文本颜色	#000000	
链接颜色	#2a3524	

- Under Logo image, uncheck Use the logo supplied by the theme.

LOGO 图像

使用主题提供的 logo

自定义标志的路径

如: logo.svg (在公开文件系统中的文件)、public://logo.svg 或 core/themes/bartik/logo.svg

上传logo图像
 No file selected.

如果您没有服务器直接文件访问权限, 请在此上传logo。

- Under Upload logo image, locate a logo file and upload it to your site. Note: You can also set a universal logo for all themes under Appearance > Settings (admin/appearance/settings). A custom logo for your theme will override the universal logo.

Once you have selected the file you would like to upload, you will see its filename next to the Choose File or Browse button in your browser.

- In order to save your changes and see the updated colors and logo on your site, click Save configuration at the bottom of the page.

Note: Under Color scheme, there is a Preview section that displays a sample of how your website will look with the new settings.



The screenshot displays a website using the Bartik theme. The header features a green gradient background with a circular logo on the left containing a farm scene and the text "ANYTOWN FARMERS MARKET" and "FARM FRESH FOOD". To the right of the logo, the word "Bartik" is displayed. Below the header is a navigation bar with three items: "Home", "Te Quidne", and "Vel Torqueo Quae Erat".

The main content area is divided into two sections. On the left, a yellow box contains the text "Etiam est risus". Below this, a larger yellow section contains placeholder text: "Maecenas id porttitor Ut enim ad minim veniam, quis nostrud felis. Laboris nisi ut aliquip ex ea".

On the right, a large yellow section contains the text "Lorem ipsum dolor" followed by a paragraph of placeholder text: "Sit amet, consectetur adipisicing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Maecenas id porttitor Ut enim ad minim veniam, quis nostrud felis."

The footer is a dark section with white text. It includes a sidebar with the heading "ETIAM EST RISUS" and the same placeholder text as the yellow box. The main footer area has a heading "ERISUS DOLOR" and four lines of text: "Donec placerat", "Nullam nibh dolor", "Blandit sed", and "Fermentum id".

7. Click Return to site or Home in the toolbar to verify that you have updated the core Bartik theme settings for your website.



Expand your understanding

- [第 11.4 节 “Finding Themes”](#)
- [第 11.5 节 “Downloading and Installing a Theme from Drupal.org”](#)
- If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Attributions

Written and edited by [Ann Greazel](#), [Amanda Luker](#) at [Advomatic](#), and [Jack Haas](#).

第 5 章 Basic Page Management

5.1. Concept: Paths, Aliases, and URLs

What is a URL?

URL is the abbreviation for "Uniform Resource Locator", which is the page's address on the web. It is the "name" by which a browser identifies a page to display. In the example "Visit us at example.com.", example.com is the URL for the home page of your website. Users use URLs to locate content on the web.

What is a Path?

A path is the unique, last part of the URL for a specific function or piece of content. For example, for a page whose full URL is <http://example.com/node/7>, the path is node/7.

Here are some examples of paths you might find in your site:

- node/7
- taxonomy/term/6
- admin/content/comment
- user/login
- user/3

What is an Alias?

The core software has a feature called "URL Alias" that allows you to provide a more understandable name to the content. So, if you have an "About Us" page with the path node/7, you can set up an alias so that your visitors will see it as <http://www.example.com/AboutUs>. The core Path module, which supports URL aliasing, provides this functionality.

Related topics

- 第 5.2 节 “Creating a Content Item”
- 第 5.3 节 “Editing a Content Item”

Attributions

Adapted by [Diána Lakatos](#) at [Pronovix](#) from "[URL aliases](#)", and "[Understanding Drupal paths](#)" copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#)

5.2. Creating a Content Item

Goal

Create and publish a content item that will be used as the home page of the site.

Prerequisite knowledge

[第 5.1 节 “Concept: Paths, Aliases, and URLs”](#)

Site prerequisites

The Basic page content type must exist. This is created on your site when you install with the core Standard installation profile.

Steps

1. In the Manage administrative menu, navigate to Content > Add content > Basic page (node/add/page). The Create Basic page form appears.
2. Click Edit summary.
3. Fill in the fields as shown below.

Field name	Explanation	Value
Title	Title of the page. Will also be used as a meta tag in the source code, URL alias, and as label of the content item in administration screens	Home
Summary	Summary of the value of the body field. Can be used as teaser in overview pages	Opening times and location of City Market.
Body	Full content of the page	Welcome to City Market - your neighborhood farmers market! Open: Sundays, 9 AM to 2 PM, April to September Location: Parking lot of Trust Bank, 1st & Union, downtown
URL path settings > URL alias	Alternate relative path for the content	/home

By clicking the Source button in the rich text editor toolbar, you can see the HTML source code of the text that you are editing.

The screenshot shows the 'Create Basic page' interface in Drupal. On the left, there's a title field containing '首页' and a summary field containing '开放时间和城市市场位置'. On the right, there's a sidebar with sections for '菜单设置', 'URL路径设置', '编著信息', and '推荐选项'. At the bottom, there are buttons for '保存和发布' (Save and Publish) and '预览' (Preview).

4. Click Preview to ensure everything looks like expected.
5. Click Back to content editing.
6. Click Save and publish. The content is saved and can be found on the Content page.
7. Follow the same steps to create an About page, with title "About", and a body telling about the history of the farmer's market.

Expand your understanding

- [第 5.5 节 “Designating a Front Page for your Site”](#)
- [第 5.7 节 “Adding a Page to the Navigation”](#)
- [第 10.4 节 “Translating Content”](#)

Related concepts

- [第 10.1 节 “Concept: User Interface, Configuration, and Content translation”](#)
- [第 5.1 节 “Concept: Paths, Aliases, and URLs”](#)
- [第 5.3 节 “Editing a Content Item”](#)

Additional resources

[Drupal.org community documentation page "About nodes"](#)

Attributions

Written by [Agnes Kiss](#) and [Boris Doesborg](#).

5.3. Editing a Content Item

Goal

Update the hours on the Home page content item.

Prerequisite knowledge

[第 5.2 节 “Creating a Content Item”](#)

Site prerequisites

A content item for the Home page must exist. See [第 5.2 节 “Creating a Content Item”](#).

Steps

1. In the Manage administrative menu, navigate to Content (admin/content).
2. If the content item you want to edit was updated or created recently, it should appear near the top of the content list on that page. If not, you can use the Content type, Title, or other filters to locate the content item.

The screenshot shows the Drupal Content management interface. At the top, there are search and filter fields for Title, Content type, Published status, and Language. Below these are buttons for '过滤' (Filter) and '删除内容' (Delete content). A 'Hide lower priority columns' link is visible. The main area displays a table of content items with columns for Title, Content type, Author, Status, and Updated. Two items are listed: '关于' (Content type: Basic page, Author: admin, Status: 已发表, Updated: 06/19/2017 - 05:24) and '首页' (Content type: Basic page, Author: admin, Status: 已发表, Updated: 06/19/2017 - 05:24). Each row has an '编辑' (Edit) button. A '应用于选中项' (Apply to selected items) button is located at the bottom left of the table.

标题	内容类型	发布状态	语言		
	- 任意 -	- 任意 -	- 任意 -		
<input type="button" value="过滤"/>					
<input type="button" value="删除内容"/>					
<input type="button" value="应用于选中项"/>					
Hide lower priority columns					
标题	内容类型	作者	状态	UPDATED	操作
关于	Basic page	admin	已发表	06/19/2017 - 05:24	<input type="button" value="编辑"/>
首页	Basic page	admin	已发表	06/19/2017 - 05:24	<input type="button" value="编辑"/>
<input type="button" value="应用于选中项"/>					

3. Click Edit in the row of the content item you want to edit (Home), to open the content editing form. Update the opening hours in the Body field. See [第 5.2 节 “Creating a Content Item”](#) for an explanation of the fields and a screenshot.
4. Check Create new revision in the box on the right, if it is not already checked, and enter a Revision log message explaining what changes you are making (for example, you might enter "Updated opening hours"). This text will appear in the revision log for the page.

已发表

最后保存: 12/07/2016 - 01:20

作者: admin

创建新的修订版本

修订日志消息

更新开放时间

简要描述您所做的更改。

5. Click Save and keep published to save your changes.
6. You will be redirected back to the Content administrative page, and there should be a message showing that the content item was updated.

✓ Basic page 首页 已更新。

Expand your understanding

As an alternative to the first two steps above, you can also reach the content edit form as follows:

1. Starting from your site's home page, use the site's navigation menus to locate the page where the content you want to edit is displayed to visitors.
2. Most themes will display an Edit link or tab near the top of that page to people with permission to edit the page; clicking the link will take you to the full content edit form.
3. You could also use the in-place editor (refer to [第 5.4 节 “Editing with the In-Place Editor”](#)) from this page.

Attributions

Written by [Chris Dart](#) and [Jennifer Hodgdon](#).

5.4. Editing with the In-Place Editor

Goal

Use the in-place editor to add information to the About page without opening the full editor page.

Prerequisite knowledge

- 第 2.3 节 “Concept: Content Entities and Fields”
- 第 5.2 节 “Creating a Content Item”
- 第 5.3 节 “Editing a Content Item”
- 第 4.1 节 “Concept: Administrative Overview”

Site prerequisites

The About page you want to edit must exist. See [第 5.2 节 “Creating a Content Item”](#).


Steps

Navigate to the About page to edit content with the in-place editor. If the page has not yet been added to a navigation menu, you can find and open it by following these steps:


1. In the Manage administrative menu, navigate to Content (admin/content).
2. If the content item you want to edit was updated or created recently, it should appear near the top of the content list on that page. If not, you can use Type, Title, or other filters to locate the content item.
3. Find the About page and click it.

Once the content you want to edit is being viewed in your browser, follow these steps to use the quick editor:

1. Find the section of the page that displays the content you want to edit, and turn on quick editing mode using the Quick edit contextual link (see [第 4.1 节 “Concept: Administrative Overview”](#) for instructions on how to access contextual links). You will see each editable field on this content item outlined in blue; also, a hovering dialog box will appear.



2. Click the Body text area to begin editing. The Body field supports a rich text editor. The editing toolbar will be displayed in a hovering dialog box.
3. Add some information about City Market. A Save button will appear in the hovering dialog box, and the field outline will change color.



4. If you are satisfied with your edits, click Save in the hovering dialog box. If not, click "x" to discard your edits, and confirm. Either way, quick editing mode will be turned off.

Expand your understanding

Try using the full editor on the same content (see [第 5.3 节 “Editing a Content Item”](#)) and note that there is much more information that can be edited that is not available in the quick editor.

Attributions

Written and edited by [David Lee](#) and [Jennifer Hodgdon](#).

5.5. Designating a Front Page for your Site

Goal

Configure which content item is displayed as the front page of your website.

Site prerequisites

The content item that you want to designate as the front page of your site must exist. See [第 5.2 节 “Creating a Content Item”](#).

Steps

1. In the Manage administrative menu, navigate to Configuration > System > Basic site settings (admin/config/system/site-information).
2. Under Front page, replace /node with the name of the page you would like to make the home page. To use the home page that was previously created, provide its path /home. Click Save configuration.

▼ 首页

默认首页

http://example.com /home

可选的，指定一个相对 URL 以便在首页中显示。留空可显示默认的首页。

3. Navigate to the home page to verify that it displays content as configured by you.

爱林镇农贸市场
农场新鲜食材

工具

添加内容

首页

查看 编辑 删除 修订版本

欢迎来到城市市场 -- 您的农贸市场邻居!

开放时间: 4月 - 9月, 星期日, 09:00 – 14:00

位置: 市中心水滴大厦一楼

Expand your understanding

- [第 5.7 节 “Adding a Page to the Navigation”](#)
- Follow [第 5.2 节 “Creating a Content Item”](#) to create an error page to be used as a 404 (page not found) or 403 (not authorized) response on your site. Then following the steps here, you can designate it as the error response, in the Error pages section of the configuration.

Related concepts

[第 5.6 节 “Concept: Menu”](#)

Attributions

Written and edited by [Ann Greazel](#), [Jack Haas](#), and [Jojo Alphonso](#) at [Red Crackle](#).

5.6. Concept: Menu

What is a menu?

Menus are a collection of links (menu items) used to navigate a website. The core Menu UI module provides an interface to control and customize the menu system. Menus are

primarily displayed as a hierarchical list of links. By default, new menu items are placed inside a built-in menu labeled Main navigation, but administrators can also create custom menus.

The core Standard installation profile contains five menus:

Main navigation

Links to sections intended for site visitors. They are usually created by site administrators.

Administration

Links to administrative tasks. This menu mainly contains links supplied by modules on your site.

User account menu

Links to tasks associated with the user account such as My account and Log out.

Footer

Links to important pages within the site intended for the footer. They are usually created by site administrators.

Tools

Links to tasks necessary for site visitors. Some modules feature their links here.

You can customize menus in the following ways, using the menu administration functionality:

- Creating new custom menus.
- Adding new menu items.
- Reordering menu items by setting their "weight" or by dragging them into place.
- Renaming menu items.
- Changing the link title (the tooltip that appears when you mouse over a menu item).
- Moving a menu item into a different menu by editing its Parent property.

A menu item will only be shown to a visitor if they have the rights to view the page it links to. For example, the admin menu item is not shown to visitors who are not logged in.

Related topics

- [第 5.7 节 “Adding a Page to the Navigation”](#)
- [第 5.8 节 “Changing the Order of Navigation”](#)
- To display a menu, you will need to place the block that corresponds to the menu in a region of your theme; see [第 8.1 节 “Concept: Blocks”](#), [第 2.1 节 “Concept: Regions in Themes”](#)

a Theme”, and 第 8.3 节 “Placing a Block in a Region”. The core Standard installation profile places all of the menus it defines except Administration in regions of the core Bartik theme. The core Toolbar module, which is installed by the core Standard installation profile, displays the Administration menu; it is also displayed by the contributed Admin Toolbar module.

Attributions

Written and edited by [Ajay Viswambharan](#), [Jojo Alphonso](#) at [Red Crackle](#), and [Jennifer Hodgdon](#).

5.7. Adding a Page to the Navigation

Goal

Add a page to the navigation. For example, the About page.

Prerequisite knowledge

- 第 5.6 节 “Concept: Menu”
- 第 5.3 节 “Editing a Content Item”

Site prerequisites

The About page content item must exist. See 第 5.2 节 “Creating a Content Item”.

Steps

1. In the Manage administrative menu, navigate to Content (admin/content).
2. Find the About page, and click Edit in that row. The content editing form appears.

□	标题	内容类型	作者	状态	已更新	操作
□	首页	基本页面	admin	Published	12/07/2016 - 01:20	编辑 删除
□	关于	基本页面	admin	Published	12/07/2016 - 01:20	编辑 删除

3. Click Menu settings on the right to expand it.
4. Check Provide a menu link for the menu options to appear.
5. Enter values from the table below:

Field name	Explanation	Example value
Menu link title	Title that will be displayed in the menu	About

Field name	Explanation	Example value
Description	Text that will be displayed when a visitor hovers over the link	History of the market
Parent item	Location of the page in the menu hierarchy. For example, if you choose <Main navigation>, the page will appear in the highest level of the navigation. By choosing another menu item as parent, you can create a menu hierarchy of multiple levels.	<Main navigation>
Weight	The order in which the page should appear in the menu (lower-weighted menu items will be shown before higher-weighted menu items)	-2

▼ 菜单设置

指定一个菜单链接

菜单链接标题
关于

描述
市场历史

当鼠标移动至菜单链接上时显示。

父级项目
<主导航> ▾

权重
-2

权重较低的菜单链接会显示在权重较高的之前。

6. Click Save and keep published to save the changes. Click Home or Return to site in the navigation bar to see the result, which could look like the picture below.



Expand your understanding

[第 5.8 节 “Changing the Order of Navigation”](#)

Additional resources

[Drupal.org community documentation page "Working with menus"](#)

Attributions

Adapted by [Boris Doesborg](#) from "[Working with Menus](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#); edited by [Jack Haas](#).

5.8. Changing the Order of Navigation

Goal

Reorder the items in a menu.

Prerequisite knowledge

- [第 5.6 节 “Concept: Menu”](#)
- [第 5.7 节 “Adding a Page to the Navigation”](#)

Site prerequisites

Home and About pages must exist in the main navigation menu. See [第 5.7 节 “Adding a Page to the Navigation”](#).

Steps

- In the Manage administrative menu, navigate to Structure > Menus (admin/structure/menu) where all menus on your site are listed. Click Edit Menu from the Operations dropdown for Main navigation. You can also reach this page using contextual links (refer to [第 4.1 节 “Concept: Administrative Overview”](#)) for the menu.

标题	描述	操作
主导航	网站段落链接	<button>编辑菜单 ▾</button>
工具	用户工具链接，通常由模块创建。	<button>编辑菜单 ▾</button>
用户帐户菜单	链接到活跃的用户账户	<button>编辑菜单 ▾</button>
管理	管理操作链接	<button>编辑菜单 ▾</button>
页脚	站点信息链接	<button>编辑菜单 ▾</button>

- The Edit menu page will display a list of each item in the menu you chose (Main navigation).

菜单语言

Chinese, Simplified ▾

菜单链接	已启用	操作
关于我们	<input checked="" type="checkbox"/>	<button>编辑 ▾</button>
主页	<input checked="" type="checkbox"/>	<button>编辑</button>

保存

- Use the cross bar handles to reorder the menu items. Drag the Home menu item above the About menu item so that it appears first.

菜单语言

Chinese, Simplified(简体中文) ▾

⚠ *你有未保存的更改。

菜单链接	已启用	操作
主页	<input checked="" type="checkbox"/>	<button>编辑</button>
关于我们	<input checked="" type="checkbox"/>	<button>编辑 ▾</button>

保存

- Click Save.
- The home page now displays the main navigation with the Home menu item displayed first.



Expand your understanding

Add a menu item called Contact, leading to the /contact page, to your Main navigation menu. The contact page is provided by the core Contact module; you may want to edit its layout and fields (see [第 6.9 节 “Changing Content Entry Forms”](#)).

Related concepts

[第 5.6 节 “Concept: Menu”](#)

Attributions

Written by [Ann Greazel](#).

第 6 章 Setting Up Content Structure

6.1. Adding a Content Type

Goal

Add and configure a new content type Vendor.

Prerequisite knowledge

[第 2.3 节 “Concept: Content Entities and Fields”](#)

Site prerequisites

You need to have a plan in place for your content structure. See [第 2.5 节 “Planning your Content Structure”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Content types (admin/structure/types). The Content types page appears showing all the available types of content.
2. Click Add content type. The Add content type page appears. Fill in the fields as shown below.

Field name	Explanation	Example value
Name	Name of the content type	Vendor
Description	Explain the use of the content type	Information about a vendor

[首页](#) » [管理](#) » [结构](#) » [内容类型](#)

各个内容类型有着不同的字段、行为以及分配到的权限。

名称 *

此内容类型的人类可读名称。此文本将显示于添加内容页面的列表中。此名称必须唯一。

描述

此文本将会显示于添加新内容页面。

3. In the vertical tab Submission form settings, configure the form that is used for creating and editing content of this type. Fill in the fields as shown below.

Field name	Explanation	Example value
Title field label	Label of the Title field that is shown when editing or creating content of this type.	Vendor name
Preview before submitting	Option to choose whether you should preview the content before submitting.	Optional
Explanation or submission guidelines	Instructions for creating or editing content.	(Leave blank)

4. In the vertical tab Publishing options, decide on default options for new content of this type. Fill in the fields as shown below.

Field name	Explanation	Example value
Published	Make the content item published by default.	Checked
Promoted to front page	In a default website, this setting can be used to show content on the homepage.	Unchecked
Sticky at top of lists	In a default website, this setting can be used to keep content on top of a list.	Unchecked

Field name	Explanation	Example value
Create new revision	Create a new revision each time the vendor is being edited.	Checked

Changing these settings does not affect the content items that have already been created.

提交表单设置 摊贩名称	默认选项 <input checked="" type="checkbox"/> 已发表 <input type="checkbox"/> 推荐到首页 <input type="checkbox"/> 置顶 <input checked="" type="checkbox"/> 创建新的修订版本 <small>具有管理内容权限的用户可以覆盖这些选项。</small>
发布选项 已发表，创建新的修订版本	
语言设置 站点默认语言 (Chinese, Simplified)	
显示设置 Don't display post information	
菜单设置	

5. In the vertical tab Display settings, decide if the author and publication date will be visible in the content item. Fill in the fields as shown below.

Field name	Explanation	Example value
Display author and date information	Display the author username and publication date on each vendor page.	Unchecked

提交表单设置 摊贩名称	<input type="checkbox"/> 显示作者和日期信息 <small>显示作者的用户名及发布日期。</small>
发布选项 已发表，创建新的修订版本	
语言设置 站点默认语言 (Chinese, Simplified)	
显示设置 Don't display post information	
菜单设置	

6. In the vertical tab Menu settings, fill in the fields as shown below.

Field name	Explanation	Example value
Available menus	Menus that this type of content can be added to. Vendors do not need to appear in menus, so uncheck all menu options.	Unchecked

The screenshot shows the 'Create Content Type' configuration page. On the left, there's a sidebar with sections like '提交表单设置' (Form Submission Settings), '发布选项' (Publish Options), '语言设置' (Language Settings), '显示设置' (Display Settings), and '菜单设置' (Menu Settings). The '菜单设置' section is highlighted. On the right, under '可用菜单' (Available Menus), several checkboxes are listed: '主导航' (Main Navigation), '工具' (Tools), '用户帐户菜单' (User Account Menu), '管理' (Management), and '页脚' (Footer). A note below says '用于给该内容类型放置链接的菜单' (Used for placing links for this content type). Under '默认父项' (Default Parent), a dropdown menu shows '<用户帐户菜单>' with a dropdown arrow. A note below it says '选择一个菜单项，作为内容发布表单中新链接的默认父项' (Select a menu item as the default parent for new links in the content publishing form).

7. Click Save and manage fields to save the content type. The Manage fields page appears that allows you to add fields to the content type. See [第 6.3 节 “Adding Basic Fields to a Content Type”](#)

The screenshot shows the 'Manage Fields' page for the '摊贩' content type. At the top, there are tabs: '编辑' (Edit), '管理字段' (Manage Fields) (which is selected), '管理表单显示' (Manage Form Display), and '管理显示' (Manage Display). Below the tabs, the breadcrumb navigation shows: 首页 » 管理 » 结构 » 内容类型 » 摊贩. A green success message box says '✓ 添加了内容类型 摊贩。' (Content type '摊贩' added successfully). Below the message is a button '+ 添加字段' (Add Field). A table lists the field 'Body' with details: 标签 (Label) is 'Body', 机读名称 (Machine-readable name) is 'body', 字段类型 (Field Type) is '文本 (已格式化, 长, 带摘要)' (Text (Formatted, Long, With Summary)), and 操作 (Operations) includes an '编辑' (Edit) button with a dropdown arrow. There is also a horizontal ellipsis button '...'.

8. Follow the same steps to create a content type for recipes. Example values for the fields in the forms, where they are different from the steps above:

Field name	Example value
Name	Recipe
Description	A recipe submitted by a vendor

Field name	Example value
Submission form settings - Title	Recipe name

Expand your understanding

- [第 6.3 节 “Adding Basic Fields to a Content Type”](#)
- Install and configure the [contributed Pathauto module](#) so that content items get automatically generated URLs/path aliases. See [第 5.1 节 “Concept: Paths, Aliases, and URLs”](#) for more on URLs within your site, [第 11.1 节 “Finding Modules”](#) for instructions on finding contributed modules, and [第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#) for instructions on downloading and installing contributed modules.

Attributions

Written and edited by [Sree Veturi](#), [Boris Doesborg](#), and [Jennifer Hodgdon](#).

6.2. Deleting a Content Type

Goal

Delete the unneeded content type Article.

Prerequisite knowledge

[第 4.1 节 “Concept: Administrative Overview”](#)

Site prerequisites

The Article content type must exist. It is created on your site when you install with the core Standard installation profile.

Steps

1. In the Manage administrative menu, navigate to Structure > Content types (admin/structure/types). The Content types page appears.
2. Click Delete in the Operations dropdown button for the Article content type.

名称	描述	操作
Article	Use <i>articles</i> for time-sensitive content like news, press releases or blog posts.	管理字段
Basic page	Use <i>basic pages</i> for your static content, such as an 'About us' page.	管理表单显示
报告	报告类型	管理显示
食谱	食谱提交的视频	编辑
		删除

3. A confirmation page is displayed. Click Delete.

是否确认删除 内容类型 Article? ☆

首页 » 管理 » 结构 » 内容类型 » Article

此动作无法撤销。

▼ 配置缺失
已列出的配置将被删除

实体表单显示

- node.article.default

实体视图显示

- node.article.default
- node.article.rss
- node.article.teaser

字段

- 正文
- 评论
- 图像
- 标签

RDF mapping

- node.article

删除 **取消**

4. The Content types page appears with a confirmation message saying that the content type has been deleted:

✓ 内容类型 Article 被删除了。

Attributions

Written and edited by [Sree Veturi](#) and [Boris Doesborg](#).

6.3. Adding Basic Fields to a Content Type

Goal

Add a link field and an image field to the Vendor content type.

Prerequisite knowledge

[第 2.3 节 “Concept: Content Entities and Fields”](#)

Site prerequisites

The Vendor content type must exist. See [第 6.1 节 “Adding a Content Type”](#).

Steps

Add the fields Vendor URL and Main image to the Vendor content type.

1. In the Manage administrative menu, navigate to Structure > Content types (admin/structure/types). Then click Manage fields in the dropdown button for the Vendor content type. The Manage fields page appears.
2. Click Add field. The Add field page appears. You can either create a new field for the content type or re-use an existing field.
3. Fill in the fields as shown below.

Field name	Explanation	Value
Add a new field	Field type	Link
Label	Label that is visible in administration pages	Vendor URL

A machine name is automatically generated, based on the Label value. Click Edit if you want to override the default name.

The screenshot shows the 'Add field' form. At the top, there is a title bar with the text '添加字段 ☆'. Below it, the breadcrumb navigation shows: 首页 » 管理 » 结构 » 内容类型 » 摆贩 » 管理字段. The main form has a title '添加一个新字段' and a dropdown menu showing '链接'. A red asterisk next to the word '标签' indicates it is a required field. The input field is labeled '摊贩 URL' and contains the machine-readable name 'field_vendor_url'. There is also an 'Edit' link next to it. At the bottom, there is a blue '保存并继续' (Save and Continue) button.

4. Click Save and continue. The page Vendor URL appears which lets you set the allowed number of values. Fill in the fields as shown below.

Field name	Explanation	Value
Allowed number of values	The number of values that can be entered	Limited, 1

5. Click Save field settings. The page Vendor URL settings for Basic page appears which allows you to configure the field. Fill in the fields as shown below.

Field name	Explanation	Value
Label	Label that is visible in the content form	Vendor URL
Help text	The instruction that is shown below the field	(leave blank)
Required field	Whether the field is required or not	Unchecked
Allowed link type	The kind of links that can be entered	External links only
Allow link text	Whether a link text can be entered	Disabled

摊贩的 摊贩 URL 设置 ☆

[编辑](#) [字段设置](#)

首页 > 管理 > 结构 > 内容类型 > 摊贩 > 管理字段

标签 *

帮助文本

显示在此字段编辑表单下面的操作指南。
允许的HTML标签: <a> <big> <code> <i> <ins> <pre> <q> <small> <sub> <sup> <tt> <p>

此字段支持置換符 (token)。

必填字段

▼ 默认值

用于创建新的内容时，此字段的默认值。

摊贩 URL

This must be an external URL such as <http://example.com>.

Allowed link type

Internal links only
 只允许外部链接
 Both internal and external links

允许链接文本

已禁用
 可选
 已请求

6. Click Save settings. The Vendor URL has been added to the content type. Continue creating the Main image field.

7. Click Add field. The Add field page appears. Fill in the fields as shown below.

Field name	Explanation	Value
Add a new field	Field type	Image
Label	Label that is visible in administration pages	Main image

8. Click Save and continue. The page Main image appears. Fill in the fields as shown below.

Field name	Explanation	Value
Allowed number of values	The number of values that can be entered	Limited, 1

You can set a default image here. This will be used when you do not provide an image when creating a Vendor content item.

9. Click Save field settings. The page Main image settings for Basic page appears. Fill in the fields as shown below.

Field name	Explanation	Value
Label	Label that is visible in the content form	Main image
Help text	The instruction that is shown below the field	(leave blank)
Required field	Whether the field is required or not	Checked
Allowed file extensions	The type of images that can be uploaded	png, gif, jpg, jpeg
File directory	The directory where the files will be stored. By providing a file directory value, you ensure that all images uploaded via the Main image field will be located in the same directory.	vendors
Minimum image resolution	The minimum resolution of the uploaded image	600 x 600
Maximum upload size	The maximum file size of the uploaded image	5 MB
Enable Alt field	Whether an alternative text can be entered	Checked
Alt field required	Whether an alternative text is required	Checked

摊贩的 主图 设置 ☆

[编辑](#) [字段设置](#)

首页 > 管理 > 结构 > 内容类型 > 摊贩 > 管理字段

标签 *

主图

帮助文本

显示在此字段编辑表单下面的操作指南。
允许的HTML标签: <a> <big> <code> <i> <ins> <pre> <q> <small> <sub> <sup> <tt> <p>
 此字段支持置換符 (token)。

必填字段

默认图片

如果没有图片被上传，此图片会显示出来。

图像

[Browse...](#) No file selected.

Image to be shown if no image is uploaded.

替换文本

This text will be used by screen readers, search engines, and when the image cannot be loaded.

标题

Title属性用于当用户鼠标移动到此图片上的工具提示。

允许的文件扩展名 *

png, gif, jpg, jpeg

用空格或逗号隔开后缀名，不包括后缀名前面的点。

文件目录

.....

10. Click Save settings. Main image has been added to the content type.

管理字段 ☆

[编辑](#) [管理字段](#) [管理表单显示](#) [管理显示](#)

首页 > 管理 > 结构 > 内容类型 > 摊贩

✓ 已保存 主图 配置。

[+ 添加字段](#)

标签	机读名称	字段类型	操作
Body	body	文本 (已格式化, 长, 带摘要)	编辑
主图	field_main_image	图像	编辑
摊贩 URL	field_vendor_url	链接	编辑

11. Add a Main image field to the Recipe content type, using similar steps. Start by navigating to the Recipe content type's Manage Fields page in step 1. Then skip to step 7 and follow the remaining steps, but reuse the existing Main image field you created for the Vendor content type rather than creating a new field. In subsequent steps, some of the configuration screens will not be available, because of the field reuse.

12. Create two Vendor content items (see 第 5.2 节 “Creating a Content Item”) called "Happy Farm" and "Sweet Honey". Make sure that they include images and URLs.

Expand your understanding

- [第 6.12 节 “Concept: Image Styles”](#)
- [第 6.11 节 “Changing Content Display”](#)
- [第 6.9 节 “Changing Content Entry Forms”](#)

Additional resources

[Drupal.org community documentation page "Add a field to a content type"](#)

Attributions

Written by [Sree Veturi](#) and [Boris Doesborg](#).

6.4. Concept: Reference Fields

Prerequisite knowledge

[第 2.3 节 “Concept: Content Entities and Fields”](#)

What is a reference field?

A reference field is a field that represents a relationship between an entity and one or more other entities, which may belong to the same or different entity type. The three most commonly-used reference fields are:

Content reference

A reference to a content item. For example, you might want to connect recipes to the vendors who submitted them. You would set up a content reference field called Submitted by referencing Vendor content items on the Recipe content type.

Taxonomy term reference

A reference to a taxonomy term. For example, you might want to connect recipes to their ingredients. You would set up a taxonomy term reference field called Ingredients on the Recipe content type. This reference field will point to the vocabulary Ingredients.

User reference

A reference to a user account. For example, you might want to connect recipes with their chefs. You would set up a user reference field called Chefs on the Recipe content type.

Related topics

[第 6.5 节 “Concept: Taxonomy”](#)

Attributions

Written and edited by [Surendra Mohan](#), and [Jojo Alphonso](#) at [Red Crackle](#).

6.5. Concept: Taxonomy

Prerequisite knowledge

- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 6.4 节 “Concept: Reference Fields”](#)

What is Taxonomy?

Taxonomy is used to classify website content. One common example of taxonomy is the tags used to classify or categorize posts in a blog website; the farmers market website could use an ingredients taxonomy to classify recipes. Individual taxonomy items are known as terms (the blog tags or recipe ingredients in these examples); and a set of terms is known as a vocabulary (the set of all blog post tags, or the set of all recipe ingredients in these examples). Technically, taxonomy terms are an entity type and the entity subtypes are the vocabularies. Like other entities, taxonomy terms can have fields attached; for instance, you could set up an image field to contain an icon for each term.

An individual vocabulary can organize its terms in a hierarchy, or it could be flat. For example, blog tags normally have a flat structure, while a recipe ingredients vocabulary could be hierarchical (for example, tomatoes could be a sub-term of vegetables, and under tomatoes, you could have green and red tomatoes).

Taxonomy terms are normally attached as reference fields to other content entities, which is how you can use them to classify content. When you set up a taxonomy reference field, you can let users enter terms in two ways:

Free tagging

New terms can be created right on the content editing form.

Fixed list of terms

The list of terms is curated and managed outside the content editing form, and users can only choose from the existing list when editing content.

Taxonomy reference fields can be added to any entity, such as user accounts, custom blocks, or regular content items. If you use them to classify regular content items, your site will automatically be set up with taxonomy listing pages for each term; each of these pages lists all of the content items that are classified with that term. For example, if you created several recipes that all had carrots as an ingredient, you might see something like this on the Carrots taxonomy listing page:

胡萝卜

新鲜胡萝卜

放置多彩的胡萝卜到晚餐碟子里

[阅读更多](#)

蔬菜沙拉

剥碎你最喜欢的蔬菜，把它们放在碗里。

[阅读更多](#)

Related topics

- [第 6.6 节 “Setting Up a Taxonomy”.](#)
- The listing pages are views, which are covered in [第 9 章 Creating Listings with Views](#).

Attributions

Adapted and edited by [Surendra Mohan](#), [Jennifer Hodgdon](#), and [Jojo Alphonso](#) at [RedCrackle](#) from "[Organizing content with taxonomies](#)" and "[About taxonomies](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

6.6. Setting Up a Taxonomy

Goal

Create an Ingredients vocabulary and add it to the Recipe content type as a field that can contain an unlimited number of values and that allows adding new terms to the vocabulary.

Prerequisite knowledge

- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 6.5 节 “Concept: Taxonomy”](#)

- 第 6.3 节 “Adding Basic Fields to a Content Type”

Site prerequisites

The Recipe content type must exist. See [第 6.1 节 “Adding a Content Type”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Taxonomy (admin/structure/taxonomy). You will see the Tags vocabulary that was created with the core Standard installation profile.

The screenshot shows the 'Taxonomy' configuration page. At the top, it says '分类 ☆'. Below that is a breadcrumb trail: '首页 » 管理 » 结构'. A note states: '分类用于内容的分类。术语由词汇表进行组织。比如，一个叫做 "水果" 的词汇表可能会包含术语 "苹果" 和 "香蕉"。' There is a blue button labeled '+ 添加词汇表'. Below this is a table with columns: '术语表名称', '描述', and '操作'. A row for '标签' is shown with the description: 'Use tags to group articles on similar topics into categories.' and an '列出术语' button with a dropdown arrow. The table has a light gray background and white text.

2. Click Add vocabulary, and fill in the values below.

Field name	Explanation	Example value
Name	The name of the vocabulary	Ingredients
Description	A brief note about the vocabulary	(Leave blank)

添加词汇表 ☆

首页 » 管理 » 结构 » 分类

名称 *

原料

描述

词汇语言

Chinese, Simplified ▾

▼ 术语语言

默认语言

站点默认语言 (Chinese, Simplified) ▾

关于语言选项的解释可在[语言列表页面](#)中找到。

在创建和编辑页面显示语言选择器

保存

- Click Save. You will be taken to the Ingredients page, which shows a list of all the terms in this vocabulary.

原料 ☆

列表 编辑 管理字段 管理表单显示 管理显示

首页 » 管理 » 结构 » 分类 » 原料

✓ 创建了新的术语表 原料。

你可以通过拖曳的方式组织在原料中的术语，通过在父级项目下拖动术语组合术语。

+ 添加术语

Show row weights

名称	权重	操作
----	----	----

No terms available. [Add term](#).

- Click Add term. Enter "Butter" in the Name field. Click Save.

添加术语 ☆

首页 » 管理 » 结构 » 分类 » 原料

名称 *
黄油

描述

B I | | | | 格式 | 源码

文本格式 Basic HTML | ▾ [关于文本格式 ?](#)

► **关系**

URL别名

Specify an alternative path by which this data can be accessed. For example, type "/about" when writing an about page.

保存

5. You will receive a confirmation about the term you created. Add more terms. For example, "Eggs" and "Milk".
6. In the Manage administrative menu, navigate to Structure > Content Types (admin/structure/types). Click Manage fields for your Recipe content type.
7. Click Add field, and enter values from the table below. Click Save and continue.

Field name	Explanation	Value
Add a new field	Select the field type	Reference > Taxonomy term
Label	The title to give the field	Ingredients

添加字段 ☆

首页 » 管理 » 结构 » 内容类型 » 食谱 » 管理字段

添加一个新字段


分类术语



或者

重用已有字段

- 选择一个现有字段 -



标签 *

原料

机读名称: field_ingredients [Edit]

保存并继续

8. On the following configuration screen, enter the values from the table below. Click Save field settings.

Field name	Explanation	Value
Type of item to reference	The type of entity that is referenced by the field	Taxonomy term
Allowed number of values	The number of values a user can enter	Unlimited

这些设置作用与 原料 字段被使用的任何地方。这些设置影响数据存储于数据库的方式，并且数据一旦被创建将不能更改。

要引用的条目类型 *

分类术语

允许的数量

不限

保存字段设置

9. On the following configuration screen, enter the values from the table below. Click Save settings.

Field name	Explanation	Value
Help text	Help shown to users creating content	Enter ingredients that site visitors might want to search for
Reference type > Reference method	Select the method used to choose allowed values	Default
Reference type > Available Vocabularies	Select the vocabulary to choose allowed values from	Ingredients

Reference type > Create referenced entities if they don't already exist	Whether new ingredient terms can be created from the content editing form	Checked
---	---	---------

标签 *

帮助文本

输入原料，网站访问可能想搜索它

显示在此字段编辑表单下面的操作指南。
允许的HTML标签: <a> <big> <code> <i> <ins> <pre> <q> <small> <sub> <sup> <tt> <p>

此字段支持置換符 (token)。

必填字段

默认值

引用类型

引用方法 *

默认 | ▾

如果引用的实体不存在，则创建该引用的实体

Available Vocabularies *

原料
 标签

保存设置 **删除**

10. Click Save settings. You will be taken back to the Manage Fields page. A message will be displayed saying that the configuration for Ingredients is complete.

The screenshot shows the 'Manage Fields' interface for the 'Ingredients' content type. At the top, there are tabs: '编辑' (Edit), '管理字段' (Manage Fields), '管理表单显示' (Manage Form Display), and '管理显示' (Manage Display). Below the tabs, a breadcrumb navigation shows: 首页 > 管理 > 结构 > 内容类型 > 食谱. A green success message box displays: ✓ 已保存 原料 配置. A table lists three fields: 'Body' (机读名称: body, 字段类型: 文本 (已格式化, 长, 带摘要), 操作: 编辑), '主图' (机读名称: field_main_image, 字段类型: 图像, 操作: 编辑), and '原料' (机读名称: field_ingredients, 字段类型: 实体引用, 操作: 编辑).

Attributions

Written and edited by [Bob Snodgrass](#), and [Jojo Alphonso](#) at [Red Crackle](#).

6.7. Adding a Reference Field

Goal

Add a reference field so that recipes can be linked to the vendor that has submitted it.

Prerequisite knowledge

- 第 6.3 节 “Adding Basic Fields to a Content Type”
- 第 6.4 节 “Concept: Reference Fields”
- 第 6.1 节 “Adding a Content Type”

Site prerequisites

The Recipe and Vendor content types must exist. See [第 6.1 节 “Adding a Content Type”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Content types (admin/structure/types). Then click Manage fields in the dropdown button for the Recipe content type. The Manage fields page appears.
2. Click Add field. The Add field page appears. Fill in the fields as shown below. Click Save and continue.

Field name	Explanation	Value
Add a new field	Option to specify the field type	Reference > Content
Label	The title you want to give the field	Submitted by

添加字段 ☆

首页 » 管理 » 结构 » 内容类型 » 食谱 » 管理字段

添加一个新字段 重用已有字段

内容 或者 - 选择一个现有字段 -

标签* 提交者 机读名称: field_submitted_by [Edit]

保存并继续

3. The page Submitted by appears which lets you set the allowed number of values. Fill in the fields as shown below. Click Save field settings.

Field name	Explanation	Value
Type of item to reference	Option to select the type of referenced item	Content
Allowed number of values	Specify the count of values associated with the field	Limited, 1

4. The page Submitted by settings for Recipe appears which allows you to configure the field. Fill in the fields as shown below. Click Save settings.

Field name	Explanation	Value
Label	Title shown for this field on the page	Submitted by
Help text	Brief text aiding the person creating content	Choose the vendor that submitted this recipe
Required field	Whether a value has to be provided or not	Checked
Reference method	Option to select reference method	Default
Content types	Specify the content type	Vendor
Sort by	Sorting field	Title
Sort direction	Sorting order	Ascending

Setting Up Content Structure

选择提交改食谱的摊贩

显示在此字段编辑表单下面的操作指南。
允许的HTML标签: <a> <big> <code> <i> <ins> <pre> <q> <small> <sub> <sup> <tt> <p>

此字段支持置換符 (token)。

必填字段

默认值
用于创建新的内容时，此字段的默认值。
提交者

引用类型

引用方法 *
默认 | ▾
 如果引用的实体不存在，则创建该引用的实体

内容类型 *
 Basic page
 摊贩
 食谱

排序依据
摊贩名称 | ▾
排序方向 *
升序 | ▾

保存设置 **删除**

5. The Submitted by field has been added to the content type.

管理字段 ☆

编辑 管理字段 管理表单显示 管理显示

首页 > 管理 > 结构 > 内容类型 > 食谱

已保存 提交者 配置。

+ 添加字段

标签	机读名称	字段类型	操作
Body	body	文本 (已格式化, 长, 带摘要)	编辑 ▾
主图	field_main_image	图像	编辑 ▾
原料	field_ingredients	实体引用	编辑 ▾
提交者	field_submitted_by	实体引用	编辑 ▾

Attributions

Written and edited by [Boris Doesborg](#), and [Jojo Alphonso](#) at [Red Crackle](#).

6.8. Concept: Forms and Widgets

Prerequisite knowledge

[第 2.3 节 “Concept: Content Entities and Fields”](#)

What are forms and widgets?

The content management system software that your site is running allows administrators to edit content and configure settings online, using various web forms. In particular, content editing forms are used to edit your site's content, and they are configurable by administrators; settings configuration forms are provided by modules and cannot themselves be configured.

The data in your site's content is stored in one or more fields that are attached to the content type and/or sub-type. When you configure the content editing form for each content sub-type, you can:

- Select a widget for each field. A widget defines the method used to enter the data for the field. For example, a taxonomy term can be chosen using an autocomplete field, a select list, or a tags-style field that lets editors add new tags automatically.
- Configure widget settings. For example, you can choose the size of a plain-text entry field.
- Hide one or more fields from the editing form.
- Reorder the fields.

In principle, you can also have multiple content editing forms available for each content sub-type. This feature is rarely used, however; the only exception in common use is for the user profile fields: you can use different forms for user registration and user editing. For example, you might have a limited set of fields shown when users first register on the site, and more fields shown later on when they edit their profiles.

Related topics

- [第 6.9 节 “Changing Content Entry Forms”](#)
- [第 6.10 节 “Concept: View Modes and Formatters”](#)

Attributions

Written by [Jennifer Hodgdon](#).

6.9. Changing Content Entry Forms

Goal

Change the Recipe form to use a different widget to enter terms in the Ingredients field.

Prerequisite knowledge

- [第 6.1 节 “Adding a Content Type”](#)
- [第 6.3 节 “Adding Basic Fields to a Content Type”](#)
- [第 6.5 节 “Concept: Taxonomy”](#)
- [第 6.8 节 “Concept: Forms and Widgets”](#)

Site prerequisites

The Recipe content type must exist, and it must have an Ingredients taxonomy term reference field. See [第 6.1 节 “Adding a Content Type”](#) and [第 6.6 节 “Setting Up a Taxonomy”](#).

Steps

1. In the Manage administrative menu, navigate to Content > Add content > Recipe (node/add/recipe) to look at the content entry form that is set up by default. Notice how you have to enter ingredients one by one, instead of having a more compact format.
2. In the Manage administrative menu, navigate to Structure > Content types (admin/structure/types). Then click Manage form display on the dropdown button for the Recipe content type. The Manage form display page appears.
3. For the Ingredients field, select Autocomplete (Tags style) in the Widget column.

字段	控件	
⊕ 食谱名称	文本字段 ▾	文本框大小: 60
⊕ 语言	选择语言 ▾	
⊕ 作者	自动完成 ▾	自动完成匹配中: 包含 文本框大小: 60 无占位符
⊕ 发布于	日期时间时间戳 ▾	
⊕ 推荐到首页	单一 开/关 复选框 ▾	使用字段标签: 是
⊕ 置顶	单一 开/关 复选框 ▾	使用字段标签: 是
⊕ URL别名	URL别名 ▾	
⊕ Body	带摘要的文本域 ▾	行数: 9 摘要行数: 3
⊕ 主图	图像 ▾	Preview image style: 缩略图 (100x100) Progress indicator: throbber
⊕ 原料	自动完成 (标签风格) ▾	自动完成匹配中: 包含 文本框大小: 60 无占位符
⊕ 提交者	自动完成 ▾	自动完成匹配中: 包含 文本框大小: 60 无占位符

已禁用

4. Click Save.
5. In the Manage administrative menu, navigate to Content > Add content > Recipe (node/add/recipe) to verify the changed behavior of the content form. The Ingredients field is now a single text field that accepts multiple values.

创建 食谱 ☆

首页 > Node > 添加内容

食谱名称 *

Body (Edit summary)

文本格式 Basic HTML | 关于文本格式 ⓘ

主图 *

提交者 *

保存和发布 | 预览

6. Create two Recipe content items (see [第 5.2 节 “Creating a Content Item”](#)), such as recipes for "Green Salad" and "Fresh Carrots". Make sure all the fields have values, including images, ingredients, and submitted by (set this to one of the Vendor content items you created in [第 6.3 节 “Adding Basic Fields to a Content Type”](#)).

Expand your understanding

Change the main site Contact form by navigating in the Manage administrative menu to Structure > Contact forms. For instance, you may want to hide the Send yourself a copy or Language fields.

Attributions

Written by [Boris Doesborg](#).

6.10. Concept: View Modes and Formatters

Prerequisite knowledge

[第 6.1 节 “Adding a Content Type”](#)

What is a View mode?

How an entity (such as content, a user or a comment) is displayed, depends on the context in which it is shown. This context is known as a view mode. Examples of view modes are:

- a full page of the content with all the field values
- a teaser of the content with a thumbnail image and a Read more link
- a full user profile with a zoomable portrait photo
- a user avatar with username and a link to the profile

Every view mode can be configured through the administration pages. To see the configuration options for the view modes of the Recipe content type, navigate in the Manage administrative menu to Structure > Content types (admin/structure/types) and click Manage display from the dropdown button. In each view mode, all fields can be hidden or displayed, and if they are displayed, you can choose and configure the field formatter.

What is a field formatter?

A field formatter is a setting for displaying the field values. For example, long text fields can be displayed trimmed or full-length, and taxonomy term reference fields can be displayed in plain text or linked to the taxonomy term page. Consult the Manage display page to see the field formatters for the fields of the Recipe content type.

Related topics

- [第 6.1 节 “Adding a Content Type”](#)
- [第 6.11 节 “Changing Content Display”](#)

Additional resources

[Drupal.org community documentation page "View modes"](#)

Attributions

Adapted by [Boris Doesborg](#) from ["View modes"](#), copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

6.11. Changing Content Display

Goal

Make the content items more readable, accessible, and visibly attractive by reordering the fields, hiding labels, and tuning the output of the fields.

Prerequisite knowledge

- 第 2.3 节 “Concept: Content Entities and Fields”
- 第 6.10 节 “Concept: View Modes and Formatters”

Site prerequisites

The Vendor content type must exist, it must have Main Image and Vendor URL fields, and your site must have at least one Vendor content item. See 第 6.1 节 “Adding a Content Type”, 第 6.3 节 “Adding Basic Fields to a Content Type”, and 第 5.2 节 “Creating a Content Item”.

Steps

1. Find and view a Vendor content item you created in 第 6.3 节 “Adding Basic Fields to a Content Type”. Notice that there are several things that could be done to improve how the page looks:
 - The Main Image and Vendor URL fields should not have labels.
 - The order of the fields should be changed so that the image comes first.
 - The image should be smaller.
2. To fix the first two problems, and update some additional settings, in the Manage administrative menu, navigate to Structure > Content types (admin/structure/types). Then click Manage display in the dropdown button for the Vendor content type.

名称	描述	操作
Basic page	Use basic pages for your static content, such as an 'About us' page.	管理字段 管理表单显示 管理显示 编辑 删除
摊贩	摊贩类型	
食谱	摊贩提交的视频	

3. Under the Label column, select Hidden for Main image. Do the same for Vendor URL.

字段	标签	格式	Show row weights	
+ 链接				
+ Body	- 隐藏 -	默认		
+ 捕获 URL	- 隐藏 -	链接	链接文本截取至 80 个字符	⚙
+ 主图	- 隐藏 -	图像	原始图像	⚙
已禁用				
+ 语言	位于上方	语言		

4. Click the gear for the Vendor URL field. Clear the Trim link text length setting. Links will no longer have a trim length. Check the Open link in new window checkbox. Now, when the link is clicked, it will open in a new browser window. Click Update.



5. Drag the cross arrows next to the field items to reorder as Main image, Body, Vendor URL, and Links.

The screenshot shows the 'Content Structure' configuration page. At the top, there is a warning message: '⚠ *你有未保存的更改。' (Warning: You have unsaved changes). Below this, there are four main sections:

- 字段 (Fields):** Contains the '主图' (Main image) field, which is set to '隐藏' (Hidden) under '标签 (Label)' and '图像' (Image) under '格式 (Format)'. It also includes a '原始图像' (Original image) link and a gear icon.
- 标签 (Labels):** Contains the 'Body' field, which is set to '隐藏' (Hidden) under 'Label' and '默认' (Default) under 'Format'.
- 格式 (Formats):** Contains the 'Page URL' field, which is set to '隐藏' (Hidden) under 'Label' and '链接' (Link) under 'Format'. It includes a note: '链接文本未截取 在新窗口打开链接' (Link text not truncated, Open in new window) and a gear icon.
- 已禁用 (Disabled):** Contains the 'Link' field, which is currently disabled.

At the bottom, there is a '语言 (Language)' section with dropdown menus for '位于上方' (Above) and '语言' (Language).

6. Click Save.
7. Find the Vendor content item from step 1 again, and verify that the updates have been made.
8. Repeat similar steps to manage the display of the Recipe content type fields.

Expand your understanding

- Make the main image smaller. See [第 6.13 节 “Setting Up an Image Style”](#).
- If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Related concepts

[第 6.12 节 “Concept: Image Styles”](#)

Additional resources

- [Drupal.org community documentation page "Specify how fields are displayed"](#)
- [Drupal.org community documentation page "Rearrange the order of fields"](#)
- [Drupal.org community documentation page "View modes"](#)

Attributions

Written by [Ann Greazel](#) and [Boris Doesborg](#).

6.12. Concept: Image Styles

Prerequisite knowledge

[第 6.3 节 “Adding Basic Fields to a Content Type”](#)

What are image styles?

Image styles allow you to upload a single image but display it in several ways; each display variation, or image style, is the result of applying one or more effects to the original image.

As an example, you might upload a high-resolution image with a 4:3 aspect ratio, and display it scaled down, square cropped, or black-and-white (or any combination of these effects). The core software provides a way to do this efficiently:

1. Configure an image style with the desired effects on the Image styles page ([admin/config/media/image-styles](#)).
2. The effects will be applied the first time a particular image is requested in that style.
3. The resulting image is saved.
4. The next time that same style is requested, the saved image is retrieved without the need to recalculate the effects.

The core software provides several effects that you can use to define styles; others may be provided by contributed modules.

Visit the Image styles page via the Manage administrative menu, navigate to Configuration > Media > Image styles ([admin/config/media/image-styles](#)) to see the image styles that are defined by default.

Related topics

- [第 6.13 节 “Setting Up an Image Style”](#)
- [第 6.14 节 “Concept: Responsive Image Styles”](#)
- [第 6.3 节 “Adding Basic Fields to a Content Type”](#)

Additional resources

[Drupal.org community documentation page "Working with images in Drupal 7 and 8"](#)

Attributions

Adapted and edited by [Boris Doesborg](#), and [Jojo Alphonso](#) at [Red Crackle](#), from "[Working with images in Drupal 7 and 8](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#)

6.13. Setting Up an Image Style

Goal

Add an image style and use it to display images on Vendor pages.

Prerequisite knowledge

- 第 6.3 节 “Adding Basic Fields to a Content Type”
- 第 6.11 节 “Changing Content Display”
- 第 6.12 节 “Concept: Image Styles”

Site prerequisites

- Vendor and Recipe content types must exist. See 第 6.1 节 “Adding a Content Type”.
- Main image fields must exist for both content types. See 第 6.3 节 “Adding Basic Fields to a Content Type”.
- Content items must exist for both content types. See 第 6.1 节 “Adding a Content Type”, 第 6.3 节 “Adding Basic Fields to a Content Type”, and 第 5.2 节 “Creating a Content Item”.

Steps

1. In the Manage administrative menu, navigate to Configuration > Media > Image styles (admin/config/media/image-styles).
2. Click Add image style.
3. Enter the name Extra medium (300x200)
4. Click Create new style. The page Edit style Extra medium (300x200) appears.
5. In the Effect table, select Scale and crop. Click Add.
6. Fill in the fields as shown below.

Field name	Value
Width	300
Height	200


7. Click Add effect. The image style is saved with the chosen effects.

编辑样式中 (300x200) ☆


首页 » 管理 » 配置 » 媒体 » 图像样式

✓ 此图像效果已成功应用。

预览



原始 (查看实际尺寸)
800px



中 (300x200) (查看实际尺寸)
300px
200px

图像样式名称 *

中 (300x200)

机读名称: extra_medium_300x200 [Edit]

Show row weights

效果	操作
⊕ 比例缩放并裁切 300×200	编辑 ▾
⊕ 选择一个新的效果 ▾	添加

更新样式 **删除**

8. In the Manage administrative menu, navigate to Structure > Content types (admin/structure/types).
9. Click Manage display in the Operations dropdown for the Vendor content type. The Manage display page (admin/structure/types/manage/vendor/display) appears.
10. Ensure that the secondary tab Default is selected.
11. Click the cogwheel next to Main image for the configuration options.
12. Fill in the fields as shown below.

Field name	Value
Image style	Extra medium (300x200)
Link image to	Nothing



13. Click Update.
14. Click Save. The new image style will be used while displaying Vendor content.
15. Open a Vendor content item and verify that it now shows up with the scaled-down image. See [第 5.3 节 “Editing a Content Item”](#) for information on how to locate an existing content item.
16. Repeat steps 8-15 for the Recipe content type.

Related concepts

- [第 6.3 节 “Adding Basic Fields to a Content Type”](#)
- [第 6.12 节 “Concept: Image Styles”](#)
- [第 6.14 节 “Concept: Responsive Image Styles”](#)

Additional resources

[Drupal.org community documentation page “Working with images in Drupal 7 and 8”](#)

Attributions

Adapted and edited by [Boris Doesborg](#), and [Joey Alphonso](#) at [Red Crackle](#) from [“Working with images in Drupal 7 and 8”](#), copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

6.14. Concept: Responsive Image Styles

Prerequisite knowledge

- [第 1.3 节 “Concept: Themes”](#)

- [第 6.11 节 “Changing Content Display”](#)
- [第 6.12 节 “Concept: Image Styles”](#)

What are responsive image styles?

The core Responsive Image module provides responsive image styles. This allows you to have images in your website that are specifically sized for different screen sizes. This is useful, for example, to make your site load faster on mobile devices because image sizes are optimized for smaller screens.

A responsive image style is a mapping between images styles and breakpoints. Breakpoints are the points where a responsive design needs to change in order to respond to different screen sizes. Responsive image styles can only be used if the breakpoints are defined in the theme.

When a responsive image style is defined, it can be used in the display settings for Image fields. This allows the site to display responsive images using the HTML5 picture tag.

Related topics

[第 6.3 节 “Adding Basic Fields to a Content Type”](#)

Additional resources

- [Drupal.org community documentation page "Responsive web design"](#)
- [Drupal.org community documentation page "Responsive images in Drupal 8"](#)
- [Drupal.org community documentation page "Working with breakpoints in Drupal 8"](#)

Attributions

Adapted by [Boris Doesborg](#) from [Responsive images in Drupal 8](#), copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

6.15. Concept: Text Formats and Editors

What are text formats and filters?

Text formats change how HTML tags and other text are processed and displayed on your site. Text formats are composed of a series of filters, each of which transforms text. When users create content, a text format is associated with the content, and the full, original text is stored in the database. The content is then passed through the filters in the text format before it becomes output on the site.

The core Filter module provides text format functionality, and the core Standard installation profile sets up Basic HTML, Restricted HTML, and Full HTML text formats. Each text format has an associated permission, so that you can allow only trusted users to use permissive text formats. This restricts untrusted users to text formats like Basic HTML, which filters out dangerous HTML tags.

What are the editors associated with text formats?

Each text format can be associated with an editor, such as a visual WYSIWYG (What You See Is What You Get) HTML editor. The core Text Editor module provides the ability to associate editors with text formats, and to configure the editors (such as adding and removing buttons from their toolbars). The core CKEditor module provides the industry-standard editor known as CKEditor, so that it can be used to edit HTML content on your site.

What is cross-site scripting?

Cross-site scripting (XSS) is a security vulnerability typically found in websites. In a site that is not well protected, malicious users can enter script into web pages that are viewed by other users (for example, in a comment or in the body of a page). A cross-site scripting vulnerability may be used by attackers to login as another user. It is important to configure the text formats of your website to prevent such abuse.

Related topics

[第 13.3 节 “Concept: Security and Regular Updates”](#)

Additional resources

- [Drupal.org community documentation page "Filter module: text formats that filter user input"](#)
- [Wikipedia page "Cross-site scripting"](#)

Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

6.16. Configuring Text Formats and Editors

Goal

Add a horizontal rule tag to the Basic HTML text format, and a corresponding button to its editor configuration.

Prerequisite knowledge


[第 6.15 节 “Concept: Text Formats and Editors”](#)

Site prerequisites

- The core Filter, Editor, and CKEditor modules must be installed. They are installed on your site when you install with the core Standard installation profile.
- The Basic HTML text format must exist. This is created on your site when you install with the core Standard installation profile.

Steps

1. In the Manage administrative menu, navigate to Configuration > Content authoring > Text formats and editors (admin/config/content/formats). The Text formats and editors page appears.
2. Click Configure for the Basic HTML text format. The Basic HTML page appears.
3. Note that CKEditor is selected in the Text editor field. This allows you to configure the editor's toolbar.
4. Drag the horizontal rule button from Available buttons to Tools in Active toolbar. You may need to click the Show group names link to see the Tools group name.



5. Note that you can change the Filter processing order.
6. In the field Allowed HTML tags, add <hr> to what is already present.

过滤条件设置

Limit allowed HTML tags and correct faulty HTML

已启用

允许的HTML标签

```
<hr> <a hreflang href> <em> <strong> <cite> <blockquote cite>
<code> <ul type> <ol start type> <li> <dl> <dt> <dd> <h2 id> <h3
id> <h4 id> <h5 id> <h6 id> <p> <br> <span> <img data-caption
data-align data-entity-uuid data-entity-type alt src height width>
```

A list of HTML tags that can be used. By default only the *lang* and *dir* attributes are allowed for all HTML tags. Each HTML tag may have attributes which are treated as allowed attribute names for that HTML tag. Each attribute may allow all values, or only allow specific values. Attribute names or values may be written as a prefix and wildcard like *jump-**. JavaScript event attributes, JavaScript URLs, and CSS are always stripped.

Display basic HTML help in long filter tips

向所有链接添加rel="nofollow"

7. Click Save configuration. You will be taken back to the Text formats and editors page. A message will be displayed saying that the text format has been updated.

✓ 输入格式 *Basic HTML* 已被更新...

Expand your understanding

If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Attributions

Written by [Boris Doesborg](#).

第 7 章 Managing User Accounts

7.1. Concept: Users, Roles, and Permissions

What are Users?

Anyone who visits your website is a user, including you. There are three groups of users:

- Users who are not logged in, or anonymous users
- Users who are logged in, or authenticated users
- The administrative user account that was automatically created when you installed your site, or User 1. See [第 7.2 节 “Concept: The User 1 Account”](#).

What are Permissions?

The ability to do actions on your site (including viewing content, editing content, and changing configuration) is governed by permissions. Each permission has a name (such as View published content) and covers one action or a small subset of actions. A user must be granted a permission in order to do the corresponding action on the site; permissions are defined by the modules that provide the actions.

What are Roles?

Rather than assigning individual permissions directly to each user, permissions are grouped into roles. You can define one or more roles on your site, and then grant permissions to each role. The permissions granted to authenticated and anonymous users are contained in the Authenticated user and Anonymous user roles, and depending on the installation profile you used when you installed your site, there may also be an Administrator role that is automatically assigned all permissions on your site.

Each user account on your site is automatically given the Authenticated user role, and may optionally be assigned one or more additional roles. When you assign a role to a user account, the user will have all the permissions of the role when logged in.

It is a good practice to make several roles on your site. In the farmers market site example, you might want the following roles:

- A Vendor role that allows vendors to edit their own vendor listing page
- A Content editor role for editing the general farmers market pages
- A User manager role for managing the vendor accounts
- The Administrator role that was installed with your site, for expert users to manage the site configuration

Related topics

- [第 7.3 节 “Creating a Role”](#)
- [第 7.5 节 “Assigning Permissions to a Role”](#)
- [第 7.6 节 “Changing a User’s Roles”](#)
- [第 7.4 节 “Creating a User Account”](#)
- [第 7.2 节 “Concept: The User 1 Account”](#)
- [第 7.7 节 “Assigning Authors to Content”](#)

Additional resources

- [Drupal.org community documentation page "Users, roles and permissions"](#)
- [Drupal.org community documentation page "Managing Users"](#)
- [Drupal.org community documentation page "User Roles"](#)

Attributions

Adapted by [Mark LaCroix](#), [Boris Doesborg](#), and [Jennifer Hodgdon](#) from "[User Roles](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

7.2. Concept: The User 1 Account

Prerequisite knowledge

[第 7.1 节 “Concept: Users, Roles, and Permissions”](#)

What is the user 1 account?

During the installation of your site, you created the first user account. Each user account internally has a numeric user ID, and since the ID of this user is one, it is commonly referred to as the user 1 account. This user account is special, because independent of what roles it is assigned, someone logged in as user 1 has permission to do all actions on the site, including viewing and editing all content, editing any user account, changing site configuration, installing and uninstalling modules, and running the update script.

Because of this level of permission, some people refer to this account as the root user, similar to the "root" user account that has full administrative permissions in Linux and other operating systems.

It is usually better to make separate accounts for each administrative user, giving them the Administrator role, rather than having all administrative users log in using the user 1 account. There are several reasons for this:

- Some actions and updates on the site are logged, and if everyone uses the same account, it is difficult to know who did them if you have questions.
- The Administrator role permissions can be modified to be safer than the full permissions of the user 1 account, so that people do not inadvertently change site features that shouldn't be changed.
- People's responsibilities on a site may change over time. With ordinary user accounts, this can be mirrored in permissions by assigning or unassigning roles to their user accounts. If they are all using the user 1 account, this is more difficult.
- On some sites, the author of content or comments is displayed or tracked, and if everyone uses the same account to create content, it is difficult to know who created the content.

It is not possible to delete the user 1 account from the administrative user interface. It would be possible to do with a database query, but it could cause problems in your site and is not advisable.

Additional resources

[Drupal.org community documentation page "Accounts and roles"](#)

Attributions

Written and edited by [Mark LaCroix](#) and [Jennifer Hodgdon](#).

7.3. Creating a Role

Goal

Create a Vendor role to allow some - but not all - users to perform specific tasks.

Prerequisite knowledge

[第 7.1 节 “Concept: Users, Roles, and Permissions”](#)

Steps

1. In the Manage administrative menu, navigate to People > Roles (admin/people/roles).
2. You will find default roles Anonymous user, Authenticated user, and Administrator already present.

角色 ★

列表 权限 角色

首页 » 管理 » 人员

一个角色定义一组拥有若干权限的用户。这些权限在[权限页面](#)上定义。这里，您可以定义您网站上的名称和显示次序。建议将最低权限的用户排到前头（例如，匿名用户）而将高级用户排到后面（例如，网站管理员）。未登录用户拥有匿名用户权限。登录用户拥有注册用户权限，其余用户拥有对应用户角色的权限。

+ 添加角色

		Show row weights
名称	操作	
⊕ 匿名用户	编辑 ▾	
⊕ 已登录用户	编辑 ▾	
⊕ 管理员	编辑 ▾	

保存

3. Click Add Role to add a custom role.
4. Type Vendor in the Role name field. Click Save.

添加角色 ★

首页 » 管理 » 人员 » 角色

角色名称 *

摊贩

此角色的名称。如“管理员”、“编辑”、“网站架构”。

保存

5. You will see the message "Role Vendor has been added." displayed at the top of the page.

✓ 角色 摊贩 已添加。

Expand your understanding

- 第 7.5 节 “[Assigning Permissions to a Role](#)”
- 第 7.6 节 “[Changing a User's Roles](#)”

Additional resources

[Drupal.org community documentation page "User Roles"](#)

Attributions

Adapted and edited by [Jack Probst](#), [Boris Doesborg](#), and [Joe Shindeler](#) from "[User Roles](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#)

7.4. Creating a User Account

Goal

Create Vendor user accounts for Sweet Honey and Happy Farm vendors.

Prerequisite knowledge

- [第 7.1 节 “Concept: Users, Roles, and Permissions”](#)
- [第 7.2 节 “Concept: The User 1 Account”](#)
- [第 7.3 节 “Creating a Role”](#)

Site prerequisites

The Vendor role must exist on your site. See [第 7.3 节 “Creating a Role”](#).

Steps

1. In the Manage administrative menu, navigate to People (admin/people).
2. Click Add user.

添加用户 ☆

[首页](#) » [管理](#) » [人员](#)

这个页面允许管理员注册新用户。用户的电子邮件地址和用户名必须是唯一的。

电子邮件地址

有效的电子邮件地址。系统的所有电子邮件将发送到此地址。此电子邮件地址不会公开，仅用于通过电子邮件接收新密码、特定新闻或通知。

用户名 *

可以使用下列特殊字符：空格、点(.)、连字符(-)、单引号(')、下划线(_)以及@符号。

密码 *

密码强度：

确认密码 *

密码匹配：

在两个文本框中为新帐户输入密码。

状态

- 阻止
- 有效

角色

- 已登录用户
- 管理员
- 摊贩

- 将新建帐号通知用户

头像

 No file selected

3. Fill in the form fields. See the table below.

Field name	Explanation	Example value
Email address	A valid email address for the vendor. All emails from the system will be sent to this address. The email address is not made public.	honey@example.com
Username	A username for the vendor that they will use to sign in or author content items. Spaces are allowed; punctuation is not allowed	Sweet Honey

Field name	Explanation	Example value
	except for periods, hyphens, apostrophes, and underscores.	
Password	A password the vendor will use to sign in to the site. You can see how safe the password is on the Password strength gauge. You also get tips on how to make it safer.	(Make a secure password)
Confirm password	Type the same password to avoid any typing mistakes.	(Repeat password)
Status	Set the status of the user account. Blocked users will not be able to sign in.	Active
Roles	Set the role of the user account.	Vendor
Notify user of new account	Whether or not to send a notification to the vendor's email address.	Checked
Picture	Click Browse and select a picture to upload. Pay attention to size restrictions.	Photo of the vendor
Contact settings	Enable or disable the display of a contact form for the account.	Checked

4. Click Create new account. You will get a notification about the user account creation.

✓ 图档已经重新缩小过，以符合所允许的最大尺寸: 85x85 像素。

A welcome message with further instructions has been emailed to the new user 甜蜜蜜蜂.

5. Create a second Vendor account for Happy Farm by following the steps above.

Expand your understanding

Create a user account for yourself.

Attributions

Written by [Diána Lakatos](#) at [Pronovix](#).

7.5. Assigning Permissions to a Role

Goal

Change the permissions for the Vendor role so that users can create, edit, and delete Recipe and Vendor content, format the content, and contact each other.

Prerequisite knowledge

- [第 7.1 节 “Concept: Users, Roles, and Permissions”](#)

Site prerequisites

The Vendor role must exist on your site. See [第 7.3 节 “Creating a Role”](#).

Steps

1. In the Manage administrative menu, navigate to People > Roles (admin/people/roles). The Roles page appears.
2. Click Edit permissions in the dropdown for the Vendor role. The Edit role page appears where you can see all the available actions for the website such as, for example, Post comments or Administer blocks. The available permissions depend on the modules that are installed in the site. Note: Some permissions may have security implications. Be cautious while assigning permissions to roles.
3. Check the boxes for the following permissions, listed by module:

Module	Permission
Contact	Use users' personal contact forms
Filter	Use the Restricted HTML text format
Node	Recipe: Create new content
Node	Recipe: Edit own content
Node	Recipe: Delete own content
Node	Vendor: Edit own content
Quick Edit	Access in-place editing

权限	摊贩
ROLE requires permission to view revisions and delete rights for nodes in question, or administer nodes.	<input type="checkbox"/>
基本页面: 编辑任何内容	<input type="checkbox"/>
基本页面: 编辑自己的内容	<input type="checkbox"/>
基本页面: Revert revisions Role requires permission <i>view revisions</i> and <i>edit rights</i> for nodes in question, or <i>administer nodes</i> .	<input type="checkbox"/>
基本页面: 查看修订版本	<input type="checkbox"/>
摊贩: 创建新内容	<input type="checkbox"/>
摊贩: 删除任何内容	<input type="checkbox"/>
摊贩: 删除自己的内容	<input type="checkbox"/>
摊贩: Delete revisions Role requires permission to <i>view revisions</i> and <i>delete rights</i> for nodes in question, or <i>administer nodes</i> .	<input type="checkbox"/>
摊贩: 编辑任何内容	<input type="checkbox"/>
摊贩: 编辑自己的内容	<input checked="" type="checkbox"/>
摊贩: Revert revisions Role requires permission <i>view revisions</i> and <i>edit rights</i> for nodes in question, or <i>administer nodes</i> .	<input type="checkbox"/>
摊贩: 查看修订版本	<input type="checkbox"/>
食谱: 创建新内容	<input checked="" type="checkbox"/>
食谱: 删除任何内容	<input type="checkbox"/>
食谱: 删除自己的内容	<input checked="" type="checkbox"/>
食谱: Delete revisions Role requires permission to <i>view revisions</i> and <i>delete rights</i> for nodes in question, or <i>administer nodes</i> .	<input type="checkbox"/>
食谱: 编辑任何内容	<input type="checkbox"/>

4. Click Save permissions. You will get a message saying your changes have been saved.

✓ 更改已保存。

Expand your understanding

- Log in as one of the new users you created in 第 7.4 节 “Creating a User Account”. Verify whether you have the correct permissions.

- 第 7.6 节 “Changing a User’s Roles”

Related concepts

[第 7.2 节 “Concept: The User 1 Account”](#)

Additional resources

[Drupal.org community documentation page "Managing Users"](#)

Attributions

Adapted and edited by [Boris Doesborg](#), [Brian Emery](#), and [Jojo Alphonso](#) at [Red Crackle](#), from "[User Roles](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

7.6. Changing a User’s Roles

Goal

Change or add roles to a given user, either by editing a single-user or by applying a bulk operation.

Prerequisite knowledge

[第 7.1 节 “Concept: Users, Roles, and Permissions”](#)

Site prerequisites

The user account that you want to update, and the role you want it to have, must already exist. See [第 7.4 节 “Creating a User Account”](#), [第 7.3 节 “Creating a Role”](#), and [第 7.5 节 “Assigning Permissions to a Role”](#).

Steps

Updating the roles using single-user editing method

1. In the Manage administrative menu, navigate to People (admin/people).
2. Locate the user 1 account (named "admin") to assign it the Administrator role. If it is not immediately visible, use the Name or email contains filter, or other filters, to narrow down the list.


3. Click Edit to update the user account.

The screenshot shows the 'People' management interface. At the top, there are tabs for '列表' (List), '权限' (Permissions), and '角色' (Roles). Below the tabs, there's a breadcrumb navigation '首页 > 管理'. A blue button '+ 添加用户' (Add User) is visible. There are search filters for 'Name or email contains' and dropdowns for '状态' (Status), '角色' (Role), and '权限' (Permissions), all set to '任意' (Any). A '过滤' (Filter) button is present. Below the filters, there's a section titled '动作' (Actions) with a dropdown menu containing 'Add the Administrator role to the selected users'. A '应用于选中项' (Apply to selected items) button is below it. The main table lists three users:


<input type="checkbox"/>	用户名	状态	角色	注册了	上次访问	操作
<input type="checkbox"/>	开心农场	有效	• 摆販	12 秒	从未	<button>编辑</button>
<input type="checkbox"/>	甜蜜蜂蜜	有效	• 摆販	16 秒	从未	<button>编辑</button>
<input type="checkbox"/>	admin	有效	• Administrator	1 天 2 小时	1 分钟 34 秒 ago	<button>编辑</button>

At the bottom left is another '应用于选中项' (Apply to selected items) button.

4. On the Edit page, scroll down to Roles section. Check the Administrator role for the user account.



5. Click Save to update the user account. You should be returned to the People page and see a message saying that the changes have been saved.



Updating the roles using bulk editing method

- If the users Happy Farm and Sweet Honey did not already have the Vendor role, here is how you would add it. In the Manage administrative menu, navigate to People (admin/people).

2. Locate Vendor user accounts Sweet Honey and Happy Farm and check them. If they are not immediately visible, use the Name or email contains filter, or other filters, to narrow down the list.
3. Select Add the Vendor role to the selected users from the Action select list.

动作

为选中的用户添加 摆販 角色 | ▾

应用于选中项

<input type="checkbox"/>	用户名	状态	角色	注册了	上次访问	操作
<input checked="" type="checkbox"/>	开心农场	有效	• 摆販	17 秒	从未	编辑
<input checked="" type="checkbox"/>	甜蜜蜜蜂	有效	• 摆販	21 秒	从未	编辑
<input type="checkbox"/>	admin	有效	• Administrator	1 天 2 小时	1 分钟 39 秒 ago	编辑

应用于选中项

4. Click Apply to selected items. You should see a message indicating that the desired changes were made.

✓ 为选中的用户添加 摆販 角色 已被应用到 2 个条目。

Attributions

Written by [Chris Dart](#) and [Jennifer Hodgdon](#)

7.7. Assigning Authors to Content

Goal

Assign Vendor content items Happy Farm and Sweet Honey to the corresponding Vendor user accounts, so they can edit their own Vendor profiles on the site.

Prerequisite knowledge

- [第 7.1 节 “Concept: Users, Roles, and Permissions”](#)

Site prerequisites

- The Vendor content type must exist, and your site must have at least two Vendor content items. See [第 6.1 节 “Adding a Content Type”](#), [第 6.3 节 “Adding Basic Fields to a Content Type”](#), and [第 5.2 节 “Creating a Content Item”](#).
- User accounts for at least two vendors must exist. See [第 7.4 节 “Creating a User Account”](#).

Steps

1. In the Manage administrative menu, navigate to Content (admin/content).
2. Find Vendor content item Happy Farm in the list. If it is not immediately visible, you can filter the list by Published status, Content type (Vendor), Title, or Language. Click Edit for the Vendor content item you would like to assign an author to.
3. Locate the information block and click Authoring information.

The screenshot shows the 'Authoring information' dialog box for a published content item. It includes sections for 'Published' status, 'Last saved: 06/20/2017 - 06:55', 'Author: Happy Farm', a checked checkbox for 'Create new revision', and a large text area for 'Revision log message' with placeholder text '简要描述您所做的更改。' (Briefly describe your changes.). Below this is a 'URL Path Settings' section with a collapsed 'Publishing Information' section containing fields for 'Author' (set to 'Happy Farm (6)'), 'Published On' (set to '2017-06-19 05:27:31'), and a note about the date format. At the bottom is a 'Recommend Options' section.

4. Start typing the Vendor's user name Happy Farm in the Authored by field. The field lists matching user names. Select the Vendor's user name from the list.
5. Click Save and keep published.
6. You will get a notification that the Vendor content item has been updated.

✓ 摆販 开心农場 已更新。

7. Follow these steps again to assign Vendor content item Sweet Honey to the Vendor user account Sweet Honey.

Attributions

Written by [Diána Lakatos](#) at [Pronovix](#).

第 8 章 Blocks

8.1. Concept: Blocks

What is a block?

Blocks are individual pieces of your site's web page layout. They are placed inside the regions (see [第 2.1 节 “Concept: Regions in a Theme”](#)) of your theme, and can be created, removed, and rearranged in the Block layout (admin/structure/block) administration page. Examples of blocks include the Who's online listing, the main navigation menu, and the breadcrumb trail. The main page content is also a block.

Some modules make new blocks available for placement on your site. For example, when the core Search module is installed and configured, it provides a block that contains a search form. You may also create and place your own custom blocks.

Each block has its own configuration settings, which allow you to select which pages of your site will display the block. It is even possible to place multiple copies of a block, each with its own separate configuration and visibility rules.

Related topics

- [第 2.1 节 “Concept: Regions in a Theme”](#)
- [第 8.2 节 “Creating A Custom Block”](#)
- [第 8.3 节 “Placing a Block in a Region”](#)

Attributions

Adapted by [Les Lim](#) from "[Working with blocks \(content in regions\)](#)" copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

8.2. Creating A Custom Block

Goal

Create a block showing the hours and location of the farmers market.

Prerequisite knowledge

- [第 8.1 节 “Concept: Blocks”](#)

- 第 2.1 节 “Concept: Regions in a Theme”

Steps

1. In the Manage administrative menu, navigate to Structure > Block layout > Custom block library (admin/structure/block/block-content).
2. Click Add custom block. The Add custom block page appears.
3. Fill in the fields as shown below.

Field name	Value
Block description	Hours and location block
Body	Open: Sundays, 9 AM to 2 PM, April to September Location: Parking lot of Trust Bank, 1st & Union, downtown Anytown.

添加自定义区块 ☆

首页

区块描述 *

开放时间和地点区块

A brief description of your block.

正文

B I | | | , , | 源码

文本格式 Basic HTML ▾ 关于文本格式 ?

修订版本信息
No revision

修订日志消息

The log entry explaining the changes in this revision.

保存

4. Click Save. A message appears indicating the block has been saved.

Expand your understanding

- Edit the content of your custom block. In the Manage administrative menu, navigate to Structure > Block layout > Custom block library (admin/structure/block/block-content). Find your block in the list and click Edit to make changes.
- Place the block you created in the sidebar. See [第 8.3 节 “Placing a Block in a Region”](#) for details.

Additional resources

[Drupal.org community documentation page "Working with blocks \(content in regions\)"](#)

Attributions

Adapted by [Jacob Redding](#) and [Boris Doesborg](#) from [Working with blocks \(content in regions\)](#), copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

8.3. Placing a Block in a Region

Goal

Place the Opening hours and location block in the website's sidebar.

Prerequisite knowledge

[第 8.1 节 “Concept: Blocks”](#)

Site prerequisites

- The core Bartik theme must be installed and set as default. See [第 4.6 节 “Configuring the Theme”](#).
- The Opening hours and location block must exist. See [第 8.2 节 “Creating A Custom Block”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Block layout (admin/structure/block). The Block layout page appears, listing the theme's regions.

2. Ensure that in the secondary tab the core Bartik theme is selected. Block placement is defined per theme.
3. Locate the region Sidebar second in the list and click Place block next to it. The Place block window appears, listing all the blocks.
4. Locate the block Opening hours and location and click Place block next to it. The Configure block window appears. Fill in the fields as shown below.

Field name	Value
Title	Hours and location
Display title	Checked
Region	Sidebar second

You can also hide or display the block on specific pages. In the case of the Farmer's market website you do not set any of these configuration options because you want to show the block everywhere.

配置区块 ☆

首页 » 管理 » 结构 » 区块布局 » 配置区块

✓ 基本区块 开放时间和地点区块 已创建。

区块描述: 开放时间和地点区块

标题 *
开放时间和地点 机读名称: hours_location [编辑]

显示标题

可见性

内容类型 未受限制	内容类型 <input type="checkbox"/> 基本页面 <input type="checkbox"/> 食谱 <input type="checkbox"/> 摆販
页面 未受限制	
角色 未受限制	

区域
Sidebar second

选择显示此区块的区域。

保存区块

5. Click Save block. The Block layout page appears. You can drag blocks to change the order in which they will appear.
6. Verify that the Opening hours and location block is listed in the Sidebar second region, and click Save blocks.

The block has been placed on the sidebar of all pages that use the core Bartik theme.



Expand your understanding

- Remove the Powered by Drupal block from the Footer fifth region by setting the region to - None -.
- Remove the Tools block from the Sidebar first region by setting the region to - None -. This block is only visible to logged-in users.
- Place the User login block in a region.
- If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

第 9 章 Creating Listings with Views

9.1. Concept: Uses of Views

Prerequisite knowledge

- [第 2.4 节 “Concept: Modular Content”](#)
- [第 2.3 节 “Concept: Content Entities and Fields”](#)

What is a view?

A view is a listing of content on a website. The core Views module handles the display of views, and the core Views UI module allows you to create and edit them in the administrative interface. When you define views, you are interested in taking data from your website and displaying it to the user.

What types of data can be displayed using views?

You can create views to output practically any content entity that is stored in the system. For example, you can create the following lists for the farmers market site:

- Lists of vendors
- Lists of recipes
- Lists of the most recent content on the site
- Lists of users on the site

What are the ways data can be output using views?

A listing created by a view can be in any of the following forms:

- Table with sortable fields
- Grid layouts
- Teasers or pictures that link to articles
- Blocks
- JSON output
- RSS feeds
- Calendars
- On-screen slideshows

Related topics

- [第 9.2 节 “Concept: The Parts of a View”](#)

- [第 9.3 节 “Creating a Content List View”](#)

Attributions

Written and edited by [Michael Lenahan](#) at [erdfisch](#), and [Jojo Alphonso](#) at [Red Crackle](#).

9.2. Concept: The Parts of a View

Prerequisite knowledge

- [第 2.3 节 “Concept: Content Entities and Fields”](#)
- [第 2.4 节 “Concept: Modular Content”](#)
- [第 9.1 节 “Concept: Uses of Views”](#)
- [第 5.1 节 “Concept: Paths, Aliases, and URLs”](#)
- [第 8.1 节 “Concept: Blocks”](#)

What are the parts of a view?

When you are editing a view in the administrative interface, you will see the following parts (or sections), which allow you to specify what data to output, in what order, and in what format:

Display

Each view can have one or more displays, each of which produces one type of output. Options for display types include:

Page

Makes output at a particular URL, for the main page content at that URL.

Block

Makes output in a block, which can be placed on pages.

Feed

Makes an RSS or another type of feed.

Attachment

Makes output that you can attach to another display.

Format

Depending on the display type, you can choose to output your data in a table, grid, HTML list, or another format. Some formats also give you a second choice that lets you output either rendered entities or fields; other formats do not give you this choice (for example, if you use a table format, you must always use fields).

Fields

Depending on the format choice, you may be able to choose which content fields are output. For example, if you were making a view of recipe content items, in a block display you might show only the recipe names, while in a full page display you might also show an image field because you have more space.

Filter criteria

Filters limit the data to be output, based on criteria such as whether the content has been published or not, the type of content, or a field value. For instance, to make a view of recipe content items, you would need to filter to the Recipe content type, and to published recipes. Filters can also be exposed, which means that users will have a form where they can choose their own filter values. You might use this on a Recipe page to let users filter for recipes with certain ingredients.

Sort criteria

Defines the order to present the output, which can be based on any content field.

Contextual filters

Contextual filters are like regular filters, except that the values come from the context of the view display, such as the full URL of the page being displayed, the current date or time, or some other value that can be detected by the view calculation.

Relationships

Relationships allow you to expand what is displayed in your view, by relating the base content being displayed to other content entities. Relationships are created using fields on the base content that relate it to the other content; one example is that all regular content items have an author field, which references the user account of the person who authored the content. Once you have created a relationship, you can display fields from the referenced entity in the view.

Related topics

[第 9.3 节 “Creating a Content List View”](#)

Attributions

Written and edited by [Surendra Mohan](#) and [Jennifer Hodgdon](#).

9.3. Creating a Content List View

Goal

Create a page listing vendors that will be automatically updated whenever a vendor is added, deleted, or updated on the site.

Prerequisite knowledge

- [第 9.1 节 “Concept: Uses of Views”](#)
- [第 9.2 节 “Concept: The Parts of a View”](#)

Site prerequisites

- The core Views and Views UI modules must be installed. These are installed for you when you install with the core Standard installation profile.
- The Vendor content type must exist, with URL and Main image fields. Your site must have a couple of Vendor content items. See [第 6.1 节 “Adding a Content Type”](#), [第 6.3 节 “Adding Basic Fields to a Content Type”](#), and [第 5.2 节 “Creating a Content Item”](#).
- The Medium (220x220) image style must be defined. This is created on your site when you install the core Image module (installed with the core Standard installation profile) but can be recreated if deleted. See [第 6.13 节 “Setting Up an Image Style”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Views > Add view (admin/structure/views/add). The Add view wizard appears.
2. Fill in the fields as shown below.

Field name	Explanation	Example value
View name	Name of the view that will be visible in the administration pages	Vendors
Show of type	Type of information listed in the view	Content
sorted by	Specify content type	Vendor
Create a page	List order	Title
Page title	Create a page that displays the view	Checked
Path	Title show above the view	Vendors
Display format	Address of the page	vendors
Items to display	Type of list	Table
Use a pager	Number of items visible on the page	10
Create a menu link	Split up the list in several pages if there are more items	Checked
	Add the view page to the menu	Checked

Field name	Explanation	Example value
Menu	Menu in which to add the link	Main navigation
Link text	Label of the link in the menu	Vendors

添加视图 ☆

首页 > 管理 > 结构 > 视图

视图基本信息

视图名称 *****
 机读名称: vendors [\[编辑\]](#)

描述

视图设置

显示: |▼| 类型为: |▼| 标记为: 排序依据: |▼|

页面设置

生成一个页面

页面标题

路径

页面显示设置

显示格式:
 |▼| 的: |▼|

要显示的条目
 |▼|

3. Click Save and edit. The view configuration page appears.
4. Click Add from the dropdown button in the Fields section. The Add fields pop-up appears.
5. Enter the word "image" in the search field.
6. Check Main image in the table.
7. Click Apply. The Configure field: Content: Main Image pop-up appears.
8. Fill in the fields as shown below.

Field name	Explanation	Example value
Create a label	Add a label before the field value	Unchecked
Image style	The format of the image	Medium (220x220)
Link image to	Add a link to the content item	Content

9. Click Apply. The view configuration page appears.

10. Click Add from the dropdown button in the Fields section. The Add fields pop-up appears.
11. Enter the word "body" in the search field.
12. Select Body in the table.
13. Click Apply. The Configure field: Content: Body pop-up appears.
14. Fill in the fields as shown below.

Field name	Explanation	Example value
Create a label	Add a label before the field value	Unchecked
Formatter	The presentation of the field value	Summary or trimmed
Trimmed limit:	The number of maximum characters shown	120

15. Click Apply. The view configuration page appears.
16. Click Content: Title (Title) in the Fields list. The Configure field: Content: Title pop-up appears.
17. Uncheck Create a label. This will remove the label that was created by the wizard.
18. Click Apply. The view configuration page appears.
19. Click Rearrange from the dropdown button in the Fields section. The Rearrange fields pop-up appears.
20. Drag the fields into the right order: Image, Title, Body.
21. Click Apply. The view configuration page appears.
22. Optionally, click Update preview for a preview.
23. Click Save.

摊贩 (内容) ☆

首页 > 管理 > 结构 > 视图 > Vendors > Edit

Displays

Page **+ 添加** 编辑视图的名称和描述

显示名称: Page

标题
标题: 摊贩

格式
格式: 表格 | 设置

字段 新增
内容: 主图
内容: 标题
内容: Body

过滤条件 新增
内容: 发布状态 (= 是)
内容: 内容类型 (= 摊贩)

排序标准 新增
内容: 标题 (升序)

页面设置
路径: /vendors
菜单: 普通: 摊贩
访问: 权限 | 查看已发布的内容

高级 查看 Page

页面
新增
页脚
新增
无任何结果时的行为
新增
分页器
使用分页器: 微型 | 迷你分页器, 10 个项目
更多链接: 否

保存 取消

24. Navigate to the homepage and click Vendors from the main navigation to see the result.

ANYTOWN FARMERS MARKET 爱林镇农贸市场 农场新鲜食材 我的帐户 退出

首页 关于 摊贩

工具	摊贩	开放时间和地铁
添加内容	 开心农场 开心农场, 种植您喜爱的蔬菜。	开放时间和地铁 开放时间: 4月 - 9月, 星期日, 09:00 - 14:00 位置: 市中心水滴大厦一楼
	 甜蜜蜂蜜 甜蜜蜂蜜常年供应各式口味蜂蜜	

Expand your understanding

The link to the view in the main navigation will probably not be in the right place. Change the order of the menu items in the main navigation. See [第 5.8 节 “Changing the Order of Navigation”](#).

Attributions

Written/edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

9.4. Duplicating a View

Goal

Create a page listing recipes by duplicating the existing Vendors view. Modify the page so that the recipes are displayed in a grid and can be filtered by ingredients.

Prerequisite knowledge

- [第 9.1 节 “Concept: Uses of Views”](#)
- [第 9.2 节 “Concept: The Parts of a View”](#)
- [第 9.3 节 “Creating a Content List View”](#)

Site prerequisites

- The Vendor and Recipe content types must exist; both must have Main image fields, and the Recipe content type must have an Ingredients field. Your site must also have a couple of Recipe content items. See [第 6.1 节 “Adding a Content Type”](#), [第 6.3 节 “Adding Basic Fields to a Content Type”](#), [第 6.6 节 “Setting Up a Taxonomy”](#), [第 6.9 节 “Changing Content Entry Forms”](#), and [第 5.2 节 “Creating a Content Item”](#).
- The Vendors view must exist. See [第 9.3 节 “Creating a Content List View”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Views (admin/structure/views). Find the view "Vendors" and click Duplicate in its dropdown button.

The screenshot shows the 'Views' configuration page. At the top, there are tabs for '视图' (Views) and '设置' (Settings). Below the tabs, there are navigation links: '首页' (Home), '管理' (Management), and '结构' (Structure). A blue button '+ 添加视图' (Add View) is visible. A search bar 'Filter by view name, machine name, description, or display path' is present. The main area is titled '已启用' (Enabled) and contains a table of views:

视图名称	机读名称	描述	DISPLAYS	操作
Who's new	who_s_new	Shows a list of the newest user accounts on the site.	区块	<button>编辑</button>
Who's online block	who_s_online	Shows the user names of the most recently active users, and the total number of active users.	区块	<button>编辑</button>
分类术语	taxonomy_term	属于某个分类词汇的内容。	种子 (/taxonomy/term/%/feed) 页面 (/taxonomy/term/%)	<button>编辑</button>
摊贩	vendors		页面 (/vendors)	<button>编辑</button> <button>复制</button> <button>禁用</button> <button>删除</button>

2. Name the duplicate "Recipes" and click Duplicate. The view configuration page appears.
3. Change the title of the view page to "Recipes" by clicking Vendors in the Title section. The Page: The title of this view pop-up appears. Type in "Recipes". Click Apply.

标题

食谱

这个标题将与视图一同显示,无论标题显示在哪里;比如,作为页面标题,区块标题,等等.

应用

取消

4. Change from a table to a grid format by clicking Table in the Format section. The Page: How should this view be styled pop-up appears. Check Grid and click Apply. The Page: Style options pop-up appears. Retain the default values and click Apply.
5. Retain only the title and image fields for the Recipes view by clicking Content: Body in the Fields section. Click Remove in the pop-up that appears.
6. Change the content type filter to use the Recipe content type by clicking Content: Type (=Vendor) in the Filter criteria section. In the Configure filter criterion: Content: Type pop-up, check Recipe and uncheck Vendor. Click Apply.
7. Add a further filter that is exposed to visitors by clicking Add in the Filter criteria section. Search for "ingredients" and check "Ingredients (field_ingredients)". Click Add and configure filter criteria.
8. The appearing pop-up offers extra settings on vocabulary and selection type. Click Apply and continue. The next pop-up allows you to expose this filter to visitors. Fill in the fields as shown below, and click Apply.

Field name	Explanation	Example value
Expose this filter to visitors, to allow them to change it	Allow visitors to filter and search	Checked
Required	Whether a value has to be provided or not	Unchecked
Label	Label shown for this filter on the view page	Find recipes using...

显示在: recipe

把这个过滤条件显示给网站的访问者，允许他们可以更改这个过滤条件。

要暴露的过滤器类型

- Single filter
- 群组过滤器

分组过滤允许使用预设操作/值配对的选择。

已请求

标签

查找食谱使用 ...

描述

9. Change the Path label field to "Recipes" by clicking "/vendors" in the Page settings section. In the pop-up that appears, enter the path "recipes" and click Apply.

Note that when editing a view, you enter paths without the leading "/", unlike on other administrative pages (such as when providing a path to a content item page).

10. Change the menu link title by clicking "Normal: Vendors" in the Page settings section. In the pop-up that appears, change the title to "Recipes" and click Apply.
11. In order to use Ajax (see [Ajax entry in the Glossary](#)) to make filtering and paging faster for users, click Advanced to expand the section for more options. In the Other section, change Use AJAX: No to "Yes" by clicking No and checking Use AJAX in the pop-up that appears. Click Apply.
12. Click Save to save the view.
13. Go back to the home page and click Recipes in the navigation to view the new Recipes page.

The screenshot shows a Drupal-based website for "Anytown Farmers Market". The header features a logo with a farm scene and the text "ANYTOWN FARMERS MARKET" and "FARM FRESH FOOD". The page title is "爱林镇农贸市场" (Ailin Town Agricultural Products Market) with the subtitle "农场新鲜食材" (Farm Fresh Ingredients). The main navigation includes "首页", "关于", "摊贩", and "食谱". On the left, a sidebar titled "工具" (Tools) has a "添加内容" (Add Content) button. The central content area is titled "食谱" (Recipes) and contains a search bar with placeholder text "查找食谱使用 ...". Below the search bar is a "应用" (Apply) button. Two images are displayed: one of fresh carrots and another of a salad. Labels "新鲜胡萝卜" (Fresh Carrots) and "蔬菜沙拉" (Vegetable Salad) are placed under their respective images. To the right, a sidebar titled "开放时间和地铁" (Opening Hours and Subway) provides information: "开放时间: 4月 - 9月, 星期日, 09:00 - 14:00" (Open hours: April - September, Sunday, 09:00 - 14:00) and "位置: 市中心水滴大厦一楼" (Location: 1st floor of the Waterdrop Building, city center).

Expand your understanding

The link to the view in the main navigation will probably not be in the right place. Change the order of the menu items in the main navigation. See [第 5.8 节 “Changing the Order of Navigation”](#).

Related concepts

- [第 2.5 节 “Planning your Content Structure”](#)
- [Ajax entry in the Glossary](#)

Attributions

Written and edited by [Laura Vass](#) at [Pronovix](#), and [Jojo Alphonso](#) at [Red Crackle](#).

9.5. Adding a Block Display to a View

Goal

Add a block display to the Recipes view to display the most recent recipes in a sidebar, and change its configuration without changing the existing Recipes page view.

Prerequisite knowledge

- [第 9.1 节 “Concept: Uses of Views”](#)
- [第 9.2 节 “Concept: The Parts of a View”](#)
- [第 9.3 节 “Creating a Content List View”](#)

Site prerequisites

- The Recipe content type must exist, it must have a Main image field, and your site must have a couple of Recipe content items. See [第 6.1 节 “Adding a Content Type”](#), [第 6.3 节 “Adding Basic Fields to a Content Type”](#), [第 6.9 节 “Changing Content Entry Forms”](#), and [第 5.2 节 “Creating a Content Item”](#).
- The Thumbnail (100x100) image style must be defined. This is created on your site when you install the core Image module (installed with the core Standard installation profile) but can be recreated if deleted. See [第 6.13 节 “Setting Up an Image Style”](#).
- The Recipes view must exist. See [第 9.3 节 “Creating a Content List View”](#) and [第 9.4 节 “Duplicating a View”](#).

Steps

1. In the Manage administrative menu, navigate to Structure > Views (admin/structure/views). Find the view "Recipes" and click Edit from its dropdown button. Alternatively, navigate to the Recipes page in the main site navigation, and click the Edit view contextual link in the main area of the page. See [第 4.1 节 “Concept: Administrative Overview”](#) for information about contextual links.
2. Create a new block display by clicking Add in the Displays section. Click Block from the dropdown button. The new display is created, and the focus is automatically switched to its configuration.

显示



3. Change the title of this display by clicking Block next to Display name. The Block: The name and the description of this display pop-up appears. Change the Administrative name to "Recent recipes". Click Apply.
4. Change the title of the view by clicking Title: Recipes in the Title section. In the pop-up that appears, select This block (override) from the For select list. Change the title to "New recipes" and click Apply (this display).



5. Change the view's style by clicking Format: Grid in the Format section. In the pop-up that appears, select This block (override) from the For select list. Select Unformatted list and Click Apply (this display). You can further configure the style options in the next pop-up that appears. Then click Apply.
6. Configure the image field by clicking Content: Main image in the Fields section. In the pop-up that appears, select This block (override) from the For select list. Select Image style Thumbnail (100x100). Click Apply (this display).

配置字段: 内容: 主图 ☆

首页 » 管理 » 结构 » 视图

为 **这个block (覆盖)**

显示在: vendor, recipe

生成标签

标签

在标签后加一个冒号

排除显示

载入字段并隐藏，一般用来群组字段或作为其它字段的占位符。

Column used for click sorting

target_id

Used by Style: Table to determine the actual column to click sort the field on. The default is usually fine.

格式化器

图像

图像样式

缩略图 (100×100)

[Configure Image Styles](#)

图像链接到

内容

▶ 样式设定

▶ 重写结果

▶ 无任何结果时的行为

7. Remove ingredients as a filter by clicking Content: Ingredients (exposed) in the Filter criteria section. In the pop-up that appears, select This block (override) from the For select list. Click Remove at the bottom.

8. Configure how you want the content to be sorted in the view by clicking Add in the Sort criteria section. In the pop-up that appears, select This block (override) from the For select list. Check the field Authored on (from Content category), and then Add and configure sort criteria.
9. In the appearing configuration pop-up, select Sort descending to have the most recent recipes appear first. Click Apply.
10. Specify the number of items to be displayed by clicking Use pager: Mini in the Pager section. In the pop-up that appears, select This block (override) from the For select list. Under Pager, select Display a specified number of items. Click Apply (this display). In the Block: Pager options pop-up, provide "5" as the value for Items to display. Click Apply.
11. Click Save. You will either see the view editing page again, or the Recipes page, depending on what you did in step 1. You should also see a message saying that the view has been saved.



12. Place the "Recipes: Recent Recipes" block in the Sidebar second region. See [第 8.3 节 "Placing a Block in a Region"](#). Navigate to the site's home page to see the block.

The screenshot shows the homepage of the 'Anytown Farmers Market'. The header features a logo for 'ANYTOWN FARMERS MARKET' with a sun and farm building icon, and the text '爱林镇农贸市场' (Ailin Town Agricultural Products Market) and '农场新鲜食材' (Farm Fresh Ingredients). The navigation menu includes '首页', '关于', '摊贩', and '食谱'. The main content area has a heading '首页' with buttons for '查看', '编辑', '删除', and '修订版本'. Below it is a welcome message: '欢迎来到城市市场 -- 您的农贸市场邻居!' and opening hours: '开放时间: 4月 - 9月, 星期日, 09:00 - 14:00' and '位置: 市中心水滴大厦一楼'. To the right, there are two sidebar blocks: '开放时间和地铁' (Opening Hours and Subway) with information about opening times and location, and '新食谱' (New Recipes) featuring a photo of a colorful salad and labels for '新鲜胡萝卜' (Fresh Carrot) and '蔬菜沙拉' (Vegetable Salad).

Attributions

Written and edited by [Laura Vass](#) at [Pronovix](#), [Jennifer Hodgdon](#), and [Jojo Alphonso](#) at [Red Crackle](#).

第 10 章 Making Your Site Multilingual

10.1. Concept: User Interface, Configuration, and Content translation

Prerequisite knowledge

- [第 1.5 节 “Concept: Types of Data”](#)
- [第 1.2 节 “Concept: Modules”](#)
- [第 2.3 节 “Concept: Content Entities and Fields”](#)

What can be translated on your site?

The base language for the software that your site runs (core software, modules, and theme) is English. However, you can create either a site that displays in a different language or a multi-lingual site; if you do so, all relevant text, images, and file attachments should be shown in the appropriate language for each site visitor. You need to have the core Language module installed in order to use a language other than English on the site.

There are three types of information that you can translate, each with its own method for translating:

User interface text

Built-in text present in the core software, modules, and themes. This can be translated from the base English language of the software into the language(s) of your site. Typically, rather than needing to translate this text yourself, you can download translations. You need to have the core Interface Translation module installed in order to translate this text.

Configuration text

Text whose structure and initial values are defined by the core software, modules, and theme, but that you can edit. Examples include the labels for fields in your content types, header text in views, your site name, and the content of automatic email messages that your site sends out. After creating configuration text in the default language of your site, you can translate it into other languages. You need to have the core Configuration Translation module installed in order to translate this text.

Content text and files

If your site is multilingual, you can configure the content fields on your site to be translatable. After creating content in one language, you can translate it into other languages. Fields can contain textual information or uploaded files, and for each field on each content type, you can configure it to be translatable or non-translatable. You need to have the core Content Translation module installed in order to translate this text.

Related topics

- [第 10.2 节 “Adding a Language”](#)
- [第 10.3 节 “Configuring Content Translation”](#)
- [第 10.4 节 “Translating Content”](#)
- [第 10.5 节 “Translating Configuration”](#)

Attributions

Written by [Jennifer Hodgdon](#).

10.2. Adding a Language

Goal

Add one or more languages to your site and define which one is used by default.

Prerequisite knowledge

[第 10.1 节 “Concept: User Interface, Configuration, and Content translation”](#)

Steps

1. Install the four core multilingual modules (Language, Interface Translation, Content Translation, and Configuration Translation), by following the steps in [第 4.3 节 “Installing a Module”](#).
2. In the Manage administrative menu, navigate to Configuration > Regional and language > Languages (admin/config/regional/language).
3. Click Add language.
4. Select Spanish (or your preferred language) from the Language name select list. Click Add language. After waiting for translations to finish downloading, you will be returned to the Languages page, with a confirmation message and the new language shown.

The screenshot shows the 'Language' configuration page in Drupal. At the top, there are tabs for 'List' and 'Detection & Selection'. Below the tabs, the breadcrumb navigation shows '首页 > 管理 > 配置 > 地区和语言'. A success message box contains the text: '语言 English 已创建，并且现在可用。' and 'Use one of the language switcher blocks to allow site visitors to switch between languages. You can enable these blocks on the block administration page.' Below this, a note says: '重新安排语言的顺序，这一顺序将显示在语言切换器区块中，也将在编辑内容界面中显示于可选择的语言中。此顺序不影响检测和选择。' Another note states: '网站默认语言也可以设置。不建议在正在使用的网站上修改默认语言。检测和选择语言页的配置已选择页面 可在备用语言上选择语言。' A third note says: '添加语言、启用新模块或主题时会自动导入界面翻译。可用翻译更新中的报告将显示翻译的状态。界面文本可以在 用户界面翻译 页面进行自定义。' At the bottom left is a blue button labeled '+ 添加语言'. On the right, there is a '显示行的权重' (Show row weights) link. The main table lists two languages: 'Chinese, Simplified' (selected as default) and 'English'. Each row has an 'Edit' button. A blue '保存配置' (Save configuration) button is at the bottom left.

5. Follow the steps in [第 8.3 节 “Placing a Block in a Region”](#) to place the Language switcher block in the Sidebar second region. This will enable site visitors to switch between languages, once the site has been translated.

Expand your understanding

- [第 10.3 节 “Configuring Content Translation”](#)
- [第 10.4 节 “Translating Content”](#)

Additional resources

[Drupal.org page "Resource Guide: Configuring a Multilingual Site"](#)

Attributions

Written and edited by [Leila Tite](#), [Jennifer Hodgdon](#), and [Boris Doesborg](#).

10.3. Configuring Content Translation

Goal

Make Custom block, Custom menu link, and Content entity types translatable. Select specific subtypes and set which fields of these can be translated.

Prerequisite knowledge

- [第 2.3 节 “Concept: Content Entities and Fields”](#)

- 第 10.1 节 “Concept: User Interface, Configuration, and Content translation”

Site prerequisites

The core Content Translation module must be installed, and your site must have at least two languages. See [第 10.2 节 “Adding a Language”](#).

Steps

1. In the Manage administrative menu, navigate to Configuration > Regional and language > Content language and translation (admin/config/regional/content-language).
2. Under Custom language settings, check Content, Custom block and Custom menu link to make these entity types translatable.

自定义语言设置

- 评论
- 联系信息
- 内容
- 自定义区块
- 定制菜单链接
- 文件
- 快捷方式链接
- 分类术语
- 用户

保存配置

3. Configuration options appear for Content, Custom block and Custom menu link. Choose the subtypes you want to translate for each entity type. Check Basic page for Content, Basic block for Custom block and Custom menu link for Custom menu link.
4. Verify the settings for the entity types as shown below:

Field name	Explanation	Example value
Default language	The default language for the entity subtype	Site's default language (English)
Show language selector on create and edit pages	Whether or not the language selector should be shown while editing and creating content	Checked

默认语言 基本区块

站点默认语言 (Chinese, Simplified) ▾

关于语言选项的解释可在[语言列表页面](#)中找到。 在创建和编辑页面显示语言选择器

5. Choose the fields that should be translatable for Basic page as shown in the table below. If a field is not translation-dependent, leave it unchecked. Enabling translation for fields that are numbers or dates has use for accountability or implementing workflows.

Field name	Explanation	Example value
Title	The title of the content	Checked
Authored by	The author	Unchecked
Publishing status	Whether the content has been published or not	Checked
Authored on	Date of publishing	Unchecked
Changed	Date of last update	Unchecked
Promoted to front page	Whether the content will be included in some content views	Unchecked
Sticky at top of lists	Whether the content will be displayed first in some content views	Unchecked
URL alias	Nicer URL for the content	Checked
Body	The main content of the page	Checked

发布状态

标题

作者

发布于

已更改

推荐到首页

置顶

URL别名

正文

6. Similarly, check the appropriate boxes for translatable fields belonging to Basic block and Custom menu link.
7. Click Save configuration.

Expand your understanding

- [第 10.5 节 “Translating Configuration”](#)
- [第 10.4 节 “Translating Content”](#)

Additional resources

- [Blog post "Multilingual Drupal 8 tidbits, part 5"](#)
- [Blog post "Multilingual Drupal 8 tidbits, part 17"](#)

Attributions

Written and edited by [Laura Vass](#) at [Pronovix](#), [Jojo Alphonso](#) at [Red Crackle](#), and [Jennifer Hodgdon](#).

10.4. Translating Content

Goal

Translate the home page to Spanish.

Prerequisite knowledge

[第 10.1 节 “Concept: User Interface, Configuration, and Content translation”](#)

Site prerequisites

- The Home content item must exist. See [第 5.2 节 “Creating a Content Item”](#).
- The core Content Translation module must be installed, and your site must have at least two languages. See [第 10.2 节 “Adding a Language”](#).
- The Basic page content type must be configured to be translatable. See [第 10.3 节 “Configuring Content Translation”](#).

Steps

- In the Manage administrative menu, navigate to Content (admin/content).
- Locate the home page. You can search for it by entering "Home" in the title field.
- Select Translate from the dropdown button in the row of the Home content item. The page Translations of Home appears.
- Click Add in the row Spanish.

语言	翻译	源语言	状态	操作
Chinese, Simplified (Original language)	首页	n/a	已发表	编辑
English	n/a	n/a	未翻译	添加

- Note that the user interface has switched to Spanish. To switch it back to English, remove the first instance of es in the browser's URL. For example, if your URL looks like example.com/es/node/5/translations/add/en/es, remove the es that comes immediately after example.com.
- Fill in the fields as shown below. You will have to click and expand URL path settings on the right to provide the value for URL alias.

Field name	Explanation	Value
Title	Translated title of the page	Página principal

Field name	Explanation	Value
Body	Translated body of the page	Bienvenido al mercado de la ciudad - el mercado de agricultores de tu barrio! Horario: Domingos de 9:00 a 14:00. Desde Abril a Septiembre Lugar: parking del Banco Trust número 1. En el centro de la ciudad
URL path settings > URL alias	Translated address of the webpage	pagina-principal

7. Click Save and keep published (this translation).
8. Go to your site's home page to view the newly translated page.

Expand your understanding

- Follow the steps above to translate more content on your site.
- [第 10.5 节 “Translating Configuration”](#)

Attributions

Written by [Boris Doesborg](#).

10.5. Translating Configuration

Goal

Translate the labels on the Recipes view page into Spanish.

Prerequisite knowledge

- [第 10.1 节 “Concept: User Interface, Configuration, and Content translation”](#)
- [第 9.3 节 “Creating a Content List View”](#)

Site prerequisites

- The core Configuration Translation module must be installed, and your site must have at least two languages. See [第 10.2 节 “Adding a Language”](#).
- The Recipes view must exist. See [第 9.3 节 “Creating a Content List View”](#) and [第 9.4 节 “Duplicating a View”](#).

Steps

The basic steps for translating any configuration on your site are:

1. Locate the page where the configuration you want to translate is created or edited in the site's primary language. For example, to translate the site name, you need to find the page where you would edit the site name (see [第 4.2 节 “Editing Basic Site Information”](#)).
2. Find a link, tab, or button on the page that says "Translate" or something similar. Click this link, tab, or button.
3. Find a button that will let you add a translation in the desired language, and click this button.
4. Enter the translation in the form, and save.

Most configuration is fairly straightforward and intuitive to edit in this manner. Views configuration is an exception, because the translation editing form is nothing like the view editing form, and it is complex and hierarchical rather than being a simple form with just a few fields. As an example of how to translate a view, here are the steps to translate the labels in the Recipes view to Spanish:

1. In the Manage administrative menu, navigate to Structure > Views (admin/structure/views).
2. Locate the Recipes view and click Translate from the dropdown button.
3. Click Add in the row Spanish. The page Add Spanish translation for Recipes view appears.
4. Find Displays > Master Display settings > Recipes default display Options. Translate the Display title from "Recipes" to "Recetas".
5. Find Displays > Master display settings > Recipes default display options > Exposed form > Reset options. Translate Submit button text (Apply) to "Aplicar". The other buttons and labels in this section do not appear on the Recipes page or block, and do not need to be translated.

6. Find Displays > Master display settings > Recipes default display options > Filters > (Empty) taxonomy term ID > Find recipes using... Expose. In the Label field, enter "Encontrar recetas usando...".
7. Click Save translation.
8. Navigate to the Recipes page and switch to Spanish using the Language switcher block. Verify that the labels have been translated.

Expand your understanding

- Translate the block display title in the Recent recipes display settings section of the Recipes view.
- Translate the page title in the Vendors view.
- Translate other configuration. Some examples of where to find the translation pages:
 - To translate the site name, navigate in the Manage administrative menu to Configuration > System > Basic site settings > Translate system information (admin/config/system/site-information/translate).
 - To translate the contact form, navigate in the Manage administrative menu to Structure > Contact forms (admin/structure/contact). Click Translate in the dropdown button in the Website feedback row.
 - To translate the name of a menu, navigate in the Manage administrative menu to Structure > Menus (admin/structure/menu). Click Translate in the dropdown button for the menu whose name you want to translate.

- Menu items within a menu are considered to be content (not configuration); see [第 10.3 节 “Configuring Content Translation”](#) to enable translation. Once translation is enabled, navigate in the Manage administrative menu to Structure > Menus (admin/structure/menu). Click Edit menu in the dropdown button for the menu whose links you want to translate. Click Translate in the dropdown button for the link you want to translate.
- To translate field labels on a content type, navigate in the Manage administrative menu to Structure > Content types (admin/structure/types). Click Manage fields in the dropdown button for the content type whose field labels you want to edit. Click Translate in the dropdown button for the field whose label you want to edit.
- Translate content. See [第 10.4 节 “Translating Content”](#).

Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

第 11 章 Extending and Customizing Your Site

11.1. Finding Modules

Goal

Find and evaluate modules on Drupal.org.

Prerequisite knowledge

- 第 1.1 节 “Concept: Drupal as a Content Management System”
- 第 1.2 节 “Concept: Modules”

Steps

1. Go to [Drupal.org](https://www.drupal.org/project/project_module), and navigate to Download & Extend > Modules (https://www.drupal.org/project/project_module).
2. Filter your search using the categories on the module search page. Fill in the fields as shown below.

Field name	Explanation	Example value
Maintenance status	How actively should the module be maintained?	Actively maintained
Development status	What kind of development should the module undergo?	Any
Module categories	The module's topic area.	Administration
Core compatibility	The version of the core software the module is compatible with.	8.x
Status	Project status: Sandbox projects are experimental projects. Full projects have already gone through an approval process, but they can still be in development.	Full projects
Search Modules	Search for Admin Toolbar, a module that will be	Admin Toolbar

Field name	Explanation	Example value
	covered in detail later. Alternatively, you can also leave the field blank if you are not sure which module to search for.	
Sort by	Order your search results by criteria like Most installed (popular modules that many sites use) or Last release (date of latest version released).	Most installed

46 Modules match your search

Maintenance status - Any ▾

Development status - Any ▾

Module categories - Any ▾

Core compatibility 8.x ▾

Status Full projects ▾

Stability All projects ▾

Search Modules Admin Toolbar

Sort by Most installed ▾

Search

- Click Search. Search results will appear.

Admin Toolbar

Posted by eme on 20 April 2015

What is Admin Toolbar module ?

Admin Toolbar intends to improve the default Drupal Toolbar (the administration menu at the top of your site) to transform it into a drop-down menu, providing a fast access to all administration pages.

The module works on the top of the default toolbar core module and is therefore a very light module and keeps all the toolbar functionalities (shortcut / media responsive).

How to use Admin Toolbar module ?

Just install it like any other module.

[Read more](#) · Categories: Actively maintained , Under active development , Administration

Adminimal Admin Toolbar (Drupal 8)

Posted by energie on 19 March 2016

This module is inspired by [Adminimal Administration Menu](#). It provides a minimalist style to [Admin Toolbar](#) for Drupal 8.

Although the "Adminimal" theme provides menu styling, there are some conflicts with Admin toolbar and styling will only be present when the admin theme is set like when editing content.

[Read more](#) · Categories: Actively maintained , Under active development , Administration ,

Theme Enhancements

Toolbar Themes

Posted by Jeff Burnz on 13 September 2016

Provides themes for the Drupal 8 Toolbar module. The main purpose of this module is to provide compact, minimal themes for the Toolbar and allow the site admin to show or hide tabs and icons.

Installation

Install like all other modules, then go to: [~/admin/config/toolbar-themes/settings](#)

[Read more](#) · Categories: Actively maintained , Under active development , Administration

4. To further evaluate a module, click its title in the list of search results to visit its project page.

Some aspects to pay attention to when evaluating modules:

- Project description: The description of the module on its project page should be clear and useful. You should get an idea of its features and requirements.
- Maintenance status: If a module is Actively maintained, you can be sure that there will be security updates, bug fixes and feature improvements provided on a regular basis. However, if the module is unmaintained or abandoned, you shouldn't use it.

- Development status: Under active development means you can expect new features to be added to the project, but some aspects (for example, API) may still change. Maintenance fixes only means that the project is considered feature complete.
- Reported installs, downloads: You can see how many people have downloaded and how many sites use the module. If it's only used by a few sites, it might be a unique solution that not many people need, or it might be a warning sign that you shouldn't use it either.
- Maintainers: When was the last commit (the last time someone updated something on the module) or last release (new version)? If the project has few open issues, a long time since commits/releases might be appropriate, but if it has a lot of open issues and there are no commits/releases, that would be a clue that it might be abandoned.
- Issues: See if there are any open issues, potential problems with the module. Check the Statistics to see how regularly issues are responded to.
- Resources: Check if the module has documentation or a README file, that can help you install, configure, explore, and test it.

Admin Toolbar

[View](#) [Version control](#) [Automated Testing](#)

Posted by [eme](#) on April 20, 2015 at 2:28pm

Admin Toolbar

What is Admin Toolbar module ?

Admin Toolbar intends to improve the default Drupal Toolbar (the administration menu at the top of your site) to transform it into a drop-down menu, providing a fast access to all administration pages.

The module works on the top of the default toolbar core module and is therefore a very light module and keeps all the toolbar functionalities (shortcut / media responsive).

How to use Admin Toolbar module ?

Just install it like any other module.

What more?

The module provides also a submodule called "Admin Toolbar Extra Tools" adding extra links like what does Admin Menu module for Drupal 7 (flush caches, run CRON, etc....).

Please provide feedback and ideas!

Complementary modules :

[Toolbar Menu](#) allows you to add easily any menu to your toolbar and plays nicely with Admin toolbar making them dropdown menus.

[Toolbar Anti-flicker](#) removes the impact of the admin toolbar sub-menu on the rest of the page. [Coffee](#) is a good module to look for admin paths.

[Adminimal Admin toolbar](#) provides a black theming, recommended for the [Adminimal theme](#).

Supporting organizations:

[emerya](#)

Project Information

Maintenance status: [Actively maintained](#)
 Development status: [Under active development](#)
 Module categories: [Administration](#)
 Reported installs: **14,813** sites currently report using this module. [View usage statistics](#).
 Downloads: 81,993
 Automated tests: Enabled
 Last modified: August 9, 2016
 shield [Stable releases receive coverage](#) from the [Drupal Security Team](#).
 Look for the shield icon below.

Maintainers for Admin Toolbar

[romainj](#) - 29 commits
 last: 5 days ago, first: 4 months ago
[eme](#) - 11 commits
 last: 3 weeks ago, first: 8 months ago
[matio89](#) - 23 commits
 last: 2 months ago, first: 1 year ago
[View all committers](#)
[View commits](#)

Issues for Admin Toolbar

To avoid duplicates, please search before submitting a new issue.

[Search](#)

[Advanced search](#)

[All issues](#)


15 open, 138 total

[Bug report](#)

6 open, 78 total

[Subscribe via e-mail](#)

Statistics



Resources

[Read license](#)

Expand your understanding

[第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#)

Attributions

Written by [Diána Lakatos](#) at [Pronovix](#).

11.2. Enabling and Disabling Maintenance Mode

Goal

Put your site in maintenance mode to allow users with the right permissions to use the site while users without this permission are presented with a message that the site is under maintenance.

Prerequisite knowledge

[第 13.3 节 “Concept: Security and Regular Updates”](#)

Steps

Enabling maintenance mode

1. In the Manage administrative menu, navigate to Configuration > Development > Maintenance mode ([admin/config/development/maintenance](#)). The Maintenance mode page appears.
2. Fill in the fields as shown below.

Field name	Explanation	Value
Put site into maintenance mode	Enable the maintenance mode	Checked
Message to display when in maintenance mode	The information that is shown to website visitors when the mode is enabled. Variables such as @site can be used in the message	@site is currently under maintenance but should be back shortly. Thank you for your patience.

3. Click Save configuration.
4. Verify that the site is in maintenance mode by accessing it from another browser where you aren't logged in. If you are not able to verify, try clearing the cache. See [第 12.2 节 “Clearing the Cache”](#).

爱林镇农贸市场
农场新鲜食材

网站正在维护

爱林镇农贸市场正在维护中，我们很快就会完成，请耐心等待。

Disabling maintenance mode

1. In the Manage administrative menu, navigate to Configuration > Development > Maintenance mode ([admin/config/development/maintenance](#)). The Maintenance mode page appears.
2. Fill in the fields as shown below.

Field name	Explanation	Value
Put site into maintenance mode	Disable the maintenance mode	Unchecked
Message to display when in maintenance mode	No message required while disabling. You can leave the field blank.	

3. Click Save configuration.
4. Verify that the site is no longer in maintenance mode by accessing it from another browser where you aren't logged in. If you are not able to verify, try clearing the cache. See [第 12.2 节 “Clearing the Cache”](#).

The screenshot shows a Drupal website for "Anytown Farmers Market". The header features a logo with a sun, clouds, and a farm, and the text "ANYTOWN FARMERS MARKET" and "FARM FRESH FOOD". The title "爱林镇农贸市场" and subtitle "农场新鲜食材" are displayed. A navigation menu includes "首页", "关于", "摊贩", and "食谱". On the right, there are three orange boxes: one for opening hours and subway info, one for new recipes (with images of carrots and salad), and one for languages (Chinese, English).

Expand your understanding

- [第 13.5 节 “Updating the Core Software”](#)
- [第 13.7 节 “Updating a Theme”](#)
- [第 13.6 节 “Updating a Module”](#)

Attributions

Written and edited by [Boris Doesborg](#), and [Jojo Alphonso](#) at [Red Crackle](#).

11.3. Downloading and Installing a Module from Drupal.org

Goal

Download and install the [contributed Admin Toolbar module](#), which allows you to easily browse through the administration section of the website.

Prerequisite knowledge

- [第 1.2 节 “Concept: Modules”](#)
- [第 11.1 节 “Finding Modules”](#)
- [第 3.2 节 “Concept: Additional Tools”](#)

Site prerequisites

- If you want to install modules via the website, the core Update Manager module must be installed. See [第 4.3 节 “Installing a Module”](#) for instructions on installing modules.
- If you want to use Drush, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

Steps

You can use the administrative interface or Drush to install a contributed module. If you are installing a custom module rather than a contributed module, if you see a message saying Installing modules and themes requires FTP access to your server, or if the steps below do not work to download and unpack the module files, follow the steps in [第 11.6 节 “Manually Downloading Module or Theme Files”](#). If you are installing a contributed module with external dependencies that are managed by Composer, follow the steps for downloading in [第 11.9 节 “Using Composer and Git to Download Files”](#). In either of these cases, then continue here with step 7 in the instructions for the administrative interface below.

Using the administrative interface

1. On the Admin toolbar project page on drupal.org (https://www.drupal.org/project/admin_toolbar), scroll to the Downloads section at the bottom of the page.
2. Copy the address of the tar.gz link. Depending on your device and browser, you might do this by right clicking and selecting Copy link address.

Downloads

Recommended releases

Version	Download	Date
8.x-1.16	tar.gz (55.55 KB) zip (62.65 KB)	2016-Jul-28

Development releases

Version	Download	Date
8.x-1.x-dev	tar.gz (16.89 KB) zip (26.26 KB)	2016-Aug-19

[View all releases](#)

3. In the Manage administrative menu, navigate to Extend (admin/modules). The Extend page appears.
4. Click Install new module. The Install new module page appears.

安装新的模块 ☆

首页 » 管理 » 扩展

您可以在 [drupal.org](#) 上找到模块和主题。支持下列扩展名: tar tgz gz bz2 zip。

从URL安装

例如: <http://ftp.drupal.org/files/projects/name.tar.gz>

或者

上传并安装模块或主题包

 No file selected.

比如: 你本地计算机的%filename

安装

5. In the field Install from a URL, paste the copied download link. This value could look like this: https://ftp.drupal.org/files/projects/admin_toolbar-8.x-1.14.tar.gz
6. Click Install to upload and unpack the new module on the server. The files are being downloaded to the modules directory.
7. Click Enable newly added modules to return to the Extend page. If you used the manual uploading procedure, start with this step, and reach the Extend page by using the Manage administrative menu and navigating to Extend (admin/modules).
8. Locate and check Admin toolbar.
9. Click Install to turn on the new module.

Using Drush

1. Find the project name for the module you want to install, which is the last segment of the module's project page URL. For example, if the project URL is https://www.drupal.org/project/admin_toolbar, the project name is "admin_toolbar".
2. Run the following Drush commands, giving the project name (for example, admin_toolbar) as a parameter:

```
drush dl admin_toolbar
drush en admin_toolbar
```

3. Follow the instructions on the screen.

Expand your understanding

- Verify that the [contributed Admin Toolbar module](#) is working by browsing through the menu in the administration section.
- Install and configure the [contributed Pathauto module](#) so that content pages in your site get nice URLs by default. See [第 5.1 节 “Concept: Paths, Aliases, and URLs”](#) for more on URLs.

- If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Additional resources

- [Drupal.org community documentation page "Contributed modules"](#)
- ["Download and Extend" page on Drupal.org](#)
- [Admin Toolbar module on Drupal.org](#)

Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

11.4. Finding Themes

Goal

Find and evaluate themes on Drupal.org.

Prerequisite knowledge

- [第 1.1 节 “Concept: Drupal as a Content Management System”](#)
- [第 1.3 节 “Concept: Themes”](#)

Steps

1. Go to <https://www.drupal.org>, and navigate to Download & Extend > Themes (https://www.drupal.org/project/project_theme).
2. Filter your search using the categories on the theme search page. For example, you might use these filters:

Field name	Explanation	Example value
Maintenance status	How actively is the theme maintained? If a theme is actively maintained, you can expect bug fixes and improvements on a regular basis.	Actively maintained
Development status	What kind of development is the theme undergoing? If you select Under active	Any

Field name	Explanation	Example value
	development, you can expect new features to be added, and some aspects may still change. If you select Maintenance fixes only, it means that the theme is considered complete.	
Core compatibility	The Drupal version the theme is compatible with.	8.x
Status	Sandbox projects are experimental projects. Full projects have already gone through an approval process, but they can still be in development.	Full projects
Search Themes	Search by search term in the theme's description.	-
Sort by	Order your search results by criteria like Most installed (popular themes that many sites use) or Last release (date of latest version released).	Most installed

179 Themes match your search

Maintenance status ▾

Development status ▾

Core compatibility ▾

Status ▾

Stability ▾

Search Themes

Sort by ▾

3. Click Search. Search results will appear.

Bootstrap

Posted by [wundo](#) on 18 May 2008

“ Sleek, intuitive, and powerful mobile first front-end framework for faster and easier web development. Bootstrap has become one of the most popular front-end frameworks and open source projects in the world.

This base theme bridges the gap between Drupal and the [Bootstrap Framework](#).

Features

- [jsDelivr CDN](#) for "out-of-the-box" styling and faster page load times.
- [Bootswatch](#) theme support, if using the CDN.
- Glyphicons support via [Icon API](#).
- Extensive integration and template/preprocessor overrides for most of the [Bootstrap Framework](#) CSS, Components and JavaScript
- Theme settings to further enhance the Drupal Bootstrap integration:
 - [Breadcrumbs](#)
 - [Navbar](#)
 - [Popovers](#)
 - [Tooltips](#)
 - [Wells](#) (per region)

Documentation

Visit the project's [official documentation site](#) or the markdown files inside the [./docs](#) directory.

Supported modules

Drupal 8

- [Bootstrap Layouts](#)

Drupal 7

- [Bootstrap Core](#)
- [jQuery Update](#)
- [Icon API](#)
- [Picture](#)
- [Views \(partial support\)](#)
- [Webform \(partial support\)](#)

5 Year Evolution (source)

<https://youtu.be/Cvq6MPJp2dI>

4. To further evaluate a theme, click its title in the list of search results to visit its project page.

Some aspects to pay attention to while evaluating themes:

- Introduction: The description of the theme on its project page should be clear and useful. A screenshot of the theme helps your evaluation as well.
- Downloads: The theme should be available for your version of the core software. Pay attention to the color-coding: Themes marked green are recommended to be used on live

sites, the ones marked yellow should be carefully evaluated before use, and the ones marked red are only recommended for testing.

- Project Information: Check the theme's maintenance and development status, and how frequently it's downloaded and installed.
- Issues: See if there are any open issues or potential problems with the theme.
- Resources: Check if the theme has documentation.

Expand your understanding

- [第 11.5 节 “Downloading and Installing a Theme from Drupal.org”](#)

Attributions

Written by [Diána Lakatos](#).

11.5. Downloading and Installing a Theme from Drupal.org

Goal

Download and install a theme from Drupal.org.

Prerequisite knowledge

- [第 11.4 节 “Finding Themes”](#)
- [第 3.2 节 “Concept: Additional Tools”](#)

Site prerequisites

If you want to install via the website, the core Update Manager module must be installed. See [第 4.3 节 “Installing a Module”](#) for instructions on installing modules.

If you want to use Drush, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

Steps

You can use the administrative interface or Drush to install a contributed theme. If you are installing a custom theme rather than a contributed theme, if you see a message saying Installing modules and themes requires FTP access to your server, or if the steps below do not work to download and unpack the theme files, follow the steps in [第 11.6 节 “Manually Downloading Module or Theme Files”](#). If you are installing a contributed theme with external dependencies that are managed by Composer, follow the steps for downloading in [第 11.9 节 “Using Composer and Git to Download Files”](#).

In either of these cases, then continue here with step 7 in the instructions for the administrative interface below.

Using the administrative interface

1. On the theme's project page on drupal.org (for example, <https://www.drupal.org/project/mayo>), scroll to the Downloads section at the bottom of the page.
2. Right-click tar.gz to copy the address.

Downloads

Version	Download	Date
8.x-1.3	tar.gz (437.31 KB) zip (486.26 KB)	2016-May-09
7.x-2.6	tar.gz (411.91 KB) zip (441.6 KB)	2015-Nov-11
7.x-1.4	tar.gz (386.35 KB) zip (403.15 KB)	2015-Nov-11

Development releases

8.x-1.x-dev	tar.gz (437.31 KB) zip (486.27 KB)	2016-Apr-27
7.x-2.x-dev	tar.gz (411.92 KB) zip (441.62 KB)	2016-Feb-11

[View all releases](#)

3. In the Manage administrative menu, navigate to Appearance (admin/appearance). The Appearance page appears.
4. Click Install new theme. The Install new theme page appears.

安装新主题 ☆

首页 » 管理

您可以在 [drupal.org](#) 上找到模块和主题。支持下列扩展名: tar tgz gz bz2 zip。

从URL安装

例如: <http://ftp.drupal.org/files/projects/name.tar.gz>

或者

上传并安装模块或主题包

No file selected.

比如: 你本地计算机的%filename

5. In the field Install from a URL, paste the copied download link. This value could look like <https://ftp.drupal.org/files/projects/mayo-8.x-1.3.tar.gz>.
6. Click Install to upload and unpack the new theme on the server. The files are being downloaded to the themes directory.
7. Click Install newly added themes to return to the Appearance page. If you used the manual uploading procedure, start with this step, and reach the Appearance page by using the Manage administrative menu and navigating to Appearance (admin/appearance).

8. Locate the new theme under Uninstalled themes and click Install and set as default to use it. All non-administrative pages on the site will now use this new theme.



Mayo 8.x-1.2

Simple but fully customizable and colorable responsive layout theme.

安装 | 安装并设置为默认

Using Drush

1. Find the project name for the theme you want to install, which is the last segment of the theme's project page URL. For example, if the project URL is <https://www.drupal.org/project/mayo>, the project name is mayo.
2. Run the following Drush commands, giving the project name (for example, mayo) as a parameter:

```
drush dl mayo  
drush en mayo  
drush config-set system.theme default mayo
```

3. Follow the instructions on the screen.

Expand your understanding

- In the Manage administrative menu, navigate to Appearance (admin/appearance) and uninstall any themes that you are not using.
- [第 11.1 节 “Finding Modules”](#)
- [第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#)
- If you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

Attributions

Written and edited by [Joe Shindelar](#) at [Drupalize.Me](#), and [Boris Doesborgh](#).

11.6. Manually Downloading Module or Theme Files

Goal

Manually download module or theme files and upload them to your site, if the website or Drush methods for installing or updating a module or theme do not work, or if you are placing a custom-written module or theme.

Prerequisite knowledge

- [第 1.2 节 “Concept: Modules”](#)
- [第 11.1 节 “Finding Modules”](#)
- [第 1.3 节 “Concept: Themes”](#)
- [第 11.4 节 “Finding Themes”](#)

Site prerequisites

You need to be facing any of the following to perform the manual download described in this topic:

- File permission issues
- FTP permission issues
- You created a custom module/theme or received its files from someone
- You could not successfully complete the instructions in [第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#), [第 11.5 节 “Downloading and Installing a Theme from Drupal.org”](#), [第 13.6 节 “Updating a Module”](#), or [第 13.7 节 “Updating a Theme”](#)

Skip this topic if none of the above applies to you.

Steps

If you are installing a module or theme from Drupal.org, follow the downloading instructions, and then the uploading/unpacking instructions. If you created the module or theme, skip the downloading step. Instead, create an archive file (that you know how to extract on the server) and proceed with the steps in uploading/unpacking, using whatever method is appropriate for the way you initially created the archive file.

Downloading the files

1. Open the module or theme project page on drupal.org; for example, the Admin toolbar page (https://www.drupal.org/project/admin_toolbar).
2. Scroll to the Downloads section near the bottom of the page.

Downloads


Version	Download	Date
8.x-1.19	tar.gz (17.07 KB) zip (27.02 KB)	2017-Apr-06
Development releases		
8.x-1.x-dev	tar.gz (19.49 KB) zip (29.81 KB)	2017-Jun-11

[View all releases](#)

- Click tar.gz to download the file to your computer.

Uploading the files to your site and unpacking them

- If you are adding a new module or theme, create subdirectories in your top-level modules and themes directories (if they don't already exist). Typically, people make a contrib subdirectory for contributed modules and themes that are downloaded from Drupal.org, and a custom subdirectory for modules and themes that they created. Your modules directory might look like this:



- If you are replacing an existing module or theme with an updated version, put the site into maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).
- If you are replacing an existing module or theme with an updated version, find and delete all the existing files and directories for the existing module or theme. Modules are normally located in directories under the top-level modules directory, and themes are normally located in directories under the top-level themes directory.
- Upload the .tar.gz file (or whatever archive you created) to your site. Place it in either the same location from which you deleted the directory (if replacing an existing module or theme) or the appropriate subdirectory of modules or themes (if adding a new module or theme).
- Extract the files from the .tar.gz archive (or whatever archive you created), making a subdirectory in the same location as the archive file. If you do not have terminal access, or your hosting server is not running Linux, your hosting control panel's file manager should provide a way to extract the files. If you have terminal access to your hosting server (running Linux) and you are using a tar.gz file, you can use a command like:

```
tar -xzf admin_toolbar-8.x-1.17.tar.gz
```

- Delete the compressed file from the server, unless your unpacking method already deleted it.
- Refer to [第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#), [第 11.5 节 “Downloading and Installing a Theme from Drupal.org”](#), [第 13.6 节 “Updating a Module”](#),

or [第 13.7 节 “Updating a Theme”](#) to complete the installation or update of the module or theme. Start at the step after the automatic download has been completed.

Expand your understanding

- If you work with multiple environments (for example, a local development site and a production site) you will have to repeat the steps on each environment, or re-clone the environment. See [第 11.8 节 “Making a Development Site”](#).
- If you added a new theme, navigate in the Manage administrative menu to Appearance (admin/appearance) and uninstall the old theme.

Additional resources

- [Drupal.org community documentation page "Updating modules"](#)
- [Drupal.org community documentation page "Installing contributed modules \(Drupal 8\)"](#)
- [Drupal.org community documentation page "Installing themes"](#)

Attributions

Written and edited by [Boris Doesborg](#), [Jennifer Hodgdon](#), and [Marc Isaacson](#).

11.7. Concept: Development Sites

What are Development Sites?

Development Sites are different copies of the same site used for developing, updating, and testing a site without risking the integrity of the live site.

An example deployment workflow for site building will usually include the sites mentioned below:

Local environment

The development process starts with developers working on new features, bug fixes, theming, and configuration in their local environment.

Development site

Developers push the changes they've been working on to the development site. For a team of more than one developer, version control is usually used. Git is a version control system that tracks your files for any changes. You can then commit those changes to a repository. Using Git allows team members to work on the same site without overriding each other's work. It also makes it possible to easily roll back to previous stages of the development.

Staging site

The staging site can be used for testing, or presenting the changes to the client for approval. QA (Quality Assurance) and UAT (User Acceptance Testing) are most

often carried out on the staging site. It is recommended to have live content on both the development and staging sites, so that you can test how the new features will work with the existing content.

Production site

The live site on the web available to visitors. It contains new features that have been proven safe to go live.

Based on the project's size, scope, requirements, or stakeholders, stages from the above workflow can be removed, or additional stages can be added. For example, a testing site before staging can be added to separate testing and user acceptance processes.

Related topics

- [第 11.8 节 “Making a Development Site”](#)
- [第 2.6 节 “Concept: Editorial Workflow”](#)

Additional resources

[Drupal.org community documentation page "Introduction to Git"](#)

Attributions

Written and edited by [Diana Lakatos](#), and [Jojo Alphonso](#) at [Red Crackle](#).

11.8. Making a Development Site

Goal

Make a copy of a site that you can use to develop new features and test updates on.

Prerequisite knowledge

[第 11.7 节 “Concept: Development Sites”](#)

Site prerequisites

- You have a live, developed site that you would like to make a copy of for development purposes.
- If you want to use Drush for some of the steps in this task, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

Steps

1. Follow the steps in [第 3.3 节 “Preparing to Install”](#), so that you have hosting set up for your development site, you know where the web root is for your development site, and you have an empty database and database user for your development site to use.

2. Make a database dump file from your live site's database. Try one of the following methods:

- If you are using MySQL as your database, and your live site's server has phpMyAdmin installed (it is available from many hosting control panels), use the Export tab in phpMyAdmin to export in SQL format. Using gzip compression on the output file is suggested, to reduce the file size.
- If you are using MySQL and have access to the command line, use this command (substituting in your site's database name, user name, and password):

```
mysqldump -u USERNAME -p'PASSWORD' DATABASENAME > BACKUPFILE.sql
```

- If you prefer to use Drush, use this command:

```
drush sql-dump > BACKUPFILE.sql
```

- Use the [contributed Backup and Migrate module](#) from within your live site. See [第 11.3 节“Downloading and Installing a Module from Drupal.org”](#) for instructions on installing contributed modules.

You now have a database dump stored in the file BACKUPFILE.sql. For security reasons, avoid storing this file on your hosting server anywhere under the Drupal site root. This will prevent others from getting a copy of your database.

3. Copy all of the files from the web root of your live site to the web root of your development site.

4. Edit the sites/default/settings.php file under your development site's top-level directory in a plain-text editor. Find the lines near the end that contain the database name, database username, and database password, and update them to the information about the development site database you set up. The lines look something like this (before editing):

```
$databases['default']['default'] = array (
  'database' => 'live_site_database_name',
  'username' => 'live_site_database_username',
  'password' => 'live_site_database_password',
```

5. Check whether your settings.php file has the following setting; if yes, then you will need to edit this to point to your development site URL instead of your production site URL:

```
$settings['trusted_host_patterns']
```

6. Import the database dump file you created, into the development site's database. Try one of the following methods:

- If you are using MySQL as your database, and your live site's server has PHPMyAdmin installed (it is available from many hosting control panels), use the Import tab in PHPMyAdmin. You may find that you have to restart the import a few times, if your database was large.
- If you are using MySQL and have access to the command line, use this command (substituting in your site's database name, user name, and password; if you made a gzip-compressed backup file, you will also need to uncompress it first):

```
mysql -u USERNAME -pPASSWORD DATABASE_NAME < BACKUPFILE.sql
```

- If you prefer to use Drush, use this command:

```
drush sql-query --file=BACKUPFILE.sql
```

7. If your development and live sites need to have different configuration, then you have to use configuration overrides in the settings.php file. The \$config variable will help you maintain override values separately from the standard configuration data. For instance, you might want the site name to be "Anytown Farmers Market" on the production site, but "Development Site for Anytown Farmers Market" on the development site. To do that, you could have the production value in the site configuration (in the database), and on the development site, in the settings.php file, you would need to have:

```
$config['system.site']['name'] = "Development Site for Anytown Farmers Market";
```

Expand your understanding

- Verify that the development site is working correctly.
- Log in to the development site as an administrator, and clear the cache. See [第 12.2 节 “Clearing the Cache”](#).
- [第 11.10 节 “Deploying New Site Features”](#)

Additional resources

- [Drupal.org community documentation page "Backing up a site"](#)
- [Drupal.org community documentation page "Create a Test Site"](#)

Attributions

Written and edited by [Jennifer Hodgdon](#), [Joe Shindelar](#) at [Drupalize.Me](#), and [Jojo Alphonso](#) at [Red Crackle](#).

11.9. Using Composer and Git to Download Files

Goal

Use Composer and/or Git to download files and dependencies in the core software, or in add-on modules and themes.

Prerequisite knowledge

- [第 3.2 节 “Concept: Additional Tools”](#)

- 第 11.7 节 “Concept: Development Sites”

Site prerequisites

If you want to use Git or Composer, they must be installed either on a local development server or your live site. See 第 3.2 节 “Concept: Additional Tools”.

Steps

If you are unable to install the Git or Composer tools on your live server, after following the steps in any of the sections below on your local server, you will need to transfer any updated or added files to your live server. The recommended procedure is to make an archive or zip file of the new and changed files, transfer the archive to your live server, and extract it there. If you are using Composer, make sure to check for updates and additions to the following files, in the root of your installation:

- vendor directory
- autoload.php
- composer.json
- composer.lock

Using Git to download a project

Follow these steps if you want to download the development version of the core software, or of a contributed module or theme, from the project’s Git version control repository:

1. In a command-line window, change to one level above the directory where you want the files to reside. For the core software, this would be your web root. For an add-on module, this would be the modules directory, or a sub-directory like contrib under the modules directory.
2. Locate the page for the project that you want to download on Drupal.org; for example, <https://www.drupal.org/project/drupal> for the core software, or https://www.drupal.org/project/admin_toolbar for the contributed Admin Toolbar module.
3. Click the Version control link near the top of the page, which opens up a page giving Git commands for this project.
4. Copy the git clone command under Setting up repository for the first time, and paste it into your command line. For example, it might be:

```
git clone --branch 8.2.x https://git.drupal.org/project/drupal.git
```

5. This will create a directory named with the short name of the project (drupal in this example), and download the required files into that directory. If necessary, rename the directory.
6. If you downloaded the drupal project (the core software), follow the instructions below to download its external dependencies.

7. Later on, you can change to the created directory and run the command `git pull` to update the files to the latest version from the Git repository for the project.

Using Composer to download external core dependencies

Follow these steps if you downloaded the core software files using Git, which does not include the external dependencies:

1. Change to the core software's root directory.
2. Run the command `composer install` at the command line. The external dependencies will be downloaded.

Using Composer to download the core software

Follow these steps if you have not yet downloaded or installed the core software, and you want to use Composer to download both the core software and its external dependencies:

1. At the command line, change to one level above the directory where you want the software to reside.
2. Enter this command, where `my_site_name` is the directory you want to create:

```
composer create-project drupal/drupal my_site_name
```

Using Composer to download a module or theme

Follow these steps if you have already downloaded the core software, and you want to use Composer to add a contributed module or theme (usually because it has external dependencies that need to be downloaded with Composer):

1. If you have not already done so, tell Composer about the download location for contributed modules and themes, by entering this command from the root of your site installation:

```
composer config repositories.drupal composer https://packages.drupal.org/8
```

2. If you have not already done so, you can optionally override the default location where Composer will put downloaded modules and themes. For example, typically you would want contributed modules to go in a `contrib` subdirectory of the top-level `modules` directory, instead of the default location of `modules`. To make this change, edit the `composer.json` file at the root level in your site installation. Find the line that says `"extra": {`, and add these lines following that line:

```
"installer-paths": {  
    "modules/contrib/{$name}": ["type:drupal-module"],  
    "modules/custom/{$name}": ["type:drupal-custom-module"],  
    "profiles/contrib/{$name}": ["type:drupal-profile"],  
    "themes/contrib/{$name}": ["type:drupal-theme"],  
    "themes/custom/{$name}": ["type:drupal-custom-theme"],  
    "libraries/{$name}": ["type:drupal-library"],
```

- ```
"drush/{$name}": ["type:drupal-drush"]
},

3. Each time you want to add a contributed module or theme, determine the project's short name. This is the last part of the URL of the project page; for example, the Geofield module, at https://www.drupal.org/project/geofield, has short name geofield.

4. To download the contributed module or theme, along with its external dependencies, enter the following command at the root of your site (substituting the short name of the module or theme for geofield):
```

```
composer require drupal/geofield
```

### Using Composer to update a project's files

Follow these steps to update the files for the core software or a contributed module or theme, after having already started to manage dependencies with Composer:

1. Determine the short name of the project you want to update. For the core software, it is drupal. For contributed modules and themes, it is the last part of the URL of the project page; for example, the Geofield module, at <https://www.drupal.org/project/geofield>, has short name geofield.
2. Determine how to enter the version number you want to update to. For example, for version 8.x-1.7 of a contributed module, you would enter just the 1.7, and for the core software version 8.3.1, you would enter 3.1.
3. Enter the following command at the root of your site (substituting the short name of the module or theme for geofield and the correct version number):

```
composer require drupal/geofield:1.7
```

### Additional resources

[Drupal.org community documentation page "Using Composer with Drupal"](#)

### Attributions

Adapted by [Jennifer Hodgdon](#) from "[Using Composer with Drupal](#)", copyright 2000-2017 by the individual contributors to the [Drupal Community Documentation](#).

## 11.10. Deploying New Site Features

### Goal

Copy a view that you have created in a local development site to the production site.

## Prerequisite knowledge

- [第 11.8 节 “Making a Development Site”](#)
- [第 11.11 节 “Synchronizing Configuration Versions”](#)
- [第 11.7 节 “Concept: Development Sites”](#)

## Site prerequisites

- The core Configuration Manager module must be installed in both the development and production sites. See [第 4.3 节 “Installing a Module”](#) for instructions on installing core modules.
- The Vendor content type must exist in both the development and production sites, with the same fields. See [第 6.1 节 “Adding a Content Type”](#).
- The Vendors view must exist in the development site but not the production site. See [第 9.3 节 “Creating a Content List View”](#).

## Steps

1. Open the local development site.
2. In the Manage administrative menu, navigate to Configuration > Development > Configuration synchronization > Export > Single item (admin/config/development/configuration/single/export). The Single export page appears.
3. Select View from the Configuration type list.
4. Select Vendors from the Configuration name list. The configuration appears in the textarea.
5. Copy the configuration from the textarea.

```

uuid: 791402ce-7967-4b8b-b902-2016a621762a
langcode: zh-hans
status: true
dependencies:
 config:
 - core.entity_view_mode.node.teaser
 - field.storage.node.body
 - field.storage.node.field_main_image
 - image.style.medium
 - node.type.vendor
 - system.menu.main
 module:
 - image
 - node
 - text
 - user
id: vendors
label: 摊贩
module: views
description: ''
tag: ''
base_table: node_field_data
base_field: nid
core: 8.x

```

6. Open the production site.
7. In the Manage administrative menu, navigate to Configuration > Development > Configuration synchronizationImport > Single item (admin/config/development/configuration). The Import page appears.
8. Select View from the Configuration type list.
9. Paste the configuration in the textarea.
10. Click Import. The confirmation page appears.
11. Click Confirm.
12. Verify that the view was imported by navigating in the Manage administrative menu to Structure > Views.

## Expand your understanding

The steps in this topic show how to export and import a single configuration item. However, often if you develop functionality on a development website and want to transfer it to your production site, you will need to transfer multiple configuration items. For instance, if you developed a new content type with fields, you would need to transfer several configuration items for each field, one for the content type itself, and possibly multiple view mode and form mode items, and they would have to be transferred in the right order. Getting this right can be both tedious and difficult.

As an alternative, you can export and import the complete configuration of the site. For this, you would need a local development site that is a clone of the production site (see [第 11.8 节 “Making a Development Site”](#)), and then you can follow the steps in [第 11.11 节 “Synchronizing Configuration Versions”](#) to synchronize configuration between development and production sites.

Another alternative is to use the [contributed Features module](#), which allows exporting and importing bundled functionality (for example, all the configuration for a photo gallery).

Finally, if you do not see the effect of these changes in your site, you might need to clear the cache. See [第 12.2 节 “Clearing the Cache”](#).

## Related concepts

- [第 11.7 节 “Concept: Development Sites”](#)
- [第 2.6 节 “Concept: Editorial Workflow”](#)

## Attributions

Written by [Boris Doesborg](#).

## 11.11. Synchronizing Configuration Versions

### Goal

Synchronize the configuration between a development and live site.

### Prerequisite knowledge

- [第 1.5 节 “Concept: Types of Data”](#)
- [第 3.3 节 “Preparing to Install”](#)
- [第 11.7 节 “Concept: Development Sites”](#)
- [第 11.8 节 “Making a Development Site”](#)

## Site prerequisites

- You must have a development copy of your production site. See [第 11.8 节 “Making a Development Site”](#).
- The core Configuration Manager module must be installed on both the development and production sites. See [第 4.3 节 “Installing a Module”](#) for instructions on how to install core modules.
- You must have changed configuration on either the production or development site (the source site), and want to synchronize the changes to the other site (the destination site). As an example, you can develop a new content type, fields, and views on your development site, and when it is all working correctly, deploy the changes to the live site.
- All configuration that should not be synchronized between the source and destination sites must be stored in configuration overrides in the settings.php file rather than in the database. See [第 11.8 节 “Making a Development Site”](#).

## Steps

1. In the source site, in the Manage administrative menu, navigate to Configuration > Development > Configuration synchronization > Export (admin/config/development/configuration/full/export).
2. Click Export. Your site will generate an archive of the full site configuration. Save the file on your local computer.
3. In the destination site, in the Manage administrative menu, navigate to Configuration > Development > Configuration synchronization > Import (admin/config/development/configuration/full/import).
4. Browse to find the downloaded configuration archive, and click Upload. Your configuration archive will be uploaded to the destination site, and you will be redirected to the configuration Synchronize page (admin/config/development/configuration) with a message saying your files were uploaded.
5. Verify that the differences shown on the page are what you expect. You may see configuration items that have been added, deleted, or changed; for changed items, you can click View differences to see what the changes are.
6. When you are satisfied, click Import all to import the configuration changes.

## Expand your understanding

- If the changes you have made involve only one configuration item (such as one view), you can use the single configuration export/import feature to deploy the change between sites. See [第 11.10 节 “Deploying New Site Features”](#).
- After the step where you export the full configuration from the source site, you might also want to unpack the archive and commit it to a version control system, such as Git, to track changes in your site configuration. See [第 3.2 节 “Concept: Additional Tools”](#).

Attributions

Written by [Jennifer Hodgdon](#).

---

# 第 12 章 Preventing and Fixing Problems

## 12.1. Concept: Cache

### Prerequisite knowledge

[第 1.1 节 “Concept: Drupal as a Content Management System”](#)

#### What is the page cache?

The software that runs your site, on each page request, must perform calculations and retrieve data from the database, in order to compose the page that is sent to the web browser or other application that is accessing the site. These calculations take time, which can mean that your page load time is longer than would be desirable.

There are several ways that page load time can be sped up, including installing software on the server. The system includes the core Internal Page Cache and Dynamic Page Cache modules, which do not require any additional server software; they use a database cache mechanism to speed up your site. The way these modules work is that during page calculations, intermediate results and the final page output are stored in a special database area (known as the cache). Then the next time a compatible request is made, intermediate or final results, as appropriate, can be retrieved and used rather than redoing the entire calculation. In addition, when content or data that affects a particular calculation is updated, the affected cached data is removed from the cache, forcing that part of the calculation to be redone the next time it is needed.

These caching modules normally work reasonably well, and offer at least some speed-up for most sites. However, sometimes the page cache can have problems, such as:

- Corrupted data in the cache, leading to garbled or incorrect page output
- Old data remaining in the cache too long, leading to outdated page output
- Insufficient caching, leading to slow page loads

#### What other data is cached?

Independent of whether the two page cache modules are installed on your site, the software that your site runs will still cache the output of many internal calculations. The core systems that cache data include:

- The theme system caches information in the database cache about which template files are used to render various types of data. If you are developing a new theme and add a new template file, you'll need to clear this cache to have your theme file recognized.

- CSS and JavaScript files can optionally be optimized and compressed (depending on your site settings). If so, the compressed versions are stored in the file system so that they don't have to be re-optimized too often. If you are developing a module or theme, you may need to either turn off or clear this file cache to have changes to CSS or JavaScript files be recognized.
- The system locates certain low-level PHP functions and classes, such as hook implementations and plugin classes, from your installed modules and stores information about which module has which functionality. If you are developing a new module or adding features to an existing module, you may need to clear this cache to have your new features be recognized.

## Related topics

If you have problems with your site, the first thing to try to fix it is usually to clear the cache. See [第 12.2 节 “Clearing the Cache”](#) for more information.

## Additional resources

Learn about additional caching and performance optimization methods in the [Drupal.org community documentation page "Caching to improve performance"](#).

### Attributions

Written by [Jennifer Hodgdon](#).

## 12.2. Clearing the Cache

### Goal

Clear or rebuild your site's internal caches to ensure they are up-to-date with the most recent data, using the user interface or Drush.

### Prerequisite knowledge

- [第 12.1 节 “Concept: Cache”](#)
- [第 3.2 节 “Concept: Additional Tools”](#)

### Site prerequisites

If you want to use Drush to clear the cache, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

## Steps

You can use the administrative interface or Drush to clear the cache.

### Using the administrative interface

1. In the Manage administrative menu, navigate to Configuration > Development > Performance (admin/config/development/performance).
2. Click Clear all caches.
3. A message saying the cache has been cleared appears at the top of the page.

### Using Drush

You can use one of two commands:

- Use the command drush cache-rebuild to clear and rebuild all cached data for a site. After running this command, you will see the output message "Cache rebuild complete."
- Use the command drush cc to see a list of individual caches and then choose the specific cache you would like to clear. Running this command should produce output like the following:

```
> drush cc
Enter a number to choose which cache to clear.
[0] : Cancel
[1] : drush
[2] : theme-registry
[3] : menu
[4] : css-js
[5] : block
[6] : module-list
[7] : theme-list
[8] : render
[9] : views
```

Choose a cache to clear by entering the number associated with that cache. Press "Enter" to continue.

### Additional resources

[Drupal.org community documentation page "Clearing or rebuilding Drupal's cache"](#)

### Attributions

Adapted and edited by [Joe Shindelar](#) and [Jack Haas](#) from "[Clearing or rebuilding Drupal's cache](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

## 12.3. Concept: Data Backups

### Prerequisite knowledge

- [第 1.1 节 “Concept: Drupal as a Content Management System”](#)
- [第 3.3 节 “Preparing to Install”](#)

### What is a site backup?

If something happens to the computer (or computers) that your site and its database are running on, or if you lose access to this computer, you could lose some or all of your site's data. You could also lose data if your site is hacked, or if someone with administrative privileges on your site deletes or alters data mistakenly from the administrative interface. In order to prevent scenarios like this from being permanent, expensive data losses, it is important to make regular backups of your site's data, and to store them in a location that is separate from the computer where your site is running.

The frequency with which you should make data backups, and how many backups you should keep, depends on how frequently your site is changing. If you have a very large amount of content on your site that is being added to or updated many times per day, you would want to make more frequent backups than you would for a site that changes rarely. Also consider that some time could pass between when a data problem occurs and when you notice that it is a problem, so storing a sequence of backups (so that you can go back to the last known good data and retrieve that), rather than overwriting a single backup repeatedly, is a good practice.

Another consideration is that whatever format you store your backups in, it is a good idea to verify that you can actually retrieve lost data from your backups. You might want to test several possible data loss scenarios, and make sure that your data can be restored to the site in all cases.

In order to make a complete backup of your site, you will need to make copies of the following:

- The data in the sites directory, including the sites/default/settings.php file.
- The data in your site's database. A few tables can be truncated, such as those storing the temporary data cache and user login session information, but it is always safe to back up the entire database.
- Uploaded files, such as images and other attachments. The location of these files is configurable; the standard location is the sites/default/files directory under your site root. In the Manage administrative menu, navigate to Configuration > Media > File system (admin/config/media/file-system) to check the file upload locations; to change them, you'll need to edit your settings.php file.
- Modules, themes and any other software files you have customized. You can find customized modules and themes in the modules and themes directories respectively.

Some people prefer to back up all software files, including core files and contributed modules and themes (which you could recover by downloading them again from the source), rather than trying to pick out specific files that definitely need to be backed up.

You can perform a test to confirm whether your backup has been done right by making a development copy of the site (see [第 11.8 节 “Making a Development Site”](#)).

## Related topics

- [第 13.5 节 “Updating the Core Software”](#)
- [第 11.8 节 “Making a Development Site”](#)
- [第 12.1 节 “Concept: Cache”](#)

## Additional resources

- [Drupal.org community documentation page "Backing up a site"](#)
- The [contributed Backup and Migrate module](#), which can be used to set up automatic backups of the database and uploaded files.

## Attributions

Written by [Jennifer Hodgdon](#).

## 12.4. Concept: Log

### What is a Log?

Your site captures system events in a log to be reviewed by an authorized individual at a later time. The log is a list of recorded events containing usage data, performance data, errors, warnings, and operational information. It is vital to check the log on a regular basis as it is often the only way to tell what is going on.

You can find your site's recent log messages in the Manage administrative menu by navigating to Reports > Recent log messages (admin/reports/dblog).

**最新日志信息 ☆**

[查看](#) [删除](#)

首页 > 管理 > 报告

Database Logging 模块在 Drupal 数据库中记录系统事件，请在本页监视您的站点或者调试站点的问题。

▼ 过滤日志信息

| 类型            | 严重性  |
|---------------|------|
| block_content | 紧急情况 |
| content       | 警告   |
| cron          | 严重   |
| file system   | 错误   |
| language      | 警告   |
| locale        | 注意   |
| 节点            | 信息   |
| system        | 调试   |

[过滤](#)

| 类型       | 日期                 | 消息                                                       | 用户    | 操作                 |
|----------|--------------------|----------------------------------------------------------|-------|--------------------|
| user     | 06/20/2017 - 08:44 | admin 的会话已打开。                                            | admin |                    |
| user     | 06/20/2017 - 08:44 | admin 的会话已关闭。                                            | admin |                    |
| user     | 06/20/2017 - 08:43 | admin 的会话已打开。                                            | admin |                    |
| user     | 06/20/2017 - 08:43 | admin 的会话已关闭。                                            | admin |                    |
| content  | 06/20/2017 - 08:41 | page: 更新了 Home.                                          | admin | <a href="#">查看</a> |
| user     | 06/20/2017 - 08:39 | admin 的会话已打开。                                            | admin |                    |
| locale   | 06/20/2017 - 07:11 | 翻译文件未找到: http://ftp.drupal.org/files/translations/8.x... | admin |                    |
| language | 06/20/2017 - 07:11 | English (en) 语言已创建。                                      | admin |                    |

## Attributions

Adapted by [Diana Lakatos](#) from "[Reports](#)" copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#)

## 12.5. Concept: Status Report

### What is a Status Report?

The status report is a short overview of your site's parameters as well as any problems detected with your installation. It may be useful to copy and paste this information into support requests filed on Drupal.org's support forums and project issue queues or when asking for help on other channels.

You can find the status report in the Manage administrative menu by navigating to Reports > Status report (admin/reports/status).

**状态报告 ☆**

首页 » 管理 » 报告

在这里您可以看到您网站各种参数的概览，以及检测到的任何问题。在 Drupal.org 支持论坛和项目问题列表中求助时，复制并粘贴此页上的信息可能会对您有所帮助。在提交支持请求之前，请确保您的服务器满足[系统要求](#)。

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| <b>1 错误</b><br><a href="#">Details</a> | <b>23 已核准</b><br><a href="#">Details</a> |
|----------------------------------------|------------------------------------------|

**GENERAL SYSTEM INFORMATION**

|                                                                                                                                            |                                                                                                                                                   |                                                                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| <b>Drupal Version</b><br>8.3.3                                                                                                             | <b>Last Cron Run</b><br>上次运行 1 小时 53 分钟 之前<br><a href="#">(更多信息)</a>                                                                              | <a href="#">运行Cron</a>                                                                         |
| <b>Web Server</b><br>Apache/2.4.7 (Ubuntu) SVN/1.8.8<br>PHP/5.5.9-1ubuntu4.21 mod_python/3.3.1<br>Python/2.7.6 mod_perl/2.0.8 Perl/v5.18.2 | <b>PHP 版本</b><br>5.5.9-1ubuntu4.21 ( <a href="#">更多信息</a> )<br>PHP 5.6.5 或 5.5.21 版本自带了对 mysql 数据库的 SQL 注入防护。推荐升级。<br><b>Memory limit</b><br>512M | <b>数据库 版本</b><br>5.5.55-0ubuntu0.14.04.1<br><b>系统</b><br>MySQL, MariaDB, Percona Server或类似的数据库 |

**Errors found**

|               |                                                                                                                   |
|---------------|-------------------------------------------------------------------------------------------------------------------|
| <b>信任主机设置</b> | 未启用<br>settings.php 中的 trusted_host_patterns 设置未配置。这可能导致安全漏洞。强烈建议您配置此项。更多详情请参见 <a href="#">防止 HTTP HOST 头攻击</a> 。 |
|---------------|-------------------------------------------------------------------------------------------------------------------|

**已核准**

DRUPAL 核心更新版本      只是更新

## Related topics

[第 14.2 节 “Getting Support”](#)

### Attributions

Adapted by [Diana Lakatos](#) from "[Reports](#)" copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#)

---

# 第 13 章 Security and Maintenance

## 13.1. Concept: Cron

What are cron tasks?

To ensure that your site and its modules continue to function well, a group of administrative operations should be run periodically. These operations are called cron tasks. Examples of cron tasks are: checking for module and theme updates, indexing content for search, or cleaning up temporary files.

What is the relationship between the site's cron tasks and Unix cron?

Linux/Unix-based operating systems have a cron scheduler that can be used to run periodic tasks. You can use the server's cron scheduler to schedule runs of the site's cron tasks. Alternatively, you can use the core Automated Cron module to run tasks. You can check the site's cron tasks' status in the status report.

Related topics

- [第 13.2 节 “Configuring Cron Maintenance Tasks”](#)
- [第 12.5 节 “Concept: Status Report”](#)

Additional resources

[Drupal.org community documentation page "Setting up cron"](#)

Attributions

Written and edited by [Diana Lakatos](#) at [Pronovix](#), [Dave Hansen-Lange](#) at [Advomatic](#), and [Boris Doesborg](#).

## 13.2. Configuring Cron Maintenance Tasks

Goal

Check whether cron maintenance tasks are run regularly, and if not, either install the core Automated Cron module or run cron maintenance tasks from outside the website.

## Prerequisite knowledge

### [第 13.1 节 “Concept: Cron”](#)

#### Steps

1. Review the Status report (see [第 12.5 节 “Concept: Status Report”](#)) to see when cron maintenance tasks were last run.

If you installed the website using the core Standard installation profile (or similar), then cron maintenance tasks might already be running via the core Automated Cron module. By default, these tasks are run about every three hours.

2. Choose whether to run cron maintenance tasks using the core Automated Cron module, or by other means. The core Automated Cron module might not be suitable for some websites because:
  - Each time someone accesses a page on the site, the module checks how long it has been since cron maintenance tasks have last run, and then runs them if necessary. If no one visits the website for a long time, cron maintenance tasks will not be run.
  - Cron maintenance tasks are run after the page has been generated. This means there is less time for the tasks to be run before various server timeouts are reached (for example, PHP execution timeout). If this happens, the logs (see [第 12.4 节 “Concept: Log”](#)) will show error messages that cron is unable to complete.
  - There is a small [scalability](#) cost associated with the core Automated Cron module. This is because one of the web server's processes is occupied (and can't serve other web pages) until the cron maintenance tasks are complete.
3. If you want to use the core Automated Cron module, first make sure it is installed (it is installed with the core Standard install profile; see [第 4.3 节 “Installing a Module”](#) if it is not installed).

Next, configure the module to control how frequently cron maintenance tasks are run. In the Manage administrative menu, navigate to Configuration > System > Cron (admin/config/system/cron). Choose the desired interval in the Cron settings section, and click Save configuration.

The screenshot shows the 'Cron' configuration page in Drupal. At the top, there's a header with the title 'Cron' and a star icon. Below the header, a breadcrumb navigation shows '首页 » 管理 » 配置 » 系统'. A note below the breadcrumb states: 'Cron 用于定时运行任务，比如检查更新、对内容创建索引。' There is a blue button labeled '运行Cron'. Below it, a message says '上次运行: 1 小时 54 分钟之前。' A link to an external cron URL is provided: '要在站外运行cron, 请访问 <http://example.com/cron/1rDURqrhNweklVIDGXF-FVL5FdCD2vEYkPNRt9b7IkII23QCd5hNGGCA4AfvjhfeLe54JRq3Kw>'.

**▼ CRON 设置**

Detailed cron logging  
Run times of individual cron jobs will be written to watchdog

运行计划任务每  
3 小时 ▾

更多有关设置计划任务的信息可往[drupal.org上的reading the cron tutorial](#)查阅。

**保存配置**

4. If you want to run cron maintenance tasks from outside the website, uninstall the core Automated Cron module (see [第 4.4 节 “Uninstalling Unused Modules”](#)). Next, find the cron URL. This URL is shown in the Status report (see [第 12.5 节 “Concept: Status Report”](#)), and in the Cron administration page (see previous step). The URL looks like this: <http://www.example.com/cron/0MgWtfB33FYbbQ5UAC3L0LL3RCOPT3RNUEZILLA0nf1Re>

Whenever this URL is visited, cron maintenance tasks will run. Set up one of the following schedulers to access this URL regularly:

- [The Cron daemon](#) (Linux, OS X, Solaris, BSD)
- [Scheduled Tasks](#) (Windows)
- A cron SASS provider (software as a service)
- A cron manager provided by your web hosting provider (see the documentation provided by your provider)

## Related concepts

[第 13.3 节 “Concept: Security and Regular Updates”](#)

## Additional resources

- [Drush page "Running Drupal cron tasks from Drush"](#)
- [Drupal.org community documentation page "Setting up cron"](#)

## Attributions

Written and edited by [Dave Hansen-Lange](#) at [Advomatic](#), [Boris Doesborg](#), and [Jennifer Hodgdon](#).

### 13.3. Concept: Security and Regular Updates

#### Prerequisite knowledge

- [第 1.1 节 “Concept: Drupal as a Content Management System”](#)
- [第 1.2 节 “Concept: Modules”](#)
- [第 1.3 节 “Concept: Themes”](#)
- [第 1.6 节 “Concept: The Drupal Project”](#)

#### What are security updates?

Any software occasionally has bugs, and sometimes these bugs have security implications. When security bugs are fixed in the core software, modules, or themes that your site uses, they are released in a security update. You will need to apply security updates in order to keep your site secure. See [第 13.4 节 “Keeping Track of Updates”](#) to learn how to be notified of security updates by email, and [第 13.5 节 “Updating the Core Software”](#), [第 13.6 节 “Updating a Module”](#), and [第 13.7 节 “Updating a Theme”](#) to learn how to make updates.

#### What is the security team?

The Drupal open-source project has a team of volunteers who track security-related bugs and release security updates. They also help other developers fix bugs, and maintain information for users on how to keep their websites secure. You can learn more about the security team and their practices and processes at the [Drupal.org Security Team](#) page.

#### How are security bugs reported?

It is important that security problems be kept confidential until they are fixed, so that sites are less likely to be compromised before they can be secured. If you find a potential security problem in any of the software you downloaded from the Drupal.org website, follow the procedures on the [Drupal.org Security Team](#) page to report it.

#### What are regular (non-security) updates?

The core software, modules, and themes also periodically have regular updates to add new features and fix bugs. These updates are less critical than security updates. As a general best practice, updates should be applied as long as they do not cause problems

with your site. Testing on a development copy of your site is always a good idea before applying updates on a live site. This is because some updates may include changes that are not compatible with the modules or themes on your site, or that will break a particular functionality on your site.

## Related topics

- [第 13.4 节 “Keeping Track of Updates”](#)
- [第 13.5 节 “Updating the Core Software”](#)
- [第 13.6 节 “Updating a Module”](#)
- [第 13.7 节 “Updating a Theme”](#)
- [第 11.8 节 “Making a Development Site”](#)

## Additional resources

- [Drupal.org community documentation page "Securing your site"](#)
- ["Security advisories" on Drupal.org](#)
- [Drupal.org Security team](#)

## Attributions

Written and edited by [Boris Doesborg](#) and [Jennifer Hodgdon](#).

## 13.4. Keeping Track of Updates

### Goal

Keep your site safe and up-to-date by keeping up with the latest security updates.

### Prerequisite knowledge

[第 13.3 节 “Concept: Security and Regular Updates”](#)

### Steps

There are a few different ways to receive notifications of security releases:

- In the Manage administrative menu, navigate to Reports > Available updates > Settings. Enter the email addresses to be notified when updates are available. You can also specify whether you want daily or weekly updates. Click Save configuration.

- Subscribe to the security announcements email list. To subscribe, log in to Drupal.org, go to your user profile page and subscribe to the security newsletter on the Edit > My newsletters tab.
- Follow @drupalsecurity on Twitter.
- Subscribe to RSS feeds for [core security updates](#), [contributed project updates](#) and [public service announcements](#).

## Related concepts

- [第 13.3 节 “Concept: Security and Regular Updates”](#)
- [第 13.5 节 “Updating the Core Software”](#)
- [第 13.6 节 “Updating a Module”](#)
- [第 13.7 节 “Updating a Theme”](#)

## Additional resources

- ["Security advisories" on Drupal.org](#)
- [Drupal.org Security Team](#)
- [@drupalsecurity on Twitter](#)

## Attributions

Written by [Sarah German](#) at [Advomatic](#).

## 13.5. Updating the Core Software

### Goal

Update the core software, either through the administrative interface or by using Drush.

### Site prerequisites

- If you want to use Drush, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).
- If your site is live, you should test this process in a development environment before running it on your production site. See [第 11.8 节 “Making a Development Site”](#).

### Steps

1. Make a complete backup of your site. Refer to [第 12.3 节 “Concept: Data Backups”](#).

2. Open settings.php (/sites/default/settings.php) in any plain text editor. Find the line with the \$settings[update\_free\_access] variable. By default, it is set to "FALSE" due to security reasons. Change the setting to "TRUE":

```
$settings['update_free_access'] = TRUE;
```

3. Disable any caching technique (memcache, varnish, and so on) your application might be using.
4. Put your site in maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).
5. If you are using Composer to manage dependencies, or using Git, skip the next six steps, and instead see [第 11.9 节 “Using Composer and Git to Download Files”](#) for instructions on downloading updated files. Continue with the update.php step.
6. Download the tar.gz or zip file archive for the latest version of Drupal 8.x core from [Drupal.org Drupal Core Downloads](#). See [第 3.3 节 “Preparing to Install”](#) for more details on how to find the latest version.
7. Upload the archive file to your web hosting server.
8. Extract the archive file to a temporary directory on your server (should be outside the directory where the site is hosted). Your hosting control panel's file manager should provide a way to extract the files. Or, if you have terminal access to your hosting server (running Linux), you can use a command like:

```
tar -xzf drupal-8.3.2.tar.gz
```

9. You can also use Drush to download the archive and extract it in one step, by navigating to the temporary directory on the server and entering this command:

```
drush dl drupal
```

10. In your site hosting directory, delete the core and vendor directories, and all files that are not in a subdirectory, including .htaccess, composer.json, and autoload.php. Don't delete custom and customized files because you may end up losing the custom functionality stored in them.
11. Copy the core and vendor directories and the non-custom/non-customized files that you deleted in the preceding step from the temporary directory to your site directory.
12. Run the update.php script using either of the following:
  - Visit <http://www.example.com/update.php> in your browser (where www.example.com is your site's URL). Click Continue in the first screen to run the updates and successfully complete the script.
  - Run the following Drush command: drush updb
13. If you get any error or warning, re-run the update.php script again till all the updates have been completed successfully.
14. Open settings.php (/sites/default/settings.php) in a text editor. Find the line with the \$settings[update\_free\_access] variable and update it to "FALSE":

```
$settings['update_free_access'] = FALSE;
```

15. Click Administration pages to return to the administration section of your site.
16. Take your site out of maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).
17. Clear the cache. See [第 12.2 节 “Clearing the Cache”](#).
18. Re-enable any caching technique you disabled at Step 3.
19. You should have the updated version running. You can verify the current version of your software by checking the Status report (see [第 12.5 节 “Concept: Status Report”](#)).

Expand your understanding

- [第 3.2 节 “Concept: Additional Tools”](#)
- [第 11.8 节 “Making a Development Site”](#)
- [第 12.3 节 “Concept: Data Backups”](#)

Related concepts

[第 12.5 节 “Concept: Status Report”](#)

Additional resources

- [“Drupal Core Downloads” page on Drupal.org](#)
- [“Registry Rebuild” page on Drupal.org](#)
- The file /core/UPDATE.txt within your installation.

Attributions

Written and edited by [Surendra Mohan](#), [Boris Doesborgh](#), and [Jojo Alphonso](#) at [Red Crackle](#).

## 13.6. Updating a Module

Goal

Update a contributed module and run the Database updates script.

Prerequisite knowledge

- [第 13.3 节 “Concept: Security and Regular Updates”](#)
- [第 13.1 节 “Concept: Cron”](#)

## Site prerequisites

- A contributed module has been installed and there is an update available for it. See [第 11.3 节 “Downloading and Installing a Module from Drupal.org”](#) and [第 13.4 节 “Keeping Track of Updates”](#).
- If your site is live, you should test this process in a development environment before running it on your production site. See [第 11.8 节 “Making a Development Site”](#).
- You have created a full-site backup. See [第 12.3 节 “Concept: Data Backups”](#).
- If you want to use the user interface, the core Update Manager module must be installed. See [第 4.3 节 “Installing a Module”](#) for instructions on installing core modules.
- If you want to use Drush, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

## Steps

Before you start, check for module-specific update instructions. This is typically necessary while updating modules that involve the usage of third-party libraries. Read and understand all module-specific requirements before proceeding with the updates. To find instructions, check the module's project page Read Documentation link.

To view further instructions, download the tar.gz or .zip file from the project page to your local computer. Unzip the file and look for README.txt, INSTALL.txt, and UPGRADE.txt that come with the module's installation file. Also, review the release notes on the project page by clicking the version number you're downloading.

### Downloads

| Version                           | Download                                                           | Date        |
|-----------------------------------|--------------------------------------------------------------------|-------------|
| <a href="#">8.x-1.19</a>          | <a href="#">tar.gz (17.07 KB)</a>   <a href="#">zip (27.02 KB)</a> | 2017-Apr-06 |
| <b>Development releases</b>       |                                                                    |             |
| <a href="#">8.x-1.x-dev</a>       | <a href="#">tar.gz (19.49 KB)</a>   <a href="#">zip (29.81 KB)</a> | 2017-Jun-11 |
| <a href="#">View all releases</a> |                                                                    |             |

You can use the administrative interface or Drush to update a contributed module. If you are updating a custom module rather than a contributed module, if you see a message saying Installing modules and themes requires FTP access to your server, or if the steps below do not work to obtain the new module files, follow the steps in [第 11.6 节 “Manually Downloading Module or Theme Files”](#). You can then continue here with step 6 in the instructions for the administrative interface below.

### Using the administrative interface

1. Put your site in maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).
2. In the Manage administrative menu, navigate to Reports > Available updates > Update (admin/reports/updates/update).
3. Find and check the module in the list. Click Download these updates for the module.

The screenshot shows the 'Updates' section of the Drupal administration interface. At the top, there's a header with tabs for '更新' (Updates), '列表' (List), '更新' (Update), and '设置' (Settings). Below the header, a breadcrumb trail shows '首页 > 管理 > 报告 > 可用更新'. A message indicates the '上次检测时间: 57 分钟 22 秒 前 (手动检查)' (Last checked: 57 minutes 22 seconds ago (manual check)). A table lists one update: 'Admin Toolbar' (version 8.x-1.15, recommended version 8.x-1.18). A button labeled '下载这些更新' (Download these updates) is visible.

4. Click Continue.
5. Click Run database updates. If you obtained the new module files manually, start with this step, and reach the database updates page by typing the URL example.com/update.php in your browser.
6. Click Continue and apply all updates. The database update scripts will be executed.
7. Click Administration pages to return to the administration section of your site.
8. Take your site out of maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).
9. Clear the cache (refer to [第 12.2 节 “Clearing the Cache”](#)).

### Using Drush

1. Find the project name for the module you wish to update. It is the last segment of the module's project page URL. For example, if the project URL is [https://www.drupal.org/project/admin\\_toolbar](https://www.drupal.org/project/admin_toolbar), the project name is "admin\_toolbar".
2. Run the following Drush command, giving the project name (for example, admin\_toolbar) as a parameter (if you have more than one module to update, add the additional module project names to the end of the command, separated by spaces):

```
drush up admin_toolbar
```

3. Follow the instructions on the screen.

### Expand your understanding

- Review the site log (refer to [第 12.4 节 “Concept: Log”](#)) once the updates are complete to check for errors.
- [第 13.7 节 “Updating a Theme”](#)

### Additional resources

[Drupal.org community documentation page “Updating modules”](#)

## Attributions

Adapted by [Boris Doesborgh](#), and [Sarah German](#) at [Advomatic](#), from "[Updating modules](#)", copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).

## 13.7. Updating a Theme

### Goal

Update a contributed theme on your site and run the Database Updates script.

### Prerequisite knowledge

- [第 13.3 节 “Concept: Security and Regular Updates”](#)
- [第 13.1 节 “Concept: Cron”](#)

### Site prerequisites

- A contributed theme has been installed and there is an update available for it. See [第 11.5 节 “Downloading and Installing a Theme from Drupal.org”](#) and [第 13.4 节 “Keeping Track of Updates”](#).
- If your site is live, you should test this process in a development environment before running it on your production site. See [第 11.8 节 “Making a Development Site”](#).
- You have created a full site backup. See [第 12.3 节 “Concept: Data Backups”](#).
- If you want to use the user interface, the core Update Manager module must be installed. See [第 4.3 节 “Installing a Module”](#) for instructions on installing core modules.
- If you want to use Drush, Drush must be installed. See [第 3.2 节 “Concept: Additional Tools”](#).

### Steps

You can use the administrative interface or Drush to update a contributed theme. If you are updating a custom theme rather than a contributed theme, if you see a message saying Installing modules and themes requires FTP access to your server, or if the steps below do not work to obtain the new theme files, follow the steps in [第 11.6 节 “Manually Downloading Module or Theme Files”](#), and then continue with step 6 in the instructions for administrative interface below.

#### Using the administrative interface

1. Put your site in maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).

2. In the Manage administrative menu, navigate to Reports > Available updates > Update (admin/reports/updates/update).
3. Find and check the theme in the list. Click Download these updates for the theme.

The screenshot shows the 'Available updates' page with the title '更新 ☆'. Below it are three tabs: '列表' (List), '更新' (Update), and '设置' (Settings). The '更新' tab is selected. The page displays a message: '上次检测时间: 1 分钟 11 秒 前 (手动检查)'. A table lists the available update for the 'MAYO (theme)'. The table has columns: '□' (checkbox), '名称' (Name), '已安装版本' (Installed Version), and '推荐版本' (Recommended Version). For 'MAYO (theme)', the checkbox is checked, the name is 'MAYO (theme)', the installed version is '8.x-1.2', and the recommended version is '8.x-1.3 (发布说明)'. At the bottom of the table is a button labeled '下载这些更新' (Download these updates).

4. Click Continue.
5. Click Run database updates. If you obtained the new theme files manually, start with this step, and reach the database updates page by typing the URL example.com/update.php in your browser.
6. Click Continue to run the updates. The database update scripts will be executed.
7. Click Administration pages to return to the administration section of your site.
8. Take your site out of maintenance mode. See [第 11.2 节 “Enabling and Disabling Maintenance Mode”](#).
9. Clear the Drupal cache (refer to [第 12.2 节 “Clearing the Cache”](#)).

## Using Drush

1. Find the project name for the theme you wish to update, which is the last segment of the theme's project page URL. For example, if the project URL is <https://www.drupal.org/project/mayo>, the project name is "mayo".
2. Run the following Drush command, giving the project name (for example, mayo) as a parameter:

```
drush up mayo
```

3. Follow the instructions on the screen.

## Expand your understanding

- Review the site log, see [第 12.4 节 “Concept: Log”](#), once the updates are complete to check for errors.
- [第 13.6 节 “Updating a Module”](#)

## Attributions

Written by [Boris Doesborg](#).

---

# 第 14 章 Final Thoughts

## 14.1. Connecting with the Community

### Prerequisite knowledge

#### [第 1.6 节 “Concept: The Drupal Project”](#)

### How can you connect with the community?

The Drupal project has a world-wide community of developers and users. One of the best ways to improve your knowledge of the platform is to connect with others that are using it, and get involved in the open-source community. There are many ways that you can get started:

#### Attend an event

There are both regional and international Drupal events held around the world. See the "[DrupalCon](#)" page on [Drupal.org](#) to find international events, and the "[Event Calendar](#)" on [groups.drupal.org](#) or [drupical.com](#) to find regional events.

#### Join a local group

There are Drupal user groups all around the world. Many of them have regular meetings, which you can attend to learn more about Drupal and connect to other Drupal users. Find local user groups on [groups.drupal.org](#).

#### Participate in a topical or language group

There are also interest groups for a wide range of topics, which have on-line discussion forums. Find topical groups on [groups.drupal.org](#). Many languages have their own websites too; you can find them on the "[Language-specific communities](#)" page on [Drupal.org](#).

#### Chat online

The Drupal project uses IRC for on-line chatting. There are regional, topical, and general-purpose chat groups available. Find out more on the "[IRC](#)" page on [Drupal.org](#).

#### Report a problem

See below.

#### Contribute

You can contribute your time and expertise to the community in many ways, such as:

- Developing modules or themes. See the "["Contribute to Development" page on Drupal.org](#)", or improving them (using the issue queues for existing projects).
- Translating the user interface. See [localize.drupal.org](#).
- Writing documentation. See "["Contribute to Documentation" on Drupal.org](#)".
- Answer Support questions. See [第 14.2 节 “Getting Support”](#).

## How can you report a problem or suggest a feature?

Each project within the community (such as the Drupal Core project for the base software, and projects for each contributed theme and module) uses issues to keep track of software bugs and plans for new features. You can participate by creating a bug report when you find a problem, creating a feature request, or commenting on existing issues. Search before creating an issue, to make sure that the problem or feature has not already been reported or requested. See the [Drupal.org page "Use the issue queue"](#) and the [Drupal.org page "Reporting a problem"](#) for more information.

If you find a problem that you believe is related to security, such as a cross-site scripting vulnerability, do not report it in the standard issue queue. Instead, report it to the security team. See the [Drupal.org page "How to report a security issue"](#) for details.

## Related topics

### [第 14.2 节 “Getting Support”](#)

## Additional resources

- ["Code of Conduct" on Drupal.org](#)
- ["Event Calendar" on groups.drupal.org or drupical.com](#)
- ["Where is the Drupal Community?" page on Drupal.org](#)
- [groups.drupal.org](#)
- ["IRC" page on Drupal.org](#)
- ["Ways to get involved" page on Drupal.org](#)
- [Drupal.org page "Why get involved?"](#)
- [Drupal.org page "Contributor tasks"](#)
- [Drupal.org page "Use the issue queue"](#)
- [Drupal.org page "Reporting a problem"](#)
- [Drupal.org page "How to report a security issue"](#)

## Attributions

Written by [Jennifer Hodgdon](#), and [Joe Shindelar](#) at [Drupalize.Me](#).

## 14.2. Getting Support

### Prerequisite knowledge

- 第 1.6 节 “Concept: The Drupal Project”
- 第 14.1 节 “Connecting with the Community”

### Where can you find support?

The Drupal project is open-source, so if you have questions about or problems with the software, your options for finding answers and fixes are somewhat different from what they would be for commercial software.

There are several options for free support provided by community volunteers. First, some IRC channels, local groups, and language communities encourage support questions, through on-line chat, in-person meetings, or websites (find out more about these on [第 14.1 节 “Connecting with the Community”](#)).

Second, some (but not all) contributed module, distribution, and theme projects encourage you to post support requests in issues. Generally, projects that have a very large number of users do not allow support requests in their issues (Drupal Core is in that category), while projects with a smaller number of users welcome the occasional support question. Be respectful of developer time and read the documentation for the project before posting a question in an issue. On the other hand, all projects encourage you to use issues to report problems and bugs; see [第 14.1 节 “Connecting with the Community”](#) to learn more about that.

In addition to those resources, the following sites provide free forums where volunteers answer support questions about Drupal:

- The [Drupal.org Forums](#)
- ["Drupal Answers" on StackExchange](#)

If you prefer to pay for support (presumably in exchange for more extensive service or better availability), you can find service providers in the ["Drupal Marketplace" on Drupal.org](#).

### Related topics

- 第 14.3 节 “Learning More”
- 第 14.1 节 “Connecting with the Community”

### Additional resources

- ["Support" page on Drupal.org](#)
- ["Drupal Marketplace" on Drupal.org](#)

- The [Drupal.org Forums](#)
- "Drupal Answers" on StackExchange

Attributions

Written by [Jennifer Hodgdon](#).

### 14.3. Learning More

Prerequisite knowledge

- 第 1.6 节 “Concept: The Drupal Project”
- 第 14.1 节 “Connecting with the Community”

Where can you go to learn more?

The following resources should prove useful to you, as you continue to advance your skills:

["Drupal Community Documentation" section on Drupal.org](#)

Wiki-like documentation contributed by the Drupal community, ranging from basic to advanced, about all aspects of Drupal (site building and administration, theming, development, and contributed modules).

[api.drupal.org](#)

Reference documentation for programmers about the Drupal API.

["Drupal Planet" page on Drupal.org](#)

An aggregation of blog posts about Drupal from around the web, posted by blogging members of the Drupal community who have applied for inclusion. Topics range from programming to site building to Drupal news.

Groups, events, and meetups

See [第 14.1 节 “Connecting with the Community”](#) for more about topical, regional, and language groups, as well as local, regional, and international events.

["Training Marketplace" page on Drupal.org](#)

The Marketplace lists paid training providers. For free training, check whether events include training sessions; there are also free or very low-cost training events listed on the ["Global Training Days" page on Drupal.org](#).

Support sites

See [第 14.2 节 “Getting Support”](#) to locate support forums; searching them can be useful for learning about specific topics.

Attributions

Written by [Jennifer Hodgdon](#), and [Joe Shindelar](#) at [Drupalize.Me](#).

---

# Glossary

## Ajax

A web technology used to exchange data with a server to dynamically update parts of a web page (for example, forms) without needing entire page reloads.

## Alias

A user-friendly name to replace the internal [path](#) that the system assigns to a URL on the site. For example, you might assign an alias of /about to the About page on your site, to replace the internal path /node/5. This would give the page a URL of <http://example.com/about> instead of <http://example.com/node/5>. See [第 5.1 节 “Concept: Paths, Aliases, and URLs”](#) for more information.

## Anonymous

A person ([user](#)) interacting with the site who is not logged in. See [第 7.1 节 “Concept: Users, Roles, and Permissions”](#) for more information.

## Block

A chunk of [content](#) (text, images, links, etc.) that can be displayed on a page of a site. Blocks are displayed in [regions](#). See [第 8.1 节 “Concept: Blocks”](#) for more information.

## Breakpoint

Breakpoints are used to separate the height or width of browser screens, printers, and other media output types into steps. A [responsive](#) site adjusts its presentation at these breakpoints. See [第 6.14 节 “Concept: Responsive Image Styles”](#) for more information.

## Bundle

Synonym for [Entity subtype](#).

## Cache

The site's internal cache stores the output of time-consuming calculations, such as computing output for an HTML page request, and then retrieves them instead of recalculating the next time they are needed. External caching systems can also be used on the web server to speed up a site's response. See [第 12.1 节 “Concept: Cache”](#) for more information on the internal cache.

## CMS

Acronym for [Content Management System](#).

## Configuration

Information about your site that is not [content](#), and is meant to be more permanent than [state](#) information, such as the name of your site, the [content types](#) and [views](#) you have defined, etc. See [第 1.5 节 “Concept: Types of Data”](#) for more information.

### Content

Information meant to be displayed on your site, such as text, images, downloads, etc. See also [Configuration](#) and [State](#). See [第 1.5 节 “Concept: Types of Data”](#) for more information.

### Content item

An item of [content](#) that is typically meant to be displayed as the main content of a page on your site. This is an [entity type](#). See [第 2.3 节 “Concept: Content Entities and Fields”](#) for more information.

### Content Management System (CMS)

A collection of tools designed to allow the creation, modification, organization, search, retrieval and removal of information on a website. See [第 1.1 节 “Concept: Drupal as a Content Management System”](#) for more information.

### Content type

An [entity subtype](#) for the [content item entity type](#). Each content type is used for some particular purpose on the site, and each has its own fields. For example, a site for a farmers market might have a content type for simple pages, and another for a vendor listing page. See [第 2.3 节 “Concept: Content Entities and Fields”](#) for more information.

### Contextual link

A link to an administrative page for editing or configuring a feature of the site, shown in the context where that feature is displayed. Example: a link to configure a [menu](#) that is shown when you hover your mouse over the menu. See [第 4.1 节 “Concept: Administrative Overview”](#) for more information.

### Contributed

[Modules](#), [themes](#), and [distributions](#) that are not part of the [Drupal core](#) download, and that can be downloaded separately from the [Drupal.org](#) website.

### Cron

On some operating systems, cron is a command scheduler application that executes commands or scripts periodically. Your site defines periodic tasks, also known as cron tasks, that need to be triggered either by an operating system cron scheduler, or internally. See [第 13.1 节 “Concept: Cron”](#) for more information.

### Distribution

A single download that provides a shortcut for setting up a specific type of site, such as a website for a club or for e-commerce. A distribution contains [Drupal core](#), along with [contributed modules](#) and/or [themes](#); many distributions also pre-configure the site or even create sample content upon installation. See [第 1.4 节 “Concept: Distributions”](#) for more information.

### Drupal core

The files, themes, profiles, and modules included with the standard project software download. See [第 1.1 节 “Concept: Drupal as a Content Management System”](#) for more information.

Entity

An item of either [content](#) or [configuration](#) data, although in common usage, the term often refers to content entities. Examples include [content items](#), custom [blocks](#), [taxonomy terms](#), and definitions of [content types](#); the first three are content entities, and the last is a configuration entity. See also [Entity type](#), [Entity subtype](#), and [Field](#). See [第 2.3 节 “Concept: Content Entities and Fields”](#) for more information.

Entity subtype

Within a [contententity type](#), a grouping of entities that share the same [fields](#). For example, within the [content item](#) entity type, a farmers market site might have subtypes (known as [content types](#)) for static pages and vendor pages, each with its own group of fields. You may also see the term bundle used (especially in programmer documentation) as a synonym of entity subtype. See [第 2.3 节 “Concept: Content Entities and Fields”](#) for more information.

Entity type

The overall type of an [entity](#); in common usage, it is only applied to a [content](#) entity. Examples include [content types](#), [taxonomy terms](#), and custom [blocks](#). See [第 2.3 节 “Concept: Content Entities and Fields”](#) for more information.

Field

Data of a certain type that is attached to a [contententity](#). For instance, on a farmers market site's vendor content type, you might have fields for an image, the vendor description, and a [taxonomy term](#). See [第 2.3 节 “Concept: Content Entities and Fields”](#) for more information.

Field bundle

Synonym for [Entity subtype](#).

Field formatter

[Configuration](#) that defines how the data in a [field](#) is displayed. For example, a text field could be displayed with a prefix and/or suffix, and it could have its HTML tags stripped out or limited. See also [View mode](#) and [Field widget](#). See [第 6.10 节 “Concept: View Modes and Formatters”](#) for more information.

Field widget

[Configuration](#) that defines how someone can enter or edit data for a [field](#) on a data entry form. For example, a text field could use a single-line or multi-line entry box, and there could be a setting for the size of the box. See also [Field formatter](#). See [第 6.8 节 “Concept: Forms and Widgets”](#) for more information.

Formatter

See [Field formatter](#).

FOSS

Acronym for Free and Open Source Software, meaning software that is developed by a community of people and released under a non-commercial license. See also [GPL](#). See [第 1.6 节 “Concept: The Drupal Project”](#) for more information.

### GPL

Acronym for the GNU General Public License, a non-commercial software license. All software downloaded from the [Drupal.org](#) website is licensed under the "[GNU General Public License, version 2](#)". See also [FOSS](#). See [第 1.7 节 “Concept: Drupal Licensing”](#) for more information.

### Image style

A set of processing steps that transform a base image into a new image; typical processing includes scaling and cropping. See [第 6.12 节 “Concept: Image Styles”](#) for more information.

### LAMP

Acronym for Linux, Apache, MySQL, and PHP: the software on the web server that the scripts commonly run on (although it can use other operating systems, web servers, and databases). See [第 3.1 节 “Concept: Server Requirements”](#) for more information.

### Log

A list of recorded events on the site, such as usage data, performance data, errors, warnings, and operational information. See [第 12.4 节 “Concept: Log”](#) for more information.

### Menu

A set of links used for navigation on a site, which may be arranged in a hierarchy. See [第 5.6 节 “Concept: Menu”](#) for more information.

### Module

Software (usually PHP, JavaScript, and/or CSS) that extends site features and adds functionality. The Drupal project distinguishes between [core](#) and [contributed](#) modules. See [第 1.2 节 “Concept: Modules”](#) for more information.

### Path

The unique, last part of the internal URL that the system assigns to a page on the site, which can be a visitor-facing page or an administrative page. For example, the internal URL for the About page on your site might be <http://example.com/node/5>, and in this case, the path is node/5. See also [Alias](#). See [第 5.1 节 “Concept: Paths, Aliases, and URLs”](#) for more information.

### Permission

The ability to perform some action on the site, such as editing a particular type of [content](#), or viewing user profiles. See also [Role](#). See [第 7.1 节 “Concept: Users, Roles, and Permissions”](#) for more information.

### Reference field

A [field](#) that represents a relationship between an [entity](#) and one or more other entities, which may be the same [entity type](#) or a different type. For example, on a farmers market site, a recipe content item might have a reference field to the vendor (also a content item) that posted the recipe. [Taxonomy term](#) fields are also reference fields. See [第 6.4 节 “Concept: Reference Fields”](#) for more information.

### Region

A defined area of a page where [content](#) can be placed, such as the header, footer, main content area, left sidebar, etc. Regions are defined by [themes](#), and the content

displayed in each region is contained in [blocks](#). See [第 2.1 节 “Concept: Regions in a Theme”](#) for more information.

**Responsive**

A site or [theme](#) is said to be responsive if it adjusts its presentation in response to the size of the browser screen, printer, or other media output type. See also [Breakpoint](#). See [第 6.14 节 “Concept: Responsive Image Styles”](#) for more information.

**Revision**

A record of the past or present state of a [contententity](#), as it is edited over time. See [第 2.6 节 “Concept: Editorial Workflow”](#) for more information.

**Role**

A named set of [permissions](#) that can be applied to a [user account](#). See [第 7.1 节 “Concept: Users, Roles, and Permissions”](#) for more information.

**Security update**

An [update](#) that fixes a security-related bug, such as a hacking vulnerability. See [第 13.3 节 “Concept: Security and Regular Updates”](#) for more information.

**State**

Information of a temporary nature about the current state of your site, such as the time when [cron](#) was last run, etc. See also [Content](#) and [Configuration](#). See [第 1.5 节 “Concept: Types of Data”](#) for more information.

**Taxonomy**

The process of classifying [content](#). See [第 6.5 节 “Concept: Taxonomy”](#) for more information.

**Taxonomy term**

A term used to classify [content](#), such as a tag or a category. See also [Vocabulary](#). See [第 6.5 节 “Concept: Taxonomy”](#) for more information.

**Text format**

[Configuration](#) that defines the processing that happens to user-entered text before it is shown in the browser. This might include stripping or limiting HTML tags, or turning URLs into links. See [第 6.15 节 “Concept: Text Formats and Editors”](#) for more information.

**Theme**

Software and asset files (images, CSS, PHP code, and/or templates) that determine the style and layout of the site. The Drupal project distinguishes between [core](#) and [contributed](#) themes. See [第 1.3 节 “Concept: Themes”](#) for more information.

**UI**

Acronym for [User Interface](#).

**Update**

A newer version of your site's software, either [Drupal core](#) or a [module](#) or [theme](#). See also [Security update](#). See [第 13.3 节 “Concept: Security and Regular Updates”](#) for more information.

User

A person interacting with the site, either logged-in or [anonymous](#). See [第 7.1 节 “Concept: Users, Roles, and Permissions”](#) for more information.

User interface

The text, styles, and images that are visible on a site, separated logically into the user interface for site visitors and the administrative user interface.

User one (User 1)

The initial [user](#) account that is created when you install the site (whose ID number is 1). It automatically has all [permissions](#), even if it is not assigned an administrative [role](#). See [第 7.2 节 “Concept: The User 1 Account”](#) for more information.

View

A formatted listing of data; typically, the data comes from [content entities](#). For example, on a farmers market site, you might create a [content item](#) for each vendor. You could then make view that generates a listing page that shows a thumbnail image and short description of each vendor, linking to the full-page content item. Using the same data, you could also make a view that generates a new vendors block, which would show information from the most recently added vendors. See [第 2.4 节 “Concept: Modular Content”](#) for more information.

View mode

A set of [field formatter configuration](#) for all of the [fields](#) of a [content entity](#), some of which may be hidden. Each [entity subtype](#) can have one or more view modes defined; for example, [content types](#) typically have Full and Teaser view modes, where the Teaser view mode displays fewer or trimmed-down fields. See [第 6.10 节 “Concept: View Modes and Formatters”](#) for more information.

Vocabulary

A group of [taxonomy terms](#) to choose from when classifying [content](#) in a particular way, such as the list of all of the vendor categories on a farmers market site. Technically, vocabularies are the [entity subtype](#) for the taxonomy term [entity type](#). See [第 6.5 节 “Concept: Taxonomy”](#) for more information.

Widget

See [Field widget](#).

Wizard

A web form that allows you to fill in a few values, and creates something with sensible defaults based on the values you chose. For example, there are wizards for creating [views](#) of different types. See [第 9.3 节 “Creating a Content List View”](#) for more information.

WYSIWYG

Acronym for What You See is What You Get, meaning a method for editing [content](#) where what you see on the editing screen closely resembles the final product. See [第 6.16 节 “Configuring Text Formats and Editors”](#) for more information.

---

# Index

## A

Account setting

  configuring , 43

Admin Toolbar module

  downloading , 152

  installing , 152

Administration

  overview , 34

Administrative interface

  using to update the core software , 187

Administrative menu

  overview , 34 , 56

Administrative user account

  overview , 100

Ajax

  definition , 200

Alias

  definition , 200

  overview , 49

Anonymous

  definition , 200

Anonymous user

  overview , 100

Apache web server

  version requirements , 21

Appearance menu entry

  administrative menu , 34

Attributions for this document , 216

Authenticated user

  overview , 100

Author

  assigning , 111

Automated Cron module

  configuring , 182

  overview , 182

## B

Backup

  overview , 178

Bartik theme

  configuring , 45

  regions in , 10

Basic page

  creating , 50

Block

  creating , 114

  creating from a view , 129

  definition , 200

  entity type , 13

  overview , 114

  placing in a region , 116

Breadcrumb region

  overview , 10

Breakpoint

  definition , 200

  overview , 96

Bug

  reporting , 185 , 195

Bundle

  definition , 200

## C

Cache

  clearing , 176

  definition , 200

  overview , 175

  rebuilding , 176

Chatting online , 195 , 197

CKEditor module

  configuring , 97

CKEditor text editor

  default assignment to text format , 97

CMS (Content Management System)

  definition , 200

  overview , 1

Coder tool

  overview , 22

Color scheme

  configuring , 45

Comment entity type

  overview , 13

Comment module

  entity type , 13

Community

  connecting with , 195

Composer tool

  overview , 22

  using to download modules , 166

  using to download the core software , 166

  using to download themes , 166

Composite page

  creating with modular content , 15

Configuration

  as a type of data , 6

copying , 169  
definition , 200  
deploying , 169  
synchronizing between development and live site , 172  
translating , 134 , 142  
Configuration Manager module  
    using to synchronize the configuration between a development and live site , 172  
Configuration menu entry  
    administrative menu , 34  
Configuration Translation module  
    installing , 135  
    overview , 134  
Configuring  
    content translation , 136  
    home page , 55  
    site , 37  
    text format , 97  
Contact form entity type  
    overview , 13  
Contact module  
    entity type , 13  
Content  
    adding to menu while editing , 58  
    as a type of data , 6  
    assigning author , 111  
    backing up , 178  
    definition , 200  
    displaying , 88  
    editing , 52 , 53  
    editing entry form , 84  
    entity type , 13  
    finding , 52  
    modular , 15  
    translating , 134 , 141  
    translation , 136  
Content attributions for this document , 216  
Content display  
    changing , 88  
    managing , 88  
Content editing form  
    overview , 84  
Content entity type  
    overview , 13  
Content item  
    creating , 50  
    definition , 201  
Content list view  
    creating , 121  
Content Management System (CMS)  
    definition , 200 , 201  
    overview , 1  
Content menu entry  
    administrative menu , 34  
Content reference field  
    adding , 80  
    overview , 73  
Content region  
    overview , 10  
Content structure  
    planning , 16  
Content Translation module  
    installing , 135  
    overview , 134  
Content type  
    adding , 63  
    adding field to , 69  
    definition , 201  
    deleting , 67  
Contextual filters part of view  
    overview , 120  
Contextual link  
    definition , 201  
    overview , 34  
Contributed  
    definition , 201  
Contributed module  
    definition , 201  
    downloading , 152 , 161 , 166  
    evaluating , 146  
    finding , 146  
    installing , 152  
    overview , 3  
    updating , 189  
Contributed theme  
    definition , 201  
    downloading , 158 , 161 , 166  
    enabling , 158  
    evaluating , 155  
    finding , 155  
    installing , 158  
    updating , 192  
Contributing to the project , 195  
Copyright for this document , vi , 216  
Core module  
    overview , 3

Core software  
  installation requirements , 21  
  installing , 27  
  updating , 187  
Core theme  
  overview , 4  
Country setting  
  configuring , 37  
Cron command scheduler  
  definition , 201  
Cron task  
  configuring , 182  
  definition , 201  
  overview , 182  
Cross-site scripting (XSS)  
  preventing , 97  
Custom block  
  creating , 114  
  entity type , 13  
Custom block module  
  entity type , 13  
Custom menu  
  overview , 56  
Custom theme  
  enabling , 158  
  installing , 158  
  overview , 4

D

Data type  
  configuration , 6  
  content , 6  
  overview , 6  
  session , 6  
  state , 6

Database  
  backing up , 178  
  configuring during the installation process , 27  
  installation requirements , 21

Deployment workflow  
  overview , 163

Devel tool  
  overview , 22

Development site  
  making , 164  
  overview , 163  
  synchronizing with live site , 172

Disk space

  installation requirements , 21  
Display part of view  
  overview , 120

Distribution  
  definition , 201  
  full-featured , 5  
  overview , 5  
  quick-start , 5

Documentation  
  about Drupal , 198  
  about the Drupal API , 198  
  available on drupal.org , 198  
  contributed by the Drupal Community , 198  
  Drupal Planet blog posts , 198  
  for programmers , 198

Downloading  
  core software , 24 , 166  
  module , 152 , 166  
  module or theme files manually , 161  
  theme , 158 , 166

Drupal Association  
  overview , 7

Drupal Console tool  
  overview , 22

Drupal content management system  
  overview , 1  
  server requirements , 1

Drupal core  
  definition , 201  
  installing , 27  
  overview , 1  
  preparing install , 24

Drupal licensing  
  overview , 8

Drupal project  
  connecting with , 195  
  overview , 7

Drupal training  
  resources for , 198

Drupal user group  
  finding , 195

Drupal.org website  
  downloading and installing module from , 152  
  downloading and installing theme from , 158  
  downloading modules and themes from , 1  
  finding and evaluating modules on , 146  
  finding and evaluating themes on , 155

Drush tool  
    overview , 22  
    using to download and install module , 152  
    using to download and install theme , 158  
    using to install the core software , 24  
    using to uninstall module , 41  
    using to update module , 189  
    using to update the core software , 187  
    using to update theme , 192

Dynamic Page Cache module  
    overview , 175

E

Editing content , 52 , 53

Editor  
    configuring , 97

Editor module  
    configuring , 97

Editorial Workflow  
    overview , 19

Effect  
    image , 92 , 92

Email address  
    configuring , 37

Enabling  
    module , 152  
    theme , 158

Entity  
    definition , 201  
    overview , 13

Entity reference field  
    adding , 80

Entity subtype  
    definition , 202  
    overview , 13

Entity type  
    definition , 202  
    overview , 13

Entity view mode  
    overview , 88

Error  
    log report , 179

Error page  
    configuring , 37

Event  
    Drupal , 195

Extend menu entry  
    administrative menu , 34

F

Farmers market  
    usage scenario for this document , xi

Feature  
    copying , 169  
    deploying , 169

Featured regions  
    overview , 10

Field  
    adding to content type , 69  
    content reference , 73  
    definition , 202  
    for adding references , 80  
    overview , 13 , 84  
    reference , 73  
    taxonomy term reference , 73  
    user reference , 73

Field bundle  
    definition , 202

Field formatter  
    definition , 202  
    overview , 88

Field module  
    overview , 3

Field UI module  
    overview , 3

Field widget  
    definition , 202

Fields part of view  
    overview , 120

File  
    backing up , 178

File module  
    entity type , 13

Filter criteria part of view  
    overview , 120

Filter module  
    configuring , 97

Firebug tool  
    overview , 22

First day of week  
    configuring , 37

Footer menu  
    overview , 56

Footer regions  
    overview , 10

Form  
    overview , 84

Form entity type  
    overview, 13

Format part of view  
    overview, 120

Formatter  
    definition, 202  
    overview, 88

Forum  
    user support, 197

FOSS (Free and Open Source Software)  
    definition, 202  
    overview, 7

Free and Open Source Software (FOSS)  
    definition, 202  
    overview, 7

Front page  
    configuring, 37, 55

Full editor, 53

Full-featured distribution  
    overview, 5

Functionality  
    extending, 152

**G**

Git tool  
    overview, 22

Glossary, 200

GNU General Public License  
    definition, 202  
    overview, 8

GPL (General Public License or GNU General Public License)  
    definition, 202  
    overview, 8

Group  
    finding, 195

Guiding scenario for this document (farmers market), xi

**H**

Header region  
    overview, 10

Help menu entry  
    administrative menu, 34

Help region  
    overview, 10

Hiawatha web server  
    version requirements, 21

Highlighted region

    overview, 10

Home page  
    configuring, 55  
    creating, 50

HTML5 picture tag  
    and responsive images, 96

**I**

Image  
    resizing, 92

Image effect  
    overview, 92

Image field  
    adding, 69

Image module  
    creating a view, 121

Image style  
    creating, 92  
    definition, 203  
    overview, 92  
    responsive, 96

In-place editor, 53

Installation process, 27

Installation profile, 27

Installation requirements  
    database, 21  
    disk space, 21  
    overview, 21  
    PHP programming language, 21  
    web server, 21

Installer tool  
    running, 27

Installing  
    core software, 21, 24  
    development site, 163  
    module, 152  
    staging site, 163  
    theme, 158

Interest group  
    finding, 195

Interface Translation module  
    installing, 135  
    overview, 134

Internal Page Cache module  
    overview, 175

Internet Relay Chat (IRC)  
    using to chat online, 195, 197

IRC (Internet Relay Chat)  
    using to chat online, 195, 197

L  
Label  
    translating , 142  
LAMP (Linux Apache MySQL PHP)  
    definition , 203  
Language  
    adding , 135  
Language module  
    installing , 135  
    overview , 134  
Layout  
    planning , 11  
Learning resource  
    link to , 198  
Legal  
    overview , 8  
Licensing  
    overview , 8  
Linux Apache MySQL PHP (LAMP)  
    definition , 203  
Listing content  
    using Views module to , 121  
Live site  
    synchronizing with development site , 172  
Locale setting  
    configuring , 37  
Log  
    definition , 203  
    overview , 179  
Logo image  
    configuring , 45

M  
Maintenance mode  
    disabling , 150  
    enabling , 150  
    overview , 150  
Manage administrative menu  
    overview , 34  
Manually downloading module or theme files  
    overview , 161  
Menu  
    adding a link to page , 58  
    administrative , 56  
    custom , 56  
    definition , 203  
    footer , 56  
    main , 56

    overview , 56  
    user account , 56  
Menu items  
    reordering , 60  
Menu region  
    overview , 10  
Menu UI module  
    overview , 3  
Metadata  
    creating , 75  
Microsoft IIS web server  
    version requirements , 21  
Modular content  
    overview , 15  
Module  
    Admin Toolbar , 152  
    CKEditor , 97  
    Comment , 18  
    Configuration Manager , 172  
    Configuration Translation , 134 , 135  
    Contact , 18  
    Content Translation , 134 , 135  
    contributed , 3 , 152  
    core , 3  
    custom , 152  
    Custom Block , 13  
    definition , 203  
    downloading , 152 , 161 , 166  
    Dynamic Page Cache , 175  
    Editor , 97  
    enabling , 39 , 152  
    evaluating , 146  
    Field , 3  
    Field UI , 3  
    File , 13  
    Filter , 97  
    finding , 146  
    Image , 121  
    installing , 39 , 152  
    Interface Translation , 134 , 135  
    Internal Page Cache , 175  
    Language , 134 , 135  
    Menu UI , 3  
    Node , 3 , 18  
    overview , 3  
    Taxonomy , 13  
    uninstalling unused , 41  
    Update Manager , 152 , 158  
    updating , 189

User , 3 , 13  
Views , 3 , 121 , 126 , 129  
Views UI , 3  
Multilingual modules  
  enabling , 135  
  installing , 135  
MySQL database  
  version requirements , 21

**N**

Navigation  
  changing the order of menu items , 60  
  linking menu to page , 58

Nginx web server  
  version requirements , 21

Node module  
  entity type , 13  
  overview , 3

**P**

Page  
  adding to menu while editing , 58  
  composite , 15

Page cache  
  overview , 175

Path  
  definition , 203  
  overview , 49

People menu entry  
  administrative menu , 34

Performance  
  improving , 41  
  log report , 179  
  status report , 180

Permission  
  changing , 107  
  changing role , 109  
  definition , 203  
  denying , 107  
  granting , 107  
  overview , 100

PHP programming language  
  version requirements , 21

PHP version  
  status report , 180

Planning  
  site layout , 11

PostgreSQL database  
  version requirements , 21

Primary menu region  
  overview , 10

Profile  
  installation , 27

Published flag  
  overview , 19

**Q**

Quick editor , 53

Quick-start distribution  
  overview , 5

**R**

Reference field  
  adding , 80  
  content , 73  
  definition , 203  
  overview , 73  
  taxonomy term , 73  
  user , 73

Region  
  breadcrumb , 10  
  content , 10  
  definition , 203  
  featured , 10  
  footer , 10  
  header , 10  
  help , 10  
  highlighted , 10  
  menu , 10  
  overview , 10  
  placing a block in , 116  
  primary menu , 10  
  secondary menu , 10  
  sidebar , 10

Regional setting  
  configuring , 37

Relationships part of view  
  overview , 120

Report  
  Recent log messages , 179

Reports menu entry  
  administrative menu , 34

Resource  
  documentation and training , 198

Responsive  
  definition , 204

Responsive image style  
  overview , 96

Revision  
  definition , 204  
  overview , 19

Role  
  administrator , 102  
  anonymous user , 102  
  authenticated user , 102  
  changing , 109  
  changing permission , 107  
  creating , 102  
  definition , 204  
  overview , 100

S

Scenario for this document (farmers market)  
  overview , xi

Secondary menu region  
  overview , 10

Security  
  assigning permission , 107  
  cross-site scripting , 97  
  managing user accounts , 43  
  overview , 185  
  status report , 180  
  text format , 97  
  user account settings , 43  
  user one account , 101

Security announcement  
  subscribing to by email , 186  
  subscribing to on Twitter , 186

Security bug  
  reporting , 185

Security team  
  overview , 185

Security update  
  applying , 189 , 192  
  definition , 204  
  keeping track of , 186

Server information  
  status report , 180

Session  
  as a type of data , 6

Sidebar regions  
  overview , 10

Site email address  
  configuring , 37

Site information  
  status report , 180

Site layout  
  planning , 11

Site name  
  configuring , 37

Site plan  
  content structure , 16

Site slogan  
  configuring , 37

Site tagline  
  configuring , 37

Slogan  
  configuring , 37

Software dependencies  
  managing , 166

Software version  
  status report , 180

Sort criteria part of view  
  overview , 120

SQLight database  
  version requirements , 21

Staging site  
  making , 164  
  overview , 163

State  
  as a type of data , 6  
  definition , 204

Status report  
  overview , 180

Structure menu entry  
  administrative menu , 34

Style  
  image , 92 , 92

Support  
  finding , 197

T

Tagline  
  configuring , 37

Taxonomy  
  creating , 75  
  definition , 204  
  overview , 74

Taxonomy module  
  entity type , 13

Taxonomy term  
  definition , 204  
  overview , 13

Taxonomy term reference field  
  adding , 80  
  overview , 73

Term (taxonomy)  
  fixed list , 74  
  free tagging , 74  
  overview , 74

Term list  
  creating , 75

Terminology (Glossary) , 200

Text format  
  configuring , 97  
  definition , 204  
  overview , 97

Theme  
  configuring , 45  
  contributed , 158  
  core , 4  
  custom , 4 , 158  
  definition , 204  
  downloading , 158 , 161 , 166  
  enabling , 158  
  evaluating , 155  
  finding , 155  
  installing , 158  
  overview , 4  
  regions in , 10  
  third-party , 4  
  updating , 192

Third-party theme  
  overview , 4

Time zone setting  
  configuring , 37

Tool  
  Coder , 22  
  Composer , 22  
  Devel , 22  
  drupal Console , 22  
  Drush , 22  
  Firebug , 22  
  Git , 22

Toolbar  
  overview , 34

Training  
  Global Training Days , 198  
  resource , 198  
  Training Marketplace , 198

Translating  
  configuration , 142  
  content , 141  
  label , 142  
  overview , 134

view , 142

Troubleshooting  
  log report , 179  
  status report , 180

U

UI (User Interface)  
  definition , 204

Uniform Resource Locator (URL)  
  overview , 49

Uninstalling  
  unused modules , 41

Unpublished flag  
  overview , 19

Update  
  definition , 204  
  keeping track of , 186  
  overview , 185  
  status report , 180

Update Manager module  
  overview , 186  
  using to install module , 152  
  using to install theme , 158

Update status  
  status report , 180

URL (Uniform Resource Locator)  
  overview , 49

URL alias  
  overview , 49

URL field  
  adding , 69

Usage scenario for this document (farmers market) , xi

User  
  administrative , 101  
  configuring account setting , 43  
  creating account , 104  
  definition , 204  
  overview , 100  
  root , 101  
  user one , 101

User account menu  
  overview , 56

User group  
  finding , 195

User interface  
  translating , 134

User Interface (UI)  
  definition , 205

User module  
entity type , 13  
overview , 3

User one  
definition , 205

User profile entity type  
overview , 13

User reference field  
adding , 80  
overview , 73

User role  
changing , 109  
creating , 102  
overview , 100

User-entered content  
filtering , 97

**V**

View  
adding block display to , 129  
and modular content , 15  
contextual filters part , 120  
creating , 121  
definition , 205  
display part , 120  
duplicating , 126  
fields part , 120  
filter criteria part , 120  
format part , 120  
overview , 119  
parts of , 120  
relationships part , 120  
sort criteria part , 120  
translating , 142

View mode  
definition , 205  
overview , 88

Views module  
adding to a view , 129  
creating a view , 121  
duplicating a view , 126  
overview , 3 , 15 , 119

Views UI module  
overview , 3

Vocabulary  
creating , 75  
definition , 205  
overview , 13 , 74

**W**

Web installer  
running , 27  
using to install the core software , 24

Web server  
installation requirements , 21

What You See Is What You Get (WYSIWYG)  
configuring editor , 97  
definition , 205

Widget  
definition , 202 , 205  
overview , 84

Wizard  
definition , 205

WYSIWYG (What You See Is What You Get)  
configuring editor , 97  
definition , 205

**X**

XSS (Cross-site scripting)  
preventing , 97

---

# 附录 A. Appendix

## A.1. Guide-Wide Attributions

This guide was written by contributors to the Drupal open-source project, and is licensed under the [CC BY-SA 2.0](#) license. See [第 i.1 节 “Copyright”](#) for more information. Details about the contributors for guide-wide tasks are below. For individual topics, the attributions for writing, editing, and/or translating are at the end of each topic.

### Project coordination of original (English, Drupal 8) text

Writing of the initial version of this guide was coordinated by the following people:

- [Amber Matz](#) - Volunteer coordination and project management
- [Jennifer Hodgdon](#) - Content oversight
- [Joe Shindelar](#) - Content oversight
- [Antje Lorch](#) - Content oversight

### Writing, editing, and testing of original text

The following people contributed to guide-wide writing:

- The glossary was written and adapted by [Jennifer Hodgdon](#), with parts from "[Glossary](#)", "[Overview of Configuration \(vs. other types of information\)](#)", and "[Working with breakpoints in Drupal 8](#)", each copyright 2000-2016 by the individual contributors to the [Drupal Community Documentation](#).
- The index was improved and curated by [Anna van Raaphorst](#).
- Topic summaries were written by [Jojo Alphonso](#) at [Red Crackle](#).

Guide-wide editing was done by the following people:

- [Amber Matz](#) at [Drupalize.Me](#)
- [Anna van Raaphorst](#)
- [Antje Lorch](#)
- [Balu Ertl](#)
- [Boris Doesborg](#)
- [Charles Leverington](#)
- [chirag shah](#)
- [Grant Dunham](#)
- [Jennifer Hodgdon](#)

- [Joe Shindelar](#) at [Drupalize.Me](#)
- [Jojo Alphonso](#) at [Red Crackle](#) – who copy edited the vast majority of the User Guide
- [Kamal Kant Pansari](#) at [Intelliswift](#)
- [Michael Lenahan](#) at [erdfisch](#)
- [Swarad Mokal](#) at [Blisstering Solutions](#)

The content was tested by:

- [Zach Carter](#)
- A workshop organized by the "[Spokane Drupal User Group](#)" on [groups.drupal.org](#), with students from the Web Development Certificate program at [Spokane Community College](#)

## Images

Most of the images in the guide are screen captures from the Drupal software, generated by software written by [Jennifer Hodgdon](#).

The word Drupal, the Druplicon logo (which appears as part of several images throughout the guide), and the Drupal wordmark logo (which is part of the cover image), are [registered trademarks of Dries Buytaert](#).

The cover image is a CC BY-SA 2.0 licensed illustration by [Amanda Luker](#) at [Advomatic](#).

The Anytown Farmers Market logo, which appears as part of several images throughout the guide, is a CC BY-SA 2.0 licensed illustration by Justin Harrell at [Drupalize.Me](#).

The honey bee image, which appears as part of several images throughout the guide, is a public domain image by [John Severns](#) at the [English Wikipedia project](#) via [Wikimedia Commons](#).

The farm image, which appears as part of several images throughout the guide, is a public domain image by Xianmin Chang via [Wikimedia Commons](#).

The salad image, which appears as part of several images throughout the guide, is a public domain image by [Yinan Chen](#) via [Wikimedia Commons](#).

The carrot image, which appears as part of several images throughout the guide, is a public domain image [K11611-1](#) by Stephen Ausmus at the [Agricultural Research Service of the United States Department of Agriculture](#) via [Wikimedia Commons](#).

## Translation into Simplified Chinese

The Simplified Chinese translation of this guide was coordinated by:

- [Qiangjun Ran](#)