Calibrated Launch Integrity: A Verifiable, Manipulation-Aware Scoring Protocol for Newly Launched Tokens

Farbod Ghasemlu[1]

[1]Drydock Org , farbodghasemlu@outlook.com , ORCID: 0009-0009-2303-5672

Working paper, version of 13 October 2026

Abstract

Scores that screen newly launched tokens are widely used and almost never validated. We audit the score DryDock published for Arc launches (v1), an additive 0 to 100 index of weighted factors with hard caps, against its own code, and report twelve findings. The score has no stated estimand, so it cannot be tested. Market-activity factors, which insiders can manufacture, carry 44% of attainable points. Insider holdings are measured against total supply rather than pool depth, so a launch whose insiders hold 20% scores 85 ("Strong setup") although their exit would cut a buyer's position by 89%.

We then specify v2, which replaces points with quantities that carry units. The *structural floor* is what a 100 USDC reference position recovers under the worst single structural event available at a given block (tradability loss, liquidity removal, insider exit), computed by simulating the pool's, hook's and token's own code. Insider holdings form an interval whose pessimistic bound Sybil splitting cannot lower. Records are to be committed on Arc before outcomes; at the time of writing the commitment contract is not yet deployed, so no record counts yet. Calibrated channel probabilities and an expected-loss *Integrity Score* follow only once pre-registered sample-size gates and ship criteria are met.

We report the first data: 202,944 launches from Arc's first three weeks, of which a fixed sample of 9,475 traded launches was recomputed at five ages. Most records abstain; 99% of the launches still too early to rate at 24 hours have fewer than ten holders. Floor grades order realised 24-hour loss, from 3.5% at grade A to 68.5% at grade E, but on today's Arc the floor's lower end is close to a hard bound on price, so the pre-registered test passes almost by construction, and it passed only after a defect found in outcome data was fixed. The floor does order outcomes better than the price multiple since launch (exploratory), and v1's score was anti-correlated with outcomes. The registered test of severity at the event fails because its measure cannot discriminate; measured at the horizon, the floor is within 2.8 points of realised recovery (exploratory). Following an audit, replacement tests are registered before any committed record can be scored. The gates for calibrated probabilities are not met. The dataset and code are released.

Keywords: token launches, rug pulls, probabilistic forecasting, calibration, proper scoring rules, strategic classification, Sybil resistance, entity resolution, automated market makers, verifiable computation.
JEL: G14, G18, G23, C53, D82.

Working paper. Not peer reviewed. The records analysed in Section 8 were recomputed after their outcomes (retrospective). Forecasts issued live since 8 October 2026 are batched for commitment on Arc, but the commitment contract is not yet deployed, so none counts yet. This version responds to an audit of the version of 12 October (Appendix D).

1. Introduction

1.1 The problem

Most new tokens fail, and most fail fast. Xia et al. flagged over 10,000 scam tokens on Uniswap V2, roughly half of all listings [5]. Cernera et al. found that about 60% of tokens on Ethereum and BNB Chain are active for less than a day and estimated $240 million in profits from one-day rug pulls [7]. On Pump.fun, 0.63% of 655,770 tokens launched in September 2025 graduated, and 92.2% of tokens with at least 30 swaps showed a dump event [10]. An industry study found pump-and-dump characteristics in 98.6% of more than 7 million Pump.fun tokens with at least five trades between January 2024 and March 2025 [14].

Buyers decide in seconds, so a single number does most of the work. That number is usually an additive point score built from heuristics. A survey of 14 rug-pull detection tools found they cover 25 of 34 known root causes and miss wash trading, hidden fees and fake liquidity locks [8]. We found no launch-scoring product that publishes calibration against outcomes.

DryDock scores every launch from seven launchpads on Arc [3]. Arc is Circle's EVM Layer 1; public mainnet opened on 16 September 2026 with USDC as gas and block times near half a second [57, 61]. The chain was less than four weeks old on the date of this paper. Any score for it starts with almost no local outcome history.

1.2 The thesis

A launch score should be a forecast, and the cheapest way to raise it should be to make the launch safer. A forecast has an estimand, a unit, a resolution rule, a stated uncertainty and a public track record. A score with those properties can be wrong in a way anyone can measure. A score without them can only be believed or ignored.

This is the standard DryDock's own research applies to launches. The verifiable-launch paper states that the mechanism "proves process, never quality" and labels every guarantee with its trust tier [4]. We apply the same discipline to the score: say exactly what is measured, compute it from public state, and make the rest a testable probability.

1.3 Contributions

1. An audit of the published v1 methodology with twelve findings, each backed by arithmetic, a closed-form result or cited evidence (Section 3).
2. A scoring protocol, v2, built on three unit-bearing quantities: a simulated structural floor, calibrated channel probabilities and an expected-loss Integrity Score (Section 5).
3. A manipulation-resistance analysis covering eleven attacks, with five propositions on what an adversary can and cannot move (Section 6).
4. A pre-registered validation protocol with baselines, metrics, sample sizes, and ship and kill criteria (Section 7).
5. An implementation and the first data: every launch from Arc's first three weeks, a retrospective sample of 47,375 records with outcomes, the pre-registered tests that the data can support, and a real worked example (Sections 8 and 9).
6. A verifiability scheme in which forecasts are committed on-chain before outcomes resolve, so the track record cannot be edited after the fact (Section 10).

1.4 Method and scope

The audit covers v1 twice: as published on DryDock's methodology, risk and launchpad pages on 7 October 2026 [1, 2, 3], and as implemented in DryDock's code at the commit that last

served it (Appendix C). The first version of this paper, written before the code was examined, inferred the scoring rules from the published text; Section 3 states for every finding whether the code confirms it, contradicts it or confirms it in part, and corrects the arithmetic where the code differs from the text.

The design (Sections 4 to 7) is unchanged from that first version except where Section 7.8 records a deviation. The hypotheses, baselines, metrics, sample-size gates and ship and kill criteria were fixed before any Arc outcome was examined. Section 8 then reports what was built and what the data since mainnet opened can and cannot show: every launch on the seven launchpads DryDock lists from 16 September to 7 October 2026, with a fixed sample of 9,475 traded launches recomputed by the production code (the backfill, D11, labelled retrospective throughout), and the forecasts DryDock has committed on Arc since 8 October 2026.

Every number in this paper is produced by a kept script: the illustrative arithmetic by the script in Appendix B, the empirical results by the analysis code released with the dataset (Appendix C). Parameters of v2 that require outcome data are left as symbols or marked as priors. The paper does not claim that v2 predicts better than v1 on Arc. It specifies the experiment that would show whether it does, and reports how far that experiment has run.

2. Background and related work

2.1 Measuring launch fraud

The measurement literature agrees on scale and disagrees on labels. Xia et al. combined a guilt-by-association heuristic with a classifier and put the scam share of Uniswap V2 listings near 50% [5]. Mazorra et al. reported accuracy of 0.9936 for predicting malicious tokens before the malicious act [6]; their labels call a Uniswap V2 token malicious when it has had no transfer or reserve update for 30 days after losing nearly all of its liquidity or price without recovering, which yielded 26,957 malicious tokens against 631 labelled non-malicious. A figure derived from that work, that 97.7% of Uniswap V2 tokens were rug pulls, was publicly contested, and the lead author said the paper's aim was detection method, not prevalence [59].

The lesson for a scoring system is that the outcome definition decides the headline. Naviglio et al. show a large share of new-token liquidity trapped in honeypots [9], contracts that accept purchases and block sales, a class Torres et al. characterised on Ethereum [18]. Mongardini and Mei studied 34,988 meme coins on four chains and found that 82.8% of tokens returning over 100% showed artificial growth, with extraction following earlier manipulation [13]. A score must therefore define its failure event mechanically, so that two parties with the same chain data label the same token the same way.

2.2 What predicts launch outcomes

Marino et al. model the probability that a Pump.fun token graduates, conditional on bonding-curve state and trader composition [10]. Fast accumulation in few trades is the strongest predictor. Bot-dominated activity predicts lower graduation odds. The presence of previously profitable traders adds "at most a modest and nonmonotonic effect." They build every conditioning variable from information available at the decision point and propose a hazard-rate formulation as the natural extension.

Ding, Luo and Xu sample 6,000 Pump.fun projects and separate manipulation tactics [11]. Creator-controlled wallets buy in the creation block in 24% of projects, and snipers buy within five blocks in 84%. Creators start the dump in about half of projects. Among traders with statistically significant positive returns, 19.2% are creators and 16.0% are snipers, against 0.8% and 1.0% among consistent losers.

Luo et al. prove an imitation penalty: a copier who trades immediately after a profitable wallet on a bonding curve earns strictly less than that wallet [12]. In their test set, copier returns were negative under all three statistical models even though the copied wallets were profitable.

2.3 Fabricated activity

Wash trading is cheap, common and effective at attracting buyers. Victor and Weintraud identified $159 million of wash trades on two early decentralized exchanges, affecting over 30% of tokens [16]. Cong et al. estimate that wash trades averaged more than 70% of reported volume on unregulated centralized exchanges [17]. Ding et al. give causal evidence at the launch level: adopting a wash-trading bot raises the number of participating traders by about 98% within the event window, and a comment bot by about 116%, with no gain in average trader profit [11].

2.4 Entity resolution and Sybils

An address is not a person. Bitcoin clustering by shared spending [19] and Ethereum heuristics based on deposit-address reuse, airdrop participation and token authorisations [20] recover some of the mapping. Douceur showed that without a trusted identity authority, one party can always present many identities [21]. Industry analysis of Pump.fun found deployer-funded same-block snipers on more than 15,000 tokens in a month using direct funding links only, and documented multi-hop funding chains that the direct method missed [15].

Clustering therefore gives a lower bound on common control. The econometric response to a quantity that data cannot pin down is partial identification: report the set of values consistent with the evidence, not a point [22]. Section 5.3 applies that idea to insider holdings.

2.5 Forecasts, calibration and uncertainty

A probability forecast is calibrated when events assigned probability p occur with frequency p. The Brier score [23] and logarithmic score are strictly proper: a forecaster minimises expected loss only by reporting true beliefs [25]. Murphy's decomposition splits the Brier score into reliability, resolution and uncertainty, which separates honest probabilities from useful ones [24].

Raw model scores are rarely calibrated. Platt scaling [26], isotonic regression [27] and their comparison [28] are standard remedies, and clinical prediction research treats calibration as the property most often neglected [29, 30]. Venn-Abers predictors output a probability interval with a validity guarantee under exchangeability [31], and adaptive conformal inference maintains coverage under distribution shift [32].

2.6 Scores that change what they measure

Goodhart's observation that a measure used as a target loses its meaning [36] has a formal literature. Strategic classification models agents who alter features at a cost to obtain a better label [33]. Kleinberg and Raghavan distinguish gaming from improvement and characterise scoring rules that induce the latter [34]. Performative prediction studies forecasts that shift the distribution they forecast [35]. In credit ratings, a rater whose revenue depends on the rated party's activity faces a documented incentive to inflate [52].

2.7 Composite indices and existing tools

The OECD handbook on composite indicators requires a theoretical framework, justified weights and a sensitivity analysis before a weighted sum is published [37]. Dawes showed that even unit-weighted linear models predict well, but only when a criterion variable defines what is being predicted [38]. Existing token scores are composites without a criterion. The DEXT Score is described by its publisher as a 0 to 99 automated rating built from contract, liquidity and holder data, and Solana Tracker exposes a 1 to 10 risk score built from weighted risk factors [58].

2.8 The gap

The academic work classifies tokens after the fact or predicts a single platform-defined outcome. The products score in real time but publish no estimand and no accuracy. We found no prior design that joins a mechanistic, unit-bearing severity measure to calibrated event probabilities, treats common control as an identified set, and commits forecasts before outcomes. That is the composition proposed here. As in [4], the claim is "not found in our search".

3. Audit of the current score (v1)

The first version of this paper audited the published methodology page only. For this version the audit was checked against the v1 source code, which was not available when the findings were first written. Section 3.2 describes v1 as it was implemented; each finding in Section 3.3 is marked confirmed, partly right or wrong, with the evidence. The findings were not rewritten to fit: where the code contradicts the page, both are stated.

3.1 The score as published

The v1 score is the sum of seven factors with four caps [1]. Full marks require the conditions below, and the page states verdict bands of 70 to 100 ("Strong setup"), 50 to 69 ("Speculative"), 30 to 49 ("High risk") and 0 to 29 ("Avoid").

Factor	Weight	Full marks when	Zero when
Insider supply	15	Creator, first-seconds buyers and same-source wallets hold under 3%	Above 30%
Top 10 holders	10	Ten largest non-pool holders hold under 15%	Above 50%
Creator	10	An earlier launch by the creator reached 100k USD	Not stated
Liquidity	15	At least 25k USDC in the pool, held by the launchpad or burned	Not stated
Demand	20	30 or more buyers in the last hour, net buying, little wash trading	Not stated

Factor	Weight	Full marks when	Zero when
Momentum	10	Price rising over the hour, near its peak, volume accelerating	Not stated
Smart money	10	Wallets with a winning record hold; snipers hold little	Not stated

The caps are: liquidity withdrawable by a regular wallet, 25; insiders above 30% of supply, 30; creator selling while holding over 5%, 35; under 1k USDC of liquidity, 40.

This is the page as committed on 1 October 2026. A revision committed on 7 October added a trading-costs factor (weight 5), a cap of 35 for a sell tax of 20% or more, a fifth listed cap for creators who repeatedly buy their own launches and sell within minutes, and the sentence "each factor earns points up to its weight, and the total is scaled to 100". The first version of this paper said the page had not changed when re-read on 8 October; the repository history shows that it had, and that statement is withdrawn.

3.2 The score as implemented

v1 ran in the reader's browser from a "dossier" of the token's on-chain history (its transfers and swaps since launch, the position NFT minted in the launch transaction, and the funders of early buyers). The code differs from the page in four respects that matter for the findings.

The score is normalised. Each factor present contributes points up to its maximum; the score is 100 times the points earned over the points attainable, rounded, and then lowered to the smallest applicable cap. The smart-money factor counts only after wallet records have loaded, so the attainable total was 80 or 90 (85 or 95 from 7 October).

The published factors are compositions. "Liquidity" was two factors and "Demand" three:

Factor (code)	Weight	Rule between the endpoints
Top 10 holders	10	Linear from 50% (0) to 15% (full) of supply held by the ten largest holders, excluding pools, routers and launchpad contracts. From 7 October multiplied by min(1, holders/25)
Insider supply	15	Linear from 30% (0) to 3% (full). From 7 October multiplied by 0.4 + 0.6 min(1, holders/25)

Factor (code)	Weight	Rule between the endpoints
Creator	10	Discrete: 6 by default; 10 if an earlier launch peaked above 100k USD; 2 after 20 or more earlier launches; 0 after 5 or more launches with none above 10k USD, or if the creator bought at least 50 USD in the launch window and sold within 30 minutes; 6 fewer if the creator had sold more than half its peak holding
Liquidity depth	10	Linear in the logarithm of the pool's USDC, from 500 to 25,000 USDC
Liquidity custody	5	Position NFT burned or held by the launchpad 5, held by another contract 3, by a wallet 0; 5 when no NFT was found
Real buyers	10	Linear from 2 to 30 distinct buyers in the last hour
Buy pressure	5	Linear from 35% to 65% of the last hour's volume being buys
Organic volume	5	Linear from 0.4 to 0.9 in one minus the larger of the wash share and (top-three volume share minus 0.3, when it exceeds 0.6)
Momentum	10	4 points linear in the 1-hour price change from -30% to $+30\%$, 3 in one minus the drawdown from 0.3 to 0.8, 3 in volume acceleration from 0.5 to 1.5
Smart money	10	10 min(1, profitable holders/3) $-$ 6 min(1, sniper share/0.2) + 3, clipped to 0 to 10; only with wallet records
Trading costs (from 7 Oct)	5	Linear in the round-trip cost (buy tax + sell tax + twice the pool fee + 1%) from 25% to 3%; 2 points if the hook's taxes could not be read

The code also capped at 30 a creator whose own wallet, over at least three launches in a day, bought in the launch window and sold after a median of under 30 minutes; the 1 October

page did not list this cap.

Liquidity is not depth. For a Uniswap V3 pool "liquidity" was the pool contract's USDC balance; for a V4 pool, which shares the PoolManager's balance with every other pool, it was the cumulative net USDC of observed swaps. Neither is the depth a sale would meet.

Insiders, funders and labels. Insider supply was the share of total supply held by the creator, by every wallet that bought within 20 blocks of the launch block (up to 40 wallets), and by shared funders and the wallets they funded. A funder was the last address to send USDC to an early buyer in the 100,000 blocks (about 14 hours) before the launch; wallets were linked when two or more early buyers shared that funder or the funder was the creator. Wallet records covered each wallet's transfers in the last 172,800 blocks (about 24 hours) for up to 40 wallets. A "profitable trader" needed at least five launches, at least 55% of them won, and more than 10 USD ahead, where a launch counted as won if realised proceeds plus the unsold balance at the current price exceeded the cost. A "losing trader" was five or more launches and more than 10 USD behind. The "base rates" line counted, per launchpad, launches between 1 and 14 days old whose peak market cap reached each step of a 1,000 USD $\times$ 1.5^n ladder, and reported the share that reached the step at twice the current market cap; from 7 October it was shown only when at least 20 launches had reached the current step and that step lay above the launchpad's median peak.

Appendix C keeps v1 runnable offline; it is the baseline B1 and B2 of Section 7.3.

3.3 Findings, checked against the code

F1. The published weights sum to 90. *Partly right.* The arithmetic holds for the page, and the page's phrase "the sum of seven factors" was inaccurate. The conclusion drawn from it was wrong: the code divided by the points attainable, so "Strong setup" required 70% of attainable points, not 77.8%, and the top band was reachable. The missing ten points are not an unpublished factor; the published "Liquidity" and "Demand" are sums of sub-factors that do total 15 and 20. A related defect the page could not show: the attainable total moved from 80 to 90 when wallet records finished loading, so the same token's score changed on screen without anything happening on chain.

F2. The score has no estimand. *Confirmed.* Neither the code nor the page names an event or a horizon.

F3. Two different constructs are added together. *Confirmed, with corrected shares.* Structure (top holders, insiders, creator, depth, custody) carries 50 points and activity (buyers, buy pressure, organic volume, momentum, smart money) 40, which is 44.4% of 90. Without wallet records activity is 30 of 80 (37.5%); from 7 October 40 of 95 (42.1%).

F4. The momentum factor is procyclical and reflexive. *Confirmed.* The code rewards a rising 1-hour price, a small drawdown from the peak and accelerating volume.

F5. Activity can buy back concentration. *Confirmed; the number was wrong in the conservative direction.* The interpolation is linear between the published endpoints, as assumed, but the score is normalised. With a measured insider share of 20%, top-ten share 30%, and everything else at full marks, the launch earns 76.27 of 90 points: a score of 85, not 76.3. At 8% it scores 92. Under the 7 October code it scores 86 and 93. Either way it is a "Strong setup", and the 89% exit impact of Proposition 1 is unchanged.

F6. Insider concentration is measured in the wrong unit. *Confirmed.* Insider holdings were divided by total supply; pool depth entered nowhere.

Proposition 1 (pool-relative concentration). In a constant-product pool [55] whose token reserve is a share g of total supply, an entity that sells a share f of total supply moves the marginal price to the multiple below and removes the stated fraction of the quote reserve, before fees.




Figure 1: Price after an insider sale in a constant-product pool, by the pool's share of supply (Proposition 1). The grey line marks an 80% drop. Computed by Appendix B.

$$\frac{P^+}{P} = \left(\frac{g}{g+f}\right)^2, \qquad \frac{\Delta x}{x} = \frac{f}{g+f}$$

Proof. With reserves x and y and invariant $xy = k$, the sale takes the token reserve from gS to $(g+f)S$, so the quote reserve falls to $x\,g/(g+f)$. The price x/y is multiplied by $(g/(g+f))^2$. ■

An 80% price drop needs an insider share of only 12.4% when the pool holds 10% of supply, and 49.4% when it holds 40%. The v1 cap at 30% is too lax for thin pools and arguably too strict for deep ones. The same objection applies to the top-ten-holders factor. Concentrated-liquidity pools need the simulated version of this calculation (Section 5.2), but the direction of the result is the same.

F7. The caps are cliffs. *Confirmed.* Caps were applied after normalisation; in the F5 example an insider share of 29.9% scores 79 and 30.1% scores 30.

F8. Absolute thresholds are not portable across launchpads. *Confirmed and wider than stated.* Not only ArcPad: lift.fun, Tolly and Argus also launch the whole supply as a single-sided position, so the pool's USDC starts at zero and every such launch began under the 1,000 USDC cap and with zero depth points. For V4 pools the "liquidity" was net swap flow, so the depth factor measured demand. Sashimi produced no graduation in the observation window, so its treatment could not be checked.

F9. Contract and hook risk is disclosed but not scored. *Confirmed for the audited version, partly addressed later.* The 1 October code had no sell simulation, no tax read and no fee-mutability check. On 7 October v1 began reading each hook's current taxes, scored round-trip costs (weight 5) and capped a sell tax of 20% or more at 35. It never simulated a sale and never asked whether a fee could change.

F10. Several inputs cost only gas to fake. *Confirmed.* Shared-funder detection followed one hop (the last USDC sender), looked only at buyers in the first 20 blocks, and ignored hubs by skipping to the previous sender rather than ending the path.

F11. The wallet labels reward luck and insiders. *Partly right.* The window (24 hours, at least five launches) is as stated, but the code required at least 55% of launches won rather than more than half, and counted unsold tokens at the current price. At five and ten launches the two rules coincide, so the false-positive rates quoted for five launches (16.3%, 23.5% and 31.7% at q of 0.30, 0.35 and 0.40) stand; at 15, 30 and 40 launches the code's rule is stricter (Appendix B). Marking unsold tokens to the current price makes a "win" depend on the moment the label was computed.




Figure 2: Chance that a wallet earns a skill label, by launches traded: v1's "profitable trader" rule as implemented (at least 55% of launches won) for wallets with no skill, and the v2 rule of Section 5.8 for wallets with no skill and with a true win rate of 0.60. Computed by Appendix B.

The label is also confounded with the insider signal. Consistent winners on launchpads are disproportionately creators and snipers [11]. A factor that awards points when "wallets with a winning record are holding" may be awarding points for the presence of the wallets the insider factor is meant to penalise. Independent evidence finds the signal weak and non-monotonic [10], and following such wallets loses money after price impact [12].

F12. There is no uncertainty, validation or version history. *Confirmed.* The code scored a token from its first block. The repository holds the code's history, but no changelog or backtest was published.

3.4 What v1 gets right

Four choices in v1 are sound and are kept. Deal-breakers are non-compensatory in spirit. Pool and launchpad contracts are excluded from holder counts. Funding-source linkage is the right first step in entity resolution. The "base rates" panel, which shows how many earlier launches at the same market cap went on to double, is an outcome-conditioned frequency and is the seed of the calibrated design in Section 5.

3.5 Summary

#	Finding	Status against the code	Evidence	Addressed in
F1	Weights sum to 90	Partly right: the score was normalised	Code; arithmetic	5.5
F2	No estimand	Confirmed	Code and page	5.1
F3	Structure and activity are summed	Confirmed (44.4% with wallet records, 37.5% without)	Code	5.7

#	Finding	Status against the code	Evidence	Addressed in
F4	Momentum is procyclical and reflexive	Confirmed	Code; [10, 11, 12, 35]	5.7, 6
F5	Compensation yields “Strong” with 89% exit impact	Confirmed; score 85, not 76.3	Code; worked example	5.5
F6	Concentration ignores pool depth	Confirmed	Code; Proposition 1	5.2
F7	Caps are cliffs	Confirmed	Code; [33]	5.5
F8	Dollar thresholds are launchpad-dependent	Confirmed for four launchpads, not one	Code; launch transactions	5.2
F9	Hook and fee risk unscored	Confirmed on 1 October; taxes scored from 7 October, still no simulation	Code history	5.2
F10	Sybil-cheap inputs	Confirmed: one hop	Code; [15, 21]	5.3, 6
F11	Labels reward luck and insiders	Partly right: 55% rule, marked to market	Code; binomial calculation	5.8
F12	No uncertainty or validation	Confirmed	Code; absence	5.6, 7, 10

4. Design requirements and threat model

4.1 Requirements

The audit yields eight requirements. Each is stated so that a design either meets it or does not.

#	Requirement	Test
R1	Estimand	Every published number names an event, a horizon, a unit and a resolution rule
R2	Separation	Structure and market activity are never summed; price momentum cannot raise the headline
R3	Non-compensation	No amount of good news on one channel offsets a fatal condition on another

#	Requirement	Test
R4	Venue invariance	Quantities are computed against the actual pool, not against fixed dollar thresholds
R5	Honest uncertainty	Outputs carry intervals, and the system abstains when evidence is thin
R6	Incentive alignment	The cheapest way to raise the score is to reduce the risk it measures
R7	Reproducibility	The score is a deterministic function of finalized chain state and a versioned specification
R8	Accountability	Forecasts are committed before outcomes and scored in public; there are no manual overrides

R6 follows Kleinberg and Raghavan's distinction between gaming and improvement [34]. R8 carries the four-input rule of [4] into scoring: the platform decides nothing on a user's behalf, and anything it asserts can be checked.

4.2 Adversary

The adversary is a token creator with colluders. The adversary knows the full specification, as the design assumes no secrecy. The adversary controls any number of addresses, since an address on Arc costs cents of USDC gas. The adversary has a capital budget b, can prepare in advance by ageing and funding wallets, can deploy any contract or hook the launchpad allows, and can trade with itself.

The adversary has three goals. The first is to raise the score while keeping the ability to extract buyers' funds. The second is to lower a competitor's score, for example by sending dust to make unrelated wallets look linked. The third is to poison the outcome data on which calibration and reputation rest.

Out of scope are compromise of DryDock's infrastructure, validator-level attacks on Arc, off-chain persuasion, and anything requiring legal identity.

4.3 The platform as a party

The design does not ask users to trust the platform's reported accuracy. It makes that accuracy independently computable (Section 10).

4.4 Properties of Arc that shape the design

- **Finality.** Arc finalizes blocks deterministically in under a second [57]. Scores are computed at a finalized block height, and no reorganisation handling is needed.
- **Gas in USDC.** Identity creation is nearly free, so any count of addresses is worthless as evidence (F10).




Figure 3: The v2 pipeline. One block feeds three layers; only Layers 1 and 2 enter the record, and the market panel has no path into it. The dashed loop is the only route by which outcomes change later forecasts.

- **A young chain.** Wallet age on Arc is at most a few weeks. Seniority evidence must come from elsewhere, for example the same address's history on other EVM chains, and must be treated as weak.
- **Issuer blocklist.** Arc enforces a USDC blocklist: a USDC transfer from or to a blocklisted address reverts, and a blocklisted sender's transaction is rejected [62]. A sale can fail for reasons outside the token contract, so tradability is tested by simulation, not inferred from code.
- **Planned confidential transfers.** Circle has described opt-in privacy for Arc [57]. If transfer amounts become hidden for a token, balance-based features are unobservable and the system must abstain for it.

5. The protocol

The protocol publishes three layers and never adds them together. Layer 1 is facts computed by simulation. Layer 2 is forecasts of defined events, calibrated against outcomes. Layer 3 is a description of market activity that cannot move the score.

The market panel receives the same block but has no arrow into the score. The loop at the bottom is the only path by which outcomes change later forecasts.

5.1 Estimands and resolution rules

Every forecast is issued at a finalized block *h* for a horizon *H*. The primary horizon is 24 hours; 1 hour and 7 days are secondary. All quantities refer to a **reference position**: 100 USDC of the token bought at *h* through the token's main pool.

Let *q* be the tokens that purchase returns, and let *Q(q)* be the USDC returned by selling them through the pool's own code, including fees and hooks. If the sale reverts, *Q* is zero. The round-trip recovery is

$$\rho_h = \frac{Q_h(q)}{100}$$

Three **structural events** are defined on the interval from h to $h + H$. Each is an on-chain occurrence that any two archive nodes will agree on. None requires a judgement about intent.

Event	Channel	Resolution rule
E_T	Tradability	The reference position cannot be sold, or a privileged state change (fee, pause, blocklist, mint, upgrade) lowers its simulated recovery by 20 points or more
E_L	Liquidity	Position owners withdraw at least 50% of the quote-side liquidity present at h
E_I	Insider exit	The pessimistic insider set (Section 5.3) net-sells at least 50% of the tokens it held at h

A fourth, all-cause endpoint is used only in the market panel: **severe loss**, meaning the reference position returns 20 USDC or less at $h + H$. It mixes structural failure with ordinary loss of interest, which is why it is kept out of the score.

The thresholds 20 points, 50% and 20 USDC are definitional. They fix what is being forecast. They are not tuned to make results look better, and Section 7 reports sensitivity to them.

5.2 Layer 1: facts by simulation

For each channel the system simulates the worst event available at block h and then sells the reference position. This is done with state-override calls against the pool at h, so fees, hooks, tick liquidity and single-sided ranges are handled by the pool's own code. No dollar threshold is involved (R4).

- **Tradability.** Set every privileged parameter to the worst value the code permits without a timelock longer than H. If the code is unverified, upgradeable without delay, or otherwise unbounded, the recovery is recorded as zero, the record is flagged "unbounded", and the record's state is unobservable: no floor or grade is published, and the token page shows an explicit warning that the code cannot be checked (Appendix A.2, step 5).
- **Liquidity.** Remove every liquidity position whose owner can withdraw within H, and have each owner sell what the withdrawal returned (from method 2.1.0). Burned positions and positions in a recognised locker that unlocks after $h + H$ stay.
- **Insider exit.** Sell the full balance of the insider set, once for the lower-bound set and once for the pessimistic set. From method 2.1.0 a member first withdraws any liquidity position it can withdraw, so tokens parked in liquidity count toward its exit.

Write the recovery of the reference position after event k as ρ with superscript k. The **loss given event** and the **structural floor** are

$$\ell_k = 1 - \rho_h^{(k)}, \qquad \Phi_h = 100 \cdot \min_{k \in \{T,L,I\}} \rho_h^{(k)}$$

The floor reads directly: "in the worst single structural event available now, 100 USDC becomes Φ". Because the insider set is an interval, so is the floor. The recovery of entering

and leaving with no event, ρ with superscript 0, is reported beside it as friction (about 98 per 100 for a pool with a 1% fee; the round-trip cost is one minus it).

The floor answers F6, F8 and F9 at once. It is pool-relative by construction. It needs no liquidity threshold. A punitive or mutable sell fee appears as a low tradability recovery.

5.3 Entity resolution as an identified set

Common control cannot be observed, so the system reports bounds (Section 2.4).

The lower-bound set contains the creator and every wallet tied to it by positive evidence: funding within d hops through non-hub addresses, purchases in the creation block, receipt of the token by transfer before a first purchase, or proceeds that converge on a common address. Bridges, exchange wallets and launchpad routers are hubs. They are listed in a public registry and end a funding path.

The pessimistic set adds every holder that cannot show independence. Independence requires all three of: an address history that predates the token by a set margin, on Arc or on another EVM chain; a first purchase outside the launch window; and funding that does not trace only to fresh unlabelled addresses. The burden of proof sits on independence.

Links are created only by value the linked wallet acted on. An unsolicited inbound transfer never creates a link. This closes the dust-griefing attack of Section 4.2.

Proposition 2 (Sybil monotonicity). Suppose the adversary redistributes a fixed insider holding among any number of newly created addresses and inserts any number of newly created funding intermediaries. The token balance of the pessimistic set, and therefore the pessimistic insider loss and the lower end of the floor, do not change.

Proof. A newly created address fails the history test and belongs to the pessimistic set whether or not it is linked. Redistribution conserves the total balance. ■

The adversary can shrink the pessimistic set only by using addresses with history, or by actually distributing tokens to independent holders. History takes time to build but is not scarce: the margin counts transactions, and on Arc a farm of 1,000 wallets that each send the required ten costs about 4.2 USDC of gas and 30 days of lead time (Section 6.3). The second is improvement, not gaming (R6).

The weakness is stated plainly. On a three-week-old chain most honest buyers also lack history, so the pessimistic bound is wide for almost every launch. The interval is still correct, and the forecasting layer learns from outcomes how much weight each end deserves.

5.4 What the forecasts condition on

Each channel has its own feature block. Every feature has one direction: more of it can only raise the forecast probability.

Channel	Risk features	Protective facts
Tradability	Privileged roles present; maximum settable fee; hook permissions that alter swap amounts; unverified or upgradeable code	Roles renounced; fee parameters immutable; timelock longer than the horizon
Liquidity	Share withdrawable within the horizon; owner is an ordinary wallet; unlock inside the horizon	Position burned; recognised locker with later unlock

Channel	Risk features	Protective facts
Insider exit	Insider loss at both bounds; share of public USDC the insiders can extract; recent insider net selling; bundled creation-block buys; creator cluster's prior event rate; wash share	Insider tokens in a vesting or timelock contract

Protective facts are irreversible or time-locked commitments. They cannot be faked without being done, and doing them lowers the risk (R6). Wash share enters as a risk feature only: fabricated activity predicts later extraction [13], and genuine activity earns no credit here.

Creator history uses a shrunk estimate. A creator cluster's prior event rate is a Beta-Binomial posterior with a launchpad-level prior [42]. A new creator gets the prior, neither penalty nor credit, which matches the treatment of fresh identities in [4]. Launches are weighted by public capital at risk so that many tiny self-traded tokens cannot manufacture a record.

5.5 Model and aggregation

Each channel probability is a discrete-time hazard with monotone components:

$$\operatorname{logit} \pi_k(h, H) = \alpha_{k,\mathrm{pad}} + s_k(\mathrm{age}) + \sum_j m_{kj}(x_j), \qquad m_{kj} \text{ non-decreasing}$$

The launchpad intercepts are partially pooled toward a common mean, so a launchpad with little history borrows strength from the others [60]. The age term is a baseline hazard. Tokens that have not reached their horizon are right-censored and handled as in survival analysis [43], and repeated forecasts for one token are evaluated at fixed ages by landmarking [44].

Monotonicity serves three purposes. Each feature has an interpretable direction. With few outcomes, the constraint is strong regularisation. An adversary cannot find a region where adding risk improves the forecast.

Under independent channel events and multiplicative recoveries, the expected recovery of the reference position is a product. Friction is paid once, whatever happens, so it is applied once; each channel then contributes the expected loss given its event, net of friction. The **Integrity Score** is that expectation on a 0 to 100 scale:

$$\mathrm{IS}_h = 100\, \rho_h^{(0)} \prod_{k \in \{T,L,I\}} \big(1 - \pi_k\, \lambda_k\big), \qquad \lambda_k = \min\big(\hat{\lambda}_k,\ \tilde{\ell}_k\big), \quad \tilde{\ell}_k = 1 - \rho_h^{(k)} / \rho_h^{(0)}$$

Here ρ with superscript 0 is the friction recovery, ρ with superscript k the simulated recovery after event k, and the cap is the simulated worst-case loss net of friction. The loss given event λ_k is estimated from resolved outcomes, as credit risk estimates loss given default: the mean realised loss, net of friction, over resolved records in which event k fired, by launchpad and age. Because π_k is the probability of a threshold event (for example, at least half of the pessimistic set's tokens sold), not of the worst case, multiplying it by the worst-case loss would overstate expected loss; λ_k is the loss that actually followed such events. Until a channel has the events of Section 7.5, λ_k is set to that worst case, the conservative choice, and the worst case always caps it. This definition replaces the one first registered, 100 times the product

over channels of one minus π_k times a loss that included friction, which counted friction up to three times and paired threshold probabilities with worst-case losses (Section 7.9).

The score has a unit: expected USDC remaining, per 100, after friction and structural events over the horizon. It equals 100 times the friction recovery when no event is likely or none would hurt. It falls toward the floor as the worst event becomes certain and its realised losses approach the worst case.

Proposition 3 (non-compensation). For every channel k, the Integrity Score is at most $100\rho^{(0)}(1 - \pi_k\lambda_k)$, and it is non-increasing in every π and every λ.

Proof. The friction recovery lies in [0, 1], and each factor of the product lies in [0, 1] and is non-increasing in its π and λ. ■

No feature outside channel k can lift the score above the bound that channel sets. Caps are unnecessary, and there are no cliffs (F5, F7). The independence assumption is tested, not trusted: Section 7 checks whether mean realised recovery matches the score in each score bin.

5.6 Calibration, uncertainty and staged release

Arc has too little history to estimate probabilities today. The release is therefore staged, and each stage says what it is.

1. **Stage 0, severity only.** Publish the floor interval, the three losses given event and friction. Publish no probability. This stage needs no outcome data and can ship now.
2. **Stage 1, calibrated channels.** Once the sample-size gates of Section 7.5 are met, publish each π with a Venn-Abers interval [31]. Recalibrate on a trailing window by isotonic regression [27] and track coverage with adaptive conformal updates [32].
3. **Stage 2, Integrity Score.** Publish the score as the headline only after it passes the ship criteria of Section 7.6 on out-of-time data.

The system abstains in three cases. "Too early" applies below a minimum token age or a minimum number of independent trading entities. "Unobservable" applies when balances are hidden or code is unbounded; unbounded code is the one abstention shown as a warning, not a neutral state, so that deploying unverifiable code earns a visible flag rather than silence. "Low confidence" applies when the probability interval is wider than a set width. An abstention is shown as such, never as a low or middling number (F12).

For Stage 0 a letter grade summarises the lower end of the floor: A for 90 or more, B for 75 to 89, C for 50 to 74, D for 20 to 49, E below 20. The bands are presentation only. Each is a statement in USDC, and none is used in any computation.

5.7 Layer 3: the market panel

Market activity is shown beside the score and never inside it (R2). Price momentum appears only as a chart.

- **Net retained public inflow.** USDC paid in by entities outside the pessimistic set, minus USDC they took out. Round-trip volume nets to zero.
- **Effective participants.** The exponential of the entropy of net-inflow shares, a Hill number [56]. Splitting one buyer into thirty linked wallets leaves it unchanged.
- **Wash share.** Volume in closed cycles or matched equal-size round trips, as a share of total volume [11, 16], with a flag when swap fees flow back to the creator.
- **Depth.** Round-trip recovery of a 1,000 USDC position.
- **Reference-class outcome.** The severe-loss frequency among earlier launches on the same launchpad at a similar age and floor grade, stated as counts.

$$N_{\text{eff}} = \exp\Big(-\sum_i s_i \ln s_i\Big)$$

The reference-class line generalises v1's "base rates". It is written as a natural frequency, for example "of N earlier launches like this one, M returned 20 USDC or less per 100 after 24 hours", because readers reason more accurately from counts than from percentages [51].

5.8 Wallet labels

Behavioural labels such as "bot" and "sniper" describe what a wallet did and stay as descriptions. The skill label changes in four ways.

1. The window is 30 days and at least 20 resolved launches, not 24 hours and five.
2. Launches where the wallet belongs to the lower-bound insider set are excluded. Insider profit is not skill.
3. A wallet is labelled only if the posterior probability that its win rate exceeds the launchpad baseline by five points is above 0.95, under a Beta prior centred on that baseline [42], with false-discovery control across wallets [39, 40, 41].
4. The label must hold out of sample: assigned on one window, confirmed on the next, as in [10].

With a prior of mean 0.35 and weight 20, a wallet with five launches can never qualify, and one with 20 launches needs 15 wins. The false-positive rate stays below 0.2% at every sample size tested. The cost is power: a wallet with a true 60% win rate is detected 77% of the time at 50 launches. Skill takes that long to tell from luck. The label never enters the score.

5.9 Presentation

The token page leads with facts in currency, then the forecast, then the market panel. Verdict words such as "Strong setup" are retired. They assert safety in a population where most launches fail, and no data yet show that the top band is safe. The stage of each number is printed beside it.

6. Manipulation-resistance analysis

Of eleven attacks, v2 removes the payoff of eight by construction and leaves three with a stated residual. The adversary is the one in Section 4.2 and knows the full specification.

6.1 Attacks

#	Attack	Effect on v1	Effect on v2	Residual in v2
A1	Split insider holdings across fresh wallets	Lowers top-ten share; lowers insider share if unlinked. Cost: gas	None on the pessimistic bound (Proposition 2)	None

#	Attack	Effect on v1	Effect on v2	Residual in v2
A2	Fund buyers through intermediaries, bridges or exchanges	Defeats the one-hop shared-funder check	Lower bound may miss the link; pessimistic bound unchanged	Wider interval
A3	Use wallets aged in advance	Not needed	Shrinks the pessimistic set	Open; see 6.3
A4	Wash trade, with fees returned to the creator	Raises demand and momentum, up to 30 points	No credit; raises wash share; net buying lowers the score (Proposition 4)	None
A5	Sit just under a threshold	Avoids each cap at 29.9% insiders or 1,001 USDC	No thresholds in any computation	None
A6	Rent liquidity by buying with own wallets	25k USDC appears in a locked pool	The buying wallets hold tokens, so insider loss rises	None
A7	Farm a creator record with one self-pumped launch	10 points on every later launch	Record is shrunk and weighted by public capital at risk	Small
A8	Flip a privilege after buyers enter	Unscored	Priced in advance by worst-case simulation	Code outside the registry gets no floor and an explicit warning that it cannot be checked
A9	Send dust to link a competitor's buyers	Possible where funding precedes a known wallet's purchase	Links need value the wallet acted on	None
A10	Mass-launch tiny tokens to bias base rates	Shifts the base-rate panel	Minimum public inflow for inclusion; grouping by creator cluster	Small
A11	Behave until the horizon passes, then exit	Unscored	Rolling forecasts; unlock dates inside 7 days are priced	Open beyond the longest horizon

The cost of A6 under v1 is the round-trip fee on the rented amount. At the 1% fee tier the launchpads use [3], that is about 500 USDC on 25,000, less wherever fees return to the creator. A4 at thirty wallets and 20 USDC each costs about 12 USDC in fees plus gas. Under v1, a few

hundred USDC of fees can therefore move 45 of 90 points. These are order-of-magnitude figures from the published rules, not measurements.

6.2 Two further propositions

Proposition 4 (no credit for buying pressure). In a constant-product pool, any net purchase of the token from the pool, by anyone, weakly raises the insider loss given event for a fixed insider balance. Holding the forecast probabilities fixed, it weakly lowers the Integrity Score.

Proof. A purchase lowers the pool's token share from g to $g' < g$. By Proposition 1 the post-exit price multiple $(g'/(g' + f))^2$ is increasing in g', so it falls. If the purchaser is in the insider set, f rises as well. The reference recovery after the exit falls in both cases, and the score is non-increasing in that loss (Proposition 3). No feature in Section 5.4 rewards purchases. ■

Pumping the price is self-defeating under v2. This is the formal content of R2.

Proposition 5 (routes to a higher floor). Under method 2.1.0, every action that raises the lower end of the structural floor falls into one of four classes: (a) removing or time-locking a privilege; (b) burning or locking liquidity; (c) burning, locking, selling or genuinely distributing insider tokens; (d) moving insider tokens to addresses that pass the independence test while remaining under common control.

Proof. The floor is the minimum of three recoveries. The tradability recovery rises only if the worst reachable privileged state improves, which is (a). The liquidity recovery rises only if the withdrawable share falls, which is (b). The insider recovery rises only if the pessimistic set's sellable balance falls relative to pool depth. Depth rises relative to that balance only through liquidity that is not withdrawable, which is (b) again, since withdrawable liquidity lowers the liquidity recovery. The balance falls only by burn, lock, sale, transfer, or deposit into a liquidity position. A deposit into a withdrawable position does not lower it: the member withdraws the position before selling (Appendix A.2, step 7), and in the liquidity event its owner sells what it withdraws (step 6). A deposit into a burned or locked position is (b) or (c). A transfer leaves the pessimistic set only if the recipient passes the independence test, which is genuine distribution (c) or aged-wallet control (d). ■

Up to method 2.0.3 the proof had a gap: tokens parked in a withdrawable position fell out of the insider exit, and the liquidity event sold only the reference position, so parking raised the floor without lowering what could be dumped. Method 2.1.0 closes it. Classes (a) to (c) reduce what the adversary can extract over the horizon. They are improvement in the sense of [34]. Class (d) is the only gaming route, and its cost is the cost of manufacturing address history.

6.3 Residual risks

Aged wallets (A3, class d). An organised farm can prepare addresses with months of plausible activity, and on Arc it is cheap. Proposition 2 rests on the history margin alone, because the other two independence conditions are easy to meet: a first purchase after the launch window means buying after 20 blocks, about ten seconds, and the funding condition passes if a direct funder is a hub or if there is no direct funder inside the 12-hour lookback, so funding through a bridge or a day early is enough. The margin itself is a transaction count: at least one transaction 30 days before the token's creation and ten before it. At the gas price observed on 13 October 2026, a farm of 1,000 such wallets needs 10,000 transactions, about 4.2 USDC of gas, and 30 days (Appendix B, S6.3). The regime of Section 8 also ends on its own: from about 16 October 2026, every wallet that transacted in mainnet's first days passes the margin, honest or farmed, so the pessimistic set will stop holding nearly every holder for reasons unrelated to safety, and results on committed records are reported separately before and after that date (Section 7.9). A contract account's transaction count rises only when it

creates contracts, so smart-contract wallets will rarely pass the margin; how common they are among Arc buyers has not been measured. Three countermeasures raise its cost without closing it: the history margin lengthens as Arc matures; co-trading recurrence across launches links wallets that repeatedly appear together; and proceeds that converge on one address link sellers after the fact, which feeds the creator cluster's record for the next launch. The lower and upper bounds are both model inputs, so if aged-wallet attacks become common the fitted weight shifts toward features they cannot move.

Opaque code (A8). Worst-case simulation is only as good as the analysis of what privileged calls can do. Template launchpads make this tractable because hooks and tokens come from a small set of known contracts. Anything else gets no floor and an explicit warning that its code cannot be checked, which is conservative and will be wrong for some honest custom tokens. A side effect of the current registry: every registered template has no swap-affecting privilege and every unregistered one abstains, so the tradability channel cannot fire on a rated launch until a template with privileges is registered.

Long cons (A11). A creator who waits past the longest horizon is outside any forecast the system issues. The score is about a stated window, and the page must say so.

Performative drift. If buyers concentrate on high-score launches, the public USDC in those pools grows, and so does the incentive to exit [35]. The feature "share of public USDC the insiders can extract" tracks this directly, and recalibration on a trailing window follows the shift. The size of the effect is an empirical question that Section 7 measures.

7. Validation protocol

This section is a pre-registration. It fixes hypotheses, data, baselines, metrics and decision rules before any Arc outcome is examined. Because forecasts are committed on-chain before they resolve (Section 10), the validation is prospective by construction.

7.1 Hypotheses

#	Hypothesis	Passes when
H1	The facts layer measures severity	Where an event occurs, realised recovery at the event is within 10 points of the loss computed at the last prior forecast, on average
H2	Channel probabilities are calibrated	Out-of-time calibration slope lies in 0.8 to 1.2 and the intercept interval covers zero, for each channel
H3	The forecasts have skill	Brier skill against the launchpad-by-age base rate is positive, and Brier score is lower than recalibrated v1
H4	Floor grades order risk	Realised mean loss rises monotonically from grade A to grade E

#	Hypothesis	Passes when
H5	The skill label finds skill	Labelled wallets beat the baseline win rate by five points out of sample, with false discoveries at or below 10%
H6	Activity factors add no structural signal	Adding v1's demand and momentum values to the channel models does not lower out-of-time log loss

H6 may fail. If it does, the result is reported, and those factors still stay out of the Integrity Score, because the exclusion rests on manipulability (Proposition 4), not on predictive weakness. That decision is declared here so it cannot be revisited after seeing the data.

7.2 Data and splits

The population is every launch on the six launchpads since mainnet. The unit of analysis is a token at a landmark age: 1 minute, 10 minutes, 1 hour, 6 hours and 24 hours after its first trade [44]. Landmarks stop long-lived tokens from dominating and remove the autocorrelation of block-by-block forecasts.

Splits run forward in calendar time. All tokens from one creator cluster fall in one fold, so that a serial launcher cannot leak between training and test. One full horizon is embargoed between folds [45]. No feature at block h may read state after h, a rule the reproducibility check in Section 10 enforces mechanically.

7.3 Baselines and ablations

Code	Model	Purpose
B0	Event frequency by launchpad and age	The climatological reference for skill scores
B1	v1 score, mapped to probability by isotonic regression on the training fold	The fairest version of the current system
B2	Logistic regression on v1's seven factor values	Tests whether v1's inputs carry signal its weights lose
B3	v2 with address-level holdings in place of entity sets	Value of entity resolution
B4	v2 with raw supply share in place of simulated loss	Value of pool-relative simulation

7.4 Metrics

Accuracy is measured with the Brier and logarithmic scores [23, 25], with Murphy's decomposition reported so that reliability and resolution are visible separately [24]. Calibration is

shown as slope, intercept and reliability diagrams with sampling bands [29, 30]. Discrimination is reported as area under the ROC curve [47] and, because events are imbalanced, under the precision-recall curve [48].

Usefulness is reported as net benefit across decision thresholds [49]. Interval coverage, abstention rate and grade changes per token-hour measure honesty and stability. For the Integrity Score, mean realised structural recovery is compared with the score in each decile.

Models are compared on paired forecast differences, with standard errors clustered by creator cluster [46]. Reporting follows the TRIPOD checklist for prediction models [50].

7.5 Sample-size gates

Stage 1 opens when three counts are met: 2,000 resolved landmark forecasts, 500 distinct creator clusters, and 100 events per channel. The reasoning is as follows.

- Estimating an event frequency in one calibration bin to within 5 points at 95% confidence needs 139 forecasts when the rate is 0.9 and 385 when it is 0.5.
- An ROC area of 0.75 estimated from 2,000 forecasts with 20% prevalence has a 95% half-width of 0.029. From 500 forecasts it is 0.059 [47].
- One hundred events per channel allows about ten events per fitted degree of freedom in a ten-term monotone model.

A launchpad gets its own intercept only after 300 resolved forecasts on it. Before that it uses the pooled estimate and a wider interval.

7.6 Ship and kill criteria

All criteria are evaluated on out-of-time data.

Ship the Integrity Score as headline when all hold:

1. H2 passes for every channel.
2. H3 passes, with the paired Brier difference against B1 significant at the 5% level.
3. Interval coverage is within 3 points of nominal.
4. Each attack A1 to A11, run on a fork or a test launch, fails to raise the score except through class (d) of Proposition 5.
5. Realised mean recovery is within 5 points of the score in at least eight of ten deciles.

Withdraw or hold back when any holds:

1. After 5,000 resolved forecasts the score still fails criterion 2. The probabilities are not published, and the product stays at Stage 0.
2. In any calendar quarter the calibration slope leaves the range 0.6 to 1.5. The display reverts to Stage 0 until recalibrated.
3. H4 fails. The facts layer is then mis-specified, and grades are withdrawn pending revision.

7.7 Sensitivity analyses

Results are re-run with the event thresholds of Section 5.1 moved to (10 points, 30%, 10 USDC) and (30 points, 70%, 30 USDC), with a 1,000 USDC reference position, with funding depth d from 1 to 4, with history margins of 7, 30 and 90 days, and with the chain's first week excluded. A conclusion that reverses under any of these is reported as fragile.

7.8 Deviations from the pre-registration

Sections 7.1 to 7.7 are unchanged from the first version of this paper, written before any Arc outcome was examined. What follows lists every way the work reported in Section 8 departs from them, with the reason. None changes a hypothesis, a baseline or a ship or kill criterion.

- **D1. Retrospective data.** Section 7 assumes forecasts committed before their outcomes. DryDock began committing on 8 October 2026, so the records behind H1 and H4 in Section 8 were recomputed after the fact for launches since 16 September 2026 (the backfill). They were produced by the same code and parameters as committed records, but their outcomes were already on chain when they were computed. They are labelled retrospective everywhere and reported separately from committed records; the pre-registered tests on committed data remain pending.
- **D2. Funding lookback.** Appendix A.1 set 7 days. Public Arc nodes that accept wide log ranges keep about 42 hours of history, and the archive nodes accept 100- to 10,000-block ranges at low rates, so a 7-day, three-hop trace cannot be computed at forecast time and records would not be reproducible from public infrastructure. The lookback is 86,400 blocks (about 12 hours), every edge of a path inside one window ending at the wallet's first purchase.
- **D3. Minimum age.** Appendix A.1 set 120 blocks, glossed as about a minute. Arc produces about 1.97 blocks a second, so every record at the 1-minute landmark was two or three blocks short and could never be rated. The minimum age is 60 seconds of block time.
- **D4. Large insider sets.** Appendix A.2 sells every insider address in turn. Beyond 100 addresses the rest of the set is sold as one block, credited to one seller through a storage override, to stay inside the 50 million gas that public nodes allow per call. In a constant-product pool with retained fees this returns slightly less to the reference position than address-by-address sales would (Appendix B: 10.93 against 10.97 and 30.33 against 30.36), so the approximation errs on the conservative side; in Uniswap V3 and V4, where fees sit outside active liquidity, the two are equal up to rounding.
- **D5. "Value the linked wallet acted on."** Section 5.3 states the principle; the implementation needs a rule. A transfer links two wallets only if it carried at least half of what the recipient then spent on its first purchase or forwarded along the path (Appendix A.3).
- **D6. Address history.** Section 5.3 allows history "on Arc or on another EVM chain". Appendix A.1, which governs, does not; the implementation reads Arc transaction counts only. History on other chains would need archive access to each of them.
- **D7. Population.** Section 7.2 names six launchpads, including Minara. DryDock lists only launchpads whose tokens its swap router can trade; by 8 October 2026 that was lift.fun, Tolly, ArcPad, Argus, Arcora, o1 Launchpad and Sashimi, while Minara's pools pair with native USDC and are not routable. The population is every launch on those seven since 16 September 2026, identified by the launchpad's own contract logs in the creating transaction.
- **D8. Committed means committed in time.** Section 10.2 does not say how late a commitment may be. A record counts as committed only if its root was posted within 1,200 blocks of its forecast block (Appendix A.1). The committer account was not funded when the runner started, so the first batches are posted late and fall outside the scoreboard.
- **D9. v1 baselines without wallet records.** B1 and B2 use v1 as it scored before wallet records loaded, without the smart-money factor: that factor needed 24 hours of every holder's trades across all launches and is not reconstructed for past blocks.
- **D10. Secondary horizons.** Records and resolutions use the 24-hour horizon only. The 1-hour and 7-day horizons are not yet computed.

- **D11. A sample, not the population, for the backfill.** Section 7.2 takes every launch. Insider sets and resolutions need each token's transfers until 48 hours after its first trade, and public nodes filter logs only by address, so reconstructing them for all 78,223 traded launches meant downloading every Transfer log on Arc since mainnet opened (estimated at more than eight hours for the transfer scan alone over the bandwidth available). The backfill therefore uses a fixed sample: every traded launch of each launchpad with at most 3,000 of them, and 3,000 drawn uniformly from each larger launchpad (Argus and lift.fun) by a seeded hash of the token address (`backfillSample` in the released code). The sample was fixed before any record was computed. Results are reported per launchpad, where the sample is uniform; pooled figures weight the smaller launchpads more heavily than the population does, and are labelled as sample figures.
- **D12. Funding stops at contracts.** Section 5.3 ends funding paths at registered hubs only. On Arc, swap routers and pools that are not in the registry (most have no public identification, which the registry requires) receive hundreds of thousands of USDC transfers a day; following their inflows linked a buyer to every other user of the same router and made a single record cost millions of log reads. From method 2.0.2 a path is traced only into accounts without contract code. Wallets funded through one personal contract still share it as an ancestor, and a contract funder fails the history test, so the pessimistic set is unaffected; the lower bound loses the links that ran through contracts.
- **D13. Valuing a held position.** Appendix A.5 as first implemented sold the reference position's tokens, credited by a storage override, into the pool as it stood at the later block. That pool never received the position's own purchase, so on thin launches the sale found almost no USDC (on Argus V5 the hook rejected the partial fill) and the resolution recorded a near-total loss that had not happened. The first run of the backfill used that rule; it was found by checking grade-A records whose launches had no trades after h, which resolved at 0 while their floor was 96. From method 2.0.3 the position is bought at the later block by exact output and sold straight back, and Uniswap V4 tradability reads the pool's positions at the horizon (it had read none). Every record in Section 8 was recomputed under 2.0.3.
- **D14. Only rated records are resolved.** Appendix A.5 resolves every record. Records that abstain carry no floor and no grade, so their outcomes enter no hypothesis, and resolving them costs as many chain reads as resolving a rated one; with 98% of records abstaining, the live resolver could not keep up. Both the backfill and, from 12 October 2026, the live runner resolve rated records only; abstaining records are closed without an outcome. The gate counts of Section 8.4 count rated resolutions only.
- **D15. Amendments after an audit.** An audit of the version of 12 October found that H1 as registered cannot discriminate and that H4 tests a bound; Section 7.9 registers replacement tests (H1′, H4′), creator clustering, launch-level gate counts, a split by history regime, a redefined Integrity Score and method 2.1.0, before any committed record could be scored. Appendix D lists every finding and change.

7.9 Amendments registered before the committed data

Sections 7.1 to 7.7 first appear in a public commit as `2c845fd` of the paper's repository (8 October 2026, 02:12 UTC), two days before the first outcome data were computed; commit times are set by the author's machine and are not independent evidence. They are unchanged here, except that one cross-reference in Section 7.2 follows the later renumbering of Section 9 to Section 10. An audit of the working paper of 12 October found that two of the tests, as registered, could not discriminate (Section 8.4). The amendments below are registered on 13 October 2026, when no record had yet been committed in time (Section 8.6), so no confirmatory data existed. They apply to committed records; on the retrospective records of

Section 8 the original tests stand as reported, and the amended measures are exploratory.

1. **H1′ replaces H1's measure.** For each rated record whose event k fires before its horizon, compare the simulated recovery after event k (the pessimistic set for insider exit) with the realised recovery at the horizon. H1′ passes for channel k when the mean absolute difference is within 10 points and is smaller than that of the friction-only prediction on the same records, with a creator-clustered bootstrap interval for the difference that excludes zero. The original event measure is reported beside it.
2. **H4′ is a test the floor can fail.** H4 stands, reported with the rate at which realised recovery falls below the floor's lower end in each grade. H4′ passes when the floor's lower end orders realised recovery better than baseline B5, defined here: the price multiple since the first trade (the pool price at the forecast block over its price after the first swap), which asks whether the floor adds anything to how far the price has run. It is measured by the difference in Spearman correlations with a creator-clustered bootstrap interval that excludes zero. B4 is reported on the same records.
3. **Clustering and counting.** Every test uses a bootstrap that resamples creators, as Section 7.4 requires; the sample-size gates count launches with an event, not records.
4. **History regime.** From about 16 October 2026 every wallet active in mainnet's first days passes the history margin (Section 6.3). Results on committed records are reported separately for records issued before and after 16 October 2026 00:00 UTC, and by whether the pessimistic set holds every holder.
5. **Definitions.** The Integrity Score is the expected recovery of Section 5.5 as amended (friction applied once; loss given event estimated from outcomes and capped by the simulated worst case). The facts layer is method 2.1.0 from its deployment (tokens parked in withdrawable liquidity count, Proposition 5).

8. Implementation and retrospective results

This section reports what was built and what the data since mainnet opened show. Every number in it is produced by `analysis/results.py` from the released dataset (Appendix C); the records were computed by the same code that issues live records, under method 2.0.3. The records behind Sections 8.2 to 8.5 are retrospective (D1): their outcomes were on chain when they were computed.

8.1 What was built

DryDock runs Stage 0 (Section 5.6). For each launch it issues a record 1 minute, 10 minutes, 1 hour, 6 hours and 24 hours after the first swap, computing the facts layer by `eth_call` simulation at the forecast block with the pool, hook, position managers and token enforcing their own code (Appendix A.2), the two insider sets (Appendix A.3), and the abstentions. Records are batched every 600 blocks under a Merkle root for the ForecastLedger contract (Section 10.2) and resolved after 24 hours (Appendix A.5). The token page shows the floor interval, its grade, friction and the three losses, with later stages shown as gated; v1's number, factors, caps and verdict words are retired, and v1 survives only as the baselines B1 and B2.

The backfill recomputes the same records for past launches. It reads pool events, token transfers and USDC moves from a local store built by scanning public Arc nodes, and everything else (simulation, code, timestamps, transaction counts) from archive nodes at the historical block.

8.2 Population, sample and records

Between 16 September and 7 October 2026 the seven launchpads DryDock lists created 202,944 launches, of which 78,223 traded at least once (Table 8). Argus accounts for 89% of launches. The backfill covers a fixed sample of 9,475 traded launches (D11): every traded launch of Tolly, o1 Launchpad, ArcPad, Arcora and Sashimi, and 3,000 each from Argus and lift.fun. Each received five records, 47,375 in all; none failed to compute and no resolution failed.

Launchpad	Launches	Traded	In the sample	Rated at 24 h
Argus	180,434	56,534	3,000	176
lift.fun	18,285	18,214	3,000	1
Tolly	2,177	1,721	1,721	25
o1 Launchpad	1,872	1,612	1,612	0
ArcPad	164	130	130	0
Arcora	11	11	11	2
Sashimi	1	1	1	0

Table 8. Launches by launchpad, 16 September to 7 October 2026.

Most records abstain. At each landmark 1,745 are unobservable: the o1 Launchpad, ArcPad and Sashimi token contracts have no verified source, so the registry cannot bound them (Section 5.2), and two lift.fun launches used unregistered code. Of the rest, between 58 (1 minute) and 215 (1 hour) are rated and the others are too early. Too early here almost never means too young: at the 24-hour landmark, 7,455 of the 7,526 too-early records have fewer than 10 holders in total and 3,764 have none. Most launches on Arc are bought by a handful of wallets or by nobody, and the method declines to rate them.

Landmark	Rated	Too early	Unobservable
1 minute	58	7,672	1,745
10 minutes	185	7,545	1,745
1 hour	215	7,515	1,745
6 hours	214	7,516	1,745
24 hours	204	7,526	1,745

Table 9. Record states by landmark, sample of 9,475 launches.

8.3 Insider sets on a three-week-old chain

Section 5.3 warned that the pessimistic set would be wide on a young chain. It is wider than wide. The history margin asks for activity 30 days before the token's creation, and every launch in the population was created within 22 days of mainnet opening. Across records, the share of holders that pass the history margin has a median of 0% and a mean of 0.9%. In 63.2% of records the pessimistic set holds every holder, and the median share of holders in it is 100%. The lower-bound set, which needs positive evidence, is much smaller: in the worked example of Section 9.1 it is empty while the pessimistic set holds 65 of 75 holders.

The consequence is that, for now, the lower end of the floor mostly answers the question "what if everyone who holds sold?" That question is the right worst case when no holder can show independence, but it is close to a bound on how far the price can fall, which limits what the test of Section 8.4 can show. The interval will narrow as holders accumulate history; from about 16 October 2026 every wallet active in mainnet's first days passes the margin (Section 6.3).




Figure 4: Mean loss of the 100 USDC reference position 24 hours after the forecast, by grade, over rated retrospective records (H4). Records per grade: A: 474; B: 127; C: 80; D: 84; E: 111. Computed by analysis/results.py from the released dataset.

8.4 Pre-registered tests

The rated records come from 240 launches by 214 creators, and almost all from two launchpads: Argus (204 launches) and Tolly (33), with two Arcora launches and one lift.fun launch. The results below describe those launchpads. Every interval is a 95% interval from a bootstrap that resamples creators, as Section 7.4 requires.

H4 (grades order realised loss): passes, but the test is weak. Over 876 resolved rated records, the mean loss of the reference position after 24 hours rises from 3.5% at grade A to 68.5% at grade E, monotonically (Table 10, Figure 4), and the ordering holds at the 10-minute, 1-hour, 6-hour and 24-hour landmarks taken separately (at 1 minute, 58 records, grades D and E swap). The Spearman correlation between grade rank and loss is 0.71 (0.62 to 0.78). This pass came only after a defect found in outcome data was fixed (D13): under method 2.0.2, the same records order 91.2%, 50.0%, 41.3%, 59.4% and 71.7% from A to E, and H4 fails (Appendix D). The retrospective pass is therefore not confirmatory; the committed record is the confirmatory test.

Grade	Records	Mean loss after 24 h	Severe loss ($\leq$ 20 USDC)	Below the floor by more than 0.5
A	474	3.5%	0.0%	1.7%
B	127	11.1%	0.0%	2.4%
C	80	24.5%	0.0%	7.5%
D	84	51.3%	0.0%	4.8%
E	111	68.5%	63.1%	0.9%

Table 10. Realised loss by grade, rated retrospective records, all landmarks.

The pass says less than it seems, because on Arc today the floor's lower end is close to a hard lower bound on price. In every rated record it equals the pessimistic insider exit, and the tradability and liquidity recoveries equal friction in 99.8% of them, so the floor is a one-channel quantity. The pessimistic set holds every holder in 63% of records (Section 8.3), and Argus, Tolly and lift.fun launch with single-sided liquidity and no USDC (F8), so if every holder sells, the pool returns to roughly its launch state. The lower end therefore measures how far

the price has run up since launch: the median grade-A record has 8 holders, the median grade-E record 181. A bound orders outcomes almost by construction. Realised recovery ended more than half a point below the floor's lower end in 22 of 876 records (2.5%); it ended below it at all in 214, but in 119 of those by less than 0.1 point, which is the bound being reached rather than broken. For the same reason the 0.0% severe-loss rate of grades A to D is mechanical: severe loss means 20 USDC or less, and those grades' floors lie above 20.

Simple proxies come close (Table 11). The USDC the pessimistic set could pull out (the raw insider take) has a Spearman correlation of -0.72 with realised recovery, the pessimistic set's share of supply (B4) -0.70, and the price multiple since the first trade (B5, Section 7.9) -0.67, against 0.79 for the floor's lower end. The floor's margin over B5, the amended test H4′, is 0.12 (0.08 to 0.16) as an exploratory result. What H4 shows is real but narrower than "grades forecast loss": the simulator gets pool arithmetic right, and launches that have run up tend to give the run-up back.

Predictor of recovery after 24 hours	Spearman correlation (95% interval)
Floor's lower end	0.79 (0.70 to 0.86)
USDC the pessimistic set could take	-0.72 (-0.80 to -0.63)
Pessimistic set's share of supply (B4)	-0.70 (-0.77 to -0.61)
Price multiple since the first trade (B5)	-0.67 (-0.75 to -0.57)
v1 score, 7 October rule	-0.48 (-0.56 to -0.40)

Table 11. Each predictor against realised recovery, 876 rated records; intervals resample 214 creators.

v1 was worse than uninformative. Its mean score (7 October rule) is 36 in grade A and 66 in grade E (Table 11 gives its correlation): the higher v1 scored a launch, the more a buyer lost. That is the clearest empirical support for findings F3 to F5, whose activity factors rewarded exactly the run-ups that were then given back.

H1 (the facts layer measures severity): fails, because the registered measure cannot discriminate. Among rated records, 70 launches saw an insider exit after a forecast. At their last prior forecast, the mean absolute difference between the realised recovery at the event and the pessimistic insider-exit recovery is 12.7 points, above the 10-point criterion. The failure is a mis-specified measure, not a near miss. Appendix A.5, step 5, measures recovery only across the block in which the exit crosses half the set's balance; that ratio has a median of 99.0 in these launches, so the test compares roughly 99 with a full-exit simulation, and every error is positive by construction (the smallest is $+1.9$). Predictors that ignore insiders would pass it (Table 12): a constant 99 scores 2.4 and friction alone 3.4, while the pessimistic exit, the one quantity that takes insiders seriously, fails. No tradability or liquidity event occurred, so H1 cannot be tested for those channels.

Prediction of recovery	At the event block (registered measure)	At the horizon
Constant 99	2.4	11.8
Friction alone	3.4	10.0
Lower-bound insider exit	8.0	4.9
Pessimistic insider exit	12.7	2.8

Table 12. Mean absolute error of each prediction for the 70 launches with an insider exit, USDC per 100.

Measured at the horizon instead, the amended test H1′ (Section 7.9), the pessimistic exit is within 2.8 points of realised recovery and beats friction alone by 7.2 points (3.2 to 11.9), as

an exploratory result. Two cautions apply. The comparison conditions on exits that happened (the median pessimistic set sold 76% of its tokens), and 41 of the 70 launches are grade A, where floor and friction nearly coincide. And because the insider-exit event is resolved against the pessimistic set, which today is nearly every holder, an insider exit on Arc is usually just "holders sold half": the ordinary loss of interest that Section 5.1 keeps out of the score.

Sample-size gates (Section 7.5): not met. The backfill holds 876 resolved records (the gate is 2,000) from 240 launches by 214 creators (an upper bound on creator clusters; the gate is 500), and 70 launches with an insider-exit event (127 records; the gate, counted in launches, is 100 per channel), with no tradability or liquidity event. No channel model was fitted. H2, H3 and H6 need one and are not tested; H5 also needs a skill label, which takes 30 days of wallet history to assign and a further 30 days to confirm out of sample (Section 5.8), so its first test cannot come before 15 November 2026, 60 days after mainnet opened.

Baselines, descriptive only. Fitting nothing, the comparisons of Section 7.3 can still be run on the insider channel to show the data's shape, but they support no claim. On an out-of-time split with a one-horizon embargo and unseen creators (286 test records, 17 insider exits), B0's Brier score is 0.059 and v1 recalibrated by isotonic regression (B1) scores 0.075, with an AUC of 0.58. The floor's lower end, which is a severity, not a probability, has an AUC of 0.46 for whether an exit occurs. Severity and likelihood are different things, which is the separation Section 5 rests on.

Grades by launchpad. Among rated records grade A is the most common on Argus (438 of 767, 57%) and Tolly (33 of 96, 34%); Arcora's eight records are mostly E and lift.fun's five are A to C (Table 13). No launchpad has more than 80% of its rated records in one grade.

Launchpad	A	B	C	D	E
Argus	438	102	54	68	105
Tolly	33	22	24	16	1
Arcora	1	1	1	0	5
lift.fun	2	2	1	0	0

Table 13. Rated records by grade and launchpad, all landmarks.

8.5 Exploratory analyses

These were not pre-registered and are reported as exploratory.

H4 net of trading costs. The floor and the realised loss both include the round-trip cost of the reference position. Measuring the horizon recovery against each record's own friction removes that shared part; the ordering survives (0.5%, 6.0%, 20.7%, 49.2% and 67.5% from A to E, with mean friction between 94 and 97 per 100 in every grade). It does not remove the bound discussed in Section 8.4.

Method 2.1.0 on the same records. Counting tokens parked in withdrawable liquidity (Proposition 5) changes the floor of 5 of the 876 rated records and the grade of none; the losses by grade are unchanged (Appendix D).

8.6 The committed record

From its first production record on 8 October 2026 (block 24,825,515) to the dataset's download on 12 October (block 25,607,224), DryDock issued 17,793 records for 4,122 launches and grouped them into 968 batches. Their rated share is close to the backfill's (1.6% against 1.8%), and 98.4% are too early. Their unobservable share is not: 15 records, 0.08%, against 18% in the sample, because the sample takes every o1 Launchpad and ArcPad launch while launches since 8 October are almost all Argus (79%) and lift.fun (21%).

None of them counts yet. The committer account that posts roots to the ForecastLedger has not been funded with the USDC Arc charges for gas, so the ledger is not deployed and no root is on chain. Under the rule that a record counts only if its root lands within 1,200 blocks of its forecast block (Appendix A.1, D8), every record issued so far will stay outside the scoreboard even after funding; the batches will still be posted, in order, so that they remain checkable. The pre-registered tests on committed data therefore start from the first record issued after the ledger is live, and the scoreboard is empty until then.

The committed record also exposed an operating limit. Resolving every record with a reference position cost more chain reads per alarm than the free-tier Worker could spend, and by 12 October the live resolver had fallen about 17,000 records behind; it now resolves rated records only, as the backfill does (D14).

9. Worked examples

The first example is a real launch from the backfill, chosen by a fixed rule before its numbers were read: the first rated 1-hour record, by block, whose insider-exit event fired before its horizon and whose floor is an interval. The second is a hypothetical launch that isolates the arithmetic.

9.1 A real launch

TOLLYTOAD (`0x517b95ae1f8ccafaba3d84eb66e9df007b2ca88a`) was created on Tolly at block 21,087,614, under three hours after mainnet opened, in a Uniswap V3 pool with a 1% fee and no hook. Its first swap came 69 blocks later. The record at the 1-hour landmark (block 21,094,790) reads:

Quantity	Value
Holders	75
Lower-bound insider set	0 holders
Pessimistic insider set	65 holders, whose exit would take 3,294 USDC from the pool
Independent entities outside the lower bound	19
Friction (100 USDC in and out, no event)	98.0
Recovery after tradability or liquidity event	98.0 (no privileged role; liquidity locked)
Recovery after insider exit, lower bound / pessimistic	98.0 / 38.8
Structural floor	38.8 to 98.0 USDC per 100; grade D
v1 score (1 October / 7 October rule)	79 / 80, “Strong setup”

No holder showed evidence of acting with the creator, so the lower bound is empty and its exit costs nothing. 65 of the 75 holders could not show independence (Section 8.3), and if they all sold the position would keep 38.8 of its 100 USDC. v1 called the launch a strong setup.

Over the next 24 hours the pessimistic set sold 96% of its tokens; the insider-exit event fired 111,660 blocks (about 16 hours) after the record. At the horizon the position was worth 39.1 USDC. The floor’s lower end had said 38.8.

The example also shows the weakness of the pre-registered event measure (Section 8.5): in the single block where the outflow crossed half of the set’s balance, the position lost only 3.3%, because most of the exit had already happened in smaller sales.

9.2 An illustrative launch

One hypothetical launch scores 85 to 92 under v1's 1 October rule (86 to 93 under its 7 October rule) and has a structural floor of 11 to 30 USDC per 100 under v2. The launch is constructed for illustration; it is not a real token.

- The pool behaves as a constant-product pool with 25,000 USDC and 10% of token supply, at a 1% fee per swap.
- Liquidity is locked by the launchpad. The token and hook have no privileged roles, and the fee is immutable.
- The creator and two creation-block buyers funded by the creator hold 8% of supply. This is the lower-bound insider set.
- A further 12% sits in fresh wallets funded through a bridge. With the 8%, this is the pessimistic set at 20%.
- The ten largest holders have 30%. More than 30 wallets bought in the last hour, the price is rising, tracked wallets are holding, and the creator has a prior launch that reached 100k USD and is not selling.

Scores.

Quantity	v1	v2
Headline if 8% insiders are detected	92 (1 October rule), 93 (7 October), "Strong setup"	See below
Headline if 20% insiders are detected	85 (1 October rule), 86 (7 October), "Strong setup"	See below
Friction: 100 USDC in and out, no event	Not reported	Returns 98.0
Loss given tradability event	Not reported	2.0% (friction only)
Loss given liquidity event	Not reported	2.0% (friction only)
Loss given insider exit, lower-bound set	Not reported	69.7%; insiders take 11,118 USDC, 44% of the pool's USDC
Loss given insider exit, pessimistic set	Not reported	89.1%; insiders take 16,699 USDC, 67% of the pool's USDC
Structural floor	Not reported	10.9 to 30.3 USDC per 100; grade E

The v1 figures are v1's own scoring rule applied to this launch (F5; Appendix B). The v2 figures follow from the pool arithmetic alone and are reproduced in Appendix B.

Reading the result.

The two systems are not contradicting each other on a prediction. v1 makes none. What v2 adds at Stage 0 is a fact the v1 number hides: a group that may be one party can remove most of a buyer's money in one block, and the pool's lock does not prevent it.

Whether that group will exit is a separate question, and only outcome data can answer it. Suppose the tradability and liquidity probabilities are near zero and the insider-exit probability over 24 hours is π. The Integrity Score (Section 5.5) is then 100 times the friction recovery times one minus π times the loss given an exit, here the simulated worst case net of friction, since no outcomes are yet available; that gives the values below. The π values are assumptions chosen to show the arithmetic.

Assumed π for insider exit	Score with lower-bound loss	Score with pessimistic loss
0.10	91	89
0.30	78	72
0.60	57	46

If Arc data show that insiders in this position rarely exit within a day, the calibrated score will be high and v1's optimism about such launches will have been justified. If they usually exit, it will be low. Either way the number will rest on counted outcomes.

What would raise it.

The creator can raise the floor from 11 to 30 by time-locking the 12% beyond the horizon, and higher still by locking part of the 8%. Wash volume, more wallets or a higher price do nothing, and net buying lowers it (Proposition 4). Under v1 as published the reverse holds: no rule credits a lock, and the wash volume earns up to 30 points.

10. Verifiability and governance

A user should not have to trust the platform's arithmetic or its account of its own accuracy. Both are made checkable.

10.1 A deterministic specification

Every output is a pure function of three inputs: Arc state at a finalized block, a versioned specification, and a versioned registry of hubs, lockers and template contracts. The specification, a reference implementation and the hashes of the parameter and registry files are public. Anyone with an archive node can recompute any score ever shown.

Recomputation also enforces time-consistency. A feature that read state after its block would fail to reproduce from state up to that block.

10.2 Committed forecasts

At fixed intervals the platform posts one transaction to Arc containing the Merkle root of every forecast record issued in that interval. A record holds the token, the block, the horizon, the version hashes, the three losses, the three probability intervals and the score. The page for any token can supply an inclusion proof for the number it displays.

Resolution at the end of the horizon is a deterministic function of chain state. The scoreboard is therefore a function of two public things: the committed forecasts and the chain. This rules out silent revision, selective reporting and accuracy claims assembled in hindsight. It is pre-registration applied to every forecast, and it parallels the launch certificate of [4], which binds a launch's claims before money moves.

A commitment shows that a forecast was made when claimed. It does not show that the forecast was computed correctly. Section 10.1 covers that.

In DryDock's implementation the roots are to go to a ForecastLedger contract on Arc (Appendix A.4), one transaction every 600 blocks. At the time of writing the contract is not deployed and no root is on chain (Section 8.6); the address in Appendix A.4 is precomputed. A record counts as committed only if its root landed within 1,200 blocks of its forecast block; a record posted later is published and resolved like any other but is left out of the scoreboard. The records themselves, their leaves and their resolutions are published by batch, so anyone can recompute every leaf, check every root against the contract, and recompute the scoreboard.

A commitment proves timing. It does not by itself prove completeness or uniqueness, so three rules make those checkable too. *Completeness:* every launch on a listed launchpad receives a record at each landmark it reaches; a verifier enumerates launches from chain state (the launchpads' own contract logs, Appendix C) and checks that every token and landmark has a record, and because the ledger accepts batches only in strict sequence a withheld batch shows as a gap. *Uniqueness:* a token and landmark have exactly one record; the implementation refuses a second, and if two ever appeared in committed batches only the earlier would count. *Versions:* every record carries the model version that produced it, and the scoreboard reports each version separately over its own committed records only, so a shadow version cannot be chosen after its outcomes are seen; a version counts from the first batch that carries it.

10.3 Versioning

A new model version runs in shadow first. Its forecasts are committed but not displayed until at least 1,000 have resolved. It is promoted only if it passes the ship criteria of Section 7.6 against the incumbent. Past forecasts keep the label of the version that issued them, and each change is logged with its reason.

10.4 No discretion

No score is adjusted by hand. Registry entries are the one place where human judgement enters, for example recognising a locker contract or an exchange wallet. Each entry is public, dated and justified, and can be challenged. Errors are corrected in later versions. The committed record is never rewritten.

10.5 Labels on addresses

A public label on a wallet is a statement about a person who cannot reply. The risk page already concedes that attribution errs [2]. Labels should therefore carry their evidence, be phrased as likelihoods, and be withheld below the evidence thresholds of Section 5.8. "Losing trader" serves no reader and should be dropped.

11. Limitations and non-goals

Validation is partial, retrospective and weak. Section 8 tests the two hypotheses that need no fitted model (H1 and H4) on records recomputed after their outcomes (D1). H4 passes, but on today's Arc the floor is close to a bound on price, so the pass is nearly guaranteed, and it came after an outcome-informed fix (D13); H1 fails because its registered measure cannot discriminate. The replacement tests of Section 7.9 apply to committed records, of which none can yet be scored. That v2's probabilities forecast better than v1 remains a hypothesis until a channel model is fitted, which the sample-size gates of Section 7.5 govern; Section 8.4 reports the counts.

The audit was checked against the code afterwards. The first version read only the page. Section 3.3 marks each finding against the v1 source; one conclusion (F1) was wrong and one number (F5) was understated.

Closed forms are illustrations. Propositions 1 and 4 and every numerical example assume a constant-product pool. The launchpads use Uniswap V3 and V4 pools [3, 53, 54]. The same algebra holds wherever liquidity is constant across the price range traversed, as with a single wide position, but magnitudes on real pools must come from simulation.

The pessimistic bound is wide on a young chain. The history margin asks for activity 30 days before a token's creation, and public mainnet opened on 16 September 2026, so for launches before mid-October only addresses active before mainnet opened can pass it. The lower end of the floor can therefore be low for sound launches. The interval is honest about this, and the letter grade may be uninformative until the chain ages (Section 12, objection 2). Section 8.3 measures how wide it is.

Public infrastructure bounds the evidence. The funding lookback is 12 hours, not 7 days (D2), because public Arc nodes keep less history than the design assumed. Funding older than that cannot link wallets, which narrows the lower-bound set; the pessimistic set does not depend on it.

Structural risk is not all risk. A launch with an Integrity Score of 95 can still fall to zero because nobody wants the token. The score measures whether the structure can take a buyer's money, not whether the market will.

Off-chain evidence is excluded. Social activity, team identity and code audits are outside the design. This is deliberate. They cannot be recomputed from chain state (R7).

Independence is assumed in the score formula. Insider exits and liquidity withdrawals may be correlated. The decile check in Section 7.6 detects the resulting error but does not repair it. A joint model is future work.

Code analysis is incomplete. No analyser decides what arbitrary contract code can do. Unknown code gets no floor and a warning that it cannot be checked, which penalises honest custom contracts.

Forecasts are bounded by their horizon. Nothing here speaks to day eight.

Evidence is borrowed from other chains. Most cited findings come from Solana, Ethereum and BNB Chain. Their transfer to Arc, with institutional validators, USDC gas and different launchpads, is assumed, not shown.

This is not advice, and law is out of scope. Publishing forecasts about tradable assets may carry obligations in some jurisdictions. As in [4], we flag the question and do not resolve it.

12. Adversarial self-review

We put eight objections to the paper that a hostile referee would raise. Two of them change the design.

Objection 1. The audit attacks a summary page, not the system. Accepted and resolved: Section 3.3 checks every finding against the v1 source code. Ten of twelve hold; F1's conclusion was wrong because the code normalised the score, and F11 used a slightly different rule than the page described. The page is still what users were told, so its inaccuracies are findings in their own right.

Objection 2. The floor will grade nearly everything E. Accepted as a real risk, and the design is changed. If more than 80% of launches on a launchpad share one Stage 0 grade, the letter is replaced on that launchpad by the floor interval and its percentile rank among launches of the same age. The grade distribution is reported monthly. In the first data the risk did not materialise: among rated records, grade A is the most common on Argus (57%) and Tolly (34%), and no launchpad has more than 80% of its rated records in one grade (Table 13; Arcora's eight rated records are too few to judge).

Objection 3. Dropping demand and momentum discards the best predictors. Speed of accumulation is the strongest predictor of graduation on Pump.fun [10]. Graduation is a different estimand from structural failure. Those variables remain visible in the market panel, H6 measures what the score loses, and the paper accepts that loss in exchange for Proposition 4. A product that forecasts upside is a legitimate separate product with a different threat model.

Objection 4. The event thresholds are as arbitrary as v1's weights. The thresholds define what is forecast. They do not decide whether a forecast was right. A different threshold yields a different, equally testable forecast, and Section 7.7 reports whether conclusions depend on the choice. A weight has no such test.

Objection 5. Calibration cannot hold against adaptive adversaries. Accepted in part. Calibration is a property of a window of past forecasts. Adaptive conformal methods bound long-run miscoverage under shift [32], and the kill criteria revert the display when calibration breaks. The severity layer does not depend on calibration at all, which is why it ships first.

Objection 6. A public specification helps attackers. It does help the aged-wallet attacker, who learns the history margin. The alternative is a score nobody can check, which fails R7 and R8 and the standard of [4]. Proposition 5 shows that the other routes to a better score are routes to a safer launch.

Objection 7. The independence test will exclude honest newcomers and so penalise fair launches. Accepted, and the design is changed. The pessimistic set is never shown alone. Every display carries both ends of the interval, and the forecasting layer, not a rule, decides how much the pessimistic end matters once outcomes exist. On Arc's first three weeks the cost is visible: the pessimistic set holds every holder in 63% of records (Section 8.3).

Objection 8. The author both proposes and evaluates. Accepted. The remedy is structural: forecasts are committed before outcomes, baselines include the strongest version of v1, the data and code are released with this paper (Appendix C), and independent replication is invited. The author also built the implementation, so a defect in it could bias the results in either direction. One did: the first backfill valued held positions against a pool that lacked their own purchase, which made grade A look worst, and it was found and corrected before any result was written (D13). Every record can be recomputed from public chain state with the released code. Citations were checked to the differing degrees stated in the verification note.

13. Conclusion and roadmap

The current score adds things that should not be added, in units that mean nothing, toward a target it does not name. Its most heavily weighted inputs are the ones an insider can buy for a few hundred USDC of fees. None of this is unusual for the category. It is the category's standard, and that is the opportunity.

The replacement rests on one separation. What a launch's structure permits is a fact, computable today from chain state by simulation, with no training data. Whether those who can act will act is a probability, estimable only from outcomes, and publishable only once it is calibrated. Stating the first without waiting for the second gives users a true and useful number now. Committing the second on-chain before it resolves gives them a reason to believe it later.

The design does not solve Sybil identity, and it says so. It bounds what cannot be identified, puts the burden of proof on independence, and enumerates the one remaining route to gaming.

Implementation order and status

1. **Corrections to v1.** Superseded: DryDock retired v1 entirely on 8 October 2026 instead of correcting it. v1 survives only as the baselines B1 and B2 (Appendix C).
2. **Stage 0.** Done on 8 October 2026: the simulator, the two insider sets, the registry and the abstentions are live, and the floor interval with its losses given event is the headline on every token page. Records are issued at the five landmarks, batched for the ForecastLedger and resolved after 24 hours. The ledger is not yet deployed, so no root is

on chain (Section 8.6). *Gates: the ledger live and committing within the deadline; a third party reproduces a sample of published floors from its own archive node. Both open.*

3. **Shadow.** Not started: the sample-size counts of Section 7.5 are not met (876 resolved records, 214 creators, no tradability or liquidity events; Section 8.4), so no channel model is fitted. The scoreboard is built and stays empty until roots are on chain (Section 8.6).
4. **Stage 1.** Pending. *Gate: H2 and H3.*
5. **Stage 2.** Pending. *Gate: all five ship criteria of Section 7.6.*
6. **External review.** Data and code are released with this version and the paper is posted as a working paper. Replication and red-teaming are invited; peer review is pending.

References

[1] DryDock. How the DryDock score works. Updated 1 October 2026. drydockprotocol.org/methodology

[2] DryDock. Risk disclosure. Updated 1 October 2026. drydockprotocol.org/risk

[3] DryDock. Launchpads. drydockprotocol.org/launchpads

[4] F. Ghasemlu. The Verifiable Launch: A Trust-Minimized Protocol for Audit-Gated Token Deployment. Draft of July 2026. drydockprotocol.org/research/verifiable-launch

[5] P. Xia, H. Wang, B. Gao, W. Su, Z. Yu, X. Luo, C. Zhang, X. Xiao, G. Xu. Trade or Trick? Detecting and Characterizing Scam Tokens on Uniswap Decentralized Exchange. Proc. ACM Meas. Anal. Comput. Syst. 5(3), article 39, 2021. doi:10.1145/3491051

[6] B. Mazorra, V. Adan, V. Daza. Do Not Rug on Me: Leveraging Machine Learning Techniques for Automated Scam Detection. Mathematics 10(6):949, 2022. arXiv:2201.07220

[7] F. Cernera, M. La Morgia, A. Mei, F. Sassi. Token Spammers, Rug Pulls, and Sniper Bots: An Analysis of the Ecosystem of Tokens in Ethereum and in the Binance Smart Chain (BNB). USENIX Security 2023. usenix.org

[8] D. Sun, W. Ma, L. Nie, Y. Liu. SoK: Comprehensive Analysis of Rug Pull Causes, Datasets, and Detection Tools in DeFi. 2024. arXiv:2403.16082

[9] M. Naviglio, F. Tarantelli, F. Lillo. Price manipulation schemes of new crypto-tokens in decentralized exchanges. 2025. arXiv:2502.10512

[10] G. Marino, M. Naviglio, F. Tarantelli, F. Lillo. Predicting the success of new crypto-tokens: the Pump.fun case. 2026. arXiv:2602.14860

[11] W. Ding, Y. Luo, J. Xu. Decompose Market Manipulation Strategies: Evidence from On-chain Meme Coin Market. Working paper, Sydney Banking and Financial Stability Conference, 2025. sbfc.sydney.edu.au. Later version with C. Lin as an additional author: SSRN 5953738. papers.ssrn.com

[12] Y. Luo, Y. Feng, J. Xu, Y. Liu. Resisting Manipulative Bots in Meme Coin Copy Trading: A Multi-Agent Approach with Chain-of-Thought Reasoning. 2026. arXiv:2601.08641

[13] A. M. Mongardini, A. Mei. A Midsummer Meme's Dream: Investigating Market Manipulations in the Meme Coin Ecosystem. 2025, revised 2026. arXiv:2507.01963

[14] Solidus Labs. The 2025 Rug Pull Report: Rug Pulls and Pump-and-Dumps on Solana. May 2025. soliduslabs.com. Reported by L. Jakobson, "Alarming" 99% of Memecoin Launches on PumpFun are Pump-and-Dumps or Rug Pulls: Report, The Defiant, 9 May 2025. thedefiant.io

[15] Pine Analytics. Exit Liquidity Machines: Dissecting Pump.fun Farming. 21 April 2025. pineanalytics.substack.com

[16] F. Victor, A. M. Weintraud. Detecting and Quantifying Wash Trading on Decentralized Cryptocurrency Exchanges. The Web Conference 2021, 23–32. doi:10.1145/3442381.3449824

[17] L. W. Cong, X. Li, K. Tang, Y. Yang. Crypto Wash Trading. Management Science 69(11):6427–6454, 2023. doi:10.1287/mnsc.2021.02709

[18] C. F. Torres, M. Steichen, R. State. The Art of the Scam: Demystifying Honeypots in Ethereum Smart Contracts. USENIX Security 2019.

[19] S. Meiklejohn, M. Pomarole, G. Jordan, K. Levchenko, D. McCoy, G. M. Voelker, S. Savage. A Fistful of Bitcoins: Characterizing Payments Among Men with No Names. ACM Internet Measurement Conference 2013, 127–140.

[20] F. Victor. Address Clustering Heuristics for Ethereum. Financial Cryptography and Data Security 2020, Lecture Notes in Computer Science, 617–633. doi:10.1007/978-3-030-51280-4_33

[21] J. R. Douceur. The Sybil Attack. International Workshop on Peer-to-Peer Systems (IPTPS) 2002, Lecture Notes in Computer Science 2429, 251–260.

[22] C. F. Manski. Partial Identification of Probability Distributions. Springer, 2003.

[23] G. W. Brier. Verification of forecasts expressed in terms of probability. Monthly Weather Review 78(1):1–3, 1950.

[24] A. H. Murphy. A new vector partition of the probability score. Journal of Applied Meteorology 12(4):595–600, 1973. doi:10.1175/1520-0450(1973)012<0595:ANVPOT>2.0.CO;2

[25] T. Gneiting, A. E. Raftery. Strictly proper scoring rules, prediction, and estimation. Journal of the American Statistical Association 102(477):359–378, 2007.

[26] J. C. Platt. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. In Advances in Large Margin Classifiers, MIT Press, 2000, 61–74 (chapter listed by the publisher as "Probabilities for SV Machines").

[27] B. Zadrozny, C. Elkan. Transforming classifier scores into accurate multiclass probability estimates. ACM SIGKDD 2002, 694–699.

[28] A. Niculescu-Mizil, R. Caruana. Predicting good probabilities with supervised learning. ICML 2005, 625–632.

[29] B. Van Calster, D. J. McLernon, M. van Smeden, L. Wynants, E. W. Steyerberg. Calibration: the Achilles heel of predictive analytics. BMC Medicine 17:230, 2019.

[30] E. W. Steyerberg et al. Assessing the performance of prediction models: a framework for traditional and novel measures. Epidemiology 21(1):128–138, 2010.

[31] V. Vovk, I. Petej. Venn-Abers predictors. Uncertainty in Artificial Intelligence 2014. arXiv:1211.0025

[32] I. Gibbs, E. Candès. Adaptive conformal inference under distribution shift. Advances in Neural Information Processing Systems 34 (NeurIPS 2021), 1660–1672.

[33] M. Hardt, N. Megiddo, C. Papadimitriou, M. Wootters. Strategic classification. Innovations in Theoretical Computer Science 2016, 111–122.

[34] J. Kleinberg, M. Raghavan. How do classifiers induce agents to invest effort strategically? ACM Transactions on Economics and Computation 8(4), article 19, 2020. doi:10.1145/3417742. Conference version: ACM EC 2019, 825–844; arXiv:1807.05307.

[35] J. C. Perdomo, T. Zrnic, C. Mendler-Dünner, M. Hardt. Performative prediction. ICML 2020.

[36] C. A. E. Goodhart. Problems of monetary management: the U.K. experience. Papers in Monetary Economics, Reserve Bank of Australia, 1975. Reprinted in Monetary Theory and Practice, Macmillan, 1984, 91–121.

[37] M. Nardo, M. Saisana, A. Saltelli, S. Tarantola, A. Hoffmann, E. Giovannini. Handbook on Constructing Composite Indicators: Methodology and User Guide. OECD, 2008.

[38] R. M. Dawes. The robust beauty of improper linear models in decision making. American Psychologist 34(7):571–582, 1979.

[39] L. Barras, O. Scaillet, R. Wermers. False discoveries in mutual fund performance: measuring luck in estimated alphas. Journal of Finance 65(1):179–216, 2010.

[40] E. F. Fama, K. R. French. Luck versus skill in the cross-section of mutual fund returns. Journal of Finance 65(5):1915–1947, 2010.

[41] Y. Benjamini, Y. Hochberg. Controlling the false discovery rate: a practical and powerful approach to multiple testing. Journal of the Royal Statistical Society B 57(1):289–300, 1995.

[42] B. Efron, C. Morris. Data analysis using Stein's estimator and its generalizations. Journal of the American Statistical Association 70(350):311–319, 1975.

[43] D. R. Cox. Regression models and life-tables. Journal of the Royal Statistical Society B 34(2):187–202, 1972.

[44] H. C. van Houwelingen. Dynamic prediction by landmarking in event history analysis. Scandinavian Journal of Statistics 34(1):70–85, 2007.

[45] M. López de Prado. Advances in Financial Machine Learning. Wiley, 2018.

[46] F. X. Diebold, R. S. Mariano. Comparing predictive accuracy. Journal of Business and Economic Statistics 13(3):253–263, 1995.

[47] J. A. Hanley, B. J. McNeil. The meaning and use of the area under a receiver operating characteristic (ROC) curve. Radiology 143(1):29–36, 1982.

[48] T. Saito, M. Rehmsmeier. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. PLoS ONE 10(3):e0118432, 2015.

[49] A. J. Vickers, E. B. Elkin. Decision curve analysis: a novel method for evaluating prediction models. Medical Decision Making 26(6):565–574, 2006.

[50] G. S. Collins, J. B. Reitsma, D. G. Altman, K. G. M. Moons. Transparent reporting of a multivariable prediction model for individual prognosis or diagnosis (TRIPOD). Annals of Internal Medicine 162(1):55–63, 2015.

[51] G. Gigerenzer, U. Hoffrage. How to improve Bayesian reasoning without instruction: frequency formats. Psychological Review 102(4):684–704, 1995.

[52] P. Bolton, X. Freixas, J. Shapiro. The credit ratings game. Journal of Finance 67(1):85–111, 2012. doi:10.1111/j.1540-6261.2011.01708.x

[53] H. Adams, N. Zinsmeister, M. Salem, R. Keefer, D. Robinson. Uniswap v3 Core. Whitepaper, March 2021. uniswap.org/whitepaper-v3.pdf

[54] H. Adams, M. Salem, N. Zinsmeister, S. Reynolds, A. Adams, W. Pote, M. Toda, A. Henshaw, E. Williams, D. Robinson. Uniswap v4 Core. Whitepaper, August 2024. uniswap.org/whitepaper-v4.pdf

[55] G. Angeris, T. Chitra. Improved price oracles: constant function market makers. ACM Advances in Financial Technologies 2020.

[56] M. O. Hill. Diversity and evenness: a unifying notation and its consequences. Ecology 54(2):427–432, 1973.

[57] Arc network facts (mainnet date, USDC gas, block time, finality, opt-in privacy): Stablecoin Insider, "Arc Mainnet Is Live"; Coin360, "Circle Sets September 16 Launch for Arc Mainnet"; Decrypt, "What Is Arc?"

[58] Existing scores: DEXTools, "What Is the DEXT Score? How to Read DEXTools Token Audits"; Solana Tracker, "Token Safety and Rugcheck"

[59] Blockworks. Are 97% of Tokens on Uniswap Really Rug Pulls? 2 November 2022. blockworks.com

[60] A. Gelman, J. Hill. Data Analysis Using Regression and Multilevel/Hierarchical Models. Cambridge University Press, 2007 (published December 2006).

[61] Arc. Arc Mainnet Goes Live on September 16, 2026. 5 August 2026. arc.io blog

[62] Arc documentation. How to: Monitor Blocklist Compliance. Arc docs

Verification note

Every reference was checked on 7 October 2026, and the checks the first version listed as open were completed on 8 October 2026, to the differing degrees listed below. A reader

should weigh them accordingly.

- **Full text fetched and read:** [1] to [4], [6] (the labelling method, Section 6 of the arXiv version), [10], [11] (the conference version), [12], [14] (the Solidus Labs report's web page), [53], [54].
- **Abstract, article or publisher page fetched and read:** [5], [7] to [9], [13], [15], [16], [18], [31], [35], [55], [59], the Stablecoin Insider item of [57], the Solana Tracker item of [58], and the SSRN listing of [11].
- **Bibliographic details matched against a Crossref record (volume, issue and pages as deposited by the publisher):** [17], [19], [21], [24], [25], [26], [27], [28], [29], [30], [33], [34], [36] (the 1984 reprint), [37], [38], [41], [42], [43], [47], [50], [51], [52], [56], [60]. Matched against a Crossref or RePEc record in the first round of checks: [20], [22], [23], [39], [40], [44], [46], [48], [49].
- **Matched against the proceedings publisher's own record:** [32] (NeurIPS proceedings, volume 34, pages 1660 to 1672).
- **Existence, authors, title and venue confirmed by search only:** [45] (a book, cited without pages) and the DEXTools item of [58], whose page appears in search results with the description quoted in Section 2.7 but returned HTTP 404 to a direct request on 8 October 2026.
- **Read only as search excerpts:** the Coin360 and Decrypt items of [57].

The completed checks changed six details. [24] is confirmed. [34] has a journal version, ACM Transactions on Economics and Computation 8(4), 2020. [43] runs to page 202; the first version's 220 included the published discussion. [26] appeared in 2000 at pages 61 to 74, under the chapter title "Probabilities for SV Machines". [14] now cites the Solidus Labs report itself, which gives 98.6% for Pump.fun tokens with at least five trades. [52]: the first version had 85 to 111 and its verification note changed this to 85 to 112 from RePEc; the publisher's Crossref deposit gives 85 to 111, which is restored (the publisher's page refused automated requests). Lookups through OpenAlex, Europe PMC and PubMed were not needed.

Two cautions still apply. [14] is an industry report whose method is described only on its web page. [11] is a working paper whose author list differs between versions: the conference paper cited here lists Ding, Luo and Xu; the later SSRN version adds Chen Lin.

References [61] and [62] were added on 13 October 2026 and read in full that day: [61] confirms the mainnet date, fees payable in USDC and sub-second finality, but states no block time and says nothing about privacy, so those facts still rest on [57]; [62] confirms that the USDC contract reverts transfers from or to blocklisted addresses and that nodes reject a blocklisted sender's transactions.

Appendix A. Normative specification

This appendix fixes the definitions an implementer needs. Where it conflicts with the body, the appendix governs. Every default is subject to the sensitivity analyses of Section 7.7. This is version 2.1.0, the specification DryDock runs; entries marked † changed from the first version of the paper, for the reasons given in Section 7.8. Its keccak-256 hash enters every record as `spec_hash`.

A.1 Constants and defaults

Symbol	Meaning	Default
B	Reference notional	100 USDC; 1,000 USDC for the depth line
H	Horizons	24 hours primary; 1 hour and 7 days secondary
Landmarks	Token ages after the first swap at which forecasts are issued and evaluated	1 min, 10 min, 1 h, 6 h, 24 h; the forecast block is the first block whose timestamp reaches the landmark
δ_T	Recovery drop that defines a tradability event	20 points
λ_L	Share of quote-side liquidity withdrawn that defines a liquidity event	50%
σ_I	Share of the pessimistic set's tokens net-sold that defines an insider exit	50%
Severe loss	All-cause endpoint for the market panel	Reference position returns 20 USDC or less at the horizon
W	Launch window for the independence test	20 blocks, about 10 seconds, as in v1 [1]
d	Funding-path depth for the lower-bound set	3 hops
Funding lookback †	Window before a wallet's first purchase that every edge of its funding path must fall in	86,400 blocks, about 12 hours
Materiality †	A transfer links two wallets only if it carried at least this share of what the recipient then spent (its first purchase) or forwarded (the next edge on the path)	50%
History margin	Minimum address history for independence: transactions sent (nonce) at least 1 at the block 30 days before token creation and at least 10 at the block before creation	30 days and 10 transactions
Dust	Transfers below this never create a link	1 USDC
Minimum evidence †	Below this the state is "too early"	60 seconds of block time since creation, and 10 entities outside the lower-bound set
Interval width	Above this the state is "low confidence"	0.40
Commit interval	Blocks between Merkle-root postings	600 blocks, about 5 minutes

Symbol	Meaning	Default
Commitment deadline †	A record counts as committed only if its root was posted within this many blocks of its forecast block	1,200 blocks
Individual sellers †	Insiders sold one by one in the exit simulation; the rest of a larger set is sold as one block	100
Shadow length	Resolved forecasts before a version can be promoted	1,000

A.2 Simulation of losses

1. Take Arc state at finalized block h. Each scenario is a separate `eth_call` at h (or several scenarios in one call, each isolated in a reverting sub-call), so every scenario starts from the same state.
2. Place the simulator's runtime code, by state override, at a fresh address and at every address that acts in the scenario. Code placed at an address acts as that address: the pool, its hook, the position managers and the token apply their own rules to the real owner.
3. From the fresh address, buy B USDC of the token through its main pool. Record the tokens received, q.
4. **Friction.** Sell q. Record the USDC returned.
5. **Tradability.** For each privileged role in the registry, act as its holder and set each parameter to the worst value the code allows without a timelock longer than H. Sell q, record. If the token or the hook is not a registered template, record zero, set the flag "unbounded" and the state "unobservable"; the display shows this state as a warning that the code cannot be checked, never as a grade. A scenario with no step returns the friction result.
6. **Liquidity.** For each position whose owner is neither burned nor a recognised lock (registry), act as the owner and withdraw it: `decreaseLiquidity` and `collect` for a V3 position NFT, `modifyLiquidities` for a V4 position NFT, `burn` and `collect` or a PoolManager unlock for a direct position. From method 2.1.0 the owner then sells the tokens the withdrawal returned (its balance above what it held before withdrawing), never tokens it already held. Sell q, record.
7. **Insider exit.** For each address in the insider set, in descending order of balance, sell its full balance through the pool. From method 2.1.0 a member that owns a position step 6 would withdraw first withdraws it and then sells everything it holds; such members always sell individually. Beyond the first 100 addresses, credit the remaining balance to one further seller by a storage override of the token's balance mapping and sell it in one block. Sell q, record. Run once for the lower-bound set and once for the pessimistic set.
8. A reverted sale records zero; a reverted event step is recorded as not taken. Each loss given event is 1 minus the recorded amount divided by B. If the purchase in step 3 reverts, the state is "unobservable".

A.3 Entity resolution

1. **Activity.** From the token's transfers up to h: in a transaction with a transfer out of the market (the V3 pool or the V4 PoolManager), wallets whose balance rose purchased; in

one with a transfer into the market, wallets whose balance fell sold; any other rise is an off-market receipt, credited to the transaction's largest sender. Registry hubs, lockers, the hook, the token and burn addresses are infrastructure, not wallets.

2. **Seeds.** The creator, wallets that purchased in the launch block, and recipients of off-market receipts from the creator or a launchpad contract before their first purchase.
3. **Links.** Funding: a USDC transfer of at least 1 USDC from a non-hub sender, inside the recipient's lookback window, carrying at least half of what the recipient then spent or forwarded, traced back up to d hops; the wallet is linked to every ancestor. A path is traced only into accounts without contract code (an EIP-7702 delegation counts as an account): a transfer from a contract links the recipient to the contract, but the contract's own inflows are not followed. Receipts: an off-market receipt before a first purchase links recipient and sender. Proceeds: a USDC transfer of at least 1 USDC to a non-hub address, after a sale, carrying at least half of the sale proceeds so far, links seller and recipient.
4. **Lower-bound set.** Holders at h in a component of the link graph that contains a seed.
5. **Pessimistic set.** The lower-bound set plus every holder that fails any of: the history margin; a first purchase more than W blocks after the launch block; funding that is not only from fresh unlabelled addresses (at least one direct funder is a hub or passes the history margin, or there is no direct funder).
6. **Entities.** Purchasers outside the lower-bound set, grouped by component of the link graph.

A.4 Forecast record and commitment

```
record = {
  token, pool, block_h, landmark, horizon,
  spec_hash, params_hash, registry_hash,
  friction, loss_T, loss_L, loss_I_lower, loss_I_pessimistic,
  floor_low, floor_high,
  pi_T: [low, high], pi_L: [low, high], pi_I: [low, high],
  score: [low, high],
  state,           // rated | too_early | unobservable | low_confidence
  model            // version of the model that issued the probabilities; zero at
  ↪  Stage 0
}
leaf = keccak256(keccak256(abi.encode(record)))
root = merkle_root(all leaves issued since the last root)   // sorted pairs;
↪  posted to the ForecastLedger on Arc
```

Fractions and probabilities are encoded as parts per million and USDC per 100 as micro-USDC per 100, in fixed-width unsigned integers; `0xffffffff` encodes null. At Stage 0 the probability and score fields are null, and the losses and floors are null unless the state is "rated". The same schema is used at every stage, so the committed history is continuous across upgrades. The ForecastLedger's address, `0xC63FA005E73bED90443A1Ffc9e363f573F04Cf23`, is precomputed: it is the committer's first contract creation and has no code until the committer is funded (Section 8.6). The contract stores nothing per batch. `commit(seq, root, firstBlock, lastBlock, records)` is accepted only from the committer and only for the next batch number in sequence, and emits `Committed(seq, root, firstBlock, lastBlock, records)`; the block of commitment is the receipt's block. A verifier reads every commitment from the contract's events and checks that the sequence has no gap.

A.5 Resolution

1. For each record, take the first block e whose timestamp is at least that of h plus H.
2. Insider exit fires at the first transfer in $(h, e]$ at which the pessimistic set's tokens sent to the market or to addresses outside the set, less tokens bought from the market, reach σ_I of its balance at h.
3. Liquidity fires at the first removal in $(h, e]$ at which the quote-side amounts removed by position owners reach λ_L of the quote-side liquidity at h (the V3 pool's USDC balance, or the USDC held by the V4 positions at the pool price).
4. Tradability fires if the reference position cannot be bought and sold at e while the pool still holds quote liquidity (for V4, the USDC held by the pool's positions at e), or if a privileged state change in $(h, e]$ lowers the simulated recovery by δ_T points. No registered template has such a privilege, so only the first route applies to registered templates.
5. The reference position bought at h is valued at a later block by buying the same number of tokens there by exact output and selling them straight back: with the pool's liquidity unchanged, the pool as it would stand had the purchase at h happened is the pool at that block plus the purchase. For each event that fired, value the position at the block before and at the firing block. Their ratio, times 100, is the realised structural recovery.
6. Value the reference position at e. Record severe loss if it returns 20 USDC or less.
7. Publish the resolution with the record. The scoreboard aggregates only records committed within the deadline.

A.6 Reporting checklist

Each scoreboard release states: the specification and registry versions; the date range and count of resolved forecasts by launchpad and landmark; event counts by channel; Brier and logarithmic scores with Murphy components; calibration slope and intercept; reliability diagrams; ROC and precision-recall areas; interval coverage; abstention rate by reason; grade distribution by launchpad; and every comparison against B0 and B1 with its interval.

Appendix B. Reproducibility

The script below reproduces every number in the paper that is computed rather than measured. It needs Python 3 with numpy and scipy and reads no data. It is `appendix_b.py` in the paper's repository, and its output is kept beside it as `analysis/output/appendix_b.txt`. The empirical numbers of Section 8 come from `analysis/results.py` and the released dataset (Appendix C).

```
# Reproduces every number computed in the paper other than the empirical results
↪  of Section 8, which
# come from analysis/ and the released dataset. Requires Python 3 with numpy and
↪  scipy; reads no data.
import numpy as np
from scipy import stats

# --- Section 3, F1 and F3: v1 weights as published, and the normalisation the
↪  implementation applied
w = dict(insider=15, top10=10, creator=10, liquidity=15, demand=20, momentum=10,
↪  smart=10)
tot = sum(w.values())
print('F1 sum of published weights:', tot)
print('F1 share of attainable needed for the top band if the score were a plain
↪  sum: %.1f%%' % (100 * 70 / tot))
```

```
# The code (DryDock v1, 1 October 2026) scored points over the points attainable,
↪  scaled to 100. Smart money
# counted only when wallet records had loaded, so the attainable total was 80 or
↪  90; on 7 October a
# trading-costs factor (5) was added, giving 85 or 95.
for label, attainable, activity in (('1 Oct, no wallet records', 80, 30), ('1
↪  Oct, wallet records', 90, 40),
                                    ('7 Oct, no wallet records', 85, 30), ('7
                                    ↪  Oct, wallet records', 95, 40)):
    print('F1 %s: attainable %d, top band needs 70%% of it; F3 activity share
    ↪  %.1f%%' % (label, attainable, 100 * activity / attainable))

# --- Section 3, F5 and Section 9: the worked example under v1's real rule
def scale(v, bad, good):
    return min(1, max(0, (v - bad) / (good - bad)))
def v1_points(insider, top10, version):
    # Linear between endpoints (verified in the code); holders >= 25 so the 7
    ↪  October breadth discount is 1.
    p = 15 * scale(insider, .30, .03) + 10 * scale(top10, .50, .15)
    p += 10                                     # creator: an earlier launch
    ↪  reached $100k
    p += 10 * scale(np.log10(25000), np.log10(500), np.log10(25000)) + 5   #
    ↪  depth 25k USDC; custody held by the launchpad
    p += 10 + 5 + 5                             # buyers >= 30, buy pressure >=
    ↪  65%, organic volume
    p += 10                                     # momentum at full marks
    p += 10                                     # smart money: three winning
    ↪  wallets holding, no snipers
    attainable = 90
    if version == '7 Oct':
        p += 5                                  # trading costs: 1% pool fee each
        ↪  way plus the 0.5% swap fee, under 3%
        attainable = 95
    return p, attainable
for version in ('1 Oct', '7 Oct'):
    for ins in (0.08, 0.20):
        p, a = v1_points(ins, .30, version)
        print('F5 v1 (%s) with measured insider share %.0f%%: %.2f of %d points,
        ↪  score %d' % (version, 100 * ins, p, a, round(100 * p / a)))
# F7: the cliff at the 30% insider cap (1 October code, wallet records loaded)
for ins in (0.299, 0.301):
    p, a = v1_points(ins, .30, '1 Oct')
    print('F7 insider share %.1f%%: score %d' % (100 * ins, 30 if ins > .30 else
    ↪  round(100 * p / a)))
# What the first version of the paper computed by assuming a plain sum of the
↪  published weights:
lin = lambda v, full, zero, pts: pts * min(1, max(0, (zero - v) / (zero - full)))
for ins in (0.08, 0.20):
    print('F5 plain-sum reading of the published page, insider share %.0f%%: %.1f'
          % (100 * ins, lin(ins, .03, .30, 15) + lin(.30, .15, .50, 10) + 10 + 15
          ↪  + 20 + 10 + 10))

# --- Section 3, F6 (Proposition 1): constant-product exit impact
for g in (.10, .20, .40):
    for f in (.15, .20, .30):
        print('P1 g=%.2f f=%.2f price drop %.0f%%, quote drained %.0f%%'
              % (g, f, 100 * (1 - (g / (g + f)) ** 2), 100 * f / (g + f)))
    print('P1 g=%.2f insider share giving an 80%% drop: %.1f%%' % (g, 100 * g *
    ↪  (1 / np.sqrt(.2) - 1)))

# --- Section 3, F11: v1's "profitable trader" label under a no-skill null. The
↪  code required at least 55%
```

```
# of launches won (P&L marked to the current price) and more than $10 ahead; the
↪  page said "more than half".
ns = (5, 10, 15, 20, 30, 40, 50)
for q in (.30, .35, .40):
    print('F11 page rule q=%.2f' % q, ['n=%d: %.3f' % (n, stats.binom.sf(n // 2,
    ↪  n, q)) for n in ns])
    print('F11 code rule q=%.2f' % q, ['n=%d: %.3f' % (n,
    ↪  stats.binom.sf(int(np.ceil(.55 * n)) - 1, n, q)) for n in ns])

# --- Section 5.8: shrinkage rule, Beta prior mean .35 weight 20, label iff P(q >
↪  .40 | data) > .95
q0, m = .35, 20
for n in ns:
    k = np.arange(n + 1)
    ok = k[stats.beta.sf(q0 + .05, q0 * m + k, (1 - q0) * m + n - k) > .95]
    if len(ok) == 0:
        print('S5.8 n=%d: cannot qualify' % n)
        continue
    kmin = ok.min()
    print('S5.8 n=%d: needs %d wins; false positive %.4f; power at q=.60 %.3f'
          % (n, kmin, stats.binom.sf(kmin - 1, n, q0), stats.binom.sf(kmin - 1,
          ↪  n, .6)))

# --- Section 9.2: v2 facts for the stylised example (constant product, fee
↪  retained in the pool)
x0, g, phi, B, S = 25000.0, 0.10, 0.01, 100.0, 1e9
def buy(x, y, usd):
    a = usd * (1 - phi); out = y * a / (x + a); return out, x + usd, y - out
def sell(x, y, tok):
    a = tok * (1 - phi); out = x * a / (y + a); return out, x - out, y + tok
q, x1, y1 = buy(x0, g * S, B)
rho0 = sell(x1, y1, q)[0]
print('S9.2 friction: 100 USDC returns %.1f' % rho0)
for name, f in (('lower-bound set, 8%', .08), ('pessimistic set, 20%', .20)):
    got, x2, y2 = sell(x1, y1, f * S)
    r = sell(x2, y2, q)[0]
    print('S9.2 insider exit as one block, %s: insiders take %.0f USDC (%.0f%% of
    ↪  pool); reference returns %.1f; loss %.1f%%'
          % (name, got, 100 * got / x1, r, 100 - r))
    # Integrity Score as amended (Section 5.5): friction once, and before any
    ↪  outcomes the loss given event is the
    # simulated worst case net of friction, 1 - r / rho0.
    for pi in (.10, .30, .60):
        print('   assumed pi=%.2f -> Integrity Score %.0f' % (pi, rho0 * (1 - pi
        ↪  * (1 - r / rho0))))
# Appendix A.2 sells address by address, largest first. With the split of Section
↪  9.2 (creator 4%, two
# launch-block buyers 2% each; six fresh wallets 2% each) and fees retained in
↪  the pool:
for name, parts in (('lower-bound set', [.04, .02, .02]), ('pessimistic set',
↪  [.04, .02, .02] + [.02] * 6)):
    x, y = x1, y1
    for f in sorted(parts, reverse=True):
        _, x, y = sell(x, y, f * S)
    print('S9.2 insider exit address by address, %s: reference returns %.2f' %
    ↪  (name, sell(x, y, q)[0]))
# Uniswap V3 and V4 keep fees outside active liquidity; with fees outside the
↪  pool the same example gives:
def sell_ext(x, y, tok):
    a = tok * (1 - phi); out = x * a / (y + a); return out, x - out, y + a
def buy_ext(x, y, usd):
    a = usd * (1 - phi); out = y * a / (x + a); return out, x + a, y - out
q2, xa, ya = buy_ext(x0, g * S, B)
```

```
print('S9.2 fees outside the pool: friction %.1f' % sell_ext(xa, ya, q2)[0])
for f in (.08, .20):
    _, xb, yb = sell_ext(xa, ya, f * S)
    print('S9.2 fees outside the pool, exit of %.0f%%: reference returns %.1f' %
    ↪  (100 * f, sell_ext(xb, yb, q2)[0]))

# --- Section 7.5: sample sizes
z = stats.norm.ppf(.975)
for p in (.5, .9):
    print('S7.5 bin rate %.1f to within 5 points: n=%d' % (p, int(np.ceil(z * z *
    ↪  p * (1 - p) / .05 ** 2))))
def se_auc(A, n1, n0):  # Hanley and McNeil (1982)
    Q1, Q2 = A / (2 - A), 2 * A * A / (1 + A)
    return np.sqrt((A * (1 - A) + (n1 - 1) * (Q1 - A * A) + (n0 - 1) * (Q2 - A *
    ↪  A)) / (n1 * n0))
for N in (500, 2000):
    print('S7.5 AUC 0.75, N=%d, prevalence 0.2: 95%% half-width %.3f' % (N, z *
    ↪  se_auc(.75, int(.2 * N), N - int(.2 * N))))

# --- Section 6.3: cost of an aged-wallet farm (gaming class (d), audit finding
↪  M1). A wallet passes the history
# margin with at least one transaction 30 days before the token's creation and at
↪  least ten before it, so each
# farm wallet needs ten transactions it sends itself. Gas price observed on Arc
↪  on 13 October 2026 (eth_gasPrice).
GAS_PRICE_GWEI, TRANSFER_GAS = 20, 21_000
per_tx = TRANSFER_GAS * GAS_PRICE_GWEI * 1e9 / 1e18  # USDC (Arc's gas token, 18
↪  decimals)
for wallets in (100, 1000):
    print('S6.3 aged-wallet farm of %d wallets: %d transactions, %.2f USDC of
    ↪  gas, ready 30 days after its first transaction'
          % (wallets, 10 * wallets, 10 * wallets * per_tx))
```

Appendix C. Data, code and v1

Availability. The dataset is deposited at Harvard Dataverse under CC BY 4.0: Ghasemlu, F. (2026), *Calibrated Launch Integrity: Forecast Records for Token Launches on Arc, 2026*, https://doi.org/10.7910/DVN/ROY5A4. The code is released under the MIT License at https://github.com/DryDockOrg/launch-integrity-paper, at the tag named in the dataset's description (this version: `v2026-10-13`); the paper is released under CC BY 4.0.

The paper's repository holds the Markdown and LaTeX editions, the figures' sources, `appendix_b.py`, the analysis code (`analysis/`) with its output, and the dataset (`data/`): every launch on the covered launchpads since 16 September 2026 with whether it traded, every retrospective record with its facts, resolution and v1 scores, and every committed record published at the time of writing. The code that produced the records is a snapshot of DryDock's `lib/integrity` (the facts layer, records and resolver), `scripts/integrity` (discovery, the backfill store and runner) and `scripts/integrity/baselines/v1.ts` (v1's assessment as it ran on 1 and on 7 October 2026, kept runnable for the baselines B1 and B2), copied to `code/` with some identifiers renamed and the RPC endpoints moved to configuration. The folder holds method 2.1.0; the 2.0.3 code that produced the records of Section 8 is the same folder at tag `v2026-10-12`, and recomputing 30 published records with it reproduces every record hash and resolution exactly (`code/README.md`). `data/method-versions.csv.gz` holds the rated records recomputed under 2.0.2 and 2.1.0 (Table D2). The retrospective records were produced by the same functions that issue live records; only the source of logs differs (a local store built from public Arc nodes instead of the nodes themselves).

Appendix D. Response to the audit of 13 October 2026

An audit of the working paper of 12 October re-ran Appendix B's script and the analysis code from the released repository, matched every number to the digit, and ran its own analysis of the records. It reported four critical findings, six major ones and thirteen errata. Table D1 lists what this version changed for each; its numbers all reproduce from the released data, except that tradability and liquidity equal friction in 99.8% of rated records, not 100%.

Finding	What changed
C1. H4 tests a bound, not a forecast	Section 8.4 reports the bound-breach rate per grade, the proxies B4, B5 and the raw insider take with clustered intervals, and the floor's margin over B5; H4′ registered (Section 7.9)
C2. H1 cannot discriminate	H1 restated as a mis-specified measure, with the comparators of Table 12; H1′ registered (Section 7.9)
C3. The retrospective H4 is not confirmatory	The abstract and Section 8.4 say the pass followed an outcome-informed fix; Table D2 gives the 2.0.2 result; the pre-registration's first public commit is cited (Section 7.9)
C4. Verifiability described as live	Abstract, Sections 10.2 and 13 and Appendix A.4 describe the ledger as not yet deployed; Section 10.2 adds completeness, uniqueness and version rules; the ledger is now event-only with a strict batch sequence; the site's verification no longer passes a proof whose root is not on Arc
M1. Aged wallets are cheap	Section 6.3 prices the attack (Appendix B, S6.3) and states the regime change from 16 October; results split by regime registered (Section 7.9); contract-wallet nonces noted, not measured
M2. Parking tokens in liquidity raises the floor	Method 2.1.0 (Appendix A.2, steps 6 and 7); Proposition 5 restated; 5 retrospective floors change, no grade (Table D2)
M3. Unverified code abstains silently	Body and appendix aligned; such launches are shown with an explicit warning that their code cannot be checked
M4. The Integrity Score multiplies mismatched quantities	Score redefined with friction applied once and loss given event estimated from outcomes (Section 5.5), registered (Section 7.9)
M5. Repeated records treated as independent	Creator-clustered intervals throughout Section 8.4; gate events counted in launches; results stated for Argus and Tolly
M6. v1's anti-correlation unreported	Reported in Section 8.4 and Table 11

Finding	What changed
Errata	Section 9.2's v1 scores (92 and 85, or 93 and 86); D4's direction; D11's count; Section 1.4's range; the abstract's 99%; Section 8.6's mix; Objection 2's table (Table 13); friction as a recovery (Section 5.2); unbounded code (Sections 5.2, 5.6, 6.1, 6.3, 11); H5's 60 days; reference [18] cited; Arc facts and the blocklist cited to Arc's own pages [61, 62]; Appendix B's labels

Method	Records rated	A	B	C	D	E	Monotone
2.0.2 (before D13's fix)	876	91.2%	50.0%	41.3%	59.4%	71.7%	No
2.0.3 (Section 8)	876	3.5%	11.1%	24.5%	51.3%	68.5%	Yes
2.1.0 (parked liquidity counted)	876	3.5%	11.1%	24.5%	51.3%	68.5%	Yes

Table D2. Mean realised loss after 24 hours by grade, for the same rated records under three method versions, computed with each version's code (the method-versions file in the dataset). 2.0.2 changes no floor or grade, only the valuation of the held position; 2.1.0 changes 5 floors and no grade.