

Shell Scripting 2

Joseph Hallett

January 12, 2023



Last time

We introduced shell scripting as a tool for automating stuff

- ▶ Gave a basic overview of syntax
- ▶ Mentioned `env` and `shellcheck`

This time

- ▶ More syntax and control flow
- ▶ Variables and techniques
As before I'll try and keep to POSIX shell and mark where things are Bashisms...
 - ▶ but some Bash-isms are useful to know

Variables

All programs have variables... Shell languages are no different:

To **create** a variable:

```
GREETING="Hello World!"
```

(No spaces around the =)

To **use** a variable

```
echo "${GREETING}"
```

If you want your variable to exist in the programs you start as an *environment variable*:

```
export GREETING
```

To **get rid of** a variable

```
unset GREETING
```

Well...

Variables in shell languages *tend* to act more like **macro variables**.

- ▶ There's no penalty for using one that's not defined.

```
NAME='Joe'
unset NAME
echo "Hello, '${NAME}'"
Hello, ''
```

If this bothers you:

```
set -o nounset
echo "${NAME:? variable 1 passed to program}"
```

(There are a *bunch* of these shell parameter expansion tricks beyond `:?` which can do search and replace, string length and various magic...)

Standard variables

`${0}` Name of the script

`${1}`, `${2}`, `${3}`... Arguments passed to your script

`${#}` The number of arguments passed to your script

`${@}` and `${*}` All the arguments

Control flow

If statements and *for* loops, with *globbing*, are available:

```
# Or [ -x myscript.sh ];  
# Or [[ -x myscript.sh ]]; if using Bash  
if test -x myscript.sh; then  
    ./myscript.sh  
fi
```

```
for file in *.py; do  
    python "${file}"  
done
```

Other loops

Well...okay you only have for really... but you can do other things with it:

```
for n in 1 2 3 4 5; do
    echo -n "${n} "
done
```

1 2 3 4 5

```
seq 5
```

1 2 3 4 5

```
for n in $(seq 5); do
    echo -n "${n} "
done
```

1 2 3 4 5

```
seq -s, 5
```

1,2,3,4,5

```
# IFS = In Field Separator
IFS=','
```

```
for n in $(seq -s, 5); do
    echo -n "${n} "
done
```

1 2 3 4 5

Case statements too!

```
3 # Remove everything upto the last / from ${SHELL}
case "${SHELL##*/}" in
    bash) echo "I'm using bash!" ;;
    zsh)  echo "Ooh fancy a zsh user!" ;;
    fish) echo "Something's fishy!" ;;
    *)    echo "Ooh something else!" ;;
esac
```


Basefilename and Dirname

In the previous example I used the `"${VAR##*/}"` trick to remove everything up to the last /... Which gives you the name of the file neatly...
...but I have to look this up everytime I use it.
Instead we can use `$(basename "${shell}")` to get the same info.

```
echo "${SHELL}"  
echo "${SHELL##*/}"  
echo "$(basename "${SHELL}")"  
echo "$(dirname "${SHELL}")"
```

You can even use it to remove *file extensions*:

```
for f in *.jpg; do  
    convert "${f}" "$(basename "${f}" .jpg).png"  
done
```

Pipelines

As part of shell scripting, it's often useful to build commands out of chains of other commands. For example I can use `ps` to list all the processes on my computer and `grep` to search.

- How many processes is `Firefox` using?

```
ps -A | grep -i firefox
```

43172	??	SpU	0:10.69	/usr/local/bin/firefox		
59551	??	Sp	0:00.06	/usr/local/lib/firefox/firefox	-contentproc	-appDir
7023	??	SpU	0:06.10	/usr/local/lib/firefox/firefox	-contentproc	{a032331
59478	??	SpU	0:00.21	/usr/local/lib/firefox/firefox	-contentproc	{3cd651d
47320	??	SpU	0:00.60	/usr/local/lib/firefox/firefox	-contentproc	{50d5261
26734	??	SpU	0:00.18	/usr/local/lib/firefox/firefox	-contentproc	{68aa722
308	??	SpU	0:00.16	/usr/local/lib/firefox/firefox	-contentproc	{bd6ff5f
42479	??	SpU	0:00.14	/usr/local/lib/firefox/firefox	-contentproc	{d874750
45572	??	Rp/2	0:00.00	grep	-i	firefox

Too much info!

Lets use the awk command to cut it to just the first and fifth columns!

```
ps -A | grep -i firefox | awk '{print $1, $5}'
```

```
43172  /usr/local/bin/firefox
59551  /usr/local/lib/firefox/firefox
7023   /usr/local/lib/firefox/firefox
59478  /usr/local/lib/firefox/firefox
47320  /usr/local/lib/firefox/firefox
26734  /usr/local/lib/firefox/firefox
308    /usr/local/lib/firefox/firefox
42479  /usr/local/lib/firefox/firefox
5634   grep
```

Why is grep in there?

Oh yes... when we search for *firefox* we create a new process with *firefox* in its commandline.
Lets drop the last line

```
ps -A | grep -i firefox | awk '{print $1, $5}' | ghead -n -1
```

```
43172 /usr/local/bin/firefox
59551 /usr/local/lib/firefox/firefox
7023 /usr/local/lib/firefox/firefox
59478 /usr/local/lib/firefox/firefox
47320 /usr/local/lib/firefox/firefox
26734 /usr/local/lib/firefox/firefox
308 /usr/local/lib/firefox/firefox
42479 /usr/local/lib/firefox/firefox
```

And really I'd just like a count of the number of processes

```
ps -A | grep -i firefox | awk '{print $1, $5}' | ghead -n -1 | wc -l
```

8

Other piping techniques

- ▶ The `|` pipe copies standard output to standard input...
- ▶ The `>` pipe copies standard output to a named file... (e.g. `ps -A >processes.txt`, see also the `tee` command)
- ▶ The `>>` pipe appends standard output to a named file...
- ▶ The `<` pipe reads a file into standard input... (e.g. `grep firefox <processes.txt`)
- ▶ The `<<<` pipe takes a string and places it on standard input
- ▶ You can even copy and merge streams if you know their file descriptors (e.g. appending `2>&1` to a command will run it with standard error merged into standard output)

Wrap up

Go forth and shell script!

What we covered

- ▶ Variable expansions
- ▶ Common control flow statements
- ▶ Different pipe tricks



Software Tools

Good Programming is not learned from
generatives, but by seeing how significant
programs can be made clean, easy to read,
easy to maintain and modify, human-
engineered, efficient, and reliable by the
application of common sense and good
programming practices. Careful study
and emulation of good programs
leads to better writing.

Kernighan
Plauger