



planetmath.org

Math for the people, by the people.

PID and UFD are equivalent in a Dedekind domain

Canonical name	PIDAndUFDAreEquivalentInADedekindDomain
Date of creation	2013-03-22 17:53:45
Last modified on	2013-03-22 17:53:45
Owner	rm50 (10146)
Last modified by	rm50 (10146)
Numerical id	7
Author	rm50 (10146)
Entry type	Theorem
Classification	msc 16D25
Classification	msc 13G05
Classification	msc 13A15
Classification	msc 11N80

This article shows that if A is a Dedekind domain, then A is a UFD if and only if it is a PID. Note that this result implies the more specific result given in the article unique factorization and ideals in ring of integers.

Since any PID is a UFD, we need only prove the other direction. So assume A is a UFD, let \mathfrak{p} be a nonzero (proper) prime ideal, and choose $0 \neq x \in \mathfrak{p}$. Note that x is a nonunit since \mathfrak{p} is a proper ideal. Since A is a UFD, we may write x uniquely (up to units) as $x = p_1^{a_1} \cdots p_k^{a_k}$ where the p_i are distinct irreducibles in A , the a_i are positive integers, and $k > 0$ since x is not a unit. Since \mathfrak{p} is prime and $x \in \mathfrak{p}$, it follows that some p_i , say p_1 , is in \mathfrak{p} . Then $(p_1) \subset \mathfrak{p}$. But (p_1) is prime since clearly in a UFD any ideal generated by an irreducible is prime. Since A is Dedekind and thus has Krull dimension 1, it must be that $(p_1) = \mathfrak{p}$ and thus \mathfrak{p} is principal.