



Documentation for dsek-typst

The D-guild within TLTH

Company registration number: 845003-2878

September 28, 2026



Contents

1	Plain document / Dokument	3
2	Statutes / Stadgar	5
3	Regulations / Reglemente	7
4	Strategic Goals / Strategiska mål	9
5	Policy	11
6	Guideline / Riktlinje	14
7	Agenda / Föredragningslista	17
8	Minutes / Protokoll	20
9	Notice / Kallelse	24
10	Board response / Styrelsens svar	27
11	Consideration / Handling	29
12	Motion	31
13	Proposal / Proposition	33
14	Requirements profile / Kravprofil	35
15	Nomination / Valförslag	38
16	Plan of operations / Verksamhetsplan	41
17	Equal treatment plan / Likabehandlingsplan	43



1 Plain document / Dokument

[Source code](#)

plain-document

Base document wrapper that applies the guild document styling.

All document-type functions in this library apply `plain-document` internally. Use this template directly only when no specialised document type fits.

Sets up page geometry, header/footer, fonts (Domitian serif body, TeX Gyre Heros sans-serif headings), heading numbering, link colours, and the resolution list formatter. Renders title as a styled document title above the content.

Parameters

```
plain-document(  
  body: content,  
  title: str content,  
  meeting: str content,  
  doc-type: str,  
  lang: str,  
  date: datetime,  
  use-cover-page: boolean  
) -> content
```

body `content`

The body of the document.

title `str` or `content`

The title of the document.

Default: `none`

meeting `str` or `content`

The meeting for which the document was written, e.g. "HTM1".

Default: `none`

doc-type `str`

Document "type" label, shown in the page header.

Default: `" "`



lang `str`

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

use-cover-page `boolean`

Whether to display the document title on a separate cover page instead of as a non-numbered heading

Default: `false`

dokument

Swedish binding for plain-document



2 Statutes / Stadgar

Source code

statutes

Creates the guild statutes (stadgar) document. Apply with `#show: stadgar.with(...)` or `#show: statutes.with(...)`.

Notes

- Terms blocks (`/ Term: Description`) are formatted as a §-numbered 3-column table.
 - The §-number combines the current heading section and the term's index within the block (e.g. §1.2 for the second term under `= Sektionen`).

Example

`#show: stadgar`

`= Sektionen`

`/ Namn:`

Sektionens namn är D-sektionen.

`/ Ändamål:`

Föreningens ändamål och syfte är att diskutera Policy för val.

Parameters

```
statutes(  
  body: content,  
  lang: str,  
  date: datetime  
) -> content
```

body `content`

The body of the document.

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"

date `datetime`

The date at which the document was written.

Default: `datetime.today()`



stadgar

Swedish binding for statutes



3 Regulations / Reglemente

Source code

regulations

Creates the guild regulations (reglemente) document. Apply with `#show: reglemente.with(...)` or `#show: regulations.with(...)`.

Notes

- Terms blocks (`/ Term: Description`) are formatted as a 2-column table (term, description).

Example

`#show: reglemente`

`= Teknologia`

`/ Råsa:`

En lämplig tolkning av råsa är `_Pepto-Bismol_`.

`/ Rosa Pantern:`

Med Rosa Pantern åsyftas den drink som skapas med mjölk, grenadin och sockerlag.

`/ Råsa Digitalis:`

Råsa, fast digitaliskt.

Parameters

```
regulations(  
  body: content,  
  lang: str,  
  date: datetime  
) -> content
```

body `content`

The body of the document.

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"

date `datetime`

The date at which the document was written.

Default: `datetime.today()`



reglemente

Swedish binding for regulations

4 Strategic Goals / Strategiska mål

Source code

strategic-goals

Creates a strategic goals (strategiska mål) document. Apply with `#show: strategiska-mål.with(...)` or `#show: strategic-goals.with(...)`.

Notes

- The document begins with an “Översikt” / “Overview” section containing the summary, purpose, scope, and a revision history table. A page break separates the Overview section from the body.

Example

```
#show: strategiska-mål.with(  
  summary: [De strategiska målen är mål som är strategiska.],  
  purpose: [  
    Syftet med de strategiska målen är göra styrelsens arbete lite jobbigare.  
  ],  
  scope: [Hela D-sektionens verksamhet.],  
  history: (  
    (  
      meeting: "HTM2 2021",  
      change: "Ursprungligen antagen",  
      who: "Framtidsutskottet 2021",  
    ),  
  ),  
)
```

= Mål

== Korrigera benämning av de strategiska målen (2026--2028)

I dagsläget är det tydligen ingen som vet vad det här dokumentet faktiskt heter, utan i folkmun kallas det av outgrundliga skäl fortfarande för "den strategiska planen".

- Få folk att kalla de strategiska målen för de strategiska målen.

Parameters

```
strategic-goals(  
  body: content,  
  summary: content,  
  purpose: content,  
  scope: content,  
  history: array,  
  date: datetime,  
  lang: str  
) -> content
```



body content

The body of the document.

summary content

Description of what this document covers.

Default: none

purpose content

Why this document exists.

Default: none

scope content

Who or what this document applies to.

Default: none

history array

Modification history. Each entry is a dict with required keys `meeting`, `change`, and `who`.

Default: `()`

date datetime

The date at which the document was written.

Default: `datetime.today()`

lang str

The language of the document (same format as `text.lang`). Only `"sv"` and `"en"` are supported.

Default: "sv"

strategiska-mål

Swedish binding for strategic-goals



5 Policy

Source code

policy

Creates a policy document. Apply with `#show: policy.with(...)`.

Notes

- The document begins with an "Översikt" / "Overview" section containing the summary, purpose, scope, and a revision history table. A page break separates the Overview section from the body.

Example

```
#show: policy.with(  
  subject: "ekonomi", // title becomes "Policy för ekonomi"  
  summary: [Policyn beskriver hur ekonomin på sektionen ska skötas.],  
  purpose: [Syftet med denna policy är att se till att vi inte bryter lagen.],  
  scope: [Sektionen i sin helhet. Men mest Skattmästeriet.],  
  history: (  
    (  
      meeting: "VTM-extra 2022",  
      change: [Tog bort kapitlet om "kreativ bokföring"],  
      who: "Styrelsen genom Truls Teknolog",  
    ),  
  ),  
)
```

= Sektionsbil

```
// highlight to show diff  
Sektionsbilen är i särklass sektionens #remove[mest]#add[minst] värdefulla ägodel.
```

= Bokslut

Bokslut måste lämnas in senast när Skattmästaren känner för det.

Parameters

```
policy(  
  body: content,  
  subject: content,  
  summary: content,  
  purpose: content,  
  scope: content,  
  history: array,  
  date: datetime,  
  lang: str,  
  use-cover-page: bool  
) -> content
```



body content

The body of the document.

subject content

The subject of the policy, e.g. "Val" or "Tackverksamhet".

Default: none

summary content

Description of what this document covers.

Default: none

purpose content

Why this document exists.

Default: none

scope content

Who or what this document applies to.

Default: none

history array

Modification history. Each entry is a dict with required keys `meeting`, `change`, and `who`.

Default: `()`

date datetime

The date at which the document was written.

Default: `datetime.today()`

lang str

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"



use-cover-page `bool`

Whether to render the title on a separate cover page instead of a heading.

Default: `false`



6 Guideline / Riktlinje

Source code

guideline

Creates a guideline (riktlinje) document. Apply with `#show: riktlinje.with(...)` or `#show: guideline.with(...)`.

Notes

- The document begins with an “Översikt” / “Overview” section containing the summary, purpose, scope, and a revision history table. A page break separates the Overview section from the body.

Example

```
#show: riktlinje.with(  
  subject: "sektionsbilens användning", // title becomes "Riktlinje för  
sektionsbilens användning"  
  summary: [Riktlinjen beskriver hur man inte är en trafikfara.],  
  purpose: [Syftet med denna riktlinje är att undvika ännu ett VTM-extra.],  
  scope: [Alla på sektionen som har körkort.],  
  history: (  
    (  
      meeting: "S14 2024",  
      change: "Uppdaterade bilens registreringsnummer",  
      who: "Styrelsen genom Truls Teknolog",  
    ),  
  ),  
)
```

= Hastigheter

Bilen får inte köras i över 80 km/h. Inte för att det är olagligt, utan för att motorn inte klarar av det.

Parameters

```
guideline(  
  body: content,  
  subject: str,  
  summary: content,  
  purpose: content,  
  scope: content,  
  history: array,  
  date: datetime,  
  lang: str,  
  use-cover-page: bool  
) -> content
```

body `content`

The body of the document.



subject `str`

The subject of the guideline, e.g. "Grafisk design" or "Överlämning".

Default: `none`

summary `content`

A description of what this document covers.

Default: `none`

purpose `content`

Why this document exists.

Default: `none`

scope `content`

Who or what this document applies to.

Default: `none`

history `array`

Modification history. Each entry is a dict with required keys `meeting`, `change`, and `who`.

Default: `()`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`



use-cover-page bool

Whether to render the title on a separate cover page instead of a heading.

Default: false

riktlinje

Swedish binding for guideline.



7 Agenda / Föredragningslista

Source code

agenda

Creates an agenda (föredragningslista) document. Apply with `#show: föredragningslista.with(...)` or `#show: agenda.with(...)`.

Notes

- The body should include a numbered list using bracket syntax: - [Action] Item name. The action label (e.g. Beslut, Information) goes inside the brackets; leave the brackets empty for no action (e.g. for OFMÖ / OFMA). If any item does not begin with brackets, the whole list is left unformatted (no error).
- Links attached to an item (using `+ #link("link.com")` in a sublist to an item) are collected into the Annex / Bilaga column and numbered in order of appearance. Referring to the same link more than once gives it the same number. A link written with a custom label (display text different from the URL) is shown as-is and is not numbered.

Example

```
#show: föredragningslista.with(
  meeting: "HTM1",
  time: date(15, 3, 2026, time: (17, 15)),
  authors: (
    (name: "Truls Teknolog", position: strings.otherpos.talman),
  ),
)

- [] TFMÖ // [] = no action label
- [Sång] Sektionshymn
+ #link("https://dsek.se/hymn")[Text] // link shown in Annex / Bilaga column
with label "Text"
- [Beslut] Val av justerare
- [Information] Ekonomisk status
+ #link("https://dsek.se/rambudget") // numbered: 1
+ #link("https://dsek.se/detaljbudget") // numbered: 2
- [Beslut] Motion: Jag tycker sektionen borde ha Financial Times
+ #link("https://dsek.se/rambudget") // numbered: 1 (same link)
- [] TFMA
```

Parameters

```
agenda(
  body: content,
  meeting: str content,
  time: datetime,
  meeting-type: content auto,
  authors: array,
  date: datetime,
  lang: str
) -> content
```



body `content`

The body of the document.

meeting `str` or `content`

The meeting which the agenda outlines, e.g. "HTM1".

Default: `none`

time `datetime`

Meeting date and time. Use `date()`, e.g. `date(15, 3, 2025, time: (13, 0))`.

Default: `none`

meeting-type `content` or `auto`

The type of meeting, e.g. "Styrelsemöte" or "Studierådsmöte". If set to `auto`, the meeting type is detected from the `meeting` parameter – `SXX` gives "Styrelsemöte" and `SRDXX` gives "Studierådsmöte" (where `X` is a digit).

Default: `auto`

authors `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`



föredragningslista

Swedish binding for agenda



8 Minutes / Protokoll

Source code

minutes

Creates a meeting minutes (protokoll) document. Apply with `#show: protokoll.with(...)` or `#show: minutes.with(...)`.

Notes

- The body uses / **Term**: description syntax where each term is an agenda item title and the description is the item text. Inside an item, term items are formatted normally.
- Items are automatically numbered as §1, §2, ... and can be cross-referenced with `@item` (resolves to "§N") or `@item[]` (resolves to "§N Item").
- Attendees are auto-labelled so they can be referenced with `@name` or `@name[]` (to include position) anywhere in the document.

Example:

```
#show: protokoll.with(  
  meeting: "S06",  
  attendees: (  
    ("Truls Teknolog", styr.ordf),  
    ("Trula Teknolog", infu.ansv),  
    ("Råsa Pantern", "Sektionsmaskot", (from: [@tid-och-sätt], to: [@val-av-  
justerare])),  
    "Pelle Postlös", // name only, no position  
  ),  
  attested: false, // default; set to true to remove watermark  
  chair: [@trulsteknolog],  
  secretary: [@trulateknolog],  
  reviewers: ([@pellepostlös],), // one or more  
)  
  
/ OFMÖ:  
  @trulsteknolog[] förklarade mötet öppnat 12:15. // Ordförande Truls Teknolog  
förklarade...  
  
/ Tid och sätt:  
  Tid och sätt godkändes.  
  
/ Val av justerare:  
  Mötet beslöt  
  - att välja @pellepostlös till justerare // *att* välja Pelle Postlös till...  
  
/ Information från kollegierna:  
  / InfoK: Ingen ny information. // normal terms  
  
/ Veckans roliga punkt:  
  @trulateknolog drog en ordvits.  
  
/ Uppföljning\ Veckans roliga punkt:
```



@pellepostlös yrkade på
- att stryka @veckans-roliga-punkt från protokollet
Mötet avslög yrkandet.

@trulateknolog yrkade på
- att ålliga @pellepostlös att "komma på något bättre själv då" med uppföljning
till nästa styrelsemöte.
Mötet biföll yrkandet.

/ **OFMA:**

@trulsteknolog förklarade mötet avslutat 12:18

Efter mötet såg beslutsuppföljningslistan ut enligt följande:

```
#followup(  
  ("S03", [Hitta den försvunna sektiondiamanten], [Råsa Pantern], "HTM1"),  
  ("S06", [Kom på en bättre ordvits än Trula], [@pellepostlös], "S07"),  
)
```

Parameters

```
minutes(  
  body: content,  
  meeting: str content,  
  attendees: array,  
  chair: content,  
  secretary: content,  
  reviewers: array,  
  meeting-type: content auto,  
  attested: bool,  
  lang: str,  
  date: datetime  
) -> content
```

body content

The body of the document.

meeting str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none

attendees array

Attendee list. Each entry is a name string/content, or a 2-element (name, position) array. Positions can be entered manually or taken from the strings module.

Default: ()



chair `content`

Meeting chair, shown in the signature block.

Default: `none`

secretary `content`

Meeting secretary, shown in the signature block.

Default: `none`

reviewers `array`

Optional minute reviewers, shown in the signature block.

Default: `()`

meeting-type `content` or `auto`

The type of meeting, e.g. "Styrelsemöte" or "Studierådsmöte". If set to auto, the meeting type is detected from the the meeting parameter – SXX gives "Styrelsemöte" and SRDXX gives "Studierådsmöte" (where X is a digit).

Default: `auto`

attested `bool`

Shows "OJUSTERAT"/"UNATTESTED" watermark when false.

Default: `false`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`



protokoll

Swedish binding for minutes



9 Notice / Kallelse

Source code

notice

Creates a meeting notice/summons (kallelse) document. Apply with `#show:`
`kallelse.with(...)` or `#show: notice.with(...)`.

Notes

- A "Tid och plats" / "Time and location" block is automatically prepended to the body.
- The body can include either free-form text or a numbered list using bracket syntax - [Action] Item name similar to the agenda function.
 - The action label (e.g. Beslut, Information) goes inside the brackets; leave the brackets empty for no action (e.g. for OFMÖ / OFMA). If any item does not begin with brackets, the whole list is left unformatted (no error).
 - Links attached to an item (using `+ #link("link.com")` in a sublist to an item) are collected into the Annex / Bilaga column and numbered in order of appearance. Referring to the same link more than once gives it the same number. A link written with a custom label (display text different from the URL) is shown as-is and is not numbered.

Example

```
#show: kallelse.with(  
  meeting: "S05",  
  time: date(15, 3, 2025, time: (13, 0)),  
  location: [E:A, LTH],  
  authors: (  
    // position defaults to "Sektionsmedlem" / "Guild member",  
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"  
    (name: "Truls Teknolog", position: styr.ordf),  
  ),  
)
```

Kära Sektionsmedlemmar,

idag har vi den stora äran att än en gång få kalla er till sektionmöte.
Tyvärr räckte inte budgeten till fika, men vi hoppas att ni kommer ändå.

```
- [] OFMÖ // [] = no action label  
- [Sång] Sektionshymn  
  + #link("https://dsek.se/hymn")[Text] // link shown in Bilaga / Annex column  
with label Text  
- [Beslut] Val av justerare  
- [Information] Ekonomisk status  
  + #link("https://dsek.se/rambudget") // numbered: 1  
  + #link("https://dsek.se/detaljbudget") // numbered: 2  
- [Beslut] Motion: Jag tycker sektionen borde ha Financial Times  
  + #link("https://dsek.se/rambudget") // numbered: 1 (same link)  
- [] OFMA
```



Parameters

```
notice(  
    body: content,  
    meeting: str content,  
    authors: array,  
    time: datetime,  
    location: str content,  
    adjournment: datetime dict,  
    meeting-type: content auto,  
    lang: str,  
    date: datetime  
) -> content
```

body content

The body of the document.

meeting str or content

The meeting for which the document was written, e.g. "HTML".

Default: none

authors array

Signatories. Each signatory dict must have at least the key name, optionally message, position and signature.

Default: ()

time datetime

Meeting date and time. Use date(), e.g. date(15, 3, 2025, time: (13, 0)).

Default: none

location str or content

Meeting venue, e.g. [E:1124].

Default: none

adjournment datetime or dict

Optional planned adjournment, shown in the time/location block. Either a date(...) or a dictionary (date: date(...), location: [...]).

Default: none



meeting-type `content` or `auto`

The type of meeting, e.g. "Styrelsemöte" or "Studierådsmöte". If set to auto, the meeting type is detected from the the meeting parameter – SXX gives "Styrelsemöte" and SRDXX gives "Studierådsmöte" (where X is a digit).

Default: `auto`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

kallelse

Swedish binding for notice



10 Board response / Styrelsens svar

Source code

board-response

Creates a board response (styrelsens svar) document. Apply with **#show:** styrelsens-svar.**with(...)** or **#show:** board-response.**with(...)**.

Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

Example

```
#show: styrelsens-svar.with(  
  title: [3.0 flugor i en smäll],  
  meeting: "HTM1",  
  // position defaults to "Sektionsmedlem" / "Guild member",  
  // message defaults to "Lund, dag som ovan" / "Lund, day as above"  
  authors: (  
    (name: "Truls Teknolog", position: strings.styr.ordf),  
    (name: "Trula Teknolog", message: "För styrelsen"),  
  )  
)
```

#emoji.thumb.up

Styrelsen yrkar på // extra space is inserted before this paragraph automatically
- att bifalla motionen i sin helhet // becomes: *att* bifalla...

Parameters

```
board-response(  
  body: content,  
  title: content,  
  meeting: str content,  
  authors: array,  
  lang: str,  
  date: datetime  
) -> content
```

body content

The body of the document.

title content

The title of the motion being responded to.

Default: none



meeting `str` or `content`

The meeting for which the motion and response were written, e.g. "HTM1".

Default: `none`

authors `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

styrelsens-svar

Swedish binding for board-response



11 Consideration / Handling

Source code

consideration

Creates a consideration (handling) document. Apply with `#show: handling.with(...)` or `#show: consideration.with(...)`.

Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

Example

```
#show: handling.with(  
  title: [3.0 flugor i en smäll],  
  meeting: "HTM1",  
  authors: (  
    // position defaults to "Sektionsmedlem" / "Guild member",  
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"  
    (name: "Truls Teknolog", position: aktu.dsportare),  
    (name: "Trula Teknolog", message: "gaming"),  
  ),  
)
```

= Bakgrund

Geekend är ett väldigt uppskattat event. Senast slog vi rekord med 247 sittande. Jag är inte helt säker på hur vi fick plats, men kul var det.

= Sammanfattning

Geekend är kul, så vi vill ha mer Geekend

Aktivitetsutskottet yrkar på // extra space is inserted before this paragraph automatically

- att införa ett månadslångt Geekend // becomes: *att* införa...

Parameters

```
consideration(  
  body: content,  
  title: content,  
  meeting: str content,  
  authors: array,  
  lang: str,  
  date: datetime  
) -> content
```



body `content`

The body of the document.

title `content`

The title of the consideration.

Default: `none`

meeting `str` or `content`

The meeting for which the document was written, e.g. "HTML".

Default: `none`

authors `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

handling

Swedish binding for consideration



12 Motion

Source code

motion

Creates a motion document. Apply with `#show: motion.with(...)`.

Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

Example

```
#show: motion.with(  
  title: [Uppdatering av Policy för ekonomi],  
  meeting: "S23",  
  // position defaults to "Sektionsmedlem" / "Guild member",  
  // message defaults to "Lund, dag som ovan" / "Lund, day as above"  
  authors: (  
    (name: "Truls Teknolog", position: km.mastare),  
    (name: "Trula Teknolog", message: "För uppdaterad information"),  
  )  
)
```

Vi har bytt sektionsbil (igen), så policy för ekonomi bör reflektera detta.

Vi yrkar på // extra space is inserted before this paragraph automatically
- att uppdatera "Policy för ekonomi" enligt bilaga // becomes: *att* uppdatera...

Parameters

```
motion(  
  body: content,  
  title: content,  
  meeting: str content,  
  authors: array,  
  lang: str,  
  date: datetime  
) -> content
```

body `content`

The body of the document.

title `content`

The title of the motion.

Default: `none`



meeting `str` or `content`

The meeting for which the motion was written, e.g. "HTM1".

Default: `none`

authors `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`



13 Proposal / Proposition

Source code

proposal

Creates a proposal (proposition) document. Apply with `#show: proposition.with(...)` or `#show: proposal.with(...)`.

Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

Example

```
#show: proposition.with(  
  title: [Budgetrevidering],  
  meeting: "VTM-Extra",  
  authors: (  
    // position defaults to "Sektionsmedlem" / "Guild member",  
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"  
    (name: "Truls Teknolog", position: styr.ordf),  
    (name: "Trula Teknolog", message: "För styrelsen"),  
  ),  
)
```

= Bakgrund

vi är broke :(

= Förslag

Styrelsen yrkar på // extra space is inserted before this paragraph automatically
- att avskaffa sektionen // becomes: *att* avskaffa...

Parameters

```
proposal(  
  body: content,  
  title: content,  
  meeting: str content,  
  authors: array,  
  lang: str,  
  date: datetime  
) -> content
```

body content

The body of the document.



title `content`

The title of the proposal.

Default: `none`

meeting `str` or `content`

The meeting for which the proposal was written, e.g. "HTM1".

Default: `none`

authors `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`

proposition

Swedish binding for proposal



14 Requirements profile / Kravprofil

Source code

requirements-profile

Creates a requirements profile (kravprofil) for an elected position. Apply with `#show: kravprofil.with(...)` or `#show: requirements-profile.with(...)`.

Notes

- A mandate-period row is rendered first, then the body as a preamble, and finally the requirements and merits as a two-column bullet list.
- The mandate period defaults to the full calendar year of year (Jan 1 – Dec 31) when mandate is left at its default auto.

Example

```
#show: requirements-profile.with(  
  position: strings.styr.ordf, // or a plain string: "Ordförande"  
  requirements: (  
    "Godkänd i B2",  
  ),  
  merits: (  
    "Erfarenhet av projektledning",  
    "Tidigare ordföranderoll i studentförening",  
  ),  
  year: 2025,  
  mandate: ( // set to `auto` or omit for default of jan 1 – dec 31  
    from: date(1, 7, 2026),  
    to: date(30, 6, 2027),  
  ),  
)
```

Ordförande leder sektionens styrelse och representerar sektionen utåt.

Parameters

```
requirements-profile(  
  body: content,  
  position: str content,  
  requirements: array,  
  merits: array,  
  mandate: dictionary auto,  
  year: int,  
  lang: str,  
  date: datetime  
) -> content
```

body content

The body of the document.



position `str` or `content`

The position title, e.g. "Vice ordförande" or `strings.medalj.mdlm`.

Default: `none`

requirements `array`

Mandatory requirements (strings or content).

Default: `()`

merits `array`

Meritorious qualifications.

Default: `()`

mandate `dictionary` or `auto`

Mandate period as (from: datetime, to: datetime). Set to auto to use the full calendar year given by year.

Default: `auto`

year `int`

Calendar year used when mandate: auto.

Default: `datetime.today().year()`

lang `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

date `datetime`

The date at which the document was written.

Default: `datetime.today()`



kravprofil

Swedish binding for requirements-profile



15 Nomination / Valförslag

Source code

nomination-proposal

Creates a nomination proposal (valförslag) document. Apply with `#show: valförslag.with(...)` or `#show: nomination-proposal.with(...)`.

- Candidates are grouped by position via the candidates dictionary and laid out in two columns. Free-form content (headings, paragraphs) can be mixed in below them.
- Author signatures are appended automatically.

Example

```
#show: nomination-proposal.with(  
  title: "Nomineringar till Presidiet",  
  meeting: "S23",  
  candidates: (  
    "Ordförande": "Trula Teknolog",  
    "Vice Ordförande": "Truls Teknolog",  
    "posten Posten": (  
      "J. Doe",  
      "Nomen Nescio",  
      "[REDACTED]",  
    ),  
  ),  
  authors: (  
    // position defaults to "Sektionsmedlem" / "Guild member",  
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"  
    (name: "Råsa Pantern", position: valb.ordf),  
  ),  
  stats: (  
    "Ordförande": [0 -- 4],  
    "Vice Ordförande": [5 -- 9],  
    "posten Posten": [250 -- 254],  
  ),  
)
```

Dessa personer gjorde bättre ifrån sig på sina intervjuer än någon annan.

```
// extra space is inserted before this paragraph automatically  
Med hänvisning till den utförliga motivationen ovan yrkar jag därmed på  
- att välja in dessa tjommar till respektive post // becomes: *att* välja...
```



Parameters

```
nomination-proposal(  
  body: content,  
  title: content,  
  meeting: str content,  
  authors: array,  
  candidates: dict,  
  stats: dict none,  
  lang: str,  
  date: datetime  
) -> content
```

body content

The body of the document.

title content

The title of the document, e.g. [Nominering till HTM1].

Default: none

meeting str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none

authors array

Signatories. Each signatory dict must have at least the key name, optionally message, position and signature.

Default: ()

candidates dict

Positions mapped to a nominee or a list of nominees, e.g. ("Ordförande": "Trula Teknolog", "Vice Ordförande": ("Truls", "Trula")).

Default: none



stats dict or none

Optional applicant counts per position, rendered as a “Valstatistik” / “Selection statistics” appendix. Keys must match candidates.

Default: none

lang str

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: “sv”

date datetime

The date at which the document was written.

Default: `datetime.today()`

valförslag

Swedish binding for nomination-proposal



16 Plan of operations / Verksamhetsplan

Source code

plan-of-operations

Creates a plan of operations (verksamhetsplan) document. Apply with `#show: verksamhetsplan.with(...)` or `#show: plan-of-operations.with(...)`.

Notes

- The document begins with a pre-filled “Översikt” / “Overview” section containing subsections summary, purpose, structure, responsibility, and reporting. A page break separates the Overview section from the body.
 - The different sections can be overridden using the `overview-overrides` parameter.

Example

```
#show: plan-of-operations // `Overview` section inserted automatically
```

= Mål från de strategiska målen

== Korrigera benämning av de strategiska målen

För att säkerställa att målet uppfylls tänker vi ta i med hårdhandskarna.

- Be jättesnällt för annars blir vi ledsna i ögat :(

Parameters

```
plan-of-operations(  
  body: content,  
  year: int,  
  overview-overrides: dict,  
  lang: str,  
  date: datetime  
) -> content
```

body `content`

The body of the document.

year `int`

The year for which the plan was written. Defaults to next year.

Default: `datetime.today().year() + 1`



overview-overrides dict

A dictionary of overrides in the Overview section. Available keys are summary, purpose, structure, responsibility and reporting.

Default: (:)

lang str

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: “sv”

date datetime

The date at which the document was written.

Default: `datetime.today()`

verksamhetsplan

Swedish binding for plan-of-operations



17 Equal treatment plan / Likabehandlingsplan

Source code

equal-treatment-plan

Creates an Equal treatment plan (likabehandlingsplan) document. Apply with **#show:** `likabehandlingsplan.with(...)` or **#show:** `equal-treatment-plan.with(...)`.

Example

```
#show: likabehandlingsplan.with(  
  committee: km.name,  
  meeting: [S21],  
)
```

Vi ska verka för att alla ska få lika mycket köttfärssås på Snickerboa.

Parameters

```
equal-treatment-plan(  
  body: content,  
  committee: str content,  
  meeting: str content,  
  date: datetime,  
  lang: str  
) -> content
```

body content

The body of the document.

committee str or content

The committee the plan applies to.

Default: none

meeting str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none

date datetime

The date at which the document was written.

Default: `datetime.today()`



lang `str`

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: `"sv"`

likabehandlingsplan

Swedish binding for equal-treatment-plan