



# **Documentation for dsek**

**The D-guild within TLTH**

**Company registration number: 845003-2878**

October 5, 2026



## Contents

|    |                                            |    |
|----|--------------------------------------------|----|
| 1  | Plain document / Dokument                  | 3  |
| 2  | Statutes / Stadgar                         | 5  |
| 3  | Regulations / Reglemente                   | 7  |
| 4  | Strategic Goals / Strategiska mål          | 9  |
| 5  | Policy                                     | 11 |
| 6  | Guideline / Riktlinje                      | 14 |
| 7  | Agenda / Föredragningslista                | 17 |
| 8  | Minutes / Protokoll                        | 20 |
| 9  | Notice / Kallelse                          | 24 |
| 10 | Board response / Styrelsens svar           | 27 |
| 11 | Consideration / Handling                   | 29 |
| 12 | Motion                                     | 31 |
| 13 | Proposal / Proposition                     | 33 |
| 14 | Requirements profile / Kravprofil          | 35 |
| 15 | Nomination / Valförslag                    | 38 |
| 16 | Plan of operations / Verksamhetsplan       | 41 |
| 17 | Equal treatment plan / Likabehandlingsplan | 43 |



# 1 Plain document / Dokument

Source code

## plain-document

Base document wrapper that applies the guild document styling.

All document-type functions in this library apply `plain-document` internally. Use this template directly only when no specialised document type fits.

Sets up page geometry, header/footer, fonts (Domitian serif body, TeX Gyre Heros sans-serif headings), heading numbering, link colours, and the resolution list formatter. Renders title as a styled document title above the content.

### Parameters

```
plain-document(  
  body: content,  
  title: str content,  
  meeting: str content,  
  doc-type: str,  
  lang: str,  
  date: datetime,  
  use-cover-page: boolean  
) -> content
```

**body** content

The body of the document.

**title** str or content

The title of the document.

Default: none

**meeting** str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none

**doc-type** str

Document "type" label, shown in the page header.

Default: ""



**lang**    `str`

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: `"sv"`

**date**    `datetime`

The date at which the document was written.

Default: `datetime.today()`

**use-cover-page**    `boolean`

Whether to display the document title on a separate cover page instead of as a non-numbered heading

Default: `false`

## dokument

Swedish binding for plain-document



## 2 Statutes / Stadgar

### Source code

### statutes

Creates the guild statutes (stadgar) document. Apply with `#show: stadgar.with(...)` or `#show: statutes.with(...)`.

### Notes

- Terms blocks (`/ Term: Description`) are formatted as a §-numbered 3-column table.
  - The §-number combines the current heading section and the term's index within the block (e.g. §1.2 for the second term under `= Sektionen`).

### Example

```
#import "@preview/dsek:0.1.0": *
```

```
#show: stadgar
```

```
= Sektionen
```

```
/ Namn:  
Sektionens namn är D-sektionen.
```

```
/ Ändamål:  
Föreningens ändamål och syfte är att diskutera Policy för val.
```

### Parameters

```
statutes(  
  body: content,  
  lang: str,  
  date: datetime  
) -> content
```

**body** `content`

The body of the document.

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"



**date**    `datetime`

The date at which the document was written.

Default: `datetime.today()`

## **stadgar**

Swedish binding for statutes



### 3 Regulations / Reglemente

[Source code](#)

#### regulations

Creates the guild regulations (reglemente) document. Apply with **#show:** `reglemente.with(...)` or **#show:** `regulations.with(...)`.

#### Notes

- Terms blocks (**/ Term:** Description) are formatted as a 2-column table (term, description).

#### Example

```
#import "@preview/dsek:0.1.0": *
```

```
#show: reglemente
```

```
= Teknologia
```

```
/ Råsa:  
En lämplig tolkning av råsa är _Pepto-Bismol_.
```

```
/ Rosa Pantern:  
Med Rosa Pantern åsyftas den drink som skapas med mjölk, grenadin och sockerlag.
```

```
/ Råsa Digitalis:  
Råsa, fast digitaliskt.
```

#### Parameters

```
regulations(  
  body: content,  
  lang: str,  
  date: datetime  
) -> content
```

**body**    `content`

The body of the document.

**lang**    `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"



**date**    `datetime`

The date at which the document was written.

Default: `datetime.today()`

## **reglemente**

Swedish binding for regulations



## 4 Strategic Goals / Strategiska mål

Source code

### strategic-goals

Creates a strategic goals (strategiska mål) document. Apply with `#show: strategiska-mål.with(...)` or `#show: strategic-goals.with(...)`.

#### Notes

- The document begins with an “Översikt” / “Overview” section containing the summary, purpose, scope, and a revision history table. A page break separates the Overview section from the body.

#### Example

```
#import "@preview/dsek:0.1.0": *

#show: strategiska-mål.with(
  summary: [De strategiska målen är mål som är strategiska.],
  purpose: [Syftet med de strategiska målen är göra styrelsens arbete lite
  jobbigare.],
  scope: [Hela D-sektionens verksamhet.],
  history: (
    (meeting: "HTM2 2021", change: "Ursprungligen antagen", who: "Framtidsutskottet
  2021"),
  ),
)
```

#### = Mål

##### == Korrigera benämning av de strategiska målen (2026--2028)

I dagsläget är det tydligen ingen som vet vad det här dokumentet faktiskt heter, utan i folkmun kallas det av outgrundliga skäl fortfarande för "den strategiska planen".

- Få folk att kalla de strategiska målen för de strategiska målen.

#### Parameters

```
strategic-goals(
  body: content,
  summary: content,
  purpose: content,
  scope: content,
  history: array,
  date: datetime,
  lang: str
) -> content
```

**body**    `content`

The body of the document.



**summary** `content`

Description of what this document covers.

Default: `none`

**purpose** `content`

Why this document exists.

Default: `none`

**scope** `content`

Who or what this document applies to.

Default: `none`

**history** `array`

Modification history. Each entry is a dict with required keys `meeting`, `change`, and `who`.

Default: `()`

**date** `datetime`

The date at which the document was written.

Default: `datetime.today()`

**lang** `str`

The language of the document (same format as `text.lang`). Only `"sv"` and `"en"` are supported.

Default: `"sv"`

## strategiska-mål

Swedish binding for strategic-goals



## 5 Policy

Source code

### policy

Creates a policy document. Apply with `#show: policy.with(...)`.

#### Notes

- The document begins with an “Översikt” / “Overview” section containing the summary, purpose, scope, and a revision history table. A page break separates the Overview section from the body.

#### Example

```
#import "@preview/dsek:0.1.0": *

#show: policy.with(
  subject: "ekonomi", // title becomes "Policy för ekonomi"
  summary: [Policyn beskriver hur ekonomin på sektionen ska skötas.],
  purpose: [Syftet med denna policy är att se till att vi inte bryter lagen.],
  scope: [Sektionen i sin helhet. Men mest Skattmästeriet.],
  history: (
    (
      meeting: "VTM-extra 2022",
      change: [Tog bort kapitlet om "kreativ bokföring"],
      who: "Styrelsen genom Truls Teknolog",
    ),
  ),
),
)
```

#### = Sektionsbil

Sektionsbilen är i särklass sektionens `#remove[mest]#add[minst]` värdefulla ägodel. `// highlight to show diff`

#### = Bokslut

Bokslut måste lämnas in senast när Skattmästaren känner för det.

#### Parameters

```
policy(
  body: content,
  subject: content,
  summary: content,
  purpose: content,
  scope: content,
  history: array,
  date: datetime,
  lang: str,
  use-cover-page: bool
) -> content
```



**body** content

The body of the document.

**subject** content

The subject of the policy, e.g. "Val" or "Tackverksamhet".

Default: none

**summary** content

Description of what this document covers.

Default: none

**purpose** content

Why this document exists.

Default: none

**scope** content

Who or what this document applies to.

Default: none

**history** array

Modification history. Each entry is a dict with required keys `meeting`, `change`, and `who`.

Default: `()`

**date** datetime

The date at which the document was written.

Default: `datetime.today()`

**lang** str

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"



**use-cover-page** `bool`

Whether to render the title on a separate cover page instead of a heading.

Default: `false`



## 6 Guideline / Riktlinje

### Source code

### guideline

Creates a guideline (riktlinje) document. Apply with `#show: riktlinje.with(...)` or `#show: guideline.with(...)`.

### Notes

- The document begins with an “Översikt” / “Overview” section containing the summary, purpose, scope, and a revision history table. A page break separates the Overview section from the body.

### Example

```
#import "@preview/dsek:0.1.0": *

#show: riktlinje.with(
  subject: "sektionsbilens användning", // title becomes "Riktlinje för
sektionsbilens användning"
  summary: [Riktlinjen beskriver hur man inte är en trafikfara.],
  purpose: [Syftet med denna riktlinje är att undvika ännu ett VTM-extra.],
  scope: [Alla på sektionen som har körkort.],
  history: (
    (
      meeting: "S14 2024",
      change: "Uppdaterade bilens registreringsnummer",
      who: "Styrelsen genom Truls Teknolog",
    ),
  ),
)
```

### = Hastigheter

Bilen får inte köras i över 80 km/h. Inte för att det är olagligt, utan för att motorn inte klarar av det.

### Parameters

```
guideline(
  body: content,
  subject: str,
  summary: content,
  purpose: content,
  scope: content,
  history: array,
  date: datetime,
  lang: str,
  use-cover-page: bool
) -> content
```



**body** `content`

The body of the document.

**subject** `str`

The subject of the guideline, e.g. "Grafisk design" or "Överlämning".

Default: `none`

**summary** `content`

A description of what this document covers.

Default: `none`

**purpose** `content`

Why this document exists.

Default: `none`

**scope** `content`

Who or what this document applies to.

Default: `none`

**history** `array`

Modification history. Each entry is a dict with required keys `meeting`, `change`, and `who`.

Default: `()`

**date** `datetime`

The date at which the document was written.

Default: `datetime.today()`

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`



### **use-cover-page** bool

Whether to render the title on a separate cover page instead of a heading.

Default: false

## **riktlinje**

Swedish binding for guideline.



## 7 Agenda / Föredragningslista

### Source code

#### agenda

Creates an agenda (föredragningslista) document. Apply with **#show:**  
föredragningslista.with(...) or **#show:** agenda.with(...).

#### Notes

- The body should include a numbered list using bracket syntax: - [Action] Item name. The action label (e.g. Beslut, Information) goes inside the brackets; leave the brackets empty for no action (e.g. for OFMÖ / OFMA). If any item does not begin with brackets, the whole list is left unformatted (no error).
- Links attached to an item (using + #link("link.com") in a sublist to an item) are collected into the Annex / Bilaga column and numbered in order of appearance. Referring to the same link more than once gives it the same number. A link written with a custom label (display text different from the URL) is shown as-is and is not numbered.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: otherpos

#show: föredragningslista.with(
  meeting: "HTM1",
  time: date(15, 3, 2026, time: (17, 15)),
  authors: (
    (name: "Truls Teknolog", position: otherpos.talman),
  ),
)

- [] TFMÖ // [] = no action label
- [Sång] Sektionshymn
  + #link("https://dsek.se/hymn")[Text] // link shown in Annex / Bilaga column
with label "Text"
- [Beslut] Val av justerare
- [Information] Ekonomisk status
  + #link("https://dsek.se/rambudget") // numbered: 1
  + #link("https://dsek.se/detaljbudget") // numbered: 2
- [Beslut] Motion: Jag tycker sektionen borde ha Financial Times
  + #link("https://dsek.se/rambudget") // numbered: 1 (same link)
- [] TFMA
```



## Parameters

```
agenda(  
  body: content,  
  meeting: str content,  
  time: datetime,  
  meeting-type: content auto,  
  authors: array,  
  date: datetime,  
  lang: str  
) -> content
```

**body** content

The body of the document.

**meeting** str or content

The meeting which the agenda outlines, e.g. "HTML".

Default: none

**time** datetime

Meeting date and time. Use date(), e.g. date(15, 3, 2025, time: (13, 0)).

Default: none

**meeting-type** content or auto

The type of meeting, e.g. "Styrelsemöte" or "Studierådsmöte". If set to auto, the meeting type is detected from the the meeting parameter – SXX gives "Styrelsemöte" and SRDXX gives "Studierådsmöte" (where X is a digit).

Default: auto

**authors** array

Signatories. Each signatory dict must have at least the key name, optionally message, position and signature.

Default: ()

**date** datetime

The date at which the document was written.

Default: datetime.today()



**lang**   `str`

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: `"sv"`

## föredragningslista

Swedish binding for agenda



## 8 Minutes / Protokoll

### Source code

#### minutes

Creates a meeting minutes (protokoll) document. Apply with `#show: protokoll.with(...)` or `#show: minutes.with(...)`.

#### Notes

- The body uses / **Term**: description syntax where each term is an agenda item title and the description is the item text. Inside an item, term items are formatted normally.
- Items are automatically numbered as §1, §2, ... and can be cross-referenced with `@item` (resolves to "§N") or `@item[]` (resolves to "§N Item").
- Attendees are auto-labelled so they can be referenced with `@name` or `@name[]` (to include position) anywhere in the document.

#### Example:

```
#import "@preview/dsek:0.1.0": *
#import strings: infu, styr

#show: protokoll.with(
  meeting: "S06",
  attendees: (
    ("Truls Teknolog", styr.ordf),
    ("Trula Teknolog", infu.ansv),
    ("Råsa Pantern", "Sektionsmaskot", (from: [@tid-och-sätt], to: [@val-av-
justerare])),
    "Pelle Postlös", // name only, no position
  ),
  attested: false, // default; set to true to remove watermark
  chair: [@trulsteknolog],
  secretary: [@trulateknolog],
  reviewers: ([@pellepostlös]), // one or more
)

/ OFMÖ:
  @trulsteknolog[] förklarade mötet öppnat 12:15. // Ordförande Truls Teknolog
  förklarade...

/ Tid och sätt:
  Tid och sätt godkändes.

/ Val av justerare:
  Mötet beslöt
  - att välja @pellepostlös till justerare // *att* välja Pelle Postlös till...

/ Information från kollegierna:
  / InfoK: Ingen ny information. // normal terms

/ Veckans roliga punkt:
  @trulateknolog drog en ordvits.
```



#### / Uppföljning\ : Veckans roliga punkt:

@pellepostlös yrkade på

- att stryka @veckans-roliga-punkt från protokollet
- Mötet avslög yrkandet.

@trulateknolog yrkade på

- att åligga @pellepostlös att "komma på något bättre själv då" med uppföljning till nästa styrelsemöte.

Mötet biföll yrkandet.

#### / OFMA:

@trulsteknolog förklarade mötet avslutat 12:18

Efter mötet såg beslutsuppföljningslistan ut enligt följande:

```
#followup(  
  ("S03", [Hitta den försvunna sektiondiamanten], [Råsa Pantern], "HTM1"),  
  ("S06", [Kom på en bättre ordvits än Trula], [@pellepostlös], "S07"),  
)
```

### Parameters

```
minutes(  
  body: content,  
  meeting: str content,  
  attendees: array,  
  chair: content,  
  secretary: content,  
  reviewers: array,  
  meeting-type: content auto,  
  attested: bool,  
  lang: str,  
  date: datetime  
) -> content
```

**body** content

The body of the document.

**meeting** str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none



**attendees** `array`

Attendee list. Each entry is a name string/content, or a 2-element (name, position) array. Positions can be entered manually or taken from the strings module.

Default: `()`

**chair** `content`

Meeting chair, shown in the signature block.

Default: `none`

**secretary** `content`

Meeting secretary, shown in the signature block.

Default: `none`

**reviewers** `array`

Optional minute reviewers, shown in the signature block.

Default: `()`

**meeting-type** `content` or `auto`

The type of meeting, e.g. "Styrelsemöte" or "Studierådsmöte". If set to auto, the meeting type is detected from the the meeting parameter – SXX gives "Styrelsemöte" and SRDXX gives "Studierådsmöte" (where X is a digit).

Default: `auto`

**attested** `bool`

Shows "OJUSTERAT"/"UNATTESTED" watermark when false.

Default: `false`

**lang** `str`

The language of the document (same format as text.lang). Only "sv" and "en" are supported.

Default: `"sv"`



**date**    `datetime`

The date at which the document was written.

Default: `datetime.today()`

## protokoll

Swedish binding for minutes



## 9 Notice / Kallelse

### Source code

#### notice

Creates a meeting notice/summons (kallelse) document. Apply with `#show:`  
`kallelse.with(...)` or `#show: notice.with(...)`.

#### Notes

- A "Tid och plats" / "Time and location" block is automatically prepended to the body.
- The body can include either free-form text or a numbered list using bracket syntax - [Action] Item name similar to the agenda function.
  - The action label (e.g. Beslut, Information) goes inside the brackets; leave the brackets empty for no action (e.g. for OFMÖ / OFMA). If any item does not begin with brackets, the whole list is left unformatted (no error).
  - Links attached to an item (using `+ #link("link.com")` in a sublist to an item) are collected into the Annex / Bilaga column and numbered in order of appearance. Referring to the same link more than once gives it the same number. A link written with a custom label (display text different from the URL) is shown as-is and is not numbered.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: styr

#show: kallelse.with(
  meeting: "S05",
  time: date(15, 3, 2025, time: (13, 0)),
  location: [E:A, LTH],
  authors: (
    // position defaults to "Sektionsmedlem" / "Guild member",
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"
    (name: "Truls Teknolog", position: styr.ordf),
  ),
)
```

Kära Sektionsmedlemmar,

idag har vi den stora äran att än en gång få kalla er till sektionsmöte.  
Tyvärr räckte inte budgeten till fika, men vi hoppas att ni kommer ändå.

```
- [] OFMÖ // [] = no action label
- [Sång] Sektionshymn
  + #link("https://dsek.se/hymn")[Text] // link shown in Bilaga / Annex column
with label Text
- [Beslut] Val av justerare
- [Information] Ekonomisk status
  + #link("https://dsek.se/rambudget") // numbered: 1
  + #link("https://dsek.se/detaljbudget") // numbered: 2
```



- [Beslut] Motion: Jag tycker sektionen borde ha Financial Times
- + `#link("https://dsek.se/rambudget")` // numbered: 1 (same link)
- [] OFMA

## Parameters

```
notice(  
  body: content,  
  meeting: str content,  
  authors: array,  
  time: datetime,  
  location: str content,  
  adjournment: datetime dict,  
  meeting-type: content auto,  
  lang: str,  
  date: datetime  
) -> content
```

**body** content

The body of the document.

**meeting** str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none

**authors** array

Signatories. Each signatory dict must have at least the key name, optionally message, position and signature.

Default: ()

**time** datetime

Meeting date and time. Use date(), e.g. date(15, 3, 2025, time: (13, 0)).

Default: none

**location** str or content

Meeting venue, e.g. [E:1124].

Default: none



### **adjournment** `datetime` or `dict`

Optional planned adjournment, shown in the time/location block. Either a `date(...)` or a dictionary (`date: date(...)`, `location: [...]`).

Default: `none`

### **meeting-type** `content` or `auto`

The type of meeting, e.g. "Styrelsemöte" or "Studierådsmöte". If set to `auto`, the meeting type is detected from the `meeting` parameter – `SXX` gives "Styrelsemöte" and `SRDXX` gives "Studierådsmöte" (where `X` is a digit).

Default: `auto`

### **lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

### **date** `datetime`

The date at which the document was written.

Default: `datetime.today()`

## **kallelse**

Swedish binding for notice



## 10 Board response / Styrelsens svar

### Source code

### board-response

Creates a board response (styrelsens svar) document. Apply with `#show: styrelsens-svar.with(...)` or `#show: board-response.with(...)`.

### Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: styr

#show: styrelsens-svar.with(
  title: [3.0 flugor i en smäll],
  meeting: "HTML",
  authors: (
    // position defaults to "Sektionsmedlem" / "Guild member",
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"
    (name: "Truls Teknolog", position: styr.ordf),
    (name: "Trula Teknolog", message: "För styrelsen"),
  ),
)

#emoji.thumb.up
```

Styrelsen yrkar på // extra space is inserted before this paragraph automatically  
- att bifalla motionen i sin helhet // becomes: \*att\* bifalla...

### Parameters

```
board-response(
  body: content,
  title: content,
  meeting: str content,
  authors: array,
  lang: str,
  date: datetime
) -> content
```

**body** `content`

The body of the document.



**title** `content`

The title of the motion being responded to.

Default: `none`

**meeting** `str` or `content`

The meeting for which the motion and response were written, e.g. "HTM1".

Default: `none`

**authors** `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

**date** `datetime`

The date at which the document was written.

Default: `datetime.today()`

## styrelsens-svar

Swedish binding for board-response



## 11 Consideration / Handling

### Source code

#### consideration

Creates a consideration (handling) document. Apply with `#show: handling.with(...)` or `#show: consideration.with(...)`.

#### Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: aktu

#show: handling.with(
  title: [3.0 flugor i en smäll],
  meeting: "HTML",
  authors: (
    // position defaults to "Sektionsmedlem" / "Guild member",
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"
    (name: "Truls Teknolog", position: aktu.dsportare),
    (name: "Trula Teknolog", message: "gaming"),
  ),
)
```

#### = Bakgrund

Geekend är ett väldigt uppskattat event. Senast slog vi rekord med 247 sittande. Jag är inte helt säker på hur vi fick plats, men kul var det.

#### = Sammanfattning

Geekend är kul, så vi vill ha mer Geekend

Aktivitetsutskottet yrkar på // extra space is inserted before this paragraph automatically

- att införa ett månadslångt Geekend // becomes: \*att\* införa...

#### Parameters

```
consideration(
  body: content,
  title: content,
  meeting: str content,
  authors: array,
  lang: str,
  date: datetime
) -> content
```



**body** `content`

The body of the document.

**title** `content`

The title of the consideration.

Default: `none`

**meeting** `str` or `content`

The meeting for which the document was written, e.g. "HTML".

Default: `none`

**authors** `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

**date** `datetime`

The date at which the document was written.

Default: `datetime.today()`

## handling

Swedish binding for consideration



## 12 Motion

### Source code

#### motion

Creates a motion document. Apply with `#show: motion.with(...)`.

#### Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: km

#show: motion.with(
  title: [Uppdatering av Policy för ekonomi],
  meeting: "S23",
  authors: (
    // position defaults to "Sektionsmedlem" / "Guild member",
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"
    (name: "Truls Teknolog", position: km.mastare),
    (name: "Trula Teknolog", message: "För uppdaterad information"),
  ),
)
```

Vi har bytt sektionsbil (igen), så policy för ekonomi bör reflektera detta.

Vi yrkar på // extra space is inserted before this paragraph automatically  
- att uppdatera "Policy för ekonomi" enligt bilaga // becomes: \*att\* uppdatera...

#### Parameters

```
motion(
  body: content,
  title: content,
  meeting: str content,
  authors: array,
  lang: str,
  date: datetime
) -> content
```

**body** `content`

The body of the document.



**title** `content`

The title of the motion.

Default: `none`

**meeting** `str` or `content`

The meeting for which the motion was written, e.g. "HTM1".

Default: `none`

**authors** `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

**date** `datetime`

The date at which the document was written.

Default: `datetime.today()`



## 13 Proposal / Proposition

### Source code

#### proposal

Creates a proposal (proposition) document. Apply with `#show: proposition.with(...)` or `#show: proposal.with(...)`.

#### Notes

- Author signatures are appended automatically through the authors parameter.
- A paragraph is given extra vertical space before it when it ends with a resolution phrase: Swedish yrka ... på or beslut/besluta, or English move/moves/decide.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: styr

#show: proposition.with(
  title: [Budgetrevidering],
  meeting: "VTM-Extra",
  authors: (
    // position defaults to "Sektionsmedlem" / "Guild member",
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"
    (name: "Truls Teknolog", position: styr.ordf),
    (name: "Trula Teknolog", message: "För styrelsen"),
  ),
)
```

#### = Bakgrund

vi är broke :(

#### = Förslag

Styrelsen yrkar på // extra space is inserted before this paragraph automatically  
- att avskaffa sektionen // becomes: \*att\* avskaffa...

#### Parameters

```
proposal(
  body: content,
  title: content,
  meeting: str content,
  authors: array,
  lang: str,
  date: datetime
) -> content
```

**body**    content

The body of the document.



**title** `content`

The title of the proposal.

Default: `none`

**meeting** `str` or `content`

The meeting for which the proposal was written, e.g. "HTM1".

Default: `none`

**authors** `array`

Signatories. Each signatory dict must have at least the key `name`, optionally `message`, `position` and `signature`.

Default: `()`

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`

**date** `datetime`

The date at which the document was written.

Default: `datetime.today()`

## proposition

Swedish binding for proposal



## 14 Requirements profile / Kravprofil

### Source code

#### requirements-profile

Creates a requirements profile (kravprofil) for an elected position. Apply with **#show:** `kravprofil.with(...)` or **#show:** `requirements-profile.with(...)`.

#### Notes

- A mandate-period row is rendered first, then the body as a preamble, and finally the requirements and merits as a two-column bullet list.
- The mandate period defaults to the full calendar year of year (Jan 1 – Dec 31) when mandate is left at its default auto.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: styr

#show: kravprofil.with(
  position: styr.ordf, // or a plain string: "Ordförande"
  requirements: (
    "Godkänd i B2",
  ),
  merits: (
    "Erfarenhet av projektledning",
    "Tidigare ordföranderoll i studentförening",
  ),
  year: 2025,
  mandate: (
    // set to `auto` or omit for default of jan 1 – dec 31
    from: date(1, 7, 2026),
    to: date(30, 6, 2027),
  ),
)
```

Ordförande leder sektionens styrelse och representerar sektionen utåt.

#### Parameters

```
requirements-profile(
  body: content,
  position: str content,
  requirements: array,
  merits: array,
  mandate: dictionary auto,
  year: int,
  lang: str,
  date: datetime
) -> content
```



**body** `content`

The body of the document.

**position** `str` or `content`

The position title, e.g. "Vice ordförande" or `strings.medalj.mdlm`.

Default: `none`

**requirements** `array`

Mandatory requirements (strings or content).

Default: `()`

**merits** `array`

Meritorious qualifications.

Default: `()`

**mandate** `dictionary` or `auto`

Mandate period as (from: datetime, to: datetime). Set to `auto` to use the full calendar year given by year.

Default: `auto`

**year** `int`

Calendar year used when `mandate: auto`.

Default: `datetime.today().year()`

**lang** `str`

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: `"sv"`



**date**    `datetime`

The date at which the document was written.

Default: `datetime.today()`

## kravprofil

Swedish binding for requirements-profile



## 15 Nomination / Valförslag

Source code

### nomination-proposal

Creates a nomination proposal (valförslag) document. Apply with `#show: valförslag.with(...)` or `#show: nomination-proposal.with(...)`.

- Candidates are grouped by position via the candidates dictionary and laid out in two columns. Free-form content (headings, paragraphs) can be mixed in below them.
- Author signatures are appended automatically.

### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: valb

#show: valförslag.with(
  title: "Nomineringar till Presidiet",
  meeting: "S23",
  candidates: (
    "Ordförande": "Trula Teknolog",
    "Vice Ordförande": "Truls Teknolog",
    "posten Posten": (
      "J. Doe",
      "Nomen Nescio",
      "[REDACTED]",
    ),
  ),
  authors: (
    // position defaults to "Sektionsmedlem" / "Guild member",
    // message defaults to "Lund, dag som ovan" / "Lund, day as above"
    (name: "Råsa Pantern", position: valb.ordf),
  ),
  stats: (
    "Ordförande": [0 -- 4],
    "Vice Ordförande": [5 -- 9],
    "posten Posten": [250 -- 254],
  ),
)
```

Dessa personer gjorde bättre ifrån sig på sina intervjuer än någon annan.

```
// extra space is inserted before this paragraph automatically
Med hänvisning till den utförliga motivationen ovan yrkar jag därmed på
- att välja in dessa tjommar till respektive post // becomes: *att* välja...
```



## Parameters

```
nomination-proposal(  
  body: content,  
  title: content,  
  meeting: str content,  
  authors: array,  
  candidates: dict,  
  stats: dict none,  
  lang: str,  
  date: datetime  
) -> content
```

**body** content

The body of the document.

**title** content

The title of the document, e.g. [Nominering till HTM1].

Default: none

**meeting** str or content

The meeting for which the document was written, e.g. "HTM1".

Default: none

**authors** array

Signatories. Each signatory dict must have at least the key name, optionally message, position and signature.

Default: ()

**candidates** dict

Positions mapped to a nominee or a list of nominees, e.g. ("Ordförande": "Trula Teknolog", "Vice Ordförande": ("Truls", "Trula")).

Default: none



**stats** dict or none

Optional applicant counts per position, rendered as a “Valstatistik” / “Selection statistics” appendix. Keys must match candidates.

Default: none

**lang** str

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: “sv”

**date** datetime

The date at which the document was written.

Default: `datetime.today()`

## valförslag

Swedish binding for nomination-proposal



## 16 Plan of operations / Verksamhetsplan

Source code

### plan-of-operations

Creates a plan of operations (verksamhetsplan) document. Apply with `#show: verksamhetsplan.with(...)` or `#show: plan-of-operations.with(...)`.

#### Notes

- The document begins with a pre-filled “Översikt” / “Overview” section containing subsections summary, purpose, structure, responsibility, and reporting. A page break separates the Overview section from the body.
  - The different sections can be overridden using the `overview-overrides` parameter.

#### Example

```
#import "@preview/dsek:0.1.0": *
```

```
#show: verksamhetsplan // `Overview` section inserted automatically
```

**= Mål från de strategiska målen**

**== Korrigera benämning av de strategiska målen**

För att säkerställa att målet uppfylls tänker vi ta i med hårdhandskarna.

- Be jättesnällt för annars blir vi ledsna i ögat :(

#### Parameters

```
plan-of-operations(  
  body: content,  
  year: int,  
  overview-overrides: dict,  
  lang: str,  
  date: datetime  
) -> content
```

**body**    `content`

The body of the document.

**year**    `int`

The year for which the plan was written. Defaults to next year.

Default: `datetime.today().year() + 1`



### **overview-overrides** dict

A dictionary of overrides in the Overview section. Available keys are summary, purpose, structure, responsibility and reporting.

Default: ( : )

### **lang** str

The language of the document (same format as `text.lang`). Only "sv" and "en" are supported.

Default: "sv"

### **date** datetime

The date at which the document was written.

Default: `datetime.today()`

## **verksamhetsplan**

Swedish binding for plan-of-operations



## 17 Equal treatment plan / Likabehandlingsplan

### Source code

#### equal-treatment-plan

Creates an Equal treatment plan (likabehandlingsplan) document. Apply with **#show:** `likabehandlingsplan.with(...)` or **#show:** `equal-treatment-plan.with(...)`.

#### Example

```
#import "@preview/dsek:0.1.0": *
#import strings: km

#show: likabehandlingsplan.with(
  committee: km.name, // title becomes "Likabehandlingsplan - Källarmästeriet"
  meeting: [S21],
)
```

Vi ska verka för att alla ska få lika mycket köttfärssås på Snickerboa.

#### Parameters

```
equal-treatment-plan(
  body: content,
  committee: str content,
  meeting: str content,
  date: datetime,
  lang: str
) -> content
```

**body** `content`

The body of the document.

**committee** `str` or `content`

The committee the plan applies to.

Default: `none`

**meeting** `str` or `content`

The meeting for which the document was written, e.g. "HTM1".

Default: `none`



**date**    `datetime`

The date at which the document was written.

Default: `datetime.today()`

**lang**    `str`

The language of the document (same format as `text.lang`). Only “sv” and “en” are supported.

Default: `"sv"`

## likabehandlingsplan

Swedish binding for equal-treatment-plan